

Project 1 Test Report

Alexander DuPre

January 8, 2020

Introduction

The following test report documents the tests performed for project one. The test cases and strategies closely follow the project one rubric.

Each section contains test cases related to the sections topic. Each test case will describe the name of the test, the expected result, actual result, as well as a discussion and indication of the Pass/Fail status. The actual result will be provided in the form of a screen shot of the console.

System Call Tracing

This section presents all tests related to tracing system calls within the xv6 system. Test cases follow closely those outlined in the rubric.

Test Case: *With PRINT_SYSCALLS set to 0 in the Makefile*

Assertions:

1. Code correctly compiles
2. No trace information is displayed

Status: **PASS**

```
|20:01:33|adupree@ada:[xv6-pdx]> grep "PRINT_SYSCALLS ?=" Makefile
PRINT_SYSCALLS ?=0
|20:02:01|adupree@ada:[xv6-pdx]> make clean run
rm -f *.tex *.dvi *.idx *.aux *.log *.ind *.ilg \
*.o *.d *.asm *.sym vectors.S bootblock entryother \
initcode initcode.out kernel xv6.img fs.img kernelmemfs \
xv6memfs.img mkfs .gdbinit \
_cat _echo _forktest _grep _init _kill _ln _ls _mkdir _rm _sh _stressfs _usertests _wc _zombie _halt
rm -rf dist dist-test
make -s clean
make -s qemu-nox
nmeta 59 (boot, super, log blocks 30 inode blocks 26, bitmap blocks 1) blocks 1941 total 2000
ballocc: first 582 blocks have been allocated
ballocc: write bitmap block at sector 58
boot block is 448 bytes (max 510)
10000+0 records in
10000+0 records out
5120000 bytes (5.1 MB, 4.9 MiB) copied, 0.160216 s, 32.0 MB/s
1+0 records in
1+0 records out
512 bytes copied, 0.00954813 s, 53.6 kB/s
315+1 records in
315+1 records out
161360 bytes (161 kB, 158 KiB) copied, 0.017853 s, 9.0 MB/s
xv6...
cpu1: starting 1
cpu0: starting 0
sb: size 2000 nblocks 1941 ninodes 200 nlog 30 logstart 2 inodestart 32 bmap start 58
init: starting sh
$
```

Figure 1: Compilation and execution with PRINT_SYSCALLS set to 0.

The command `grep "PRINT_SYSCALLS ?=" Makefile` shows that the PRINT_SYSCALLS macro is indeed turned off. The following command `make clean run` demonstrates that the code correctly compiles and the output does not display any trace information. Furthermore, it should be noted that the timestamps for each command was performed within thirty seconds of each other.

Test Case: *With PRINT_SYSCALLS set to 1 in the Makefile*

Assertions:

1. Code correctly compiles
2. Trace information is displayed
3. Correct call trace on boot

Status: **PASS**

```
|20:09:07|adupree@ada:[xv6-pdx]> grep "PRINT_SYSCALLS ?=" Makefile
PRINT_SYSCALLS ?=1
|21:15:15|adupree@ada:[xv6-pdx]> make clean run
rm -f *.tex *.dvi *.idx *.aux *.log *.ind *.ilg \
*.o *.d *.asm *.sym vectors.S bootblock entryother \
initcode initcode.out kernel xv6.img fs.img kernelmemfs \
xv6memfs.img mkfs .gdbinit \
_cat _echo _forktest _grep _init _kill _ln _ls _mkdir _rm _sh _stressfs _usertests _wc _zombie _halt
rm -rf dist dist-test
make -s clean
make -s qemu-nox
nmeta 59 (boot, super, log blocks 30 inode blocks 26, bitmap blocks 1) blocks 1941 total 2000
ballocc: first 582 blocks have been allocated
ballocc: write bitmap block at sector 58
boot block is 448 bytes (max 510)
10000+0 records in
10000+0 records out
5120000 bytes (5.1 MB, 4.9 MiB) copied, 0.161945 s, 31.6 MB/s
1+0 records in
1+0 records out
512 bytes copied, 0.0105074 s, 48.7 kB/s
315+1 records in
315+1 records out
161472 bytes (161 kB, 158 KiB) copied, 0.0155575 s, 10.4 MB/s
xv6...
cpu1: starting 1
cpu0: starting 0
sb: size 2000 nblocks 1941 ninodes 200 nlog 30 logstart 2 inodestart 32 bmap start 58
exec -> 0
open -> -1
mknod -> 0
open -> 0
dup -> 1
dup -> 2
iwrite -> 1
nwrite -> 1
iwrite -> 1
twrite -> 1
:write -> 1
write -> 1
swrite -> 1
twrite -> 1
awrite -> 1
rwrite -> 1
twrite -> 1
iwrite -> 1
nwrite -> 1
gwrite -> 1
write -> 1
swrite -> 1
hwrite -> 1

write -> 1
fork -> 2
exec -> 0
open -> 3
close -> 0
$write -> 1
write -> 1
```

Figure 2: Compilation and Boot call trace with PRINT_SYSCALLS set to 1.

The command `grep "PRINT_SYSCALLS ?=" Makefile` shows that the `PRINT_SYSCALLS` macro is indeed turned on. The following command `make clean run` demonstrates that the code correctly compiles and the output displays trace information for the system calls. The system call trace in Figure 2 is the boot sequence for the xv6 system. Furthermore, it should be noted that the timestamps for each command was performed within 10 seconds of each other.

Conditional Compilation and Date System Call

This section presents tests related to the conditional compilation of the CS333_P1 project flag and the Date system call. Test cases follow closely those outlined in the rubric.

Test Case: *With CS333_P1 turned off, when CS333_PROJECT is set to 0*

Assertions:

1. Code correctly compiles
2. Kernel boots
3. forktest runs to completion correctly
4. usertests runs to completion correctly

Status: **PASS**

```
|21:44:11|adupree@ada:[xv6-pdx]> grep "CS333_PROJECT ?=" Makefile
CS333_PROJECT ?= 0
|21:44:17|adupree@ada:[xv6-pdx]> make clean run
rm -f *.tex *.dvi *.idx *.aux *.log *.ind *.ilg \
*.o *.d *.asm *.sym vectors.S bootblock entryother \
initcode initcode.out kernel xv6.img fs.img kernelmemfs \
xv6memfs.img mkfs .gdbinit \
_cat _echo _forktest _grep _init _kill _ln _ls _mkdir _rm _sh _stressfs _usertests _wc _zombie _halt
rm -rf dist dist-test
make -s clean
make -s qemu-nox
nmeta 59 (boot, super, log blocks 30 inode blocks 26, bitmap blocks 1) blocks 1941 total 2000
ballocc: first 582 blocks have been allocated
ballocc: write bitmap block at sector 58
boot block is 448 bytes (max 510)
10000+0 records in
10000+0 records out
5120000 bytes (5.1 MB, 4.9 MiB) copied, 0.150241 s, 34.1 MB/s
1+0 records in
1+0 records out
512 bytes copied, 0.0100407 s, 51.0 kB/s
315+1 records in
315+1 records out
161360 bytes (161 kB, 158 KiB) copied, 0.0149619 s, 10.8 MB/s
xv6...
cpu1: starting 1
cpu0: starting 0
sb: size 2000 nblocks 1941 ninodes 200 nlog 30 logstart 2 inodestart 32 bmap start 58
init: starting sh
$
```

Figure 3: Compilation and Kernel Boot with CS333_P1 turned off.

Figure 3, 4, and 5 present the results of this test case. The command `grep "CS333_PROJECT ?=" Makefile` shows that the CS333_PROJECT is defined with 0. The following command `make clean run` demonstrates that the code correctly compiles the kernel successfully boots. Because `forktest` is included with the `usertests` only the user tests were ran. The results of which are shown in figure 4 and 5. Due to the size of the test, much of the output was elided.

```
|21:44:17|adupree@ada:[xv6-pdx]> make clean run
rm -f *.tex *.dvi *.idx *.aux *.log *.ind *.ilg \
*.o *.d *.asm *.sym vectors.S bootblock entryother \
initcode initcode.out kernel xv6.img fs.img kernelmemfs \
xv6memfs.img mkfs .gdbinit \
_cat _echo _forktest _grep _init _kill _ln _ls _mkdir _rm _sh _stressfs _usertests _wc _zombie _halt
rm -rf dist dist-test
make -s clean
make -s qemu-nox
nmeta 59 (boot, super, log blocks 30 inode blocks 26, bitmap blocks 1) blocks 1941 total 2000
ballocc: first 582 blocks have been allocated
ballocc: write bitmap block at sector 58
boot block is 448 bytes (max 510)
10000+0 records in
10000+0 records out
5120000 bytes (5.1 MB, 4.9 MiB) copied, 0.150241 s, 34.1 MB/s
1+0 records in
1+0 records out
512 bytes copied, 0.0100407 s, 51.0 kB/s
315+1 records in
315+1 records out
161360 bytes (161 kB, 158 KiB) copied, 0.0149619 s, 10.8 MB/s
xv6...
cpu1: starting 1
cpu0: starting 0
sb: size 2000 nblocks 1941 ninodes 200 nlog 30 logstart 2 inodestart 32 bmap start 58
init: starting sh
$ usertests
usertests starting
arg test passed
```

Figure 4: Execution of usertests from the same session.

```
unlinkread test
unlinkread ok
dir vs file
dir vs file OK
empty file name
empty file name OK
fork test
fork test OK
bigdir test
bigdir ok
uio test
pid 591 usertests: trap 13 err 0 on cpu 1 eip 0x33ce addr 0x8013d620--kill proc
uio test done
exec test
ALL TESTS PASSED
$
```

Figure 5: Results of usertests with output elided.