

Taming Infinity One Chunk at a Time: Concisely Represented Strategies in One-Counter MDPs

Michal Ajdarów² James C. A. Main¹
Petr Novotný² Mickael Randour¹

¹F.R.S.-FNRS and UMONS – Université de Mons, Belgium

²Masaryk University, Brno, Czech Republic



Highlights 2025

Talk overview

- We study **synthesis** and **verification** in **Markov decision processes**.
- Small controllers, i.e., **concisely represented strategies** are desirable for practical synthesis.
- In **infinite-state systems**, such representations are necessary.

Contributions

We focus on **one-counter Markov decision processes** (OC-MDPs).

- 1 We focus on **interval strategies**, a subclass of strategies that make decisions based on the current state and counter value.
- 2 We provide **PSPACE** algorithms for the verification and synthesis of interval strategies.


Table of contents

- 1 Markov decision processes
- 2 One-counter Markov decision processes and interval strategies
- 3 Verification and synthesis

Markov decision processes

Markov decision process (MDP) \mathcal{M}

- **Finite or countable** state space S .
- **Finite** action space A .
- **Randomised** transition function $\delta: S \times A \rightarrow \mathcal{D}(S)$.





Plays are sequences in $(SA)^\omega$ coherent with transitions.

\rightsquigarrow **Example**: $s_0 a s_1 b s_1 \dots$

Strategies and induced Markov chains


- A **strategy** is a function $\sigma: (SA)^*S \rightarrow \mathcal{D}(A)$.
- σ is **memoryless** if its choices depend only on the **current state**.
- We view memoryless strategies as functions $S \rightarrow \mathcal{D}(A)$.
- A memoryless strategy σ induces a **Markov chain** over S .



One-counter Markov decision processes


One-counter MDP (OC-MDP) \mathcal{Q}

- **Finite** MDP (Q, A, δ) .
- **Weight function**
 $w: Q \times A \rightarrow \{-1, 0, 1\}$.




MDP $\mathcal{M}^{\leq \infty}(\mathcal{Q})$ induced by \mathcal{Q}

- **Countable** MDP over
 $S = Q \times \mathbb{N}$.
- State transitions via δ .
- Counter updates via w .




Objectives

- We study variants of **reachability objectives**.
- Let $T \subseteq Q$ be a target.



State reachability $\text{Reach}(T)$



Selective termination $\text{Term}(T)$

Interval strategies

We study subclasses of **memoryless strategies** of $\mathcal{M}^{\leq \infty}(\mathcal{Q})$.

Open-ended interval strategies (OEIS)

σ is an OEIS if $\exists k_0 \in \mathbb{N}$ s.t. $\forall q \in Q$ and $\forall k \geq k_0$, $\sigma(q, k) = \sigma(q, k_0)$.

\mathbb{N}_0	1	2	\dots	$k_0 - 1$	k_0	$k_0 + 1$	\dots
Q	σ_1	σ_2	\dots	σ_{k_0-1}	σ_{k_0}	σ_{k_0}	\dots

Group counter values
in intervals



constant


Inter.	I_1	I_2	\dots	$I_d = \llbracket k_0, \infty \rrbracket$
Q	τ_1	τ_2	\dots	$\tau_d = \sigma_{k_0}$

\rightsquigarrow **Finite partition** of
 \mathbb{N}_0 into **intervals**

Interval strategy verification problem

Interval strategy verification problem

Decide whether $\mathbb{P}_{\mathcal{M}^{\leq \infty}(\mathcal{Q}), s_{\text{init}}}^{\sigma}(\Omega) \geq \theta$ given an **interval strategy** σ , an **objective** $\Omega \in \{\text{Reach}(T), \text{Term}(T)\}$, a **threshold** $\theta \in \mathbb{Q} \cap [0, 1]$ and an **initial configuration** $s_{\text{init}} \in Q \times \mathbb{N}$.



Solving the verification problem

Main ideas

- **Transition probabilities** of compressed Markov chains are represented as **least solutions of equation systems**.
- Algorithm that checks the validity of a **universal formula in the theory of the reals** parameterised by the **strategy probabilities**.

Unbounded counter	Bounded counter
co-ETR	p^{PosSLP}
Square-root-sum-hard [EWY10] ¹	Square-root-sum-hard

¹Etesami et al., “Quasi-Birth-Death Processes, Tree-Like QBDs, Probabilistic 1-Counter Automata, and Pushdown Systems”, Perform. Evaluation 2010.

Synthesis of interval strategies

We have also studied the **synthesis** of **structurally-constrained interval strategies**.

Parameterised interval strategy synthesis problem

Given **parameters** d and $n \in \mathbb{N}_0$, does there exist an interval partition \mathcal{I} of \mathbb{N} and an OEIS σ such that

- 1 $|\mathcal{I}| \leq d$ and all bounded $I \in \mathcal{I}$ satisfy $|I| \leq n$;
- 2 σ is **based on** \mathcal{I} and
- 3 $\mathbb{P}_{s_{\text{init}}}^{\sigma}(\text{Term}(T)) \geq \theta$.

Unbounded counter	Bounded counter
PSPACE	NP^{ETR}
Square-root-sum-hard and NP-hard	

References I

- [EWY10] Kousha Etessami, Dominik Wojtczak, and Mihalis Yannakakis. “Quasi-Birth-Death Processes, Tree-Like QBDs, Probabilistic 1-Counter Automata, and Pushdown Systems”. In: *Perform. Evaluation* 67.9 (2010), pp. 837–857. DOI: 10.1016/J.PEVA.2009.12.009. URL: <https://doi.org/10.1016/j.peva.2009.12.009>.
- [KEM06] Antonín Kucera, Javier Esparza, and Richard Mayr. “Model Checking Probabilistic Pushdown Automata”. In: *Log. Methods Comput. Sci.* 2.1 (2006). DOI: 10.2168/LMCS-2(1:2)2006. URL: [https://doi.org/10.2168/LMCS-2\(1:2\)2006](https://doi.org/10.2168/LMCS-2(1:2)2006).
- [PB24] Jakob Piribauer and Christel Baier. “Positivity-hardness results on Markov decision processes”. In: *TheoretiCS* 3 (2024). DOI: 10.46298/THEORETICS.24.9. URL: <https://doi.org/10.46298/theoretics.24.9>.

References II

- [Tiw92] Praseon Tiwari. “A problem that is easier to solve on the unit-cost algebraic RAM”. In: *J. Complex.* 8.4 (1992), pp. 393–397. DOI: 10.1016/0885-064X(92)90003-T. URL: [https://doi.org/10.1016/0885-064X\(92\)90003-T](https://doi.org/10.1016/0885-064X(92)90003-T).