

Unit 5: Clustering

BigSurv Text Analysis

Dr. Rochelle Terman

Department of Political Science
University of Chicago

October 2018



Today: Cluster press releases

Goal: partition documents such that:

- **similar** documents are together
- **dissimilar** documents are apart

Method: Clustering methods

Game Plan:

- 1) What makes two data points (i.e. documents) similar?
- 2) How do we find a good partition?
- 3) How do we interpret the clusters?

Key Terms:

- (Multidimensional) Space
- Distance
- Euclidean Distance
- Cosine Distance
- Cluster Analysis / Clustering
- K-means
- Centroid

K-Means Clustering

K-means clustering is popular method to partition a data set into K distinct, non-overlapping clusters.

K-Means Clustering

K-means clustering is popular method to partition a data set into K distinct, non-overlapping clusters.

Inputs

- 1 A document term matrix (or any multidimensional dataset)
- 2 K : the desired number of clusters.

K-Means Clustering

K-means clustering is popular method to partition a data set into K distinct, non-overlapping clusters.

Inputs

- 1 A document term matrix (or any multidimensional dataset)
- 2 K : the desired number of clusters.

Then the K -means algorithm will assign each observation into exactly one of the K clusters.

K-Means Clustering

K-means clustering is popular method to partition a data set into K distinct, non-overlapping clusters.

Inputs


- 1 A document term matrix (or any multidimensional dataset)
- 2 K : the desired number of clusters.

Then the K -means algorithm will assign each observation into exactly one of the K clusters.

Outputs

- 1 C_k : The set of observations assigned to each cluster.
- 2 μ_k : The mean for each K – a vector representing the average values of all observations in that cluster. Also called **centroid**.

K-Means Clustering



K-Means Clustering: Outputs

Centroid (μ_k): The mean for each K – a vector representing the average values of all observations in that cluster.

K-Means Clustering: Outputs

Centroid (μ_k): The mean for each K – a vector representing the average values of all observations in that cluster.

Consider the following cluster with two vectors:

$$\mathbf{x}_1 = [1, 0, 3]$$

$$\mathbf{x}_2 = [0, 4, 1]$$

K-Means Clustering: Outputs

Centroid (μ_k): The mean for each K – a vector representing the average values of all observations in that cluster.

Consider the following cluster with two vectors:

$$\mathbf{x}_1 = [1, 0, 3]$$

$$\mathbf{x}_2 = [0, 4, 1]$$

Then its mean is:

$$\mu = [\text{mean}(X_{1,1}, X_{2,1}), \text{mean}(X_{1,2}, X_{2,2}), \text{mean}(X_{1,3}, X_{2,3})]$$

K-Means Clustering: Outputs

Centroid (μ_k): The mean for each K – a vector representing the average values of all observations in that cluster.

Consider the following cluster with two vectors:

$$\mathbf{x}_1 = [1, 0, 3]$$

$$\mathbf{x}_2 = [0, 4, 1]$$

Then its mean is:

$$\mu = [\text{mean}(x_{1,1}, x_{2,1}), \text{mean}(x_{1,2}, x_{2,2}), \text{mean}(x_{1,3}, x_{2,3})]$$

$$\mu = [0.5, 2, 2]$$

K-Means Clustering: Outputs

Centroid (μ_k): The mean for each K – a vector representing the average values of all observations in that cluster.

Consider the following cluster with two vectors:

$$\mathbf{x}_1 = [1, 0, 3]$$

$$\mathbf{x}_2 = [0, 4, 1]$$

Then its mean is:

$$\mu = [\text{mean}(X_{1,1}, X_{2,1}), \text{mean}(X_{1,2}, X_{2,2}), \text{mean}(X_{1,3}, X_{2,3})]$$

$$\mu = [0.5, 2, 2]$$

The K-means algorithm will assign each observation to the cluster with the closest mean.

K-Means Clustering: Example

Goal: Cluster the following documents:

- I like to eat broccoli and bananas.
- I eat a banana smoothie for breakfast.
- Hamsters and kittens are cute.
- She adopted a cute kitten.

K-Means Clustering: Example

Inputs

1 A document term matrix

	adopt	banana	breakfast	broccoli	cute	eat	hamster	kitten	like	smoothie
1	0	1	0	1	0	1	0	0	1	0
2	0	1	1	0	0	1	0	0	0	1
3	0	0	0	0	1	0	1	1	0	0
4	1	0	0	0	1	0	0	1	0	0

K-Means Clustering: Example

Inputs

1 A document term matrix

	adopt	banana	breakfast	broccoli	cute	eat	hamster	kitten	like	smoothie
1	0	1	0	1	0	1	0	0	1	0
2	0	1	1	0	0	1	0	0	0	1
3	0	0	0	0	1	0	1	1	0	0
4	1	0	0	0	1	0	0	1	0	0

2 K : 2

K-Means Clustering: Example

Inputs

1 A document term matrix

	adopt	banana	breakfast	broccoli	cute	eat	hamster	kitten	like	smoothie
1	0	1	0	1	0	1	0	0	1	0
2	0	1	1	0	0	1	0	0	0	1
3	0	0	0	0	1	0	1	1	0	0
4	1	0	0	0	1	0	0	1	0	0

2 K : 2

Outputs

1 C_k : Cluster assignment:

- C_1 : [1, 2]
- C_2 : [3, 4]

K-Means Clustering: Example

Inputs

- 1 A document term matrix

	adopt	banana	breakfast	broccoli	cute	eat	hamster	kitten	like	smoothi
1	0	1	0	1	0	1	0	0	1	0
2	0	1	1	0	0	1	0	0	0	1
3	0	0	0	0	1	0	1	1	0	0
4	1	0	0	0	1	0	0	1	0	0

- 2 K : 2

Outputs

- 1 C_k : Cluster assignment:

- C_1 : [1, 2]
- C_2 : [3, 4]

- 2 μ_k : Cluster means / centroids:

	adopt	banana	breakfast	broccoli	cute	eat	hamster	kitten	like	smoothi
μ_1	0.0	1.0	0.5	0.5	0.0	1.0	0.0	0.0	0.5	0.5
μ_2	0.5	0.0	0.0	0.0	1.0	0.0	0.5	1.0	0.0	0.0

K-Means Clustering

A chicken and egg problem:

K-Means Clustering

A chicken and egg problem:

- Means \rightsquigarrow Assignments

K-Means Clustering

A chicken and egg problem:

- Means \rightsquigarrow Assignments
- Assignments \rightsquigarrow Means

K-Means Clustering

A chicken and egg problem:

- Means \rightsquigarrow Assignments
- Assignments \rightsquigarrow Means


How do we find a good partition?

K-Means Clustering: Algorithm


- 1) Randomly initialize K cluster centroids $(\mu_1, \mu_2, \dots, \mu_k)$ in random locations.
- 2) Repeat:
 - **Assignment:** Assign each observation \mathbf{X} to cluster with closest mean μ_k .
 - **Update:** Calculate new centroids μ_k by averaging all points assigned to each cluster.

Stop when cluster assignments stop changing.


K-Means Clustering: Algorithm




K-Means Clustering: Algorithm




K-Means Clustering: Algorithm




K-Means Clustering: Algorithm




K-Means Clustering: Algorithm



K-Means Clustering: Algorithm



K-Means Clustering: Algorithm



K-Means Clustering: Decisions

Small Decisions with Big Consequences:

K-Means Clustering: Decisions

Small Decisions with Big Consequences:

1) How should we preprocess the data?

- k-means are very sensitive to feature scaling / weighting.
- Common to normalize the DTM in some way, e.g. by dividing each vector by the vector length.

K-Means Clustering: Decisions

Small Decisions with Big Consequences:

1) How should we preprocess the data?

- k-means are very sensitive to feature scaling / weighting.
- Common to normalize the DTM in some way, e.g. by dividing each vector by the vector length.

2) How to chose K ?

- User must assign the number of clusters (K)
- Different values of K will lead to different partitions.

K-Means Clustering: Decisions

Small Decisions with Big Consequences:

1) How should we preprocess the data?

- k-means are very sensitive to feature scaling / weighting.
- Common to normalize the DTM in some way, e.g. by dividing each vector by the vector length.

2) How to chose K ?

- User must assign the number of clusters (K)
- Different values of K will lead to different partitions.

3) Random starting values!

- Results will depend on the initial (random) cluster centroid assignment (in step 1).
- Important to run the algorithm multiple times from different random starting values.

K-Means Clustering: Decisions

Small Decisions with Big Consequences:

1) How should we preprocess the data?

- k-means are very sensitive to feature scaling / weighting.
- Common to normalize the DTM in some way, e.g. by dividing each vector by the vector length.

2) How to chose K ?

- User must assign the number of clusters (K)
- Different values of K will lead to different partitions.

3) Random starting values!

- Results will depend on the initial (random) cluster centroid assignment (in step 1).
- Important to run the algorithm multiple times from different random starting values.

How do we decide?

K-Means Clustering: How do we decide?

What makes a good partition?

K-Means Clustering: How do we decide?

What makes a good partition?

Two kinds of validation criteria:

K-Means Clustering: How do we decide?

What makes a good partition?

Two kinds of validation criteria:

1 Quantitative evaluation:

- A good clustering is one for which the within-cluster variation is as small as possible.

K-Means Clustering: How do we decide?

What makes a good partition?

Two kinds of validation criteria:

1 Quantitative evaluation:

- A good clustering is one for which the within-cluster variation is as small as possible.

2 Qualitative evaluation:

- A good clustering is one for which clusters are substantially / semantically interpretable.

Quantitative evaluation: within-cluster variation is as small as possible.

- **Within-cluster variation:** a measure of the amount by which the observations within a cluster differ from each other.
- Common metric: **Sum of Squared Euclidean Distance**

For a given document \mathbf{X} in cluster k , the **squared Euclidean distance** is:

$$D(\mathbf{X}, \mu_k)^2 = \sum_{p=1}^P (x_p - \mu_{kp})^2$$

For a given document \mathbf{X} in cluster k , the **squared Euclidean distance** is:

$$D(\mathbf{X}, \mu_k)^2 = \sum_{p=1}^P (x_p - \mu_{kp})^2$$

The **within-cluster sum of squared distances** for a given cluster C_k is:

$$W(C_k) = \sum_{i \in C_k} D(\mathbf{X}_i, \mu_k)^2$$

For a given document \mathbf{X} in cluster k , the **squared Euclidean distance** is:

$$D(\mathbf{X}, \mu_k)^2 = \sum_{p=1}^P (x_p - \mu_{kp})^2$$

The **within-cluster sum of squared distances** for a given cluster C_k is:

$$W(C_k) = \sum_{i \in C_k} D(\mathbf{X}_i, \mu_k)^2$$

Thus our goal is to minimize the **total within-cluster sum of squares**:

$$\sum_{k=1}^K W(C_k)$$

Qualitative evaluation: clusters are substantially / semantically interpretable.

How do we interpret the clusters?

Qualitative evaluation: clusters are substantially / semantically interpretable.

How do we interpret the clusters?

1 Manual identification

- Sample set of documents from same cluster
- Read documents
- Assign cluster “label” by hand
 - I like to eat broccoli and bananas. \rightsquigarrow “food”
 - Hamsters and kittens are cute. \rightsquigarrow “pets”

Qualitative evaluation: clusters are substantially / semantically interpretable.

How do we interpret the clusters?

1 Manual identification

- Sample set of documents from same cluster
- Read documents
- Assign cluster “label” by hand
 - I like to eat broccoli and bananas. \rightsquigarrow “food”
 - Hamsters and kittens are cute. \rightsquigarrow “pets”

2 Automatic identification

- Use methods to identify separating words between clusters
- Use these to help infer differences across clusters

Qualitative evaluation: clusters are substantially / semantically interpretable.

How do we interpret the clusters?

1 Manual identification

- Sample set of documents from same cluster
- Read documents
- Assign cluster “label” by hand
 - I like to eat broccoli and bananas. \rightsquigarrow “food”
 - Hamsters and kittens are cute. \rightsquigarrow “pets”

2 Automatic identification

- Use methods to identify separating words between clusters
- Use these to help infer differences across clusters

3 Be **Transparent**

- Provide documents + code
- Detail labeling procedures
- Acknowledge ambiguity

To the R code!