Standard Operating Procedure

<UsingLibrary>

include;

```
superapi::supercolordialog;
                          superapi::supercore;
                          superapi::superfiledialog;
                           superapi::superfilemanager;
                          superapi::superfinddialog;
                           superapi::superfontdialog;
                           superapi::supergroupbox;
                           superapi::superlogger;
                           superapi::supernotedialog;
                          superapi::supertab;
                          superapi::superwindow;
             public;
                           richerbox public superapi::supertab;
                          richerbox::datadialog public superapi::superwindow;
<RicherBox>
<RicherBox::DataDialog>
              F
                           clicked;
                                        open font family dialog;
              8.0
                           edit finished;
                                        change highlight text's point size;
                                        value available at 0~100;
              В
                           clicked;
                                        change highlight text's weight property;
                          clicked;
                                        change highlight text's italic property;
              U
                           clicked;
                                        change highlight text's underline property;
                           clicked;
                                        change local row's align as left;
                           clicked;
                                        change local row's align as right;
                          clicked;
                                        change local row's align as center;
                           clicked;
                                        change local row's align as justify;
                           clicked;
                                        open color select dialog;
```

nousercontrol;

display local textcursor position's color;

```
clicked;
              control + Key_G;
                              get local textcursor position's font format;
                              include family, pointsize, weight, italic, underline, red, green, blue;
               clicked;
                              open file dialog;
                              select .png file and add to this .html;
               clicked;
               control + Key_B;
                              use recorded font format brush highlight text;
               clicked;
                              run apply function;
                              print this .html file to .pdf file;
               clicked;
                              open .html file's path with system explor;
               nousercontrol;
                              display save progress;
                              if maxisize,run apply function;
                              else progress add value every second;
Microsoft YaHei,8,50,0,0,0,0,127
               nousercontrol;
                              display recorded font format;
 Editor
               clicked;
                              for edit html code;
  Source
               clicked;
                              display html source code;
   Apply
               clicked;
               control + Key_S;
                              save html source code to current file;
                              reset save progress;
```

Version Logs

<20220301 Version 1.09> fix font bold bugs; <20220209 Version 1.08> use supertab, supergroupbox api; <20220113 Version 1.07> fix bugs daily; add load and record function; <20211126 Version 1.06> add check function before open file; <20211008 Version 1.05> fix font dialog preview bug when first open; <20211008 Version 1.04>

add explain for every function;

not include init function;

<20211003 Version 1.03>

add shortcut key; find at datadialog sop;

<20211002 Version 1.02>

add load picture function; add printer function; add open html path function;

<20210930 Version 1.01>

change init brush label text;
"Microsoft Yahei,8,-1,5,50,0,0,0,0" ---> "Microsoft Yahei,8,50,0,0,0,0,0";

<20210929 Version 1.00>

first release;