

Standard Operating Procedure

<UsingLibrary>

```
include;
    superapi::supercore;
    superapi::supergroupbox;
    superapi::superlogger;
    superapi::supernetwork;
    superapi::supernotedialog;
    superapi::supersender;
    superapi::supertab;
    superapi::superwindow;

public;
    tcpclientbox public superapi::supertab;
```

<TcpClientBox>

10.10.128.113

▼

textchanged;
change connect ip address;
if text is ip rules and listen port is int,enable connect server widget;

6666

▼

textchanged;
schange server listen port;
if text is ip rules and listen port is int,enable connect server widget;

Get Local Ipaddress

clicked;
add system ip address to combobox;

Connect Server

clicked;
use current setting connect to server;
operate related widgets;

Disconnect Server

clicked;
disconnect from server;
operate related widgets;

String: ☒

statechanged;
change command mode,current is string;

Hex: ☐

statechanged;
change command mode,current is string too;

Add \r: ☐

statechanged;
add \r to command last or not;

Add \n: ☐

statechanged;
add \n to command last or not;

5

textchanged;
adjust senderbox counts;

Transfer codec

triggered;
transfer latest result from utf-8 to gbk codec;

Version Logs

<20220209 Version 1.02>

```
use supertab,supergroupbox api;
```

<20220105 Version 1.01>

add custom senderbox counts;
bugs fixed daily;

<20211003 Version 1.00>

first release;