

The **axessibility** package

Dragan Ahmetovic, Tiziana Armano, Cristian Bernareggi, Michele Berra,
Anna Capietto, Sandro Coriasco, Nadir Murru, Alice Ruighi
(Department of Mathematics G. Peano, University of Turin)

June 13, 2018

Abstract

PDF documents containing formulae generated by \LaTeX are usually not accessible by assistive technologies for visually impaired people (i.e., by screen readers and braille displays). The package manages this issue allowing to create a PDF document where the formulae are read by these assistive technologies, since it automatically generates hidden comments in the PDF document (by means of the `/ActualText` attribute) in correspondence to each formula. The package does not generate PDF/UA. Status is in progress.

Contents

1 Introduction

This package focuses on the specific problem of the accessibility of PDF documents generated by \LaTeX for visually impaired people. When a PDF document is generated starting from \LaTeX formulae are not accessible by screen readers and braille displays. They can be made accessible by inserting a hidden comment, i.e., an actual text, similarly to the case of web pages. This can be made, e.g., by using the \LaTeX package `pdfcomment.sty`. In any case, this task must be manually performed by the author and it is surely inefficient, since the author should write the formulae and, in addition, insert a description for each formula. Note also that the package `pdfcomment.sty` does not allow to insert special characters like ‘backslash’, ‘brace’, etc, in the comment. Moreover, with these solutions, the reading is bothered since the screen reader reads incorrectly the formula and then the correct comment of the formula. There are also some \LaTeX packages that try to improve the accessibility of PDF documents produced by \LaTeX . In particular the packages `accsupp.sty` and `accessibility_meta.sty` has been developed in order to obtain tagged PDF documents. However, both packages do not solve the problem of the accessibility of formulae. The package `accsupp.sty` develops

some interesting tools for commenting formulae using also special characters (possibility that is not available in the pdfcomment.sty package). Moreover, this is not an automatized method, since the comment must be manually inserted by the author. The package accessibility_meta.sty is an improved version of the package accessibility.sty. This package allows the possibility of inserting several tags for sections, links, figures and tables. However, even if these tags are recognized by the tool for chekcing tags of Acrobat Reader Pro, they are not always recognized by the screen readers. Moreover, this package does not manage formulae. Our package automatically produces an actual text corresponding to the L^AT_EX commands that generate the formulae. This actual text is hidden in the PDF document but the screen reader reads it without reading any incorrect sequence before.

2 Prerequisites

The package **axessiblity** requires the following packages: **accsupp**, **ams-math**, **amssymb**.

3 Package specification

If you use L^AT_EX 2_ε simply do the following

```
\usepackage{axessiblity}
```

The package includes the following features:

- The commands

```
\pdfcompresslevel=0
\pdfoptionpdfminorversion=6
```

that produce an uncompressed PDF document.

- The command

```
\BeginAccSupp
```

contained in the package **accsupp** has been redefined so that the screen readers access the actual text created by this command.

- The new command

```
\wrap#1
```

allows to store its input into an actual text in the PDF document (e.g., the \LaTeX commands for generating a formula).

- The environments

```
\begin{equation}, \end{equation}
\begin{equation*}, \end{equation*}
\[, \]
\[, \]
```

has been redefined. In each environment above listed, the command $\text{\texttt{\textbackslash wrap}}$ is inserted together to the command $\text{\texttt{\textbackslash collect@body}}$ so that all the content of the environment is automatically stored into an ActualText in the PDF document.

4 Usage

An author that would like to create an accessible PDF document for visually impaired people can add this package using the above environments for inserting the formulae. The \LaTeX code of the inserted formulae will be added as hidden comments in correspondence to the location of the formulae in the text. This will allow the user to access the formula code with the screen reader and with the braille refreshable display. Additionally, the package enables to copy the formula \LaTeX code from the PDF reader and paste it elsewhere.

Note that, to preserve the compatibility with Acrobat Reader, our package discourages the use of the underscore character ($_$) which is not correctly read using screen readers in combination with this PDF reader. Alternatively, we suggest to use the equivalent command $\text{\texttt{\textbackslash sb}}$.

Inlined and display mathematical modes ($\text{\$}$, $\text{\$ \$}$) are not supported in this version of the package. However external scripts provided as companion software described in the following section can also address these use cases. While multiline environments

```
\begin{align}, \begin{eqnarray}, \begin{multline}
```

are not directly supported, it is possible to use

```
\begin{equation}\begin{aligned}
```

for typesetting multiline formulae.

5 External scripts and screen reader integration

In addition to the package, we also provide scripts that complement package functionalities.

5.1 Preprocessing scripts

While we warmly suggest to follow the indications provided in the usage guide (suggested commands and environments), it is also possible to apply our package to an already existing \LaTeX document. In this case, it is necessary to preprocess the document in order to replace the unsupported commands and environments with the suggested ones. We provide a preprocessing script for this use case at our Github repository.

5.2 Expansion of user macros

Note that, custom macros used by the author within the formulae are copied as-is into the actual text in the hidden comment. This macros may bear no meaning for other readers, so it may be more meaningful to expand those macros into the original \LaTeX commands. We provide a script that can parse \LaTeX document and replace all the user macros within the formulae with their expanded definitions. You can download this script at our Github repository.

5.3 Screen reader dictionaries

\LaTeX commands that are included as actual text in the hidden comments corresponding to formulae may appear awkward when read by the screen reader. We provide dictionaries for JAWS and ?NVDA? screen readers that convert \LaTeX commands into natural language. Please note that the braille refreshable display will still show the formulae in their original \LaTeX representations. The dictionaries can be downloaded at our Github repository.