```
No.      Time            Source                   Destination              Protocol Length Info
     906 47.029932       66.6.101.171             192.168.137.208          HTTP     241    HTTP/1.1 301 Moved Permanently
Frame 906: 241 bytes on wire (1928 bits), 241 bytes captured (1928 bits) on interface \Device\NPF_{6FA3E7CE-A519-455D-821F-4AF69DA9A9BD}, id
0
Ethernet II, Src: HonHaiPr_43:3c:28 (b8:76:3f:43:3c:28), Dst: AzureWav_0a:a3:f7 (80:c5:f2:0a:a3:f7)
Internet Protocol Version 4, Src: 66.6.101.171, Dst: 192.168.137.208
Transmission Control Protocol, Src Port: 80, Dst Port: 65287, Seq: 1, Ack: 491, Len: 187
    Source Port: 80
    Destination Port: 65287
    [Stream index: 50]
    [TCP Segment Len: 187]
    Sequence number: 1    (relative sequence number)
    Sequence number (raw): 363428390
    [Next sequence number: 188    (relative sequence number)]
    Acknowledgment number: 491    (relative ack number)
    Acknowledgment number (raw): 2399446990
    0101 .... = Header Length: 20 bytes (5)
    Flags: 0x018 (PSH, ACK)
    Window size value: 30016
    [Calculated window size: 30016]
    [Window size scaling factor: -2 (no window scaling used)]
    Checksum: 0x4bca [unverified]
    [Checksum Status: Unverified]
    Urgent pointer: 0
    [SEQ/ACK analysis]
    [Timestamps]
    TCP payload (187 bytes)
Hypertext Transfer Protocol
```