Stereo



What can be done with stereo vision?



Autonomous driving



SLAM- robot navigation

3D reconstruction

References

- http://szeliski.org/Book/
- http://www.cs.cornell.edu/courses/cs5670/2019sp/lectures/lectures.html
- http://www.cs.cmu.edu/~16385/

Contents

- **structure from motion**
- Epipolar geometry
  - Essential matrix
  - Fundamental matrix
  - Estimating the fundamental matrix
- Camera rectification
- Triangulation
- Stereo matching
- Other 3D sensors

Structure from motion

- **Structure from motion (SfM)** is the process of estimating the 3-D structure of a scene from a set of 2-D images. SfM is used in many applications, such as 3-D scanning and augmented reality.
  - [Mathworks]
- SfM is also known as **3D reconstruction**.
- **Stereo vision** is a subcategory of SfM in which we are dealing only with 2 images.



Structure and motion

	Structure (3D model of world)	Motion (6 DOFs of cameras)	Measurements
Pose Estimation (camera pose estimation)	known	**estimate**	3D to 2D correspondences
Triangulation	**estimate**	known	2D to 2D correspondences
3D reconstruction/ SfM/ stereo vision	**estimate**	**estimate**	2D to 2D correspondences + triangulation

Structure and motion

- So essentially one can say that “structure from motion” is the wrong name…
  - Structure and motion is more precise, but nobody will understand what are you talking about.
- In this class we are dealing with 3D reconstruction and Triangulation.

Contents

- structure from motion
- **Epipolar geometry**
  - Essential matrix
  - Fundamental matrix
  - Estimating the fundamental matrix
- Camera rectification
- Triangulation
- Stereo matching
- Other 3D sensors

Epipolar geometry

- **Epipolar geometry** is the geometry of stereo vision. When two cameras view a 3D scene from two distinct positions, there are a number of geometric relations between the 3D points and their projections onto the 2D images that lead to constraints between the image points.
  - [Wikipedia]

Epipolar geometry - The triangulation problem

- Given:
  - two 2D points in the **normalized image coordinate system** (x, x') in two different images (I, I') that describes the same point p in 3D space.
  - Rotation and translation between the two cameras.
- Find p.

- Normalized image coordinate system: $x = K^{-1}\begin{bmatrix} u \\ v \\ 1 \end{bmatrix}$



Epipolar geometry



Epipolar geometry

- We can trace lines from the **camera center** of each image, through the given 2D point to the 3D point p.



Camera center

Epipolar geometry

- **Baseline** is a vector that represent the translation between two cameras



Epipolar geometry

- **Epipole e:** projection of o' onto I.
  - The place of camera o' in image I.



Epipolar geometry

- **Epipolar plane**: the plane that is constructed from the 3 points $(\boldsymbol{p}, \boldsymbol{o}, \boldsymbol{o}')$.



Epipolar geometry

- **Epipolar line**: intersection of Epipolar plane and image plane.



Epipolar constraint

- **The epipolar constraint**: a point $\boldsymbol{x}$ in image $\boldsymbol{I}$ is mapped onto an epipolar line $\boldsymbol{l'}$ in image $\boldsymbol{I'}$.
  - This happens since we don't know $\boldsymbol{p}$ in advance.



Epipolar geometry

- Note: all epipolar lines pass through the epipole.



Epipolar geometry

- Where is the epipole in this images?



Epipolar geometry

- Where is the epipole in this images? The epipole doesn't have to be inside the image!



Epipolar geometry

- Where is the epipole in this image?

Epipolar geometry

- Where is the epipole in this image? The epipolar lines doesn’t converge since the baseline translation is parallel to the image plane!

Epipolar geometry

- Even if the image plane $\boldsymbol{I}$ was infinite, you can't see the place of $\boldsymbol{o}'$.



Contents

- structure from motion
- Epipolar geometry
  - **Essential matrix**
  - Fundamental matrix
  - Estimating the fundamental matrix
- Camera rectification
- Triangulation
- Stereo matching
- Other 3D sensors

Recall: Dot Product



$$c \cdot a = 0 \qquad c \cdot b = 0$$

dot product of two orthogonal vectors is zero

Recall: Cross Product

Vector (cross) product
takes two vectors and returns a vector perpendicular to both

$$\boldsymbol{c} = \boldsymbol{a} \times \boldsymbol{b}$$



$$\boldsymbol{c} \cdot \boldsymbol{a} = 0 \qquad \boldsymbol{c} \cdot \boldsymbol{b} = 0$$

Recall: Cross Product

$$\boldsymbol{a} \times \boldsymbol{b} = \begin{bmatrix} a_2 b_3 - a_3 b_2 \\ a_3 b_1 - a_1 b_3 \\ a_1 b_2 - a_2 b_1 \end{bmatrix}$$

Can also be written as a matrix multiplication

$$\boldsymbol{a} \times \boldsymbol{b} = [\boldsymbol{a}]_\times \boldsymbol{b} = \begin{bmatrix} 0 & -a_3 & a_2 \\ a_3 & 0 & -a_1 \\ -a_2 & a_1 & 0 \end{bmatrix} \begin{bmatrix} b_1 \\ b_2 \\ b_3 \end{bmatrix}$$

Skew symmetric

Building the essential matrix

- Let's define the o system as world coordinate system.



$$x' = \mathbf{R}(x - t)$$

*t here is c from camera calibration class

Building the essential matrix



These three vectors are coplanar $\boldsymbol{x}, \boldsymbol{t}, \boldsymbol{x}'$

Building the essential matrix



These three vectors are coplanar $\boldsymbol{x}, \boldsymbol{t}, \boldsymbol{x}'$

$$\boldsymbol{x}^\top (\boldsymbol{t} \times \boldsymbol{x}) = \ ?$$

Building the essential matrix



These three vectors are coplanar $\boldsymbol{x}, \boldsymbol{t}, \boldsymbol{x}'$

$$\boldsymbol{x}^\top (\boldsymbol{t} \times \boldsymbol{x}) = 0$$

Building the essential matrix



These three vectors are coplanar $\boldsymbol{x}, \boldsymbol{t}, \boldsymbol{x}'$

$$(\boldsymbol{x} - \boldsymbol{t})^\top (\boldsymbol{t} \times \boldsymbol{x}) = \ ?$$

Building the essential matrix



These three vectors are coplanar $\boldsymbol{x}, \boldsymbol{t}, \boldsymbol{x}'$

$$(\boldsymbol{x} - \boldsymbol{t})^\top (\boldsymbol{t} \times \boldsymbol{x}) = 0$$

Building the essential matrix

rigid motion

$$\boldsymbol{R^T = R^{-1}}$$

$$\boldsymbol{x' = \mathbf{R}(x - t)}$$

$$\boldsymbol{R^T x' = x - t}$$

$$\boldsymbol{x'^T R = (x - t)^T}$$

coplanarity

$$(\boldsymbol{x} - \boldsymbol{t})^\top (\boldsymbol{t} \times \boldsymbol{x}) = 0$$

$$(\boldsymbol{x}'^\top \mathbf{R})(\boldsymbol{t} \times \boldsymbol{x}) = 0$$

Building the essential matrix

rigid motion

$$\boldsymbol{x'} = \mathbf{R}(\boldsymbol{x} - \boldsymbol{t})$$

$$\boldsymbol{R^T} = \boldsymbol{R^{-1}}$$

$$\boldsymbol{R^T x'} = \boldsymbol{x} - \boldsymbol{t}$$

$$\boldsymbol{x'^T R} = (\boldsymbol{x} - \boldsymbol{t})^{\boldsymbol{T}}$$

coplanarity

$$(\boldsymbol{x} - \boldsymbol{t})^\top (\boldsymbol{t} \times \boldsymbol{x}) = 0$$

$$(\boldsymbol{x'}^\top \mathbf{R})(\boldsymbol{t} \times \boldsymbol{x}) = 0$$

$$(\boldsymbol{x'^T R})([\boldsymbol{t}]_{\boldsymbol{x}} \boldsymbol{x}) = 0$$

Building the essential matrix

rigid motion

$$\boldsymbol{x}' = \mathbf{R}(\boldsymbol{x} - \boldsymbol{t})$$

$$\boldsymbol{R}^{\boldsymbol{T}} = \boldsymbol{R}^{-\mathbf{1}}$$

$$\boldsymbol{R}^{\boldsymbol{T}}\boldsymbol{x}' = \boldsymbol{x} - \boldsymbol{t}$$

$$\boldsymbol{x}'^{\boldsymbol{T}}\boldsymbol{R} = (\boldsymbol{x} - \boldsymbol{t})^{\boldsymbol{T}}$$

coplanarity

$$(\boldsymbol{x} - \boldsymbol{t})^{\top}(\boldsymbol{t} \times \boldsymbol{x}) = 0$$

$$(\boldsymbol{x}'^{\top}\mathbf{R})(\boldsymbol{t} \times \boldsymbol{x}) = 0$$

$$(\boldsymbol{x}'^{\boldsymbol{T}}\boldsymbol{R})([\boldsymbol{t}]_{\boldsymbol{x}}\boldsymbol{x}) = 0$$

$$\boldsymbol{x}'^{\boldsymbol{T}}(\boldsymbol{R}[\boldsymbol{t}]_{\boldsymbol{x}})\boldsymbol{x} = 0$$

Building the essential matrix

rigid motion

$$\boldsymbol{R^T = R^{-1}}$$

$$\boldsymbol{x' = \mathbf{R}(x - t)}$$

$$\boldsymbol{R^T x' = x - t}$$

$$\boldsymbol{x'^T R = (x - t)^T}$$

coplanarity

$$(\boldsymbol{x} - \boldsymbol{t})^\top (\boldsymbol{t} \times \boldsymbol{x}) = 0$$

$$(\boldsymbol{x}'^\top \mathbf{R})(\boldsymbol{t} \times \boldsymbol{x}) = 0$$

$$(\boldsymbol{x'^T R})([\boldsymbol{t}]_x \boldsymbol{x}) = 0$$

$$\boldsymbol{x'^T}(\boldsymbol{R}[\boldsymbol{t}]_x)\boldsymbol{x} = 0$$

$$\boldsymbol{x}'^\top \mathbf{E} \boldsymbol{x} = 0$$

Building the essential matrix

rigid motion

$$\boldsymbol{R^T = R^{-1}}$$

$$\boldsymbol{x' = \mathrm{R}(x - t)}$$

$$\boldsymbol{R^T x' = x - t}$$

$$\boldsymbol{x'^T R = (x - t)^T}$$

coplanarity

$$(\boldsymbol{x} - \boldsymbol{t})^\top (\boldsymbol{t} \times \boldsymbol{x}) = 0$$

$$(\boldsymbol{x}'^\top \mathbf{R})(\boldsymbol{t} \times \boldsymbol{x}) = 0$$

$$(\boldsymbol{x}'^T \boldsymbol{R})([\boldsymbol{t}]_x \boldsymbol{x}) = 0$$

$$\boldsymbol{x}'^T (\boldsymbol{R}[\boldsymbol{t}]_x)\boldsymbol{x} = 0$$

$$\boldsymbol{x}'^\top \mathbf{E}\boldsymbol{x} = 0$$

Essential Matrix

$$\boldsymbol{E = R}[\boldsymbol{t}]_x$$

properties of the E matrix

(points in normalized image coordinates)

Essential matrix definition $x'^T E x = 0$

Epipolar lines equation

- Recall this version of line equation:

$$ax + by + c = 0$$

For homogenous vector $x = \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$ and $l = \begin{bmatrix} a \\ b \\ c \end{bmatrix}$:

$$x^T l = l^T x = 0$$

Epipolar lines equation

- $x'^T E x = x'^T l' = 0$
  $Ex = l'$ is the epipolar line in I' corresponding to x.
- $x'^T E x = l^T x = 0$
  $(x'^T E)^T = l^{T^T} = l$ is the epipolar line in I corresponding to x'.



properties of the E matrix

(points in normalized image coordinates)

Essential matrix definition $x'^T E x = 0$

Epipolar lines

- $Ex = l'$ is the epipolar line in I' corresponding to x
- $(x'^T E)^T = l^{T^T} = l$ is the epipolar line in I corresponding to x'.

- Full proof for the epipolar lines can be found here:

http://www.cs.cornell.edu/courses/cs4670/2015sp/lectures/lec21_stereo_web.pdf

Epipolar lines equation

- $e'^T l' = 0 \quad \forall x$ s.t. $Ex = l'$, meaning:

$$\boldsymbol{e'^T E = 0}$$

- $l^T e = 0 \quad \forall x'$ s.t. $x'^T E = l^T$ meaning:

$$\boldsymbol{Ee = 0}$$



properties of the E matrix

(points in normalized image coordinates)

Essential matrix definition $x'^T E x = 0$

Epipolar lines
- $Ex = l'$ is the epipolar line in I' corresponding to x
- $(x'^T E)^T = l^{T^T} = l$ is the epipolar line in I corresponding to x'.

Epipoles $e'^T E = 0$ $Ee = 0$

Contents

- structure from motion
- Epipolar geometry
  - Essential matrix
  - **Fundamental matrix**
  - Estimating the fundamental matrix
- Camera rectification
- Triangulation
- Stereo matching
- Other 3D sensors

Fundamental matrix

$$\hat{\boldsymbol{x}}'^{\top}\mathbf{E}\hat{\boldsymbol{x}} = 0$$

The Essential matrix operates on image points expressed in **normalized coordinates**
(points have been aligned (normalized) to camera coordinates)

$$\hat{\boldsymbol{x}}' = \mathbf{K}^{-1}\boldsymbol{x}'$$

$$\hat{\boldsymbol{x}} = \mathbf{K}^{-1}\boldsymbol{x}$$

camera point

image point

Fundamental matrix

$$\hat{\boldsymbol{x}}'^{\top}\mathbf{E}\hat{\boldsymbol{x}} = 0$$

The Essential matrix operates on image points expressed in **normalized coordinates**
(points have been aligned (normalized) to camera coordinates)

$$\hat{\boldsymbol{x}}' = \mathbf{K}^{-1}\boldsymbol{x}' \qquad \hat{\boldsymbol{x}} = \mathbf{K}^{-1}\boldsymbol{x}$$

camera point — image point

Writing out the epipolar constraint in terms of image coordinates

$$\boldsymbol{x}'^{\top}\mathbf{K}'^{-\top}\mathbf{E}\mathbf{K}^{-1}\boldsymbol{x} = 0$$
$$\boldsymbol{x}'^{\top}(\mathbf{K}'^{-\top}\mathbf{E}\mathbf{K}^{-1})\boldsymbol{x} = 0$$
$$\boldsymbol{x}'^{\top}\mathbf{F}\boldsymbol{x} = 0$$

Essential Matrix

$$\boldsymbol{F} = \boldsymbol{K}'^{-\boldsymbol{T}}\boldsymbol{E}\boldsymbol{K}^{-\mathbf{1}}$$

properties of the F matrix

- All of the below functions works with $\boldsymbol{F}$ and un-normalized points the same!

(points in un-normalized image coordinates)

Fundamental matrix definition $x'^T \boldsymbol{F} x = 0$

Epipolar lines

- $\boldsymbol{F}x = l'$ is the epipolar line in I' corresponding to x
- $(x'^T \boldsymbol{F})^T = l^{T^T} = l$ is the epipolar line in I corresponding to x'.

Epipoles $e'^T \boldsymbol{F} = 0$ $\boldsymbol{F} e = 0$

Contents

- structure from motion
- Epipolar geometry
  - Essential matrix
  - Fundamental matrix
  - **Estimating the fundamental matrix**
- Camera rectification
- Triangulation
- Stereo matching
- Other 3D sensors

Estimating F

- If we don't know $\mathbf{K}_1$, $\mathbf{K}_2$, $\mathbf{R}$, or $\mathbf{t}$, can we estimate $\mathbf{F}$ for two images?
- Yes, given enough correspondences

Estimating F – 8-point algorithm

- The fundamental matrix F is defined by

$$\mathbf{x}'^{\mathrm{T}}\mathbf{F}\mathbf{x} = 0$$

for any pair of matches x and x’ in two images.

- Let x=$(u,v,1)^{\mathrm{T}}$ and x’=$(u’,v’,1)^{\mathrm{T}}$,

$$\mathbf{F} = \begin{bmatrix} f_{11} & f_{12} & f_{13} \\ f_{21} & f_{22} & f_{23} \\ f_{31} & f_{32} & f_{33} \end{bmatrix}$$

each match gives a linear equation

$$uu'\,f_{11} + vu'\,f_{12} + u'\,f_{13} + uv'\,f_{21} + vv'\,f_{22} + v'\,f_{23} + uf_{31} + vf_{32} + f_{33} = 0$$

8-point algorithm

- Like with homographies, instead of solving $\mathbf{Af} = 0$, we seek $\mathbf{f}$ to minimize $\|\mathbf{Af}\|$, least eigenvector of $\mathbf{A}^{\mathrm{T}}\mathbf{A}$.

$$\begin{bmatrix} u_1u_1' & v_1u_1' & u_1' & u_1v_1' & v_1v_1' & v_1' & u_1 & v_1 & 1 \\ u_2u_2' & v_2u_2' & u_2' & u_2v_2' & v_2v_2' & v_2' & u_2 & v_2 & 1 \\ \vdots & \vdots & \vdots & \vdots & \vdots & \vdots & \vdots & \vdots & \vdots \\ u_nu_n' & v_nu_n' & u_n' & u_nv_n' & v_nv_n' & v_n' & u_n & v_n & 1 \end{bmatrix} \begin{bmatrix} f_{11} \\ f_{12} \\ f_{13} \\ f_{21} \\ f_{22} \\ f_{23} \\ f_{31} \\ f_{32} \\ f_{33} \end{bmatrix} = 0$$

8-point algorithm – Problem?

- **F** should have rank 2
- To enforce that **F** is of rank 2, F is replaced by F' that minimizes $\|\mathbf{F}-\mathbf{F}'\|$ subject to the rank constraint.

- This is achieved by SVD. Let $\mathbf{F}=\mathbf{U}\Sigma\mathbf{V}^{\mathrm{T}}$, where

$$\Sigma=\begin{bmatrix}\sigma_1 & 0 & 0\\ 0 & \sigma_2 & 0\\ 0 & 0 & \sigma_3\end{bmatrix},\ \text{let}\quad \Sigma'=\begin{bmatrix}\sigma_1 & 0 & 0\\ 0 & \sigma_2 & 0\\ 0 & 0 & 0\end{bmatrix}$$

then $\mathbf{F}'=\mathbf{U}\Sigma'\mathbf{V}^{\mathrm{T}}$ is the solution.

8-point algorithm

- Pros: it is linear, easy to implement and fast
- Cons: susceptible to noise.
  - Solutions: (all out of scope)
    - normalized 8 points algorithm.
    - 7 points algorithm.
    - Finding K,K’ with single camera intrinsics calibration and then search for E (only 5 DOFs instead of 8/7).

Contents

- structure from motion
- Epipolar geometry
  - Essential matrix
  - Fundamental matrix
  - Estimating the fundamental matrix
- **Camera rectification**
- Triangulation
- Stereo matching
- Other 3D sensors

Structure and motion

	Structure (3D model of world)	Motion (6 DOFs of cameras)	Measurements
Pose Estimation (camera pose estimation)	known	**estimate**	3D to 2D correspondences
Triangulation	**estimate**	known	2D to 2D correspondences
3D reconstruction	**estimate**	**Estimated!**	2D to 2D correspondences + triangulation

We've found the motion, let's find the structure – back to triangulation problem!

How would you reconstruct 3D points?

Left image

Right image

How would you reconstruct 3D points?



Left image

Right image

1. Select point in one image

How would you reconstruct 3D points?



Left image



Right image

1. Select point in one image
2. Form epipolar line for that point in second image

How would you reconstruct 3D points?



Left image

Right image

1. Select point in one image
2. Form epipolar line for that point in second image
3. Find matching point along line (how?)

How would you reconstruct 3D points?



Left image



Right image

1. Select point in one image
2. Form epipolar line for that point in second image
3. Find matching point along line (how?)
4. Perform triangulation (how?)

Stereo image rectification

- Out of scope…
- Let’s say the images comes rectified (as in the yellow samples).





Original stereo pair

After rectification

Contents

- structure from motion
- Epipolar geometry
  - Essential matrix
  - Fundamental matrix
  - Estimating the fundamental matrix
- Camera rectification
- **Triangulation**
- Stereo matching
- Other 3D sensors

triangulation

triangulation

Objects that are close move more or less?

triangulation





- The amount of horizontal movement is inversely proportional to the distance from the camera.
- The amount of horizontal movement == disparity.
- Distance from the camera == depth (or Z).

triangulation



Similar triangles:

$$\frac{T}{Z} = \frac{T + x_r - x_l}{Z - f}$$

$$Z = \frac{f \cdot T}{x_l - x_r}$$

baseline

focal length

disparity

Contents

- structure from motion
- Epipolar geometry
  - Essential matrix
  - Fundamental matrix
  - Estimating the fundamental matrix
- Camera rectification
- Triangulation
- **Stereo matching**
- Other 3D sensors

Stereo Block Matching



- Slide a window along the epipolar line and compare contents of that window with the reference window in the left image
- Matching cost: SSD or normalized correlation



SSD



Normalized cross-correlation

Effect of window size

W = 3



W = 20

Effect of window size

W = 3



W = 20

Smaller window

+ More detail
- More noise

Larger window

+ Smoother disparity maps
- Less detail
- Fails near boundaries

When will stereo block matching fail?



When will stereo block matching fail?





Block matching



Ground truth

What are some problems with the result?



How can we improve depth estimation?



How can we improve depth estimation?

Too many discontinuities.
We expect disparity values to change slowly.

Let's make an assumption:
depth should change smoothly

Energy Minimization



What defines a good stereo correspondence?

1. **Match quality**
   - Want each pixel to find a good match in the other image
2. **Smoothness**
   - If two pixels are adjacent, they should (usually) move about the same amount

energy function
(for one pixel)

$$E(d) = \underbrace{E_d(d)}_{\text{data term}} + \lambda \underbrace{E_s(d)}_{\text{smoothness term}}$$

Want each pixel to find a good match in the other image

(block matching result)

Adjacent pixels should (usually) move about the same amount

(smoothness function)

$$E(d) = E_d(d) + \lambda E_s(d)$$

$$E_d(d) = \sum_{(x,y)\in I} C(x, y, d(x, y))$$

data term

SSD distance between windows
centered at I(x, y) and J(x+ d(x,y), y)

$$E(d) = E_d(d) + \lambda E_s(d)$$

$$E_d(d) = \sum_{(x,y) \in I} C(x, y, d(x, y))$$

SSD distance between windows centered at I(x, y) and J(x+ d(x,y), y)

$$E_s(d) = \sum_{(p,q) \in \mathcal{E}} V(d_p, d_q)$$

smoothness term

$\mathcal{E}$: set of neighboring pixels



4-connected neighborhood

8-connected neighborhood

$$E_s(d) = \sum_{(p,q)\in\mathcal{E}} V(d_p, d_q)$$

smoothness term

$$V(d_p, d_q) = |d_p - d_q|$$

L_1 distance



$$V(d_p, d_q) = \begin{cases} 0 & \text{if } d_p = d_q \\ 1 & \text{if } d_p \neq d_q \end{cases}$$

"Potts model"



Dynamic Programming

One possible solution…

$$E(d) = E_d(d) + \lambda E_s(d)$$

Can minimize this independently per scanline using dynamic programming (DP) ●…●…●

$D(x, y, d)$: minimum cost of solution such that d(x,y) = d

$$D(x, y, d) = C(x, y, d) + \min_{d'} \{D(x-1, y, d') + \lambda \, |d - d'|\}$$



Y. Boykov, O. Veksler, and R. Zabih, Fast Approximate Energy Minimization via Graph Cuts, PAMI 2001

Contents

- structure from motion
- Epipolar geometry
  - Essential matrix
  - Fundamental matrix
  - Estimating the fundamental matrix
- Camera rectification
- Triangulation
- Stereo matching
- **Other 3D sensors**

Other types of 3D sensors

- **LIDAR**, which stands for **Light Detection and Ranging (or light radar),** is a remote sensing method that uses light in the form of a pulsed laser to measure ranges.
- Most known: velodyne projector.





Other types of 3D sensors

- Structured light





(a)



(b)



(c)

Other types of 3D sensors

- Coded light
- Realsense SR305
- https://www.youtube.com/watch?v=PluL7WTlKrM

Other types of 3D sensors

- *Light Coding*
- *Used in Kinect v1- Kinect for xbox 360.*
- *Iphone x front camera*