



EXERCISES — Array Max Min

version #7be580532266ed398481e31366afcc24b1950c2a



**The way is lit. The path is clear.
We require only the strength to follow it.**

Copyright

This document is for internal use at EPITA ([website](#)) only.

Copyright © 2022-2023 Assistants <assistants@tickets.assistants.epita.fr>

The use of this document must abide by the following rules:

- ▷ You downloaded it from the assistants' intranet.*
- ▷ This document is strictly personal and must **not** be passed onto someone else.
- ▷ Non-compliance with these rules can lead to severe sanctions.

Contents

1	Goal	3
2	Example	3

*<https://intra.assistants.epita.fr>

File Tree

```
array_max_min/  
├── array_max_min.c  (to submit)  
└── array_max_min.h  (to submit)
```

Authorized headers : You are only allowed to use the functions defined in the following headers

- err.h
- errno.h
- assert.h
- stddef.h

Compilation : Your code must compile with the following flags

- -std=c99 -pedantic -Werror -Wall -Wextra -Wvla

Main function : None

1 Goal

Write a function that takes an array `tab` of integers and its length `len`, along with two pointers and set the value of the two pointers to the maximum and minimum of the array.

If `tab` is `NULL` or `len` is equal to 0, the function does nothing.

Prototype:

```
void array_max_min(int tab[], size_t len, int *max, int *min);
```

2 Example

```
int main(void)  
{  
    int max = 0;  
    int min = 0;  
    int tab[] = { 5, 3, 1, 42, 53, 3, 47 };  
    size_t len = 7;  
  
    array_max_min(tab, len, &max, &min);  
  
    printf("max : %d\n", max);  
    printf("min : %d\n", min);  
  
    return 0;  
}
```

Output:

```
42sh$ ./array_max_min  
max : 53  
min : 1
```

The way is lit. The path is clear. We require only the strength to follow it.