



EXERCISES — Variant

version #7be580532266ed398481e31366afcc24b1950c2a



**The way is lit. The path is clear.
We require only the strength to follow it.**

Copyright

This document is for internal use at EPITA ([website](#)) only.

Copyright © 2022-2023 Assistants <assistants@tickets.assistants.epita.fr>

The use of this document must abide by the following rules:

- ▷ You downloaded it from the assistants' intranet.*
- ▷ This document is strictly personal and must **not** be passed onto someone else.
- ▷ Non-compliance with these rules can lead to severe sanctions.

Contents

1	Goal	3
2	Display	4
3	Equal	4
4	Find	4
5	Sum	4

*<https://intra.assistants.epita.fr>

File Tree

```
variant/  
├── variant.c  (to submit)  
└── variant.h
```

Authorized functions : You are only allowed to use the following functions

- `printf(3)`
- `strcmp(3)`

Authorized headers : You are only allowed to use the functions defined in the following headers

- `err.h`
- `errno.h`
- `assert.h`
- `stddef.h`
- `stdbool.h`

Compilation : Your code must compile with the following flags

- `-std=c99 -pedantic -Werror -Wall -Wextra -Wvla`

Main function : None

1 Goal

In this exercise you will implement a variant using a tagged union. To do so, you need to write a structure named `variant` containing:

- An union, named `type_any`
- An enum representing the field currently held by the union, named `type`

The variant must be able to store the following types:

- `int`
- `float`
- `char`
- `const char *`

2 Display

Write a function that will print the content of a variant on the standard output, followed by a line feed (\n).

For instance, if the variant contains the following integer value: 12, it should display 12\n.

```
void variant_display(const struct variant *e);
```

3 Equal

Write a function that returns true if two variants have the same type **and** the same content.

```
bool variant_equal(const struct variant *left, const struct variant *right);
```

Note that you must include `stdbool.h` to have booleans.

4 Find

Write a function that will look for an element in a variant array. The function will return the index of the first matched element if found, otherwise it returns -1.

```
int variant_find(const struct variant *array, size_t len, enum type type,
                union type_any value);
```

5 Sum

Write a function that returns the sum of all numeric elements in a variant array (int and float)

```
float variant_sum(const struct variant *array, size_t len);
```

The way is lit. The path is clear. We require only the strength to follow it.