



EXERCISES — Simple fnmatch

version #7be580532266ed398481e31366afcc24b1950c2a



**The way is lit. The path is clear.
We require only the strength to follow it.**

Copyright

This document is for internal use at EPITA ([website](#)) only.

Copyright © 2022-2023 Assistants <assistants@tickets.assistants.epita.fr>

The use of this document must abide by the following rules:

- ▷ You downloaded it from the assistants' intranet.*
- ▷ This document is strictly personal and must **not** be passed onto someone else.
- ▷ Non-compliance with these rules can lead to severe sanctions.

Contents

1	Goal	3
2	Requirements	3

*<https://intra.assistants.epita.fr>

File Tree

```
simple_fnmatch/  
├── simple_fnmatch.c  (to submit)  
└── simple_fnmatch.h
```

Authorized headers : You are only allowed to use the functions defined in the following headers

- `err.h`
- `errno.h`
- `assert.h`
- `stddef.h`

Compilation : Your code must compile with the following flags

- `-std=c99 -pedantic -Werror -Wall -Wextra -Wvla`

Main function : None

1 Goal

You have to implement a subset of the `fnmatch(3)` function from the standard C library, with the following signature.

```
int simple_fnmatch(const char *pattern, const char *string);
```

The expected return value is 0 if there is a match between the pattern and the string, `FNM_NOMATCH` otherwise.

2 Requirements

Your function must accept and handle accurately:

- the `?` wildcard, matching any one character,
- the `*` wildcard, matching 0 or more characters,
- the escaping character `\\`.

Your function shall have the same behaviour as `fnmatch(3)` when called with an empty `flags` argument (the value 0).

The way is lit. The path is clear. We require only the strength to follow it.