SALESIA ENTERPRISE · FASE 16

Diccionario de datos

Esquema completo de PostgreSQL: 23 tablas

DOCUMENTO	diccionario-datos.md
VERSIÓN	1.0
FECHA	14 de octubre de 2026
PLATAFORMA	React 19 + TypeScript · FastAPI · PostgreSQL 17
DESPLIEGUE	Render (API) · Vercel (web) · Supabase (BD)
ESTADO	Sistema desplegado y verificado

Índice

audit_logs 4
bayes_analyses 4
categories 5
companies 5
customers 5
dataset_variables 6
datasets 6
employees 6
insights 7
inventory 7
inventory_movements 8
observations 8
payment_methods 9
payments 9
products 9
random_variables 10
reports 10
roles 11
sale_details 11
sales 11
statistical_analyses 12
statistical_results 12
users 13

- audit_logs
- bayes_analyses
- categories
- companies
- customers
- dataset_variables
- datasets
- employees
- insights
- inventory
- inventory_movements
- observations
- payment_methods
- payments
- products
- random_variables
- reports
- roles
- sale_details
- sales
- statistical_analyses
- statistical_results
- users

Diccionario de datos — SalesIA Enterprise

> Generado desde el esquema real de PostgreSQL (`database/migrations/001_initial_schema.sql`). **23 tablas · 191 columnas.** Conventions: las claves primarias `id` son `BIGINT` autogenerados (`GENERATED BY DEFAULT AS IDENTITY`); todos los registros llevan `created_at` y, si son editables, `updated_at` (`TIMESTAMPTZ` , UTC). **Aislamiento multiempresa**: toda tabla operativa incluye `company_id` y el backend filtra siempre por la empresa del usuario autenticado.

Índice de tablas

- **Núcleo comercial**: `companies` · `roles` · `users` · `employees` · `customers` · `categories` · `products` · `payment_methods`
- **Operación**: `sales` · `sale_details` · `payments` · `inventory` · `inventory_movements`

- **Analítica**: `datasets` · `dataset_variables` · `observations` · `random_variables` · `statistical_analyses` · `statistical_results` · `bayes_analyses`
- **Inteligencia**: `insights` · `reports` · `audit_logs`

Leyenda de tipos: `VARCHAR(n)` = texto de longitud máxima · `NUMERIC` = decimal exacto (importes) · `DOUBLE` = doble precisión (cálculos estadísticos) · `JSONB` = documento flexible · `INET` = dirección IP · `TIMESTAMPTZ` = fecha-hora con zona (UTC).

`audit_logs`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`company_id`	BIGINT → `companies`	NULL	—
`user_id`	BIGINT → `users`	NULL	—
`action`	VARCHAR(100)	—	—
`entity_type`	VARCHAR(80)	NULL	—
`entity_id`	VARCHAR(80)	NULL	—
`ip_address`	INET	NULL	—
`details`	JSONB	—	'{}'::jsonb
`created_at`	TIMESTAMPTZ	—	NOW()

`bayes_analyses`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`analysis_id`	BIGINT → `statistical_analyses`	—	—
`probability_a`	DOUBLE	—	—
`probability_b_given_a`	DOUBLE	—	—
`probability_b`	DOUBLE	—	—
`posterior_probability`	DOUBLE	—	—
`explanation`	TEXT	NULL	—
`created_at`	TIMESTAMPTZ	—	NOW()

`categories`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`company_id`	BIGINT → `companies`	—	—
`name`	VARCHAR(100)	—	—
`description`	TEXT	NULL	—
`is_active`	BOOLEAN	—	true
`created_at`	TIMESTAMPTZ	—	NOW()

`companies`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`name`	VARCHAR(160)	—	—
`tax_id`	VARCHAR(30)	NULL	—
`email`	VARCHAR(255)	NULL	—
`phone`	VARCHAR(30)	NULL	—
`address`	VARCHAR(255)	NULL	—
`is_active`	BOOLEAN	—	true
`created_at`	TIMESTAMPTZ	—	NOW()
`updated_at`	TIMESTAMPTZ	—	NOW()

`customers`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`company_id`	BIGINT → `companies`	—	—
`document_type`	VARCHAR(20)	NULL	—
`document_number`	VARCHAR(30)	NULL	—
`full_name`	VARCHAR(160)	—	—
`email`	VARCHAR(255)	NULL	—

Columna	Tipo	Nulo	Default
`phone`	VARCHAR(30)	NULL	—
`address`	VARCHAR(255)	NULL	—
`is_active`	BOOLEAN	—	true
`created_at`	TIMESTAMPTZ	—	NOW()
`updated_at`	TIMESTAMPTZ	—	NOW()

`dataset_variables`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`dataset_id`	BIGINT → `datasets`	—	—
`name`	VARCHAR(120)	—	—
`data_type`	VARCHAR(30)	—	—
`variable_type`	VARCHAR(30)	NULL	—
`description`	TEXT	NULL	—

`datasets`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`company_id`	BIGINT → `companies`	—	—
`name`	VARCHAR(160)	—	—
`source_type`	VARCHAR(50)	—	—
`description`	TEXT	NULL	—
`created_by`	BIGINT → `users`	NULL	—
`created_at`	TIMESTAMPTZ	—	NOW()

`employees`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—

Columna	Tipo	Nulo	Default
`company_id`	BIGINT → `companies`	—	—
`user_id`	BIGINT → `users`	NULL	—
`employee_code`	VARCHAR(40)	NULL	—
`full_name`	VARCHAR(160)	—	—
`email`	VARCHAR(255)	NULL	—
`phone`	VARCHAR(30)	NULL	—
`is_active`	BOOLEAN	—	true
`created_at`	TIMESTAMPTZ	—	NOW()

`insights`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`company_id`	BIGINT → `companies`	—	—
`analysis_id`	BIGINT → `statistical_analyses`	NULL	—
`dataset_id`	BIGINT → `datasets`	NULL	—
`rule_code`	VARCHAR(40)	—	—
`fingerprint`	VARCHAR(64)	—	—
`title`	VARCHAR(180)	—	—
`description`	TEXT	—	—
`evidence`	JSONB	—	'{}'::jsonb
`severity`	VARCHAR(20)	—	'info'::character varying
`created_at`	TIMESTAMPTZ	—	NOW()

`inventory`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`company_id`	BIGINT → `companies`	—	—
`product_id`	BIGINT → `products`	—	—

Columna	Tipo	Nulo	Default
`quantity_on_hand`	NUMERIC	—	0
`minimum_quantity`	NUMERIC	—	0
`updated_at`	TIMESTAMPTZ	—	NOW()

`inventory_movements`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`company_id`	BIGINT → `companies`	—	—
`product_id`	BIGINT → `products`	—	—
`user_id`	BIGINT → `users`	NULL	—
`sale_id`	BIGINT → `sales`	NULL	—
`movement_type`	VARCHAR(20)	—	—
`quantity`	NUMERIC	—	—
`reason`	VARCHAR(255)	NULL	—
`created_at`	TIMESTAMPTZ	—	NOW()

`observations`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`dataset_id`	BIGINT → `datasets`	—	—
`variable_id`	BIGINT → `dataset_variables`	—	—
`numeric_value`	DOUBLE	NULL	—
`text_value`	TEXT	NULL	—
`observed_at`	TIMESTAMPTZ	NULL	—
`metadata`	JSONB	—	'{}'::jsonb
`created_at`	TIMESTAMPTZ	—	NOW()

payment_methods

Columna	Tipo	Nulo	Default
id	BIGINT	—	—
company_id	BIGINT → companies	—	—
name	VARCHAR(80)	—	—
code	VARCHAR(40)	—	—
is_active	BOOLEAN	—	true
created_at	TIMESTAMPTZ	—	NOW()

payments

Columna	Tipo	Nulo	Default
id	BIGINT	—	—
sale_id	BIGINT → sales	—	—
payment_method_id	BIGINT → payment_methods	—	—
amount	NUMERIC	—	—
currency	CHARACTER(3)	—	'PEN'::bpchar
status	VARCHAR(20)	—	'pending'::character varying
reference	VARCHAR(120)	NULL	—
paid_at	TIMESTAMPTZ	NULL	—
created_at	TIMESTAMPTZ	—	NOW()

products

Columna	Tipo	Nulo	Default
id	BIGINT	—	—
company_id	BIGINT → companies	—	—
category_id	BIGINT → categories	NULL	—
sku	VARCHAR(60)	—	—
name	VARCHAR(180)	—	—
description	TEXT	NULL	—

Columna	Tipo	Nulo	Default
`unit_price`	NUMERIC	—	—
`cost_price`	NUMERIC	—	0
`is_active`	BOOLEAN	—	true
`created_at`	TIMESTAMPTZ	—	NOW()
`updated_at`	TIMESTAMPTZ	—	NOW()

`random_variables`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`dataset_id`	BIGINT → `datasets`	—	—
`variable_id`	BIGINT → `dataset_variables`	—	—
`distribution_name`	VARCHAR(80)	NULL	—
`parameters`	JSONB	—	'{}'::jsonb
`created_at`	TIMESTAMPTZ	—	NOW()

`reports`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`company_id`	BIGINT → `companies`	—	—
`report_type`	VARCHAR(60)	—	—
`title`	VARCHAR(180)	—	—
`filters`	JSONB	—	'{}'::jsonb
`content`	JSONB	—	'{}'::jsonb
`file_path`	TEXT	NULL	—
`created_by`	BIGINT → `users`	NULL	—
`created_at`	TIMESTAMPTZ	—	NOW()

roles

Columna	Tipo	Nulo	Default
id	BIGINT	—	—
name	VARCHAR(40)	—	—
description	VARCHAR(255)	NULL	—

sale_details

Columna	Tipo	Nulo	Default
id	BIGINT	—	—
sale_id	BIGINT → sales	—	—
product_id	BIGINT → products	—	—
quantity	NUMERIC	—	—
unit_price	NUMERIC	—	—
discount_amount	NUMERIC	—	0
line_total	NUMERIC	—	—
created_at	TIMESTAMPTZ	—	NOW()

sales

Columna	Tipo	Nulo	Default
id	BIGINT	—	—
company_id	BIGINT → companies	—	—
customer_id	BIGINT → customers	NULL	—
employee_id	BIGINT → employees	NULL	—
created_by	BIGINT → users	NULL	—
sale_number	VARCHAR(50)	—	—
status	VARCHAR(20)	—	'draft'::character varying
currency	CHARACTER(3)	—	'PEN'::bpchar
subtotal	NUMERIC	—	0
discount_amount	NUMERIC	—	0

Columna	Tipo	Nulo	Default
tax_amount	NUMERIC	—	0
total_amount	NUMERIC	—	0
notes	TEXT	NULL	—
sold_at	TIMESTAMPTZ	—	NOW()
created_at	TIMESTAMPTZ	—	NOW()
updated_at	TIMESTAMPTZ	—	NOW()

statistical_analyses

Columna	Tipo	Nulo	Default
id	BIGINT	—	—
company_id	BIGINT → companies	—	—
dataset_id	BIGINT → datasets	NULL	—
analysis_type	VARCHAR(60)	—	—
parameters	JSONB	—	'{}'::jsonb
status	VARCHAR(20)	—	'completed'::character varying
created_by	BIGINT → users	NULL	—
created_at	TIMESTAMPTZ	—	NOW()

statistical_results

Columna	Tipo	Nulo	Default
id	BIGINT	—	—
analysis_id	BIGINT → statistical_analyses	—	—
metric_name	VARCHAR(100)	—	—
numeric_result	DOUBLE	NULL	—
result_payload	JSONB	—	'{}'::jsonb
created_at	TIMESTAMPTZ	—	NOW()

`users`

Columna	Tipo	Nulo	Default
`id`	BIGINT	—	—
`company_id`	BIGINT → `companies`	—	—
`role_id`	BIGINT → `roles`	—	—
`full_name`	VARCHAR(160)	—	—
`email`	VARCHAR(255)	—	—
`password_hash`	VARCHAR(255)	—	—
`is_active`	BOOLEAN	—	true
`last_login_at`	TIMESTAMPTZ	NULL	—
`created_at`	TIMESTAMPTZ	—	NOW()
`updated_at`	TIMESTAMPTZ	—	NOW()