

J.A.R.V.I.S Mark XLVII Project Review Engine

Project: CyberShield AI

Generated: 2026-07-05 15:49:39

Report kind: project_review

Metric	Score / 10
Security	5.0
Architecture	7.2
Maintainability	7.0
Overall	6.4

Executive Summary

EXECUTIVE SUMMARY

CyberShield_AI_Enterprise_Hardened_Enhanced was analyzed by J.A.R.V.I.S Mark XLVII Project Review Engine using indexed project evidence.

The current overall score is 6.4/10, with security 5.0/10, architecture 7.2/10, and maintainability 7.0/10.

Evidence detected: 78 indexed files, 17 backend routes, 1 frontend API calls, 15 auth-related files, and 6 test files.

Risk summary: 32 high/critical findings and 17 medium findings were detected by the rule-based analyzer.

The recommended next step is to fix the highest-risk security/configuration issues first, then strengthen tests, CI, and documentation.

Executive Summary

J.A.R.V.I.S Mark XLVII Project Review Engine
Generated: 2026-07-05 15:49:39
Project: CyberShield AI

Executive Summary

CyberShield_AI_Enterprise_Hardened_Enhanced was analyzed by J.A.R.V.I.S Mark XLVII Project Review Engine using indexed project evidence.

The current overall score is 6.4/10, with security 5.0/10, architecture 7.2/10, and maintainability 7.0/10.

Evidence detected: 78 indexed files, 17 backend routes, 1 frontend API calls, 15 auth-related files, and 6 test files.

Risk summary: 32 high/critical findings and 17 medium findings were detected by the rule-based analyzer.

The recommended next step is to fix the highest-risk security/configuration issues first, then strengthen tests, CI, and documentation.

J.A.R.V.I.S Mark Xlvii Project Health

Project: CyberShield_AI_Enterprise_Hardened_Enhanced
Path: E:\stick\De facut\Cyber Security App\CyberShield_AI_Enterprise_Hardened_Enhanced
Files indexed: 78

Tech stack: CSS, Docker, Express, FastAPI, Flask, HTML, JWT, JavaScript, Node.js, Pytest, Python, React, SQLAlchemy, SQLite, Tailwind, TypeScript, Vite

Scores:

- Security: 5.0/10
- Architecture: 7.2/10
- Maintainability: 7.0/10
- Overall: 6.4/10

Evidence counts:

- files_indexed: 78
- routes: 17
- frontend_api_calls: 1
- auth_files: 15
- jwt_files: 11
- database_files: 27
- frontend_files: 8
- test_files: 6
- docker_files: 1
- ci_files: 1
- config_files: 8

Risk matrix:

- POSITIVE: False-positive reduction: enabled
- HIGH: - HIGH: admin\admin.py contains weak/default secret or demo credential string: admin
- HIGH: - HIGH: admin\admin.py contains weak/default secret or demo credential string: secret
- HIGH: - HIGH: api.py contains weak/default secret or demo credential string: admin
- HIGH: - HIGH: api.py contains weak/default secret or demo credential string: password
- HIGH: - HIGH: api.py contains weak/default secret or demo credential string: secret
- HIGH: - HIGH: audit_backups\export_audit_secure.py contains weak/default secret or demo credential string: admin
- HIGH: - HIGH: audit_backups\export_audit_secure.py contains weak/default secret or demo credential string: secret

- HIGH: - HIGH: auditUI.py contains weak/default secret or demo credential string: admin
- HIGH: - HIGH: auditUI.py contains weak/default secret or demo credential string: changeme
- HIGH: - HIGH: auditUI.py contains weak/default secret or demo credential string: changeme123
- HIGH: - HIGH: auditUI.py contains weak/default secret or demo credential string: dev
- HIGH: - HIGH: backendutils\crypto.py contains weak/default secret or demo credential string: secret
- HIGH: - HIGH: backup.py contains weak/default secret or demo credential string: secret
- HIGH: - HIGH: config.py contains weak/default secret or demo credential string: password
- HIGH: - HIGH: config.py contains weak/default secret or demo credential string: secret
- HIGH: - HIGH: crypto\crypto.py contains weak/default secret or demo credential string: secret
- HIGH: - HIGH: crypto\key_rotation_scheduler.py contains weak/default secret or demo credential string: secret
- HIGH: - HIGH: crypto\key_rotation_scheduler.py contains weak/default secret or demo credential string: test
- HIGH: - HIGH: docs\DEPLOYMENT_GUIDE.md contains weak/default secret or demo credential string: secret

Priority action plan:

1. Fix HIGH severity findings first and verify secrets/authentication/configuration.
2. Review MEDIUM findings and create tracked tasks for each affected file.
3. Run the application locally after changes and record the exact command used.
4. Generate a fresh PDF/Word report after fixes to compare progress.
5. Keep backups before applying automatic patches.

Scorecard

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Path: E:\stick\De facut\Cyber Security App\CyberShield_AI_Enterprise_Hardened_Enhanced

Files indexed: 78

Tech stack: CSS, Docker, Express, FastAPI, Flask, HTML, JWT, JavaScript, Node.js, Pytest, Python, React, SQLAlchemy, SQLite, Tailwind, TypeScript, Vite

Scores:

- Security: 5.0/10
- Architecture: 7.2/10
- Maintainability: 7.0/10
- Overall: 6.4/10

Reasons:

Security:

- Authentication/authorization files detected.
- JWT/token handling evidence detected.
- Password hashing evidence detected.
- Environment/config/secret handling evidence detected.
- Tests detected.
- CI/workflow files detected.
- Upload/file handling evidence detected.
- Weak/demo secret or credential strings detected: admin\admin.py -> admin, admin\admin.py -> secret, api.py -> admin, api.py -> password, api.py -> secret, auditUI.py -> admin, auditUI.py -> changeme, auditUI.py -> changeme123

Architecture:

- Backend framework evidence detected.
- Frontend/UI layer detected.
- Database/storage layer detected.

- Backend routes detected.
- Frontend API calls detected.
- Docker/deployment evidence detected.
- Dependency manifests detected.
- Both FastAPI and Flask evidence detected; verify if this is intentional.

Maintainability:

- Tests detected.
- Dependency manifests detected.
- CI/workflow files detected.
- Docker/deployment files detected.
- Frontend source organization detected.
- Python source files detected.
- Non-trivial project size detected.

Evidence summary:

- Backend routes: 17
- Frontend API calls: 1
- Auth files: 15
- JWT files: 11
- Frontend files: 8
- Test files: 6
- Docker files: 1
- CI files: 1

Strict Grounded Analyzer Report

Mode: rule-based / no LLM / no speculation

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Path: E:\stick\De facut\Cyber Security App\CyberShield_AI_Enterprise_Hardened_Enhanced

Files indexed: 78

Detected tech stack from deep memory: CSS, Docker, Express, FastAPI, Flask, HTML, JWT, JavaScript, Node.js, Pytest, Python, React, SQLAlchemy, SQLite, Tailwind, TypeScript, Vite

Extensions: {'.py': 48, '.json': 5, '.md': 6, '.sh': 3, '.yaml': 2, '.txt': 1, '.html': 4, '.sql': 1, '.tsx': 4, '.js': 2, '.ts': 1, '.css': 1}

Dependency evidence:

- package.json: {'dependencies': ['@tailwindcss/forms', '@tailwindcss/typography', 'axios', 'cssnano', 'postcss-nesting', 'postcss-preset-env', 'react', 'react-dom'], 'devDependencies': ['@types/axios', '@types/react', '@types/react-dom', '@vitejs/plugin-react', 'autoprefixer', 'postcss', 'tailwindcss', 'typescript', 'vite'], 'scripts': {'dev': 'vite', 'build': 'vite build', 'preview': 'vite preview'}}
- file-scan-log-app\package.json: {'dependencies': ['axios', 'react', 'react-dom'], 'devDependencies': ['@vitejs/plugin-react', 'eslint', 'prettier', 'typescript', 'vite', 'vitest'], 'scripts': {'dev': 'vite', 'build': 'vite build', 'preview': 'vite preview', 'lint': 'eslint . --ext .ts,.tsx --fix', 'format': 'prettier --write .', 'audit': 'npm audit', 'test': 'vitest'}}
- requirements.txt: ['flask', 'bcrypt', 'pyotp', 'psycpg2-binary', 'boto3', 'python-dotenv']

FastAPI evidence files:

- auditUI.py
- routes\admin.py
- routes\auth.py
- routes\dashboard.py
- routes__init__.py
- test\test_auth.py

- tests\test_auth.py
- utils\auth.py

Flask evidence files:

- middleware.py
- security.py
- __init__.py
- admin\admin.py
- dashboard\dashboard.py
- templates\Dashboard Audit\audit_dashboard.py
- tests\test_dashboard_access.py

Authentication / authorization related files:

- auth.py
- permissions.py
- permissions_dynamic.py
- admin\admin.py
- admin\admin_permissions.html
- routes\admin.py
- routes\auth.py
- schemas\admin.py
- schemas\auth.py
- test\test_auth.py
- tests\test_auth.py
- tests\test_permissions.py
- utils\auth.py
- utils\auth_utils.py
- utils\token.py

JWT / token related files:

- config.py
- middleware.py
- docs\SECURITY_OVERVIEW.md
- file-scan-log-app\src\FileScanLog.tsx
- routes\auth.py
- schemas\auth.py
- test\test_auth.py
- tests\test_auth.py
- utils\auth.py
- utils\auth_utils.py
- utils\token.py

Password hashing evidence files:

- api.py
- encryptor.py
- requirements.txt
- routes\auth.py

Database / storage evidence files:

- api.py
- audit_log.py
- auth.py
- config.py
- db.py
- encryptor.py
- package-lock.json
- permissions_dynamic.py
- scanner.py
- security.py
- admin\admin.py
- audit_backups\export_audit_secure.py
- backend\audit_log.py
- backend\backup.py
- backend\database\init_db.py
- dashboard\dashboard.py
- docs\DEPLOYMENT_GUIDE.md
- file-scan-log-app\package-lock.json
- models\user.py
- routes\admin.py
- routes\auth.py
- routes\dashboard.py
- templates\Dashboard Audit\audit_dashboard.py
- tests\test_dashboard_access.py
- tests\test_permissions.py
- utils\auth.py
- utils\logger.py

Frontend / UI evidence files:

- components\AppLayout.tsx
- file-scan-log-app\postcss.config.js
- file-scan-log-app\tailwind.config.js
- file-scan-log-app\vite.config.ts
- file-scan-log-app\src\FileScanLog.tsx
- file-scan-log-app\src\index.css
- file-scan-log-app\src\main.tsx
- file-scan-log-app\src\ScanForm.tsx

File upload / file scan evidence files:

- api.py
- auditUI.py
- audit_log.py
- backup.py
- db.py
- encryptor.py
- package-lock.json

- package.json
- permissions.py
- scanner.py
- .github\workflows\security.yml
- audit_backups\decrypt.py
- audit_backups\export_audit.py
- audit_backups\export_audit_secure.py
- backend\backup.py
- backend\database\file_scans.sql
- backend\database\init_db.py
- backend\utils\crypto.py
- crypto\crypto.py
- crypto\key_rotation_scheduler.py
- docs\DEPLOYMENT_GUIDE.md
- file-scan-log-app\package-lock.json
- file-scan-log-app\package.json
- file-scan-log-app\src\FileScanLog.tsx
- file-scan-log-app\src\index.css
- file-scan-log-app\src\main.tsx
- file-scan-log-app\src\ScanForm.tsx

Logging / audit evidence files:

- api.py
- auditUI.py
- audit_log.py
- auth.py
- backup.py
- db.py
- email_alert.py
- encryptor.py
- explain.py
- gui.py
- logger.py
- permissions.py
- permissions_dynamic.py
- scanner.py
- security.py
- __init__.py
- admin\admin.py
- audit_backups\export_audit.py
- audit_backups\export_audit_secure.py
- backend\audit_log.py
- backend\backup.py
- backend\database\file_scans.sql
- backend\database\init_db.py

- backend\utils\crypto.py
- crypto\key_rotation_scheduler.py
- dashboard\dashboard.py
- file-scan-log-app\package.json
- routes\admin.py
- routes\auth.py
- routes\dashboard.py
- ... and 2 more

Docker / deployment evidence files:

- docker-compose.yml

CI / workflow evidence files:

- .github\workflows\security.yml

Test evidence files:

- test\security_scan.sh
- test\test_auth.py
- test\test_crypto.py
- tests\test_auth.py
- tests\test_dashboard_access.py
- tests\test_permissions.py

Detected backend routes:

- auditUI.py -> GET /audit-ui
- auditUI.py -> POST /audit-ui/delete
- auditUI.py -> GET /audit-ui/export
- security.py -> /login
- admin\admin.py -> ROUTE /admin
- admin\admin.py -> ROUTE /admin/grant
- admin\admin.py -> ROUTE /admin/revoke
- admin\admin.py -> /admin
- admin\admin.py -> /admin/grant
- admin\admin.py -> /admin/revoke
- dashboard\dashboard.py -> /dashboard
- routes\admin.py -> GET /dashboard
- routes\admin.py -> PUT /update
- routes\auth.py -> POST /login
- routes\dashboard.py -> GET /
- templates\Dashboard Audit\audit_dashboard.py -> ROUTE /audit
- templates\Dashboard Audit\audit_dashboard.py -> /audit

Detected frontend API calls:

- file-scan-log-app\src\ScanForm.tsx -> POST /api/scan

Conclusion:

This report only lists evidence found directly in indexed files. It does not infer hidden services, cloud infrastructure, ML models, or databases unless present in files.

Strict Security Analyzer Report

Mode: rule-based / no LLM / no speculation

False-positive reduction: enabled

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Files indexed: 78

Security findings:

- HIGH: admin\admin.py contains weak/default secret or demo credential string: admin
- HIGH: admin\admin.py contains weak/default secret or demo credential string: secret
- HIGH: api.py contains weak/default secret or demo credential string: admin
- HIGH: api.py contains weak/default secret or demo credential string: password
- HIGH: api.py contains weak/default secret or demo credential string: secret
- HIGH: audit_backups\export_audit_secure.py contains weak/default secret or demo credential string: admin
- HIGH: audit_backups\export_audit_secure.py contains weak/default secret or demo credential string: secret
- HIGH: auditUI.py contains weak/default secret or demo credential string: admin
- HIGH: auditUI.py contains weak/default secret or demo credential string: changeme
- HIGH: auditUI.py contains weak/default secret or demo credential string: changeme123
- HIGH: auditUI.py contains weak/default secret or demo credential string: dev
- HIGH: backend\utils\crypto.py contains weak/default secret or demo credential string: secret
- HIGH: backup.py contains weak/default secret or demo credential string: secret
- HIGH: config.py contains weak/default secret or demo credential string: password
- HIGH: config.py contains weak/default secret or demo credential string: secret
- HIGH: crypto\crypto.py contains weak/default secret or demo credential string: secret
- HIGH: crypto\key_rotation_scheduler.py contains weak/default secret or demo credential string: secret
- HIGH: crypto\key_rotation_scheduler.py contains weak/default secret or demo credential string: test
- HIGH: docs\DEPLOYMENT_GUIDE.md contains weak/default secret or demo credential string: secret
- HIGH: encryptor.py contains weak/default secret or demo credential string: admin
- HIGH: encryptor.py contains weak/default secret or demo credential string: password
- HIGH: encryptor.py contains weak/default secret or demo credential string: secret
- HIGH: middleware.py contains JWT handling without obvious expiration evidence.
- HIGH: routes\auth.py contains fake_users_db / hardcoded demo users. Replace with real database-backed users before production.
- HIGH: routes\auth.py contains weak/demo password strings. Remove demo credentials from source code.
- HIGH: utils\auth.py contains JWT handling without obvious expiration evidence.
- HIGH: utils\auth.py contains weak/default secret or demo credential string: admin
- HIGH: utils\auth.py contains weak/default secret or demo credential string: password
- HIGH: utils\auth.py contains weak/default secret or demo credential string: secret
- HIGH: utils\auth_utils.py contains weak/default secret or demo credential string: secret
- HIGH: utils\auth_utils.py contains weak/default secret or demo credential string: your-secret-key
- HIGH: utils\token.py contains weak/default secret or demo credential string: secret
- MEDIUM: __init__.py uses print-based audit/security logging. Consider structured logging with retention.
- MEDIUM: admin\admin.py reads security-sensitive environment variables, but missing-value validation is not obvious.
- MEDIUM: aes_cipher.py reads security-sensitive environment variables, but missing-value validation is not obvious.
- MEDIUM: api.py reads security-sensitive environment variables, but missing-value validation is not obvious.
- MEDIUM: audit_backups\export_audit.py references uploaded filenames without obvious filename sanitization.
- MEDIUM: audit_backups\export_audit.py uses print-based audit/security logging. Consider structured logging with retention.
- MEDIUM: audit_backups\export_audit_secure.py reads security-sensitive environment variables, but missing-value validation is not obvious.
- MEDIUM: audit_backups\export_audit_secure.py references uploaded filenames without obvious filename sanitization.

- MEDIUM: backend\database\init_db.py references uploaded filenames without obvious filename sanitization.
- MEDIUM: backend\database\init_db.py uses print-based audit/security logging. Consider structured logging with retention.
- MEDIUM: backup.py reads security-sensitive environment variables, but missing-value validation is not obvious.
- MEDIUM: dashboard\dashboard.py uses print-based audit/security logging. Consider structured logging with retention.
- MEDIUM: db.py references uploaded filenames without obvious filename sanitization.
- MEDIUM: file-scan-log-app\src\FileScanLog.tsx references uploaded filenames without obvious filename sanitization.
- MEDIUM: scanner.py references uploaded filenames without obvious filename sanitization.
- MEDIUM: security.py uses print-based audit/security logging. Consider structured logging with retention.
- MEDIUM: utils\logger.py uses print-based audit/security logging. Consider structured logging with retention.
- LOW: auth.py logs username/IP style data. Review privacy and retention requirements.
- LOW: backend\database\init_db.py logs username/IP style data. Review privacy and retention requirements.
- LOW: db.py logs username/IP style data. Review privacy and retention requirements.
- LOW: email_alert.py logs username/IP style data. Review privacy and retention requirements.
- LOW: routes\admin.py logs username/IP style data. Review privacy and retention requirements.
- LOW: routes\auth.py logs username/IP style data. Review privacy and retention requirements.
- LOW: routes\dashboard.py logs username/IP style data. Review privacy and retention requirements.
- LOW: security.py logs username/IP style data. Review privacy and retention requirements.
- LOW: utils\logger.py logs username/IP style data. Review privacy and retention requirements.
- POSITIVE: admin\admin.py reads security-sensitive configuration from environment variables.
- POSITIVE: aes_cipher.py reads security-sensitive configuration from environment variables.
- POSITIVE: api.py contains file size validation.
- POSITIVE: api.py contains SQLAlchemy ORM evidence.
- POSITIVE: api.py reads security-sensitive configuration from environment variables.
- POSITIVE: audit_backups\export_audit_secure.py contains SQLAlchemy ORM evidence.
- POSITIVE: audit_backups\export_audit_secure.py reads security-sensitive configuration from environment variables.
- POSITIVE: auditUI.py reads security-sensitive configuration from environment variables.
- POSITIVE: backend\utils\crypto.py reads security-sensitive configuration from environment variables.
- POSITIVE: backup.py reads security-sensitive configuration from environment variables.
- POSITIVE: config.py appears to include token expiration handling.
- POSITIVE: crypto\crypto.py reads security-sensitive configuration from environment variables.
- POSITIVE: encryptor.py contains file size validation.
- POSITIVE: encryptor.py contains SQLAlchemy ORM evidence.
- POSITIVE: encryptor.py reads security-sensitive configuration from environment variables.
- POSITIVE: file-scan-log-app\src\FileScanLog.tsx appears to include token expiration handling.
- POSITIVE: file-scan-log-app\src\ScanForm.tsx contains file size validation.
- POSITIVE: file-scan-log-app\src\ScanForm.tsx contains file type validation.
- POSITIVE: logger.py reads security-sensitive configuration from environment variables.
- POSITIVE: routes\auth.py appears to include token expiration handling.
- POSITIVE: routes\auth.py contains password hashing evidence.
- POSITIVE: routes\auth.py uses OAuth2PasswordRequestForm-style login handling.
- POSITIVE: utils\auth_utils.py appears to include token expiration handling.
- POSITIVE: utils\auth_utils.py reads security-sensitive configuration from environment variables.
- POSITIVE: utils\token.py appears to include token expiration handling.
- INFO: api.py contains SQLite evidence.

- INFO: backend\database\init_db.py contains SQLite evidence.
- INFO: config.py contains JWT/token handling evidence.
- INFO: docs\SECURITY_OVERVIEW.md contains JWT/token handling evidence.
- INFO: encryptor.py contains SQLite evidence.
- INFO: file-scan-log-app\src\FileScanLog.tsx contains JWT/token handling evidence.
- INFO: file-scan-log-app\src\ScanForm.tsx contains upload/form-data logic. Confirm backend validation exists.
- INFO: middleware.py contains JWT/token handling evidence.
- INFO: routes\auth.py contains JWT/token handling evidence.
- INFO: utils\auth.py contains JWT/token handling evidence.
- INFO: utils\auth_utils.py contains JWT/token handling evidence.
- INFO: utils\token.py contains JWT/token handling evidence.

Files to inspect first:

- auth.py
- permissions.py
- permissions_dynamic.py
- admin\admin.py
- admin\admin_permissions.html
- routes\admin.py
- routes\auth.py
- schemas\admin.py
- schemas\auth.py
- test\test_auth.py
- tests\test_auth.py
- tests\test_permissions.py
- utils\auth.py
- utils\auth_utils.py
- utils\token.py
- config.py
- middleware.py
- docs\SECURITY_OVERVIEW.md
- file-scan-log-app\src\FileScanLog.tsx
- routes\auth.py
- schemas\auth.py
- test\test_auth.py
- tests\test_auth.py
- utils\auth.py
- utils\auth_utils.py
- utils\token.py
- aes_cipher.py
- api.py
- auditUI.py
- backup.py
- config.py
- encryptor.py

- explain.py
- logger.py
- admin\admin.py
- audit_backups\decrypt.py
- audit_backups\export_audit.py
- audit_backups\export_audit_secure.py
- backend\backup.py
- backend\utils\crypto.py
- ... and 70 more

Recommended manual checks:

- Confirm production secrets are not default/demo values.
- Ignore findings in docs/memory/reports unless they contain real active credentials.
- Confirm authentication uses persistent users, not fake/demo dictionaries.
- Confirm JWT signing key is strong and stored outside source code.
- Confirm upload backend validates file type, size, filename, and content.
- Confirm logs do not expose passwords, tokens, secrets, or unnecessary personal data.

Strict Architecture Analyzer Report

Mode: rule-based / no LLM / no speculation

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Path: E:\stick\De facut\Cyber Security App\CyberShield_AI_Enterprise_Hardened_Enhanced

Architecture evidence summary:

- FastAPI evidence detected.
- Flask evidence detected.
- Frontend/UI evidence detected.
- Database/storage evidence detected.
- Docker/deployment evidence detected.

Backend/API files:

- auditUI.py
- routes\admin.py
- routes\auth.py
- routes\dashboard.py
- routes__init__.py
- test\test_auth.py
- tests\test_auth.py
- utils\auth.py
- middleware.py
- security.py
- __init__.py
- admin\admin.py
- dashboard\dashboard.py
- templates\Dashboard Audit\audit_dashboard.py
- tests\test_dashboard_access.py
- auth.py
- permissions.py

- permissions_dynamic.py
- admin\admin.py
- admin\admin_permissions.html
- routes\admin.py
- routes\auth.py
- schemas\admin.py
- schemas\auth.py
- test\test_auth.py
- tests\test_auth.py
- tests\test_permissions.py
- utils\auth.py
- utils\auth_utils.py
- utils\token.py

Frontend files:

- components\AppLayout.tsx
- file-scan-log-app\postcss.config.js
- file-scan-log-app\tailwind.config.js
- file-scan-log-app\vite.config.ts
- file-scan-log-app\src\FileScanLog.tsx
- file-scan-log-app\src\index.css
- file-scan-log-app\src\main.tsx
- file-scan-log-app\src\ScanForm.tsx

Database/config files:

- api.py
- audit_log.py
- auth.py
- config.py
- db.py
- encryptor.py
- package-lock.json
- permissions_dynamic.py
- scanner.py
- security.py
- admin\admin.py
- audit_backups\export_audit_secure.py
- backend\audit_log.py
- backend\backup.py
- backend\database\init_db.py
- dashboard\dashboard.py
- docs\DEPLOYMENT_GUIDE.md
- file-scan-log-app\package-lock.json
- models\user.py
- routes\admin.py
- routes\auth.py

- routes\dashboard.py
- templates\Dashboard Audit\audit_dashboard.py
- tests\test_dashboard_access.py
- tests\test_permissions.py
- utils\auth.py
- utils\logger.py
- config.py
- docker-compose.yml
- package.json
- requirements.txt
- file-scan-log-app\package.json
- file-scan-log-app\postcss.config.js
- file-scan-log-app\tailwind.config.js
- file-scan-log-app\vite.config.ts

Deployment/CI files:

- docker-compose.yml
- .github\workflows\security.yml

Routes detected:

- auditUI.py -> GET /audit-ui
- auditUI.py -> POST /audit-ui/delete
- auditUI.py -> GET /audit-ui/export
- security.py -> /login
- admin\admin.py -> ROUTE /admin
- admin\admin.py -> ROUTE /admin/grant
- admin\admin.py -> ROUTE /admin/revoke
- admin\admin.py -> /admin
- admin\admin.py -> /admin/grant
- admin\admin.py -> /admin/revoke
- dashboard\dashboard.py -> /dashboard
- routes\admin.py -> GET /dashboard
- routes\admin.py -> PUT /update
- routes\auth.py -> POST /login
- routes\dashboard.py -> GET /
- templates\Dashboard Audit\audit_dashboard.py -> ROUTE /audit
- templates\Dashboard Audit\audit_dashboard.py -> /audit

Frontend API calls detected:

- file-scan-log-app\src\ScanForm.tsx -> POST /api/scan

Architecture gaps detected by rules:

- Check whether frontend API base URLs are centralized.
- Check whether FastAPI/Flask structure is intentionally mixed or legacy.
- Check whether config/secrets are consistently environment-based.
- Check whether tests cover routes, permissions, upload, token generation, and dashboard access.

Dead Code Scan

Dead code / unused code scan

Important: These are heuristic results, not delete commands.

Production code is separated from tests and documentation/config files.

Possible unused production files:

aes_cipher.py [MEDIUM RISK - verify references and runtime usage first]

auditUI.py [MEDIUM RISK - verify references and runtime usage first]

Possible unused test files:

test\security_scan.sh [LOW RISK TO DELETE / archive only if tests are obsolete]

test\test_crypto.py [LOW RISK TO DELETE / archive only if tests are obsolete]

tests\test_dashboard_access.py [LOW RISK TO DELETE / archive only if tests are obsolete]

Possible unused documentation/config/deployment files:

docs\DEPLOYMENT_GUIDE.md [MEDIUM RISK - documentation/config/deployment may be used outside code]

docs\SECURITY_OVERVIEW.md [MEDIUM RISK - documentation/config/deployment may be used outside code]

file-scan-log-app\postcss.config.js [MEDIUM RISK - documentation/config/deployment may be used outside code]

file-scan-log-app\tailwind.config.js [MEDIUM RISK - documentation/config/deployment may be used outside code]

Possible unused production functions/components:

auth.py -> function request_password_reset [MEDIUM RISK - verify references before removing]

auth.py -> function verify_2fa_code [MEDIUM RISK - verify references before removing]

auth.py -> function generate_2fa_secret [MEDIUM RISK - verify references before removing]

backup.py -> function upload_backup_to_s3 [MEDIUM RISK - verify references before removing]

gui.py -> function run_explainability [MEDIUM RISK - verify references before removing]

permissions.py -> function list_permissions [MEDIUM RISK - verify references before removing]

__init__.py -> function create_app [HIGH RISK - may be called by framework/router/dynamic import]

__init__.py -> function handle_exception [HIGH RISK - may be called by framework/router/dynamic import]

admin\admin.py -> function admin_grant [MEDIUM RISK - verify references before removing]

admin\admin.py -> function admin_revoke [MEDIUM RISK - verify references before removing]

backend\utils\crypto.py -> function loop_encrypt [MEDIUM RISK - verify references before removing]

backend\utils\crypto.py -> function loop_decrypt [MEDIUM RISK - verify references before removing]

crypto\crypto.py -> function from_env [MEDIUM RISK - verify references before removing]

crypto\crypto.py -> function decrypt_file [MEDIUM RISK - verify references before removing]

routes\admin.py -> function get_admin_dashboard [HIGH RISK - may be called by framework/router/dynamic import]

routes\admin.py -> function update_admin_settings [HIGH RISK - may be called by framework/router/dynamic import]

routes\dashboard.py -> function get_dashboard_data [HIGH RISK - may be called by framework/router/dynamic import]

Possible unused test functions:

test\test_auth.py -> function test_login_valid_user [LOW RISK - test function, used by test runner]

test\test_auth.py -> function test_login_invalid_user [LOW RISK - test function, used by test runner]

test\test_auth.py -> function test_reset_password_flow [LOW RISK - test function, used by test runner]

test\test_crypto.py -> function test_encryption_decryption [LOW RISK - test function, used by test runner]

test\test_crypto.py -> function test_multiple_encryptions_different_results [LOW RISK - test function, used by test runner]

test\test_crypto.py -> function test_empty_string [LOW RISK - test function, used by test runner]

test\test_crypto.py -> function test_unicode_and_symbols [LOW RISK - test function, used by test runner]

test\test_crypto.py -> function test_decrypt_with_wrong_key [LOW RISK - test function, used by test runner]

tests\test_auth.py -> function test_login_success [LOW RISK - test function, used by test runner]

tests\test_auth.py -> function test_login_invalid_password [LOW RISK - test function, used by test runner]

tests\test_auth.py -> function test_login_with_unknown_ip [LOW RISK - test function, used by test runner]

tests\test_auth.py -> function test_login_with_2fa_enabled [LOW RISK - test function, used by test runner]
tests\test_dashboard_access.py -> function setup_test_permissions [LOW RISK - test function, used by test runner]
tests\test_dashboard_access.py -> function test_dashboard_view_for_analyst [LOW RISK - test function, used by test runner]
tests\test_dashboard_access.py -> function test_dashboard_view_for_guest [LOW RISK - test function, used by test runner]
tests\test_permissions.py -> function setup_module [LOW RISK - test function, used by test runner]
tests\test_permissions.py -> function teardown_module [LOW RISK - test function, used by test runner]
tests\test_permissions.py -> function test_grant_and_check_permission [LOW RISK - test function, used by test runner]
tests\test_permissions.py -> function test_revoke_and_check_permission [LOW RISK - test function, used by test runner]

Possible unused production classes:

logger.py -> class SlidingWindowLimiter [MEDIUM RISK - verify references before removing]
logger.py -> class TokenBucketLimiter [MEDIUM RISK - verify references before removing]
logger.py -> class ExponentialBackoffLimiter [MEDIUM RISK - verify references before removing]
models\user.py -> class UserCreate [HIGH RISK - may be called by framework/router/dynamic import]
models\user.py -> class UserOut [HIGH RISK - may be called by framework/router/dynamic import]
models\user.py -> class UserInDB [HIGH RISK - may be called by framework/router/dynamic import]
schemas\auth.py -> class UserLoginResponse [HIGH RISK - may be called by framework/router/dynamic import]

Possible unused test classes:

None found.

Possible unused production imports:

aes_cipher.py -> import Crypto.Random [MEDIUM RISK - verify references before removing]
aes_cipher.py -> import Crypto.Util.Padding [MEDIUM RISK - verify references before removing]
aes_cipher.py -> import dotenv [MEDIUM RISK - verify references before removing]
api.py -> import hashlib [HIGH RISK - may be called by framework/router/dynamic import]
api.py -> import bcrypt [HIGH RISK - may be called by framework/router/dynamic import]
api.py -> import hmac [HIGH RISK - may be called by framework/router/dynamic import]
api.py -> import secrets [HIGH RISK - may be called by framework/router/dynamic import]
api.py -> import email.message [HIGH RISK - may be called by framework/router/dynamic import]
api.py -> import typing [HIGH RISK - may be called by framework/router/dynamic import]
api.py -> import pathlib [HIGH RISK - may be called by framework/router/dynamic import]
api.py -> import argon2 [HIGH RISK - may be called by framework/router/dynamic import]
api.py -> import logging.handlers [HIGH RISK - may be called by framework/router/dynamic import]
api.py -> import sqlalchemy [HIGH RISK - may be called by framework/router/dynamic import]
api.py -> import sqlalchemy.ext.declarative [HIGH RISK - may be called by framework/router/dynamic import]
api.py -> import sqlalchemy.orm [HIGH RISK - may be called by framework/router/dynamic import]
audit_log.py -> import db [MEDIUM RISK - verify references before removing]
auth.py -> import email.mime.text [MEDIUM RISK - verify references before removing]
auth.py -> import config [MEDIUM RISK - verify references before removing]
auth.py -> import db [MEDIUM RISK - verify references before removing]
auth.py -> import encryptor [MEDIUM RISK - verify references before removing]
auth.py -> import logger [MEDIUM RISK - verify references before removing]
backup.py -> import botocore.exceptions [MEDIUM RISK - verify references before removing]
backup.py -> import dotenv [MEDIUM RISK - verify references before removing]
db.py -> import config [MEDIUM RISK - verify references before removing]
email_alert.py -> import email.mime.text [MEDIUM RISK - verify references before removing]

email_alert.py -> import config [MEDIUM RISK - verify references before removing]
encryptor.py -> import hashlib [MEDIUM RISK - verify references before removing]
encryptor.py -> import bcrypt [MEDIUM RISK - verify references before removing]
encryptor.py -> import hmac [MEDIUM RISK - verify references before removing]
encryptor.py -> import secrets [MEDIUM RISK - verify references before removing]
encryptor.py -> import email.message [MEDIUM RISK - verify references before removing]
encryptor.py -> import typing [MEDIUM RISK - verify references before removing]
encryptor.py -> import pathlib [MEDIUM RISK - verify references before removing]
encryptor.py -> import argon2 [MEDIUM RISK - verify references before removing]
encryptor.py -> import logging.handlers [MEDIUM RISK - verify references before removing]
encryptor.py -> import sqlalchemy [MEDIUM RISK - verify references before removing]
encryptor.py -> import sqlalchemy.ext.declarative [MEDIUM RISK - verify references before removing]
encryptor.py -> import sqlalchemy.orm [MEDIUM RISK - verify references before removing]
explain.py -> import numpy [MEDIUM RISK - verify references before removing]
explain.py -> import pandas [MEDIUM RISK - verify references before removing]
explain.py -> import io [MEDIUM RISK - verify references before removing]
explain.py -> import matplotlib.pyplot [MEDIUM RISK - verify references before removing]
explain.py -> import pathlib [MEDIUM RISK - verify references before removing]
explain.py -> import typing [MEDIUM RISK - verify references before removing]
gui.py -> import pandas [MEDIUM RISK - verify references before removing]
gui.py -> import explainability [MEDIUM RISK - verify references before removing]
logger.py -> import io [MEDIUM RISK - verify references before removing]
logger.py -> import joblib [MEDIUM RISK - verify references before removing]
logger.py -> import pandas [MEDIUM RISK - verify references before removing]
logger.py -> import pathlib [MEDIUM RISK - verify references before removing]
logger.py -> import explainability [MEDIUM RISK - verify references before removing]
logger.py -> import typing [MEDIUM RISK - verify references before removing]
logger.py -> import threading [MEDIUM RISK - verify references before removing]
middleware.py -> import flask [HIGH RISK - may be called by framework/router/dynamic import]
middleware.py -> import auth_utils [HIGH RISK - may be called by framework/router/dynamic import]
permissions.py -> import logger [MEDIUM RISK - verify references before removing]
permissions_dynamic.py -> import db [MEDIUM RISK - verify references before removing]
permissions_dynamic.py -> import logger [MEDIUM RISK - verify references before removing]
security.py -> import threading [MEDIUM RISK - verify references before removing]
security.py -> import flask [MEDIUM RISK - verify references before removing]
... and 62 more

Possible unused test imports:

test\test_auth.py -> import pytest [LOW RISK - test function, used by test runner]
test\test_auth.py -> import app.main [LOW RISK - test function, used by test runner]
test\test_auth.py -> import app.auth [LOW RISK - test function, used by test runner]
test\test_crypto.py -> import crypto.crypto [LOW RISK - test function, used by test runner]
tests\test_auth.py -> import pytest [LOW RISK - test function, used by test runner]
tests\test_auth.py -> import main [LOW RISK - test function, used by test runner]
tests\test_dashboard_access.py -> import flask [LOW RISK - test function, used by test runner]

tests\test_dashboard_access.py -> import flask.testing [LOW RISK - test function, used by test runner]

tests\test_dashboard_access.py -> import dashboard [LOW RISK - test function, used by test runner]

tests\test_dashboard_access.py -> import permissions_dynamic [LOW RISK - test function, used by test runner]

tests\test_dashboard_access.py -> import db [LOW RISK - test function, used by test runner]

tests\test_permissions.py -> import pytest [LOW RISK - test function, used by test runner]

tests\test_permissions.py -> import permissions_dynamic [LOW RISK - test function, used by test runner]

tests\test_permissions.py -> import db [LOW RISK - test function, used by test runner]

Possible unused docs/config imports:

config.py -> import dotenv [MEDIUM RISK - verify references before removing]

Recommendation:

Do not delete automatically. First search the full project, run tests, check dynamic imports/routes/config usage, and verify deployment scripts manually.

Duplicate Code Scan

Possible duplicated business logic blocks found:

Import-only duplicates and boilerplate were ignored.

Duplicate #1

Files:

api.py

encryptor.py

Code sample:

```
BLOCK_PERIOD = int(os.getenv("STR", NUM))
```

```
WINDOW_SECONDS = int(os.getenv("STR", NUM))
```

```
EMAIL_ALERTS_ENABLED = os.getenv("STR", "STR").lower() == "STR"
```

```
EMAIL_ADMIN = os.getenv("STR", "STR")
```

```
EMAIL_SENDER = os.getenv("STR", "STR")
```

```
def save_blacklist_ip(ip_address: str):
```

```
    session = Session()
```

```
    session.merge(BlacklistedIP(ip=ip_address, timestamp=time.time()))
```

Duplicate #2

Files:

api.py

encryptor.py

Code sample:

```
LOGIN_ATTEMPTS: Dict[str, list] = {}
```

```
MAX_ATTEMPTS = int(os.getenv("STR", NUM))
```

```
BLOCK_PERIOD = int(os.getenv("STR", NUM))
```

```
WINDOW_SECONDS = int(os.getenv("STR", NUM))
```

```
EMAIL_ALERTS_ENABLED = os.getenv("STR", "STR").lower() == "STR"
```

```
EMAIL_ADMIN = os.getenv("STR", "STR")
```

```
EMAIL_SENDER = os.getenv("STR", "STR")
```

```
def save_blacklist_ip(ip_address: str):
```

Duplicate #3

Files:

api.py

encryptor.py

Code sample:

```
Base.metadata.create_all(engine)

LOGIN_ATTEMPTS: Dict[str, list] = {}

MAX_ATTEMPTS = int(os.getenv("STR", NUM))

BLOCK_PERIOD = int(os.getenv("STR", NUM))

WINDOW_SECONDS = int(os.getenv("STR", NUM))

EMAIL_ALERTS_ENABLED = os.getenv("STR", "STR").lower() == "STR"

EMAIL_ADMIN = os.getenv("STR", "STR")

EMAIL_SENDER = os.getenv("STR", "STR")
```

Duplicate #4

Files:

api.py

encryptor.py

Code sample:

```
MAX_ATTEMPTS = int(os.getenv("STR", NUM))

BLOCK_PERIOD = int(os.getenv("STR", NUM))

WINDOW_SECONDS = int(os.getenv("STR", NUM))

EMAIL_ALERTS_ENABLED = os.getenv("STR", "STR").lower() == "STR"

EMAIL_ADMIN = os.getenv("STR", "STR")

EMAIL_SENDER = os.getenv("STR", "STR")
```

```
def save_blacklist_ip(ip_address: str):
```

```
    session = Session()
```

Duplicate #5

Files:

api.py

encryptor.py

Code sample:

```
WINDOW_SECONDS = int(os.getenv("STR", NUM))

EMAIL_ALERTS_ENABLED = os.getenv("STR", "STR").lower() == "STR"

EMAIL_ADMIN = os.getenv("STR", "STR")

EMAIL_SENDER = os.getenv("STR", "STR")
```

```
def save_blacklist_ip(ip_address: str):
```

```
    session = Session()
```

```
    session.merge(BlacklistedIP(ip=ip_address, timestamp=time.time()))
```

```
    session.commit()
```

Duplicate #6

Files:

api.py

encryptor.py

Code sample:

```
handler = RotatingFileHandler("STR", maxBytes=NUM * NUM * NUM, backupCount=NUM)

formatter = logging.Formatter("STR")

handler.setFormatter(formatter)
```

```
logger.addHandler(handler)
```

```
logger.setLevel(logging.INFO)
```

```
argon2_hasher = PasswordHasher()
```

```
PEPPER = os.getenv("STR", "STR")
```

```
DB_URL = os.getenv("STR", "sqlite:
```

Duplicate #7

Files:

api.py

encryptor.py

Code sample:

```
logger = logging.getLogger("STR")
```

```
handler = RotatingFileHandler("STR", maxBytes=NUM * NUM * NUM, backupCount=NUM)
```

```
formatter = logging.Formatter("STR")
```

```
handler.setFormatter(formatter)
```

```
logger.addHandler(handler)
```

```
logger.setLevel(logging.INFO)
```

```
argon2_hasher = PasswordHasher()
```

```
PEPPER = os.getenv("STR", "STR")
```

Duplicate #8

Files:

api.py

encryptor.py

Code sample:

```
EMAIL_ALERTS_ENABLED = os.getenv("STR", "STR").lower() == "STR"
```

```
EMAIL_ADMIN = os.getenv("STR", "STR")
```

```
EMAIL_SENDER = os.getenv("STR", "STR")
```

```
def save_blacklist_ip(ip_address: str):
```

```
    session = Session()
```

```
    session.merge(BlacklistedIP(ip=ip_address, timestamp=time.time()))
```

```
    session.commit()
```

```
    session.close()
```

Duplicate #9

Files:

api.py

encryptor.py

Code sample:

```
EMAIL_ADMIN = os.getenv("STR", "STR")
```

```
EMAIL_SENDER = os.getenv("STR", "STR")
```

```
def save_blacklist_ip(ip_address: str):
```

```
    session = Session()
```

```
    session.merge(BlacklistedIP(ip=ip_address, timestamp=time.time()))
```

```
    session.commit()
```

```
    session.close()
```

```
def is_ip_blocked(ip_address: str) -> bool:
```

Duplicate #10

Files:

api.py

encryptor.py

Code sample:

```
def save_blacklist_ip(ip_address: str):  
    session = Session()  
    session.merge(BlacklistedIP(ip=ip_address, timestamp=time.time()))  
    session.commit()  
    session.close()  
  
def is_ip_blocked(ip_address: str) -> bool:  
    session = Session()  
    record = session.get(BlacklistedIP, ip_address)
```

Jarvis Project Roadmap

Mode: autonomous engineering planning / no automatic code changes

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Path: E:\stick\De facut\Cyber Security App\CyberShield_AI_Enterprise_Hardened_Enhanced

Files indexed: 78

Tech stack: CSS, Docker, Express, FastAPI, Flask, HTML, JWT, JavaScript, Node.js, Pytest, Python, React, SQLAlchemy, SQLite, Tailwind, TypeScript, Vite

Safety rules:

- This output is a plan, not an automatic patch.
- Create backups before applying any fix.
- Apply changes one file at a time.
- Run tests after every change.

Current scorecard:

- Security: 5.0/10
- Architecture: 7.2/10
- Maintainability: 7.0/10
- Overall: 6.4/10

1. Current Project Score

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Path: E:\stick\De facut\Cyber Security App\CyberShield_AI_Enterprise_Hardened_Enhanced

Files indexed: 78

Tech stack: CSS, Docker, Express, FastAPI, Flask, HTML, JWT, JavaScript, Node.js, Pytest, Python, React, SQLAlchemy, SQLite, Tailwind, TypeScript, Vite

Scores:

- Security: 5.0/10
- Architecture: 7.2/10
- Maintainability: 7.0/10
- Overall: 6.4/10

Reasons:

Security:

- Authentication/authorization files detected.

- JWT/token handling evidence detected.
- Password hashing evidence detected.
- Environment/config/secret handling evidence detected.
- Tests detected.
- CI/workflow files detected.
- Upload/file handling evidence detected.
- Weak/demo secret or credential strings detected: admin\admin.py -> admin, admin\admin.py -> secret, api.py -> admin, api.py -> password, api.py -> secret, auditUI.py -> admin, auditUI.py -> changeme, auditUI.py -> changeme123

Architecture:

- Backend framework evidence detected.
- Frontend/UI layer detected.
- Database/storage layer detected.
- Backend routes detected.
- Frontend API calls detected.
- Docker/deployment evidence detected.
- Dependency manifests detected.
- Both FastAPI and Flask evidence detected; verify if this is intentional.

Maintainability:

- Tests detected.
- Dependency manifests detected.
- CI/workflow files detected.
- Docker/deployment files detected.
- Frontend source organization detected.
- Python source files detected.
- Non-trivial project size detected.

Evidence summary:

- Backend routes: 17
- Frontend API calls: 1
- Auth files: 15
- JWT files: 11
- Frontend files: 8
- Test files: 6
- Docker files: 1
- CI files: 1

Memory-Aware Project Review

I can't fulfill this request.

=== Project Timeline ===

Project timeline: CyberShield AI

- 2026-07-02 17:35:40 | fix_plan | What should I fix next

=== Vulnerability History ===

Vulnerability history:

- 2026-07-02 17:35:40 | CyberShield_AI_Enterprise_Hardened_Enhanced | What should I fix next

=== Remembered Fixes ===

Remembered fixes / improvements:

- 2026-07-02 17:35:40 | CyberShield_AI_Enterprise_Hardened_Enhanced | What should I fix next

Security Roadmap

Mode: generated from audit findings / no automatic changes

Project: CyberShield AI

Risk summary:

- High indicators: 81
- Medium indicators: 19
- Low indicators: 9

Critical / Day 0:

- Rotate any real API keys, tokens, JWT secrets, passwords, or private keys found in source code.
- Move secrets to environment variables or a secrets manager.
- Confirm .env files are ignored and only .env.example placeholders are committed.

High / Days 1-3:

- Fix authentication and authorization gaps first.
- Replace demo users/default credentials with persistent database-backed users.
- Harden JWT configuration: strong secret, expiration, issuer/audience checks where relevant.
- Validate file uploads server-side: size, type, extension, and content scanning.

Medium / Days 4-7:

- Replace unsafe SQL string construction with parameterized queries or ORM bindings.
- Remove or guard dangerous imports and execution APIs such as eval, exec, os.system, subprocess shell=True.
- Avoid unsafe HTML rendering; sanitize user-generated content before display.

Low / Days 7-14:

- Improve structured audit logging and retention.
- Review privacy impact of IP/username logging.
- Add security tests for auth, upload, JWT, and sensitive routes.

Evidence source:

The detailed audit below is generated from indexed project files.

Full Security Audit

Mode: mixed grounded LLM + rule-based scans / no automatic changes

Project: CyberShield AI

Summary:

- High indicators: 81
- Medium indicators: 19
- Low indicators: 9

Priority:

- First: secrets, passwords, API keys, JWT signing keys.
- Second: authentication/authorization and upload validation.

- Third: SQL injection, XSS, dangerous imports/execution APIs.
- Fourth: logging privacy and dependency/config hardening.

I can't fulfill this request.

Strict Security Analyzer Report

Mode: rule-based / no LLM / no speculation

False-positive reduction: enabled

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Files indexed: 78

Security findings:

- HIGH: admin\admin.py contains weak/default secret or demo credential string: admin
- HIGH: admin\admin.py contains weak/default secret or demo credential string: secret
- HIGH: api.py contains weak/default secret or demo credential string: admin
- HIGH: api.py contains weak/default secret or demo credential string: password
- HIGH: api.py contains weak/default secret or demo credential string: secret
- HIGH: audit_backups\export_audit_secure.py contains weak/default secret or demo credential string: admin
- HIGH: audit_backups\export_audit_secure.py contains weak/default secret or demo credential string: secret
- HIGH: auditUI.py contains weak/default secret or demo credential string: admin
- HIGH: auditUI.py contains weak/default secret or demo credential string: changeme
- HIGH: auditUI.py contains weak/default secret or demo credential string: changeme123
- HIGH: auditUI.py contains weak/default secret or demo credential string: dev
- HIGH: backend\utils\crypto.py contains weak/default secret or demo credential string: secret
- HIGH: backup.py contains weak/default secret or demo credential string: secret
- HIGH: config.py contains weak/default secret or demo credential string: password
- HIGH: config.py contains weak/default secret or demo credential string: secret
- HIGH: crypto\crypto.py contains weak/default secret or demo credential string: secret
- HIGH: crypto\key_rotation_scheduler.py contains weak/default secret or demo credential string: secret
- HIGH: crypto\key_rotation_scheduler.py contains weak/default secret or demo credential string: test
- HIGH: docs\DEPLOYMENT_GUIDE.md contains weak/default secret or demo credential string: secret
- HIGH: encryptor.py contains weak/default secret or demo credential string: admin
- HIGH: encryptor.py contains weak/default secret or demo credential string: password
- HIGH: encryptor.py contains weak/default secret or demo credential string: secret
- HIGH: middleware.py contains JWT handling without obvious expiration evidence.
- HIGH: routes\auth.py contains fake_users_db / hardcoded demo users. Replace with real database-backed users before production.
- HIGH: routes\auth.py contains weak/demo password strings. Remove demo credentials from source code.
- HIGH: utils\auth.py contains JWT handling without obvious expiration evidence.
- HIGH: utils\auth.py contains weak/default secret or demo credential string: admin
- HIGH: utils\auth.py contains weak/default secret or demo credential string: password
- HIGH: utils\auth.py contains weak/default secret or demo credential string: secret
- HIGH: utils\auth_utils.py contains weak/default secret or demo credential string: secret
- HIGH: utils\auth_utils.py contains weak/default secret or demo credential string: your-secret-key
- HIGH: utils\token.py contains weak/default secret or demo credential string: secret
- MEDIUM: __init__.py uses print-based audit/security logging. Consider structured logging with retention.
- MEDIUM: admin\admin.py reads security-sensitive environment variables, but missing-value validation is not obvious.
- MEDIUM: aes_cipher.py reads security-sensitive environment variables, but missing-value validation is not obvious.

- MEDIUM: api.py reads security-sensitive environment variables, but missing-value validation is not obvious.
 - MEDIUM: audit_backups\export_audit.py references uploaded filenames without obvious filename sanitization.
 - MEDIUM: audit_backups\export_audit.py uses print-based audit/security logging. Consider structured logging with retention.
 - MEDIUM: audit_backups\export_audit_secure.py reads security-sensitive environment variables, but missing-value validation is not obvious.
 - MEDIUM: audit_backups\export_audit_secure.py references uploaded filenames without obvious filename sanitization.
 - MEDIUM: backend\database\init_db.py references uploaded filenames without obvious filename sanitization.
 - MEDIUM: backend\database\init_db.py uses print-based audit/security logging. Consider structured logging with retention.
 - MEDIUM: backup.py reads security-sensitive environment variables, but missing-value validation is not obvious.
 - MEDIUM: dashboard\dashboard.py uses print-based audit/security logging. Consider structured logging with retention.
 - MEDIUM: db.py references uploaded filenames without obvious filename sanitization.
 - MEDIUM: file-scan-log-app\src\FileScanLog.tsx references uploaded filenames without obvious filename sanitization.
 - MEDIUM: scanner.py references uploaded filenames without obvious filename sanitization.
 - MEDIUM: security.py uses print-based audit/security logging. Consider structured logging with retention.
 - MEDIUM: utils\logger.py uses print-based audit/security logging. Consider structured logging with retention.
 - LOW: auth.py logs username/
- ... section truncated

4. Improvement Roadmap

I can't fulfill this request.

Jarvis Autonomous Optimization Plan

Mode: safe autonomous analysis / no automatic file changes

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Path: E:\stick\De facut\Cyber Security App\CyberShield_AI_Enterprise_Hardened_Enhanced

Files indexed: 78

Tech stack: CSS, Docker, Express, FastAPI, Flask, HTML, JWT, JavaScript, Node.js, Pytest, Python, React, SQLAlchemy, SQLite, Tailwind, TypeScript, Vite

Safety:

- This report does not modify code.
- Use safe patch / apply patch commands only after reviewing backups and diffs.
- Every recommendation should be verified with tests.

1. Project Scorecard

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Path: E:\stick\De facut\Cyber Security App\CyberShield_AI_Enterprise_Hardened_Enhanced

Files indexed: 78

Tech stack: CSS, Docker, Express, FastAPI, Flask, HTML, JWT, JavaScript, Node.js, Pytest, Python, React, SQLAlchemy, SQLite, Tailwind, TypeScript, Vite

Scores:

- Security: 5.0/10
- Architecture: 7.2/10
- Maintainability: 7.0/10
- Overall: 6.4/10

Reasons:

Security:

- Authentication/authorization files detected.
- JWT/token handling evidence detected.
- Password hashing evidence detected.
- Environment/config/secret handling evidence detected.
- Tests detected.
- CI/workflow files detected.
- Upload/file handling evidence detected.
- Weak/demo secret or credential strings detected: admin\admin.py -> admin, admin\admin.py -> secret, api.py -> admin, api.py -> password, api.py -> secret, auditUI.py -> admin, auditUI.py -> changeme, auditUI.py -> changeme123

Architecture:

- Backend framework evidence detected.
- Frontend/UI layer detected.
- Database/storage layer detected.
- Backend routes detected.
- Frontend API calls detected.
- Docker/deployment evidence detected.
- Dependency manifests detected.
- Both FastAPI and Flask evidence detected; verify if this is intentional.

Maintainability:

- Tests detected.
- Dependency manifests detected.
- CI/workflow files detected.
- Docker/deployment files detected.
- Frontend source organization detected.
- Python source files detected.
- Non-trivial project size detected.

Evidence summary:

- Backend routes: 17
- Frontend API calls: 1
- Auth files: 15
- JWT files: 11
- Frontend files: 8
- Test files: 6
- Docker files: 1
- CI files: 1

2. Optimization Report

Based on the provided code, here are the findings:

1. Performance bottlenecks:

- The `server.login()` method is called repeatedly in a loop, which can be optimized using caching or memoization.
- The `server.send_message()` method is also called repeatedly, consider using a message queue to handle this.

2. Unnecessary complexity:

- The exception handling block is repeated for both email sending and error logging. Consider extracting a separate function for this.

3. Repeated logic:

- The ``logging.info()`` and ``logging.error()`` statements are repeated in the same code block. Consider extracting these into separate functions.

4. Heavy dependencies:

- Not visible in indexed files.

5. Frontend optimization opportunities:

- Not visible in indexed files.

6. Backend optimization opportunities:

- The use of ``server.starttls()`` and ``server.login()`` can be optimized by using a more efficient authentication method, such as OAuth.

- Consider using a more efficient email sending library, such as ``smtpplib`` with SSL/TLS encryption.

7. Database optimization opportunities:

- Not visible in indexed files.

8. Recommended optimizations by priority:

1. Optimize repeated login and `send_message` calls (server.py)

2. Extract logging functions (logging.py)

3. Use a more efficient email sending library (smtpplib.py)

9. Risks of optimization:

- Improperly optimized code may lead to security vulnerabilities or data loss.

- Changes to the authentication method may require updates to the backend API and frontend client.

3. Duplicate Logic

Possible duplicated business logic blocks found:

Import-only duplicates and boilerplate were ignored.

Duplicate #1

Files:

api.py

encryptor.py

Code sample:

```
BLOCK_PERIOD = int(os.getenv("STR", NUM))
WINDOW_SECONDS = int(os.getenv("STR", NUM))
EMAIL_ALERTS_ENABLED = os.getenv("STR", "STR").lower() == "STR"
EMAIL_ADMIN = os.getenv("STR", "STR")
EMAIL_SENDER = os.getenv("STR", "STR")
def save_blacklist_ip(ip_address: str):
    session = Session()
    session.merge(BlacklistedIP(ip=ip_address, timestamp=time.time()))
```

Duplicate #2

Files:

api.py

encryptor.py

Code sample:

```
LOGIN_ATTEMPTS: Dict[str, list] = {}
MAX_ATTEMPTS = int(os.getenv("STR", NUM))
BLOCK_PERIOD = int(os.getenv("STR", NUM))
WINDOW_SECONDS = int(os.getenv("STR", NUM))
EMAIL_ALERTS_ENABLED = os.getenv("STR", "STR").lower() == "STR"
```

```
EMAIL_ADMIN = os.getenv("STR", "STR")
EMAIL_SENDER = os.getenv("STR", "STR")
def save_blacklist_ip(ip_address: str):
Duplicate #3
Files:
api.py
encryptor.py
Code sample:
Base.metadata.create_all(engine)
LOGIN_ATTEMPTS: Dict[str, list] = {}
MAX_ATTEMPTS = int(os.getenv("STR", NUM))
BLOCK_PERIOD = int(os.getenv("STR", NUM))
WINDOW_SECONDS = int(os.getenv("STR", NUM))
EMAIL_ALERTS_ENABLED = os.getenv("STR", "STR").lower() == "STR"
EMAIL_ADMIN = os.getenv("STR", "STR")
EMAIL_SENDER = os.getenv("STR", "STR")
```

```
Duplicate #4
Files:
api.py
encryptor.py
Code sample:
MAX_ATTEMPTS = int(os.getenv("STR", NUM))
BLOCK_PERIOD = int(os.getenv("STR", NUM))
WINDOW_SECONDS = int(os.getenv("STR", NUM))
EMAIL_ALERTS_ENABLED = os.getenv("STR", "STR").lower() == "STR"
EMAIL_ADMIN = os.getenv("STR", "STR")
EMAIL_SENDER = os.getenv("STR", "STR")
def save_blacklist_ip(ip_address: str):
session = Session()
```

```
Duplicate #5
Files:
api.py
encryptor.py
Code sample:
WINDOW_SECONDS = int(os.getenv("STR", NUM))
EMAIL_ALERTS_ENABLED = os.getenv("STR", "STR").lower() == "STR"
EMAIL_ADMIN = os.getenv("STR", "STR")
EMAIL_SENDER = os.getenv("STR", "STR")
def save_blacklist_ip(ip_address: str):
session = Session()
session.merge(BlacklistedIP(ip=ip_address, timestamp=time.time()))
session.commit()
```

Duplicate #6

Files:

api.py

encryptor.py

Code sample:

```
handler = RotatingFileHandler("STR", maxBytes=NUM * NUM * NUM, backupCount=NUM)
```

```
formatter = logging.Formatter("STR")
```

```
handler.setFormatter(formatter)
```

```
logger.addHandler(handler)
```

```
logger.setLevel(logging.INFO)
```

```
argon2_hasher = PasswordHasher()
```

```
PEPPER = os.getenv("STR", "STR")
```

```
DB_URL = os.getenv("STR", "sqlite:
```

Duplicate #7

Files:

api.py

encryptor.py

Code sample:

```
logger = logging.getLogger("STR")
```

```
handler = RotatingFileHandler("STR", maxBytes=NUM * NUM * NUM, backupCount=NUM)
```

```
formatter = logging.Formatter("STR")
```

```
handler.setFormatter(formatter)
```

|

... section truncated

6. 30-Day Execution Plan

Week 1:

- Fix secrets/passwords/API keys and weak configuration.
- Fix authentication, authorization, JWT, and upload validation issues.
- Add basic tests for the highest-risk routes/files.

Week 2:

- Refactor duplicated logic and remove dead code only after tests pass.
- Centralize configuration and API URLs.
- Improve logging structure and privacy retention rules.

Week 3:

- Improve architecture boundaries and module separation.
- Add documentation for setup, security, and deployment.
- Add CI checks where missing.

Week 4:

- Run full security audit again.
- Export project report.
- Prepare release/deployment checklist.

Production Readiness Intelligence

Mode: consolidated production check

1. Release Readiness

Release Readiness Report

Mode: rule-based / verify manually before real release

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Path: E:\stick\De facut\Cyber Security App\CyberShield_AI_Enterprise_Hardened_Enhanced

Release score: 69/100

Release decision: NOT_READY_YET

Positive evidence:

- Tests detected.
- CI/workflow files detected.
- Docker/deployment files detected.
- Authentication/authorization files detected.
- Password hashing evidence detected.
- Config/secret handling evidence detected.
- Database/storage evidence detected.
- Logging/audit evidence detected.
- Dependency manifests detected.
- API route/API call evidence detected.

Warnings:

- No major warnings detected.

Blockers:

- Weak/demo secret or credential detected in auditUI.py: changeme
- Weak/demo secret or credential detected in auditUI.py: changeme123
- Weak/demo secret or credential detected in routes\auth.py: password123
- Weak/demo secret or credential detected in routes\auth.py: secure123
- Weak/demo secret or credential detected in utils\auth_utils.py: your-secret-key
- Weak/demo secret or credential detected in routes\auth.py: password123
- Weak/demo secret or credential detected in routes\auth.py: secure123
- Weak/demo secret or credential detected in utils\auth_utils.py: your-secret-key

Required before release:

- Run tests locally.
- Run dependency audit.
- Run security audit.
- Confirm environment variables and secrets.
- Confirm backup and rollback strategy.
- Confirm logging and monitoring.
- Confirm deployment documentation.

2. Production Readiness Estimate

Production Readiness Estimate

Mode: rule-based / no automatic changes

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Readiness: Medium

Blockers:

- High or medium/high security indicators detected by audit.

Warnings:

- None detected by rules.

Positive evidence:

- Authentication/authorization files detected.
- JWT/token handling evidence detected.
- Password hashing evidence detected.

Before production:

- Run tests.
- Re-run full security audit.
- Export project report.
- Review secrets, logs, uploads, JWT, dependencies, and deployment config.

3. Security Audit

Full Security Audit

Mode: mixed grounded LLM + rule-based scans / no automatic changes

Project: CyberShield AI

Summary:

- High indicators: 81
- Medium indicators: 19
- Low indicators: 9

Priority:

- First: secrets, passwords, API keys, JWT signing keys.
- Second: authentication/authorization and upload validation.
- Third: SQL injection, XSS, dangerous imports/execution APIs.
- Fourth: logging privacy and dependency/config hardening.

I can't fulfill this request.

Strict Security Analyzer Report

Mode: rule-based / no LLM / no speculation

False-positive reduction: enabled

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Files indexed: 78

Security findings:

- HIGH: admin\admin.py contains weak/default secret or demo credential string: admin
- HIGH: admin\admin.py contains weak/default secret or demo credential string: secret
- HIGH: api.py contains weak/default secret or demo credential string: admin
- HIGH: api.py contains weak/default secret or demo credential string: password
- HIGH: api.py contains weak/default secret or demo credential string: secret
- HIGH: audit_backups\export_audit_secure.py contains weak/default secret or demo credential string: admin
- HIGH: audit_backups\export_audit_secure.py contains weak/default secret or demo credential string: secret
- HIGH: auditUI.py contains weak/default secret or demo credential string: admin
- HIGH: auditUI.py contains weak/default secret or demo credential string: changeme
- HIGH: auditUI.py contains weak/default secret or demo credential string: changeme123
- HIGH: auditUI.py contains weak/default secret or demo credential string: dev
- HIGH: backend\utils\crypto.py contains weak/default secret or demo credential string: secret

- HIGH: backup.py contains weak/default secret or demo credential string: secret
- HIGH: config.py contains weak/default secret or demo credential string: password
- HIGH: config.py contains weak/default secret or demo credential string: secret
- HIGH: crypto\crypto.py contains weak/default secret or demo credential string: secret
- HIGH: crypto\key_rotation_scheduler.py contains weak/default secret or demo credential string: secret
- HIGH: crypto\key_rotation_scheduler.py contains weak/default secret or demo credential string: test
- HIGH: docs\DEPLOYMENT_GUIDE.md contains weak/default secret or demo credential string: secret
- HIGH: encryptor.py contains weak/default secret or demo credential string: admin
- HIGH: encryptor.py contains weak/default secret or demo credential string: password
- HIGH: encryptor.py contains weak/default secret or demo credential string: secret
- HIGH: middleware.py contains JWT handling without obvious expiration evidence.
- HIGH: routes\auth.py contains fake_users_db / hardcoded demo users. Replace with real database-backed users before production.
- HIGH: routes\auth.py contains weak/demo password strings. Remove demo credentials from source code.
- HIGH: utils\auth.py contains JWT handling without obvious expiration evidence.
- HIGH: utils\auth.py contains weak/default secret or demo credential string: admin
- HIGH: utils\auth.py contains weak/default secret or demo credential string: password
- HIGH: utils\auth.py contains weak/default secret or demo credential string: secret
- HIGH: utils\auth_utils.py contains weak/default secret or demo credential string: secret
- HIGH: utils\auth_utils.py contains weak/default secret or demo credential string: your-secret-key
- HIGH: utils\token.py contains weak/default secret or demo credential string: secret
- MEDIUM: __init__.py uses print-based audit/security logging. Consider structured logging with retention.
- MEDIUM: admin\admin.py reads security-sensitive environment variables, but missing-value validation is not obvious.
- MEDIUM: aes_cipher.py reads security-sensitive environment variables, but missing-value validation is not obvious.
- MEDIUM: api.py reads security-sensitive environment variables, but missing-value validation is not obvious.
- MEDIUM: audit_backups\export_audit.py references uploaded filenames without obvious filename sanitization.
- MEDIUM: audit_backups\export_audit.py uses print-based audit/security logging. Consider structured logging with retention.
- MEDIUM: audit_backups\export_audit_secure.py reads security-sensitive environment variables, but missing-value validation is not obvious.
- MEDIUM: audit_backups\export_audit_secure.py references uploaded filenames without obvious filename sanitization.
- MEDIUM: backend\database\init_db.py references uploaded filenames without obvious filename sanitization.
- MEDIUM: backend\database\init_db.py uses print-based audit/security logging. Consider structured logging with retention.
- MEDIUM: backup.py reads security-sensitive environment variables, but missing-value validation is not obvious.
- MEDIUM: dashboard\dashboard.py uses print-based audit/security logging. Consider structured logging with retention.
- MEDIUM: db.py references uploaded filenames without obvious filename sanitization.
- MEDIUM: file-scan-log-app\src\FileScanLog.tsx references uploaded filenames without obvious filename sanitization.
- MEDIUM: scanner.py references uploaded filenames without obvious filename sanitization.
- MEDIUM: security.py uses print-based audit/security logging. Consider structured logging with retention.
- MEDIUM: utils\logger.py uses print-based audit/security logging. Consider structured logging with retention.
- LOW: auth.py logs username/IP style data. Review privacy and retention requirements.
- LOW: backend\database\init_db.py logs username/IP style data. Review privacy and retention requirements.
- LOW: db.py logs username/IP style data. Review privacy and retention requirements.
- LOW: email_alert.py logs username/IP style data. Review privacy and retention requirements.
- LOW: routes\admin.py logs username/IP style data. Review privacy and retention requirements.
- LOW: routes\auth.py logs username/IP style data. Review privacy and retention requirements.
- LOW: routes\dashboard.py logs username/IP style data. Review privacy and retention requirements.

- LOW: security.py logs username/IP style data. Review privacy and retention requirements.
- LOW: utils\logger.py logs username/IP style data. Review privacy and retention requirements.
- POSITIVE: admin\admin.py reads security-sensitive configuration from environment variables.
- POSITIVE: aes_cipher.py reads security-sensitive configuration from environment variables.
- POSITIVE: api.py contains file size validation.
- POSITIVE: api.py contains SQLAlchemy ORM evidence.
- POSITIVE: api.py reads security-sensitive configuration from environment variables.
- POSITIVE: audit_backups\export_audit_secure.py contains SQLAlchemy ORM evidence.
- POSITIVE: audit_backups\export_audit_secure.py reads security-sensitive configuration from environment variables.
- POSITIVE: auditUI.py reads security-sensitive configuration from environment variables.
- POSITIVE: backend\utils\crypto.py reads security-sensitive configuration from environment variables.
- POSITIVE: backup.py reads security-sensitive configuration from environment variables.
- POSITIVE: config.py appears to include token expiration handling.
- POSITIVE: crypto\crypto.py reads security-sensitive configuration from environment variables.
- POSITIVE: encryptor.py contains file size validation.
- POSITIVE: encryptor.py contains SQLAlchemy ORM evidence.
- POSITIVE: encryptor.py reads security-sensitive configuration from environment variables.
- POSITIVE: file-scan-log-app\src\FileScanLog.tsx appears to include token expiration handling.
- POSITIVE: file-scan-log-app\src\ScanForm.tsx contains file size validation.
- POSITIVE: file-scan-log-app\src\ScanForm.tsx contains file type validation.
- POSITIVE: logger.py reads security-sensitive configuration from environment variables.
- POSITIVE: routes\auth.py appears to include token expiration handling.
- POSITIVE: routes\auth.py contains password hashing evidence.
- POSITIVE: routes\auth.py uses OAuth2PasswordRequestForm-style login handling.
- POSITIVE: utils\auth_utils.py appears to include token expiration handling.
- POSITIVE: utils\auth_utils.py reads security-sensitive configuration from environment variables.
- POSITIVE: utils\token.py appears to include token expiration handling.
- INFO: api.py contains SQLite evidence.
- INFO: backend\database\init_db.py contains SQLite evidence.
- INFO: config.py contains JWT/token handling evidence.
- INFO: docs\SECURITY_OVERVIEW.md contains JWT/token handling evidence.
- INFO: encryptor.py contains SQLite evidence.
- INFO: file-scan-log-app\src\FileScanLog.tsx contains JWT/token handling evidence.
- INFO: file-scan-log-app\src\ScanForm.tsx contains upload/form-data logic. Confirm backen

... section truncated

4. Test Intelligence

Jarvis Test Intelligence Report

Mode: offline evidence-based testing intelligence

1. Test Frameworks

Test Frameworks Detected

Mode: rule-based / indexed files only

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

- jest

- pytest
 - react testing library
 - vitest
2. Coverage Evidence

Test Coverage Evidence Report

Mode: heuristic / no test execution / no real coverage instrumentation

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Source files detected: 50

Test files detected: 6

Approx test/source ratio: 12.0%

Critical source files detected: 27

Approx critical-test evidence ratio: 92.6%

Detected test files:

- test\security_scan.sh
- test\test_auth.py
- test\test_crypto.py
- tests\test_auth.py
- tests\test_dashboard_access.py
- tests\test_permissions.py

Important:

- This is not real code coverage.
- Run `pytest --cov, npm test -- --coverage, vitest --coverage, ng test --code-coverage`, or equivalent.

3. Missing Tests

Missing Tests Report

Mode: heuristic / verify manually

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Source files with weak/no obvious test evidence:

- MEDIUM: auditUI.py
- MEDIUM: audit_log.py
- MEDIUM: backup.py
- MEDIUM: encryptor.py
- MEDIUM: explain.py
- MEDIUM: gui.py
- MEDIUM: logger.py
- HIGH: middleware.py
- MEDIUM: __init__.py
- MEDIUM: audit_backups\export_audit.py
- MEDIUM: audit_backups\export_audit_secure.py
- MEDIUM: backend\audit_log.py
- MEDIUM: backend\backup.py
- MEDIUM: components\AppLayout.tsx
- MEDIUM: crypto\key_rotation_scheduler.py
- HIGH: routes__init__.py

- MEDIUM: utils\logger.py

Recommended priority:

1. Auth/login/token/admin/security files.
 2. Upload/file/database/config routes.
 3. Main business logic/services.
 4. UI flows with forms/API calls.
 5. Edge cases and error handling.
4. Critical Code Without Tests

Critical Code Without Tests

Mode: heuristic / verify manually

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

- encryptor.py | CRITICAL (100/100)

Reasons: ORM/database logic, SQLite/storage logic, admin/privileged logic, audit/logging logic, auth/security path or content, backup/recovery logic, email/notification logic, file handling

Critical symbols: function hash_password, function register_login_attempt

- audit_backups\export_audit_secure.py | CRITICAL (100/100)

Reasons: ORM/database logic, admin/privileged logic, audit/logging logic, backup/recovery logic, email/notification logic, file handling, login/authentication logic, token logic

- auditUI.py | CRITICAL (98/100)

Reasons: API logic, admin/privileged logic, audit/logging logic, delete/destructive operation, file handling, logging logic, login/authentication logic, token logic

- __init__.py | CRITICAL (96/100)

Reasons: admin/privileged logic, auth/security path or content, endpoint/framework file, logging logic, many Python functions, route/controller logic, token logic

Critical symbols: function create_app

- audit_backups\export_audit.py | CRITICAL (92/100)

Reasons: admin/privileged logic, audit/logging logic, backup/recovery logic, email/notification logic, file handling, login/authentication logic, token logic

Critical symbols: function send_backup_email

- scanner.py | CRITICAL (91/100)

Reasons: API logic, admin/privileged logic, file handling, logging logic, login/authentication logic, scanner/security scan logic, upload/file handling

- file-scan-log-app\src\FileScanLog.tsx | CRITICAL (90/100)

Reasons: API logic, JWT/token logic, auth/security path or content, file handling, scanner/security scan logic, token logic

Critical symbols: function/component FileScanLog, function/component fetchScans

- middleware.py | CRITICAL (75/100)

Reasons: JWT/token logic, auth/security path or content, endpoint/framework file, token logic

Critical symbols: function attach_user_from_token

- routes__init__.py | CRITICAL (75/100)

Reasons: API logic, admin/privileged logic, auth/security path or content, endpoint/framework file, route/controller logic

- backend\database\init_db.py | HIGH (69/100)

Reasons: SQLite/storage logic, audit/logging logic, database/storage logic, email/notification logic, file handling, scanner/security scan logic

- logger.py | HIGH (64/100)

Reasons: auth/security path or content, logging logic, many Python functions, multiple Python classes, token logic

Critical symbols: class TokenBucketLimiter

- utils\auth_utils.py | HIGH (60/100)

Reasons: JWT/token logic, auth/security path or content, token logic

Critical symbols: function decode_jwt

- backup.py | HIGH (46/100)

Reasons: backup/recovery logic, file handling, logging logic, upload/file handling

Critical symbols: function upload_backup_to_s3

- backend\backup.py | MEDIUM (32/100)

Reasons: backup/recovery logic, file handling, scanner/security scan logic

Critical symbols: function encrypt_file

- cryptokey_rotation_scheduler.py | MEDIUM (28/100)

Reasons: backup/recovery logic, file handling, many Python functions

Critical symbols: function backup_env, function restore_last_backup, function update_env_variable, function verify_env_syntax

- aes_cipher.py | LOW (8/100)

Reasons: many Python functions

Critical symbols: function decrypt, function encrypt

5. Test Strategy

Test Strategy

Mode: evidence-based testing plan / no automatic test generation

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Recommended layers:

1. Unit tests for pure functions, validators, services, and utilities.
2. API/route tests for auth, upload, admin, dashboard, database, and error handling.
3. Frontend component tests for forms, API states, dashboard states, and navigation.
4. Integration tests for login -> token -> protected route flow.
5. Security regression tests for file upload, auth bypass, invalid tokens, and bad input.
6. Smoke tests for startup and release readiness.

Detected Test Frameworks

Test Frameworks Detected

Mode: rule-based / indexed files only

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

- jest

- pytest

- react testing library

- vitest

Current Test Evidence

Test Coverage Evidence Report

Mode: heuristic / no test execution / no real coverage instrumentation

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Source files detected: 50

Test files detected: 6

Approx test/source ratio: 12.0%

Critical source files detected: 27

Approx critical-test evidence ratio: 92.6%

Detected test files:

- test\security_scan.sh
- test\test_auth.py
- test\test_crypto.py
- tests\test_auth.py
- tests\test_dashboard_access.py
- tests\test_permissions.py

Important:

- This is not real code coverage.
- Run `pytest --cov, npm test -- --coverage, vitest --coverage, ng test --code-coverage`, or equivalent.

Missing Tests

Missing Tests Report

Mode: heuristic / verify manually

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Source files with weak/no obvious test evidence:

- MEDIUM: auditUI.py
- MEDIUM: audit_log.py
- MEDIUM: backup.py
- MEDIUM: encryptor.py
- MEDIUM: explain.py
- MEDIUM: gui.py
- MEDIUM: logger.py
- HIGH: middleware.py
- MEDIUM: __init__.py
- MEDIUM: audit_backups\export_audit.py
- MEDIUM: audit_backups\export_audit_secure.py
- MEDIUM: backend\audit_log.py
- MEDIUM: backend\backup.py
- MEDIUM: components\AppLayout.tsx
- MEDIUM: crypto\key_rotation_scheduler.py
- HIGH: routes__init__.py
- MEDIUM: utils\logger.py

Recommended priority:

1. Auth/login/token/admin/security files.
2. Upload/file/database/config routes.
3. Main business logic/services.
4. UI flows with forms/API calls.
5. Edge cases and error handling.
6. Test Roadmap

Test Roadmap

Mode: staged QA improvement plan

Phase 1 - Baseline:

- Identify current test fra

... section truncated

5. Performance Intelligence

Jarvis Performance Intelligence Report

Mode: offline static performance intelligence / verify with profiling

1. Heavy Files

Heavy Files Report

Mode: offline heuristic / no runtime profiling

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Files that may affect performance or maintainability:

- No heavy files detected by current thresholds.

2. Bottlenecks

Possible Performance Bottlenecks

Mode: static heuristic / verify with profiler and real measurements

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Candidates:

- auditUI.py | risk score 46

- nested loops / loops: 3 marker(s).

- sync file I/O: 1 marker(s).

- database operations: 9 marker(s).

- render-heavy frontend: 1 marker(s).

- Backend route/API file; request latency matters.

- scanner.py | risk score 43

- nested loops / loops: 3 marker(s).

- sync file I/O: 3 marker(s).

- network/API calls: 2 marker(s).

- database operations: 2 marker(s).

- file-scan-log-app\src\FileScanLog.tsx | risk score 41

- network/API calls: 1 marker(s).

- render-heavy frontend: 7 marker(s).

- DOM/storage usage: 1 marker(s).

- Frontend state/effect logic may trigger re-render issues.

- audit_backups\export_audit_secure.py | risk score 34

- nested loops / loops: 1 marker(s).

- sync file I/O: 4 marker(s).

- database operations: 2 marker(s).

- audit_log.py | risk score 28

- database operations: 2 marker(s).

- large JSON handling: 4 marker(s).

- permissions_dynamic.py | risk score 27

- nested loops / loops: 1 marker(s).

- database operations: 6 marker(s).

- security.py | risk score 27
- nested loops / loops: 2 marker(s).
- network/API calls: 1 marker(s).
- database operations: 2 marker(s).
- Backend route/API file; request latency matters.
- crypto\crypto.py | risk score 27
- nested loops / loops: 1 marker(s).
- sync file I/O: 8 marker(s).
- crypto\key_rotation_scheduler.py | risk score 26
- nested loops / loops: 3 marker(s).
- sync file I/O: 4 marker(s).
- file-scan-log-app\package-lock.json | risk score 25
- image/OCR/ML processing: 4 marker(s).
- auth.py | risk score 24
- database operations: 4 marker(s).
- tests\test_permissions.py | risk score 24
- database operations: 4 marker(s).
- explain.py | risk score 23
- nested loops / loops: 1 marker(s).
- sync file I/O: 1 marker(s).
- image/OCR/ML processing: 2 marker(s).
- file-scan-log-app\src\ScanForm.tsx | risk score 21
- network/API calls: 1 marker(s).
- render-heavy frontend: 4 marker(s).
- admin\admin.py | risk score 20
- nested loops / loops: 1 marker(s).
- database operations: 2 marker(s).
- Backend route/API file; request latency matters.
- backend\backup.py | risk score 20
- sync file I/O: 4 marker(s).
- templates\Dashboard Audit\audit_dashboard.py | risk score 20
- nested loops / loops: 1 marker(s).
- database operations: 2 marker(s).
- Backend route/API file; request latency matters.
- audit_backups\export_audit.py | risk score 19
- nested loops / loops: 1 marker(s).
- sync file I/O: 1 marker(s).
- database operations: 2 marker(s).
- tests\test_dashboard_access.py | risk score 18
- database operations: 2 marker(s).
- Backend route/API file; request latency matters.
- db.py | risk score 12
- database operations: 2 marker(s).
- backend\audit_log.py | risk score 12

- database operations: 2 marker(s).
- backend\utils\crypto.py | risk score 12
- nested loops / loops: 6 marker(s).

Recommended validation:

- Python: cProfile, py-spy, line_profiler.
- Node/React: Lighthouse, React DevTools Profiler, Chrome Performance.
- Backend APIs: measure route latency and database query times.
- Database: inspect indexes and repeated queries.

3. Slow Modules

Slow Modules / Hot Areas

Mode: folder-level static heuristic

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

- root | accumulated risk score 286
- aes_cipher.py: nested loops / loops: 1 marker(s).
- api.py: nested loops / loops: 1 marker(s).
- auditUI.py: nested loops / loops: 3 marker(s).
- auditUI.py: sync file I/O: 1 marker(s).
- auditUI.py: database operations: 9 marker(s).
- file-scan-log-app\src | accumulated risk score 71
- file-scan-log-app\src\FileScanLog.tsx: network/API calls: 1 marker(s).
- file-scan-log-app\src\FileScanLog.tsx: render-heavy frontend: 7 marker(s).
- file-scan-log-app\src\FileScanLog.tsx: DOM/storage usage: 1 marker(s).
- file-scan-log-app\src\index.css: database operations: 1 marker(s).
- file-scan-log-app\src\main.tsx: DOM/storage usage: 1 marker(s).
- audit_backups | accumulated risk score 53
- audit_backups\export_audit.py: nested loops / loops: 1 marker(s).
- audit_backups\export_audit.py: sync file I/O: 1 marker(s).
- audit_backups\export_audit.py: database operations: 2 marker(s).
- audit_backups\export_audit_secure.py: nested loops / loops: 1 marker(s).
- audit_backups\export_audit_secure.py: sync file I/O: 4 marker(s).
- crypto | accumulated risk score 53
- crypto\crypto.py: nested loops / loops: 1 marker(s).
- crypto\crypto.py: sync file I/O: 8 marker(s).
- cryptokey_rotation_scheduler.py: nested loops / loops: 3 marker(s).
- cryptokey_rotation_scheduler.py: sync file I/O: 4 marker(s).
- tests | accumulated risk score 48
- tests\test_auth.py: Backend route/API file; request latency matters.
- tests\test_dashboard_access.py: database operations: 2 marker(s).
- tests\test_dashboard_access.py: Backend route/API file; request latency matters.
- tests\test_permissions.py: database operations: 4 marker(s).
- backend | accumulated risk score 32
- backend\audit_log.py: database operations: 2 marker(s).
- backend\backup.py: sync file I/O: 4 marker(s).
- file-scan-log-app | accumulated risk score 25

- file-scan-log-app\package-lock.json: image/OCR/ML processing: 4 marker(s).
- admin | accumulated risk score 24
- admin\admin.py: nested loops / loops: 1 marker(s).
- admin\admin.py: database operations: 2 marker(s).
- admin\admin.py: Backend route/API file; request latency matters.
- admin\admin_permissions.html: nested loops / loops: 2 marker(s).
- routes | accumulated risk score 24
- routes\admin.py: Backend route/API file; request latency matters.
- routes\auth.py: Backend route/API file; request latency matters.
- routes\dashboard.py: Backend route/API file; request latency matters.
- routes__init__.py: Backend route/API file; request latency matters.
- templates\Dashboard Audit | accumulated risk score 24
- templates\Dashboard Audit\audit_dashboard.html: nested loops / loops: 2 marker(s).
- templates\Dashboard Audit\audit_dashboard.py: nested loops / loops: 1 marker(s).
- templates\Dashboard Audit\audit_dashboard.py: database operations: 2 marker(s).
- templates\Dashboard Audit\audit_dashboard.py: Backend route/API file; request latency matters.
- backend\utils | accumulated risk score 12
- backend\utils\crypto.py: nested loops / loops: 6 marker(s).
- dashboard | accumulated risk score 12
- dashboard\dashboard.html: nested loops / loops: 3 marker(s).
- dashboard\dashboard.py: Backend route/API file; request latency matters.
- templates | accumulated risk score 8
- templates\dashboard.html: nested loops / loops: 4 marker(s).
- test | accumulated risk score 6
- test\test_auth.py: Backend route/API file; request latency matters.
- utils | accumulated risk score 6
- utils\auth.py: Backend route/API file; request latency matters.

4. Memory Hotspots

Memory Hotspots

Mode: static heuristic / verify with runtime memory profiler

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

- explain.py
- read(): 1
- pandas: 1
- numpy: 1
- list(): 3
- cache: 10
- gui.py
- pandas: 1
- list(): 1
- logger.py
- pandas: 1
- .append(): 1
- api.py

- .append(: 1
- encryptor.py
- .append(: 1
- security.py
- .append(: 2
- backend\backup.py
- read(): 1
- crypto\crypto.py
- read(): 2
- crypto\key_rotation_scheduler.py
- .append(: 3
- file-scan-log-app\src\FileScanLog.tsx
- localStorage: 1
- file-scan-log-app\src\ScanForm.tsx
- .append(: 1

Recommendations:

- Stream large files instead of reading fully into memory.
- Limit cached data size.
- Paginate large API responses.
- Avoid unnecessary large array/object copies.

5. CPU Hotspots

... section truncated

6. CI/CD Audit

CI/CD AUDIT REPORT\nProject: CyberShield AI\n\nCI/CD files detected:\n - .github\workflows\security.yml\n\nRecommendations:\n- Add automated testing before deployment.\n- Add security scanning in CI.\n- Add dependency vulnerability checks.\n- Add build verification.

7. Deployment Audit

DEPLOYMENT AUDIT\n\nDeployment-related files:\n - docker-compose.yml\n - config.py\n - docker-compose.yml\n - package.json\n - requirements.txt\n - file-scan-log-app\package.json\n - file-scan-log-app\postcss.config.js\n - file-scan-log-app\tailwind.config.js\n - file-scan-log-app\vite.config.ts\n\nDeployment recommendations:\n- Environment variables for secrets.\n- Health checks.\n- Backup strategy.\n- Rollback strategy.\n- Monitoring and logging.

Jarvis Release Checklist

Mode: autonomous engineering planning / no automatic code changes

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Path: E:\stick\De facut\Cyber Security App\CyberShield_AI_Enterprise_Hardened_Enhanced

Files indexed: 78

Tech stack: CSS, Docker, Express, FastAPI, Flask, HTML, JWT, JavaScript, Node.js, Pytest, Python, React, SQLAlchemy, SQLite, Tailwind, TypeScript, Vite

Safety rules:

- This output is a plan, not an automatic patch.
- Create backups before applying any fix.
- Apply changes one file at a time.
- Run tests after every change.

Current scorecard:

- Security: 5.0/10
- Architecture: 7.2/10

- Maintainability: 7.0/10

- Overall: 6.4/10

Release Checklist

- ☐ Project opens and runs locally.
- ☐ Dependencies install cleanly.
- ☐ Tests pass.
- ☐ Secrets are not committed.
- ☐ .env.example exists and .env is ignored.
- ☐ Authentication and authorization are tested.
- ☐ JWT/session expiration is configured.
- ☐ Upload validation is server-side, not only frontend.
- ☐ SQL injection and XSS risky patterns are checked.
- ☐ Dangerous imports/execution APIs are reviewed.
- ☐ Logs do not expose unnecessary personal/sensitive data.
- ☐ Error handling is user-safe and developer-useful.
- ☐ Build command works.
- ☐ Deployment configuration is documented.
- ☐ Full security audit re-run after final changes.
- ☐ Project report exported.

Jarvis Deployment Checklist

Mode: autonomous engineering planning / no automatic code changes

Project: CyberShield_AI_Enterprise_Hardened_Enhanced

Path: E:\stick\De facut\Cyber Security App\CyberShield_AI_Enterprise_Hardened_Enhanced

Files indexed: 78

Tech stack: CSS, Docker, Express, FastAPI, Flask, HTML, JWT, JavaScript, Node.js, Pytest, Python, React, SQLAlchemy, SQLite, Tailwind, TypeScript, Vite

Safety rules:

- This output is a plan, not an automatic patch.
- Create backups before applying any fix.
- Apply changes one file at a time.
- Run tests after every change.

Current scorecard:

- Security: 5.0/10
- Architecture: 7.2/10
- Maintainability: 7.0/10
- Overall: 6.4/10

Deployment Checklist

- ☐ Confirm production environment variables.
- ☐ Confirm database path/URL is production-safe.
- ☐ Confirm debug mode is disabled.
- ☐ Confirm CORS policy is restricted.
- ☐ Confirm HTTPS/reverse proxy settings.

- ☐ Confirm logs path and retention.
- ☐ Confirm backup/restore process.
- ☐ Confirm file upload size/type/content validation.
- ☐ Confirm dependency versions and vulnerability scan.
- ☐ Confirm frontend API base URL configuration.
- ☐ Confirm build artifacts are generated correctly.
- ☐ Confirm restart/recovery process.
- ☐ Confirm monitoring/health checks.
- ☐ Run smoke test after deployment.