Optimal round-communication lower bound for Hidden Pointer Chasing

Sepehr Assadi, Prantar Ghosh, Bruno Loff, Parth Mittal, Sagnik Mukhopadhyay

doi:10.4230/LIPIcs.CCC.2024.7; CC BY 4.0

Editorial note. Native fixed arXiv v1 author TeX under CC BY 4.0. Counted result: thm:lb-hpc. The complete common lower-bound section is retained so every supporting epsilon-solver argument and cross-reference remains available; the other stated main result is supporting context and is not counted in this record. Appendix input directives are mechanically expanded via original-file spans. Unrelated streaming reduction appendix is omitted.

Allowed standard prerequisites (editorial).

- Set-intersection internal information lower bound. Jayram, Kumar and Sivakumar 2003; author Proposition prop:SI-hard and exact distribution retained
- Standard entropy, mutual information, rectangle property, Chernoff and Pinsker facts. Author information-theory and sampling appendix retained; Cover and Thomas 2006 and cited sources

2.1 k-Cores and Degeneracy in Graph Streams

For any undirected graph $G = (V, E)$ and integer $k \geqslant 1$, a *k-core* in G is a maximal set S of vertices such that the induced subgraph of G on S, denoted by $G[S]$, has a minimum degree of at least k. In other words, any vertex in S has at least k other neighbors in S.

k-Cores provide a natural notion of well-connectedness in massive graphs, and as such, computing k-cores (and more generally k-core decompositions; see, e.g., [LSY+22]) has been widely studied in databases [BGKV14, CZL+20, LZZ+19], social networks [DBS17, DBS18, KBVT15], machine learning [ADBV05, ELM18, GLM19], among others [LWSX18, GBGL20, SGJ+13].

As a result, in recent years, there has been a rapidly growing body of work on computing k-cores on massive graphs in parallel and streaming models of computation [SGJ+13, DBS17, DBS18, ELM18, GLM19, LSY+22]. In particular, [ELM18] presented a single-pass algorithm that for any $\varepsilon > 0$, computes a $(1-\varepsilon)$-approximation of every k-core in G (i.e., obtains a $(1-\varepsilon)$-approximate k-core decomposition) in $\widetilde{O}(n/\varepsilon^2)$ space (see also [SGJ+13] for an earlier streaming algorithm and [GLM19] for a closely related parallel algorithm).

The *degeneracy* of a graph $G = (V, E)$, denoted by $\kappa(G)$, is the largest integer $k \geqslant 0$ such that G contains a non-empty k-core. The simple greedy algorithm that at every step peels off the smallest degree vertex results in the so-called *degeneracy ordering* of G and $\kappa(G)$ is equal to the largest degree of a vertex removed in this peeling process [MB83]. Degeneracy is a standard measure of uniform sparsity and is closely related to other such notions like arboricity (which is within a factor 2 of degeneracy). Moreover, computing degeneracy is a subroutine for approximating various other problems such as arboricity [AYZ97], densest subgraph [Cha00], $(\kappa + 1)$ coloring [EH66].

The degeneracy problem, and closely related uniform-sparsity measures such as densest subgraph, have also been studied extensively in the graph streaming literature [BKV12,FT14,BHNT15, MTVV15, FT16, BCG20, AA20]. In particular, [FT14] provided an $O(\log n)$-pass semi-streaming algorithm that outputs a constant factor approximation to degeneracy, and [FT16] subsequently improved this to a single-pass $(1-\varepsilon)$-approximation in $\widetilde{O}(n/\varepsilon^2)$ space (see also [MTVV15] for densest subgraph and [BCG20, AA20] for degeneracy coloring).

In terms of lower bounds, [BCG20] prove that any *single-pass* streaming algorithm that computes the exact value of degeneracy or approximates it within an additive factor of λ requires $\Omega(n^2)$ space or $\Omega(n^2/\lambda^2)$ space respectively. Our *polynomial-pass* lower bounds for k-cores and degeneracy, now in a very strong sense, rule out the possibility of extending any prior semi-streaming algorithms computing near-optimal solutions to these problems, to compute *exactly* optimal solutions.

3 Preliminaries

3.1 The Set-Intersection Problem

Definition 3.1. The m**-bit Set-Intersection** problem is a communication problem for two players Alice and Bob. Alice is given a subset $X \subseteq [m]$ and Bob is given a subset $Y \subseteq [m]$, with the promise that $|X \cap Y| = 1$. Their goal is to learn the point of intersection $\{t\} = X \cap Y$.

Let us define a distribution $\mathcal{D}_{\mathsf{Set\text{-}Int}}$ over inputs for Set-Intersection. This is the positive case of Razborov's original hard distribution for disjointness [Raz92].

Distribution $\mathcal{D}_{\mathsf{Set\text{-}Int}}$ [AR20] on sets (X, Y) from the universe $\mathcal{X} = [m]$:

- Uniformly sample two disjoint sets $X', Y' \subseteq [m]$ of size $\frac{m}{4} - 1$.
- Sample $e^* \in [m] \setminus (X' \cup Y')$ uniformly at random and define $X = X' \cup \{e^*\}$ and $Y = Y' \cup \{e^*\}$.

Proposition 3.2. *The internal information complexity of* finding *the intersecting element in a* SetInt_m *instance sampled from* $\mathcal{D}_{\mathsf{Set\text{-}Int}}$ *is* $\Omega(m)$.

Proposition 3.2 is not directly implied by standard set-intersection lower bounds, since they use distributions where X and Y never intersect. To obtain this proposition, one can (for example) apply the result of [JKS03] on the information cost of set disjointness protocols on intersecting distributions (see [ACK19] for more details).

3.2 The (Boolean) Hidden Pointer Chasing Problem

The Hidden Pointer Chasing (HPC) problem is a composition of Pointer Chasing and Set-Intersection, defined as follows.

Definition 3.3. The **Hidden Pointer Chasing** (HPC) problem is a communication problem with four players P_A, P_B, P_C, and P_D. Let $\mathcal{X} := \{x_1, ..., x_m\}$ and $\mathcal{Y} := \{y_1, ..., y_m\}$ be two disjoint universes.

- For any $x \in \mathcal{X}$, P_A and P_B are given an instance (A_x, B_x) of SetInt over the universe $\mathcal{Y}$ where $A_x \cap B_x = \{t_x\}$ for a single target element $t_x \in \mathcal{Y}$. We define $A := \{A_{x_1}, \ldots, A_{x_m}\}$ and $B := \{B_{x_1}, \ldots, B_{x_m}\}$ as the whole input to P_A and P_B, respectively.

- For any $y \in \mathcal{Y}$, P_C and P_D are given an instance (C_y, D_y) of SetInt over the universe $\mathcal{X}$ where $C_y \cap D_y = \{t_y\}$ for a single target element $t_y \in \mathcal{X}$. We define $C := \{C_{y_1}, \ldots, C_{y_m}\}$ and $D := \{D_{y_1}, \ldots, D_{y_m}\}$ as the whole input to P_C and P_D, respectively.
- We define two mappings $f_{AB} : \mathcal{X} \to \mathcal{Y}$ and $f_{CD} : \mathcal{Y} \to \mathcal{X}$ such that:

$$(a) \text{ for any } x \in \mathcal{X},\ f_{AB}(x) = t_x; \qquad (b) \text{ for any } y \in \mathcal{Y},\ f_{CD}(y) = t_y.$$

- Let $x_1 \in \mathcal{X}$ be an arbitrary fixed element known to all players. The pointers $z_0, z_1, z_2, \ldots$ are defined inductively as

$$z_0 := x_1, \quad z_1 := f_{AB}(z_0), \quad z_2 := f_{CD}(z_1), \quad z_3 := f_{AB}(z_2), \ \ldots.$$

For any integers $m, r \geqslant 1$, the **m-bit, r-step Hidden Pointer Chasing** problem, denoted by $\mathsf{HPC}_{m,r}$ is defined as the communication problem of finding the pointer z_r. Meaning, we wish to output the index $i \in [m]$ such that $z_r = x_i$ (when r is even) or $z_r = y_i$ (when r is odd).

We also define a Boolean variant of HPC as follows. In the **m-bit, r-step Boolean Hidden Pointer Chasing** problem, denoted by $\mathsf{BHPC}_{m,r}$, the goal is to output the bit $b(z_r) := i \mod 2$, where $z_r = x_i$ or y_i depending on if r is even or odd respectively.

3.3 The (Boolean) Multilayer Hidden Pointer Chasing Problem

The Multilayer Hidden Pointer Chasing problem (MHPC) combines r instances of HPC as its input in the following manner.

Definition 3.4. The **Multilayer Hidden Pointer Chasing** (MHPC) problem is a communication problem with four players P_A, P_B, P_C and P_D. Let m, r be integers $\geqslant 1$. The m-bit, r-layer MHPC problem, denoted by $\mathsf{MHPC}_{m,r}$ is defined as follows.

- For each $i \in [r]$, the players receive an HPC instance (A^i, B^i, C^i, D^i), each over the disjoint universes $\mathcal{X}$ and $\mathcal{Y}$ of size m. Let t^i_x denote the unique element in the intersection $A^i_x \cap B^i_x$, and t^i_y the unique element in $C^i_y \cap D^i_y$.
- For each $i \in [r]$, we have the maps $f^i_{AB} : \mathcal{X} \to \mathcal{Y}$ and $f^i_{CD} : \mathcal{Y} \to \mathcal{X}$, defined as:

$$(a) \text{ for any } x \in \mathcal{X},\ f^i_{AB}(x) = t^i_x; \qquad (b) \text{ for any } y \in \mathcal{Y},\ f^i_{CD}(y) = t^i_y.$$

- The pointers z_i are defined inductively as:

$$z_0 := x_1, \quad z_1 := f^1_{AB}(z_0), \quad z_2 := f^2_{CD}(z_1), \quad z_3 := f^3_{AB}(z_2), \ \ldots.$$

The goal of the problem is to find z_r, i.e., the index $i \in [m]$ such that $z_r = x_i$ (when r is even) or $z_r = y_i$ (when r is odd).

Analogous to HPC, we define the Boolean variant of MHPC as follows. In the **m-bit, r-layer Boolean** MHPC problem, denoted by $\mathsf{BMHPC}_{m,r}$, the goal is to output the bit $b(z_r) := i \mod 2$, where $z_r = x_i$ or y_i depending on if r is even or odd respectively.

We remark that C^j, D^j for odd j, and A^j, B^j for even j, are redundant (they do not affect the output of the function). They are kept for notational convenience and ease of presentation.

3.4 Misaligned r-Round Protocols

We are interested in bounded-round protocols for HPC, BHPC, MHPC and BMHPC. In each round, two of the players speak with each other (P_A with P_B, or P_C with P_D), but not with the other pair of players, with a message between pairs of players triggering the next round.

Definition 3.5 (Round of $\mathsf{HPC}_{m,r}$)**.** An r-round protocol is a protocol where the communication is organized in rounds $1, 2, \ldots, r$. A given pair of players — P_A and P_B or P_C and P_D — communicate with each other in the odd rounds (the first, third, etc rounds) and the other pair of players communicate with each other in the even rounds. Each round ends with the speaking pair of players sending a message to the other pair of players, and this marks the beginning of the next round.

It is easy to see that one can solve any of the above HPC variants by r-round protocols communicating $O(rm)$ bits, if P_A and P_B speak in the odd rounds, and P_C and P_D speak in the even rounds. We will show lower-bounds for *misaligned* r-round protocols where the *wrong* pair of players speak:

Definition 3.6. We call an r-round protocol *misaligned* if the pair of players P_C and P_D speak in the odd rounds, and P_A and P_B speak in the even rounds.

The above definitions naturally suggest that, in an r-round protocol, we should think of z_j as the pointer that the players wish to know by the end of round j. In a misaligned protocol, however, the players speaking in round j do not hold the Set-Intersection instance that needs to be solved to find z_j.

3.5 Notation and Terminology

Notation for Protocols. We use the notation $\pi_{\mathsf{Set\text{-}Int}}$, π_{BHPC}, and π_{BMHPC}, to denote protocols for Set-Intersection, BHPC and BMHPC, respectively.

In general, we will use the upright A to denote a random variable associated with A.

Now consider a situation where we choose inputs (A, B, C, D) from some distribution on inputs to $\mathsf{HPC}_{m,r}$. We then let $\mathsf{Z}_1, \ldots, \mathsf{Z}_r$ denote random variables with values $z_1, \ldots, z_r$ of Definition 3.3. We use the variable $j \in [r]$ to index the rounds of a r-round protocol. For any $j \in [r]$, we define Π_j as the set of all messages communicated in round j, and more generally Π denotes the entire protocol transcript.

For any $x \in \mathcal{X}$ and $y \in \mathcal{Y}$, we define random variables $\mathsf{T}_x \in \mathcal{Y}$ and $\mathsf{T}_y \in \mathcal{X}$ giving the intersecting elements of the Set-Intersection instance $(\mathsf{A}_x, \mathsf{B}_x)$ and $(\mathsf{C}_y, \mathsf{D}_y)$, respectively. We define $\mathsf{E}_j = (\Pi_1, \ldots, \Pi_{j-1}, \mathsf{Z}_1, \ldots, \mathsf{Z}_{j-1})$ to include all messages exchanged before round j, together with the entire path followed by the pointers before round j. Note that during round j, the players wish to compute the intersection $A_{z_j} \cap B_{z_j}$ (or $C_{z_j} \cap D_{z_j}$), so knowing E_j should not help them to do that. (Note that E_1 is empty.)

On an input (A, B, C, D) to $\mathsf{BMHPC}_{m,r}$, we define the notation Z_i, j, Π_j, T_x^j, T_y^j analogously.

If we have random variables A, B, we will broadly use the notation $\mu(\mathsf{A} \mid \mathsf{B})$ to mean "the distribution of A, conditioned on the value of B that occurred". So, for example, if B is constant we may write $\mu(\mathsf{A})$, and this is some fixed distribution. But if B is non-constant, the distribution $\mu(\mathsf{A} \mid \mathsf{B})$ may vary depending on B, and so $\mu(\mathsf{A} \mid \mathsf{B})$ is itself also a random variable, which depends on B and can be determined by knowing B alone (even without knowing A).

Other notation. An input graph to a streaming algorithm will usually be called $G = (V, E)$ and n will denote $|V|$. The degeneracy of graph G will be denoted by $\kappa(G)$, or simply κ if the graph is clear from the context. The notation "$\log x$" stands for $\log_2 x$. For a positive integer a, the notation $[a]$ denotes the set $\{1, 2, \ldots, a\}$ and for integers $a < b$, $[a, b]$ denotes the set $\{a, a+1, \ldots, b\}$.

3.6 Positive Triangular Discrimination

Definition 3.7 (Positive triangular discrimination)**.** Given two distributions μ and ν on a sample space Ω, the *positive triangular discrimination* $\Lambda(\mu, \nu)$ is:

$$\Lambda(\mu, \nu) = \sum_{\substack{x \in \Omega \\ \mu(x) > \nu(x)}} \frac{(\mu(x) - \nu(x))^2}{\mu(x) + \nu(x)}.$$

In this paper, we work exclusively with *positive* triangular discrimination. Below we state some of the useful properties of positive triangular discrimination. We defer the proofs of the following propositions to Section B.

Proposition 3.8. $0 \leqslant \frac{\|\mu-\nu\|_1^2}{8} \leqslant \Lambda(\mu, \nu) \leqslant \frac{\|\mu-\nu\|_1}{2} \leqslant 1$.

The following property is already implicit in [Yeh20], but making it explicit now simplifies the presentation later. Note that an analogous equation for total variation distance, i.e., $\mathbb{E}_\mu[f(x)] \leqslant \|\mu - \nu\|_1 \cdot \max_{x \in x} f(x) + \cdot \mathbb{E}_\nu[f(x)]$ can be obtained almost from the definition. The following statement, however, needs a bit more work.

Proposition 3.9. *For any function* $f : \Omega \to \mathbb{R}_{\geqslant 0}$,

$$\mathop{\mathbb{E}}_{\mu}[f(x)] \leqslant \Lambda(\mu, \nu) \cdot \max_{x \in \Omega} f(x) + 6 \cdot \mathop{\mathbb{E}}_{\nu}[f(x)].$$

We will also make use of the convexity of Λ.

Proposition 3.10. *Positive triangular discrimination* $\Lambda(\mu, \nu)$ *is convex as a joint function of the two distributions* μ *and* ν.

3.7 Degeneracy and k-Cores

The definition of a k-core and the degeneracy $\kappa(G)$ of a graph G can be found in Section 2.1. Here, we define some related terms that come up often in the paper. We also state some basic facts about them that we later use in our proofs.

Given an ordering σ of vertices, we say $v \prec_\sigma u$ if u appears (somewhere) after v in σ.

Definition 3.11 (Outdegree with respect to an ordering)**.** For a graph $G = (V, E)$. given an ordering σ of vertices in V, the outdegree of a vertex v with respect to σ, denoted by $\mathrm{odeg}_\sigma(v)$, is the number of neighbors of v that appear after it in σ. Formally,

$$\mathrm{odeg}_\sigma(v) = |\{u \in N(v) : v \prec_\sigma u\}|$$

We can also think of it as orienting all edges (x, y) from x to y if $x \prec_\sigma y$. Then $\mathrm{odeg}_\sigma(v)$ is the outdegree of v in the resultant oriented graph.

Definition 3.12 (k-ordering)**.** Given a graph $G = (V, E)$, an ordering σ of vertices in V is called a k-ordering if $\forall v \in V : \mathrm{odeg}_\sigma(v) \leqslant k$.

The following fact connects vertex orderings to degeneracy.

Fact 3.13 ([MB83])**.** *The minimum number* k *for which a graph* G *admits a* k*-ordering is* $\kappa(G)$.

The above fact implies that to prove that a graph has degeneracy at most k, it suffices to exhibit a k-ordering of the nodes. We now formally define *degeneracy ordering* of a graph.

Definition 3.14 (Degeneracy ordering)**.** Given a graph $G = (V, E)$, a $\kappa(G)$-ordering of V is called a degeneracy ordering of G.

A degeneracy ordering of a graph can be obtained by running the following "peeling algorithm" on it: starting with an empty sequence σ, recursively remove the minimum degree vertex from G and append it to σ until the graph becomes empty. Again, the maximum degree that a node has when it is peeled by this algorithm is exactly $\kappa(G)$. If not, then the peeling algorithm gives a k-ordering for some $k < \kappa(G)$ which violates Fact 3.13. Hence, we get the following fact.

Fact 3.15. *Suppose the peeling algorithm on a graph G removes its nodes in the order $v_1, \ldots, v_n$. Define $G_0 := G$ and $G_i := G \setminus \{v_1, \ldots, v_i\}$ for $i \in [n]$. Then,*

$$\kappa(G) = \max_{i \in [n]} \deg_{G_{i-1}}(v_i)$$

.

4 New Lower Bounds for HPC and Multilayer HPC

The two main results of this section are an $\Omega(m^2)$ lower-bound against misaligned r-round protocols for $\mathsf{BMHPC}_{m,r}$, and an $\Omega(\frac{m^2}{r})$ lower-bound against misaligned r-round protocols for $\mathsf{BHPC}_{m,r}$. Notice that in a misaligned r-round round protocol for $\mathsf{BMHPC}_{m,r}$ or $\mathsf{BHPC}_{m,r}$, it is players P_C and P_D who begin the protocol by talking with each other. This means that the "wrong" pair of players begin to speak, in the sense that they wish to compute the value $\{z_1\} = A_{z_0} \cap B_{z_0}$, but this instance is with Alice and Bob, so they have no way to do this. So the first round of communication says nothing about z_1: the best P_C and P_D can do is send some information about all of their Set-Intersection instances, without knowing which is important. So each bit that P_C and P_D communicate with P_A and P_B in the first round, can only reveal $\frac{1}{m}$ bits of information about the average instance. So, in the next round, P_A and P_B cannot have learned what C_{z_1} or D_{z_1} are, either. But then, how can they learn z_2? The difficult situation is now reversed! This "always one step behind" situation is similar to what happens for pointer chasing [NW93, PRV99, Yeh20], except now the pointers are "hidden" behind set intersection instances.

How much communication must the players use in order to escape this unfortunate situation? In the case of $\mathsf{BMHPC}_{m,r}$, it is not clear how to do this in less than $O(m^2)$ bits of communication. One can think of two strategies: either reveal an entire layer, causing the protocol to become aligned at that layer, or solve roughly $\frac{m}{r}$ set intersections instances in each layer, which will cause the protocol to become aligned (follow the pointer of a solved instance) at any given layer with probability $\frac{1}{r}$. We will prove that these two strategies are essentially optimal.

However, in the case of $\mathsf{BHPC}_{m,r}$, it can be seen that $O(\frac{m^2}{r})$ bits of communication suffice. Indeed, P_C and P_D (who speak first) may choose $N = O(\frac{m}{r})$ of their Set-Intersection instances uniformly at random, solve them all by communicating $O(\frac{m^2}{r})$ bits, and then send the solution of all these instances to P_A and P_B. Then, in the next round, P_A and P_B begin the standard protocol for solving $\mathsf{HPC}_{m,r}$, meaning, they compute z_1 and send it back, then P_C and P_D compute z_2 and send it back, etc. If at any point P_A and P_B compute some z_j which is among the N revealed Set-Intersection instances, then they can skip a step, and learn z_{j+2} immediately without communicating. The protocol is now aligned, and can be finished within the remaining number of rounds. The probability that the path taken crosses one of the instances revealed by P_C and P_D is $\Omega(r/N)$, which can be made arbitrarily close to 1 with our choice of N.

On the other hand, one should not expect to be able to prove any significant lower-bound when r is a sufficiently large fraction of $\sqrt{n}$. Indeed, in this case, the birthday paradox says that the path

being traversed will cycle with high probability. The players may then follow the path (wasting the first round entirely) until they find a cycle, and then they will immediately learn z_k.

The intuitive explanation and the upper-bounds given above will lead us to conjecture the following, necessarily tight lower-bounds, which are the main results of this section.

Theorem 4.1. *Any misaligned r-round protocol, solving $\mathsf{BMHPC}_{m,r}$ correctly with constant probability requires $\Omega(m^2)$ bits of communication.*

Theorem 4.2. *Any misaligned r-round protocol, where $r = o(\sqrt{m})$, solving $\mathsf{BHPC}_{m,r}$ correctly with constant probability requires $\Omega(\frac{m^2}{r})$ bits of communication.*

A weaker lower-bound of $\frac{m^2}{r^2}$ for HPC was proven in [ACK19]. Our proofs of these tight lower-bounds follow a similar strategy to the earlier proof, but with a somewhat modified protocol inspired by [Yeh20]. We begin by proving Theorem 4.2 in Section 4.3, because the proof is slightly simpler, and it is enough for our streaming lower-bounds. The proof of Theorem 4.2 appears in Section 4.5. Both proofs follow a similar outline. We first show that a short, misaligned r-round protocol for BMHPC (or BHPC) must be "almost solving" an instance of Set-Intersection on one of the rounds, while revealing little information. The notion of "almost solving" will be formally defined in Section 4.1. Then, in Section 4.4, we show that any low-information protocol for "almost-solving" Set-Intersection can be used to actually solve Set-Intersection, also with low information. Putting it all together in Section 4.6, we will find that a misaligned r-round protocol for $\mathsf{BMHPC}_{m,r}$ communicating $o(m^2)$ bits (or for $\mathsf{BHPC}_{m,r}$ communicating $o(\frac{m^2}{r})$ bits), would allow us to solve Set-Intersection with $o(m)$ information cost, which is known to be impossible by [JKS03].

4.1 "Almost Solving"

The notion of "almost solving" is given precisely below. Intuitively, a protocol ε-solves Set-Intersection if the distribution of the intersection point $\{\mathsf{e}^*\} = \mathsf{A} \cap \mathsf{B}$ is sufficiently altered by the execution of the protocol. Meaning, the distribution of e^* conditioned on knowing the protocol (and possibly one of the inputs) is sufficiently far-away from the distribution of e^* without this knowledge. In [ACK19], the chosen notion of *sufficiently far* is the total variation distance. Here we will choose positive triangular discrimination.

Definition 4.3 (ε-solving Set-Intersection, with respect to positive triangular discrimination)**.** Let $\mathcal{D}$ be a distribution on inputs (A, B) for Set-Intersection. A randomized protocol π *internally ε-solves Set-Intersection* (with respect to positive triangular discrimination) on $\mathcal{D}$ if *at least one* of the following hold true (where Π is the transcript of π, including public randomness):

$$\mathop{\mathbb{E}}_{\Pi,\mathsf{A}}[\Lambda(\mu(\mathsf{e}^* \mid \Pi, \mathsf{A}), \mu(\mathsf{e}^* \mid \mathsf{A}))] \geqslant \varepsilon \qquad \text{or} \qquad \mathop{\mathbb{E}}_{\Pi,\mathsf{B}}[\Lambda(\mu(\mathsf{e}^* \mid \Pi, \mathsf{B}), \mu(\mathsf{e}^* \mid \mathsf{B}))] \geqslant \varepsilon.$$

A protocol π *externally ε-solves Set-Intersectiom* on $\mathcal{D}$ if the following holds true:

$$\mathop{\mathbb{E}}_{\Pi}[\Lambda(\mu(\mathsf{e}^* \mid \Pi), \mu(\mathsf{e}^*))] \geqslant \varepsilon.$$

Observation 4.4. *From the joint convexity of positive triangular discrimination (Proposition 3.10), it follows that for any (possibly correlated) random variables $\mathsf{A}, \mathsf{B}, \mathsf{C}$,*

$$\begin{aligned}
\mathop{\mathbb{E}}_{\mathsf{B},\mathsf{C}}[\Lambda(\mu(\mathsf{A} \mid \mathsf{B}, \mathsf{C}), \mu(\mathsf{A} \mid \mathsf{C}))] &= \mathop{\mathbb{E}}_{\mathsf{B}}\left[\sum_c \Pr[\mathsf{C} = c]\Lambda(\mu(\mathsf{A} \mid \mathsf{B}, \mathsf{C} = c), \mu(\mathsf{A} \mid \mathsf{C} = c))\right] \\
&\geqslant \mathop{\mathbb{E}}_{\mathsf{B}}\left[\Lambda\left(\sum_c \Pr[\mathsf{C} = c]\mu(\mathsf{A} \mid \mathsf{B}, \mathsf{C} = c), \sum_c \Pr[\mathsf{C} = c]\mu(\mathsf{A} \mid \mathsf{C} = c)\right)\right] \\
&= \mathop{\mathbb{E}}_{\mathsf{B}}[\Lambda(\mu(\mathsf{A} \mid \mathsf{B}), \mu(\mathsf{A}))].
\end{aligned}$$

That is, removing a random variable from both conditions can only decrease the Λ-distance. In particular, if a protocol externally ε-solves Set-Intersection on some distribution $\mathcal{D}$, it also internally ε-solves Set-Intersection on $\mathcal{D}$.

Observation 4.5. *It may be felt that a more natural definition of internally ε-solving should include any eventual private randomness of the protocol π. However, noting that $\{\mathsf{e}^*\} = \mathsf{A} \cap \mathsf{B}$ is a function of A and B, and that A and B are independent given Π (by Fact D.9) it follows that the distribution of e^* is independent of the private randomness of π, when given A and Π. So*

$$\mathop{\mathbb{E}}_{\Pi,\mathsf{A}}[\Lambda(\mu(\mathsf{e}^* \mid \Pi, \mathsf{A}), \mu(\mathsf{e}^* \mid \mathsf{A}))] = \mathop{\mathbb{E}}_{\Pi,\mathsf{A}}[\Lambda(\mu(\mathsf{e}^* \mid \Pi, \mathsf{R}_A, \mathsf{A}), \mu(\mathsf{e}^* \mid \mathsf{A}))]$$

where R_A is Alice's randomness, and likewise on Bob's side. That is, including the private randomness gives the same definition.

4.2 Hard Distributions

Next, we define two hard distributions for $\mathcal{D}_{\mathsf{BMHPC}}$ and $\mathcal{D}_{\mathsf{BHPC}}$, over inputs to BMHPC and BHPC, respectively.

Distribution $\mathcal{D}_{\mathsf{BMHPC}}$ on tuples $(\mathsf{A}, \mathsf{B}, \mathsf{C}, \mathsf{D})$ from the universes $\mathcal{X}$ and $\mathcal{Y}$:

1. For any $i \in [r]$, and any $x \in \mathcal{X}$, sample $(A_x^i, B_x^i) \sim \mathcal{D}_{\mathsf{Set\text{-}Int}}$ from the universe $\mathcal{Y}$ *independently.*
2. For any $i \in [r]$, and any $y \in \mathcal{Y}$, sample $(C_y^i, D_y^i) \sim \mathcal{D}_{\mathsf{Set\text{-}Int}}$ from the universe $\mathcal{X}$ *independently.*

Distribution $\mathcal{D}_{\mathsf{BHPC}}$ [ACK19] on tuples $(\mathsf{A}, \mathsf{B}, \mathsf{C}, \mathsf{D})$ from the universes $\mathcal{X}$ and $\mathcal{Y}$:

1. For any $x \in \mathcal{X}$, sample $(A_x, B_x) \sim \mathcal{D}_{\mathsf{Set\text{-}Int}}$ from the universe $\mathcal{Y}$ *independently.*
2. For any $y \in \mathcal{Y}$, sample $(C_y, D_y) \sim \mathcal{D}_{\mathsf{Set\text{-}Int}}$ from the universe $\mathcal{X}$ *independently.*

It was shown in [ACK19] that misaligned randomized r-round protocols for $\mathsf{HPC}_{m,r}$ need $\frac{m^2}{r^2}$ bits of communication under $\mathcal{D}_{\mathsf{BHPC}}$. In Section 4.5, we improve this result and show that misaligned randomized r-round protocols for $\mathsf{BHPC}_{m,r}$ (an easier problem than $\mathsf{HPC}_{m,r}$) need $\frac{m^2}{r}$ bits of communication.

We restate the following simple observations from [ACK19] about $\mathcal{D}_{\mathsf{BHPC}}$. Analogous statements can be made for $\mathcal{D}_{\mathsf{BMHPC}}$.

Observation 4.6 ([ACK19])**.** *Distribution $\mathcal{D}_{\mathsf{BHPC}}$ is <u>not</u> a product distribution. However, in this distribution:*

(i) The inputs to P_A and P_B are independent of the inputs to P_C and P_D, i.e., $(\mathsf{A}, \mathsf{B}) \perp (\mathsf{C}, \mathsf{D})$.

(ii) For any $x \in \mathcal{X}$, $(\mathsf{A}_x, \mathsf{B}_x)$ is independent of all other $(\mathsf{A}_{x'}, \mathsf{B}_{x'})$ for $x' \neq x \in \mathcal{X}$. Similarly for all $y, y' \in \mathcal{Y}$ and $(\mathsf{C}_y, \mathsf{D}_y)$ and $(\mathsf{C}_{y'}, \mathsf{D}_{y'})$.

Based on this observation, we also have the following simple property.

Proposition 4.7 ([ACK19]). *Let π_{BHPC} be any deterministic protocol for $\mathsf{BHPC}_{m,r}$ on $\mathcal{D}_{\mathsf{BHPC}}$. Then, for any transcript Π of π_{BHPC}, $(\mathsf{A},\mathsf{B}) \perp (\mathsf{C},\mathsf{D}) \mid \Pi = \Pi$.*

Proof. Follows from the rectangle property of the protocol π_{BHPC} (Fact D.9). In particular, the same exact argument as in the two-player case implies that if $[(A,B),(C,D)]$ and $[(A',B'),(C',D')]$ are mapped to the same transcript Π, then $[(A,B),(C',D')]$ and $[(A',B'),(C,D)]$ are mapped to Π as well. Hence, since $(\mathsf{A},\mathsf{B}) \perp (\mathsf{C},\mathsf{D})$ by Observation 4.6, the inputs corresponding to the same protocol would also be independent of each other, namely, $(\mathsf{A},\mathsf{B}) \perp (\mathsf{C},\mathsf{D}) \mid \Pi = \Pi$. □

4.3 Short Protocols for BMHPC Give Low-Information ε-Solvers for Set-Int

We now show that if we have a short, r-round protocol for $\mathsf{BMHPC}_{m,r}$ on $\mathcal{D}_{\mathsf{BMHPC}}$, then during one of its rounds it must be externally (and hence also internally) ε-solving Set-Intersection on $\mathcal{D}_{\mathsf{Set\text{-}Int}}$, while revealing little information. This is proven by making precise the following intuitive line of thinking, the statement of which is formally captured by Lemma 4.11.

- By the end of round j, the speaking pair of players would like to have learned $\{\mathsf{Z}_j\} = \mathsf{A}^j_{\mathsf{Z}_{j-1}} \cap \mathsf{B}^j_{\mathsf{Z}_{j-1}}$ (for odd j, or $\{\mathsf{Z}_j\} = \mathsf{C}^j_{\mathsf{Z}_{j-1}} \cap \mathsf{D}^j_{\mathsf{Z}_{j-1}}$, for even j). Now suppose that in this round they have very little information about Z_{j-1}. Let us say, for example, that the distribution of $\mathsf{Z}_{j-1} \mid \mathsf{E}_{j-1}, \Pi_{j-1}$ is close to uniform. This certainly holds when $j = 2$, since $\mu(\mathsf{Z}_1|\mathsf{E}_1,\Pi_1) = \mu(\mathsf{Z}_1)$ is completely uniform (because the wrong pair of players speak first and the way we construct $\mathcal{D}_{\mathsf{BMHPC}}$).
- Now suppose that despite this, somehow, the two speaking players nonetheless manage to learn a lot of information about Z_j. Then they have "almost solved" an *unknown* instance (an instance belonging to the other players, no less), out of the possible remaining instances of Set-Intersection. Because they have little information about Z_{j-1}, meaning Z_{j-1} is close to uniform, they have thus "almost solved" an unknown, nearly-uniformly-chosen instance.
- Then, intuitively, they must have "almost solved" this unknown instance of Set-Intersection without revealing a lot of information about it. This turns out to be impossible, as we will see in Section 4.4.

One difficulty in implementing this intuitive strategy is in finding the right measure of information that allows for one to carry through the entire argument. In [ACK19], *total variation distance from uniform* was used as a measure of how much the speaking players know about which Set-Intersection instance they are trying to solve. But TVD incurs the quadratic loss inherent in Pinsker's inequality, leading to a lower-bound of $\frac{m^2}{r^2}$. The same quadratic loss appeared originally in Nisan and Wigderson's lower-bounds for pointer chasing [NW93], and this led to a three-decade-long gap between known upper and lower-bounds for pointer chasing. This gap was finally closed by Amir Yehudayoff [Yeh20], using positive triangular discrimination. This suggested the possibility of using Yehudayoff's approach to improve the lower-bound of [ACK19], and it is this plan that we realize here.

The following lemma states that no low-information protocol (in the sense of information cost) for BMHPC can reveal a lot of information (in the sense of Λ-distance-from-uniform) about a uniformly chosen SetInt instance at any layer j. The proof shows that any such protocol would give us a low-information protocol for ε-solving SetInt, which we will show is impossible in Section 4.4.

Lemma 4.8. *There is a constant $c > 0$ such that, for any protocol for $\mathsf{BMHPC}_{m,r}$ running on input $(\mathsf{A},\mathsf{B},\mathsf{C},\mathsf{D})$ sampled from $\mathcal{D}_{\mathsf{BMHPC}}$, and for any $j \in [r]$, we have:*

$$\mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)} \mathop{\mathbb{E}}_{x\sim\mathcal{U}_\mathcal{X}} \left[\Lambda(\mu(\mathsf{T}_x^j \mid \mathsf{E}_j,\Pi_j),\mu(\mathsf{T}_x^j))\right] \leqslant c \cdot \frac{\mathbb{I}(\Pi\,;\mathsf{A}^j \mid \mathsf{A}^{<j},\mathsf{B}) + \mathbb{I}(\Pi\,;\mathsf{B}^j \mid \mathsf{B}^{>j},\mathsf{A})}{m^2}$$

$$\mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)} \mathop{\mathbb{E}}_{y\sim\mathcal{U}_\mathcal{Y}} \left[\Lambda(\mu(\mathsf{T}_y^j \mid \mathsf{E}_j,\Pi_j),\mu(\mathsf{T}_y^j))\right] \leqslant c \cdot \frac{\mathbb{I}(\Pi\,;\mathsf{C}^j \mid \mathsf{C}^{<j},\mathsf{D}) + \mathbb{I}(\Pi\,;\mathsf{D}^j \mid \mathsf{D}^{>j},\mathsf{C})}{m^2}$$

Proof. Take any given $j \in [r]$, and consider the following protocol for ε-solving SetInt on $\mathcal{D}_{\mathsf{Set\text{-}Int}}$:

Protocol π_{SI}: The protocol for ε-solving Set-Int using a protocol π_{HPC} for $\mathsf{BMHPC}_{m,r}$.
Input: An instance $(X,Y) \sim \mathcal{D}_{\mathsf{Set\text{-}Int}}$ with $X, Y \subseteq \mathcal{Y}$.

1. **Sampling the instance.** Alice and Bob create an instance (A,B,C,D) of $\mathsf{BMHPC}_{m,r}$ as follows:
   (a) Using public coins, Alice and Bob sample an index $I \in [m]$ uniformly at random, and Alice sets $A^j_{x_I} = X$ and Bob sets $B^j_{x_I} = Y$ using their given inputs in Set-Int.
   (b) Using public coins, Alice and Bob sample $A^j_{x_1},\ldots,A^j_{x_{I-1}}$ from the A-side marginal of $\mathcal{D}_{\mathsf{Set\text{-}Int}}$, and they sample $B^j_{x_{I+1}},\ldots,B^j_{x_m}$ from the B-side marginal of $\mathcal{D}_{\mathsf{Set\text{-}Int}}$.
   (c) Using private coins, Alice samples $A^j_{x_r}$ for $r \in \{I+1,\ldots,n\}$ so that $(A^j_{x_r}, B^j_{x_r}) \sim \mathcal{D}_{\mathsf{Set\text{-}Int}}$. Similarly Bob samples $B^j_{x_\ell}$ for $\ell \in \{1,\ldots,I-1\}$. This completes the construction of (A^j, B^j).
   (d) Using public coins, Alice and Bob sample $A^{<j}, B^{>j}, C$ and D from their respective marginals in $\mathcal{D}_{\mathsf{BMHPC}}$ (this is possible by independence).
   (e) Using private coins, Alice samples $A^{>j}$ conditioned on the publicly sampled $B^{>j}$, and Bob samples $B^{<j}$ conditioned on the publicly sampled $A^{<j}$.
2. The players now run the first j rounds of the protocol π_{BMHPC} on the instance (A,B,C,D), by Alice playing P_A, Bob playing P_B, and both Alice and Bob simulating P_C and P_D with no communication (this is possible as both Alice and Bob know (C,D) entirely).
   Let us write $\Pi_{\mathsf{Set\text{-}Int}}$ to denote the messages of P_A and P_B, which were actually sent by Alice and Bob, and $\Pi_{\leqslant j}$ to denote the entire simulated transcript of π_{BMHPC}, including the messages of P_C and P_D (which Alice and Bob learned without communicating).

From a simple direct-sum argument, we get an upper-bound on the information cost of $\pi_{\mathsf{Set\text{-}Int}}$:

Claim 4.9.

$$\mathsf{IC}_{\mathcal{D}_{\mathsf{Set\text{-}Int}}}(\pi_{\mathsf{Set\text{-}Int}}) = \frac{\mathbb{I}(\Pi_{\leqslant j}\,;\mathsf{A}^j \mid \mathsf{A}^{<j},\mathsf{B}) + \mathbb{I}(\Pi\,;\mathsf{B}^j \mid \mathsf{B}^{>j},\mathsf{A})}{m}.$$

Proof. The internal information cost of $\pi_{\mathsf{Set\text{-}Int}}$ is

$$\mathsf{IC}_{\mathcal{D}_{\mathsf{Set\text{-}Int}}}(\pi_{\mathsf{Set\text{-}Int}}) := \mathbb{I}(\mathsf{X}\,;\Pi_{\mathsf{SI}} \mid \mathsf{Y},\mathsf{R},\mathsf{R}_B) + \mathbb{I}(\mathsf{Y}\,;\Pi_{\mathsf{SI}} \mid \mathsf{X},\mathsf{R},\mathsf{R}_A),$$

where R, R_A, R_B are the public, Alice's, and Bob's randomness. Let us bound the first term, as the second term can be bounded in just the same way. We then derive:

$$\begin{aligned}
\mathbb{I}(\Pi_{\mathsf{Set\text{-}Int}}\,;\mathsf{X} \mid \mathsf{Y},\mathsf{R},\mathsf{R}_B) &= \mathbb{I}(\Pi_{\leqslant j}\,;\mathsf{X} \mid \mathsf{Y},\mathsf{I},\mathsf{A}^j_{<\mathsf{I}},\mathsf{B}^j_{>\mathsf{I}},\mathsf{A}^{<j},\mathsf{B}^{>j},\mathsf{C},\mathsf{D},\mathsf{B}^j_{<\mathsf{I}},\mathsf{B}^{<j}) \\
&= \mathbb{I}(\Pi_{\leqslant j}\,;\mathsf{A}^j_{\mathsf{I}} \mid \mathsf{I},\mathsf{A}^j_{<\mathsf{I}},\mathsf{A}^{<j},\mathsf{B},\mathsf{C},\mathsf{D}) \\
&= \sum_{i=1}^{m} \frac{1}{m}\mathbb{I}(\Pi_{\leqslant j}\,;\mathsf{A}^j_i \mid \mathsf{I}=i,\mathsf{A}^j_{<i},\mathsf{A}^{<j},\mathsf{B},\mathsf{C},\mathsf{D}) \\
&= \sum_{i=1}^{m} \frac{1}{m}\mathbb{I}(\Pi_{\leqslant j}\,;\mathsf{A}^j_i \mid \mathsf{A}^j_{<i},\mathsf{A}^{<j},\mathsf{B},\mathsf{C},\mathsf{D}) \\
&= \frac{1}{m}\mathbb{I}(\Pi_{\leqslant j}\,;\mathsf{A}^j \mid \mathsf{A}^{<j},\mathsf{B},\mathsf{C},\mathsf{D}) \\
&= \frac{1}{m}\mathbb{I}(\Pi_{\leqslant j}\,;\mathsf{A}^j \mid \mathsf{A}^{<j},\mathsf{B}).
\end{aligned}$$

All equalities are by definition, except for the fourth which is because none of the remaining distributions depend on the choice of I, and the last, which is because C,D are independent of A^j, even when conditioned on $\Pi_{\leqslant j}, \mathsf{A}^{<j}, \mathsf{B}$. □

On the other hand, we also get an ε-solver, for ε being exactly the Λ distance-from-uniform of a uniformly chosen coordinate in the j-th layer:

Claim 4.10. *$\pi_{\mathsf{Set\text{-}Int}}$ internally ε-solves Set-Intersection on $\mathcal{D}_{\mathsf{Set\text{-}Int}}$ where:*

$$\varepsilon \geqslant \mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)} \mathop{\mathbb{E}}_{x\sim\mathcal{U}_{\mathcal{X}}} \left[\Lambda(\mu(\mathsf{T}^j_x \mid \mathsf{E}_j,\Pi_j),\mu(\mathsf{T}^j_x))\right].$$

Proof. By Definition 4.3 and Observation 4.5, we have an ε-solver on Bob's side, for

$$\varepsilon = \mathbb{E}[\Lambda(\mu(\mathsf{T} \mid \mathsf{Y},\Pi_{\mathsf{Set\text{-}Int}},\mathsf{I},\mathsf{R},\mathsf{R}_B),\mu(\mathsf{T} \mid \mathsf{Y},\mathsf{I},\mathsf{R},\mathsf{R}_B))],$$

where $T = X \cap Y = A^j_I \cap B^j_I$, I and $R = A^j_{<I}, B^j_{>I}, A^{<j}, B^{>j}, C, D$ are the public randomness, and $R_B = B^j_{<I}, B^{<j}$ is Bob's private randomness. This is exactly equal to

$$\mathbb{E}[\Lambda(\mu(\mathsf{T} \mid \mathsf{Y},\mathsf{E}_j,\Pi_j,\mathsf{I},\mathsf{R},\mathsf{R}_B),\mu(\mathsf{T} \mid \mathsf{Y},\mathsf{I},\mathsf{R},\mathsf{R}_B))],$$

because E_j, Π_j is a function of $\Pi_{\mathsf{Set\text{-}Int}}, I, R, R_B$ (Bob knows both $A^{<j}$, $B^{<j}$ and C, D, so he also knows $Z_{<j}$, and $\Pi_{\leqslant j}$). In turn, this equals

$$\mathop{\mathbb{E}}_{\mathsf{E}_j,\Pi_j,i\sim\mathcal{U}_{[m]}} \mathbb{E}\left[\Lambda(\mu(\mathsf{T}^j_{x_i} \mid \mathsf{E}_j,\Pi_j,\mathsf{I}=i,\mathsf{Y},\mathsf{R},\mathsf{R}_B),\mu(\mathsf{T}^j_{x_i} \mid \mathsf{Y},\mathsf{I}=i,\mathsf{R},\mathsf{R}_B))\right]$$

Observe that none of the distributions above depend on the event $\mathsf{I}=i$. So this quantity is equal to

$$\mathop{\mathbb{E}}_{\mathsf{E}_j,\Pi_j,i\sim\mathcal{U}_{[m]}} \mathbb{E}\left[\Lambda(\mu(\mathsf{T}^j_{x_i} \mid \mathsf{E}_j,\Pi_j,\mathsf{Y},\mathsf{R},\mathsf{R}_B),\mu(\mathsf{T}^j_{x_i} \mid \mathsf{Y},\mathsf{R},\mathsf{R}_B))\right]$$

Now, by Observation 4.4, this is greater or equal to

$$\mathop{\mathbb{E}}_{\mathsf{E}_j,\Pi_j,i\sim\mathcal{U}_{[m]}} \mathbb{E}\left[\Lambda(\mu(\mathsf{T}^j_{x_i} \mid \mathsf{E}_j,\Pi_j),\mu(\mathsf{T}^j_{x_i}))\right].$$ □

From Corollary 4.13 proven in the next section, it now follows:

$$\begin{aligned}\frac{\mathbb{I}(\Pi_{\leqslant j}\,;\mathsf{A}^j \mid \mathsf{A}^{<j},\mathsf{B}) + \mathbb{I}(\Pi_{\leqslant j}\,;\mathsf{B}^j \mid \mathsf{B}^{>j},\mathsf{A})}{m} &\geqslant c\cdot\varepsilon m \\ &\geqslant cm\cdot \mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)} \mathop{\mathbb{E}}_{x\sim\mathcal{U}_{\mathcal{X}}} \left[\Lambda(\mu(\mathsf{T}^j_x \mid \mathsf{E}_j,\Pi_j),\mu(\mathsf{T}^j_x))\right].\end{aligned}$$

This concludes the proof of Lemma 4.8. □

It is now possible to prove that there is no low-information protocol for solving BMHPC. The argument was roughly outlined above: if we assume by induction that the Λ distance-from-uniform is small for the answer at the previous layer, then we are essentially trying to solve a uniformly random instance at the current layer. And we just proved that this is not possible.

Lemma 4.11. *For the same constant $c>0$ of the Lemma 4.8, and for any protocol for $\mathsf{BMHPC}_{m,r}$ running on input (A,B,C,D) sampled from $\mathcal{D}_{\mathsf{BMHPC}}$, the following statement holds for all $j\in[r]$:*[1]

$$\mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)}[\Lambda(\mu(\mathsf{Z}_j \mid \mathsf{E}_j,\Pi_j),\mu(\mathsf{Z}_j))] \leqslant 6c\cdot\frac{\mathbb{I}(\Pi\,;\mathsf{A}^{\leqslant j},\mathsf{C}^{\leqslant j} \mid \mathsf{B},\mathsf{D}) + \mathbb{I}(\Pi\,;\mathsf{B}^{\leqslant j},\mathsf{D}^{\leqslant j} \mid \mathsf{B}^{>j},\mathsf{D}^{>j},\mathsf{A},\mathsf{C})}{m^2}.$$

This is proven by induction. The base case is easy to see: note that $\mu(\mathsf{Z}_1 \mid \mathsf{E}_1,\Pi_1)=\mu(\mathsf{Z}_1)$ as Z_1 is independent of $\mathsf{E}_1=z_0$ which is fixed and Z_1 is independent of Π_1 as Π_1 is a function of (C,D). We obtain case j from case $j-1$ in two steps: we first show that if the protocol reveals a lot of information about the variable Z_j, then it must essentially be ε-solving a *uniformly random instance*. This is because $Z_j = T_{Z_{j-1}}$ and Z_{j-1} is, under the inductive case $j-1$, close to uniform. We then appeal to the previous lemma.

Proof. The information—measured by Λ-distance to uniform—that the j-th round of the protocol reveals about $\mathsf{Z}_j = \mathsf{T}_{\mathsf{Z}_{j-1}}$ is the information revealed about an instance sampled according to Z_{j-1}:

$$\begin{aligned}\mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)}\left[\Lambda(\mu(\mathsf{Z}_j \mid \mathsf{E}_j,\Pi_j),\mu(\mathsf{Z}_j))\right] &= \mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)}\left[\Lambda(\mu(\mathsf{Z}_j \mid \mathsf{E}_j),\mu(\mathsf{Z}_j))\right] \\ &= \mathop{\mathbb{E}}_{(\mathsf{Z}_{<j},\Pi_{<j})}\left[\Lambda(\mu(\mathsf{Z}_j \mid \mathsf{Z}_{<j},\Pi_{<j}),\mu(\mathsf{Z}_j))\right] \\ &\qquad \text{(by definition of } \mathsf{E}_j := (\mathsf{Z}_{<j},\Pi_{<j}), \text{ and since } \mathsf{Z}_j \text{ and } \Pi_j \text{ are independent given } \mathsf{E}_j.) \\ &= \mathop{\mathbb{E}}_{(\mathsf{Z}_{<j},\Pi_{<j})}\left[\Lambda(\mu(\mathsf{T}^j_{\mathsf{Z}_{j-1}} \mid \mathsf{Z}_{<j-1},\mathsf{Z}_{j-1},\Pi_{<j}),\mu(\mathsf{Z}_j))\right] \\ &\qquad\qquad \text{(by definition, the pointer } Z_j = T_{Z_{j-1}}) \\ &= \mathop{\mathbb{E}}_{(\mathsf{Z}_{<j-1},\Pi_{<j})} \mathop{\mathbb{E}}_{z\sim\mathsf{Z}_{j-1}\mid(\mathsf{Z}_{<j-1},\Pi_{<j})}\left[\Lambda(\mu(\mathsf{T}^j_z \mid \mathsf{Z}_{<j-1},\Pi_{<j}),\mu(\mathsf{Z}_j))\right].\end{aligned}$$

We removed the conditioning on $\mathsf{Z}_{j-1}=z$ in the first distribution because, conditioned on knowing $\mathsf{Z}_{<j-1},\Pi_{<j}$, for any fixed value of z the value of T_z is independent of the value of Z_{j-1}:

- If $j-1$ is odd, T_z is a function of (C,D) and Z_{j-1} is a function of (A,B).
- If $j-1$ is even, T_z is a function of (A,B) and Z_{j-1} is a function of (C,D).
- And, furthermore, (A,B) and (B,D) are independent given $\mathsf{Z}_{<j-1},\Pi_{<j}$.

[1] Intuitively, the statement says that, if π_{BMHPC} communicates little, then the distribution of Z_j, conditioned on the information available at the end of round j, is close to uniform.

Lemma 4.8 says that if the protocol were to reveal information about the solution T_z of a truly uniform instance z, then this would give us a protocol for ε-solving set disjointness. But, by induction, we know that the chosen instance $z \sim \mathsf{Z}_{j-1}$ is close to uniform. It should then follow from Proposition 3.9 that if the protocol reveals some information about this almost uniform instance, it must also reveal information about a truly uniform instance. Let us now make this precise.

Without loss of generality suppose that $j-1$ is odd and hence $z \in \mathcal{Y}$. Then we can upper bound the last expression above by:[2]

$$
\begin{aligned}
&\mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)}\Big[\Lambda(\mu(\mathsf{Z}_j \mid \mathsf{E}_j,\Pi_j),\mu(\mathsf{Z}_j))\Big] \\
&\quad\leqslant \mathop{\mathbb{E}}_{(\mathsf{Z}_{<j-1},\Pi_{<j})}\left[6\cdot \mathop{\mathbb{E}}_{(z\sim\mathcal{U}_\mathcal{Y})}\Big[\Lambda(\mu(\mathsf{T}^j_z \mid \mathsf{Z}_{<j-1},\Pi_{<j}),\mu(\mathsf{Z}_j))\Big]\right] \\
&\qquad\qquad + \mathop{\mathbb{E}}_{(\mathsf{Z}_{<j-1},\Pi_{<j})}\Big[\Lambda(\mu(\mathsf{Z}_{j-1} \mid \mathsf{E}_{j-1},\Pi_{j-1}),\mathcal{U}_\mathcal{Y})\Big] \\
&\qquad\qquad\qquad\qquad \text{(by Proposition 3.9 and linearity of expectatiom)} \\
&\quad= 6\cdot \mathop{\mathbb{E}}_{(\mathsf{Z}_{<j-1},\Pi_{<j})}\left[\mathop{\mathbb{E}}_{(z\sim\mathcal{U}_\mathcal{Y})}\Big[\Lambda(\mu(\mathsf{T}^j_z \mid \mathsf{Z}_{<j-1},\Pi_{<j}),\mu(\mathsf{Z}_j))\Big]\right] \\
&\qquad\qquad + \mathop{\mathbb{E}}_{(\mathsf{Z}_{<j-1},\Pi_{<j})}\Big[\Lambda(\mu(\mathsf{Z}_{j-1} \mid \mathsf{E}_{j-1},\Pi_{j-1}),\mu(\mathsf{Z}_{j-1}))\Big] \\
&\qquad\qquad\qquad\qquad \text{(by definition } z_{j-1}\in\mathcal{Y} \text{ and } \mu(\mathsf{Z}_{j-1})=\mathcal{U}_\mathcal{Y}.) \\
&\quad\leqslant \Bigg[6\cdot \underbrace{c\cdot\frac{\mathbb{I}(\Pi;\mathsf{A}^j \mid \mathsf{A}^{<j},\mathsf{B})+\mathbb{I}(\Pi;\mathsf{B}^j \mid \mathsf{B}^{>j},\mathsf{A})}{m^2}}_{\text{Lemma 4.8}} \\
&\qquad + \underbrace{6c\cdot\frac{\mathbb{I}(\Pi;\mathsf{A}^{\leqslant j-1},\mathsf{C}^{\leqslant j-1} \mid \mathsf{B},\mathsf{D})+\mathbb{I}(\Pi;\mathsf{B}^{\leqslant j-1},\mathsf{D}^{\leqslant j-1} \mid \mathsf{B}^{>j-1},\mathsf{D}^{>j-1},\mathsf{A},\mathsf{C})}{m^2}}_{\text{induction hypothesis (case } j-1)}\Bigg] \\
&\quad= \Bigg[6c\cdot\frac{\mathbb{I}(\Pi;\mathsf{A}^j \mid \mathsf{A}^{<j},\mathsf{C}^{<j},\mathsf{B},\mathsf{D})+\mathbb{I}(\Pi;\mathsf{B}^j \mid \mathsf{B}^{>j},\mathsf{D}^{>j},\mathsf{A},\mathsf{C})}{m^2} \\
&\qquad + 6c\cdot\frac{\mathbb{I}(\Pi;\mathsf{A}^{\leqslant j-1},\mathsf{C}^{\leqslant j-1} \mid \mathsf{B},\mathsf{D})+\mathbb{I}(\Pi;\mathsf{B}^{\leqslant j-1},\mathsf{D}^{\leqslant j-1} \mid \mathsf{B}^{>j-1},\mathsf{D}^{>j-1},\mathsf{A},\mathsf{C})}{m^2}\Bigg] \\
&\quad\leqslant \Bigg[6c\cdot\frac{\mathbb{I}(\Pi;\mathsf{A}^j,\mathsf{C}^j \mid \mathsf{A}^{<j},\mathsf{C}^{<j},\mathsf{B},\mathsf{D})+\mathbb{I}(\Pi;\mathsf{B}^j,\mathsf{D}^j \mid \mathsf{B}^{>j},\mathsf{D}^{>j},\mathsf{A},\mathsf{C})}{m^2} \\
&\qquad + 6c\cdot\frac{\mathbb{I}(\Pi;\mathsf{A}^{\leqslant j-1},\mathsf{C}^{\leqslant j-1} \mid \mathsf{B},\mathsf{D})+\mathbb{I}(\Pi;\mathsf{B}^{\leqslant j-1},\mathsf{D}^{\leqslant j-1} \mid \mathsf{B}^{>j-1},\mathsf{D}^{>j-1},\mathsf{A},\mathsf{C})}{m^2}\Bigg] \\
&\quad= 6c\cdot\frac{\mathbb{I}(\Pi;\mathsf{A}^{\leqslant j},\mathsf{C}^{\leqslant j} \mid \mathsf{B},\mathsf{D})+\mathbb{I}(\Pi;\mathsf{B}^{\leqslant j},\mathsf{D}^{\leqslant j} \mid \mathsf{B}^{>j},\mathsf{D}^{>j},\mathsf{A},\mathsf{C})}{m^2},
\end{aligned}
$$

where the last inequality follows from the data processing inequality (Fact D.2 Item 8). This concludes the proof. □

[2] In the first inequality it should be understood how Λ is playing two different roles. On the one hand it is being used as an information-theoretic quantity (the distance to uniform), and on the other it is being used in a capacity similar to how total variation distance appears in the obvious upper-bound $\mathbb{E}_\mu[f(x)] \leqslant \mathbb{E}_\nu[f(x)] + \|\mu-\nu\|_1 \cdot \max f(x)$.

4.4 ε-Solvers for Set-Int Give Exact Solvers

We now show a lower-bound against protocols trying to ε-solve Set-Intersection, by reducing from exactly solving Set-Intersection:

Theorem 4.12. *For any constant $\gamma \in (0,1)$, there exists a constant $c \geqslant 1$ such that, given a protocol $\pi_{\mathsf{Set\text{-}Int}}$ which internally ε-solves Set-Intersection (in Λ distance) on $\mathcal{D}_{\mathsf{Set\text{-}Int}}$ with $\varepsilon \geqslant \frac{8}{m}$, we may obtain a protocol π that exactly solves Set-Intersection on $\mathcal{D}_{\mathsf{Set\text{-}Int}}$, such that $\mathsf{IC}_{\mathcal{D}_{\mathsf{Set\text{-}Int}}}(\pi) \leqslant \frac{c}{\varepsilon} \cdot \mathsf{IC}_{\mathcal{D}_{\mathsf{Set\text{-}Int}}}(\pi_{\mathsf{Set\text{-}Int}}) + \gamma m$.*

From the known fact (Proposition 3.2) that Set-Intersection has information complexity $\Omega(m)$ on $\mathcal{D}_{\mathsf{Set\text{-}Int}}$ we get the following:

Corollary 4.13. *There exists a constant $c > 0$ such that any protocol $\pi_{\mathsf{Set\text{-}Int}}$ that internally (Λ, ε)-solves SetInt_m on inputs from the distribution $\mathcal{D}_{\mathsf{Set\text{-}Int}}$, with $\varepsilon \geqslant 8/m$, has $\mathsf{IC}_{\mathcal{D}_{\mathsf{Set\text{-}Int}}}(\pi_{\mathsf{Set\text{-}Int}}) \geqslant c \cdot \varepsilon m$.*

An analogue of Theorem 4.12 was proven in [AR20], where ε-solving was with respect to total variation distance instead of triangular discrimination. It was then shown that any protocol for ε-solving Set-Intersection in this TVD sense gives a protocol for Set-Intersection with a $O(1/\varepsilon^2)$ blowup in information cost. Theorem 4.12, instead, gives a blowup of $O(1/\varepsilon)$. So our assumption is stronger, but our conclusion is also stronger.

Proof of Theorem 4.12. We begin by recalling the notation we use for the Set-Intersection problem: Alice and Bob's input sets are denoted by X and Y respectively, and their corresponding random variables by X and Y. The unique element in the intersection $X \cap Y$ is denoted by e^*, and its random variable is e^*. Throughout this proof, for a permutation σ and a set S, $\sigma(S)$ denotes the set $\{\sigma(s) \mid s \in S\}$.
Without loss of generality, we may assume that we have a protocol $\pi_{\mathsf{Set\text{-}Int}}$ that internally ε-solves from *Alice*'s side Set-Intersection on inputs distributed according to $\mathcal{D}_{\mathsf{Set\text{-}Int}}$, that is,

$$\mathbf{\Lambda} = \mathop{\mathbb{E}}_{\mathsf{X},\mathsf{\Pi}}[\Lambda(\mu(\mathsf{e}^* \mid \mathsf{\Pi}, \mathsf{X}), \mu(\mathsf{e}^*, \mathsf{X}))] \geqslant \varepsilon,$$

where $\varepsilon \geqslant 8/m$. We will use $\pi_{\mathsf{Set\text{-}Int}}$ to design a protocol π which solves Set-Intersection on $\mathcal{D}_{\mathsf{Set\text{-}Int}}$.

For now, suppose that Alice and Bob proceed as follows: they sample a uniformly random permutation Γ of $[m]$ using public randomness, and run the ε-solving protocol $\pi_{\mathsf{Set\text{-}Int}}$ on $(\Gamma(X), \Gamma(Y))$, obtaining a transcript Π. Alice now knows the induced distribution of the intersection point $\mu(\mathsf{\Gamma}(e^*) \mid \mathsf{\Pi} = \Pi, \mathsf{\Gamma}(X) = \Gamma(X))$, conditioned on the transcript she has seen, and Bob knows the analogous distribution with his input fixed. Without the conditioning on the transcript, we know by symmetry of $\mathcal{D}_{\mathsf{Set\text{-}Int}}$ that $\mu(\mathsf{\Gamma}(e^*) \mid \mathsf{\Gamma}(X) = \Gamma(X))$ is uniform over $\Gamma(X)$. In fact, we have the following observation about the distribution of inputs generated by applying $\mathsf{\Gamma}$.

Observation 4.14. *For any fixed X and Y such that $|X| = |Y| = m/4$, and $|X \cap Y| = 1$, and a uniformly random permutation $\mathsf{\Gamma}$, the instance $(\mathsf{\Gamma}(X), \mathsf{\Gamma}(Y))$ is distributed according to $\mathcal{D}_{\mathsf{Set\text{-}Int}}$.*

To see this, consider the fixed values $X = \{1, \ldots m/4\}$ and $Y = \{m/4, \ldots m/2 - 1\}$. Because $\mathsf{\Gamma}$ is a uniformly random permutation, it maps $m/4$ to a uniformly random element of $[m]$, and the rest of X and Y to uniformly random subsets of size $m/4 - 1$. By symmetry, this argument applies to any fixed X and Y of size $m/4$ intersecting in exactly one element.

4.4.1 A single round of π

We start by describing a single round of the protocol π. On the input (X, Y):

1. Alice and Bob publicly sample a random permutation Γ of $[m]$, and apply it to X and Y to obtain $\Gamma(X)$ and $\Gamma(Y)$ respectively.
2. They run $\pi_{\mathsf{Set\text{-}Int}}$ on $\Gamma(X)$ and $\Gamma(Y)$ to obtain a transcript Π. By doing so, Alice learns a distribution $q_1^\Pi, \ldots, q_m^\Pi$, where
$$q_i^\Pi = \Pr[\mathsf{\Gamma}(e^*) = i \mid \mathsf{\Pi} = \Pi, \mathsf{\Gamma}(X) = \Gamma(X)].$$
3. Alice uses q^Π to assign "scores" to each element e of $[m]$, which reflect the likelihood that $\{e\}$ is the intersection of X and Y.

This strategy follows the general idea of [AR20], but where they assigned the score 1 to all e such that $q^\Pi_{\Gamma(e)}$ is in the largest-probability half of $q_1^\Pi, \ldots, q_m^\Pi$ (and this works for ε-solving under TVD), we assign scores in a smoother fashion. Let $i = \Gamma(e)$ and $n = m/4$ for brevity. Then if $q_i^\Pi \leqslant 1/n$, we give e a score of 0. Otherwise, its score is $(q_i^\Pi - 1/n)/(q_i^\Pi + 1/n)$. This choice of the "scoring function" may seem odd at this juncture, so we offer two comments about it:

- Note that this is equal to $1 - (2/n)/(q_i^\Pi + 1/n)$, which is an increasing function of q_i^Π, and hence passes a basic sanity test (i.e. if $\pi_{\mathsf{Set\text{-}Int}}$ says an element is more likely to be $\Gamma(e^*)$, we believe it).
- The scoring function was chosen to make the expected score of e^* larger than the expected score of any non-e^* element by at least $\mathbf{\Lambda}$, and the variance of every element's score turned out to be small.

We package the properties of this scoring function into a few claims below. Throughout these claims, we will use the shorthand notation $\mathsf{A} \mid B$ to mean $\mathsf{A} \mid \mathsf{B} = B$, where A and B are random variables, and B is some fixed value that B can take.

Claim 4.15. *For any non-e^* element $e \in [m]$,*
$$\mathop{\mathbb{E}}_{\mathsf{\Gamma}}[\mathsf{Score}(e^*) - \mathsf{Score}(e)] \geqslant \mathbf{\Lambda}/2.$$

Proof. The proof is in two parts; first we bound $\mathsf{Score}(e^*)$ under some appropriate conditioning, and then $\mathsf{Score}(e)$ for non-e^* elements.
Fix any (X, Y) with $|X| = |Y| = n$ and $|X \cap Y| = 1$. Consider a fixed choice of $\Gamma(X)$ and the transcript Π, and hence a distribution q^Π. Let P denote the set of indices where $q_i^\Pi > 1/n$ (i.e. those that lead to positive scores). Note that $P \subseteq \Gamma(X)$; because we condition on $\Gamma(X)$ (and more) to obtain q^Π. By definition, the probability that e^* is mapped to i is q_i, and hence:
$$\mathop{\mathbb{E}}_{\mathsf{\Gamma} \mid \Gamma(X), \Pi}[\mathsf{Score}(e^*)] = \sum_{i \in P} q_i^\Pi \cdot \frac{q_i^\Pi - 1/n}{q_i^\Pi + 1/n}.$$
On the other hand, fixing both $\Gamma(X)$, $\Gamma(Y)$ (and hence also $\Gamma(e^*)$) and Π, fixes the distribution q^Π, but leaves completely free the map $\Gamma : X \setminus \{e^*\} \to \Gamma(X) \setminus \{\Gamma(e^*)\}$. So we find that:
$\mathsf{\Gamma}(e)$ is uniformly random over $\Gamma(X) \setminus \{\Gamma(e^*)\}$ for any non-e^* element $e \in X$.
This means that for any $i \in [m]$,
$$\Pr_{\mathsf{\Gamma} \mid \Gamma(X), \Gamma(Y), \Pi}[\mathsf{\Gamma}(e) = i] \leqslant \frac{1}{n-1}.$$

Hence we can compute the expected score of e as:

$$\begin{aligned}\mathop{\mathbb{E}}_{\mathsf{\Gamma}|\Gamma(X),\Gamma(Y),\Pi}[\mathsf{Score}(e)] &= \sum_{i\in P}\Pr[\mathsf{\Gamma}(e)=i]\cdot\frac{q_i^\Pi-1/n}{q_i^\Pi+1/n} \leqslant \sum_{i\in P}\frac{1}{n-1}\cdot\frac{q_i^\Pi-1/n}{q_i^\Pi+1/n}\\ &= \sum_{i\in P}\left(\frac{1}{n}+\frac{1}{n(n-1)}\right)\cdot\frac{q_i^\Pi-1/n}{q_i^\Pi+1/n} \leqslant \frac{1}{n}+\sum_{i\in P}\frac{1}{n}\cdot\frac{q_i^\Pi-1/n}{q_i^\Pi+1/n},\end{aligned}$$

where the last inequality follows because $|P|\leqslant n-1$. And now taking expectation over $\Gamma(X)$ and Π:

$$\begin{aligned}\mathop{\mathbb{E}}_{\mathsf{\Gamma}(X),\mathsf{\Pi}}\mathop{\mathbb{E}}_{\mathsf{\Gamma}|\mathsf{\Pi},\mathsf{\Gamma}(X)}[\mathsf{Score}(e^*)-\mathsf{Score}(e)] &= \mathop{\mathbb{E}}_{\mathsf{\Gamma}(X),\mathsf{\Pi}}\left[\mathop{\mathbb{E}}_{\mathsf{\Gamma}|\mathsf{\Pi},\mathsf{\Gamma}(X)}[\mathsf{Score}(e^*)]-\mathop{\mathbb{E}}_{\mathsf{\Gamma}(Y)|\mathsf{\Pi},\mathsf{\Gamma}(X)}\mathop{\mathbb{E}}_{\mathsf{\Gamma}|\mathsf{\Gamma}(X),\mathsf{\Gamma}(Y)}[\mathsf{Score}(e)]\right]\\ &\geqslant \mathop{\mathbb{E}}_{\mathsf{\Gamma}(X),\mathsf{\Pi}}\left[\sum_{i\in P}\frac{\left(q_i^\Pi-1/n\right)^2}{q_i^\Pi+1/n}-1/n\right]\\ &= \mathop{\mathbb{E}}_{\mathsf{\Gamma}(X),\mathsf{\Pi}}\left[\Lambda(q^\Pi,\mathcal{U}_{\Gamma(X)})\right]-1/n = \mathbf{\Lambda}-1/n \geqslant \mathbf{\Lambda}/2.\end{aligned}$$

where the last inequality is because $\mathbf{\Lambda}\geqslant\varepsilon\geqslant 8/m = 2/n$.

□

Claim 4.16. *The variance of* $\mathsf{Score}(e^*)$ *is at most* $\mathbf{\Lambda}$.

Proof. Recall that $\mathrm{Var}[X]\leqslant\mathbb{E}[X^2]$ for any random variable X. As before, we will bound $\mathbb{E}[\mathsf{Score}(e^*)]$ by conditioning on fixed choices of $\Gamma(X)$ and the transcript Π, which gives Alice the distribution q^Π. Also as before, let P denote the set of indices i such that $q_i\geqslant 1/n$.

$$\begin{aligned}\mathop{\mathbb{E}}_{\mathsf{\Gamma}|\Gamma(X),\Pi}\left[\mathsf{Score}(e^*)^2\right] &= \sum_{i\in P}q_i^\Pi\cdot\left(\frac{q_i^\Pi-1/n}{q_i^\Pi+1/n}\right)^2\\ &= \sum_{i\in P}\frac{q_i^\Pi}{q_i^\Pi+1/n}\cdot\frac{(q_i^\Pi-1/n)^2}{q_i^\Pi+1/n}\\ &\leqslant \Lambda(q^\Pi,\mathcal{U}_{\Gamma(X)}).\end{aligned}$$

And taking expectation over $\Gamma(X)$ and Π:

$$\mathop{\mathbb{E}}_{\mathsf{\Gamma}(X),\mathsf{\Pi}}\mathop{\mathbb{E}}_{\mathsf{\Gamma}|\mathsf{\Gamma}(X),\mathsf{\Pi}}\left[\mathsf{Score}(e^*)^2\right]\leqslant\mathop{\mathbb{E}}_{\mathsf{\Gamma}(X),\mathsf{\Pi}}\left[\Lambda(q^\Pi,\mathcal{U}_{\mathsf{\Gamma}(X)})\right]=\mathbf{\Lambda}.$$

□

Claim 4.17. *For any* $e(\neq e^*)\in X$, *the variance of* $\mathsf{Score}(e)$ *is at most* $2\mathbf{\Lambda}$.

Proof. Again, because $\mathrm{Var}[X]\leqslant\mathbb{E}[X^2]$ for any random variable X, and conditioning on fixed choices of $\Gamma(X),\Gamma(Y)$ and Π, $\mathsf{\Gamma}(e)$ for $e\in X\setminus\{e^*\}$ is uniformly random over $\Gamma(X\setminus\{e^*\})$:

$$\begin{aligned}\mathop{\mathbb{E}}_{\mathsf{\Gamma}|\Gamma(X),\Gamma(Y),\Pi}\left[\mathsf{Score}(e)^2\right] &= \sum_{i\in P}\frac{1}{n-1}\cdot\left(\frac{q_i^\Pi-1/n}{q_i^\Pi+1/n}\right)^2\\ &\leqslant \sum_{i\in P}\frac{1}{n-1}\cdot\frac{\left(q_i^\Pi-1/n\right)^2}{q_i^\Pi+1/n}\cdot\frac{1}{1/n}\\ &= \Lambda\big(q^\Pi,\mathcal{U}_{\Gamma(X)}\big)\cdot\left(1+\frac{1}{n-1}\right)\leqslant 2\Lambda\big(q^\Pi,\mathcal{U}_{\Gamma(X)}\big),\end{aligned}$$

where the first inequality holds because $q_i^{\Pi} \geqslant 0$. And taking expectation over $\Gamma(X), \Gamma(Y)$ and Π:

$$\mathop{\mathbb{E}}_{\Gamma(X),\Pi}\left[\mathop{\mathbb{E}}_{\Gamma(Y)|\Gamma(X),\Pi}\left[\mathop{\mathbb{E}}_{\Gamma|\Gamma(X),\Gamma(Y),\Pi}\left[\mathsf{Score}(e)^2\right]\right]\right] \leqslant \mathop{\mathbb{E}}_{\Gamma(X),\Pi}\left[2\Lambda\left(q^{\Pi}, \mathcal{U}_{\Gamma(X)}\right)\right] = 2\boldsymbol{\Lambda}.$$

□

4.4.2 The actual protocol

We are ready to describe the protocol π. Let $\gamma \in (0,1)$ be any constant. We will run $k = 1600/(\varepsilon\gamma^2)$ (independent) rounds of the protocol in Section 4.4.1, and for each element $e \in X$, Alice will add up its scores in each round to obtain the total score $\mathsf{TScore}(e)$. Claim 4.15 tells us that we should expect the total score for e^* to be higher than the total score of an element $e \neq e^*$. We then choose the threshold

$$\tau = \left(\mathbb{E}[\mathsf{TScore}(e^*)] + \mathbb{E}[\mathsf{TScore}(e)]\right)/2,$$

to be exactly in the middle of these two expected values.

Alice will then send to Bob all elements in X which have TScore at least τ; let us call this set S. Bob will then compute the intersection $S \cap Y$, and report the unique element that is (hopefully) present there as the answer.

To complete the reduction, we need to show that:

- The total score of the target element $\mathsf{TScore}(e^*)$ is at least τ. This will ensure that $e^* \in S$, which means that π is correct.
- The number of elements Alice sends is *small*. This is required to control the information cost of π.

We will get both of these properties only with some (constant) high probability; in particular, if S is too large, Alice will just report failure instead of communicating S.

Claim 4.18. *$\mathsf{TScore}(e^*) \leqslant \tau$ with probability at most $1/100$.*

Proof. Using Chebyshev's inequality on the total score of e^*, we have:

$$\begin{aligned}
&\Pr\left[\left|\mathsf{TScore}(e^*) - \mathbb{E}[\mathsf{TScore}(e^*)]\right| > 1/2 \cdot \mathbb{E}[\mathsf{TScore}(e^*) - \mathsf{TScore}(e)]\right] \\
&\quad\leqslant \frac{\mathrm{Var}[\mathsf{TScore}(e^*)]}{(1/2 \cdot \mathbb{E}[\mathsf{TScore}(e^*) - \mathsf{TScore}(e)])^2} = \frac{k \cdot \mathrm{Var}[\mathsf{Score}(e^*)]}{k^2/4 \cdot \mathbb{E}[\mathsf{Score}(e^*) - \mathsf{Score}(e)]^2} \\
&\quad\leqslant \frac{4\boldsymbol{\Lambda}}{k \cdot (\boldsymbol{\Lambda}/2)^2} \leqslant 16/k\varepsilon = \gamma^2/100,
\end{aligned}$$

where the second inequality follows from Claims 4.15 and 4.16. Hence the probability that $\mathsf{TScore}(e^*)$ is less than τ is at most $1/100$. □

Claim 4.19. *For any non-e^* element $e \in X$, $\mathsf{TScore}(e) \geqslant \tau$ with probability at most $\gamma^2/50$.*

Proof. Using Chebyshev on the total score of $e \neq e^*$, we have:

$$\begin{aligned}
&\Pr\Big[\Big|\mathsf{TScore}(e) - \mathbb{E}[\mathsf{TScore}(e)]\Big| > 1/2 \cdot \mathbb{E}[\mathsf{TScore}(e^*) - \mathsf{TScore}(e)]\Big] \\
&\quad\leqslant \frac{\mathrm{Var}[\mathsf{TScore}(e)]}{(1/2 \cdot \mathbb{E}[\mathsf{TScore}(e^*) - \mathsf{TScore}(e)])^2} = \frac{k \cdot \mathrm{Var}[\mathsf{Score}(e)]}{k^2/4 \cdot \mathbb{E}[\mathsf{Score}(e^*) - \mathsf{Score}(e)]^2} \\
&\quad\leqslant \frac{4 \cdot 2\boldsymbol{\Lambda}}{k \cdot (\boldsymbol{\Lambda}/2)^2} \leqslant 32/k\varepsilon = \gamma^2/50,
\end{aligned}$$

where the second inequality follows from Claims 4.15 and 4.17. □

This means that the expected size of $S \setminus \{e^*\}$ is at most $\gamma^2 m/50$, and hence by Markov's this number is $> \gamma^2 m/10$ with probability $\leqslant 1/5$. If the number of elements above the threshold exceeds $\gamma^2 m/10 + 1$, then the protocol π fails.

And now we have everything we need to bound the information cost of π. Note that this part of the argument is exactly as in [AR20]. By the chain rule of mutual information, the information cost of π on $\mathcal{D}_{\mathsf{Set\text{-}Int}}$ can be broken down into three components:

- The mutual information $\mathbb{I}(\Gamma_1, \ldots, \Gamma_k, R_1, \ldots, R_k; \mathsf{X} \mid \mathsf{Y})$ and the symmetric term with X and Y exchanging roles, where Γ_i denotes the random permutations used to scramble the input in the $i-$th round of π, and R_i denotes the randomness of the i-th run of $\pi_{\mathsf{Set\text{-}Int}}$. These are both 0, because the permutations and the randomness are chosen independently of the inputs X and Y.

- The mutual information $\mathbb{I}(\Pi_1, \ldots, \Pi_k; \mathsf{X} \mid \mathsf{Y}, \Sigma, \mathsf{R})$ (and the symmetric term with X and Y swapped), where $\Pi_1, \ldots, \Pi_k$ denote the transcripts of the k runs of $\pi_{\mathsf{Set\text{-}Int}}$, $\Sigma = \Gamma_1, \ldots, \Gamma_k$, and $\mathsf{R} = R_1, \ldots, R_k$. By the chain rule of mutual information, we have:

  $$\mathbb{I}(\Pi_1, \ldots, \Pi_k; \mathsf{X} \mid \mathsf{Y}, \Sigma, \mathsf{R}) \leqslant \sum_{i=1}^{k} \mathbb{I}(\Pi_i; \mathsf{X} \mid \mathsf{Y}, \Sigma, \mathsf{R}, \Pi_{<i}).$$

  Observe that conditioning on X, Y, Γ_i, and R_i fixes Π_i, and hence makes it independent of $\Pi_{<i}$, Γ_{-i}, and R_{-i}. Applying Proposition D.4, we get that the i-th term of the sum above is upper bounded by $\mathbb{I}(\Pi_i; \mathsf{X} \mid \mathsf{Y}, \Gamma_i, R_i)$. But now (once again) Π_i is fixed after conditioning on $\Gamma_i(\mathsf{X})$, $\Gamma_i(\mathsf{Y})$, and R_i, and hence independent of the remaining parts of Γ_i and X and Y. So by Proposition D.4, each term in the sum is bounded above by $\mathbb{I}(\Pi_i; \Gamma_i(\mathsf{X}) \,|\, \Gamma(\mathsf{Y}), R_i)$. Repeating this entire argument for the symmetric term tells us that:

  $$\mathbb{I}(\Pi_1, \ldots, \Pi_k; \mathsf{X}|\mathsf{Y}, \Sigma, \mathsf{R}) + \mathbb{I}(\Pi_1, \ldots, \Pi_k; \mathsf{Y}|\mathsf{X}, \Sigma, \mathsf{R}) \leqslant \sum_{i=1}^{k} \mathbb{I}(\Pi_i; \Gamma_i(\mathsf{X})|\Gamma(\mathsf{Y}), R_i) + \mathbb{I}(\Pi_i; \Gamma_i(\mathsf{Y})|\Gamma(\mathsf{X}), R_i),$$

  which is exactly $k \cdot \mathsf{IC}^{\mathrm{int}}_{\mathcal{D}_{\mathsf{Set\text{-}Int}}}(\pi_{\mathsf{Set\text{-}Int}})$.

- The mutual information between the final set S Alice sends and her input. This is trivially upper bounded by $\mathbb{H}(\mathsf{S})$, which (since S is a set of size at most $\gamma^2 \cdot m/10$) is upper bounded by $H_2(\gamma^2/10) \cdot m$. Since $H_2(p) \leqslant 2\sqrt{p \cdot (1-p)} \leqslant 2\sqrt{p}$ (by Fact D.1), this is at most γm.

So letting $c = \frac{1600}{\gamma^2}$, we get that $\mathsf{IC}^{\mathrm{int}}_{\mathcal{D}_{\mathsf{Set\text{-}Int}}}(\pi) \leqslant \frac{c}{\varepsilon}\, \mathsf{IC}^{\mathrm{int}}_{\mathcal{D}_{\mathsf{Set\text{-}Int}}}(\pi_{\mathsf{Set\text{-}Int}}) + \gamma m$. □

Remark 4.20. The protocol π actually works in the worst case, that is, it needs no assumptions about X and Y other than $|X| = |Y| = m/4$, and that $|X \cap Y| = 1$. But of course without a distribution on its inputs we cannot talk about its information cost.

4.5 Short Protocols for BHPC Give Low-Information ε-Solvers for Set-Int

We also wish to prove a tight lower bound for $\mathsf{BHPC}_{m,r}$. Note that this lower-bound is not necessary to derive our lower-bounds for k-cores and degeneracy, so this section may be skipped for that purpose. The lower-bound ultimately follows from the following lemma, which is analogous to Lemma 4.11.

Lemma 4.21. *There is a constant $c > 0$ such that the following statement holds for all $j \in [r]$:*[3]

$$\mathsf{Hypothesis}_j: \quad \mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)} [\Lambda(\mu(\mathsf{Z}_j \mid \mathsf{E}_j, \Pi_j), \mu(\mathsf{Z}_j))] \leqslant j \cdot c \cdot \left(\frac{CC(\pi_{\mathsf{BHPC}}) + r \log m}{m^2} + \frac{r}{m} \right).$$

One can already see that the statement is more complicated. This is owed to the possibility of the pointers pointing either to some of the (few) instances about which the protocol has revealed information, and the possibility of the pointers looping. These two obstacles raise technical difficulties, which are overcome in two ways: the number of jumps r is assumed to be smaller than $\sqrt{m}$, so looping is unlikely, and there are only $O(m/r)$ instances about which the protocol could have revealed significant information, hence when hiding an instance of set-intersection in a random position, as we did before, it is unlikely we will hit such an instance.

As before, this is proven by induction. The base case $\mathsf{Hypothesis}_1$ is easy to see: note that $\mu(\mathsf{Z}_1 \mid \mathsf{E}_1, \Pi_1) = \mu(\mathsf{Z}_1)$ as Z_1 is independent of $\mathsf{E}_1 = z_0$ which is fixed and Z_1 is independent of Π_1 as Π_1 is a function if (C, D). We obtain $\mathsf{Hypothesis}_j$ from $\mathsf{Hypothesis}_{j-1}$ in two steps: we first show that if the protocol reveals a lot of information about the variable Z_j, then it must essentially be "almost-solving" a *uniformly random instance*. This is because $Z_j = T_{Z_{j-1}}$ and Z_{j-1} is, under $\mathsf{Hypothesis}_{j-1}$, close to uniform. We then show that this is impossible for a short protocol to do, namely:

Lemma 4.22. *There is a constant $c' > 0$ such that for any $j \in [r]$, we have:*

$$\mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)} \mathop{\mathbb{E}}_{x \sim \mathcal{U}_{\mathcal{X}}} [\Lambda(\mu(\mathsf{T}_x \mid \mathsf{E}_j, \Pi_j), \mu(\mathsf{T}_x))] \leqslant c' \cdot \left(\frac{CC(\pi_{\mathsf{BHPC}}) + r \log m}{m^2} + \frac{j}{m} \right)$$

$$\mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)} \mathop{\mathbb{E}}_{y \sim \mathcal{U}_{\mathcal{Y}}} [\Lambda(\mu(\mathsf{T}_y \mid \mathsf{E}_j, \Pi_j), \mu(\mathsf{T}_y))] \leqslant c' \cdot \left(\frac{CC(\pi_{\mathsf{BHPC}}) + r \log m}{m^2} + \frac{j}{m} \right).$$

We state the proof of Lemma 4.22 shortly. Before that, we show how Lemma 4.22 lets us complete the induction in order to prove Lemma 4.21. This also follows very closely to the analogous proof of [ACK19] where they showed it for total variation distance.

Proof of Lemma 4.21. The information—measured by Λ-distance to uniform—that the j-th round of the protocol reveals about $\mathsf{Z}_j = \mathsf{T}_{\mathsf{Z}_{j-1}}$ is the information revealed about an instance sampled

[3] Intuitively, the statement says that, if π_{BHPC} communicates little, then the distribution of Z_j, conditioned on the information available at the end of round j, is close to uniform.

according to Z_{j-1}:

$$\begin{aligned}
\mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)}\Big[\Lambda(\mu(\mathsf{Z}_j \mid \mathsf{E}_j,\Pi_j),\mu(\mathsf{Z}_j))\Big] &= \mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)}\Big[\Lambda(\mu(\mathsf{Z}_j \mid \mathsf{E}_j),\mu(\mathsf{Z}_j))\Big] \\
&= \mathop{\mathbb{E}}_{(\mathsf{Z}^{<j},\Pi^{<j})}\Big[\Lambda(\mu(\mathsf{Z}_j \mid \mathsf{Z}^{<j},\Pi^{<j}),\mu(\mathsf{Z}_j))\Big] \\
&\qquad \text{(by definition of } \mathsf{E}_j := (\mathsf{Z}^{<j},\Pi^{<j}), \text{ and since } \mathsf{Z}_j \text{ and } \Pi_j \text{ are independent given } \mathsf{E}_j.) \\
&= \mathop{\mathbb{E}}_{(\mathsf{Z}^{<j},\Pi^{<j})}\Big[\Lambda(\mu(\mathsf{T}_{\mathsf{Z}_{j-1}} \mid \mathsf{Z}^{<j-1},\mathsf{Z}_{j-1},\Pi^{<j}),\mu(\mathsf{Z}_j))\Big] \\
&\qquad \text{(by definition, the pointer } Z_j = T_{Z_{j-1}}) \\
&= \mathop{\mathbb{E}}_{(\mathsf{Z}^{<j-1},\Pi^{<j})}\ \mathop{\mathbb{E}}_{z\sim\mathsf{Z}_{j-1}|(\mathsf{Z}^{<j-1},\Pi^{<j})}\Big[\Lambda(\mu(\mathsf{T}_z \mid \mathsf{Z}^{<j-1},\Pi^{<j}),\mu(\mathsf{Z}_j))\Big].
\end{aligned}$$

We removed the conditioning on Z_{j-1} in the first distribution because, conditioned on knowing $\mathsf{Z}^{<j-1},\Pi^{<j}$, for any fixed value of z the value of T_z is independent of the value of Z_{j-1}:

- If $j-1$ is odd, T_z is a function of (C,D) and Z_{j-1} is a function of (A,B).
- If $j-1$ is even, T_z is a function of (A,B) and Z_{j-1} is a function of $(\boldsymbol{C},\boldsymbol{D})$.
- And, furthermore, (A,B) and (B,D) are independent given $\mathsf{Z}^{<j-1},\Pi^{<j}$.

Lemma 4.22 says that if the protocol were to reveal information about the solution T_z of a truly uniform instance z, then this would give us a protocol for ε-solving set disjointness. But, by induction, we know that the chosen instance $z \sim \mathsf{Z}_{j-1}$ is close to uniform. It should then follow from Proposition 3.9 that if the protocol reveals some information about this almost uniform instance, it must also reveal information about a truly uniform instance. Let us now make this precise.

Without loss of generality suppose that $j-1$ is odd and hence $z \in \mathcal{Y}$. Then we can upper bound the last expression above by:

$$\begin{aligned}
&\mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)}\Big[\Lambda(\mu(\mathsf{Z}_j \mid \mathsf{E}_j,\Pi_j),\mu(\mathsf{Z}_j))\Big] \\
&\quad\leqslant \mathop{\mathbb{E}}_{(\mathsf{Z}^{<j-1},\Pi^{<j})}\left[6\cdot\mathop{\mathbb{E}}_{(z\sim\mathcal{U}_\mathcal{Y})}\Big[\Lambda(\mu(\mathsf{T}_z \mid \mathsf{Z}^{<j-1},\Pi^{<j}),\mu(\mathsf{Z}_j))\Big]\right] \\
&\qquad\qquad + \mathop{\mathbb{E}}_{(\mathsf{Z}^{<j-1},\Pi^{<j})}\Big[\Lambda(\mu(\mathsf{Z}_{j-1} \mid \mathsf{E}_{j-1},\Pi_{j-1}),\mathcal{U}_\mathcal{Y})\Big] \\
&\qquad\qquad \text{(by Proposition 3.9 and linearity of expectatiom)} \\
&\quad= 6\cdot\mathop{\mathbb{E}}_{(\mathsf{Z}^{<j-1},\Pi^{<j})}\left[\mathop{\mathbb{E}}_{(z\sim\mathcal{U}_\mathcal{Y})}\Big[\Lambda(\mu(\mathsf{T}_z \mid \mathsf{Z}^{<j-1},\Pi^{<j}),\mu(\mathsf{Z}_j))\Big]\right] \qquad (*) \\
&\qquad\qquad + \mathop{\mathbb{E}}_{(\mathsf{Z}^{<j-1},\Pi^{<j})}\Big[\Lambda(\mu(\mathsf{Z}_{j-1} \mid \mathsf{E}_{j-1},\Pi_{j-1}),\mu(\mathsf{Z}_{j-1}))\Big] \\
&\qquad\qquad \text{(by definition } z_{j-1} \in \mathcal{Y} \text{ and } \mu(\mathsf{Z}_{j-1}) = \mathcal{U}_\mathcal{Y}.) \\
&\quad\leqslant 6\cdot\underbrace{c'\cdot\left(\frac{CC(\pi_{\mathsf{BHPC}})+r\log m}{m^2}+\frac{j}{m}\right)}_{\text{Lemma 4.22}} + \underbrace{(j-1)\cdot c\cdot\left(\frac{CC(\pi_{\mathsf{BHPC}})+r\log m}{m^2}+\frac{r}{m}\right)}_{\mathsf{Hypothesis}_{j-1}} \\
&\quad\leqslant j\cdot c\cdot\left(\frac{CC(\pi_{\mathsf{BHPC}})+r\log m}{m^2}+\frac{r}{m}\right) \\
&\qquad\qquad \text{(where we replaced } j\leqslant r \text{ by } r \text{ in the first term and set } c = 6c')
\end{aligned}$$

This concludes the proof. □

We now prove Lemma 4.22. The proof shows that any protocol that reveals information about the solution T_z to random instance z can be converted to a low-information protocol for externally ε-solving Set-Intersection. This will later be shown to be impossible. Let us state the lemma again:

Lemma 4.22. *There is a constant $c' > 0$ such that for any $j \in [r]$, we have:*

$$\mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)} \mathop{\mathbb{E}}_{x\sim\mathcal{U}_\mathcal{X}} [\Lambda(\mu(\mathsf{T}_x \mid \mathsf{E}_j, \Pi_j), \mu(\mathsf{T}_x))] \leqslant c' \cdot \left(\frac{CC(\pi_{\mathsf{BHPC}}) + r\log m}{m^2} + \frac{j}{m}\right)$$
$$\mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)} \mathop{\mathbb{E}}_{y\sim\mathcal{U}_\mathcal{Y}} [\Lambda(\mu(\mathsf{T}_y \mid \mathsf{E}_j, \Pi_j), \mu(\mathsf{T}_y))] \leqslant c' \cdot \left(\frac{CC(\pi_{\mathsf{BHPC}}) + r\log m}{m^2} + \frac{j}{m}\right).$$

Suppose towards a contradiction that this equation does not hold. We use π_{HPC} to design a protocol π_{SI} that can externally ε-solve the Set-Intersection problem (A_x, B_x) for a uniformly at random chosen $x \in \mathcal{X}$ and appropriately chosen $\varepsilon \in (0,1)$ to be determined later (see Definition 4.3 for the notion of ε-solving).

Protocol π_{SI}: The protocol for ε-solving Set-Int using a protocol π_{HPC} for $\mathsf{BHPC}_{m,r}$.
Input: An instance $(X, Y) \sim \mathcal{D}_{\text{Set-Int}}$ over the universe $\mathcal{Y}$ and a number $j \in [r]$.

1. **Sampling the instance.** Alice and Bob create an instance (A, B, C, D) of $\mathsf{BHPC}_{m,r}$ as follows:
   (a) Using public coins, Alice and Bob sample an index $i \in [m]$ uniformly at random, and Alice sets $A_{x_i} = X$ and Bob sets $B_{x_i} = Y$ using their given inputs in Set-Int.
   (b) Using public coins, Alice and Bob sample $A_{x_1}, \ldots, A_{x_{i-1}}$ from the A-side marginal of $\mathcal{D}_{\text{Set-Int}}$, and they sample $B_{x_{i+1}}, \ldots, B_{x_m}$ from the B-side marginal of $\mathcal{D}_{\text{Set-Int}}$.
   (c) Using private coins, Alice samples A_{x_r} for $r \in \{i+1, \ldots, n\}$ so that $(A_{x_r}, B_{x_r}) \sim \mathcal{D}_{\text{Set-Int}}$. Similarly Bob samples B_{x_ℓ} for $\ell \in \{1, \ldots, i-1\}$. This completes construction of $(\boldsymbol{A}, \boldsymbol{B})$.
   (d) Using public coins, Alice and Bob sample (C, D) completely from $\mathcal{D}_{\mathsf{BHPC}}$ (this is possible by Observation 4.6 as $(\mathsf{A}, \mathsf{B}) \perp (\mathsf{C}, \mathsf{D})$).
2. **Computing the answer.** For $q = 1$ to j, Alice and Bob do the following:
   (a) **Running protocol:** In round q, Alice and Bob run the round q of the protocol π_{BHPC} on the instance (A, B, C, D) by Alice playing P_A, Bob playing P_B, and both Alice and Bob simulating P_C and P_D with no communication (this is possible as both Alice and Bob know (C, D) entirely). Denote this transcript by Π_q.
   (b) **Fixing pointer:** Alice and Bob compute the pointer z_q using the fact that for any underlying instance $(A_x, B_x) \in (A, B) \setminus (A_{x_i}, B_{x_i})$ either Alice or Bob knows the entire instance. We use Π^* to denote the cumulative transcript generated by this step in all rounds.
   (c) They stop if $x_i = z_q$.
3. The players return $\Pi_{\text{Set-Int}} := (\Pi_1, \ldots, \Pi_j, \Pi^*)$ from which $\mu(e^*)$ is calculated.

First, we show that the internal information cost of this protocol is small if the communication cost of Π_{BHPC} is small. This uses standard direct sum argument of information complexity. More concretely, we have the following:

Claim 4.23. $\mathsf{IC}_{\mathcal{D}}(\pi_{\mathsf{Set\text{-}Int}}) = O\left(\frac{CC(\pi_{\mathsf{BHPC}})}{m} + \frac{j \log m}{m}\right)$.

The proof of Claim 4.23 is similar to that of Claim 5.6 of [ACK19]. We defer it to the Section C. At this point, we also need a bound on how well $\Pi_{\mathsf{Set\text{-}Int}}$ can "almost" solve Set-Intersection. To this end, we have the following guarantee.

Claim 4.24. $\pi_{\mathsf{Set\text{-}Int}}$ *externally* ε*-solves Set-Intersection on* $\mathcal{D}$ *where:*

$$\varepsilon \geqslant \mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)} \mathop{\mathbb{E}}_{x\sim\mathcal{U}_{\mathcal{X}}} [\Lambda(\mu(\mathsf{T}_x \mid \mathsf{E}_j, \Pi_j), \mu(\mathsf{T}_x))] - \frac{j}{m}.$$

Proof. This proof follows the proof of Claim 5.5 of [ACK19] almost verbatim. The only change is that we are working with positive triangular discrimination (Λ) instead of the total variation distance (Δ_{TVD}). However, as Λ is bounded by Δ_{TVD} (Proposition 3.8), a similar calculation yields the claim. By Definition 4.3, $\varepsilon = \mathbb{E}_{\Pi_{\mathsf{Set\text{-}Int}}}[\Lambda(\mu(\mathsf{T} \mid \Pi_{\mathsf{Set\text{-}Int}}), \mu(\mathsf{T}))]$. So we have:

$$\begin{aligned}
\mathop{\mathbb{E}}_{\Pi_{\mathsf{Set\text{-}Int}}} [\Lambda(\mu(\mathsf{T} \mid \Pi_{\mathsf{Set\text{-}Int}}), \mu(\mathsf{T}))] &= \mathop{\mathbb{E}}_{\mathsf{E}_j,\Pi_j,\Pi^*,\mathsf{I}} [\Lambda(\mu(\mathsf{T}_{x_\mathsf{I}} \mid \Pi_{\mathsf{Set\text{-}Int}}), \mu(\mathsf{T}_{x_\mathsf{I}}))] && (\text{as } \mathsf{T} = \mathsf{T}_{x_\mathsf{I}}) \\
&= \mathop{\mathbb{E}}_{\mathsf{E}_j,\Pi_j} \mathop{\mathbb{E}}_{\mathsf{I}} \mathop{\mathbb{E}}_{\Pi^*|\mathsf{E}_j,\Pi_j,\mathsf{I}} [\Lambda(\mu(\mathsf{T}_{x_\mathsf{I}} \mid \Pi_{\mathsf{Set\text{-}Int}}), \mu(\mathsf{T}_{x_i}))] && (\text{as } \mathsf{I} \text{ is independent of } (\mathsf{E}_j, \Pi_j)) \\
&= \mathop{\mathbb{E}}_{\mathsf{E}_j,\Pi_j} \left[\sum_i \frac{1}{m} \mathop{\mathbb{E}}_{\Pi^*|\mathsf{E}_j,\Pi_j,\mathsf{I}=i} [\Lambda(\mu(\mathsf{T}_{x_i} \mid \Pi_{\mathsf{Set\text{-}Int}}), \mu(\mathsf{T}_{x_i}))] \right] && (\text{as } \mathsf{I} \sim \mathcal{U}_{[m]}) \\
&= \mathop{\mathbb{E}}_{\mathsf{E}_j,\Pi_j} \left[\sum_{x_i \in \mathsf{Z}^{<j}} \frac{1}{m} \Lambda(\mu(\mathsf{T}_{x_i} \mid \Pi_{\mathsf{Set\text{-}Int}}), \mu(\mathsf{T}_{x_i})) + \sum_{x_i \notin \mathsf{Z}^{<j}} \frac{1}{m} \Lambda(\mu(\mathsf{T}_{x_i} \mid \mathsf{E}_j, \Pi_j), \mu(\mathsf{T}_{x_i})) \right] \\
& && (\text{If } x_i \notin \mathsf{Z}^{<j} \text{ then } \Pi_{\mathsf{Set\text{-}Int}} = (\mathsf{E}_j, \Pi_j)) \\
&\geqslant \mathop{\mathbb{E}}_{\mathsf{E}_j,\Pi_j} \left[\sum_{x_i \notin \mathsf{Z}^{<j}} \frac{1}{m} \Lambda(\mu(\mathsf{T}_{x_i} \mid \mathsf{E}_j, \Pi_j), \mu(\mathsf{T}_{x_i})) \right] \\
& && (\text{as the first sum term is at least } 0) \\
&\geqslant \mathop{\mathbb{E}}_{\mathsf{E}_j,\Pi_j} \mathop{\mathbb{E}}_{i} [\Lambda(\mu(\mathsf{T}_{x_i} \mid \mathsf{E}_j, \Pi_j), \mu(\mathsf{T}_{x_i}))] - \frac{j}{m}. && (\text{as } \Lambda \text{ is upper bounded by } 1)
\end{aligned}$$

□

Using Claim 4.23 and the lower bound on $\mathsf{IC}_{\mathcal{D}}(\pi_{\mathsf{Set\text{-}Int}})$ (Corollary 4.13), we have:

$$\varepsilon = O\left(\frac{CC(\pi_{\mathsf{BHPC}})}{m^2} + \frac{j \log m}{m^2}\right)$$

Now, using Claim 4.24, we get:

$$\mathop{\mathbb{E}}_{(\mathsf{E}_j,\Pi_j)} \mathop{\mathbb{E}}_{x\sim\mathcal{U}_{\mathcal{X}}} [\Lambda(\mu(\mathsf{T}_x \mid \mathsf{E}_j, \Pi_j), \mu(\mathsf{T}_x))] - \frac{j}{n} = O\left(\frac{CC(\pi_{\mathsf{BHPC}})}{m^2} + \frac{j \log m}{m^2}\right),$$

which concludes the proof of Lemma 4.22.

4.6 Putting it All Together

Given Lemma 4.11, we prove Theorem 4.1 in the following way: Consider a protocol π that is solving $\mathsf{BMHPC}_{m,r}$ with communication cost $o(m^2)$. By Lemma 4.11, we have:

$$\begin{aligned}\mathop{\mathbb{E}}_{(\mathsf{E}_r,\Pi_r)}\left[\Lambda(\mu(\mathsf{Z}_r \mid \mathsf{E}_r,\Pi_r),\mu(\mathsf{Z}_r))\right] &\leqslant 6c\cdot\frac{\mathbb{I}(\Pi\,;\mathsf{A},\mathsf{C}\mid\mathsf{B},\mathsf{D})+\mathbb{I}(\Pi\,;\mathsf{B},\mathsf{D}\mid\mathsf{A},\mathsf{C})}{m^2}\\ &\mathop{\leqslant}_{(*)} 12c\cdot\frac{\mathsf{CC}(\pi_{\mathsf{BHPC}})}{m^2}=o(1),\end{aligned}$$

where inequality $(*)$ follows from Items 1 and 3 in Fact D.2. However, next, we show that, for a correct protocol for $\mathsf{BMHPC}_{m,r}$, this quantity should be $\Omega(1)$, which contradicts the assumption that $\mathsf{CC}(\pi_{\mathsf{BHPC}})=o(m^2)$. An entirely similar argument derives Theorem 4.2 from Lemma 4.21. The only difference between these two arguments is the bound on r: We have to assume $r=o(\sqrt{m})$ because of the additive r^2/m factor in Lemma 4.21 (when applied with on the r-th round of the protocol).

Lemma 4.25. *Any protocol that solves $\mathsf{BMHPC}_{m,r}$ on distribution $\mathcal{D}_{\mathsf{BMHPC}}$, or $\mathsf{BHPC}_{m,r}$, on distribution $\mathcal{D}_{\mathsf{BHPC}}$, with constant probability must have:*

$$\mathop{\mathbb{E}}_{(\mathsf{E}_r,\Pi_r)}\left[\Lambda(\mu(\mathsf{Z}_r \mid \mathsf{E}_r,\Pi_r),\mu(\mathsf{Z}_r))\right]=\Omega(1).$$

Proof. Let b denote the modulus function such that $b(z_k)=i \mod 2$ iff $z_r=x_i$ or y_i depending on where r is even or odd. If the protocol π computes $\mathsf{BMHPC}_{m,r}$ or $\mathsf{BHPC}_{m,r}$ with probability $2/3$, we have the following inequality:

$$\begin{aligned}2/3&=\mathop{\mathbb{E}}_{\mathsf{E}_r,\Pi_r}\Pr_{\mathsf{Z}_r\mid\mathsf{E}_r,\Pi_r}[b(\mathsf{Z}_r)=\mathcal{O}_\pi(\mathsf{E}_r,\Pi_r)]\\ &\mathop{\leqslant}_{(1)}\mathop{\mathbb{E}}_{\mathsf{E}_r,\Pi_r}\left[\Pr_{\mathsf{Z}_r\sim\mathcal{U}_\mathcal{X}}[b(\mathsf{Z}_r)=\mathcal{O}_\pi(\mathsf{E}_r,\Pi_r)]+\|\mu(b(\mathsf{Z}_r)\mid\mathsf{E}_r,\Pi_r)-\mathcal{U}_{0,1}\|_1\right]\\ &\mathop{\leqslant}_{(2)}\mathop{\mathbb{E}}_{\mathsf{E}_r,\Pi_r}\left[\Pr_{\mathsf{Z}_r\sim\mathcal{U}_\mathcal{X}}[b(\mathsf{Z}_r)=\mathcal{O}_\pi(\mathsf{E}_r,\Pi_r)]+\|\mu(\mathsf{Z}_r\mid\mathsf{E}_r,\Pi_r)-\mathcal{U}_\mathcal{X}\|_1\right]\\ &=\frac{1}{2}+\mathop{\mathbb{E}}_{\mathsf{E}_r,\Pi_r}[\|\mu(\mathsf{Z}_r\mid\mathsf{E}_r,\Pi_r)-\mathcal{U}_\mathcal{X}\|_1]\end{aligned}$$

where (1) holds because of the simple fact that $\Pr_p[\mathcal{E}]\leqslant\Pr_q[\mathcal{E}]+\|p-q\|_1$ where p and q are two distributions over a sample space of which $\mathcal{E}$ is an event (see Footnote 2), and (2) holds because of data processing inequality. This implies:

$$\begin{aligned}\mathop{\mathbb{E}}_{\mathsf{E}_r,\Pi_r}[\|\mu(\mathsf{Z}_r\mid\mathsf{E}_r,\Pi_r)-\mathcal{U}_{0,1}\|_1]\geqslant 1/6 &\Rightarrow\left(\mathop{\mathbb{E}}_{\mathsf{E}_r,\Pi_r}[\|\mu(\mathsf{Z}_r\mid\mathsf{E}_r,\Pi_r)-\mathcal{U}_{0,1}\|_1]\right)^2\geqslant 1/36\\ &\Rightarrow\mathop{\mathbb{E}}_{\mathsf{E}_r,\Pi_r}\left[\|\mu(\mathsf{Z}_r\mid\mathsf{E}_r,\Pi_r)-\mathcal{U}_{0,1}\|_1^2\right]\geqslant 1/36\\ &\Rightarrow\mathop{\mathbb{E}}_{\mathsf{E}_r,\Pi_r}[\Lambda(\mu(\mathsf{Z}_r\mid\mathsf{E}_r,\Pi_r),\mathcal{U}_{0,1})]\geqslant 1/288=\Omega(1),\end{aligned}$$

which completes the proof. □

A Sampling Bounds

Recall the Chernoff bound:

Proposition A.1. *Let $X_1, \cdots, X_n$ be independent random variables with values in $[0,1]$ and $X = \sum_i X_i$. Then:*

- ***Additive form:*** *For any $b \geqslant 0$, $\Pr[|X - \mathbb{E}[X]| \geqslant b] \leqslant 2 \cdot \exp\left(-\frac{b^2}{2n}\right)$,*
- ***Multiplicative form:*** *For $0 \leqslant \delta \leqslant 1$, $\Pr[|X - \mathbb{E}[X]| \geqslant (1+\delta)E[X]] \leqslant \exp\left(-\frac{\delta^2 E[X]}{3}\right)$.*

Now suppose we are allowed to repeatedly sample from an unknown Bernoulli distribution μ. We know that μ either has acceptance probability p or acceptance probability q. We wish to determine which is the case, via some method that may err with probability γ. Suppose that, for some $1 \geqslant \alpha, \beta > 0$, $p \leqslant \alpha$, whereas $q \geqslant (1+\beta)\alpha$. We may then draw

$$k = k(\alpha, \beta, \gamma) = \left\lceil \frac{48}{\alpha\beta^2} \ln\left(\frac{1}{\gamma}\right) \right\rceil$$

samples $X_1, \ldots, X_k$ from μ, and choose the threshold

$$\tau = \tau(\alpha, \beta, \gamma) = \alpha \cdot \left(1 + \frac{\beta}{4}\right) \cdot k$$

It now follows, from the multiplicative form of the Chernoff bound (Proposition A.1), that

$$\Pr[\sum_i X_i \geqslant \tau] = \Pr[\sum_i X_i \geqslant \alpha k \ \left(1 + \frac{\beta}{4}\right)] \leqslant \exp\left(-\frac{\beta^2}{48}\alpha k\right) \leqslant \gamma.$$

Now, whenever $\beta \in [0,1]$, we have $1 + \frac{\beta}{4} \leqslant (1+\beta)(1-\frac{\beta}{4})$, and so, if the acceptance probability is $q \geqslant \alpha(1+\beta)$, then

$$\begin{aligned}\Pr[\sum_i X_i \leqslant \tau] = \Pr[\sum_i X_i \leqslant \alpha k \left(1 + \frac{\beta}{4}\right)] &\leqslant \Pr[\sum_i X_i \leqslant \alpha(1+\beta)k \left(1 - \frac{\beta}{4}\right)] \\ &\leqslant \exp\left(-\frac{\beta^2}{48}\alpha(1+\beta)k\right) \leqslant \gamma.\end{aligned}$$

B Proof of Propositions Regarding Triangular Discrimination

Proposition 3.8. $0 \leqslant \frac{\|\mu-\nu\|_1^2}{8} \leqslant \Lambda(\mu,\nu) \leqslant \frac{\|\mu-\nu\|_1}{2} \leqslant 1$.

Proof. To see the lower bound on $\Lambda(\mu,\nu)$:

$$\frac{\|\mu-\nu\|_1}{2} = \sum_{x:\mu(x)>\nu(x)} (\mu(x) - \nu(x)) = \sum_{x:\mu(x)>\nu(x)} \frac{(\mu(x)-\nu(x))^2}{\sqrt{\mu(x)+\nu(x)}} \sqrt{\mu(x)+\nu(x)} \underset{(*)}{\leqslant} \sqrt{2\Lambda(\mu,\nu)}.$$

Here $(*)$ follows from Cauchy-Schwarz. To see the upper bound:

$$\Lambda(\mu,\nu) = \sum_{x:\mu(x)>\nu(x)} \frac{(\mu(x)-\nu(x))^2}{\mu(x)+\nu(x)} = \sum_{x:\mu(x)>\nu(x)} \frac{(\mu(x)-\nu(x))^2}{\mu(x)-\nu(x)} \cdot \frac{\mu(x)-\nu(x)}{\mu(x)+\nu(x)} \underset{(**)}{\leqslant} \frac{\|\mu-\nu\|_1}{2}.$$

Here $(**)$ follows from $\frac{\mu(x)-\nu(x)}{\mu(x)+\nu(x)} \leqslant 1$.

□

We will make use of the following:

Proposition B.1 ([Yeh20]). *If $|\eta| \leqslant \sqrt{a(b+\eta)}$ with $a, b \geqslant 0$, then $\eta \leqslant a + 2b$.*

Proof. If $a = 0$, then $\eta = 0$ and the upper-bound follows. Otherwise, if $\eta^2 - a\eta - ab \leqslant 0$, then

$$\eta \leqslant \frac{a + \sqrt{a^2 + 4ab}}{2} = \frac{a}{2}(1 + \sqrt{1 + 4b/a}) \leqslant \frac{a}{2}(1 + 1 + 4b/a). \qquad \square$$

Proposition 3.9. *For any function $f : \Omega \to \mathbb{R}_{\geqslant 0}$,*

$$\mathop{\mathbb{E}}_{\mu}[f(x)] \leqslant \Lambda(\mu, \nu) \cdot \max_{x \in \Omega} f(x) + 6 \cdot \mathop{\mathbb{E}}_{\nu}[f(x)].$$

Proof. We have:

$$\begin{aligned}
|\eta| = \left|\mathop{\mathbb{E}}_{\mu}(f(x)) - \mathop{\mathbb{E}}_{\nu}(f(x))\right| &= \left|\sum_x (\mu(x) - \nu(x)) f(x)\right| \\
&\leqslant \sum_x |(\mu(x) - \nu(x))|\, f(x) && \text{(By triangle inequality)} \\
&= \sum_x \frac{|\mu(x) - \nu(x)|\sqrt{f(x)}}{\sqrt{\mu(x) + \nu(x)}} \sqrt{(\mu(x) + \nu(x)) f(x)} \\
&\leqslant \sqrt{\sum_x \frac{(\mu(x) - \nu(x))^2 f(x)}{\mu(x) + \nu(x)}} \sqrt{\sum_x (\mu(x) + \nu(x)) f(x)} \\
& && \text{(By Cauchy-Schwarz)}
\end{aligned}$$

Let us look at the first term without the square root:

$$\begin{aligned}
\sum_x \frac{(\mu(x) - \nu(x))^2 f(x)}{\mu(x) + \nu(x)} &= \sum_{x : \mu(x) \geqslant \nu(x)} \frac{(\mu(x) - \nu(x))^2 f(x)}{\mu(x) + \nu(x)} + \sum_{x : \mu(x) < \nu(x)} \frac{(\mu(x) - \nu(x))^2 f(x)}{\mu(x) + \nu(x)} \\
&\leqslant \Lambda(\mu, \nu) \cdot \max_x f(x) + \sum_{x : \mu(x) < \nu(x)} \frac{(\mu(x) - \nu(x))^2 f(x)}{\mu(x) + \nu(x)} \\
&\leqslant \Lambda(\mu, \nu) \cdot \max_x f(x) + \sum_x \frac{(\nu(x))^2}{\nu(x)} f(x) = \Lambda(\mu, \nu) \cdot \max_x f(x) + \mathop{\mathbb{E}}_{\nu}(f(x)).
\end{aligned}$$

which implies:

$$|\eta| = \left|\mathop{\mathbb{E}}_{\mu}(f(x)) - \mathop{\mathbb{E}}_{\nu}(f(x))\right| \leqslant \sqrt{\underbrace{(\Lambda(\mu, \nu) \cdot \max_x f(x) + \mathop{\mathbb{E}}_{\nu}(f(x)))}_{a} (\eta + \underbrace{2 \mathop{\mathbb{E}}_{\nu}(f(x)))}_{b}}$$

At this point, we can use Proposition B.1 to get the following:

$$\begin{aligned}
\mathop{\mathbb{E}}_{\mu}(f(x)) - \mathop{\mathbb{E}}_{\nu}(f(x)) &\leqslant \Lambda(\mu, \nu) \cdot \max_x f(x) + 5 \Pr_{\nu}(\mathcal{E}), \\
\text{i.e., } \mathop{\mathbb{E}}_{\mu}(f(x)) &\leqslant \Lambda(\mu, \nu) \cdot \max_x f(x) + 6 \mathop{\mathbb{E}}_{\nu}(f(x)),
\end{aligned}$$

which completes the proof. $\square$

Proposition 3.10. *Positive triangular discrimination $\Lambda(\mu, \nu)$ is convex as a joint function of the two distributions μ and ν.*

Proof. To see this, it suffices to compute the Hessian of each term. We have

$$\Lambda(\mu,\nu) = \sum_x \begin{cases} \frac{(\mu(x)-\nu(x))^2}{\mu(x)+\nu(x)} & \text{if } \mu(x) \geqslant \nu(x) \\ 0 & \text{otherwise.} \end{cases}$$

So let us prove that each term is jointly convex in the values of $(\mu(x), \nu(x))$. We restrict our attention to the unit square. The function is zero, hence convex, inside the region where $\mu(x) \leqslant \nu(x)$. Furthermore, it is (obviously) non-negative inside the region where $\mu(x) > \nu(x)$. It is also convex in this region, since the Hessian is positive semidefinite there:

$$\nabla^2 \frac{(\mu(x)-\nu(x))^2}{\mu(x)+\nu(x)} = \begin{pmatrix} \frac{8\nu(x)^2}{(\mu(x)+\nu(x))^3} & -\frac{8\mu(x)\nu(x)}{(\mu(x)+\nu(x))^3} \\ -\frac{8\mu(x)\nu(x)}{(\mu(x)+\nu(x))^3} & \frac{8\mu(x)^2}{(\mu(x)+\nu(x))^3} \end{pmatrix}.$$

(The matrix is PSD since the off-diagonal entry, in absolute value, does not exceed the geometric mean of the diagonal entries.) It follows that each term is convex, and hence $\Lambda(\mu,\nu)$ is convex, in (μ,ν). □

C Proof of Claim 4.23

Proof. This proof is a verbatim reproduction of that in [ACK19]. For any $i \in [m]$, define $\boldsymbol{A}^{<i} := \{A_{x_1}, \ldots, A_{x_{i-1}}\}$, $\boldsymbol{B}^{>i} := \{B_{x_{i+1}}, \ldots, B_{x_m}\}$. Recall that the internal information cost of $\pi_{\mathsf{Set\text{-}Int}}$ is $\mathsf{IC}_{\mathcal{D}_{\mathsf{Set\text{-}Int}}}(\pi_{\mathsf{Set\text{-}Int}}) := \mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}) + \mathbb{I}(\mathsf{B}\,;\Pi_{\mathsf{SI}} \mid \mathsf{A})$. In the following, we focus on bounding the first term. The second term can be bounded exactly the same by symmetry.

As $(\mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}, \boldsymbol{C}, \boldsymbol{D})$ is sampled via public randomness in $\pi_{\mathsf{Set\text{-}Int}}$, by Proposition D.7,

$$\mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}) = \mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}, \boldsymbol{C}, \boldsymbol{D}) \leqslant \mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}).$$

The inequality is by Proposition D.4 as we now show $\mathsf{A} \perp (\boldsymbol{C}, \boldsymbol{D}) \mid \Pi_{\mathsf{SI}}, \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}$ (and hence conditioning on $(\boldsymbol{C}, \boldsymbol{D})$ can only decrease the mutual information). This is because $\mathsf{A} \perp (\boldsymbol{C}, \boldsymbol{D}) \mid \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}$ by Observation 4.6 and Π_{SI} is transcript of a deterministic protocol plus $z_1, \ldots, z_j$ obtained deterministically and hence we can apply Proposition 4.7.

Define a random variable $\Theta \in \{0,1\}$ where $\Theta = 1$ iff in Line (2) of protocol $\pi_{\mathsf{Set\text{-}Int}}$, we terminate the protocol. In other words $\Theta = 1$ iff $x_i \in Z^{<j}$. Since $\mathsf{A} \perp \Theta \mid \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}$, further conditioning on Θ can only increase the mutual information term above by Proposition D.3, hence,

$$\begin{aligned} \mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}) &\leqslant \mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}, \Theta) \\ &= \frac{m-j}{m} \cdot \mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}, \Theta = 0) + \frac{j}{m} \cdot \mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}, \Theta = 1) \\ &\leqslant \frac{m-j}{m} \cdot \mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}, \Theta = 0), \end{aligned} \tag{1}$$

since conditioned on $\Theta = 1$, the protocol Π_{SI} is simple some prefix of $\mathsf{Z}^{<j}$ and is hence independent of the input (A, B) and carries no information about A (see Fact D.2-(2)). We now further bound the RHS of Eq (1). When $\Theta = 0$, $\Pi_{\mathsf{SI}} = (\mathsf{Z}^{<j}, \Pi_1, \ldots, \Pi_j) = (\mathsf{E}^{<j}, \Pi_j)$. Hence, we can write,

$$\begin{aligned} \mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}, \Theta = 0) &\leqslant \mathbb{I}(\mathsf{A}\,;\mathsf{E}_j, \Pi_j \mid \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}, \Theta = 0) \\ &= \mathbb{I}(\mathsf{A}\,;\mathsf{Z}^{<j} \mid \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}, \Theta = 0) \\ &\quad + \mathbb{I}(\mathsf{A}\,;\Pi^{<j}, \Pi_j \mid \mathsf{Z}^{<j}, \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}, \Theta = 0) \\ &\quad \text{(by chain rule in Fact D.2-(7) and since } \mathsf{E}_j = (\Pi^{<j}, \mathsf{Z}^{<j})) \\ &\leqslant \mathbb{I}(\mathsf{A}\,;\Pi \mid \mathsf{Z}^{<j}, \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}, \Theta = 0), \end{aligned}$$

as $\mathsf{A} \perp \mathsf{Z}^{<j} \mid \Theta = 0$ (and other variables) and hence the first term is zero, and in the second term Π contains $\Pi^{<j}, \Pi_j$ (plus potentially other terms) and so having Π in instead can only increase the information. By further expanding the conditional information term above,

$$
\begin{aligned}
&\mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}, \mathsf{I}, \boldsymbol{A}^{<\mathsf{I}}, \boldsymbol{B}^{>\mathsf{I}}, \Theta = 0) \\
&\qquad \leqslant \mathop{\mathbb{E}}_{(Z^{<j},i)\mid\Theta=0} \left[\mathbb{I}(\mathsf{A}\,;\Pi \mid \mathsf{B}, \boldsymbol{A}^{<i}, \boldsymbol{B}^{>i}, \mathsf{I} = i, \mathsf{Z}^{<j} = Z^{<j}, \Theta = 0)\right] \\
&\qquad = \mathop{\mathbb{E}}_{Z^{<j}\mid\Theta=0} \left[\sum_{\substack{i=1 \\ i\notin Z^{<j}}}^{m} \frac{1}{m-j} \mathbb{I}(\mathsf{A}_{x_i}\,;\Pi \mid \mathsf{B}_{x_i}, \boldsymbol{A}^{<i}, \boldsymbol{B}^{>i}, \mathsf{I} = i, \mathsf{Z}^{<j} = Z^{<j}, \Theta = 0) \right] \\
&\qquad\quad \text{(conditioned on } \Theta = 0,\ i \text{ is chosen uniformly at random from } Z^{<j}\text{; also } (\mathsf{A}, \mathsf{B}) = (\mathsf{A}_{x_i}, \mathsf{B}_{x_i})) \\
&\qquad = \mathop{\mathbb{E}}_{Z^{<j}\mid\Theta=0} \left[\sum_{i\notin Z^{<j}} \frac{1}{m-j} \cdot \mathbb{I}(\mathsf{A}_{x_i}\,;\Pi \mid \mathsf{B}_{x_i}, \boldsymbol{A}^{<i}, \boldsymbol{B}^{>i}, \mathsf{Z}^{<j} = Z^{<j}, \Theta = 0) \right] \\
&\qquad\quad \text{(we dropped the conditioning on } \mathsf{I} = i \text{ as all remaining variables are independent of this event)} \\
&\qquad = \mathop{\mathbb{E}}_{Z^{<j}\mid\Theta=0} \left[\sum_{i\notin Z^{<j}} \frac{1}{m-j} \cdot \mathbb{I}(\mathsf{A}_{x_i}\,;\Pi \mid \boldsymbol{A}^{<i}, \boldsymbol{B}, \mathsf{Z}^{<j} = Z^{<j}, \Theta = 0) \right] \\
&\qquad\quad \text{(as } \mathsf{A}_{x_i} \perp \boldsymbol{B}^{<i} \mid \mathsf{B}_{x_i}, \boldsymbol{A}^{<i} \text{ by Observation 4.6 and hence we can apply Proposition D.3)} \\
&\qquad \leqslant \mathop{\mathbb{E}}_{Z^{<j}\mid\Theta=0} \left[\sum_{i=1}^{m} \frac{1}{m-j} \cdot \mathbb{I}(\mathsf{A}_{x_i}\,;\Pi \mid \boldsymbol{A}^{<i}, \boldsymbol{B}, \mathsf{Z}^{<j} = Z^{<j}, \Theta = 0) \right]
\end{aligned}
$$

(mutual information is non-negative by Fact D.2-(2) and so we can add the terms in $Z^{<j}$ as well)

$$
\begin{aligned}
&= \mathop{\mathbb{E}}_{Z^{<j}\mid\Theta=0} \left[\sum_{i=1}^{m} \frac{1}{m-j} \cdot \mathbb{I}(\mathsf{A}_{x_i}\,;\Pi \mid \boldsymbol{A}^{<i}, \boldsymbol{B}, \mathsf{Z}^{<j} = Z^{<j}, \Theta = 0) \right] \\
&= \frac{1}{m-j} \cdot \mathop{\mathbb{E}}_{Z^{<j}\mid\Theta=0} \left[\mathbb{I}(\boldsymbol{A}\,;\Pi \mid \boldsymbol{B}, \mathsf{Z}^{<j} = Z^{<j}, \Theta = 0)\right] \quad \text{(by chain rule in Fact D.2-(7))} \\
&= \frac{1}{m-j} \cdot \mathbb{I}(\boldsymbol{A}\,;\Pi \mid \boldsymbol{B}, \mathsf{Z}^{<j}, \Theta = 0) \\
&\leqslant \frac{1}{m-j} \cdot \left(\mathbb{I}(\boldsymbol{A}\,;\Pi \mid \boldsymbol{B}, \Theta = 0) + \mathbb{H}(\mathsf{Z}^{<j})\right) \\
&= \frac{1}{m-j} \cdot \left(\mathbb{I}(\boldsymbol{A}\,;\Pi \mid \boldsymbol{B}) + \mathbb{H}(\mathsf{Z}^{<j})\right) \\
&\qquad \text{(transcript of the protocol } \pi_{\mathsf{BHPC}} \text{ (namely } \Pi\text{) on input } (\boldsymbol{A}, \boldsymbol{B}) \text{ is independent of } \Theta) \\
&\leqslant \frac{1}{m-j} \cdot \left(\mathbb{H}(\Pi) + \mathbb{H}(\mathsf{Z}^{<j})\right) \leqslant \frac{\mathsf{CC}(\pi_{\mathsf{BHPC}})}{m-j} + \frac{j \cdot \log m}{m-j}. \\
&\qquad\qquad \text{(by sub-additivity of entropy (Fact D.2-(5)) and Fact D.2-(1))}
\end{aligned}
$$

By plugging in this bound in Eq (1), we have that,

$$
\mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}) \leqslant \frac{m-j}{m} \cdot \left(\frac{\mathsf{CC}(\pi_{\mathsf{BHPC}})}{m-j} + \frac{j \cdot \log m}{m-j}\right) = \frac{\mathsf{CC}(\pi_{\mathsf{BHPC}})}{m} + \frac{j \cdot \log m}{m}.
$$

By symmetry, we can also prove the same bound on $\mathbb{I}(\mathsf{B}\,;\Pi_{\mathsf{SI}} \mid \mathsf{A})$. As such, we have,

$$
\mathbb{I}(\mathsf{A}\,;\Pi_{\mathsf{SI}} \mid \mathsf{B}) + \mathbb{I}(\mathsf{B}\,;\Pi_{\mathsf{SI}} \mid \mathsf{A}) \leqslant 2 \cdot \left(\frac{\mathsf{CC}(\pi_{\mathsf{BHPC}})}{m} + \frac{j \cdot \log m}{m}\right).
$$

We shall note that strictly speaking the factor 2 above is not needed (similar to the proof of Proposition D.8) but as this factor is anyway suppressed through O-notation later in the proof, the above bound suffices for our purpose.

□

D Background on Information Theory

We now briefly introduce some definitions and facts from information theory that are needed in this thesis. We refer the interested reader to the text by Cover and Thomas [CT06] for an excellent introduction to this field, and the proofs of the statements used in this Appendix.

For a random variable A, we use $\textsc{supp}(\mathsf{A})$ to denote the support of A and $\mathrm{dist}(\mathsf{A})$ to denote its distribution. When it is clear from the context, we may abuse the notation and use A directly instead of $\mathrm{dist}(\mathsf{A})$, for example, write $A \sim \mathsf{A}$ to mean $A \sim \mathrm{dist}(\mathsf{A})$, i.e., A is sampled from the distribution of random variable A.

We denote the *Shannon Entropy* of a random variable A by $\mathbb{H}(\mathsf{A})$, which is defined as:

$$\mathbb{H}(\mathsf{A}) := \sum_{A \in \textsc{supp}(\mathsf{A})} \Pr\left(\mathsf{A} = A\right) \cdot \log\left(1/\Pr\left(\mathsf{A} = A\right)\right) \tag{2}$$

The *conditional entropy* of A conditioned on B is denoted by $\mathbb{H}(\mathsf{A} \mid \mathsf{B})$ and defined as:

$$\mathbb{H}(\mathsf{A} \mid \mathsf{B}) := \mathop{\mathbb{E}}_{B \sim \mathsf{B}} \left[\mathbb{H}(\mathsf{A} \mid \mathsf{B} = B)\right], \tag{3}$$

where $\mathbb{H}(\mathsf{A} \mid \mathsf{B} = B)$ is defined in a standard way by using the distribution of A conditioned on the event $\mathsf{B} = B$ in Eq (2).
Recall that the binary entropy $H(p)$ is the entropy of a two-valued random variable that takes one value with probability p. We need the following upper bound on the binary entropy.

Fact D.1. *The binary entropy* $H_2(p) \leqslant 2\sqrt{p \cdot (1-p)}$.

The *mutual information* of two random variables A and B is denoted by $\mathbb{I}(\mathsf{A}\,;\mathsf{B})$ and is defined as:

$$\mathbb{I}(\mathsf{A}\,;\mathsf{B}) := \mathbb{H}(A) - \mathbb{H}(A \mid B) = \mathbb{H}(B) - \mathbb{H}(B \mid A). \tag{4}$$

The *conditional mutual information* $\mathbb{I}(\mathsf{A}\,;\mathsf{B} \mid \mathsf{C})$ is $\mathbb{H}(\mathsf{A} \mid \mathsf{C}) - \mathbb{H}(\mathsf{A} \mid \mathsf{B}, \mathsf{C})$ and hence by linearity of expectation:

$$\mathbb{I}(\mathsf{A}\,;\mathsf{B} \mid \mathsf{C}) = \mathop{\mathbb{E}}_{C \sim \mathsf{C}} \left[\mathbb{I}(\mathsf{A}\,;\mathsf{B} \mid \mathsf{C} = C)\right]. \tag{5}$$

D.1 Useful Properties of Entropy and Mutual Information

We shall use the following basic properties of entropy and mutual information throughout.

Fact D.2. *Let* A, B, C, *and* D *be four (possibly correlated) random variables.*

1. $0 \leqslant \mathbb{H}(\mathsf{A}) \leqslant \log|\textsc{supp}(\mathsf{A})|$. *The right equality holds iff* $\mathrm{dist}(\mathsf{A})$ *is uniform.*
2. $\mathbb{I}(\mathsf{A}\,;\mathsf{B} \mid \mathsf{C}) \geqslant 0$. *The equality holds iff* A *and* B *are* independent *conditioned on* C.
3. $\mathbb{I}(\mathsf{A}\,;\mathsf{B} \mid \mathsf{C}) \leqslant \mathbb{H}(\mathsf{A})$.

4. Conditioning on a random variable reduces entropy: $\mathbb{H}(\mathsf{A} \mid \mathsf{B}, \mathsf{C}) \leqslant \mathbb{H}(\mathsf{A} \mid \mathsf{B})$. *The equality holds iff* $\mathsf{A} \perp \mathsf{C} \mid \mathsf{B}$.

5. Subadditivity of entropy: $\mathbb{H}(\mathsf{A}, \mathsf{B} \mid \mathsf{C}) \leqslant \mathbb{H}(\mathsf{A} \mid C) + \mathbb{H}(\mathsf{B} \mid \mathsf{C})$.

6. Chain rule for entropy: $\mathbb{H}(\mathsf{A}, \mathsf{B} \mid \mathsf{C}) = \mathbb{H}(\mathsf{A} \mid \mathsf{C}) + \mathbb{H}(\mathsf{B} \mid \mathsf{C}, \mathsf{A})$.

7. Chain rule for mutual information: $\mathbb{I}(\mathsf{A}, \mathsf{B}\,; \mathsf{C} \mid \mathsf{D}) = \mathbb{I}(\mathsf{A}\,; \mathsf{C} \mid \mathsf{D}) + \mathbb{I}(\mathsf{B}\,; \mathsf{C} \mid \mathsf{A}, \mathsf{D})$.

8. Data processing inequality: *for a function* $f(\mathsf{A})$ *of* A, $\mathbb{I}(f(\mathsf{A})\,; \mathsf{B} \mid \mathsf{C}) \leqslant \mathbb{I}(\mathsf{A}\,; \mathsf{B} \mid \mathsf{C})$.

We also use the following two standard propositions, regarding the effect of conditioning on mutual information.

Proposition D.3. *For random variables* $\mathsf{A}, \mathsf{B}, \mathsf{C}, \mathsf{D}$, *if* $\mathsf{A} \perp \mathsf{D} \mid \mathsf{C}$, *then,*

$$\mathbb{I}(\mathsf{A}\,; \mathsf{B} \mid \mathsf{C}) \leqslant \mathbb{I}(\mathsf{A}\,; \mathsf{B} \mid \mathsf{C}, \mathsf{D}).$$

Proof. Since A and D are independent conditioned on C, by Fact D.2-(4), $\mathbb{H}(\mathsf{A} \mid \mathsf{C}) = \mathbb{H}(\mathsf{A} \mid \mathsf{C}, \mathsf{D})$ and $\mathbb{H}(\mathsf{A} \mid \mathsf{C}, \mathsf{B}) \geqslant \mathbb{H}(\mathsf{A} \mid \mathsf{C}, \mathsf{B}, \mathsf{D})$. We have,

$$\begin{aligned}\mathbb{I}(\mathsf{A}\,; \mathsf{B} \mid \mathsf{C}) &= \mathbb{H}(\mathsf{A} \mid \mathsf{C}) - \mathbb{H}(\mathsf{A} \mid \mathsf{C}, \mathsf{B}) = \mathbb{H}(\mathsf{A} \mid \mathsf{C}, \mathsf{D}) - \mathbb{H}(\mathsf{A} \mid \mathsf{C}, \mathsf{B}) \\ &\leqslant \mathbb{H}(\mathsf{A} \mid \mathsf{C}, \mathsf{D}) - \mathbb{H}(\mathsf{A} \mid \mathsf{C}, \mathsf{B}, \mathsf{D}) = \mathbb{I}(\mathsf{A}\,; \mathsf{B} \mid \mathsf{C}, \mathsf{D}). \quad \square\end{aligned}$$

□

Proposition D.4. *For random variables* $\mathsf{A}, \mathsf{B}, \mathsf{C}, \mathsf{D}$, *if* $\mathsf{A} \perp \mathsf{D} \mid \mathsf{B}, \mathsf{C}$, *then,*

$$\mathbb{I}(\mathsf{A}\,; \mathsf{B} \mid \mathsf{C}) \geqslant \mathbb{I}(\mathsf{A}\,; \mathsf{B} \mid \mathsf{C}, \mathsf{D}).$$

Proof. Since $\mathsf{A} \perp \mathsf{D} \mid \mathsf{B}, \mathsf{C}$, by Fact D.2-(4), $\mathbb{H}(\mathsf{A} \mid \mathsf{B}, \mathsf{C}) = \mathbb{H}(\mathsf{A} \mid \mathsf{B}, \mathsf{C}, \mathsf{D})$. Moreover, since conditioning can only reduce the entropy (again by Fact D.2-(4)),

$$\begin{aligned}\mathbb{I}(\mathsf{A}\,; \mathsf{B} \mid \mathsf{C}) &= \mathbb{H}(\mathsf{A} \mid \mathsf{C}) - \mathbb{H}(\mathsf{A} \mid \mathsf{B}, \mathsf{C}) \geqslant \mathbb{H}(\mathsf{A} \mid \mathsf{D}, \mathsf{C}) - \mathbb{H}(\mathsf{A} \mid \mathsf{B}, \mathsf{C}) \\ &= \mathbb{H}(\mathsf{A} \mid \mathsf{D}, \mathsf{C}) - \mathbb{H}(\mathsf{A} \mid \mathsf{B}, \mathsf{C}, \mathsf{D}) = \mathbb{I}(\mathsf{A}\,; \mathsf{B} \mid \mathsf{C}, \mathsf{D}). \quad \square\end{aligned}$$

□

D.2 Background on Communication and Information Complexity

Communication complexity. We briefly review the standard definitions of the two-party communication model of Yao [Yao79]. See the text by Kushilevitz and Nisan [KN97] for an extensive overview of communication complexity. In Section 4, we also use a standard generalization of this model to allow for more than two players, but we defer the necessary definitions to that section.

Let $P : \mathcal{X} \times \mathcal{Y} \to \mathcal{Z}$ be a relation. Alice receives an input $X \in \mathcal{X}$ and Bob receives $Y \in \mathcal{Y}$, where (X, Y) are chosen from a joint distribution $\mathcal{D}$ over $\mathcal{X} \times \mathcal{Y}$. We allow players to have access to both public and private randomness. They communicate with each other by exchanging messages such that each message depends only on the private input and random bits of the player sending the message, and the already communicated messages plus the public randomness. At the end, one of the players need to output an answer Z such that $Z \in P(X, Y)$.

We use π to denote a protocol used by the players. We always assume that the protocol π can be randomized (using both public and private randomness), *even against a prior distribution* $\mathcal{D}$ *of inputs*. For any $0 < \delta < 1$, we say π is a δ-error protocol for P over a distribution $\mathcal{D}$, if the probability that for an input (X, Y), π outputs some Z where $Z \notin P(X, Y)$ is at most δ (the probability is taken over the randomness of *both* the distribution and the protocol).

Definition D.5 (Communication cost)**.** The *communication cost* of a protocol π on an input distribution $\mathcal{D}$, denoted by $\mathsf{CC}_{\mathcal{D}}(\pi)$, is the *worst-case* bit-length of the transcript communicated between Alice and Bob in the protocol π, when the inputs are chosen from $\mathcal{D}$.

Communication complexity of a problem P is defined as the minimum communication cost of a protocol π that solves P on every distribution $\mathcal{D}$ with probability at least $2/3$.

Information complexity. There are several possible definitions of information cost of a communication prtocol that have been considered depending on the application (see, e.g., [CSWY01, BJKS02, BBCR10, BR11, BEO+13]). We use the notion of *internal information cost* [BBCR10] that measures the average amount of information each player learns about the input of the other player by observing the transcript of the protocol.

Definition D.6 (Information cost)**.** Consider an input distribution $\mathcal{D}$ and a protocol π. Let $(\mathsf{X}, \mathsf{Y}) \sim \mathcal{D}$ denote the random variables for the input of Alice and Bob and Π be the the random variable for the transcript of the protocol *concatenated* with the public randomness R used by π. The *(internal) information cost* of π with respect to $\mathcal{D}$ is $\mathsf{IC}_{\mathcal{D}}(\pi) := \mathbb{I}_{\mathcal{D}}(\Pi\,; \mathsf{X} \mid \mathsf{Y}) + \mathbb{I}_{\mathcal{D}}(\Pi\,; \mathsf{Y} \mid \mathsf{X})$.

One can also define information complexity of a problem P similar to communication complexity with respect to the information cost. However, we avoid presenting this definition formally due to some subtle technical issues that need to be addressed which lead to multiple different but similar-in-spirit definitions. As such, we state our results directly in terms of information cost.

Note that any public coin protocol is a distribution over private coins protocols, run by first using public randomness to sample a random string $\mathsf{R} = R$ and then running the corresponding private coin protocol π^R. We also use Π^R to denote the transcript of the protocol π^R. We have the following standard proposition.

Proposition D.7. *For any distribution $\mathcal{D}$ and any protocol π with public randomness $\boldsymbol{R}$,*

$$\mathsf{IC}_{\mathcal{D}}(\pi) = \mathbb{I}_{\mathcal{D}}(\Pi\,; \mathsf{X} \mid \mathsf{Y}, \mathsf{R}) + \mathbb{I}_{\mathcal{D}}(\Pi\,; \mathsf{Y} \mid \mathsf{X}, \mathsf{R}) = \mathop{\mathbb{E}}_{R \sim \mathsf{R}} \left[\mathsf{IC}_{\mathcal{D}}(\pi^R)\right].$$

Proof. By definition of internal information cost,

$$\begin{aligned}
\mathsf{IC}_{\mathcal{D}}(\pi) &= \mathbb{I}_{\mathcal{D}}(\Pi\,; \mathsf{X} \mid \mathsf{Y}) + \mathbb{I}_{\mathcal{D}}(\Pi\,; \mathsf{Y} \mid \mathsf{X}) = \mathbb{I}(\Pi, \mathsf{R}\,; \mathsf{X} \mid \mathsf{Y}) + \mathbb{I}(\Pi, \mathsf{R}\,; \mathsf{Y} \mid \mathsf{X}) \\
&\qquad\qquad \text{(Π denotes the transcript and the public randomness)} \\
&= \mathbb{I}(\mathsf{R}\,; \mathsf{X} \mid \mathsf{Y}) + \mathbb{I}(\Pi\,; \mathsf{X} \mid \mathsf{Y}, \mathsf{R}) + \mathbb{I}(\mathsf{R}\,; \mathsf{Y} \mid \mathsf{X}) + \mathbb{I}(\Pi\,; \mathsf{Y} \mid \mathsf{X}, \mathsf{R}) \\
&\qquad\qquad \text{(chain rule of mutual information, Fact D.2-(7))} \\
&= \mathbb{I}(\Pi\,; \mathsf{X} \mid \mathsf{Y}, \mathsf{R}) + \mathbb{I}(\Pi\,; \mathsf{Y} \mid \mathsf{X}, \mathsf{R}) \\
&\qquad\qquad \text{($\mathbb{I}(\mathsf{R}\,; \mathsf{X} \mid \mathsf{Y}) = \mathbb{I}(\mathsf{R}\,; \mathsf{Y} \mid \mathsf{X}) = 0$ since $\mathsf{R} \perp \mathsf{X}, \mathsf{Y}$ and Fact D.2-(2))} \\
&= \mathop{\mathbb{E}}_{R \sim \mathsf{R}} \left[\mathbb{I}(\Pi\,; \mathsf{X} \mid \mathsf{Y}, \mathsf{R} = R) + \mathbb{I}(\Pi\,; \mathsf{Y} \mid \mathsf{X}, \mathsf{R} = R)\right] = \mathop{\mathbb{E}}_{R \sim \mathsf{R}} \left[\mathsf{IC}_{\mathcal{D}}(\pi^R)\right],
\end{aligned}$$

concluding the proof. □

The following well-known proposition relates communication cost and information cost.

Proposition D.8 (cf. [BR11])**.** *For any distribution $\mathcal{D}$ and any protocol π: $\mathsf{IC}_{\mathcal{D}}(\pi) \leqslant \mathsf{CC}_{\mathcal{D}}(\pi)$.*

Proof. Let us assume first that π only uses private randomness and thus Π only contain the transcript. For any $b \in [\mathsf{CC}_{\mathcal{D}}(\pi)]$, we define Π_b to be the b-th bit of the transcript. We have,

$$\begin{aligned}
\mathsf{IC}_{\mathcal{D}}(\pi) &= \mathbb{I}(\Pi\,;\mathsf{X} \mid \mathsf{Y}) + \mathbb{I}(\Pi\,;\mathsf{Y} \mid \mathsf{X}) \\
&= \sum_{b=1}^{\mathsf{CC}_{\mathcal{D}}(\pi)} \mathbb{I}(\Pi_b\,;\mathsf{X} \mid \Pi^{<b},\mathsf{Y}) + \mathbb{I}(\Pi_b\,;\mathsf{Y} \mid \Pi^{<b},\mathsf{X}) \\
&\qquad\qquad \text{(by chain rule of mutual information in Fact D.2-(7))} \\
&= \sum_{b=1}^{\mathsf{CC}_{\mathcal{D}}(\pi)} \mathop{\mathbb{E}}_{\Pi^{<b}} \left[\mathbb{I}(\Pi_b\,;\mathsf{X} \mid \Pi^{<b}=\Pi^{<b},\mathsf{Y}) + \mathbb{I}(\Pi_b\,;\mathsf{Y} \mid \Pi^{<b}=\Pi^{<b},\mathsf{X})\right].
\end{aligned}$$

Consider each term in the RHS above. By conditioning on $\Pi^{<b}$, the player that transmit Π_b would become fix. If this player is Alice, then $\mathbb{I}(\Pi_b\,;\mathsf{Y} \mid \Pi^{<b}=\Pi^{<b},\mathsf{X}) = 0$, because Π_b is only a function of $(\Pi^{<b},\mathsf{X})$ in this case; similarly, if this player is Bob, then $\mathbb{I}(\Pi_b\,;\mathsf{X} \mid \Pi^{<b}=\Pi^{<b},\mathsf{Y}) = 0$. Moreover, $\mathbb{I}(\Pi_b\,;\mathsf{X} \mid \Pi^{<b}=\Pi^{<b},\mathsf{Y}) \leqslant \mathbb{H}(\Pi_b) \leqslant 1$ and similarly $\mathbb{I}(\Pi_b\,;\mathsf{Y} \mid \Pi^{<b}=\Pi^{<b},\mathsf{X}) \leqslant 1$. As such, the above term can be upper bounded by $\mathsf{CC}_{\mathcal{D}}(\pi)$. To finalize the proof, note that by Proposition D.7, for any public-coin protocol π, $\mathsf{IC}_{\mathcal{D}}(\pi) = \mathbb{E}_{R\sim\mathsf{R}}\left[\mathsf{IC}_{\mathcal{D}}(\pi^R)\right] \leqslant \mathbb{E}_{R\sim\mathsf{R}}\left[\mathsf{CC}_{\mathcal{D}}(\pi^R)\right] \leqslant \mathsf{CC}_{\mathcal{D}}(\pi)$, where the first inequality is by the first part of the argument. □

Proposition D.8 provides a convinent way of proving communication complexity lower bounds by lower bounding information cost of any protocol.

Rectangle Property of Communication Protocols

We conclude this section by mentioning some basic properties of communication protocols. For any protocol π and inputs $x \in \mathcal{X}$ and $y \in \mathcal{Y}$, we define $\Pi_{x,y}$ as the transcript of the protocol conditioned on the input x to Alice and input y to Bob. Note that for randomized protocols, $\Pi_{x,y}$ is a random variable which we denote by $\Pi_{x,y}$.

The following is referred to as the rectangle property of deterministic protocols.

Fact D.9 (Rectangle property)**.** *For any deterministic protocol π and inputs $x, x' \in \mathcal{X}$ to Alice and $y, y' \in \mathcal{Y}$ to Bob, if $\Pi_{x,y} = \Pi_{x',y'}$, then $\Pi_{x,y'} = \Pi_{x',y}$.*

Fact D.9 implies that the set of inputs consistent with any transcript $\Pi_{x,y}$ of a deterministic protocol forms a combinatorial rectangle. One can also extend the rectangle property of deterministic protocols to randomized protocols using the following fact.

Fact D.10 (Cut-and-paste property; cf. [BJKS02])**.** *For any randomized protocol π and inputs $x, x' \in \mathcal{X}$ to Alice and $y, y' \in \mathcal{Y}$ to Bob,* $\mathrm{h}(\Pi_{x,y}, \Pi_{x',y'}) = \mathrm{h}(\Pi_{x,y'}, \Pi_{x',y})$.

References

[A17] Sepehr Assadi A. Tight space-approximation tradeoff for the multi-pass streaming set cover problem. In *Proceedings of the 36th ACM SIGMOD-SIGACT-SIGAI Symposium on Principles of Database Systems, PODS 2017, Chicago, IL, USA, May 14-19, 2017*, pages 321–335, 2017.

[A22] Sepehr Assadi A. A two-pass (conditional) lower bound for semi-streaming maximum matching. In Joseph (Seffi) Naor and Niv Buchbinder, editors, *Proceedings of the 2022 ACM-SIAM Symposium on Discrete Algorithms, SODA 2022, Virtual Conference / Alexandria, VA, USA, January 9 - 12, 2022*, pages 708–742. SIAM, 2022.

[AA20] Noga Alon and Sepehr Assadi. Palette sparsification beyond (Δ+1) vertex coloring. In Jaroslaw Byrka and Raghu Meka, editors, *Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques, APPROX/RANDOM 2020, August 17-19, 2020, Virtual Conference*, volume 176 of *LIPIcs*, pages 6:1–6:22. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2020. 2

[ACK19] Sepehr Assadi, Yu Chen, and Sanjeev Khanna. Polynomial pass lower bounds for graph streaming algorithms. In *STOC*, pages 265–276. ACM, 2019. 2, 7, 8, 9, 19, 22, 26

[ACKP21] Amir Abboud, Keren Censor-Hillel, Seri Khoury, and Ami Paz. Smaller cuts, higher lower bounds. *ACM Trans. Algorithms*, 17(4):30:1–30:40, 2021.

[AD21] Sepehr Assadi and Aditi Dudeja. A simple semi-streaming algorithm for global minimum cuts. In *SOSA*, pages 172–180. SIAM, 2021.

[ADBV05] J. Ignacio Alvarez-Hamelin, Luca Dall'Asta, Alain Barrat, and Alessandro Vespignani. Large scale networks fingerprinting and visualization using the k-core decomposition. In *Advances in Neural Information Processing Systems 18 [Neural Information Processing Systems, NIPS 2005, December 5-8, 2005, Vancouver, British Columbia, Canada]*, pages 41–50, 2005. 1

[AJJ+22] Sepehr Assadi, Arun Jambulapati, Yujia Jin, Aaron Sidford, and Kevin Tian. Semi-streaming bipartite matching in fewer passes and optimal space. In *SODA*, pages 627–669. SIAM, 2022.

[AKSY20] Sepehr Assadi, Gillat Kol, Raghuvansh Saxena, and Huacheng Yu. Multi-pass graph streaming lower bounds for cycle counting, max-cut, matching size, and other problems. In *61st Annual IEEE Symposium on Foundations of Computer Science, FOCS (to appear)*, 2020.

[AKZ22] Sepehr Assadi, Gillat Kol, and Zhijun Zhang. Rounds vs communication tradeoffs for maximal independent sets. In *63rd IEEE Annual Symposium on Foundations of Computer Science, FOCS 2022, Denver, CO, USA, October 31 - November 3, 2022*, pages 1193–1204. IEEE, 2022.

[AN21] Sepehr Assadi and Vishvajeet N. Graph streaming lower bounds for parameter estimation and property testing via a streaming XOR lemma. In Samir Khuller and Virginia Vassilevska Williams, editors, *STOC '21: 53rd Annual ACM SIGACT Symposium on Theory of Computing, Virtual Event, Italy, June 21-25, 2021*, pages 612–625. ACM, 2021.

[AR20] Sepehr Assadi and Ran Raz. Near-quadratic lower bounds for two-pass graph streaming algorithms. In *FOCS*, pages 342–353. IEEE, 2020. 2, 14, 15, 18

[AYZ97] Noga Alon, Raphael Yuster, and Uri Zwick. Finding and counting given length cycles. *Algorithmica*, 17(3):209–223, 1997. 1

[BBCR10] Boaz Barak, Mark Braverman, Xi Chen, and Anup Rao. How to compress interactive communication. In *Proceedings of the 42nd ACM Symposium on Theory of Computing, STOC 2010, 5-8 June 2010*, pages 67–76, 2010. 30

[BCD+19] Nir Bachrach, Keren Censor-Hillel, Michal Dory, Yuval Efron, Dean Leitersdorf, and Ami Paz. Hardness of distributed optimization. In Peter Robinson and Faith Ellen, editors, *Proceedings of the 2019 ACM Symposium on Principles of Distributed Computing, PODC 2019, Toronto, ON, Canada, July 29 - August 2, 2019*, pages 238–247. ACM, 2019.

[BCG20] Suman K. Bera, Amit Chakrabarti, and Prantar Ghosh. Graph coloring via degeneracy in streaming and other space-conscious models. In *47th International Colloquium on Automata, Languages, and Programming, ICALP 2020, July 8-11, 2020, Saarbrücken, Germany (Virtual Conference)*, pages 11:1–11:21, 2020. 2

[BEO+13] Mark Braverman, Faith Ellen, Rotem Oshman, Toniann Pitassi, and Vinod Vaikuntanathan. A tight bound for set disjointness in the message-passing model. In *54th Annual IEEE Symposium on Foundations of Computer Science, FOCS 2013, 26-29 October, 2013, Berkeley, CA, USA*, pages 668–677, 2013. 30

[BGKV14] Francesco Bonchi, Francesco Gullo, Andreas Kaltenbrunner, and Yana Volkovich. Core decomposition of uncertain graphs. In Sofus A. Macskassy, Claudia Perlich, Jure Leskovec, Wei Wang, and Rayid Ghani, editors, *The 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, KDD '14, New York, NY, USA - August 24 - 27, 2014*, pages 1316–1325. ACM, 2014. 1

[BHNT15] Sayan Bhattacharya, Monika Henzinger, Danupon Nanongkai, and Charalampos E. Tsourakakis. Space- and time-efficient algorithm for maintaining dense subgraphs on one-pass dynamic streams. In *Proceedings of the Forty-Seventh Annual ACM on Symposium on Theory of Computing, STOC 2015, Portland, OR, USA, June 14-17, 2015*, pages 173–182, 2015. 2

[BJKS02] Ziv Bar-Yossef, T. S. Jayram, Ravi Kumar, and D. Sivakumar. An information statistics approach to data stream and communication complexity. In *43rd Symposium on Foundations of Computer Science (FOCS 2002), 16-19 November 2002, Proceedings*, pages 209–218, 2002. 30, 31

[BKS02] Ziv Bar-Yossef, Ravi Kumar, and D. Sivakumar. Reductions in streaming algorithms, with an application to counting triangles in graphs. In *Proceedings of the Thirteenth Annual ACM-SIAM Symposium on Discrete Algorithms, January 6-8, 2002, San Francisco, CA, USA.*, pages 623–632, 2002.

[BKV12] Bahman Bahmani, Ravi Kumar, and Sergei Vassilvitskii. Densest subgraph in streaming and mapreduce. *PVLDB*, 5(5):454–465, 2012. 2

[BR11] Mark Braverman and Anup Rao. Information equals amortized communication. In *IEEE 52nd Annual Symposium on Foundations of Computer Science, FOCS 2011, October 22-25, 2011*, pages 748–757, 2011. 30

[BvdBE+22] Joakim Blikstad, Jan van den Brand, Yuval Efron, Sagnik Mukhopadhyay, and Danupon Nanongkai. Nearly optimal communication and query complexity of bipartite matching. In *FOCS*, pages 1174–1185. IEEE, 2022.

[CFHT20] Yi-Jun Chang, Martin Farach-Colton, Tsan-sheng Hsu, and Meng-Tsung Tsai. Streaming complexity of spanning tree computation. In *37th International Symposium on Theoretical Aspects of Computer Science, STACS 2020, March 10-13, 2020, Montpellier, France*, pages 34:1–34:19, 2020.

[CGMV20] Amit Chakrabarti, Prantar Ghosh, Andrew McGregor, and Sofya Vorotnikova. Vertex ordering problems in directed graph streams. In *Proceedings of the 2020 ACM-SIAM Symposium on Discrete Algorithms, SODA 2020, Salt Lake City, UT, USA, January 5-8, 2020*, pages 1786–1802, 2020.

[Cha00] Moses Charikar. Greedy approximation algorithms for finding dense components in a graph. In Klaus Jansen and Samir Khuller, editors, *Approximation Algorithms for Combinatorial Optimization, Third International Workshop, APPROX 2000, Saarbrücken, Germany, September 5-8, 2000, Proceedings*, volume 1913 of *Lecture Notes in Computer Science*, pages 84–95. Springer, 2000. 1

[CKP+21a] Lijie Chen, Gillat Kol, Dmitry Paramonov, Raghuvansh R. Saxena, Zhao Song, and Huacheng Yu. Almost optimal super-constant-pass streaming lower bounds for reachability. In Samir Khuller and Virginia Vassilevska Williams, editors, *STOC '21: 53rd Annual ACM SIGACT Symposium on Theory of Computing, Virtual Event, Italy, June 21-25, 2021*, pages 570–583. ACM, 2021.

[CKP+21b] Lijie Chen, Gillat Kol, Dmitry Paramonov, Raghuvansh R. Saxena, Zhao Song, and Huacheng Yu. Near-optimal two-pass streaming algorithm for sampling random walks over directed graphs. In Nikhil Bansal, Emanuela Merelli, and James Worrell, editors, *48th International Colloquium on Automata, Languages, and Programming, ICALP 2021, July 12-16, 2021, Glasgow, Scotland (Virtual Conference)*, volume 198 of *LIPIcs*, pages 52:1–52:19. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2021.

[CKP+23] Lijie Chen, Gillat Kol, Dmitry Paramonov, Raghuvansh R. Saxena, Zhao Song, and Huacheng Yu. Towards multi-pass streaming lower bounds for optimal approximation of max-cut. In Nikhil Bansal and Viswanath Nagarajan, editors, *Proceedings of the 2023 ACM-SIAM Symposium on Discrete Algorithms, SODA 2023, Florence, Italy, January 22-25, 2023*, pages 878–924. SIAM, 2023.

[CSWY01] Amit Chakrabarti, Yaoyun Shi, Anthony Wirth, and Andrew Chi-Chih Yao. Informational complexity and the direct sum problem for simultaneous message complexity. In *42nd Annual Symposium on Foundations of Computer Science, FOCS 2001, 14-17 October 2001*, pages 270–278, 2001. 30

[CT06] Thomas M. Cover and Joy A. Thomas. *Elements of information theory (2. ed.)*. Wiley, 2006. 28

[CZL+20] Deming Chu, Fan Zhang, Xuemin Lin, Wenjie Zhang, Ying Zhang, Yinglong Xia, and Chenyi Zhang. Finding the best k in core decomposition: A time and space optimal solution. In *36th IEEE International Conference on Data Engineering, ICDE 2020, Dallas, TX, USA, April 20-24, 2020*, pages 685–696. IEEE, 2020. 1

[DBS17] Laxman Dhulipala, Guy E. Blelloch, and Julian Shun. Julienne: A framework for parallel graph algorithms using work-efficient bucketing. In Christian Scheideler and Mohammad Taghi Hajiaghayi, editors, *Proceedings of the 29th ACM Symposium on Parallelism in Algorithms and Architectures, SPAA 2017, Washington DC, USA, July 24-26, 2017*, pages 293–304. ACM, 2017. 1

[DBS18] Laxman Dhulipala, Guy E. Blelloch, and Julian Shun. Theoretically efficient parallel graph algorithms can be fast and scalable. In Christian Scheideler and Jeremy T. Fineman, editors, *Proceedings of the 30th on Symposium on Parallelism in Algorithms*

and Architectures, SPAA 2018, Vienna, Austria, July 16-18, 2018, pages 393–404. ACM, 2018. 1

[DNO19] Shahar Dobzinski, Noam Nisan, and Sigal Oren. Economic efficiency requires interaction. *Games Econ. Behav.*, 118:589–608, 2019.

[EH66] Paul Erdős and András Hajnal. On chromatic number of graphs and set-systems. *Acta Math. Acad. Sci. Hungar*, 17(61-99):1, 1966. 1

[ELM18] Hossein Esfandiari, Silvio Lattanzi, and Vahab S. Mirrokni. Parallel and streaming algorithms for k-core decomposition. In Jennifer G. Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 1396–1405. PMLR, 2018. 1

[FHW12] Silvio Frischknecht, Stephan Holzer, and Roger Wattenhofer. Networks cannot compute their diameter in sublinear time. In Yuval Rabani, editor, *Proceedings of the Twenty-Third Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2012, Kyoto, Japan, January 17-19, 2012*, pages 1150–1162. SIAM, 2012.

[FKM+05] Joan Feigenbaum, Sampath Kannan, Andrew McGregor, Siddharth Suri, and Jian Zhang. On graph problems in a semi-streaming model. *Theor. Comput. Sci.*, 348(2-3):207–216, 2005.

[FT14] Martin Farach-Colton and Meng-Tsung Tsai. Computing the degeneracy of large graphs. In Alberto Pardo and Alfredo Viola, editors, *LATIN 2014: Theoretical Informatics - 11th Latin American Symposium, Montevideo, Uruguay, March 31 - April 4, 2014. Proceedings*, volume 8392 of *Lecture Notes in Computer Science*, pages 250–260. Springer, 2014. 2

[FT16] Martin Farach-Colton and Meng-Tsung Tsai. Tight approximations of degeneracy in large graphs. In *LATIN 2016: Theoretical Informatics - 12th Latin American Symposium, Ensenada, Mexico, April 11-15, 2016, Proceedings*, pages 429–440, 2016. 2

[GBGL20] Edoardo Galimberti, Francesco Bonchi, Francesco Gullo, and Tommaso Lanciano. Core decomposition in multilayer networks: Theory, algorithms, and applications. *ACM Trans. Knowl. Discov. Data*, 14(1):11:1–11:40, 2020. 1

[GLM19] Mohsen Ghaffari, Silvio Lattanzi, and Slobodan Mitrovic. Improved parallel algorithms for density-based network clustering. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pages 2201–2210. PMLR, 2019. 1

[GO13] Venkatesan Guruswami and Krzysztof Onak. Superlinear lower bounds for multipass graph processing. In *Proceedings of the 28th Conference on Computational Complexity, CCC 2013, K.lo Alto, California, USA, 5-7 June, 2013*, pages 287–298, 2013.

[HSSW12] Magnús M. Halldórsson, Xiaoming Sun, Mario Szegedy, and Chengu Wang. Streaming and communication complexity of clique approximation. In *Automata, Languages, and Programming - 39th International Colloquium, ICALP 2012, Warwick, UK, July 9-13, 2012, Proceedings, Part I*, pages 449–460, 2012.

[IKL+12] Gábor Ivanyos, Hartmut Klauck, Troy Lee, Miklos Santha, and Ronald de Wolf. New bounds on the classical and quantum communication complexity of some graph properties. In *FSTTCS*, volume 18 of *LIPIcs*, pages 148–159. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2012.

[JKS03] T. S. Jayram, Ravi Kumar, and D. Sivakumar. Two applications of information complexity. In *STOC*, pages 673–682. ACM, 2003. 2, 7

[KBVT15] Wissam Khaouid, Marina Barsky, S. Venkatesh, and Alex Thomo. K-core decomposition of large networks on a single PC. *Proc. VLDB Endow.*, 9(1):13–23, 2015. 1

[Kla00] Hartmut Klauck. On quantum and probabilistic communication: Las vegas and one-way protocols. In *32nd Annual ACM Symposium on Theory of Computing (STOC)*, pages 644–651, 2000.

[KN97] Eyal Kushilevitz and Noam Nisan. *Communication complexity*. Cambridge University Press, 1997. 29

[KPP16] Tsvi Kopelowitz, Seth Pettie, and Ely Porat. Higher lower bounds from the 3sum conjecture. In Robert Krauthgamer, editor, *Proceedings of the Twenty-Seventh Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2016, Arlington, VA, USA, January 10-12, 2016*, pages 1272–1287. SIAM, 2016.

[KPSY23] Gillat Kol, Dmitry Paramonov, Raghuvansh R. Saxena, and Huacheng Yu. Characterizing the multi-pass streaming complexity for solving boolean csps exactly. In Yael Tauman Kalai, editor, *14th Innovations in Theoretical Computer Science Conference, ITCS 2023, January 10-13, 2023, MIT, Cambridge, Massachusetts, USA*, volume 251 of *LIPIcs*, pages 80:1–80:15. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2023.

[LJS19] Yang P. Liu, Arun Jambulapati, and Aaron Sidford. Parallel reachability in almost linear work and square root depth. In David Zuckerman, editor, *60th IEEE Annual Symposium on Foundations of Computer Science, FOCS 2019, Baltimore, Maryland, USA, November 9-12, 2019*, pages 1664–1686. IEEE Computer Society, 2019.

[LSY+22] Quanquan C. Liu, Jessica Shi, Shangdi Yu, Laxman Dhulipala, and Julian Shun. Parallel batch-dynamic algorithms for k-core decomposition and related graph problems. In Kunal Agrawal and I-Ting Angelina Lee, editors, *SPAA '22: 34th ACM Symposium on Parallelism in Algorithms and Architectures, Philadelphia, PA, USA, July 11 - 14, 2022*, pages 191–204. ACM, 2022. 1

[LWSX18] Chao Li, Li Wang, Shiwen Sun, and Chengyi Xia. Identification of influential spreaders based on classified neighbors in real-world complex networks. *Appl. Math. Comput.*, 320:512–523, 2018. 1

[LZZ+19] Conggai Li, Fan Zhang, Ying Zhang, Lu Qin, Wenjie Zhang, and Xuemin Lin. Efficient progressive minimum k-core search. *Proc. VLDB Endow.*, 13(3):362–375, 2019. 1

[MB83] David W. Matula and Leland L. Beck. Smallest-last ordering and clustering and graph coloring algorithms. *J. ACM*, 30(3):417–427, 1983. 1, 5

[McG14] Andrew McGregor. Graph stream algorithms: a survey. *SIGMOD Rec.*, 43(1):9–20, 2014.

[MN20] Sagnik Mukhopadhyay and Danupon Nanongkai. Weighted min-cut: sequential, cut-query, and streaming algorithms. In *STOC*, pages 496–509. ACM, 2020.

[MTVV15] Andrew McGregor, David Tench, Sofya Vorotnikova, and Hoa T. Vu. Densest subgraph in dynamic graph streams. In *Mathematical Foundations of Computer Science 2015 - 40th International Symposium, MFCS 2015, Milan, Italy, August 24-28, 2015, Proceedings, Part II*, pages 472–482, 2015. 2

[NW91] Noam Nisan and Avi Wigderson. Rounds in communication complexity revisited. In *Proceedings of the 23rd Annual ACM Symposium on Theory of Computing, May 5-8, 1991, New Orleans, Louisiana, USA*, pages 419–429, 1991.

[NW93] Noam Nisan and Avi Wigderson. Rounds in communication complexity revisited. *SIAM J. Comput.*, 22(1):211–219, 1993. 6, 9

[PRV99] Stephen Ponzio, Jaikumar Radhakrishnan, and Srinivasan Venkatesh. The communication complexity of pointer chasing: Applications of entropy and sampling. In *Proceedings of the Thirty-First Annual ACM Symposium on Theory of Computing, May 1-4, 1999, Atlanta, Georgia, USA*, pages 602–611, 1999. 6

[PS84] Christos H. Papadimitriou and Michael Sipser. Communication complexity. *J. Comput. Syst. Sci.*, 28(2):260–269, 1984.

[Raz92] Alexander A. Razborov. On the distributional complexity of disjointness. *Theor. Comput. Sci.*, 106(2):385–390, 1992. 2

[RSW18] Aviad Rubinstein, Tselil Schramm, and S. Matthew Weinberg. Computing exact minimum cuts without knowing the graph. In *ITCS*, volume 94 of *LIPIcs*, pages 39:1–39:16. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2018.

[RW13] Liam Roditty and Virginia Vassilevska Williams. Fast approximation algorithms for the diameter and radius of sparse graphs. In Dan Boneh, Tim Roughgarden, and Joan Feigenbaum, editors, *Symposium on Theory of Computing Conference, STOC'13, Palo Alto, CA, USA, June 1-4, 2013*, pages 515–524. ACM, 2013.

[SGJ+13] Ahmet Erdem Sariyüce, Bugra Gedik, Gabriela Jacques-Silva, Kun-Lung Wu, and Ümit V. Çatalyürek. Streaming algorithms for k-core decomposition. *Proc. VLDB Endow.*, 6(6):433–444, 2013. 1

[Yao79] Andrew Chi-Chih Yao. Some complexity questions related to distributive computing (preliminary report). In *Proceedings of the 11h Annual ACM Symposium on Theory of Computing, April 30 - May 2, 1979, Atlanta, Georgia, USA*, pages 209–213, 1979. 29

[Yeh20] Amir Yehudayoff. Pointer chasing via triangular discrimination. *Comb. Probab. Comput.*, 29(4):485–494, 2020. 5, 6, 7, 9, 25