Average-case ResLin depth-size tradeoff for binary-encoded clique

Susanna F. de Rezende, David Engström, Yassine Ghannane, Duri Andrea Janett, Artur Riazanov

arxiv:2605.10941; CC BY 4.0

Editorial note. Full original author sections including detailed ResLin continuation omitted by short version are preserved. Only selected formal theorem counts; random-graph/a.a.s. and parameter conditions retained. Two indicator-one glyphs render as bold 1 instead of unavailable bbm font; complete original TeX archive retained.

Allowed standard prerequisites (editorial).

- Author-cited bounded-arithmetic correspondence and complexity background. Complete source-local support and citations retained.

1 Introduction

The k-Clique problem asks whether a given graph G contains a complete subgraph of size k. This is one of the classical **NP**-hard problems [Karp(1972)]. Under the *Exponential Time Hypothesis*, solving k-Clique on an N-vertex graph requires time $N^{\Omega(k)}$ [Chen et al.(2004)Chen, Huang, Kanj, and Xia], nearly matching the $O(N^k)$ upper bound that can be obtained by simply checking all $\binom{N}{k}$ possible subgraphs. Furthermore, it is **NP**-hard to approximate the maximum size of a clique even within a factor $N^{1-\varepsilon}$ [Håstad(1999), Zuckerman(2007)].

Showing unconditional super-polynomial lower bounds for k-Clique seems beyond the reach of current techniques, as it would immediately imply $\mathbf{P} \neq \mathbf{NP}$. Thus, significant effort has been made to provide unconditional *evidence* for the hardness of k-Clique. The most direct evidence is hardness in restricted computational models. In circuit complexity, k-Clique was the first problem proven to require exponential-size *monotone Boolean circuits* [Razborov(1985)]. In a later breakthrough, Rossman [Rossman(2008), Rossman(2014)] showed that the k-Clique problem is hard for monotone and bounded-depth circuits even *on average*.

1.1 Clique in Proof Complexity

Another type of evidence for hardness comes from *propositional proof complexity*, the study of the complexity of certifying, in various formal proof systems, that a given Boolean formula is a tautology or that it is unsatisfiable.

Proof complexity provides a perspective to analyze several algorithmic approaches to the k-Clique problem: If an algorithm rejects a k-Clique instance, the trace of its execution can be viewed as a certificate of the claim that the given graph *does not* contain a k-clique. This claim can be encoded as a CNF formula asserting that the graph *does* have a k-clique, and in this paper we study certificates of unsatisfiability, also called *refutations*, of this formula. Many classes of algorithms can be captured by propositional proof systems in this way: the core reasoning of state-of-the-art SAT-solvers is captured by *resolution* [Beame et al.(2004)Beame, Kautz, and Sabharwal]; Gröebner basis algorithms by *polynomial calculus* [Clegg et al.(1996)Clegg, Edmonds, and Impagliazzo]; the cutting planes methods in integer linear optimization by the *cutting planes* proof system [Cook et al.(1987)Cook, Coullard, and Turán]; and the Lassere hierarchy in semi-definite programming [Lasserre(2001)] by the *sum-of-squares* proof system.

Assuming the *Nondeterministic Exponential Time Hypothesis* [Carmosino et al.(2016)Carmosino, Gao, Impagliazzo, Mih
in *every* proof system the shortest refutation of k-Clique for *some* graph has length at least $N^{\Omega(k)}$. On the other hand, unconditional lower bounds are only known for very restricted proof systems. Two encodings of the clique problem into CNF formulas are studied in the literature. The *unary encoding* uses N propositional variables to encode the ith vertex of the purported k-clique, for every i, while the more succinct *binary encoding* uses only $\log N$ variables to encode the same information in binary.

The following results are known about the unary encoding. For *treelike* resolution, there are $N^{\Omega(k)}$ length lower bounds even on average with respect to the Erdős-Rényi graph distribution [Beyersdorff et al.(2013)Beyersdorff, Galesi

Lauria(2018)]. The current best known results are analogous average-case bounds for *regular* resolution [Atserias et al.(2021) and Sherali–Adams with bounded coefficients [de Rezende et al.(2023)de Rezende, Potechin, and Risse]. For general resolution, in the parameter range $N^{5/6} \ll k \leq N/3$, an $\exp(N^{\Omega(1)})$ average-case lower bound for dense graphs is known [Beame et al.(2007a)Beame, Impagliazzo, and Sabharwal], and when $k < N^{1/3}$, an average-case lower bound $2^{k^{1-\varepsilon}}$ holds [Pang(2021)]. Improving this to an optimal $N^{\Omega(k)}$ lower bounds is a long-standing open problem, see, e.g., [Beyersdorff et al.(2012)Beyersdorff, Galesi, Lauria, and Razborov, Buss and Nordström(2021)], even for worst-case instances. In particular, all known techniques for proving resolution lower bounds seem to fail for this task [Atserias et al.(2021)Atserias, Bonacina, de Rezende, Lauria, Nordström, and

Weak proof systems can, however, be very sensitive to the choice of encoding, as was shown in, e.g., [Dantchev et al.(2024) This is also the case for the binary encoding of clique, where strong lower bounds are known for resolution: There is an $N^{\Omega(k)}$ average-case lower bound for resolution [Lauria et al.(2017)Lauria, Pudlák, Rödl, and Thapen], which was further extended to s-DNF resolution, for $s = o(\log \log n)$, at the cost of some loss in the exponent of the bound depending on s [Dantchev et al.(2024)Dantchev, Galesi, Ghani, and Martin].

1.2 Our contributions

We prove new lower bounds for k-Clique in three settings. Our first result is that the binary encoding of k-Clique requires exponential proof length in cutting planes. Prior to our work, nothing was known about the hardness of k-Clique for cutting planes, even in the treelike setting.

Theorem 1.1 (Informal)**.** *For N-vertex graphs G sampled from the Erdős-Rényi distribution with appropriate edge density, any cutting planes refutation of the binary-encoded clique formula must have length at least $2^{N^{\Omega(1)}}$.*

We consider next the frontier proof system *resolution over parities* (Res(⊕)) [Itsykson and Sokolov(2020)], which recently received a lot of attention [Bhattacharya et al.(2024)Bhattacharya, Chattopadhyay, and Dvorák, Alekseev and Itsykson(2025), Efremenko and Itsykson(2025), Bhattacharya and Chattopadhyay(2025), Byramji and Impag particularly following the breakthrough of [Efremenko et al.(2024)Efremenko, Garlík, and Itsykson]. Lower bounds are only known for restricted versions of this system, and in particular, nothing is known about the hardness of refuting k-Clique in Res(⊕). We prove the following length lower bound on Res(⊕) proofs of bounded depth.

Theorem 1.2 (Informal)**.** *For N-vertex graphs G sampled from the Erdős-Rényi distribution with appropriate edge density, any Res(⊕) refutation of the binary-encoded clique formula in depth $m^{1.5-\varepsilon}$, where m is the number of variables in the formula, must have length at least $2^{N^{\Omega(1)}}$.*

Lastly, we study the communication version of the problem. Two parties are both given partial information about the members of a purported k-clique in a graph G. Again, G does not actually have a k-clique, and the parties must find a missing edge in the purported clique, while communicating as few bits as possible. This corresponds to finding a falsified clause in the binary-encoded clique formula, if the partial information consists of the bits encoding the purported clique members. We prove the following lower bound in the setting where the parties have access to shared randomness.

Theorem 1.3 (Informal)**.** *For N-vertex graphs G sampled from the Erdős-Rényi distribution with appropriate edge density, the randomized communication cost of finding a falsified clause in the binary-encoded clique formula is $N^{\Omega(1)}$.*

Randomized communication complexity remains the most versatile tool for obtaining lower bounds for *treelike* cutting planes. Most of the known lower bounds are obtained via this connection [Impagliazzo et al.(1994)Impagliazzo Beame et al.(2007b)Beame, Pitassi, and Segerlind, Huynh and Nordström(2012), Göös and Pitassi(2018), Itsykson and Ria Treelike cutting planes is a natural next candidate for proving clique lower bounds in the *unary* encoding.

There is, however, a growing evidence that the randomized communication model is too strong to give strong lower bounds for k-Clique. If, for example, the density of Erdős-Rényi graph is constant, then Alice and Bob can randomly sample a pair of indices of their nodes and verify whether or not the corresponding pair is connected with an edge. Thus, we can only hope for a non-trivial lower bound for the dense setting of k-Clique. Another weakness of the communication approach to k-Clique lower bounds was established by Jukna [Jukna(2012)], who observed that for a *bipartite* version of the unary k-Clique, the corresponding problem has a $O(\log n)$-cost *deterministic* communication protocol.

Given these drawbacks, we view Theorem 1.3 as an indication of some hope for the communication approach to k-Clique lower bounds: at least in the dense binary setting the barriers above do not apply. Moreover, Theorem 1.3 (qualitatively) generalizes the main theorem in [Yang and Zhang(2024)] with a much simpler proof.

1.3 Discussion

Our contributions can be viewed as matching the lower bounds known for the *weak* version of *binary pigeonhole principle* (BPHP) with bounds for the binary encoding of k-Clique. In fact, all three bounds are obtained by adapting the techniques previously used to prove lower bounds for the weak binary pigeonhole principle [Beame and Whitmeyer(2025), Byramji and Impagliazzo(2025)], or by adapting extensions of such techniques [Göös et al.(2025a)Göös, Gur, Jain, and Li, Yang and Zhang(2024)]. Is there a more general principle behind our results, i.e., is there an explicit reduction from BPHP to average-case k-Clique? We know such a reduction exists in the *worst case*—indeed, the BPHP is a special case of the binary-encoded k-Clique—but in the average case such reductions are not known.

One concrete direction would be to prove

lower bounds on k-Clique in the treelike version of Th(2), the generalization of cutting planes refutations to degree-2 inequalities. Only the *strong* BPHP is known to be hard for this system [Itsykson and Riazanov(2021)], and the proof of this fact uses global symmetries of the formula. Therefore, it is unclear how to apply the technique to k-Clique for an Erdős-Rényi random graph, since the latter is unlikely to have symmetries. Does it fail because of the particular technique, or is the strong version of BPHP crucially easier than the weak one?

Open Problem 1.4. Suppose weak BPHP requires exponential tree-like Th(2) refutation. Show that the binary encoding of k-Clique does as well.

Another interesting direction to extend our lower bounds is to the *Ramsey principles* [Lauria et al.(2017)Lauria, Pudlák, R
A graph is c-*Ramsey* if it has neither a clique nor an independent set of size $c \log n$. The Ramsey principle formulas defined in [Lauria et al.(2017)Lauria, Pudlák, Rödl, and Thapen] encodes in binary the claim that a given graph is c-Ramsey. For resolution, an asymptotically optimal $n^{\Omega(\log n)}$ length lower bound was proven in [Lauria et al.(2017)Lauria, Pudlák, Rödl, and Thapen]. We ask the same question for cutting planes and Res($\oplus$).

Open Problem 1.5. Prove that the Ramsey principles are hard for cutting planes or bounded-depth Res($\oplus$).

In particular, matching the bounds known for resolution would require improving our lower bounds and extending them to randomly sampled graphs for a broader range of parameters, specifically to graphs which are not as dense.

As discussed above, for sparse graphs there is always a *randomized* communication protocol solving k-Clique in binary or unary encoding. However, we can weaken the communication model so it still captures tree-like cutting planes. One such model is a *deterministic* communication protocol with a Greater Than oracle, i.e., the players can compare real numbers at unit cost.

This model is shown to be significantly weaker than randomized communication [Chattopadhyay et al.(2019)Chattopadhy
Cheung et al.(2025)Cheung, Hatami, Hosseini, Nikolov, Pitassi, and Shirley, Göös et al.(2025b)Göös, Harms, and Riazano
Can we still solve k-Clique over a sparse graph?

Open Problem 1.6. Suppose that Π is a deterministic communication protocol with a Greater Than oracle. Can Π solve k-Clique for Erdős-Rényi graphs of constant sparsity with $O(\log n)$ cost?

1.4 Techniques

We give a brief technical overview of our proofs. Notably, all of our techniques are to some extent based on previous work proving lower bounds on BPHP.

Cutting Planes. Theorem 1.1 is proved via a *bottleneck counting* argument [Haken and Cook(1999)]. The approach is based on an adaptation of this framework to cutting planes due to Sokolov [Sokolov(2024)], that was also subsequently refined by Beame and Whitmeyer [Beame and Whitmeyer(2025)] to prove cutting planes BPHP lower bounds. It leverages a connection between cutting planes proofs and triangle-DAG protocols, saying that small cutting planes refutations of some formula imply small protocols for a related search problem. Informally, the main idea is to then define a partial function μ that maps inputs of the search problem to nodes of the protocol. Intuitively, μ measures progress made by the protocol at some step. By giving a lower bound on the size of the domain of μ and an upper bound on the maximum number of inputs mapped to each node, we establish a size lower bound on the protocol and thus on cutting planes refutations of our starting formula. The twist of our approach is to show that a certain combinatorial property of graphs related to the density of neighborhoods is sufficient to construct such a partial map μ. In particular, dense random graphs asymptotically almost surely exhibit such properties.

Bounded depth Res(⊕)**.** Recent progress has led to a BPHP lower bound for depth-$m^{1.5-\varepsilon}$ Res(⊕) [Byramji and Impaglia based on a notion of *closure* for a set of linear forms [Efremenko et al.(2024)Efremenko, Garlík, and Itsykson], and the *random walks with restarts* framework [Alekseev and Itsykson(2025)]. This framework works by performing a random walk on the proof in a top-down manner. If one can bound below the probability that this walk proceeds for many steps without reaching a falsified clause, and assuming that the given refutation is small, some node in the proof must be visited by many random walks, and thus the rank of the linear system at that node must be low. Using the notion of closure, one can then fix only few variables to satisfy that system, which allows repeating this procedure, walking further down the proof, and eventually establishing a depth lower bound.

Adapting the framework to binary-encoded clique formulas, finding a falsified clause is the same as identifying a non-edge in the underlying graph. Our random walk then mimics a uniformly drawn input while maintaining a partial assignment of the clique members to vertices without non-edges between them. We ensure this by always staying within the common neighborhood of previously assigned vertices, and find that the walk can proceed for many steps with sufficient probability. Additionally, we use concentrations bounds on the number of common neighbors of a set of vertices to show that, in the right parameter regimes, after fixing variables, the remaining instance is similar enough to a smaller instance of the original problem, thus allowing us to restart the random walk.

Randomized communication. Theorem 1.3 (qualitatively) generalizes the BPHP lower bound of Yang and Zhang [Yang and Zhang(2024)]. They used query-to-communication lifting machinery from [Göös et al.(2020)Göös, Pita to essentially reduce the communication lower bound to a corresponding *decision tree* lower bound. The proof in [Yang and Zhang(2024)] is quite involved due to a white-box use of the lifting machinery. Later, [Göös et al.(2025a)Göös, Gur, Jain, and Li] proved a structural theorem that allows a black-box proof of the main result in [Yang and Zhang(2024)], and this theorem was recently extended and used in [Riazanov et al.(2025)Riazanov, to get a lower bound for the clause-search problem for random $O(\log n)$-CNFs. We show how to apply this framework to the clique problem.

2 Preliminaries

We use the symbol ⊔ to denote a disjoint union of sets. We write $\{1, \ldots, n\}$ as $[n]$, where $n \in \mathbb{N}^+$. Let $\boldsymbol{x} \sim A$ denote $\boldsymbol{x}$ uniformly sampled from a set A. We say that an event occurs *asymptotically almost surely (a.a.s)* if it occurs with probability $1 - o(1)$ as $n \to \infty$. We will also need the following special case of the Chernoff bound:

Theorem 2.1 (Multiplicative Chernoff bounds)**.** *Let $\boldsymbol{X}_1, \ldots, \boldsymbol{X}_n$ be independent $\{0,1\}$-valued random variables, and let $\boldsymbol{X} = \sum_{i=1}^{n} \boldsymbol{X}_i$, $\mu = \mathbb{E}[\boldsymbol{X}]$. Then, for $0 \le \delta \le 1$,*

$$\Pr\left[\boldsymbol{X} \ge (1+\delta)\mu\right] \le \exp\left(-\frac{\mu\delta^2}{3}\right),$$
$$\Pr\left[\boldsymbol{X} \le (1-\delta)\mu\right] \le \exp\left(-\frac{\mu\delta^2}{2}\right).$$

2.1 Graph Theory

Let G be a graph over k blocks $V(G) = V_1 \sqcup \cdots \sqcup V_k$, with $|V_i| = n$ for all $i \in [k]$. In everything that follows, let us assume, without loss of generality, that n is a power of 2. For $u \in V(G)$, let $B(u) \in [k]$ denote the index of the block that contains u, and for every set of vertices $U \subseteq V(G)$, we define $B(U) \coloneqq \{B(u) \mid u \in U\}$. For a subset $U \subseteq V(G)$ we use $N^{\cap}(U, i)$ to denote the *common neighborhood* of U at block i. For a set of blocks $I \subset [k]$, we then use $N^{\cap}(U, I) = \bigcup_{i \in I} N^{\cap}(U, i)$. For all $i \in [k]$, every $u \in V_i$ can be identified with an integer in $[n]$, and we denote its binary representation by $\mathsf{bin}(u) = u_1 \ldots u_{\log(n)}$.

The natural distribution for which k-Clique is conjectured to be hard is an Erdős-Rényi distribution. The p-biased Erdős-Rényi distribution $\mathcal{G}(n,p)$ is defined by sampling an n-vertex graph with each of the $\binom{n}{2}$ edges present with probability p independently of the other edges. The parameter p that conjecturally makes finding a k-clique in $\boldsymbol{G} \sim \mathcal{G}(n,p)$ hard is at the threshold p' where for a lower $p < p'$ the graph $\boldsymbol{G}$ does not have a k-clique a.a.s., and for a higher $p > p'$ it does have a k-clique a.a.s.. By looking at the expected number of k-cliques in $\boldsymbol{G}$, one can conclude that the threshold value is $\Theta(n^{-2/(k-1)})$.

We also define the *k-partite* version of the same distribution: For a fixed partition of the nodes, $\mathcal{G}(n,p,k)$ is sampled from by first sampling $\boldsymbol{G} \sim \mathcal{G}(nk,p)$ and then intersecting $\boldsymbol{G}$ with a complete k-partite graph with n nodes in each part.

2.2 Proof Complexity

We next recall some basic notions from proof complexity; see, e.g., [Krajíček(2019), Buss and Nordström(2021)] for a more thorough exposition. A Boolean variable x or its negation $\overline{x}$ is called a *literal*, and a disjunction of literals over pairwise disjoint variables $C = \ell_1 \vee \cdots \vee \ell_k$ is called a *clause*. A *CNF formula* is a conjunction of clauses $F = C_1 \wedge \cdots \wedge C_m$. We sometimes call the clauses of F *axioms*, and denote the set of variables occurring in F as $\mathrm{Vars}(F)$.

Cutting Planes. The *cutting planes* proof system [Cook et al.(1987)Cook, Coullard, and Turán] operates on systems of linear inequalities. In its syntactic form, it derives new constraints from previously derived ones by *linear combination* and *division with rounding*. Since our lower bounds also apply to it, we define the stronger *semantic* version of the proof system, which subsumes all usual cutting planes derivation rules.

Let $Ax \geq b$ be a system of linear inequalities, where $A \in \mathbb{Z}^{m \times n}$ and $b \in \mathbb{Z}^m$. A *semantic cutting planes refutation* of $Ax \geq b$ is a sequence of linear inequalities $\{d_i x \geq c_i\}_{i \in [L]}$, where $d_i \in \mathbb{R}^n$ and $c_i \in \mathbb{R}$, such that the following hold: The final inequality is the trivially false $0 \geq 1$, and for every $i \in [L]$, the inequality $d_i x \geq c_i$ is part of the linear system $Ax \geq b$, or there are $j, k < i$ such that $d_i x \geq c_i$ follows from $d_j x \geq c_j$ and $d_k x \geq c_k$ by *semantic deduction*. That is, from inequalities $d_j x \geq c_j$ and $d_k x \geq c_k$, one can derive any inequality $d_i x \geq c_i$ for which it holds that any $x \in \{0,1\}^n$ satisfying both $d_j x \geq c_j$ and $d_k x \geq c_k$ satisfies $d_i x \geq c_i$. The *length* of a semantic cutting planes refutation is the number L of inequalities appearing in the sequence.

The following translation enables us to consider cutting planes refutations of unsatisfiable CNF formulas. For every propositional variable x, we add the constraints $0 \leq x$ and $x \leq 1$. For a clause $C = \bigvee_{i \in I} x_i \vee \bigvee_{j \in J} \overline{x_j}$, we add the inequality $\sum_{i \in I} x_i + \sum_{j \in J} (1 - x_j) \geq 1$.

Resolution over Parities. The *resolution over parities* proof system [Itsykson and Sokolov(2020)], which we refer to as Res($\oplus$), operates on linear equations over $\mathbb{F}_2$. Let $x_1, \ldots, x_n$ be variables taking values in $\mathbb{F}_2$. A *linear form* is a polynomial $\sum_{i=1}^n a_i x_i$, where all $a_i \in \mathbb{F}_2$. Taking a linear form f and $a \in \mathbb{F}_2$, we get a *linear equality* $f = a$. A disjunction of linear equations $C = \bigvee_{i=1}^m (f_i = a_i)$ is called a *linear clause*. Sometimes, it is convenient to view a linear clause as a negation of a linear system, i.e., $C = \neg \bigwedge_{i=1}^m (f_i = a_i + 1)$. Note that a propositional clause $C = \bigvee_{i \in I} x_i \vee \bigvee_{j \in J} x_j$ is a special case of a linear clause: we can write $C = \bigvee_{i \in I} (x_i = 1) \vee \bigvee_{j \in J} (x_j = 0)$.

Given a CNF formula F, a *Res($\oplus$) refutation of F* is a sequence of linear clauses $\{C_i\}_{i \in L}$ ending with the empty clause and where every clause either belongs to F or was derived from two previous clauses using one of the following two derivation rules: The *resolution rule*

$$\frac{C \vee (x = 1) \qquad D \vee (x = 0)}{C \vee D},$$

or the *semantic weakening rule*, which allows to derive from a linear clause C any linear clause D that semantically follows from it, i.e., such that any $x \in \{0,1\}^n$ satisfying C also satisfies D.

The *length* of a Res($\oplus$) refutation is the number L of linear clauses appearing in it. The *depth* d of a Res($\oplus$) refutation is the largest number of resolution steps among all the paths from axioms to the empty clause in the refutation. The proof system *depth-d Res($\oplus$)* is the subsystem of Res($\oplus$) consisting only of refutation of depth at most d, where d can depend on the number of variables n.

Shape-DAGs. We will also work with the top-down definition of the proof systems defined above, namely, *triangle-* and *affine-DAGs* solving *total search problems*. A *total search problem* is defined as a relation $S \subseteq \mathcal{I} \times \mathcal{O}$ over finite sets of inputs $\mathcal{I}$ and outputs $\mathcal{O}$, such that for every input $x \in \mathcal{I}$ there is an output $o \in \mathcal{O}$ with $(x, o) \in S$. Let $S^{-1}(o) = \{x \in \mathcal{I} \mid (x, o) \in S\}$.

For a given unsatisfiable CNF formula $F = C_1 \wedge \ldots C_m$, we consider the *falsified clause search problem* Search_F: Given an assignment $x \in \{0,1\}^n$ to the variables of F, output $i \in [m]$, such that the clause C_i is falsified under x. In detail, $(x, i) \in \mathrm{Search}_F$ if and only if $C_i(x) = 0$.

Definition 2.2 ([Garg et al.(2020)Garg, Göös, Kamath, and Sokolov]). Let $S \subseteq \mathcal{I} \times \mathcal{O}$ be a total search problem, $\mathcal{F} \subseteq 2^{\mathcal{I}}$. We call the elements of $\mathcal{F}$ *shapes*. A *shape-DAG* ($\mathcal{F}$-DAG) solving S is a rooted directed acyclic graph D of fan-out at most 2, where each node $v \in D$ is labeled by a shape $F_v \in \mathcal{F}$ such that

1. the root $r \in D$ is labeled by $F_r = \mathcal{I}$;
2. for a node v with children u, w, $F_v \subseteq F_u \cup F_w$;
3. and for every leaf ℓ, there is an output $o \in \mathcal{O}$ such that $F_\ell \subseteq S^{-1}(o)$.

The *depth* of D is the longest root-to-leaf path in D; its *length* is the number of nodes in it.

Given a bipartite domain $X \times Y$, a *triangle* $T \subseteq X \times Y$ is a set which can be written as $T = \{(x, y) \in X \times Y \mid a_T(x) \leq b_T(y)\}$, for some $a_T \colon X \to \mathbb{R}$, $b_T \colon Y \to \mathbb{R}$. A *triangle-DAG* is a shape-DAG where the shapes are all triangles. To consider triangle-DAGs for the falsified clause search problem, we split the variables of F into two parts and view $\{0,1\}^n$ as the corresponding product. Let $\mathrm{Search}_F^{X,Y} \subseteq (X \times Y) \times [m]$ denote $\{((x, y), i) \mid C_i(x, y) = 0\}$. As the following proposition states, lower bounds from cutting planes follow from lower bounds for triangle-DAGs.

Proposition 2.3 ([Sokolov(2017), Hrubeš and Pudlák(2018)]). *A semantic cutting planes refutation of a given CNF formula F yields, for any partition of the variables $Vars(F) = X \sqcup Y$, a triangle-DAG solving $\mathrm{Search}_F^{X,Y}$ of the same length.*

An *affine subspace-DAG* is a shape-DAG where the shapes are affine subspaces of the domain $\mathbb{F}_2^n$. An *affine-DAG* is an affine subspace-DAG D, where every non-leaf node $v \in D$ has two outgoing edges, (v, w) and (v, w'), labeled $P_v = 0$ and $P_v = 1$, respectively. In addition, for the linear systems $\Psi_v, \Psi_w, \Psi_{w'}$ corresponding to the affine subspaces labeling v, w, w', it holds that Ψ_w is implied by $\Psi_v \wedge (P_v = 0)$ and $\Psi_{w'}$ is implied by $\Psi_v \wedge (P_v = 1)$. Similar to Proposition 2.3, lower bounds for affine-DAGs can be used to derive lower bounds for Res($\oplus$), as stated formally below.

Proposition 2.4 ([Efremenko et al.(2024)Efremenko, Garlík, and Itsykson]). *A Res($\oplus$) refutation of a given CNF formula F yields an affine-DAG solving Search_F of the same length and depth.*

2.3 Binary Encoding of Clique Formula

We encode the claim that a graph G has a clique of size k. We use the so-called *binary encoding* [Lauria et al.(2017)Lauria, Pu Dantchev et al.(2024)Dantchev, Galesi, Ghani, and Martin], where for every $i \in [k]$, there are $\log|V|$ variables to point out the ith member of a purported k-clique. For a propositional variable x, we use the notation $(x \neq 0)$ to denote the literal x, and $(x \neq 1)$ to denote the literal $\overline{x}$.

Assume that the vertices v_i, v_j and v are represented as $v_{i,1}, \ldots, v_{i,\log|V|}$, $v_{j,1}, \ldots, v_{j,\log|V|}$, and $v_1, \ldots, v_{\log|V|}$ in binary, respectively. Let $x_{i,a}$, where $i \in [k]$ and $a \in [\log|V|]$, be propositional variables. The formula $\mathsf{BClique}(G, k)$ consists of the clauses

$$\bigvee_{a=1}^{\log|V|} (x_{i,a} \neq v_{i,a}) \vee \bigvee_{a=1}^{\log|V|} (x_{j,a} \neq v_{j,a}), \qquad \forall v_i \neq v_j \in V, i \neq j \in [k] : \{v_i, v_j\} \notin E, \tag{1}$$

$$\bigvee_{a=1}^{\log|V|} (x_{i,a} \neq v_a) \vee \bigvee_{a=1}^{\log|V|} (x_{j,a} \neq v_a), \qquad \forall v \in V, i \neq j \in [k]. \tag{2}$$

The clauses (1) are called *edge axioms*, and the clauses (2) are called *functionality axioms*. The edge axioms encode that two non-neighbors are not simultaneously chosen as clique members, while the functionality axioms ensure that all clique members are distinct.

Block encoding. We next consider a version of the binary clique formula, where cliques are required to have a "block-respecting" structure. That is, we partition the vertices of G into k *blocks* of equal size $V = V_1 \sqcup \cdots \sqcup V_k$. We then encode the claim that G has a k-clique with one vertex from every block. Such a clique is also called *transversal*.

Assume that v_i is represented as $v_{i,1}, \ldots, v_{i,\log n}$ and v_j is represented as $v_{j,1}, \ldots, v_{j,\log n}$. Let $x_{i,a}$, where $i \in [k]$ and $a \in [\log n]$, be propositional variables. Then the formula $\mathsf{BClique}_{\mathrm{block}}(G, k)$ consists of the clauses

$$\bigvee_{a=1}^{\log n} (x_{i,a} \neq v_{i,a}) \vee \bigvee_{a=1}^{\log n} (x_{j,a} \neq v_{j,a}), \qquad \forall v_i \in V_i, v_j \in V_j : \{v_i, v_j\} \notin E. \tag{3}$$

The clauses (3) are edge axioms, and again, encode that for $(v_i, v_j) \notin E$, "v_i is not the clique member from block i or v_j is not the clique member from block j". Note that in the block encoding, we do not need functionality axioms, since the clique members are from distinct blocks by definition.

The following lemma shows that lower bounds for $\mathsf{BClique}_{\mathrm{block}}(G, k)$ imply lower bounds for $\mathsf{BClique}(G, k)$. Therefore, for the rest of the paper, we will only consider the block encoding.

Lemma 2.5 ([Beame et al.(2007a)Beame, Impagliazzo, and Sabharwal]). *Let $k \in \mathbb{N}^+$ and G be a graph. If there is a cutting planes (respectively, Res($\oplus$)) refutation of $\mathsf{BClique}(G, k)$ of length L and depth d, then there is a cutting planes (respectively, Res($\oplus$)) refutation of $\mathsf{BClique}_{block}(G, k)$ of length at most L and depth at most d.*

While the statement in [Beame et al.(2007a)Beame, Impagliazzo, and Sabharwal] is for the unary encoding of clique formulas and the resolution proof system, its proof can be modified to obtain the lemma above. Indeed, one can obtain $\mathsf{BClique}_{\text{block}}(G,k)$ from $\mathsf{BClique}(G,k)$ by applying a random restriction, and both cutting planes and Res($\oplus$) are closed under random restrictions.

2.4 Communication Complexity

In this paper, we consider randomized (public coin) two party number-in-hand communication complexity. We quickly define the model and refer to [Kushilevitz and Nisan(1997), Rao and Yehudayoff(2020)] for details.

Two players, *Alice* and *Bob*, are given inputs $x \in X$ and $y \in Y$, respectively. To solve a search problem $S \subseteq (X \times Y) \times \mathcal{O}$, they need to find $o \in \mathcal{O}$ such that $((x,y),o) \in S$, while communicating as few bits as possible. A *deterministic communication protocol* Π for S is a rooted binary tree as follows. Every internal node $v \in \Pi$ determines who is going to speak, and the spoken bit, which is a function of v and the input x or y (x if Alice speaks, y otherwise), determines which child of v the computation moves to. Every leaf $\ell \in \Pi$ is labeled by $o_\ell \in \mathcal{O}$, such that $((x,y),o_\ell) \in S$. We define a *randomized communication protocol* Π_r for S as a distribution over deterministic communication protocols, such that the computation is correct with constant probability. The *cost* of a deterministic protocol $|\Pi|$ is the maximum, over all inputs, of the number of bits communicated. The *cost* of a randomized protocol $|\Pi_r|$ is the maximum cost among the deterministic protocols in the distribution.

We study the communication complexity of $\text{Search}^{X,Y}_{\mathsf{BClique}(G,k)}$, where we split the variables of $\mathsf{BClique}(G,k)$ such that Alice and Bob each get half of the bits from every clique member, i.e., $X = Y = (\{0,1\}^{\log|V|/2})^k$, and denote this problem by $\mathsf{BClique}^{cc}(G,k)$. As in the proof complexity setting, a version of Lemma 2.5 applies and we may prove lower bounds for the block encoding, i.e., for $\mathsf{BClique}^{cc}_{\text{block}}(G,k)$.

Furthermore, we will make use of the characterization of randomized communication cost in terms of distributional communication complexity [Yao(1983)]: To prove a lower bound on the randomized communication cost, it is enough to prove a lower bounds on deterministic protocols with constant error probability for *any* input distribution. In particular, we will prove a lower bound for the uniform distribution.

3 Density Properties of Random Graphs

In the subsequent sections, we prove hardness results for graphs satisfying some combinatorial property related to the density of their neighbor sets. In this section, we define the properties we consider and prove that random graphs satisfy them.

Definition 3.1. Given $s,k,n > 0$, we say a graph G over k blocks of size n is *s-almost-complete* if for every $i,j \in [k]$, $i \neq j$, and $x_i, y_i, x_j \in \Sigma$, where $\Sigma = \{0,1\}^{\log(n)/2}$, there are at most s different y_j such that there is no edge between (x_i,y_i) and (x_j,y_j) in G.

We show that random dense graphs a.a.s. satisfy this property for an appropriate value of s.

Lemma 3.2. *For $p \in [0,1]$, if $\boldsymbol{G} \sim \mathcal{G}(n,p,k)$, then, a.a.s., $\boldsymbol{G}$ is $\max(2\sqrt{n}(1-p), 9e^2\log(kn))$-almost-complete.*

Proof. For fixed $i,j \in [k]$ and fixed x_i, y_i, and x_j, let $\boldsymbol{Z}$ be the random variable denoting number of y_j such that there is no edge between (x_i,y_i) and (x_j,y_j). First, suppose that $p \leq 1 - \frac{9\log(nk)}{\sqrt{n}}$. Chernoff's inequality implies that

$$\Pr[\boldsymbol{Z} \geq 2\sqrt{n}(1-p)] \leq \exp\left(-\frac{\sqrt{n}(1-p)}{3}\right).$$

Taking a union bound over every choice of i,j and of x_i, y_i and x_j, we find that the probability of a graph not satisfying the desired property is bounded by

$$\begin{aligned}\binom{k}{2}\sqrt{n}^3 \cdot \Pr[\boldsymbol{Z} \geq 2\sqrt{n}(1-p)] &\leq k^2 n^{3/2} \cdot \exp\left(-\frac{\sqrt{n}(1-p)}{3}\right) \\ &\leq k^2 n^{3/2} \cdot \exp(-3\log(nk)) \ll \frac{1}{nk}.\end{aligned}$$

Now, we consider the case where $p > 1 - \frac{9\log(nk)}{\sqrt{n}}$. Then a naive union bound gives

$$\begin{aligned}\binom{k}{2}\sqrt{n}^3 \cdot \Pr[\boldsymbol{Z} \geq 9e^2\log(kn)] &\leq \binom{k}{2}\sqrt{n}^3\binom{\sqrt{n}}{9e^2\log(kn)}(1-p)^{9e^2\log(kn)} \\ &\leq \binom{k}{2}\sqrt{n}^3\left(\frac{\sqrt{n}}{9e\log(kn)}\right)^{9e^2\log(kn)}\left(\frac{9\log(kn)}{\sqrt{n}}\right)^{9e^2\log(kn)} \\ &\leq k^2\sqrt{n}^3\frac{1}{(kn)^{9e^2}}\,.\end{aligned}$$

This completes the proof of the lemma. □

The following property, which appeared in [de Rezende et al.(2023)de Rezende, Potechin, and Risse], is about the common neighborhood of small subsets of vertices. Similar definitions have also appeared in [Beame et al.(2007a)B Beyersdorff et al.(2013)Beyersdorff, Galesi, and Lauria, Atserias et al.(2021)Atserias, Bonacina, de Rezende, Lauria, Nords

Definition 3.3. Given $\alpha, \beta, R, k, n > 0$, we say a graph G over k blocks of size n has (α, β, R)-*bounded* common neighborhoods if every $S \subseteq V(G)$ of size at most R and every block $i \in [k] \setminus B(S)$ satisfies

$$N^{\cap}(S, i) \in (1 \pm \beta)\alpha^{|S|}n\,.$$

For random graphs, this property expresses that the size of common neighborhoods of small sets behaves approximately as expected.

Lemma 3.4. *For $0 \leq \delta < 1$, $p \geq 1 - n^{-\delta}$, $\beta \geq \sqrt{\frac{18\log(kn)}{n^{1-\delta}}}$, if $\boldsymbol{G} \sim \mathcal{G}(n, p, k)$, then, a.a.s., $\boldsymbol{G}$ has (p, β, n^{δ})-bounded common neighbors.*

Proof. For fixed $S \subseteq V(\boldsymbol{G})$ and $i \in [k] \setminus B(S)$, let $N^{\cap}_{\boldsymbol{G}}(S, i)$ be the random variable which is equal to the number of vertices of block i lying in the common neighborhood of S. By Chernoff's inequality,

$$\begin{aligned}\Pr_{\boldsymbol{G}}\left[\left|N^{\cap}_{\boldsymbol{G}}(S,i)\right| - p^{|S|}n\right| \geq \beta p^{|S|}n\right] &\leq 2\cdot\exp\left(-\frac{\beta^2 p^{|S|}\cdot n}{3}\right) \\ &\leq 2\cdot\exp\left(-\frac{\beta^2(1-|S|/n^{\delta})\cdot n}{3}\right)\,,\end{aligned}$$

where we use that $p^{|S|} \geq 1 - |S|n^{-\delta}$ for the second inequality. Then, by a union bound over all such sets S and blocks i, we conclude that $\boldsymbol{G}$ does not verify the property with probability at most

$$\begin{aligned}2k\cdot\sum_{j=1}^{n^{\delta}}\binom{kn}{j}\cdot\exp\left(-\frac{\beta^2(1-j/n^{\delta})\cdot n}{3}\right) &\leq 2k\cdot\sum_{j=1}^{n^{\delta}}(kn)^j\cdot\exp\left(-\frac{\beta^2 n}{6}\right) \\ &\leq 4k\cdot(kn)^{n^{\delta}}\exp\left(-3n^{\delta}\log(kn)\right) \\ &\leq \exp\left(2n^{\delta}\log(kn) - 3n^{\delta}\log(kn)\right) \\ &\leq \exp(-n^{\delta}\log(kn)).\end{aligned}$$

□

4 Lower Bound for Cutting Planes

This section is devoted to proving our first result, stated formally below.

Theorem 4.1. *For any integers n and k, and for any real $p \in [0, 1]$ if $\boldsymbol{G}$ is a graph sampled from $\mathcal{G}(n, p, k)$ then a.a.s. semantic cutting planes requires length*

$$\exp\left(\Omega\left(\min\left(\frac{1}{\sqrt{1-p}}, \frac{n^{1/4}}{\log(kn)}\right)\right)\right)$$

to refute $\mathsf{BClique}_{block}(G, k)$.

We quickly verify that Theorem 1.1 follows from the theorem stated above. For $p = 1 - n^{-1/3}$ and $k = n$, we have $N = nk = n^2$, and the bound in Theorem 4.1 becomes $2^{\Omega(N^{1/12})}$, and it applies to $\mathsf{BClique}(G, k)$ by Lemma 2.5. Also note that at this edge density, and with $k = n$, the formula $\mathsf{BClique}(G, k)$ is a.a.s. unsatisfiable, meaning the bound is non-trivial.

By Proposition 2.3 and Lemma 3.2, we obtain the above theorem by proving a size lower bound on triangle-DAG protocols solving the corresponding search problem, for the variable partition introduced in the preliminaries and over almost-complete graphs.

Algorithm 1: Definition of μ

Input: input set $X \times Y$ and triangle-DAG Π
Output: partial map $\mu : X \sqcup Y \to V(\Pi)$

Let $X' := X$ and $Y' = Y$; /* the remaining coordinates not yet assigned by μ */
for *u in a topological ordering of $V(\Pi)$, starting from the sinks* **do**
  /* T_u is the triangle at vertex u in Π */
  $T'_u := T_u \cap (X' \times Y')$;
  for $x \in X'$ **do**
    if $\mathsf{bw}(T_u, x) > q$ **then**
      Let $\mu(x) := u$ and delete x from X';
    $T'_u := T_u \cap (X' \times Y')$;
  for $y \in Y'$ **do**
    if $\mathsf{bw}(T_u, y) > q$ **then**
      Let $\mu(y) := u$ and delete y from Y';
    $T'_u := T_u \cap (X' \times Y')$;
return μ

Theorem 4.2. *Let $s, k, n > 0$, $q = n^{1/4}/\sqrt{8s}$ and G over k blocks of size n and s-almost-complete then triangle-DAG protocols solving* $\mathrm{Search}^{X,Y}_{\mathsf{BClique}(G,k)}$ *require size 2^{q-2}.*

To see that Theorem 4.1 follows from Theorem 4.2 recall that, by Lemma 3.2, $\boldsymbol{G} \sim \mathcal{G}(n, p, k)$ is, a.a.s., s-almost-complete for $s = \max(2\sqrt{n}(1-p), 9e^2 \log(kn))$. Applying Theorem 4.2 to such an s-almost-complete graph we have that

$$q = \frac{n^{1/4}}{\sqrt{8s}} = \Omega\left(\frac{n^{1/4}}{\sqrt{\max(\sqrt{n}(1-p), \log(nk))}}\right) = \Omega\left(\min\left(\frac{1}{\sqrt{1-p}}, \frac{n^{1/4}}{\log(kn)}\right)\right)$$

from which Theorem 4.1 follows. Before we present the proof of this theorem, let us establish some additional notation. Let G be a graph over k blocks each of size n with $V(G) = V_1 \sqcup \cdots \sqcup V_k$. Recall that for $X = Y = \Sigma^k$, where $\Sigma = \{0,1\}^{\log(n)/2}$, every $x = (x_i)_{1 \le i \le k} \in X$, $y = (y_i)_{1 \le i \le k} \in Y$, (x_i, y_i) uniquely identifies a vertex in the i-th block. Given $u \in V_i$ and $v \in V_j$, where $i \neq j$, we define $R_{u,v} \subseteq X \times Y$ to be the rectangle consisting of inputs $(x, y) \in X \times Y$ verifying $(x_i, y_i) = u$ and $(x_j, y_j) = v$, that is, $R_{u,v} := \{x \in X \mid x_i = u_1 \dots u_{\log(n)/2} \wedge x_j = v_1 \dots v_{\log(n)/2}\} \times \{y \in Y \mid y_i = u_{\log(n)/2+1} \dots u_{\log(n)} \wedge y_j = v_{\log(n)/2+1} \dots v_{\log(n)}\}$. Let $\mathcal{R}$ be the set of all rectangles $R_{u,v}$ where u and v are non-adjacent. Additionally, for any $R \in \mathcal{R}$, we define $B(R)$ to be the set of vertices $\{u, v\}$ such that $R = R_{u,v}$. Note that $\mathcal{R}$ corresponds to the collection of sets of inputs corresponding to pre-images of solutions of $\mathrm{Search}^{X,Y}_{\mathsf{BClique}(G,k)}$.

For a triangle $T \subseteq X \times Y$ and an input $x \in X$, let T^x denote the slice $(\{x\} \times Y) \cap T$. We define the *block width* [Sokolov(2024), Beame and Whitmeyer(2025)] of x in T, denoted $\mathsf{bw}(T, x)$, to be the minimum number of unique blocks mentioned in a covering of T^x by rectangles from $\mathcal{R}$, i.e

$$\mathsf{bw}(T, x) = \min_{\substack{S \subseteq \mathcal{R} \\ T^x \subseteq \bigcup_{R \in S} S}} \left| \bigcup_{R \in S} B(R) \right|.$$

When T is evident from context, we simply call this the block width of x.

The proof of the main theorem is based on a bottleneck counting argument following a framework that appeared in previous work [Haken and Cook(1999), Sokolov(2024), Beame and Whitmeyer(2025)], adapted to our setting. We construct a partial function $\mu \colon X \sqcup Y \to V(\Pi)$, defined in Algorithm 1 for which we prove two properties. First, we show that a substantial fraction of all inputs must be assigned by μ to some node. We then prove that no single node can have many inputs assigned to it and conclude that there must be many nodes in the protocol.

Informally, for a threshold q, the map μ is constructed by traversing the nodes of the triangle-DAG in topological order from the leaves to the root and, whenever we encounter a $z \in X \sqcup Y$ such that $\mathsf{bw}(T, z) > q$, we let μ map z to that node in Π and remove z from all nodes not yet considered.

The first property of μ is straightforwardto prove.

Lemma 4.3. *For $q \le n^{1/4}/\sqrt{s}$ and G s-almost-complete, then μ assigns at least $|X \sqcup Y|/4$ elements.*

Algorithm 2: Definition of a tree $\mathcal{T}$ of potential coverings of T'^x

Input: Sets $X' \subseteq X$, $Y' \subseteq Y$, and triangle $T' \subseteq X' \times Y'$ s.t. $\mathsf{bw}(T', y) \leq 2q$ for all $y \in Y'$
Output: A tree $\mathcal{T}$ of coverings of T'^x for every $x \in X'$

```
Initialize 𝒯 as a tree with a single node labeled T';
Let Leaves := {T'};
while Leaves ≠ ∅ do
    Choose some T from Leaves and remove it from Leaves;
    Choose a y ∈ Y such that |T^y| is maximized;
    Let R_{u_1,v_1}, ..., R_{u_ℓ,v_ℓ} be a minimal covering for T^y with respect to block-width;
    /* note that |B({u_1, v_1, ..., u_ℓ, v_ℓ})| ≤ 2q                                  */
    for i ∈ [ℓ] do
        Let R := R_{u_i,v_i} = X_R × Y_R;
        Let T_R := T ∩ (X_R × (Y ∖ Y_R));
        Add an edge to 𝒯 labeled by (u_i, v_i) from the node of 𝒯 labeled T to a new leaf labeled by T_R;
        if T_R ≠ ∅ then
            Add T_R to Leaves;
return 𝒯
```

Proof. Consider the rectangle $T'_r = X' \times Y'$ of unassigned inputs at the root. We prove that either X' is empty and therefore μ assigns $|X| = |X \sqcup Y|/2$ elements, or $|Y'| \leq |Y|/2$ and thus μ assigns at least $|Y|/2 = |X \sqcup Y|/4$ elements.

If X' is empty, then we are done; otherwise, let x be any element in X'. By construction of μ, there exists a set $S \subseteq \mathcal{R}$ that covers $\{x\} \times Y'$ and mentions at most q blocks. Since the graph is s-almost-complete, and since every rectangle of S is indexed by a pair of vertices that do not share an edge,

$$|S| \leq \binom{q}{2}\sqrt{n} \cdot s \leq n/2\,, \tag{4}$$

where we use that $q \leq n^{\frac{1}{4}}/\sqrt{s}$. This implies that

$$\begin{aligned}\Pr_{\boldsymbol{y}\sim Y}\left[\boldsymbol{y} \in Y'\right] &\leq \Pr_{\boldsymbol{y}\sim Y}\left[\exists R_{u,v} \in S \text{ s.t. } (x, \boldsymbol{y}) \in R_{u,v}\right] \\ &\leq |S|/n \\ &\leq 1/2\,,\end{aligned}$$

and therefore, $|Y'| < |Y|/2$, which concludes the proof. □

By definition of a triangle-DAG, the following claim is immediate from Algorithm 1.

Claim 4.4 ([Sokolov(2024), Beame and Whitmeyer(2025)])**.** *During the execution of Algorithm 1, for every u in the triangle-DAG Π and $z \in X' \cup Y'$, the block width of z in T'_u is at most $2q$.*

We now state the main lemma of this section.

Lemma 4.5. *Let $q \leq n^{1/4}/\sqrt{8s}$ and G s-almost-complete. For all $u \in V(\Pi)$, μ maps at most $|X \sqcup Y| \cdot 2^{-q}$ elements of $X \sqcup Y$ to u.*

Assuming this lemma, Theorem 4.2 follows immediately.

Proof of Theorem 4.2. By Lemma 4.3, at least $|X \sqcup Y|/4$ elements from $|X \sqcup Y|$ are assigned to some vertex in Π by μ. On the other hand, Lemma 4.5 bounds the number of $z \in X \sqcup Y$ assigned to any one vertex in Π. Put together, we conclude that there must be at least $\frac{|X\sqcup Y|/4}{|X\sqcup Y|2^{-q}} = 2^{q-2}$ vertices in Π. □

The rest of this section is dedicated to the proof of Lemma 4.5. Fix $u \in V(\Pi)$. Our goal is to show that the number of elements $x \in X$ assigned by μ to u is at most $2^{-q} \cdot |X|$. By symmetry, we have the same bound on the number of such $y \in Y$ and the lemma follows.

To obtain this bound, we run Algorithm 2 on $T' = (X' \times Y') \cap T_u$, with X' and Y' taking their values right before processing node u in Algorithm 1. From this, we obtain a tree $\mathcal{T}$ with the inner nodes labeled by triangles that are subsets of T' not covered yet, and with the edges labeled by rectangles in $\mathcal{R}$. It satisfies the following properties:

1. First, the set of edge label rectangles cover T', i.e., for every (x, y) in T', there is an edge labeled $R_{u,v}$ s.t. $(x, y) \in R_{u,v}$.

2. Second, if $(x, y) \in T'$ is in triangle T_1 at node t_1, and (x, y) is in triangle T_2 at node t_2, then either t_1 is a descendant of t_2 or vice-versa, and (x, y) is in every triangle labeling nodes between t_1 and t_2.

3. Furthermore, for every x, there is a unique path from the root to some leaf t in T' such that $\{R_{u,v} \mid R_{u,v} \text{ edge labels of path}\}$ covers T'^x.

For any node t of $\mathcal{T}$ whose path from the root is labeled by $R = (R_1, R_2, \ldots, R_\ell)$, the block-depth of t is the number of unique blocks mentioned by the rectangles in R. Then, the block-depth of an input $x \in X'$ is the maximal block-depth over nodes that x is consistent with.

Note that for every leaf t in $\mathcal{T}$, property 3 above implies that the block-depth of t is an upper bound on $bw(T'_u, x)$ for any $x \in X'$ consistent with t. To prove the lemma, we thus only have to bound the number of elements $x \in X'$ that are consistent with leaves of block-depth greater than q. Before doing so, we prove a claim that will allow us to simplify $\mathcal{T}$.

Claim 4.6. *Let t be a vertex in $V(\mathcal{T})$. If t has out-degree greater than one, then every child of t has block-depth greater than the block-depth of t.*

Proof. Let t' be a vertex that has the same block-depth as its parent t. The edge from t to t' must be labeled by a rectangle $R_{u,v}$ with vertices from blocks $i = B(u)$ and $j = B(v)$, both already mentioned on the path from the root to t. In particular, this means that all $x \in X'$ consistent with t agree on the ith and jth coordinate.

Now, let $y \in Y$ chosen when processing t in Algorithm 2. If there exists an $x' \in X'$ consistent with t such that $(x', y) \in R_{u,v}$, i.e., such that $(x'_i, y_i) = u$ and $(x'_j, y_j) = v$, this implies that for every $x \in X'$ consistent with t it holds that $(x_i, y_i) = u$ and $(x_j, y_j) = v$ since x agrees with x' in the ith and jth coordinate, and therefore $(x, y) \in R_{u,v}$. Hence T^y in Algorithm 2 is fully covered by $R_{u,v}$ and the out-degree of t is 1. □

We can now modify $\mathcal{T}$ by removing every vertex in $\mathcal{T}$ with a child of the same block-depth and replacing it with that child. This leaves us with a new tree $\mathcal{T}'$ where every path from the root to a leaf has strictly increasing block-depth. Note that the block-depth of an input $x \in X'$ is the same in $\mathcal{T}'$ as in $\mathcal{T}$. In order to conclude the proof, it is now sufficient to prove the following claim.

Claim 4.7. *The number of vertices at block-depth d in $\mathcal{T}'$ is at most $\left(\frac{\sqrt{n}}{2}\right)^d$.*

Proof. We prove this by induction over the block-depth d. For $d \leq 1$, the claim follows since the only vertex at block-depth 0 is the root of $\mathcal{T}'$, and there are no vertices at block-depth 1.

For the induction step, note that the children of a vertex $t \in V(\mathcal{T}')$ at block-depth d' either have block-depth $d' + 1$ or $d' + 2$. We will argue that any vertex $t \in V(\mathcal{T}')$ at block-depth d' can have at most $\sqrt{n}/4$ children of block-depth $d' + 1$ and at most $n/4$ children of block-depth $d' + 2$. This would imply the claim since we can conclude that, for $d \geq 2$, there are at most

$$\frac{\sqrt{n}}{4}\left(\frac{\sqrt{n}}{2}\right)^{d-1} + \frac{n}{4}\left(\frac{\sqrt{n}}{2}\right)^{d-2} \leq \left(\frac{\sqrt{n}}{2}\right)^d$$

vertices at block-depth d, where we apply the induction hypothesis to bound the number of vertices at level $d - 1$ and $d - 2$.

Let $t \in V(\mathcal{T}')$ be a vertex at block-depth d'. Consider the y chosen when processing this vertex in Algorithm 2 and the rectangles $R_{u_1,v_1}, \ldots, R_{u_d,v_d}$ chosen to be a minimal covering for T^y. These rectangles are the labels of the out-edges of t. Since the block-width of y is at most $2q$, there is a set of indices $S \subseteq [k]$, with $|S| \leq 2q$, such that $B(\{u_1, v_1, \ldots, u_d, v_d\}) \subseteq S$.

We first argue that t has at most $\sqrt{n}/4$ children of block-depth $d' + 1$. A child of t which is adjacent to an edge labeled $R_{u,v}$ is at level $d' + 1$ if and only if exactly one of $B(u)$ or $B(v)$ is a block that already appeared in the path from the root of $\mathcal{T}$ to t. For each pair of indices $i, j \in S$, where i already appears in the path from the root to t and j does not, we bound the number of rectangles $R_{u,v}$ such that $\{i, j\} = B(\{u, v\})$. Since i appears earlier in the path, all $x \in X'$ consistent with t agree on the ith coordinate and thus x_i is fixed for all rectangles $R_{u,v}$ labeling the out-edges of t with $B(\{u, v\}) = \{i, j\}$. Since G is s-almost-complete, and both y_i and y_j are clearly also fixed in T^y, then there are at most s such rectangles. Considering every possible pair of indices (i, j), of which there are at most $\binom{|S|}{2} \leq 2q^2$, we conclude that t has at most $2q^2 s \leq \frac{\sqrt{n}}{4}$ children of block-depth $d' + 1$.

It remains to argue that t has at most $n/4$ children of block-depth $d' + 2$. A child of t which is adjacent to an edge labeled $R_{u,v}$ is at level $d' + 2$ if and only if neither $B(u)$ nor $B(v)$ is a block that appears in the

path from the root of $\mathcal{T}$ to t. For each pair of indices $i, j \in S$, where neither i nor j appears in the path from the root to t, and for each $x_i \in [\sqrt{n}]$ we use that G is s-almost-complete (again using that y_i and y_j are fixed in T^y) to obtain that the number of rectangles $R_{u,v}$ labeling out-edges of t such that $B(u) = i$, $B(v) = j$ and $(x_i, y_i) = u$ is at most s. Considering every possible pair of indices (i, j) and every $x_i \in [\sqrt{n}]$, we conclude that t has at most $2q^2\sqrt{n}s \leq n/4$ children of block-depth $d' + 2$. □

Given this claim we can conclude that Lemma 4.5 holds. Indeed, every $x \in X'$ mapped by μ must be consistent with a leaf in $\mathcal{T}$ of block-depth larger that q, and since block-depth can only increase by 1 or 2 from parent to child in $\mathcal{T}$, every $x \in X'$ consistent with a leaf of block-depth greater that q is consistent with a vertex of block-depth exactly $q + 1$ or $q + 2$. Furthermore, only $|X|/\sqrt{n}^{\ell}$ inputs $x \in X'$ can be consistent with a vertex $t \in V(\mathcal{T}')$ at block-depth ℓ since all $x \in X'$ consistent with t coincide on the ℓ blocks mentioned on the path to t. From Claim 4.7, it follows that at most

$$\left(\frac{\sqrt{n}}{2}\right)^{q+1} \cdot \frac{|X|}{(\sqrt{n})^{q+1}} + \left(\frac{\sqrt{n}}{2}\right)^{q+2} \cdot \frac{|X|}{(\sqrt{n})^{q+2}} \leq \cdot 2^{-q}|X|$$

elements of $|X|$ are mapped to u by μ. By symmetry the same holds for $|Y|$ and the lemma follows.

5 Lower Bound for Bounded Depth Resolution over Parities

In this section, we prove our second result, stated formally below.

Theorem 5.1. *Let $\gamma > 0$ be a constant, let $p \in [1 - n^{-\gamma}, 1]$ and $k \in \mathbb{N}$ be functions of n, where $k < \exp(n^{o(1)})$ and let $\boldsymbol{G} \sim \mathcal{G}(n, p, k)$. Then asymptotically almost surely, for any Res($\oplus$)-refutation of depth D and size S that refutes $\mathsf{BClique}(G, k)$ it must hold that*

$$D\sqrt{\log S} \geq \begin{cases} \Omega(n^{3\gamma/2}), & \text{if } \gamma < 1/2 \\ \Omega(\frac{n^{\frac{1+\gamma}{2}}}{\sqrt{\log kn}}), & \text{if } 1/2 \leq \gamma < 1 \\ \Omega(n^{1-\varepsilon}), & \text{if } \gamma \geq 1 \end{cases}$$

for any constant $\varepsilon > 0$.

We start by verifying that Theorem 1.2 from the introduction follows from this theorem. Let $\gamma = 1/3$ and $k = n^{1/3+\varepsilon/100}$ for $\varepsilon > 0$ given in Theorem 1.2. Then $N = kn = n^{4/3+\varepsilon/100}$, and $\mathsf{BClique}(G, k)$ has $m = k \log N = O(n^{1/3+\varepsilon/100} \log n)$. So, if

$$D \leq m^{1.5-\varepsilon} = O(n^{(1/3+\varepsilon/100)(1.5-\varepsilon)} \log^{1.5-\varepsilon} n) = o(n^{3\gamma/2-\varepsilon/4}),$$

we have that $\log S = \Omega(\text{poly}(n)) = \Omega(\text{poly}(N))$. Therefore, sampling $\mathbf{G}$ using $p = n^{-1/3}$ and $k = n^{1/3+\varepsilon/100}$ a.a.s. yields an unsatisfiable formula requiring size $S = 2^{N^{\Omega(1)}}$ to refute in depth at most $m^{1.5-\varepsilon}$, as required.

To prove Theorem 5.1 we prove the slightly more general statement below.

Theorem 5.2. *Let $\alpha > 0$, $0 < \beta < 1/300$ be real numbers and let $R \leq 1/100(1 - \alpha)$ be a positive integer. Given a graph G with (α, β, R)-bounded common neighborhoods and a Res($\oplus$)-refutation of $\mathsf{BClique}(G, k)$ of depth D and size S, it must hold that*

$$D\sqrt{\log S} \geq \Omega(R \cdot \min(\sqrt{R}, 1/\beta))$$

The remainder of this section is dedicated to the proof of this theorem. But first we show that Theorem 5.1 follows from Theorem 5.2.

Proof of Theorem 5.1. Let $\alpha = p \geq 1 - n^{-\gamma}$. We choose δ differently according to γ. Let $\delta = \gamma$ if $\gamma < 1$, otherwise, let $\delta = 1 - \varepsilon$. Now let $R = n^{\delta}/100$ and let $\beta = \sqrt{\frac{18 \log(kn)}{n^{1-\delta}}}$. By Lemma 3.4, $\boldsymbol{G}$ will asymptotically almost surely have (α, β, R)-bounded common neighbourhoods. Note that $R \leq 1/100(1 - \alpha)$ and so we can apply Theorem 5.2 and obtain the lower bound

$$D\sqrt{\log S} \geq \Omega(R \cdot \min(\sqrt{R}, 1/\beta)).$$

We split the analysis into cases depending on γ. If $\gamma < 1/2$, note that $1/\beta \geq n^{-\delta/2} = n^{-\gamma/2} \geq \sqrt{R}$ for large enough n and $k < \exp(n^{o(1)})$, and therefore we get the first lower bound, that is, $D\sqrt{\log S} \geq \Omega(n^{\gamma} \cdot n^{\gamma/2}) = \Omega(n^{3\gamma/2})$.

If $\gamma \geq 1/2$, note that $1/\beta \leq n^{(1-\delta)/2} \leq n^{\delta/2} = 10\sqrt{R}$ for large enough n and using the assumption $k < \exp(n^{o(1)})$. This implies that we get the bound

$$D\sqrt{\log S} \geq \Omega\left(n^{\gamma} \cdot \frac{n^{\frac{1-\gamma}{2}}}{\sqrt{\log nk}}\right) = \Omega\left(\frac{n^{\frac{1+\gamma}{2}}}{\sqrt{\log nk}}\right)$$

for $1/2 \leq \gamma < 1$ and the bound

$$D\sqrt{\log S} \geq \Omega\left(n^{\delta} \cdot \frac{n^{\frac{1-\delta}{2}}}{\sqrt{\log nk}}\right) = \Omega\left(\frac{n^{\frac{1+\delta}{2}}}{\sqrt{\log nk}}\right) = \Omega\left(\frac{n^{1-\varepsilon/2}}{\sqrt{\log nk}}\right) \geq \Omega\left(n^{1-\varepsilon}\right)$$

for $\gamma > 1$, where for the last inequality we assume n large enough and $k < \exp(n^{o(1)})$.

□

The proof of Theorem 5.2 adapts the proof by Byramji and Impagliazzo [Byramji and Impagliazzo(2025)] of a Res(⊕) size depth tradeoff for the BPHP. They do this by showing that in a small Res(⊕) refutation of BPHP, it is possible to repeatedly perform long random walks without reaching a sink.

5.1 Technical Lemmas and Definitions

Here we collect some technical preliminaries that are used only in this section. We start by recalling the notion of safe systems, introduced by [Efremenko et al.(2024)Efremenko, Garlík, and Itsykson].

We say that a set of linear forms F over variables $x_{i,j} \in (\{0,1\}^{\log n})^{[k]}$ is *dangerous* if the number of distinct blocks from which variables appear in F is smaller than the size of F. If no subset of F is dangerous we say that F is *safe*. It turns out that safe sets have a very nice characterization making them nice to work with.

Lemma 5.3 ([Efremenko et al.(2024)Efremenko, Garlík, and Itsykson])**.** *Let L be a collection of k independent linear forms and M the corresponding coefficient matrix. V is safe if and only if we can pick k variables, no two from the same block, such that the corresponding columns in M are linearly independent.*

To handle non-safe systems we use the notion of closure. The *closure* of F, $\mathrm{Cl}(F) \subseteq [k]$ is defined as the minimal set (with respect to inclusion) of blocks such that $F[\setminus \mathrm{Cl}(F)]$ is safe, where $F[\setminus S]$ denotes the set of linear forms F after setting variables belonging to a block in S to zero. It turns out that the closure is uniquely defined [Efremenko et al.(2024)Efremenko, Garlík, and Itsykson, Lemma 4.1]. In an abuse of notation we will, for a linear system Ψ, write $\mathrm{Cl}(\Psi)$ to refer to the closure of

Lemma 5.4 ([Efremenko et al.(2024)Efremenko, Garlík, and Itsykson])**.** *If F is a collection of linear forms, then $|\mathrm{Cl}(F)| + \dim(\langle F[\setminus \mathrm{Cl}(F)]\rangle) \leq \dim(F)$.*

To assign variables in a way that satisfies linear systems, we need the concept of affine restrictions. A (block respecting) *affine restriction* ρ is a partial assignment that for some set $F \subseteq [k]$ sets all variables $x_{i,j}$, $i \in [k] \setminus F$ as an affine function of the unassigned variables $x_{i,j}$, $i \in F$. In this paper all affine restrictions will be block respecting and will for brevity just be called affine restrictions. For a linear system Ψ we use $\Psi|_\rho$ to denote the system after substituting variables according to ρ.

We introduce the search problem $\mathrm{NonEdge}_M^G \subseteq (\{0,1\}^{\log n})^{[k]\setminus B(M)} \times \binom{V(G)}{2}$, where M is some set of vertices of G such that vertices in M from distinct blocks in G always have edges between them. As input we are given an assignment to the blocks outside of the support of M such that every selected vertex lies in $N^{\cap}(M, [k] \setminus B(M))$. We are then asked to output two selected vertices not connected by an edge. When the graph G is clear from context, we simply write $\mathrm{NonEdge}_M$. Observe that $\mathrm{NonEdge}_M^G$ is equivalent to $\mathrm{Search}_{\mathsf{BClique}(G', k-|B(M)|)}$ where G' is the subgraph of G induced by $N^{\cap}(M, [k]\setminus B(M))$. Thus, any affine-DAG solving the falsified clause search problem also solves $\mathrm{NonEdge}_\emptyset^G$, as such it is enough to find lower bound for this problem. The following lemma was stated in [Byramji and Impagliazzo(2025)] with $A_1 = A_2 = \cdots = A_n$. Their proof still works for or slightly more general formulation.

Lemma 5.5 ([Byramji and Impagliazzo(2025), Lemma 4.6])**.** *Let Ψ be a linear system on $(\{0,1\}^{\log n})^k$ whose rank is r. For each $i \in [k]$ let $A_i \subseteq \{0,1\}^{\log n}$ be such that $|A_i| \geq 2n/3$. Let $\boldsymbol{x}_i \sim A_i$ independently for each $i \in [k]$ Then*

$$\Pr[\boldsymbol{x} \text{ satisfies } \Psi] \leq \left(\frac{3}{4}\right)^r.$$

Lastly, we will later need to use a Chernoff bound on the sum of dependent variables. For this the following lemma will be useful.

Lemma 5.6 ([Mitzenmacher and Upfal(2017), Lemma 17.3]). *Let $\boldsymbol{X}_1, \boldsymbol{X}_2 \ldots, \boldsymbol{X}_n$ be a sequence of random variables in an arbitrary domain and let $\boldsymbol{Y}_1, \boldsymbol{Y}_2, \ldots, \boldsymbol{Y}_n$ be a sequence of binary variables with the property that $\boldsymbol{Y}_i = \boldsymbol{Y}_i(\boldsymbol{X}_1, \ldots, \boldsymbol{X}_i)$. If*

$$\Pr[\boldsymbol{Y}_i = 1 \mid \boldsymbol{X}_1, \ldots, \boldsymbol{X}_{i-1}] \leq p,$$

then

$$\Pr\left[\sum_{i=1}^{n} \boldsymbol{Y}_i > k\right] \leq \Pr\left[\mathrm{Ber}^n(p) > k\right].$$

5.2 Proof of Theorem 5.2

Throughout this section we let $\alpha, \beta < 1/300$ be positive real values and $R < 1/100(1-\alpha)$ a positive integer. Furthermore, we assume G is a fixed graph with (α, β, R)-bounded common neighborhoods. Note that this choice of parameters ensures that for every vertex set $|M| \leq R$, $|N^{\cap}(M, i)| \leq 2n/3$.

The proof of Theorem 5.2 follows the same strategy as [Byramji and Impagliazzo(2025)]. Given an affine-DAG solving $\mathrm{NonEdge}_M$ we wish to find an affine-DAG of much smaller depth solving a slightly smaller instance $\mathrm{NonEdge}_{M^*}$; repeating this process shows that the original depth must have been large. Formally, we use the following lemma which we will spend the remainder of the section proving.

Lemma 5.7. *Let $M \subseteq V(G)$ be a set of vertices and suppose there is an affine-DAG Π solving $\mathrm{NonEdge}_M$ whose depth is at most D and size is at most S. Then*

$D > (R - |M|)/8$.

Moreover, for some universal constant C it holds that if $|M| + 8d \leq R$ for $d = \lfloor \sqrt{\log S} \cdot \min(\sqrt{R}, 1/\beta) \rfloor$ then there exists a set $M^* \supseteq M$ of size $|M^*| \leq |M| + C \log S$ and an affine-DAG Π' solving $\mathrm{NonEdge}_{M^*}$ whose depth is at most $D - d$ and size is at most S.

First we show how Theorem 5.2 follows from Lemma 5.7.

Proof of Theorem 5.2. A Res($\oplus$)-refutation of $\mathsf{BClique}(G, k)$ of depth D and size S immediately gives an affine Π solving $\mathrm{NonEdge}_\emptyset$. Let $d = \lfloor \sqrt{\log S} \cdot \min((1-\alpha)^{-1/2}, 1/\beta) \rfloor$ we start by considering the case when $8d \geq R/2$. Then

$$R \leq 16d \leq \sqrt{\log S} \min(\sqrt{R}, 1/\beta) \leq \sqrt{\log S}\sqrt{R}.$$

This means $\sqrt{\log S} \geq \sqrt{R}$ and the desired bound follows immediately since by Lemma 5.7 we have that $D > R/8$.

Now consider the case $8d < R/2$. We can here use Lemma 5.7 to find a set M_1 of size $|M_1| = C \log S$ and an affine-DAG Π_1 of depth at most $D - d$ and size at most S solving $\mathrm{NonEdge}_{M_1}$. We keep applying Lemma 5.7 iteratively in this way, using $M = M_{t-1}$ to find $M_t = M^*$ of size $|M_t| \leq tC \log S$ and Π_t of depth at most $D - dt$ and size at most S. We repeat this process as long as the condition of Lemma 5.7 holds, i.e., as long as $|M_t| + 8d \leq R$. Thus the final t must satisfy $tC \log S + 8d \geq R$ which means $t \geq R/2C \log S$. But at that point we have an affine-DAG Π_t of depth $D - dR/2C \log S$ solving M_t. Since an affine-DAG cannot have negative depth we find that $D \geq \Omega(dR/\log S) = \Omega(R \cdot \min(\sqrt{R}, 1/\beta)/\sqrt{\log S})$ and thus the theorem follows. □

Now all that remains is to prove Lemma 5.7. We do so by constructing a random walk according to Algorithm 3, over our affine-DAG. We require from this random walk to satisfy several properties. During the walk, we build an affine restriction, which sets relatively few variables and satisfies all linear systems labeling nodes on the walked path. We will ensure that the walk visits all nodes with the same probability, as answering according to a uniformly sampled fixed input. We show that, with a significant probability, the walk does not witness a missing edge. On the other hand, if the affine-DAG is not sufficiently large, some node v must be visited with a significant probability in one of these successful runs. This is only possible if the rank of the system Ψ labeling v is not too large.

We can then use the fact that a small rank Ψ can be satisfied by restricting a few blocks. We combine this with the fact that v was reached in a successful run to find a valid instance of $\mathrm{NonEdge}_{M^*}$ that is solved by the dag rooted at v, i.e., a DAG of lower depth as desired.

We start by presenting Algorithm 3. This is essentially the same algorithm as [Byramji and Impagliazzo(2025), Algorithm 1] with two main differences. First, we require x_i to lie in $N^{\cap}(M, i)$ rather than an arbitrary set A. Second, we say that the algorithm *fails* if it assigns blocks in a way that could select vertices not connected by an edge rather than if it finds a collision between pigeons.

Let us state two properties of Algorithm 3 that follow immediately from the analysis of [Byramji and Impagliazzo(2025)], the difference lying in the fact that we use $N^{\cap}(M, i)$ as a set of valid assignments to the x_i rather than an arbitrary set A.

Algorithm 3: Random walk simulator

Input: M: Set of vertices. T: Parity decision tree.

1 $C \leftarrow []$; // List of vertices used during simulation
2 $F \leftarrow [k] \setminus B(M)$; // Unassigned blocks
3 $L \leftarrow \emptyset$; // Collection of equations
4 $v \leftarrow$ root of T;
5 **while** *v is not a leaf* **do**
6 $P' \leftarrow$ query at v;
7 $P \leftarrow P'$ after substituting according to L;
8 **if** *P is a constant, $b \in \{0,1\}$* **then**
9 update v according to b;
10 **else**
11 $(i,j) \leftarrow \min\{(i,j) \in F \times [\log n] \mid x_{i,j}$ appears in $P\}$;
12 pick y uniformly from $N^{\cap}(M,i)$;
13 $L \leftarrow L \cup \{x_{i,h} = y_h \mid h \in [\log n] \setminus \{j\}\}$;
14 **if** $y^{\oplus j} \notin N^{\cap}(M,i)$ **then**
15 $L \leftarrow L \cup \{x_{i,j} = y_j\}$;
16 append $\{(i,y)\}$ to C;
17 **else**
18 pick $b \in \{0,1\}$ uniformly at random;
19 $L \leftarrow L \cup \{P = b\}$;
20 append $\{(i,y),(i,y^{\oplus j})\}$ to C;
21 update v according to b;
22 $F \leftarrow F \setminus \{i\}$
23 **if** *there exists $j_1 \neq j_2$ such that $(i_1,y_1) \in C_{j_1}, (i_2,y_2) \in C_{j_2}$ and there is no edge between vertex y_1 in block i_1 and y_2 in block i_2* **then**
24 **return** FAIL;
25 **else**
26 **return** v, C, L, F;

Lemma 5.8 ([Byramji and Impagliazzo(2025), Lemma 4.1])**.** *At the end of every iteration of the while loop in Algorithm 3*

1. *the equations in L uniquely determine $x_{i,j}$ for all $i \in [k] \setminus F$, $j \in [\log n]$ as an affine function of $x_{i,j}$, $i \in F$, $j \in [\log n]$;*
2. *fixing the variables in $x_{i,j}$, $i \in F$, $j \in [\log n]$ and setting the remaining variables as determined by L ensures that $x_{i'} \in N^{\cap}(M,i')$ for all $i' \in [k] \setminus F$;*
3. *L implies all parity constraints on the path from the root to the current node.*

Lemma 5.9 ([Byramji and Impagliazzo(2025), Lemma 4.2])**.** *Let W_v be the event that node v of T is visited by Algorithm 3, Let $\boldsymbol{x}_i \sim N^{\cap}(M,i)$ independently for each $i \in [k] \setminus B(M)$, and V_v be the event that running T on $\boldsymbol{x}$ reaches v. Then for every $v \in T$, we have* $\Pr[W_v] = \Pr[V_v]$.

Now, we will show that the algorithm does not fail with a non-negligible probability (i.e., the walk does not witness a missing edge).

Lemma 5.10. *Let T be a depth-d parity decision tree and M a set of vertices. If $|M| + 8d \leq R$, then the probability that Algorithm 3 does not return FAIL when run on T and M is at least* $\exp(-\Omega(d\beta + d^2(1-\alpha))$.

Proof. To bound the probability of failure we consider two cases depending on the number of iterations of the while loop on Line 5. First consider the case where the algorithm runs for more than $4d$ iterations. We wish to show that the probability of this happening is small. To see this, notice that in every iteration we update v except if we reach Line 14 with $y^{\oplus j} \notin N^{\cap}(M,i)$. But since $|M| \leq R \leq 1/100(1-\alpha)$, it follows by the bounded common neighborhood property of the underlying graph that $|N^{\cap}(M,i)| > 2n/3$. Since y is picked uniformly from $N^{\cap}(M,i)$, the probability of $y^{\oplus j} \notin N^{\cap}(M,i)$ is bounded above by $1/2$. Let $\boldsymbol{X}_t$ be the indicator of the event that we update v on iteration t. Then, since $\mathbb{E}[\boldsymbol{X}_t \mid \boldsymbol{X}_{t-1}, \ldots, \boldsymbol{X}_1] \geq 1/2$ we can apply Lemma 5.6 with $\boldsymbol{Y}_i = \boldsymbol{X}_i$ to find $\Pr[\sum_{t=1}^{4d} \boldsymbol{X}_t < d] \leq \Pr[\mathrm{Ber}^{4d}(1/2) < d] \leq \exp(-d/4)$.

We now wish to bound the probability of finding a non-edge in the first $4d$ iterations. We start by bounding the probability in the tth iteration. Let i and j be the indices selected on Line 11. In every iteration, we append a set of at most size 2 to C, and so by the tth iteration the union of all sets in C contains at most $2(t-1)$ elements. Call this union C_t. By the bounded common neighborhood property, we know that the number of vertices in the ith block that lie in the common neighborhood of vertices in C_t and M is at least $(1-\beta)\alpha^{|M|+2(t-1)}$ while the size of $N^{\cap}(M,i)$ is at most $(1+\beta)\alpha^{|M|}$. Thus, the probability of y having an edge to a vertex in C_t is at least $\frac{1-\beta}{1+\beta}\alpha^{2(t-1)} \geq (1-2\beta)\alpha^{2(t-1)}$. Similarly, the probability of $y^{\oplus j}$ either not lying in $N^{\cap}(M,i)$ or having an edge to some vertex in C_t is also bounded below by this. By a union bound, the probability of not failing at the tth iteration is at least $2(1-2\beta)\alpha^{2(t-1)} - 1$. Note that, for $t \leq 4d$,

$$\alpha^{2(t-1)} \geq \alpha^{8d} \geq \alpha^{R} \geq \alpha^{1/2(1-\alpha)} \geq \alpha^{-1/2\log\alpha} = 1/\sqrt{2}.$$

Hence, using the fact that $\beta < 1/20$, we have that

$$2(1-2\beta)\alpha^{2(t-1)} - 1 \geq \sqrt{2}(1-1/10) - 1 \geq 1/4\,.$$

The probability of not failing after $4d$ iterations is thus at least

$$\begin{aligned}
\prod_{t=1}^{4d}\left(2(1-2\beta)\alpha^{2(t-1)} - 1\right) &\geq \prod_{t=1}^{4d}\exp(4((1-2\beta)\alpha^{2t} - 1)) \\
&\geq \exp(4\sum_{t=1}^{4d}((1-2\beta)\alpha^{2t} - 1)) \\
&\geq \exp(4\sum_{t=1}^{4d}((1-2\beta)(1-2t(1-\alpha)) - 1)) \\
&\geq \exp(-8\sum_{t=1}^{4d}(\beta + t(1-\alpha))) \\
&\geq \exp(-32d\beta - 64d^2(1-\alpha))\,,
\end{aligned}$$

where for the first inequality, we use that $1 - x \geq \exp(-2x)$ for $x < 0.75$. In total, the probability of both not failing within the first $4d$ iterations and terminating within $4d$ steps is bounded from below by $\exp(-32d\beta - 64d^2(1-\alpha)) - \exp(-d/4) \geq \Omega(\exp(-32d\beta - 64d^2(1-\alpha)))$, using the fact that $\beta \leq 1/300$ and $8d \leq R \leq 1/100(1-\alpha)$. □

We now wish to show that it is possible to use a successful run of Algorithm 3 to find an affine restriction satisfying the reached node.

Lemma 5.11. *Let v, C, L, F be returned by a successful run of Algorithm 3 when run on T and M. Let Ψ be the linear system labeling the node in the affine-DAG corresponding to v, and let r be the rank of Ψ. If $|M| + 2r \leq R$, then there exists a set $F' \subseteq [k]$ and an affine restriction ρ fixing blocks $[k] \setminus F'$ satisfying the following conditions:*

1. *The number of blocks fixed by ρ, say s, is at most r.*
2. *Ψ is implied by Ψ_ρ (the linear system equivalent to the affine restriction ρ).*
3. *There exists a set $M' \subseteq V(G) \setminus M$ such that $|M'| \leq 2s$ and for any assignment to F', if we set the blocks $[k] \setminus F'$ according to ρ, all the vertices assigned to $[k] \setminus F'$ lie in M' and form a complete subgraph of G.*

Proof. We start by fixing the variables in $\mathrm{Cl}(\Psi) \cap F$. Let $\hat{M}$ be the set of vertices assigned by the simulation to the blocks in $\mathrm{Cl}(\Psi) \setminus F$, i.e., the yth vertex of the ith block for every $(i,y) \in C_t$ for some t and $i \in \mathrm{Cl}(\Psi) \setminus F$. Note that $|\hat{M}| \leq 2|\mathrm{Cl}(\Psi) \setminus F|$. We now assign x_i, for every $i \in \mathrm{Cl}(\Psi)$, such that $x_i \in N^{\cap}(M \cup \hat{M}, i)$ and all vertices selected form a complete subgraph. Since G has (α, β, R)-bounded common neighborhoods, this can be done as long as $|M \cup \hat{M}| + |\mathrm{Cl}(\Psi) \cap F| \leq R$. But this holds since

$$|M \cup \hat{M}| + |\mathrm{Cl}(\Psi) \cap F| \leq |M| + 2|\mathrm{Cl}(\Psi) \setminus F| + |\mathrm{Cl}(\Psi) \cap F| \leq |M| + 2|\mathrm{Cl}(\Psi)| \leq |M| + 2r \leq R$$

Set all blocks in $F \setminus \mathrm{Cl}(\Psi)$ arbitrarily and extend this to a full assignment x according to L. Since all blocks in F have been set, this extension exists and is unique by Lemma 5.8. Furthermore, L implies all parity constraints on some path to node v which in particular means that L implies Ψ. Thus, x satisfies

Ψ. Let ρ_1 be the partial assignment setting every block in $\mathrm{Cl}(\Psi)$ according to x. By construction this assignment will not falsify any equation in Ψ. For the second step, we consider $\Psi' = \Psi|_{\rho_1}$. Since $\mathrm{Cl}(\Psi)$ is fixed by ρ_1, Ψ' is safe. By Lemma 5.3, there exists a set of variables of size $\dim(\Psi)$ belonging to different blocks and whose corresponding columns in Ψ are linearly independent. Let X be this set of variables and B the corresponding set of blocks. We now wish to fix all but one variable of every block in B, leaving the variables in X untouched, such that no matter what the variables of X are set to, the vertices in the blocks B all have edges to each other and to all vertices in M and the ones fixed by ρ_1. We do this one block at a time. When we get to block i, we fix $\log n - 1$ variables, such that both vertices $\{v_i, v_i'\}$, we could potentially select when setting the last variable, lie in the common neighborhood of M, of the vertices selected by ρ_1 and of all previous $\{v_{i'}, v_{i'}'\}$. By the pigeonhole principle, we can find such an assignment to the $\log n - 1$ variables of block i, as long as the common neighborhood of all potential previous selections at block i is larger than $n/2$. But the number of previously selected vertices is at most $|M| + |\mathrm{Cl}(\Psi)| + 2(\dim(\Psi') - 1)$ which by Lemma 5.4 can be bounded by

$$|M| + |\mathrm{Cl}(\Psi)| + 2(\dim(\Psi') - 1) \leq |M| + 2(|\mathrm{Cl}(\Psi)| + \dim(\Psi') - 1) \leq |M| + 2r < R.$$

This means that the common neighborhood will have size greater than $n/2$ as desired.

Call this partial assignment of $(\log n - 1)|B|$ variables ρ_2. To find the final ρ we use the fact that Ψ' is safe to solve Ψ expressing the variables in X as an affine function of the variables outside of B. We now let ρ be this affine restricting combined with ρ_1 and ρ_2. □

With this we have both shown that the probability of succeeding is significant and that when we succeed, we can extract an affine restriction satisfying the system labeling the reached node. We can now combine these facts to prove Lemma 5.7, restated here for convenience.

Lemma 5.7 (Restated). *Let $M \subseteq V(G)$ be a set of vertices and suppose there is an affine-DAG Π solving $\mathrm{NonEdge}_M$ whose depth is at most D and size is at most S. Then*

$D > (R - |M|)/8$.

Moreover, for some universal constant C it holds that if $|M| + 8d \leq R$ for $d = \lfloor \sqrt{\log S} \cdot \min(\sqrt{R}, 1/\beta) \rfloor$ then there exists a set $M^* \supseteq M$ of size $|M^*| \leq |M| + C \log S$ and an affine-DAG Π' solving $\mathrm{NonEdge}_{M^*}$ whose depth is at most $D - d$ and size is at most S.

Proof of Lemma 5.7. We start by showing that $D > (R - |M|)/8$. Assume for contradiction that $D \leq (R - |M|)/8$ and expand Π into a parity decision tree T of depth D solving $\mathrm{NonEdge}_{\mathrm{M}}$. Since $|M| + 8D \leq R$, Lemma 5.10 gives a non-zero probability of Algorithm 3 succeeding. But after a successful run returning (v, C, L, F), an input x that reaches v can be constructed by setting the variables in F arbitrarily and setting the remaining variables according to L. Since the variables in blocks of F can be set arbitrarily, v cannot be labeled with a valid answer to $\mathrm{NonEdge}_{\mathrm{M}}$ mentioning vertices in F. But the vertices assigned outside of F are all connected. This contradicts the assumption that T solves $\mathrm{NonEdge}_{\mathrm{M}}$ and $D > (R - |M|)/8$ must hold.

To prove the second claim of Lemma 5.7, let T be the depth d parity decision tree obtained by starting at the root of the DAG Π, expanding the DAG into a tree, and removing any node at depth greater than d. We run Algorithm 3 on T and, by Lemma 5.10, the algorithm succeeds with probability q at least $\exp(-\Omega(d\beta + d^2(1-\alpha)) \geq S^{-O(1)}$, here we use the fact that $R \leq 1/100(1-\alpha)$. Since the DAG has size at most S, one of the nodes v must be reached, after a successful run, with probability at least $q/S \geq S^{-O(1)}$. By Lemma 5.9, this is also a lower bound on the probability that $\boldsymbol{x} \sim \prod_{i \in [k] \setminus B(M)} N^{\cap}(M, i)$ ends at this node. By Lemma 5.5, the rank of Ψ_v is bounded by $O(\log S)$.

Now fix some successful run of T that ends at v and apply Lemma 5.11 to find a corresponding F', M', ρ. Let $M^* = M \cup M'$ and let Π' be the affine-DAG consisting of the sub-DAG of Π of vertices reachable from v and restricted by ρ. Note that Lemma 5.11 ensures that ρ satisfies Ψ and thus the root of Π' is labeled by the empty system as desired. Furthermore, for any assignment to the blocks F', only selecting vertices within $N^{\cap}(M^*, [k] \setminus F')$, extending it to all blocks according to ρ can never introduce a non-edge outside of F'. Thus Π' solves $\mathrm{NonEdge}_{\mathrm{M}^*}$. Furthermore, note that v can not be a sink in Π since Π' solves a non-trivial problem. Thus v must have been reached after exactly d steps in T which means that Π' cannot have depth higher than $D - d$.

□

6 Lower Bound for Randomized Communication

In this section, we lower bound randomized communication cost required to solve $\mathsf{BClique}^{cc}_{\mathrm{block}}(G, k)$.

Theorem 6.1. *For any integers n and k, and for any real $p \in [0,1]$, if $\boldsymbol{G}$ is a graph sampled from $\mathcal{G}(n,p,k)$ then a.a.s. randomized communication protocol solving $\mathsf{BClique}^{cc}_{block}(\boldsymbol{G},k)$ has cost*

$$\Omega\left(\min\left(\frac{1}{\sqrt{n^{0.05}(1-p)}}, \frac{n^{0.225}}{\log(kn)}\right)\right).$$

To see that Theorem 1.3 follows we set $p = 1 - n^{-1/3}$ and $k = n$. $\boldsymbol{G}$ then has $N = n^2$ vertices and we get the lower bound $\Omega(n^{0.22}) = N^{\Omega(1)}$ on the cost of the protocol as required.

For the rest of this section, recall that $S_G \coloneqq \mathsf{BClique}^{cc}_{\text{block}}(G,k) = \{(x,y,uv) \mid x,y \in \Sigma^k,\ uv \notin E(G),\ \{u,v\} \subseteq V(x,y)\}$, where $\Sigma = \{0,1\}^{\log n/2}$, $V(x,y) \in V^k$ is the list on nodes described by $x,y \in \Sigma^k$.

Theorem 6.2. *Let $s,k,n > 0$, and G be an s-almost-complete graph on k blocks of size n. Then the randomized communication complexity of S_G is $\Omega(\sqrt{n^{0.45}/s})$.*

Theorem 6.1 follows immediately from Theorem 6.2 and Lemma 3.2. To see this recall that Lemma 3.2 states that a.a.s. a graph $\boldsymbol{G}$ sampled as in Theorem 6.1 is s-almost-complete for $s = \max\{2\sqrt{n}(1-p), 9e^2\log(kn)\}$. From Theorem 6.2 it then follows that the randomized communication complexity of S_G is

$$\Omega\left(\sqrt{\frac{n^{0.45}}{s}}\right) = \Omega\left(\min\left(\frac{1}{\sqrt{n^{0.05}(1-p)}}, \frac{n^{0.225}}{\sqrt{\log(kn)}}\right)\right.$$

The rest of this section is dedicated to the proof of Theorem 6.2. By Yao's principle for randomized communication complexity [Yao(1983)], it suffices to show that every small cost deterministic protocol errs significantly on some input distribution. We will show this for the uniform distribution over inputs $(\boldsymbol{x},\boldsymbol{y}) \sim \Sigma^k \times \Sigma^k$.

6.1 Lifting Background

We start by introducing some concepts necessary to define subcube-like protocols, which we will use in our analysis. Every node v in a communication protocol Π is associated with a rectangle $R_v = X_v \times Y_v$. For a random variable $\boldsymbol{x}$ we write its min-entropy as $\mathrm{H}_\infty(\boldsymbol{x}) = \min_x \log(1/\Pr[\boldsymbol{x} = x])$. We say that a random variable $\boldsymbol{x} \in \{0,1\}^m$ is γ-*spread* if for every subset $I \subseteq [m]$, the marginal distribution $\boldsymbol{x}_I$ satisfies $\mathrm{H}_\infty(\boldsymbol{x}_I) \geq \gamma|I|$. We define *subcube-like communication protocols* [Göös et al.(2025a)Göös, Gur, Jain, and Li, Riazanov et al.(2025)Riazanov, Sofronova, Sokolov, and Yuan].

Definition 6.3. We say that a rectangle $R = X \times Y \subseteq \{0,1\}^m \times \{0,1\}^m$ is γ-*subcube-like* with respect to $I,J \subseteq [m]$ if X_I, Y_J are fixed to some values, and the random variables $\boldsymbol{x}_{[m]\setminus I}, \boldsymbol{y}_{[m]\setminus J}$ are γ-spread for $\boldsymbol{x} \sim X$ and $\boldsymbol{y} \sim Y$. We write $\mathsf{fix}(X) = I$ and $\mathsf{fix}(Y) = J$.

A communication protocol Π is called γ-*subcube-like* if all the rectangles associated to the nodes in Π are γ-subcube-like.

In our proof of Theorem 6.2, we use the following theorem from [Göös et al.(2025a)Göös, Gur, Jain, and Li], which essentially says that, without loss of generality, we can assume the protocol to be subcube-like.

Theorem 6.4 ([Göös et al.(2025a)Göös, Gur, Jain, and Li], Theorem 29)**.** *Let Π be a deterministic communication protocol with input from $X \times Y$. Then, for any constant $\gamma < 1$, there is a protocol Π' that γ-subcube-like, and has cost $|\Pi'| = O(|\Pi|/\varepsilon)$ such that $\Pr_{\boldsymbol{x},\boldsymbol{y}\sim X\times Y}[\Pi'(\boldsymbol{x},\boldsymbol{y}) \neq \Pi(\boldsymbol{x},\boldsymbol{y})] \leq \varepsilon$.*

6.2 Proof of Theorem 6.2

Assume that Π solves S_G with an error ε. By Theorem 6.4, there is a 0.9-subcube-like protocol Π' of cost $O(|\Pi|/\varepsilon) =: d$ solving S_G to an error 2ε. Sample uniform random inputs $\boldsymbol{x},\boldsymbol{y} \in \Sigma^k = \{0,1\}^{k\log|\Sigma|}$ for Alice and Bob. Let the output of $\Pi'(\boldsymbol{x},\boldsymbol{y})$ be an edge connecting nodes from blocks $\boldsymbol{a} \in [k]$ and $\boldsymbol{b} \in [k]$. We denote this edge with $(\boldsymbol{a}\boldsymbol{x}_{\boldsymbol{a}}\boldsymbol{y}_{\boldsymbol{a}}, \boldsymbol{b}\boldsymbol{x}_{\boldsymbol{b}}\boldsymbol{y}_{\boldsymbol{b}})$ meaning that both nodes are described by first specifying the block, and then specifying the number of the node inside the block identified with $\Sigma \times \Sigma$. Let $\boldsymbol{\ell}$ be the leaf of Π' such that $(\boldsymbol{x},\boldsymbol{y}) \in R_{\boldsymbol{\ell}}$. For a set $I \subseteq [k\log|\Sigma|]$ let the set $\mathsf{blocks}(I)$ be the set of all blocks $i \in [k]$ whose bits are mentioned in I.

The proof can be summarized as follows. If one of the blocks $\boldsymbol{a}$ and $\boldsymbol{b}$ is never mentioned in the fixed part of the leaf rectangle $R_{\boldsymbol{\ell}}$, then, by density of the graph, the answer is likely to be wrong. Otherwise, at least one bit describing the nodes in $\boldsymbol{a}$ and $\boldsymbol{b}$ is fixed at the leaf. In that case, we argue that since there are at most d blocks that can be mentioned, it is unlikely that a non-edge was discovered among those.

For an arbitrary node v of Π' let $D_v \coloneqq \mathsf{blocks}(\mathsf{fix}(X_v)) \cup \mathsf{blocks}(\mathsf{fix}(Y_v))$. Then the event where one of the block $\boldsymbol{a}, \boldsymbol{b}$ is never fixed in the run of the protocol is expressed simply as "$\{\boldsymbol{a}, \boldsymbol{b}\} \not\subseteq D_{\boldsymbol{\ell}}$". Then

$$\Pr[(\boldsymbol{a}\boldsymbol{x}_{\boldsymbol{a}}\boldsymbol{y}_{\boldsymbol{a}}, \boldsymbol{b}\boldsymbol{x}_{\boldsymbol{b}}\boldsymbol{y}_{\boldsymbol{b}}) \notin E(G)] \le \Pr[(\boldsymbol{a}\boldsymbol{x}_{\boldsymbol{a}}\boldsymbol{y}_{\boldsymbol{a}}, \boldsymbol{b}\boldsymbol{x}_{\boldsymbol{b}}\boldsymbol{y}_{\boldsymbol{b}}) \notin E(G) \mid \{\boldsymbol{a}, \boldsymbol{b}\} \not\subseteq D_{\boldsymbol{\ell}}] \tag{5}$$
$$+ \Pr[(\boldsymbol{a}\boldsymbol{x}_{\boldsymbol{a}}\boldsymbol{y}_{\boldsymbol{a}}, \boldsymbol{b}\boldsymbol{x}_{\boldsymbol{b}}\boldsymbol{y}_{\boldsymbol{b}}) \notin E(G) \wedge \{\boldsymbol{a}, \boldsymbol{b}\} \subseteq D_{\boldsymbol{\ell}}] \tag{6}$$

Bounding the summand (5). Observe that for each leaf ℓ of Π' the probability $\Pr[\{\boldsymbol{a}, \boldsymbol{b}\} \subseteq D_\ell \mid \boldsymbol{\ell} = \ell] \in \{0, 1\}$, i.e., leaves can be categorized into safe and dangerous: ℓ is *safe* if $\Pr[\{\boldsymbol{a}, \boldsymbol{b}\} \subseteq D_{\boldsymbol{\ell}} \mid \boldsymbol{\ell} = \ell] = 1$, otherwise it is *dangerous*. We also note the following useful claim.

Claim 6.5. *Suppose ℓ is a safe leaf, then*

$$\Pr[(\boldsymbol{a}\boldsymbol{x}_{\boldsymbol{a}}\boldsymbol{y}_{\boldsymbol{a}}, \boldsymbol{b}\boldsymbol{x}_{\boldsymbol{b}}\boldsymbol{y}_{\boldsymbol{b}}) \notin E(G) \mid (\boldsymbol{x}, \boldsymbol{y}) \in R_\ell] \le s/n^{0.45}. \tag{7}$$

Proof of Claim 6.5. Wlog assume that $\boldsymbol{a} \notin D_{\boldsymbol{\ell}}$. Fix $\boldsymbol{x}_{\boldsymbol{a}}\boldsymbol{x}_{\boldsymbol{b}}\boldsymbol{y}_{\boldsymbol{b}} = \alpha \in \Sigma^3$ arbitrarily. By the total probability law it suffices to bound the target probability conditioned on each value α. By definition of $\mathsf{blocks}(\mathsf{fix}(Y_{\boldsymbol{\ell}}))$ we have $\mathrm{H}_\infty(\boldsymbol{y}_{\boldsymbol{a}} \mid (\boldsymbol{x}, \boldsymbol{y}) \in R_\ell) \ge 0.9 \log |\Sigma|$. By s-neighbor density we have that $\Pr[(\boldsymbol{a}\boldsymbol{x}_{\boldsymbol{a}}\boldsymbol{y}_{\boldsymbol{a}}, \boldsymbol{b}\boldsymbol{x}_{\boldsymbol{b}}\boldsymbol{y}_{\boldsymbol{b}}) \notin E(G) \mid (\boldsymbol{x}, \boldsymbol{y}) \in R_\ell, \boldsymbol{x}_{\boldsymbol{a}}\boldsymbol{x}_{\boldsymbol{b}}\boldsymbol{y}_{\boldsymbol{b}} = \alpha] \le |\Sigma|^{-0.9} s \le n^{-0.45} s$. □

Since (5) is a convex combination of left-hand sides of (7), we conclude by Claim 6.5 that the summand (5) is bounded with $s/n^{0.45}$ as well.

Bounding the summand (6). We would like to apply a union bound over all values of $\{\boldsymbol{a}, \boldsymbol{b}\}$. We first show this for a *fixed* pair of blocks a and b:

Claim 6.6. *For every $a \neq b \in [k]$ we have*

$$\Pr[(a\boldsymbol{x}_a\boldsymbol{y}_a, b\boldsymbol{x}_b\boldsymbol{y}_b) \notin E(G) \mid \{a, b\} \subseteq D_{\boldsymbol{\ell}}] \le s/n^{0.45}.$$

Proof. Let the run of the protocol $\Pi'(\boldsymbol{x}, \boldsymbol{y})$, be the sequence $\boldsymbol{v}_1, \ldots, \boldsymbol{v}_d = \boldsymbol{\ell}$ of nodes in the protocol tree.

Consider a node v in Π' corresponding to a rectangle $R_v = X_v \times Y_v \ni (\boldsymbol{x}, \boldsymbol{y})$ such that $\{a, b\} \subseteq D_v$, but the inclusion is false for the parent of v in Π'. Let T_i be the set of these nodes in Π' at the depth i, and $T \coloneqq \bigcup_{i \le d} T_i$. We then have

$$\Pr[(a\boldsymbol{x}_a\boldsymbol{y}_a, b\boldsymbol{x}_b\boldsymbol{y}_b) \notin E(G) \mid \{a, b\} \subseteq D_{\boldsymbol{\ell}}] = \sum_{i \in [k], v \in T_i} \Pr[\boldsymbol{v}_i = v] \Pr[(a\boldsymbol{x}_a\boldsymbol{y}_a, b\boldsymbol{x}_b\boldsymbol{y}_b) \notin E(G) \mid (\boldsymbol{x}, \boldsymbol{y}) \in R_v].$$

Then it suffices to bound the probability $\Pr[(a\boldsymbol{x}_a\boldsymbol{y}_a, b\boldsymbol{x}_b\boldsymbol{y}_b) \notin E(G) \mid (\boldsymbol{x}, \boldsymbol{y}) \in R_v]$ for an arbitrary $v \in T$, since the target probability is a convex combination of these probabilities. Now suppose wlog that the node v was a node where Alice spoke, i.e., for the parent u of v we have $Y_u = Y_v$. Then $\{a, b\} \not\subseteq \mathsf{blocks}(\mathsf{fix}(Y_v))$. Indeed, since $v \in T$ we have $\{a, b\} \not\subseteq D_u$, so $\{a, b\} \not\subseteq \mathsf{blocks}(\mathsf{fix}(Y_u)) = \mathsf{blocks}(\mathsf{fix}(Y_v))$. Assume again wlog that $b \notin \mathsf{blocks}(\mathsf{fix}(Y_v))$.

Finally, we have by the subcube likeness of R_v and the definition of $\mathsf{blocks}(\mathsf{fix}(Y_v))$ that $\mathrm{H}_\infty(\boldsymbol{y}_b \mid \boldsymbol{y} \in Y_v) \ge 0.9 \log |\Sigma|$. Then by the graph density $\Pr[(a\boldsymbol{x}_a\boldsymbol{y}_a, b\boldsymbol{x}_b\boldsymbol{y}_b) \notin E(G) \mid (\boldsymbol{x}, \boldsymbol{y}) \in R_v] \le s/n^{0.45}$ as required. □

We need some additional notation to implement our union bound. For a protocol leaf ℓ define

$$p_{a,b}(\ell) \coloneqq \Pr_{\boldsymbol{z}, \boldsymbol{w} \sim R_\ell}[(a\boldsymbol{z}_a\boldsymbol{w}_a, b\boldsymbol{z}_b\boldsymbol{w}_b) \notin E(G)].$$

Since the pair $(\boldsymbol{a}, \boldsymbol{b})$ is uniquely determined by $\boldsymbol{\ell}$, so denote $a(\ell)$ and $b(\ell)$ the blocks returned in the leaf ℓ.

Having that, we rewrite

$$\begin{aligned}
&\Pr[(\boldsymbol{a}\boldsymbol{x}_{\boldsymbol{a}}\boldsymbol{y}_{\boldsymbol{a}}, \boldsymbol{b}\boldsymbol{x}_{\boldsymbol{b}}\boldsymbol{y}_{\boldsymbol{b}}) \notin E(G) \wedge \neg F] \\
(\text{def. of dangerous leaves}) \quad &= \sum_{\ell\colon \text{ dangerous leaf}} p_{a(\ell),b(\ell)}(\ell) \Pr[(\boldsymbol{x}, \boldsymbol{y}) \in R_\ell] \\
&= \mathbb{E}[p_{\boldsymbol{a},\boldsymbol{b}}(\boldsymbol{\ell}) \cdot \mathbf{1}_{\{\boldsymbol{a},\boldsymbol{b}\} \subseteq D_{\boldsymbol{\ell}}}] \\
(\text{sum includes the term } \boldsymbol{a}, \boldsymbol{b}) \quad &\leq \sum_{a \neq b \in [k]} \mathbb{E}[\mathbf{1}_{\{a,b\} \subseteq D_{\boldsymbol{\ell}}} \cdot p_{a,b}(\boldsymbol{\ell})] \\
&= \sum_{a \neq b \in [k]} \Pr[\{a, b\} \subseteq D_{\boldsymbol{\ell}} \wedge (a\boldsymbol{x}_a\boldsymbol{y}_a, b\boldsymbol{x}_b\boldsymbol{y}_b) \notin E(G)] \\
&= \sum_{a \neq b \in [k]} \Pr[(a\boldsymbol{x}_a\boldsymbol{y}_a, b\boldsymbol{x}_b\boldsymbol{y}_b) \notin E(G) \mid \{a, b\} \subseteq D_{\boldsymbol{\ell}}] \cdot \Pr[\{a, b\} \subseteq D_{\boldsymbol{\ell}}] \\
(\text{number of pairs is} \leq |D_{\boldsymbol{\ell}}|^2) \quad &\leq \mathbb{E}[|D_{\boldsymbol{\ell}}|^2] \cdot \max_{a \neq b \in [k]} \Pr[(a\boldsymbol{x}_a\boldsymbol{y}_a, b\boldsymbol{x}_b\boldsymbol{y}_b) \notin E(G) \mid \{a, b\} \subseteq D_{\boldsymbol{\ell}}] \\
(\text{Claim 6.6}) \quad &\leq d^2 s / n^{0.45}.
\end{aligned}$$

Finally, we have established that the success probability of Π' is at most $2d^2 s/n^{0.45} \geq 1 - 2\varepsilon = \Omega(1)$, so $d = \Omega(\sqrt{n^{0.45}/s})$ as required.

Acknowledgements

We would like to thank Dmitry Itsykson and Kilian Risse for insightful discussions.

David Engström and Susanna F. de Rezende received funding from the Knut and Alice Wallenberg grant KAW 2023.0116, ELLIIT, and the Swedish Research Council grant 2021-05104. Yassine Ghannane and Duri Andrea Janett were supported by the Independent Research Fund Denmark grant 9040-00389B. Artur Riazanov is supported by Swiss State Secretariat for Education, Research, and Innovation (SERI) under contract number MB22.00026. We also gratefully acknowledge that we have benefited greatly from being part of Basic Algorithms Research Copenhagen (BARC) environment financed by the Villum Investigator grant 54451.

References

[Alekseev and Itsykson(2025)] Yaroslav Alekseev and Dmitry Itsykson. Lifting to bounded-depth and regular resolutions over parities via games. In *Proceedings of the 57th Annual ACM Symposium on Theory of Computing (STOC '25)*, pages 584–595, 2025. doi: 10.1145/3717823.3718150.

[Atserias et al.(2021)Atserias, Bonacina, de Rezende, Lauria, Nordström, and Razborov] Albert Atserias, Ilario Bonacina, Susanna F. de Rezende, Massimo Lauria, Jakob Nordström, and Alexander Razborov. Clique is hard on average for regular resolution. *Journal of the ACM*, 68(4):23:1–23:26, 2021. doi: 10.1145/3449352. Preliminary version in *STOC '18*.

[Beame and Whitmeyer(2025)] Paul Beame and Michael Whitmeyer. Multiparty communication complexity of collision-finding and cutting planes proofs of concise pigeonhole principles. In *Procceedings of the 52nd International Colloquium on Automata, Languages, and Programming (ICALP '25)*, volume 334 of *LIPIcs*, pages 21:1–21:20, 2025. doi: 10.4230/LIPIcs.ICALP.2025.21.

[Beame et al.(2004)Beame, Kautz, and Sabharwal] Paul Beame, Henry Kautz, and Ashish Sabharwal. Towards understanding and harnessing the potential of clause learning. *Journal of Artificial Intelligence Research*, 22(1):319–351, 2004. ISSN 1076-9757. doi: 10.1613/jair.1410.

[Beame et al.(2007a)Beame, Impagliazzo, and Sabharwal] Paul Beame, Russell Impagliazzo, and Ashish Sabharwal. The resolution complexity of independent sets and vertex covers in random graphs. *Computational Complexity*, 16(3):245–297, 2007a. doi: 10.1007/S00037-007-0230-0. Preliminary version in *CCC '01*.

[Beame et al.(2007b)Beame, Pitassi, and Segerlind] Paul Beame, Toniann Pitassi, and Nathan Segerlind. Lower bounds for Lovász–Schrijver systems and beyond follow from multiparty communication complexity. *SIAM Journal on Computing*, 37(3):845–869, 2007b. doi: 10.1137/060654645. Preliminary version in *ICALP '05*.

[Beyersdorff et al.(2012)Beyersdorff, Galesi, Lauria, and Razborov] Olaf Beyersdorff, Nicola Galesi, Massimo Lauria, and Alexander A Razborov. Parameterized bounded-depth Frege is not optimal. *ACM Transactions on Computation Theory (TOCT)*, 4(3):1–16, 2012. doi: 10.1145/2355580.2355582. Preliminary version in *ICALP '11*.

[Beyersdorff et al.(2013)Beyersdorff, Galesi, and Lauria] Olaf Beyersdorff, Nicola Galesi, and Massimo Lauria. Parameterized complexity of DPLL search procedures. *ACM Transactions on Computational Logic*, 14(3):20:1–20:21, 2013. doi: 10.1145/2499937.2499941. Preliminary version in *SAT '11*.

[Bhattacharya and Chattopadhyay(2025)] Sreejata Kishor Bhattacharya and Arkadev Chattopadhyay. Exponential lower bounds on the size of reslin proofs of nearly quadratic depth. *arXiv preprint arXiv:2507.23008*, 2025. doi: 10.48550/ARXIV.2507.23008.

[Bhattacharya et al.(2024)Bhattacharya, Chattopadhyay, and Dvorák] Sreejata Kishor Bhattacharya, Arkadev Chattopadhyay, and Pavel Dvorák. Exponential separation between powers of regular and general resolution over parities. In *Proceedings of the 39th Computational Complexity Conference (CCC '24)*, volume 300 of *LIPIcs*, pages 23:1–23:32, 2024. doi: 10.1145/3618260.3649652.

[Buss and Nordström(2021)] Sam R. Buss and Jakob Nordström. Proof complexity and SAT solving. In Armin Biere, Marijn J. H. Heule, Hans van Maaren, and Toby Walsh, editors, *Handbook of Satisfiability*, volume 336 of *Frontiers in Artificial Intelligence and Applications*, chapter 7, pages 233–350. IOS Press, 2nd edition, 2021. doi: 10.3233/faia200990.

[Byramji and Impagliazzo(2025)] Farzan Byramji and Russell Impagliazzo. Lower bounds for bit pigeonhole principles in bounded-depth resolution over parities. *arXiv preprint arXiv:2511.20023*, 2025. doi: 10.48550/ARXIV.2511.20023.

[Carmosino et al.(2016)Carmosino, Gao, Impagliazzo, Mihajlin, Paturi, and Schneider] Marco L. Carmosino, Jiawei Gao, Russell Impagliazzo, Ivan Mihajlin, Ramamohan Paturi, and Stefan Schneider. Nondeterministic extensions of the strong exponential time hypothesis and consequences for non-reducibility. In *Proceedings of the 7th ACM Conference on Innovations in Theoretical Computer Science (ITCS '16)*, page 261–270, 2016. doi: 10.1145/2840728.2840746.

[Chattopadhyay et al.(2019)Chattopadhyay, Lovett, and Vinyals] Arkadev Chattopadhyay, Shachar Lovett, and Marc Vinyals. Equality alone does not simulate randomness. In *Proceedings of the 34th Computational Complexity Conference (CCC '19)*, pages 14:1–14:11, 2019. doi: 10.4230/LIPIcs.CCC.2019.14.

[Chen et al.(2004)Chen, Huang, Kanj, and Xia] Jianer Chen, Xiuzhen Huang, Iyad A. Kanj, and Ge Xia. Linear FPT reductions and computational lower bounds. In *Proceedings of the 36th Annual ACM Symposium on Theory of Computing (STOC '04)*, pages 212–221, 2004. doi: 10.1145/1007352.1007391.

[Cheung et al.(2025)Cheung, Hatami, Hosseini, Nikolov, Pitassi, and Shirley] Tsun-Ming Cheung, Hamed Hatami, Kaave Hosseini, Aleksandar Nikolov, Toniann Pitassi, and Morgan Shirley. A lower bound on the trace norm of boolean matrices and its applications. In *Proceedings of the 16th Innovations in Theoretical Computer Science Conference (ITCS '25)*, pages 37:1–37:15, 2025. doi: 10.4230/LIPIcs.ITCS.2025.37.

[Clegg et al.(1996)Clegg, Edmonds, and Impagliazzo] Matthew Clegg, Jeffery Edmonds, and Russell Impagliazzo. Using the Groebner basis algorithm to find proofs of unsatisfiability. In *Proceedings of the 28th Annual ACM Symposium on Theory of Computing (STOC '96)*, page 174–183, 1996. doi: 10.1145/237814.237860.

[Cook et al.(1987)Cook, Coullard, and Turán] William Cook, Collette Rene Coullard, and György Turán. On the complexity of cutting-plane proofs. *Discrete Applied Mathematics*, 18(1):25–38, 1987. doi: 10.1016/0166-218x(87)90039-4.

[Dantchev et al.(2024)Dantchev, Galesi, Ghani, and Martin] Stefan Dantchev, Nicola Galesi, Abdul Ghani, and Barnaby Martin. Proof complexity and the binary encoding of combinatorial principles. *SIAM Journal on Computing*, 53(3):764–802, 2024. doi: 10.1137/20M134784X.

[de Rezende et al.(2023)de Rezende, Potechin, and Risse] Susanna de Rezende, Aaron Potechin, and Kilian Risse. Clique is hard on average for unary Sherali-Adams. In *Proceedings of the 64th IEEE Annual Symposium on Foundations of Computer Science (FOCS 23')*, pages 12–25, 2023. doi: 10.1109/focs57990.2023.00008.

[Efremenko and Itsykson(2025)] Klim Efremenko and Dmitry Itsykson. Amortized closure and its applications in lifting for resolution over parities. In *Proceedings of the 40th Computational Complexity Conference (CCC '25)*, pages 8:1–8:24, 2025. doi: 10.4230/LIPICS.CCC.2025.8.

[Efremenko et al.(2024)Efremenko, Garlík, and Itsykson] Klim Efremenko, Michal Garlík, and Dmitry Itsykson. Lower bounds for regular resolution over parities. In *Proceedings of the 56th Annual ACM Symposium on Theory of Computing (STOC '24)*, pages 640–651, 2024. doi: 10.1145/3618260.3649652.

[Garg et al.(2020)Garg, Göös, Kamath, and Sokolov] Ankit Garg, Mika Göös, Pritish Kamath, and Dmitry Sokolov. Monotone circuit lower bounds from resolution. *Theory of Computing*, 16(13):1–30, 2020. doi: 10.4086/TOC.2020.V016A013. Preliminary version in *STOC '18*.

[Göös et al.(2020)Göös, Pitassi, and Watson] Mika Göös, Toniann Pitassi, and Thomas Watson. Query-to-communication lifting for BPP. *SIAM Journal on Computing*, 49(4):FOCS17–441–FOCS17–461, 2020. doi: 10.1137/17M115339X.

[Göös et al.(2025a)Göös, Gur, Jain, and Li] Mika Göös, Tom Gur, Siddhartha Jain, and Jiawei Li. Quantum communication advantage in TFNP. In *Proceedings of the 57th Annual ACM Symposium on Theory of Computing, (STOC '25)*, pages 1465–1475, 2025a. doi: 10.1145/3717823.3718155. URL https://doi.org/10.1145/3717823.3718155.

[Göös et al.(2025b)Göös, Harms, and Riazanov] Mika Göös, Nathaniel Harms, and Artur Riazanov. Equality is far weaker than constant-cost communication. In *Proceedings of the 29th International Conference on Randomization and Computation (RANDOM '25)*, volume 353, pages 58:1–58:14, 2025b. doi: 10.4230/LIPIcs.APPROX/RANDOM.2025.58.

[Göös and Pitassi(2018)] Mika Göös and Toniann Pitassi. Communication lower bounds via critical block sensitivity. *SIAM Journal on Computing*, 47(5):1778–1806, 2018. doi: 10.1137/16M1082007. Preliminary version in *STOC '14*.

[Haken and Cook(1999)] Armin Haken and Stephen A. Cook. An exponential lower bound for the size of monotone real circuits. *Journal of Computer and System Sciences*, 58(2):326–335, 1999. doi: 10.1006/jcss.1998.1617.

[Håstad(1999)] Johan Håstad. Clique is hard to approximate within $n^{1-\varepsilon}$. *Acta Mathematica*, 182(1), 1999. doi: DOI:10.1007/BF02392825.

[Hrubeš and Pudlák(2018)] Pavel Hrubeš and Pavel Pudlák. A note on monotone real circuits. *Information Processing Letters*, 131:15–19, 2018. doi: 10.1016/j.ipl.2017.11.002.

[Huynh and Nordström(2012)] Trinh Huynh and Jakob Nordström. On the virtue of succinct proofs: amplifying communication complexity hardness to time-space trade-offs in proof complexity. In *Proceedings of the 44th Symposium on Theory of Computing Conference, (STOC '12)*, pages 233–248, 2012. doi: 10.1145/2213977.2214000.

[Impagliazzo et al.(1994)Impagliazzo, Pitassi, and Urquhart] Russell Impagliazzo, Toniann Pitassi, and Alasdair Urquhart. Upper and lower bounds for tree-like cutting planes proofs. In *Proceedings 9th Annual IEEE Symposium on Logic in Computer Science (LICS '94)*, pages 220–228, 1994. doi: 10.1109/LICS.1994.316069.

[Itsykson and Riazanov(2021)] Dmitry Itsykson and Artur Riazanov. Proof complexity of natural formulas via communication arguments. In *Proceedings of the 36th Computational Complexity Conference (CCC '21)*, pages 3:1–3:34, 2021. doi: 10.4230/LIPIcs.CCC.2021.3.

[Itsykson and Sokolov(2020)] Dmitry Itsykson and Dmitry Sokolov. Resolution over linear equations modulo two. *Annals of Pure and Applied Logic*, 171(1):102722, 2020. doi: 10.1016/J.APAL.2019.102722. Preliminary version in *MFCS '14*.

[Jukna(2012)] Stasys Jukna. Clique problem, cutting plane proofs and communication complexity. *Information Processing Letters*, 112(20):772–777, 2012. ISSN 0020-0190. doi: https://doi.org/10.1016/j.ipl.2012.07.003.

[Karp(1972)] Richard M. Karp. *Reducibility among Combinatorial Problems*, pages 85–103. Springer US, 1972. doi: 10.1007/978-1-4684-2001-2_9.

[Krajíček(2019)] Jan Krajíček. *Proof Complexity*, volume 170 of *Encyclopedia of Mathematics and Its Applications*. Cambridge University Press, 2019. doi: 10.1017/9781108242066.

[Kushilevitz and Nisan(1997)] Eyal Kushilevitz and Noam Nisan. *Communication Complexity*. Cambridge University Press, 1997. doi: 10.1016/S0065-2458(08)60342-3.

[Lasserre(2001)] Jean B. Lasserre. Global optimization with polynomials and the problem of moments. *SIAM Journal on Optimization*, 11(3):796–817, 2001. doi: 10.1137/s1052623400366802.

[Lauria(2018)] Massimo Lauria. Cliques enumeration and tree-like resolution proofs. *Information Processing Letters*, 135:62–67, 2018. doi: 10.1016/J.IPL.2018.03.001.

[Lauria et al.(2017)Lauria, Pudlák, Rödl, and Thapen] Massimo Lauria, Pavel Pudlák, Vojtěch Rödl, and Neil Thapen. The complexity of proving that a graph is Ramsey. *Combinatorica*, 37(2):253–268, 2017. doi: 10.1007/S00493-015-3193-9. Preliminary version in *ICALP '13*.

[Mitzenmacher and Upfal(2017)] Michael Mitzenmacher and Eli Upfal. *Probability and computing: Randomization and probabilistic techniques in algorithms and data analysis*. Cambridge University Press, 2017. doi: 10.1017/CBO9780511813603.

[Pang(2021)] Shuo Pang. Large clique is hard on average for resolution. In *International Computer Science Symposium in Russia (CSR '21)*, pages 361–380, 2021. doi: 10.1007/978-3-030-79416-3_22.

[Rao and Yehudayoff(2020)] Anup Rao and Amir Yehudayoff. *Communication Complexity and Applications*. Cambridge University Press, 2020. doi: 10.1145/3357713.3384286.

[Razborov(1985)] Alexander A. Razborov. Lower bounds on the monotone complexity of some boolean functions. *Doklady Akademii Nauk SSSR*, 1985. doi: 10.1007/bf01157687.

[Riazanov et al.(2025)Riazanov, Sofronova, Sokolov, and Yuan] Artur Riazanov, Anastasia Sofronova, Dmitry Sokolov, and Weiqiang Yuan. Searching for falsified clause in random $(\log n)$-CNFs is hard for randomized communication. In *Proceedings of the 29th International Conference on Randomization and Computation (RANDOM '25)*, pages 64:1–64:17, 2025. doi: 10.4230/LIPIcs.APPROX/RANDOM.2025.64.

[Rossman(2008)] Benjamin Rossman. On the constant-depth complexity of k-clique. In *Proceedings of the 40th Annual ACM Symposium on Theory of Computing (STOC '08)*, pages 721–730, 2008. doi: 10.1145/1374376.1374480.

[Rossman(2014)] Benjamin Rossman. The monotone complexity of k-clique on random graphs. *SIAM Journal on Computing*, 43(1):256–279, 2014. doi: 10.1137/110839059. Preliminary version in *FOCS '10*.

[Sokolov(2017)] Dmitry Sokolov. Dag-like communication and its applications. In *Proceedings of the 12th International Computer Science Symposium in Russia (CSR '17)*, volume 10304 of *Lecture Notes in Computer Science*, pages 294–307. Springer, 2017. doi: 10.1007/978-3-319-58747-9_26.

[Sokolov(2024)] Dmitry Sokolov. Random $(\log n)$-CNF are hard for cutting planes (again). In *Proceedings of the 56th Annual ACM Symposium on Theory of Computing (STOC '24)*, pages 2008–2015, 2024. doi: 10.1145/3618260.3649636.

[Yang and Zhang(2024)] Guangxu Yang and Jiapeng Zhang. Communication lower bounds for collision problems via density increment arguments. In *Proceedings of the 56th Annual ACM Symposium on Theory of Computing (STOC '24)*, pages 630–639, 2024. doi: 10.1145/3618260.3649607.

[Yao(1983)] Andrew C. Yao. Lower bounds by probabilistic arguments. In *Proceedings of the 24th Annual Symposium on Foundations of Computer Science (FOCS '83)*, pages 420–428, 1983. doi: 10.1109/SFCS.1983.30.

[Zuckerman(2007)] David Zuckerman. Linear degree extractors and the inapproximability of max clique and chromatic number. *Theory of Computing*, 3(6):103–128, 2007. doi: 10.4086/TOC.2007.V003A006.