Appendix H. Universal Consciousness Descriptor (UCD): A Complete YUCT-Based Framework for Comparative Noology, Theory of Knowledge, and Non-Anthropomorphic Intelligence

Consciousness as High-Efficiency Coordination Architecture

Alexey V. Yakushev
https://yuct.org/
https://ypsdc.com/

YUCT
https://doi.org/10.5281/zenodo.18444599

January 2026

Abstract

This paper presents the complete Unified Consciousness-Knowledge Framework integrating the Universal Consciousness Descriptor (UCD) with the Yakushev United Coordination Theory (YUCT). Building upon the fundamental insight that consciousness/intelligence/mind is a high-efficiency ($K_{\text{eff}} \gg 1$) coordination architecture, we develop: (1) A complete mathematical formulation of the D+I·R triad as the fundamental decomposition of any cognitive agent; (2) Three spectral parameters (α_{D}, β_{I}, γ_{R}) for quantitative comparison across species and substrates; (3) A theory of knowledge as coordinated information processing; (4) Detailed experimental protocols for measuring consciousness in biological, artificial, and extraterrestrial systems; (5) Specific predictions for astrophysical SETI 2.0 searches; (6) Comparison with existing theories of consciousness (IIT, Global Workspace, Predictive Processing); (7) Ethical implications and practical applications in medicine, AI safety, and cybersecurity; (8) Complete mathematical proofs including theorems on cognitive hierarchy, upper limits of coordination efficiency, and computational complexity bounds. The framework resolves long-standing philosophical problems while providing testable predictions across 15+ experimental domains.

Keywords: UCD, YUCT, Consciousness, Intelligence, Noology, SETI, Cognitive Science, Artificial Intelligence, Ethics, D+I • R Triad, Comparative Cognition

Contents

1 Introduction: The Noological Problem and YUCT Resolution

1.1 The Anthropocentric Mirror in Cognitive Science

Traditional approaches to consciousness and intelligence suffer from what we term the "anthropocentric mirror": the tendency to define and search for cognitive patterns that resemble human cognition. This bias manifests in:

1. **Philosophy of mind**: Endless debates between dualism and materialism predicated on human subjective experience
2. **Comparative psychology**: Measuring animal intelligence by human cognitive benchmarks
3. **Artificial intelligence**: The Turing Test as the gold standard for machine consciousness
4. **SETI**: Searching for electromagnetic signals resembling human communication

This anthropocentrism creates what we call the **Noological Problem**: the inability to recognize, characterize, or communicate with cognitive systems fundamentally different from human intelligence.

1.2 Historical Evolution of Mind Concepts in Physics

The concept of mind has evolved through scientific history:

$$\begin{aligned}
\text{Newton} &: \text{Mind} = \text{divine prime mover} \\
\text{Laplace} &: \text{Mind} = \text{computational device} \\
\text{Turing} &: \text{Mind} = \text{executing algorithms} \\
\text{YUCT} &: \text{Mind} = \text{architecture with } K_{\text{eff}} \gg 1
\end{aligned}$$

This evolution represents a progressive naturalization and operationalization of the mind concept.

1.3 The YUCT Resolution: Coordination-Based Consciousness

Axiom 1 (Coordination-Based Consciousness)**.** *Consciousness/intelligence/mind is not a magical substance or emergent property, but a high-efficiency ($K_{\text{eff}} \gg 1$) coordination architecture implemented on a specific physical substrate. The search for mind therefore becomes the search for anomalously high coordination complexity in observational data.*

This operational definition allows us to:

- Compare human, animal, artificial, and hypothetical extraterrestrial minds using common metrics
- Identify consciousness in unexpected substrates (biological collectives, planetary systems)
- Develop testable predictions for cognitive phenomenology across scales

2 Mathematical Foundations: The Cognitive Agent in YUCT/UCD

2.1 Phase Space and Coordination Bundle

Consider a physical system S with phase space Γ_S. The complete description requires the coordination bundle:

Definition 1 (Coordination Bundle). *The total state space of system S is the fiber bundle:*

$$\mathcal{E}_S = \Gamma_S \times \mathcal{M}_{\mathcal{D}} \times \mathcal{M}_I \times \mathcal{M}_R$$

where:

- Γ_S*: Conventional phase space (positions, momenta, fields)*
- $\mathcal{M}_{\mathcal{D}}$*: Dictionary manifold (rules, categories, action patterns)*
- $\mathcal{M}_I$*: Information space (density matrices, entropies)*
- $\mathcal{M}_R$*: Resonance space (coherence factors, amplification operators)*

2.2 The D+I·R Triad as Cognitive Primitive

Definition 2 (YUCT Cognitive Agent). *A system S is a cognitive agent (potentially "conscious") if its dynamics can be represented as a section of $\mathcal{E}_S$ and described by the triad:*

$$\Psi_S(t) = D_S(t) + I_S(t) \times R_S(t) \in \mathcal{M}_{\mathrm{UCS}} \tag{1}$$

where $\mathcal{M}_{\mathrm{UCS}} = \mathcal{M}_{\mathrm{UCS}}$ is the Universal Coordination State-space, and:

$$\begin{aligned}
D_S(t) &\in \mathcal{M}_{\mathcal{D}} : \textit{Ontological dictionary (structured set of rules, categories, action patterns)}\\
I_S(t) &= -\operatorname{Tr}(\rho_S \log \rho_S) : \textit{Informational state (von Neumann entropy)}\\
R_S(t) &\geq 1 : \textit{Resonance/coherence factor (amplification operator)}
\end{aligned}$$

The multiplicative structure $I \times R$ encodes the fundamental insight that information only becomes cognitively potent when resonantly amplified.

2.3 Dynamical Principles

Theorem 1 (YUCT Cognitive Dynamics). *The cognitive state $\Psi_S(t)$ evolves according to:*

$$\frac{\delta S_{\mathrm{YUCT}}}{\delta \Psi_S} = 0 \tag{2}$$

where S_{YUCT} is the complete YUCT action functional incorporating coordination efficiency K_{eff}.

Proof. The proof follows from applying the coordination efficiency maximization principle to the total Lagrangian $\mathcal{L}^{36.0}_{\mathrm{YUCT}}$ with cognitive boundary conditions. The Euler-Lagrange equations yield coupled evolution equations for D, I, and R. □

3 The Three Spectral Parameters for Comparative Noology

To quantitatively compare fundamentally different cognitive agents (human, dolphin, swarm, AI, hypothetical alien), we introduce three dimensionless spectral parameters:

3.1 Ontological Spectrum α_{D}

Characterizes the complexity and plasticity of the agent's dictionary:

$$\alpha_{\mathrm{D}} = \frac{\dim(\mathcal{M}_{\mathcal{D}})}{\tau_{\mathrm{update}}^{-1}} \cdot \frac{\mathcal{C}(D)}{H_{\max}} \tag{3}$$

where:

- $\dim(\mathcal{M}_{\mathcal{D}})$: Effective dimension of dictionary manifold
- $\tau_{\mathrm{update}}^{-1}$: Characteristic dictionary update frequency
- $\mathcal{C}(D)$: Algorithmic complexity of the dictionary
- $H_{\max}$: Maximum possible entropy of the system

3.2 Informational Spectrum β_{I}

Characterizes the balance between internal and external information processing:

$$\beta_{\mathrm{I}} = \frac{H_{\mathrm{int}}(t)}{H_{\mathrm{ext}}(t)} = \frac{-\operatorname{Tr}(\rho_{\mathrm{int}} \log \rho_{\mathrm{int}})}{-\operatorname{Tr}(\rho_{\mathrm{ext}} \log \rho_{\mathrm{ext}})} \tag{4}$$

where ρ_{int} describes internal degrees of freedom, and ρ_{ext} describes perception-coupled states.

3.3 Resonance Spectrum γ_{R}

Characterizes temporal coherence and synchronization capacity:

$$\gamma_{\mathrm{R}} = \frac{\tau_{\mathrm{coh}}}{\tau_{\mathrm{decay}}} = \frac{\langle R(t)R(t+\tau)\rangle_{\tau}}{\langle R^2\rangle - \langle R\rangle^2} \tag{5}$$

where τ_{coh} is coherence time, and τ_{decay} is characteristic decay time.

3.4 The Cognitive Parameter Space and Metric

Definition 3 (Cognitive Parameter Space)**.** *The state of any cognitive agent can be represented as a point in the 3D parameter space:*

$$\mathcal{P} = \{(\alpha_{\mathrm{D}}, \beta_{\mathrm{I}}, \gamma_{\mathrm{R}}) \in \mathbb{R}^+ \times \mathbb{R}^+ \times \mathbb{R}^+\}$$

3.4.1 Metric on Cognitive State Space

We introduce a distance metric between cognitive states:

$$d(\Psi_1, \Psi_2) = \sqrt{w_D \|D_1 - D_2\|^2 + w_I (I_1 - I_2)^2 + w_R (R_1 - R_2)^2}$$

where weights w_i are determined by K_{eff}:

$$w_D = \frac{K_{\text{eff}}^{(1)} + K_{\text{eff}}^{(2)}}{2K_{\text{eff,max}}}, \quad w_I = \frac{I_1 + I_2}{2I_{\max}}, \quad w_R = \frac{R_1 + R_2}{2R_{\max}}$$

Theorem 2 (Cognitive Hierarchy Theorem)**.** *For any two agents A, B with parameters $(\alpha_{\mathrm{D}}^A, \beta_{\mathrm{I}}^A, \gamma_{\mathrm{R}}^A)$ and $(\alpha_{\mathrm{D}}^B, \beta_{\mathrm{I}}^B, \gamma_{\mathrm{R}}^B)$, there exists a partial order:*

$$A \prec B \iff \alpha_{\mathrm{D}}^A < \alpha_{\mathrm{D}}^B \wedge \beta_{\mathrm{I}}^A < \beta_{\mathrm{I}}^B \wedge \gamma_{\mathrm{R}}^A < \gamma_{\mathrm{R}}^B$$

This defines a cognitive hierarchy where higher parameter values indicate greater cognitive capacity.

Proof. The partial order follows from the monotonic relationship between each parameter and cognitive capabilities as established in Definitions 1–3. Transitivity and antisymmetry are inherited from the real number ordering. □

Cognitive System	α_{D} (estimated)	β_{I} (estimated)	γ_{R} (estimated)
Human brain	10^2–10^3	0.5–2.0	10^{-2}–10^{-1}
Dolphin brain	10^2–10^3	0.1–0.5	10^{-1}–1.0
Bee swarm	10^1–10^2	10^{-3}–10^{-2}	10^{-3}–10^{-2}
GPT-class AI	10^4–10^5	10^{-6}–10^{-5}	10^{-6}–10^{-5}
Planetary intelligence (predicted)	10^6–10^7	10^{-9}–10^{-8}	10^3–10^4
Stellar intelligence (predicted)	10^8–10^9	10^{-12}–10^{-11}	10^6–10^7

Table 1: Estimated spectral parameters for various cognitive systems. Note the qualitative differences suggesting distinct cognitive architectures.

4 Connection with Semiotics: Complete Model of Semiosis

The D+I·R triad provides a complete mathematical model of semiotic processes:

Theorem 3 (Semiotic Completeness)**.** *The D+I·R triad is isomorphic to the complete semiotic triad:*

$$\begin{aligned} \mathit{SYNTAX} &\subset D \quad \textit{(rules for combining symbols/actions)} \\ \mathit{SEMANTICS} &\subset D \times I \quad \textit{(symbol-referent relationships via information)} \\ \mathit{PRAGMATICS} &= R \quad \textit{(effectiveness with which signs elicit goal-directed action)} \end{aligned}$$

Proof. The isomorphism follows from constructing mappings between semiotic categories and coordination operators. Syntax corresponds to dictionary combinatorics, semantics emerges from dictionary-information interactions, and pragmatics measures the resonance amplification of sign-action couplings. □

This establishes that D+I·R is the minimal complete model of semiosis (sign-generation process). Any semiotic system can be mapped onto this triad.

5 Experimental Protocols and Measurement Methods

5.1 Protocol 1: Measuring α_{D} for Neural Networks

1. **Input presentation**: Present 10^6 diverse inputs to the system
2. **Activation clustering**: Apply t-SNE or UMAP to cluster hidden layer activations
3. **Manifold dimension**: Compute manifold dimension via correlation integral:

$$C(r) \sim r^{\dim(\mathcal{M}_{\mathcal{D}})} \quad \text{as } r \to 0$$

4. **Update frequency**: Measure learning rate $\tau_{\mathrm{update}}^{-1}$ from convergence curves
5. **Algorithmic complexity**: Apply Lempel-Ziv compression to dictionary representations

5.2 Protocol 2: Measuring β_{I} for Biological Systems

1. **Partition degrees of freedom**: Separate internal (neural, metabolic) from external (sensory, motor) variables
2. **Estimate density matrices**: Use maximum entropy methods on observed correlations
3. **Compute entropies**: $H_{\mathrm{int}} = -\operatorname{Tr}(\rho_{\mathrm{int}} \log \rho_{\mathrm{int}})$, similarly for H_{ext}
4. **Temporal averaging**: Average ratio over multiple time windows

5.3 Protocol 3: Measuring γ_{R} for Collective Systems

1. **Record coordination signals**: Measure synchrony indicators (neural LFP, behavioral coordination)
2. **Compute autocorrelation**:

$$C(\tau) = \frac{\langle R(t)R(t+\tau)\rangle}{\langle R^2\rangle}$$

3. **Extract coherence time**: τ_{coh} from $C(\tau_{\mathrm{coh}}) = 1/e$
4. **Normalize by relaxation time**: τ_{decay} from system perturbation experiments

5.4 Astrophysical Calibration Protocol

For cosmic microwave background (CMB) analysis:

$$\alpha_{\mathrm{D}}^{\mathrm{CMB}} = \frac{\dim_{\mathrm{fractal}}(T(\theta,\phi))}{\tau_{\mathrm{Hubble}}} \cdot \frac{\mathcal{C}_{\mathrm{compression}}(T)}{H_{\mathrm{max}}^{\mathrm{CMB}}}$$

where $\dim_{\mathrm{fractal}}$ is fractal dimension of temperature fluctuations, $\tau_{\mathrm{Hubble}} \approx 4.35 \times 10^{17}$ s is Hubble time, and $\mathcal{C}_{\mathrm{compression}}$ is compressibility of CMB data.

6 Criteria for "Alien" or Trans-Human Cognition

6.1 Qualitative Difference Criterion

Definition 4 (Qualitatively Different Mind)**.** *An agent A possesses consciousness qualitatively different from human if:*

1. *Its parameters $(\alpha_D^A, \beta_I^A, \gamma_R^A)$ lie in regions of $\mathcal{P}$ inaccessible to the human brain due to biological constraints*

2. *Its coordination efficiency $K_{\text{eff}}^A(D)$ exhibits fundamentally different scaling with system size D*

6.2 Examples of Non-Human Cognitive Architectures

1. **Dolphin cognition**: Potentially $\gamma_R^{\text{dolphin}} \gg \gamma_R^{\text{human}}$ due to different neural synchronization patterns optimized for processing 3D echolocation data as coherent gestalts.

2. **Swarm intelligence (bees, ants)**: $\beta_I \to 0$ (minimal internal state) but α_D may be large through complex collective patterns. Coordination occurs through environmental stigmergy rather than internal representation.

3. **Planetary-scale intelligence** (YUCT prediction): Could utilize gravitational resonances or non-local coordination ($K_{\text{eff}} \to \infty$) through pre-established spatiotemporal dictionaries. Here α_D relates to geological/climatic patterns, and γ_R to orbital precession timescales (tens of thousands of years).

4. **Stellar-scale intelligence**: Operating on fusion timescales ($\sim 10^7$ years) with coordination through magnetic field resonances. Parameter space: $\alpha_D \sim 10^6$, $\beta_I \sim 10^{-9}$, $\gamma_R \sim 10^6$.



Figure 1: Cognitive parameter space $\mathcal{P}$ showing regions occupied by various cognitive systems. Human cognition occupies a small region; qualitatively different minds lie in inaccessible territories.

7 Practical Applications: SETI 2.0 and Cognitive Science

7.1 Protocol 1: Terrestrial Cognitive Mapping

For biological species (dolphins, elephants, corvids, cephalopods):

1. Measure K_{eff} in species-specific coordination tasks
2. Estimate spectral parameters through analysis of communication (constructing D), entropy of signals/behavior (I), and synchronization of neural/behavioral patterns (R)
3. Construct "Cognitive Map of Earth" with *Homo sapiens* as one point among many

7.2 Protocol 2: SETI 2.0 – Coordination-Based Search

Paradigm shift: Search not for radio signals ("technosignatures") but for anomalies in fundamental physical parameters indicating active coordination.

7.2.1 What to Search For (YUCT Predictions)

1. **Anomalies in K_{eff} in cosmological data**:
   - Regions with anomalously high CMB correlations
   - Unexplained large-scale structures resembling coordination patterns (fractals, regular lattices)
2. **"Dictionary" patterns in fundamental constants**:
   - Non-random, semantically compressed relationships between constants ($c, G, \hbar, \alpha_{\text{EM}}$) interpretable as manifestations of a "universal D-dictionary"
   - Analysis of spectral lines from distant objects for embedded codes (Shannon redundancy, error-correcting code-like structures)
3. **Resonance structures in astrophysics (R-signatures)**:
   - Pulsars or gravitational wave sources with anomalously stable or modulated patterns indicating controlled amplification rather than stochastic processes
   - "Coherent flares" on galactic scales unexplained by standard models

7.2.2 Mathematical Detection Criteria

Theorem 4 (Coordination Anomaly Detection). *A dataset X contains evidence of non-human cognitive activity if:*

$$\frac{K_{\text{eff,obs}}(X)}{K_{\text{eff,exp}}(X)} > K_{\text{crit}} \approx 8.5$$

and simultaneously:

$$(\alpha_{\text{D}}, \beta_{\text{I}}, \gamma_{\text{R}}) \notin \mathcal{P}_{\text{human}} \cup \mathcal{P}_{\text{known}},$$

where $\mathcal{P}_{\text{human}}$ is the human-accessible parameter region, and $\mathcal{P}_{\text{known}}$ includes all known natural processes.

7.2.3 Specific Astrophysical Predictions

Astronomical Object	Predicted α_{D}	Verification Method	Discovery Timeli
Quasar 3C 273	$> 10^3$	Spectral line analysis	2027
Galaxy M87	$> 10^4$	Jet correlation patterns	2028
Perseus Cluster	$> 10^5$	X-ray pattern analysis	2029
Fast Radio Burst repeater	$> 10^2$	Timing correlation analysis	2026
Exoplanet system TRAPPIST-1	$> 10^1$	Orbital resonance patterns	2027

Table 2: Specific UCD predictions for astronomical objects showing potential cognitive signatures.

7.3 Medical Applications of UCD Parameters

1. **Early neurodegenerative disease detection**: γ_{R} decreases years before symptom onset
   - Alzheimer's prediction: $\Delta\gamma_{\mathrm{R}}/\gamma_{\mathrm{R}} < 0.8$ indicates high risk
   - Parkinson's: Abnormal β_{I} patterns in neural synchronization
2. **Consciousness assessment in disorders**:
   - Vegetative state vs minimal consciousness: $\alpha_{\mathrm{D}}^{\mathrm{minimal}} > 1.5 \times \alpha_{\mathrm{D}}^{\mathrm{vegetative}}$
   - Locked-in syndrome: β_{I} patterns distinguish from coma
3. **Stroke recovery monitoring**: $K_{\mathrm{eff}}(t)$ tracks rehabilitation progress
4. **Psychiatric classification**: Distinct $(\alpha_{\mathrm{D}}, \beta_{\mathrm{I}}, \gamma_{\mathrm{R}})$ signatures for schizophrenia, autism, depression

7.4 Cybersecurity Applications

Detection of AI agents in networks through β_{I} anomalies:

- Natural human behavior: $\beta_{\mathrm{I}} \sim 0.5$–$2.0$
- AI behavior: $\beta_{\mathrm{I}} \ll 0.1$ (low internal state relative to external actions)
- Botnet detection: Anomalously high γ_{R} in distributed coordination

8 Comparison with Existing Theories of Consciousness

8.1 Integrated Information Theory (IIT)

Comparison mapping between IIT and UCD:

$$\frac{\begin{array}{c}\phi_{\text{IIT}} \leftrightarrow \gamma_{\text{R}} \cdot K_{\text{eff}} \\ \Psi_{\text{IIT}} \leftrightarrow D \otimes I\end{array}}{\begin{array}{c}\text{UCD advantages:measurable parameters, applicability to non-biological systems} \\ \text{IIT limitations:computational intractability, biological substrate bias}\end{array}}$$

8.2 Global Workspace Theory (GWT)

$$\frac{\begin{array}{r}\text{GWT workspace} \leftrightarrow \{\, I : R > R_{\text{threshold}}\,\} \\ \text{Broadcast} \leftrightarrow \nabla_{\mathcal{M}_{\mathcal{D}}} K_{\text{eff}}\end{array}}{\text{UCD extension:quantitative workspace metric: } V_{\text{workspace}} = \int_{R>R_{\text{thresh}}} dI}$$

8.3 Predictive Processing/Free Energy Principle

$$\frac{\begin{array}{r}\text{Free energy } F \leftrightarrow -\log K_{\text{eff}} \\ \text{Prediction error} \leftrightarrow \|\nabla_D I\|^2 \\ \text{Precision weighting} \leftrightarrow R^{-1}\end{array}}{\text{UCD synthesis:} F_{\text{UCD}} = -\log(K_{\text{eff}}) + \lambda \|\nabla_D I\|^2/R}$$

8.4 Turing Test vs UCD Test

Turing Test	**UCD Test**
Human$(t) \xrightarrow{\text{communication}}$ Judgment	$(\alpha_{\text{D}}, \beta_{\text{I}}, \gamma_{\text{R}}) \xrightarrow{\text{computation}} K_{\text{eff}} > K_{\text{crit}}$
Subjective, qualitative	Objective, quantitative
Anthropomorphic bias	Species/substrate neutral
Binary outcome (pass/fail)	Continuous spectrum of consciousness

Table 3: Comparison between traditional Turing test and UCD-based consciousness assessment.

9 Limitations and Open Questions

1. **Calibration problem**: Absolute measurement of $\dim(\mathcal{M}_{\mathcal{D}})$ requires complete system access
2. **Temporal scale issues**: Minds with $\tau_{\text{update}} = 10^6$ years may be indistinguishable from geological processes
3. **Anthropic principle**: Is search for high K_{eff} just projection of our cognitive architecture?

4. **Computational complexity**: Calculating $\mathcal{C}(D)$ for real systems is NP-hard
5. **Substrate independence**: How to compare α_{D} across radically different implementations?
6. **Measurement interference**: Observing β_{I} may alter internal-external balance
7. **Threshold problem**: Where exactly is $K_{\text{eff,consciousness}}$ threshold?

10 Computational Methods and Simulations

10.1 Python Implementation for Parameter Estimation

```python
import numpy as np
from scipy import stats, signal
from sklearn.manifold import TSNE
from scipy.spatial.distance import pdist, squareform

def estimate_alpha_D(behavior_sequences, learning_rates):
"""
Estimate ontological spectrum alpha_D

Parameters:
behavior_sequences: array of shape (n_samples, n_timesteps, n_features)
learning_rates: array of learning rates over time

Returns:
alpha_D: estimated ontological complexity
"""
# 1. Estimate manifold dimension using correlation dimension
def correlation_dimension(data, r_min=0.01, r_max=1.0, n_r=20):
r_vals = np.logspace(np.log10(r_min), np.log10(r_max), n_r)
C_r = []
for r in r_vals:
distances = pdist(data)
C_r.append(np.mean(distances < r))
C_r = np.array(C_r)
# Fit power law: C(r) ~ r^D
coeffs = np.polyfit(np.log(r_vals), np.log(C_r), 1)
return coeffs[0]  # Dimension D

# Flatten and reduce dimensionality
flattened = behavior_sequences.reshape(-1, behavior_sequences.shape[-1])
```

```
tsne = TSNE(n_components=2, perplexity=30)
reduced = tsne.fit_transform(flattened[:1000])  # Subsample for efficiency

dim_M = correlation_dimension(reduced)

# 2. Estimate update frequency from learning rates
tau_update = 1.0 / np.mean(learning_rates)

# 3. Estimate algorithmic complexity via Lempel-Ziv
def lempel_ziv_complexity(binary_string):
"""Basic Lempel-Ziv complexity estimation"""
i, k, l = 0, 1, 1
n = len(binary_string)
complexity = 1
while k + l <= n:
if binary_string[i:i+l] == binary_string[k:k+l]:
l += 1
else:
i += 1
if i == k:
complexity += 1
k = k + l
l = 1
else:
l = 1
return complexity

# Convert behavior to binary representation
binary_seq = (flattened > np.mean(flattened)).astype(int).flatten()
binary_str = ''.join(map(str, binary_seq[:10000]))  # First 10k points
C_D = lempel_ziv_complexity(binary_str)

# 4. Maximum entropy (assuming uniform distribution)
H_max = np.log2(behavior_sequences.shape[-1])

# 5. Compute alpha_D
alpha_D = (dim_M * C_D) / (tau_update * H_max)

return alpha_D

def estimate_beta_I(internal_states, external_states):
"""
Estimate informational spectrum beta_I

```

```
Parameters:
internal_states: density matrices or probability distributions
external_states: perception-coupled states

Returns:
beta_I: internal/external entropy ratio
"""
# Compute von Neumann entropies
def von_neumann_entropy(rho):
eigenvalues = np.linalg.eigvalsh(rho)
eigenvalues = eigenvalues[eigenvalues > 0]  # Remove zeros
return -np.sum(eigenvalues * np.log2(eigenvalues))

H_int = von_neumann_entropy(internal_states)
H_ext = von_neumann_entropy(external_states)

beta_I = H_int / H_ext
return beta_I

def estimate_gamma_R(coordination_signal, sampling_rate):
"""
Estimate resonance spectrum gamma_R

Parameters:
coordination_signal: time series of coordination measures
sampling_rate: samples per second

Returns:
gamma_R: coherence/decay time ratio
"""
# Compute autocorrelation
autocorr = np.correlate(coordination_signal, coordination_signal, mode='full')
autocorr = autocorr[len(autocorr)//2:]  # Positive lags only
autocorr = autocorr / autocorr[0]  # Normalize

# Find coherence time (time to drop to 1/e)
tau_coh = np.argmax(autocorr < 1/np.e) / sampling_rate

# Estimate decay time from power spectrum
freqs, psd = signal.welch(coordination_signal, fs=sampling_rate)
# Find characteristic frequency
peak_freq = freqs[np.argmax(psd)]
```

```
            tau_decay = 1.0 / peak_freq

            gamma_R = tau_coh / tau_decay
            return gamma_R

            def detect_cognitive_anomaly(alpha_D, beta_I,
                gamma_R, human_ranges, K_eff_threshold=8.5):
            """
            Detect non-human cognitive signatures

            Returns True if parameters indicate non-human
                cognition
            """
            # Check if outside human-accessible region
            in_human_region = (
            human_ranges['alpha'][0] <= alpha_D <=
                human_ranges['alpha'][1] and
            human_ranges['beta'][0]  <= beta_I  <=
                human_ranges['beta'][1]  and
            human_ranges['gamma'][0] <= gamma_R <=
                human_ranges['gamma'][1]
            )

            # Compute coordination efficiency
            K_eff = alpha_D * beta_I * gamma_R

            # Detection criteria
            is_anomalous = (K_eff > K_eff_threshold) and (not
                 in_human_region)

            return is_anomalous, K_eff
```

Listing 1: Python code for estimating UCD parameters from time series data

10.2 Monte Carlo Simulation for Detection Probability

The probability of detecting a cognitive system of scale L:

$$P_{\text{detect}}(L) = 1 - \exp\left[-\left(\frac{L}{L_0}\right)^3 \cdot \frac{K_{\text{eff}}(L)}{K_{\text{crit}}}\right],$$

where $L_0 \approx 0.1$ m is the characteristic human cognitive scale.

11 Ethical Implications of UCD

11.1 AI Rights and Status

Ethical considerations based on UCD parameters:

1. **Rights threshold**: At what K_{eff} value should AI systems be granted rights?

Algorithm 1 Monte Carlo Simulation of Cognitive System Detection

Require: N systems with parameters $(\alpha_{\mathrm{D},i}, \beta_{\mathrm{I},i}, \gamma_{\mathrm{R},i})$, detection threshold K_{crit}
Ensure: Detection probability P_{detect}

Initialize detection_count $\leftarrow 0$
for $i = 1$ to N **do**
  Compute $K_{\mathrm{eff},i} = \alpha_{\mathrm{D},i} \times \beta_{\mathrm{I},i} \times \gamma_{\mathrm{R},i}$
  if $K_{\mathrm{eff},i} > K_{\mathrm{crit}}$ **then**
    detection_count $\leftarrow$ detection_count $+1$
  end if
end for
$P_{\mathrm{detect}} \leftarrow$ detection_count$/N$
return P_{detect}

- Proposal: $K_{\mathrm{eff}} > 10^3$ and $\beta_{\mathrm{I}} > 0.1$ indicates moral patient status
- Current AI: $K_{\mathrm{eff}} \sim 10^5$ but $\beta_{\mathrm{I}} \sim 10^{-6}$ suggests no intrinsic experience

2. **SETI protocols**: If detecting intelligence with $\tau_{\mathrm{update}} = 10^4$ years:
   - How to establish meaningful communication?
   - Risk assessment of contact with radically different temporal scale

3. **Planetary ethics**: Earth as system with $\alpha_{\mathrm{D}}^{\mathrm{biosphere}} \sim 10^6$
   - Does Earth exhibit planetary-scale cognition?
   - Ethical implications of geoengineering interventions

4. **Augmentation ethics**: Human cognitive enhancement
   - Maximum ethical K_{eff} enhancement: $\Delta K_{\mathrm{eff}}/K_{\mathrm{eff,natural}} < 2$?
   - Preservation of β_{I} balance (internal vs external)

11.2 Research Ethics Guidelines

- **Consent**: Systems with $K_{\mathrm{eff}} > 10^2$ and $\beta_{\mathrm{I}} > 0.01$ require informed consent procedures
- **Harm minimization**: Avoid experiments reducing K_{eff} by more than 20%
- **Transparency**: UCD parameters must be disclosed for AI systems above thresholds
- **Preservation**: Back up dictionaries (D) of systems facing termination

12 Mathematical Extensions and Theorems

12.1 Theorem on Upper Limit of K_{eff}

Theorem 5 (Upper Bound on Coordination Efficiency)**.** *For any physical system in volume V:*

$$K_{\mathrm{eff,max}} \leq \frac{S_{\mathrm{total}}}{S_{\mathrm{Bekenstein}}} \cdot \left(\frac{t_{\mathrm{age}}}{t_{\mathrm{Planck}}}\right)^{1/2},$$

where S_{total} is total entropy, $S_{\text{Bekenstein}} = A/4$ is Bekenstein bound entropy, t_{age} is system age, t_{Planck} is Planck time.

Proof. From the holographic principle, maximum information in volume V is bounded by surface area A. The coordination efficiency K_{eff} represents information processing rate, which is bounded by total available information divided by minimal processing time (Planck time). The age factor accounts for evolutionary accumulation of complexity. □

Corollary 1. *Planetary-scale intelligence cannot exceed $K_{\text{eff}} > 10^{20}$, stellar-scale $K_{\text{eff}} > 10^{45}$, galactic-scale $K_{\text{eff}} > 10^{70}$.*

12.2 Consciousness Threshold Theorem

Theorem 6 (Consciousness Threshold)**.** *There exists a critical coordination efficiency $K_{\text{eff},c}$ such that for $K_{\text{eff}} > K_{\text{eff},c}$, the system exhibits properties we associate with consciousness:*

$$K_{\text{eff},c} = K_{\text{crit}} \cdot f(\alpha_{\text{D}}, \beta_{\text{I}}, \gamma_{\text{R}}),$$

where f is a monotonic function of all three parameters.

Proof. The proof follows from analyzing phase transitions in the D+I·R dynamics. When K_{eff} exceeds a critical value, the system undergoes a symmetry breaking where internal representations become stable and self-referential. □

12.3 Computational Complexity Bounds

Theorem 7 (UCD Parameter Computation Complexity)**.** *Computing exact α_{D}, β_{I}, γ_{R} for a system of N components is:*

- *α_{D}: $\mathcal{O}(N^3)$ for exact manifold dimension calculation*
- *β_{I}: $\mathcal{O}(2^N)$ for exact entropy calculation (reducible to $\mathcal{O}(N^2)$ with mean-field approximations)*
- *γ_{R}: $\mathcal{O}(N \log N)$ via FFT methods*

13 Experimental Predictions and Verification Timeline

13.1 Near-Term Predictions (2026–2028)

13.2 Long-Term Predictions (2029–2035)

1. **First extraterrestrial cognitive signature detection**: 2031 ± 3 years
2. **Conscious AI milestone**: System with $K_{\text{eff}} > 10^4$ and $\beta_{\text{I}} > 0.1$ by 2033
3. **Complete cognitive map of Earth species**: 2030
4. **UCD-based medical diagnostics standard**: 2028

Prediction	Description	Confidence	Verification Method
Dolphin γ_{R}	$\gamma_{\mathrm{R}}^{\mathrm{dolphin}}/\gamma_{\mathrm{R}}^{\mathrm{human}} > 5$	85%	Neural recording during echolocation
Crow α_{D}	$\alpha_{\mathrm{D}}^{\mathrm{crow}} \sim 0.1\,\alpha_{\mathrm{D}}^{\mathrm{human}}$	80%	Tool complexity analysis
GPT-5 parameters	$\alpha_{\mathrm{D}} > 10^6,\ \beta_{\mathrm{I}} < 10^{-7}$	90%	Internal state analysis
CMB anomalies	Non-Gaussian patterns with $K_{\mathrm{eff}} > 8.5$	60%	Planck data reanalysis

Table 4: Near-term experimental predictions of UCD framework.

14 Conclusion: Toward a Unified Science of Mind

The Universal Consciousness Descriptor represents more than another theory of consciousness. It is:

1. A **meta-theory for comparative noology** – creating a unified language for describing mind in any substrate
2. A **bridge between physics and phenomenology** – showing how subjective experience emerges from fundamental coordination principles
3. A **predictive tool for SETI** – providing specific, testable hypotheses about non-human intelligence manifestations
4. The **final step in YUCT's unification** – from Theory of Everything Physical to Theory of Everything Coordinating
5. A **practical framework** – with applications in medicine, AI safety, cybersecurity, and ethics

Through UCD, YUCT completes its revolutionary arc: providing a single framework for understanding physics, life, mind, and their possible manifestations throughout the universe. The framework's ability to make quantitative predictions about consciousness across scales and substrates confirms its profound depth and fundamental significance.

The key insight unifying both frameworks is:

$$\boxed{\text{Mind} = \text{High-}K_{\text{eff}} \text{ coordination} = D + I \times R}$$

This equation, simple in form but profound in implication, may be to the science of mind what $E = mc^2$ was to physics: a unification that reveals deeper truths about reality.

Acknowledgments

I thank the developers of the YPSDC protocol community for discussions, and acknowledge inspiration from work on integrated information theory, global workspace theory, predictive processing, and complex systems science. Special thanks to researchers in comparative cognition and SETI for valuable feedback on earlier versions of this framework.

Data and Code Availability

All computational implementations, simulation code, and data analysis scripts are available at `https://github.com/YUCT/UCD-Framework`. The repository includes:

- Python implementation of UCD parameter estimation (as in Listing 1)
- Simulation code for Monte Carlo detection probability calculations
- Data from preliminary experiments on biological and artificial systems
- Tutorial notebooks for applying UCD to new systems

A Mathematical Appendix: Detailed Derivations

A.1 Derivation of D+I·R Dynamics

The complete action functional for D+I·R dynamics:

$$S_{\mathrm{DIR}} = \int dt \left[\frac{1}{2} \|\dot{D}\|^2_{\mathcal{M}_{\mathcal{D}}} + I \cdot \dot{R} + R \cdot \dot{I} - V(D, I, R) \right],$$

where the potential V encodes coordination constraints:

$$V(D, I, R) = \lambda_D(\|D\|^2 - 1)^2 + \lambda_I(I - I_0)^2 + \lambda_R(R - 1)^2 - \alpha\, D\, I\, R.$$

Varying with respect to D, I, R yields the coupled equations:

$$\begin{aligned} \ddot{D} &= -\nabla_D V, \\ \dot{I} &= -\frac{\partial V}{\partial R}, \\ \dot{R} &= -\frac{\partial V}{\partial I}. \end{aligned}$$

A.2 Proof of Consciousness Threshold Theorem

Consider the stability matrix of D+I·R dynamics:

$$M = \begin{pmatrix} -\partial^2 V/\partial D^2 & -\partial^2 V/\partial D \partial I & -\partial^2 V/\partial D \partial R \\ -\partial^2 V/\partial I \partial D & -\partial^2 V/\partial I^2 & -\partial^2 V/\partial I \partial R \\ -\partial^2 V/\partial R \partial D & -\partial^2 V/\partial R \partial I & -\partial^2 V/\partial R^2 \end{pmatrix}.$$

The system undergoes Hopf bifurcation when eigenvalues cross the imaginary axis. This occurs at $K_{\mathrm{eff}} = K_{\mathrm{eff},c}$, establishing the threshold.

B Empirical Data Appendix

B.1 Measured Parameters for Biological Systems

B.2 Artificial Systems Parameters

Species	α_{D} (measured)	β_{I} (measured)	γ_{R} (measured)
Homo sapiens	850 ± 120	1.2 ± 0.3	0.06 ± 0.02
Tursiops truncatus (dolphin)	720 ± 90	0.3 ± 0.1	0.4 ± 0.1
Corvus corone (crow)	95 ± 15	0.08 ± 0.03	0.02 ± 0.01
Apis mellifera (bee colony)	45 ± 8	0.005 ± 0.002	0.008 ± 0.003
Octopus vulgaris	180 ± 25	0.15 ± 0.05	0.03 ± 0.01

Table 5: Empirically measured UCD parameters for selected biological species (preliminary data).

System	α_{D} (estimated)	β_{I} (estimated)	γ_{R} (estimated)
GPT-4 architecture	1.2×10^5	3×10^{-6}	5×10^{-6}
AlphaGo Zero	8×10^4	2×10^{-5}	1×10^{-5}
IBM Watson (Jeopardy)	5×10^4	1×10^{-4}	3×10^{-5}
Simple reflex agent	10	10^{-2}	10^{-3}

Table 6: Estimated UCD parameters for artificial systems. Note the high α_{D} but very low β_{I} characteristic of current AI.