

# Angular 2+

## Workshop. Routing.

### Contents

Contents.....	1
Explanation of Colors.....	3
Task 01. Basic Setup. <base> Tag.....	4
Task 02. Components.....	5
Task 03. Routes Config.....	6
Task 04. Import Routes .....	7
Task 05. <router-outlet> .....	8
Task 06. routerLink .....	9
Task 07. routerLinkActive .....	10
Task 08. Task Feature Module .....	11
Task 09. Tasks Feature Route Configuration .....	15
Task 10. Tasks List on Home Page.....	16
Task 11. Navigate .....	17
Task 12. Getting the route parameter .....	20
Task 13. Navigate Back .....	21
Task 14. Secondary Router Outlet .....	22
Task 15. Users Components.....	26
Task 16. Users Feature Area .....	31
Task 17. Users Nested Routing .....	32
Task 18. Relative Navigation.....	33
Task 19. Optional Parameters.....	35
Task 20. Admin Feature Area.....	37
Task 21. canActivate Guard .....	39
Task 22. Auth Service.....	40
Task 23. Login Component.....	42
Task 24. canActivateChild Guard .....	45
Task 25. canDeactivate Guard .....	46
Task 26. resolve Guard.....	49
Task 27. Apply Spinner.....	52
Task 28. Query Parameters and Fragment .....	56
Task 29. Lazy-Loading Route Configuration.....	58

Task 30. canLoad Guard.....59

Task 31. Default Preloading Strategy.....60

Task 32. Custom Preloading Strategy .....61

Task 33. Router Events and Title Service .....63

Task 34. Meta Service .....66

## Explanation of Colors

Blue color is a snippet of code that you need to fully use to create a new file.

Black color in combination with green or red, means the snippet of code that was added earlier.

Green color is the snippet of code that needs to be added.

Red color is the snippet of code that needs to be removed.

## Task 01. Basic Setup. <base> Tag.

1. Add tag <base> to the file **src/index.html**

```
<title>Angular Routing</title>
```

```
<base href="/">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

## Task 02. Components

1. Create module **LayoutModule**. Run the following command in the command line:

```
ng g m layout -m app.module
```

2. Create 3 blank components **HomeComponent**, **AboutComponent**, **PathNotFoundComponent**. Run the following commands in command line from project root folder<sup>1</sup>:

```
ng g c layout/components/home --skip-tests true --skip-import true
ng g c layout/components/about --skip-tests true --skip-import true
ng g c layout/components/path-not-found --skip-tests true --skip-import true
```

3. Create file **app/layout/components/index.ts** and add the following snippet of code to it:

```
export * from './about/about.component';
export * from './home/home.component';
export * from './path-not-found/path-not-found.component';
```

4. Create file **app/layout/index.ts** and add the following snippet of code to it:

```
export * from './components';
```

5. Make changes to **LayoutModule**. Use the following snippet of code:

```
// 1
import { AboutComponent, HomeComponent, PathNotFoundComponent } from './components';

// 2
declarations: [HomeComponent, AboutComponent, PathNotFoundComponent]
```

---

<sup>1</sup> All commands run from project root folder.

## Task 03. Routes Config

1. Create file **app/app-routing.module.ts**. Add the following snippet of code to it.

```
import { NgModule } from '@angular/core';
import { Routes, RouterModule } from '@angular/router';

import { AboutComponent, HomeComponent, PathNotFoundComponent } from './layout';

const routes: Routes = [
  {
    path: 'home',
    component: HomeComponent
  },
  {
    path: 'about',
    component: AboutComponent
  },
  {
    path: '',
    redirectTo: '/home',
    pathMatch: 'full'
  },
  {
    // The router will match this route if the URL requested
    // doesn't match any paths for routes defined in our configuration
    path: '**',
    component: PathNotFoundComponent
  }
];

@NgModule({
  imports: [
    RouterModule.forRoot(routes)
  ],
  exports: [RouterModule]
})
export class AppRoutingModule {}
```

## Task 04. Import Routes

1. Make changes to the **AppModule**. Use the following snippets of code:

```
// 1
import { Router } from '@angular/router';
import { AppRoutingModule } from './app-routing.module';

// 2
imports: [
  BrowserModule,
  FormsModule,
  LayoutModule,
  // MUST BE LAST
  AppRoutingModule
]

// 3
constructor(router: Router) {
  const replacer = (key: string, value: any): string =>
    typeof value === 'function' ? value.name : value;

  console.log('Routes: ', JSON.stringify(router.config, replacer, 2));
}
```

## Task 05. <router-outlet>

1. Make changes to the **AppComponent template**. Use the following snippet of HTML:

```
<div class="container">
  <!-- #routerOutlet="outlet" - access to the properties of router-outlet directive -->
  <router-outlet
    #routerOutlet="outlet"
    (activate)='onActivate($event, routerOutlet)'
    (deactivate)='onDeactivate($event, routerOutlet)'>
  </router-outlet>
  <!-- Routed views go here -->
</div>
```

2. Make changes to the **AppComponent**. Use the following snippet of code:

```
// 1
import { RouterOutlet } from '@angular/router';

// 2
onActivate($event: any, routerOutlet: RouterOutlet) {
  console.log('Activated Component', $event, routerOutlet);
}

onDeactivate($event: any, routerOutlet: RouterOutlet) {
  console.log('Deactivated Component', $event, routerOutlet);
}
```



## Task 06. routerLink

1. Make changes to the **AppComponent template**. Use the following snippet of HTML:

```
// 1
<a class="navbar-brand" href="#" routerLink="/home">Task Manager</a>

// 2
<a routerLink="/about" href="#" >About</a>
```

## Task 07. routerLinkActive

1. Make changes to **AppComponent template**. Use the following snippet of HTML:

```
<li routerLinkActive="active">  
  <a routerLink="/about">About</a>  
</li>
```

## Task 08. Task Feature Module

1. Create modules **TasksModule** and **TasksRoutingModule**. Run the following command from command line:

```
ng g m tasks --routing true -m app.module
```

2. Make changes to the **TasksModule**. Use the following snippet of code:

```
import { FormsModule } from '@angular/forms';

@NgModule({
  declarations: [
  ],
  imports: [
    CommonModule,
    FormsModule,
    TasksRoutingModule
  ],
  providers: [
  ]
})
export class TasksModule {}
```

3. Create a **model of task**. Run the following command from command line:

```
ng g cl tasks/models/task --type model --skip-tests true
```

4. Replace the content of the class. Use the following snippet of code:

```
export class TaskModel {
  constructor(
    public id: number = null,
    public action: string = '',
    public priority: number = 0,
    public estHours: number = 0,
    public actHours?: number,
    public done?: boolean
  ) {
    this.actHours = actHours || 0;
    this.done = done || false;
  }
}
```

5. Create service **TaskArrayService**. Run the the following command from command line:

```
ng g s tasks/services/task-array --skip-tests true
```

6. Replace the content of service **TaskArrayService**. Use the following snippet of code:

```
import { Injectable } from '@angular/core';
import { TaskModel } from './../../models/task.model';

const taskList = [
  new TaskModel(1, 'Estimate', 1, 8, 8, true),
  new TaskModel(2, 'Create', 2, 8, 4, false),
  new TaskModel(3, 'Deploy', 3, 8, 0, false)
];
```

```

const taskListPromise = Promise.resolve(taskList);

@Injectable({
  providedIn: 'any'
})
export class TaskArrayService {
  getTasks(): Promise<TaskModel[]> {
    return taskListPromise;
  }

  getTask(id: number | string): Promise<TaskModel> {
    return this.getTasks()
      .then(tasks => tasks.find(task => task.id === +id))
      .catch(() => Promise.reject('Error in getTask method'));
  }

  createTask(task: TaskModel): void {
    taskList.push(task);
  }

  updateTask(task: TaskModel): void {
    const i = taskList.findIndex(t => t.id === task.id);

    if (i > -1) {
      taskList.splice(i, 1, task);
    }
  }

  deleteTask(task: TaskModel): void {
    const i = taskList.findIndex(t => t.id === task.id);

    if (i > -1) {
      taskList.splice(i, 1);
    }
  }
}

```

7. Create **TaskListComponent**. Run the following command from command line.

```
ng g c tasks/components/task-list --skip-tests true -m tasks.module
```

8. Replace the content of **TaskListComponent**. Use the following snippet of code:

```

import { Component, OnInit } from '@angular/core';

import { TaskModel } from './../../models/task.model';
import { TaskArrayService } from './../../services/task-array.service';

@Component({
  templateUrl: './task-list.component.html',
  styleUrls: ['./task-list.component.css']
})
export class TaskListComponent implements OnInit {
  tasks: Promise<Array<TaskModel>>;

  constructor(private taskArrayService: TaskArrayService) {}
}

```

```

ngOnInit() {
  this.tasks = this.taskArrayService.getTasks();
}

onCompleteTask(task: TaskModel): void {
  const updatedTask = { ...task, done: true };
  this.taskArrayService.updateTask(updatedTask);
}

onEditTask(task: TaskModel): void {}
}

```

9. Replace the content of **TaskListComponent template**. Use the following snippet of HTML:

```

<app-task
  *ngFor="let task of tasks | async"
  [task]="task"
  (completeTask)="onCompleteTask($event)"
  (editTask)="onEditTask($event)">
</app-task>

```

10. Create **TaskComponent**. Run the following command from command line:

```
ng g c tasks/components/task --skip-tests true -c OnPush -m tasks.module
```

11. Replace the content of **TaskComponent**. Use the following snippet of code:

```

import {
  Component,
  EventEmitter,
  Input,
  Output,
  ChangeDetectionStrategy
} from '@angular/core';

import { TaskModel } from './../../models/task.model';

@Component({
  selector: 'app-task',
  templateUrl: './task.component.html',
  styleUrls: ['./task.component.css'],
  changeDetection: ChangeDetectionStrategy.OnPush
})
export class TaskComponent {
  @Input() task: TaskModel;

  @Output() completeTask = new EventEmitter<TaskModel>();
  @Output() editTask = new EventEmitter<TaskModel>();

  onCompleteTask(): void {
    this.completeTask.emit(this.task);
  }

  onEditTask() {
    this.editTask.emit(this.task);
  }
}

```

12. Replace the content of **TaskComponent template**. Use the following snippet of HTML:

```

<div class="panel panel-default">
  <div class="panel-heading">Task</div>
  <div class="panel-body">
    <ul>
      <li>Action: {{task.action}}</li>
      <li>Priority: {{task.priority}}</li>
      <li>Estimate Hours: {{task.estHours}}</li>
      <li>Actual Hours: {{task.actHours}}</li>
      <li>Done: {{task.done}}</li>
    </ul>
    <button class="btn btn-primary btn-sm"
      (click)="onCompleteTask()"
      [disabled]="task.done">
      Done
    </button>
    <button class="btn btn-warning btn-sm"
      (click)="onEditTask()">
      Edit
    </button>
  </div>
</div>

```

13. Create file **tasks/components/index.ts**. Add the following snippet of code to it:

```

export * from './task/task.component';
export * from './task-list/task-list.component';

```

14. Create file **tasks/index.ts**. Add the following snippet of code to it:

```

export * from './components';

```

15. Make changes to **TasksModule**. Use the following snippet of code:

```

import { TaskListComponent } from './components/task-list/task-list.component';
import { TaskComponent } from './components/task/task.component';
import { TaskListComponent, TaskComponent } from './components';

```

## Task 09. Tasks Feature Route Configuration

1. Make changes to file **tasks/tasks-routing.module.ts**. Use the following snippet of code:

```
import { TaskListComponent } from './components';

const routes: Routes = [
  {
    path: 'task-list',
    component: TaskListComponent
  }
];
```

## Task 10. Tasks List on Home Page

1. Make changes to **TasksRoutingModule**. Use the following snippet of code:

```
const routes: Routes = [  
  {  
    path: 'task-list',  
    path: 'home',  
    component: TaskListComponent  
  }  
];
```

2. Make changes to **AppRoutingModule**. Use the following snippet of code:

```
// 1  
import { AboutComponent, HomeComponent, PathNotFoundComponent } from './layout';  
{  
  path: 'home',  
  component: HomeComponent  
},
```

3. Make changes to file **app/layout/components/index.ts**. Use the following snippet of code:

```
export * from './components/about/about.component';  
export * from './components/home/home.component';  
export * from './components/path-not-found/path-not-found.component';
```

4. Make changes to **LayoutModule**. Use the following snippet of code:

```
// 1  
import { AboutComponent, HomeComponent, PathNotFoundComponent } from './components';  
  
// 2  
declarations: [HomeComponent, AboutComponent, PathNotFoundComponent]
```

5. Delete **HomeComponent** (folder layout/components/home)



## Task 11. Navigate

1. Create **TaskFormComponent**. Run the following command from command line:

**ng g c tasks/components/task-form --skip-tests true --skip-import true**

2. Replace the content of **TaskFormComponent**. Use the following snippet of code:

```
import { Component, OnInit } from '@angular/core';

import { TaskModel } from '../../../models/task.model';
import { TaskArrayService } from '../../../services/task-array.service';

@Component({
  templateUrl: './task-form.component.html',
  styleUrls: ['./task-form.component.css']
})
export class TaskFormComponent implements OnInit {
  task: TaskModel;

  constructor(private taskArrayService: TaskArrayService) {}

  ngOnInit(): void {
    this.task = new TaskModel();
  }

  onSaveTask() {
    const task = { ...this.task } as TaskModel;

    if (task.id) {
      this.taskArrayService.updateTask(task);
    } else {
      this.taskArrayService.createTask(task);
    }
  }

  onGoBack(): void {}
}
```

3. Replace the content of **TaskFormComponent template**. Use the following snippet of HTML:

```
<div class="panel panel-default">
  <div class="panel-heading">
    <h4 class="panel-title">
      Task Form
    </h4>
  </div>
  <div class="panel-body">
    <form *ngIf="task" (ngSubmit)="onSaveTask()" id="task-form" #form="ngForm">
      <div class="form-group">
        <label for="action">Action</label>
        <input type="text"
          class="form-control"
          id="action" name="action"
          placeholder="Action"
          required
          [(ngModel)]="task.action">
      </div>
      <div class="form-group">
        <label for="priority">Priority</label>
```

```

        <input type="number"
              min="1" max="3"
              class="form-control"
              id="priority" name="priority"
              placeholder="Priority"
              [(ngModel)]="task.priority">
    </div>
    <div class="form-group">
      <label for="estHours">Est. Hours</label>
      <input type="number"
            min="0"
            step="2"
            class="form-control"
            id="estHours" name="estHours"
            placeholder="Est. Hours"
            [(ngModel)]="task.estHours">
    </div>
    <button
      type="submit"
      class="btn btn-primary"
      form="task-form"
      [disabled]="form.invalid" >Save
    </button>
    <button
      type="button"
      class="btn btn-primary"
      (click)="onGoBack()">Back
    </button>
  </form>
</div>
</div>

```

4. Make changes to the file **tasks/components/index.ts**. Use the following snippet of code:

```

export * from './task/task.component';
export * from './task-form/task-form.component';
export * from './task-list/task-list.component';

```

5. Make changes to **TasksModule**. Use the following snippet of code:

```

// 1
import { TaskListComponent, TaskComponent, TaskFormComponent } from './components';

// 2
declarations: [
  ...
  TaskFormComponent
],

```

6. Make changes to **TasksRoutingModule**. Use the following snippet of code:

```

// 1
import { TaskListComponent, TaskFormComponent } from './components';

// 2
const routes: Routes = [
  {
    path: 'home',

```

```
      component: TaskListComponent
    },
    {
      path: 'edit/:taskID',
      component: TaskFormComponent
    }
  ];
```

7. Make changes to **TaskListComponent**. Use the following snippet of code:

```
// 1
import { Router } from '@angular/router';

// 2
constructor(
  private router: Router,
  private taskArrayService: TaskArrayService
) { }

// 3
onEditTask(task: Task): void {
  const link = ['/edit', task.id];
  this.router.navigate(link);
}
```

## Task 12. Getting the route parameter

1. Make changes to **TaskFormComponent**. Use the following snippet of code:

```
// 1
import { ActivatedRoute, ParamMap } from '@angular/router';

// rxjs
import { switchMap } from 'rxjs/operators';

// 2
constructor(
  private taskArrayService: TaskArrayService,
  private route: ActivatedRoute
) { }

// 3
ngOnInit(): void {
  this.task = new TaskModel();

  // it is not necessary to save subscription to route.paramMap
  // when router destroys this component, it handles subscriptions automatically
  const observer = {
    next: (task: TaskModel) => (this.task = { ...task }),
    error: (err: any) => console.log(err)
  };
  this.route.paramMap
    .pipe(
      switchMap((params: ParamMap) => this.taskArrayService.getTask(+params.get('taskID')))
    )
    .subscribe(observer);
}
```

## Task 13. Navigate Back

1. Make changes to **TaskFormComponent**. Use the following snippet of code:

```
// 1
import { ActivatedRoute, ParamMap, Router } from '@angular/router';

// 2
constructor(
  private taskArrayService: TaskArrayService,
  private router: Router,
  private route: ActivatedRoute
) { }

// 3
onGoBack(): void {
  this.router.navigate(['/home']);
}

// 4
if (task.id) {
  this.taskArrayService.updateTask(task);
}
else {
  this.taskArrayService.createTask(task);
}

this.onGoBack();
```

## Task 14. Secondary Router Outlet

1. Make changes to **AppComponent** template. Use the following snippet of HTML:

```
<div class="container">
  <!-- #routerOutlet="outlet" - access to the properties of router-outlet directive -->
  <router-outlet
    #routerOutlet="outlet"
    (activate)='onActivate($event, routerOutlet)'
    (deactivate)='onDeactivate($event, routerOutlet)'\>
  </router-outlet>
  <!-- Routed views go here -->
</div>

<div class="container">
  <div class="col-md-10">
    <!-- #routerOutlet="outlet" - access to the properties of router-outlet directive -->
    <router-outlet
      #routerOutlet="outlet"
      (activate)='onActivate($event, routerOutlet)'
      (deactivate)='onDeactivate($event, routerOutlet)'\>
    </router-outlet>
    <!-- Routed views go here -->    </div>
  <div class="col-md-2">
    <router-outlet name="messages"></router-outlet>
  </div>
</div>
```

2. Create **MessagesService**. Run the following command from command line

```
ng g s core/services/messages --skip-tests true
```

3. Create file **core/index.ts**. Use the following snippet of code:

```
export * from './services/messages.service';
```

4. Replace the content of **MessagesService**. Use the following snippet of code:

```
import { Injectable } from '@angular/core';

@Injectable({
  providedIn: 'root'
})
export class MessagesService {
  isDisplayed = false;

  private messages: string[] = [];

  addMessage(message: string): void {
    const currentDate = new Date();
    this.messages.unshift(`${message} at ${currentDate.toLocaleString()}`);
  }

  getMessages(): Array<string> {
    return this.messages;
  }
}
```

5. Make changes to **LayoutModule**. Use the following snippet of code:

```
// 1
import { FormsModule } from '@angular/forms';

// 2
imports: [CommonModule, FormsModule],
```

6. Create **MessagesComponent**. Run the following command from command line:

```
ng g c layout/components/messages --skip-tests true -m layout.module
```

7. Replace the content of **MessagesComponent template**. Use the following snippet of code:

```
<div class="row">
  <h4 class="col-md-10">Message Log</h4>
  <span class="col-md-2">
    <a class="btn btn-default" (click)="onClose()">x</a>
  </span>
</div>
<div>
  <textarea [(ngModel)]="message"></textarea>
</div>
<div>
  <button type="button" class="btn btn-primary" (click)="onSend()">Send</button>
</div>
<div *ngFor="let message of messagesService.getMessages()" class="message-row">
  {{message}}
</div>
```

8. Replace the content of **MessagesComponent style**. Use the following snippet of CSS:

```
.message-row {
  margin-bottom: 10px;
}
```

9. Replace the content of **MessagesComponent**. Use the following snippet of code:

```
import { Component, OnInit } from '@angular/core';
import { Router } from '@angular/router';
import { MessagesService } from '../../core';

@Component({
  selector: 'app-messages',
  templateUrl: './messages.component.html',
  styleUrls: ['./messages.component.css']
})
export class MessagesComponent implements OnInit {
  message = '';

  constructor(
    public messagesService: MessagesService,
    private router: Router
  ) {}

  ngOnInit() {}

  onClose() {
    this.router.navigate([{ outlets: { messages: null } }]);
    this.messagesService.isDisplayed = false;
  }
}
```

```

onSend() {
  if (this.message) {
    this.messagesService.addMessage(this.message);
    this.message = '';
  }
}
}
}

```

10. Make changes to **layout/components/index.ts**. Use the following snippet of code:

```
export * from './messages/messages.component';
```

11. Make changes to **LayoutModule**. Use the following snippet of code:

```
import { MessagesComponent } from './layout/components/messages/messages.component';
import { AboutComponent, MessagesComponent, PathNotFoundComponent } from './components';
```

12. Make changes to **AppRoutingModule**. Use the following snippet of code:

```
// 1
import { AboutComponent, MessagesComponent, PathNotFoundComponent } from './layout';

// 2
{
  path: 'messages',
  component: MessagesComponent,
  outlet: 'messages'
},

```

13. Make changes to **AppComponent**. Use the following snippet of code:

```
// 1
import { MessagesService } from './core';

// 2
constructor(public messagesService: MessagesService) { }
```

14. Make changes to **AppComponent template**. Use the following snippet of HTML:

```
<div class="col-md-2">
  <button class="btn btn-success"
    *ngIf="!messagesService.isDisplayed"
    [routerLink]="[{outlets: {messages: ['messages']}}]">
    Show Messages
  </button>
  <router-outlet name="messages"></router-outlet>
</div>
```

Look at the result.

15. Make changes to **AppComponent**. Use the following snippet of code:

```
// 1
import { Router, RouterOutlet } from '@angular/router';

// 2
constructor(
  public messagesService: MessagesService,
```



```

    private router: Router
  ) { }

  // 3
  onDisplayMessages(): void {
    this.router.navigate([{ outlets: { messages: ['messages'] } }]);
    this.messagesService.isDisplayed = true;
  }

```

16. Make changes to **AppComponent template**. Use the following snippet of HTML:

```

<button class="btn btn-success"
  *ngIf="!messagesService.isDisplayed"
  [routerLink]="[{outlets: {messages: ['messages']}}]">
  Show Messages
</button>
<button class="btn btn-success"
  *ngIf="!messagesService.isDisplayed"
  (click)="onDisplayMessages()">Show Messages</button>

```

## Task 15. Users Components

1. Create **UsersModule**. Run the following command in the command line:

```
ng g m users --routing true -m app.module
```

2. Make changes to **UsersModule**. Use the following snippet of code:

```
// 1
import { FormsModule } from '@angular/forms';

// 2
imports: [
  ...,
  FormsModule,
]
```

3. Create a **model of user**. Run the following command from command line:

```
ng g cl users/models/user --type model --skip-tests true
```

4. Replace the content of the class. Use the following snippet of code:

```
export class UserModel {
  constructor(
    public id: number,
    public firstName: string,
    public lastName: string
  ) {}
}
```

5. Create **UserArrayService**. Run the following command from command line:

```
ng g s users/services/user-array --skip-tests true
```

6. Replace the content of **UserArrayService**. Use the following snippet of code:

```
import { Injectable } from '@angular/core';

// rxjs
import { Observable, of, throwError } from 'rxjs';
import { map, catchError } from 'rxjs/operators';

import { UserModel } from '../models/user.model';

const userList: Array<UserModel> = [
  new UserModel(1, 'Anna', 'Borisova'),
  new UserModel(2, 'Boris', 'Vlasov'),
  new UserModel(3, 'Gennadiy', 'Dmitriev')
];

const userListObservable: Observable<Array<UserModel>> = of(userList);

@Injectable({
  providedIn: 'any'
})
export class UserArrayService {
  users$: Observable<UserModel[]> = userListObservable;
```

```

getUser(id: number | string): Observable<UserModel> {
  return this.users$
    .pipe(
      map((users: Array<UserModel>) => users.find(user => user.id === +id)),
      catchError(err => throwError('Error in getUser method'))
    );
}

createUser(user: UserModel): void {
  userList.push(user);
}

updateUser(user: UserModel): void {
  const i = userList.findIndex(u => u.id === user.id);

  if (i > -1) {
    userList.splice(i, 1, user);
  }
}
}

```

7. Create **UserListComponent**. Run the following command from command line:

```
ng g c users/components/user-list --skip-tests true --skip-import true
```

8. Replace the content of **UserListComponent**. Use the following snippet of code:

```

import { Component, OnInit } from '@angular/core';

// rxjs
import { EMPTY, Observable } from 'rxjs';
import { catchError } from 'rxjs/operators';

import { UserModel } from './../../models/user.model';
import { UserArrayService } from './../../services/user-array.service';

@Component({
  templateUrl: './user-list.component.html',
  styleUrls: ['./user-list.component.css']
})
export class UserListComponent implements OnInit {
  users$: Observable<Array<UserModel>>;

  constructor(
    private userArrayService: UserArrayService,
  ) { }

  ngOnInit() {
    this.users$ = this.userArrayService.users$
      .pipe(
        catchError(err => {
          console.log(err);
          return EMPTY;
        })
      );
  }
}

```

9. Replace the content of **UserListComponent template**. Use the following snippet of HTML:

```
<app-user
  *ngFor="let user of users$ | async"
  [user]="user">
</app-user>
```

10. Create **UserComponent**. Run the following command from command line:

```
ng g c users/components/user --skip-tests true -c OnPush --skip-import true
```

11. Replace the content of **UserComponent**. Use the following snippet of code:

```
import { Component, Input, ChangeDetectionStrategy } from '@angular/core';

import { UserModel } from './../../models/user.model';

@Component({
  selector: 'app-user',
  templateUrl: './user.component.html',
  styleUrls: ['./user.component.css'],
  changeDetection: ChangeDetectionStrategy.OnPush
})
export class UserComponent {
  @Input() user: UserModel;

  onEditUser() {

  }
}
```

12. Replace the content of **UserComponent template**. Use the following snippet of HTML:

```
<div class="panel panel-default">
  <div class="panel-heading">User</div>
  <div class="panel-body">
    <ul>
      <li>FirstName: {{user.firstName}}</li>
      <li>LastName: {{user.lastName}}</li>
    </ul>
    <button class="btn btn-warning btn-sm"
      (click)="onEditUser()">
      Edit
    </button>
  </div>
</div>
```

13. Create **UserFormComponent**. Run the following command from the command line:

```
ng g c users/components/user-form --skip-tests true --skip-import true
```

14. Replace the content of **UserFormComponent**. Use the following snippet of code:

```
import { Component, OnInit, OnDestroy } from '@angular/core';
import { ActivatedRoute } from '@angular/router';

// rxjs
import { Subscription } from 'rxjs';

import { UserModel } from './../../models/user.model';
```

```

import { UserArrayService } from './../../services/user-array.service';

@Component({
  templateUrl: './user-form.component.html',
  styleUrls: ['./user-form.component.css'],
})
export class UserFormComponent implements OnInit, OnDestroy {
  user: UserModel;
  originalUser: UserModel;

  private sub: Subscription;

  constructor(
    private userArrayService: UserArrayService,
    private route: ActivatedRoute,
  ) { }

  ngOnInit(): void {
    this.user = new UserModel(null, '', '');

    // we should recreate component because this code runs only once
    const id = +this.route.snapshot.paramMap.get('userID');
    const observer = {
      next: (user: UserModel) => {
        this.user = { ...user };
        this.originalUser = { ...user };
      },
      error: (err: any) => console.log(err)
    };
    this.sub = this.userArrayService.getUser(id).subscribe(observer);
  }

  ngOnDestroy() {
    this.sub.unsubscribe();
  }

  onSaveUser() {
    const user = {...this.user};

    if (user.id) {
      this.userArrayService.updateUser(user);
    } else {
      this.userArrayService.createUser(user);
    }
    this.originalUser = {...this.user};
  }

  onGoBack() {
  }
}

```

15. Replace the content of **UserFormComponent template**. Use the following snippet of HTML:

```

<div class="panel panel-default">
  <div class="panel-heading">
    <h4 class="panel-title">
      User Form
    </h4>
  </div>

```

```

<div class="panel-body">
  <form *ngIf="user" (ngSubmit)="onSaveUser()" id="user-form" #form="ngForm">
    <div class="form-group">
      <label for="firstName">First Name</label>
      <input type="text"
        class="form-control"
        id="firstName" name="firstName"
        placeholder="First Name"
        required
        [(ngModel)]="user.firstName">
    </div>
    <div class="form-group">
      <label for="lastName">Last Name</label>
      <input type="text"
        class="form-control"
        id="lastName" name="lastName"
        placeholder="Last Name"
        [(ngModel)]="user.lastName">
    </div>
    <button
      type="submit"
      class="btn btn-primary"
      [disabled]="form.invalid">Save
    </button>
    <button class="btn btn-primary"
      type="button"
      (click)="onGoBack()">Back
    </button>
  </form>
</div>
</div>

```

1. Create file **users/components/index.ts**. Add the following snippet of code to it:

```

export * from './user/user.component';
export * from './user-form/user-form.component';
export * from './user-list/user-list.component';

```

1. Create file **users/services/index.ts**. Add the following snippet of code to it:

```

export * from './user-array.service';

```

2. Create file **users/index.ts**. Add the following snippet of code to it:

```

export * from './services';
export * from './components';

```

3. Make changes to **UsersModule**. Use the following snippet of code:

```

// 1
import { UserComponent } from './components';

// 2
declarations: [UserComponent],

```

## Task 16. Users Feature Area

1. Create **UsersComponent**. Run the following command from the command line:

**ng g c users/users --skip-tests true --flat true --skip-import true**

2. Remove selector from meta data of **UsersComponent**.
3. Replace the content of **UsersComponent template**. Use the following snippet of HTML:

`<h2>Users</h2>`

## Task 17. Users Nested Routing

1. Make changes to **AppComponent** template. Use the following snippet of HTML:

```
<div>
  <ul class="nav navbar-nav">
    <li routerLinkActive="active">
      <a routerLink="/users">Users</a>
    </li>
    ...
  </ul>
</div>
```

2. Make changes to **UsersComponent** template. Use the following snippet of HTML:

```
<h2>Users</h2>
<router-outlet></router-outlet>
```

3. Make changes to **UsersRoutingModule**. Use the following snippet of code:

```
// 1
import { UsersComponent } from './users.component';
import { UserListComponent, UserFormComponent } from './components';

const routes: Routes = [
  {
    path: 'users',
    component: UsersComponent,
    children: [
      {
        path: 'add',
        component: UserFormComponent
      },
      {
        path: 'edit/:userID',
        component: UserFormComponent,
      },
      {
        path: '',
        component: UserListComponent
      },
    ],
  }
];

export class UsersRoutingModule {
  static components = [UsersComponent, UserListComponent, UserFormComponent];
}
```

4. Make changes to **UsersModule**. Use the following snippet of code:

```
// 2
declarations: [
  UsersRoutingModule.components,
  UserComponent,
]
```



## Task 18. Relative Navigation

1. Make changes to **UserComponent**. Use the following snippet of code:

```
// 1
import { Component, Input, ChangeDetectionStrategy, Output, EventEmitter } from '@angular/core';

// 2
@Output() editUser = new EventEmitter<UserModel>();

// 3
onEditUser() {
    this.editUser.emit(this.user);
}
```

2. Make changes to **UserListComponent** template. Use the following snippet of HTML:

```
<app-user
  *ngFor='let user of users$ | async'
  [user]="user"
  (editUser)="onEditUser($event)">
</app-user>
```

3. Make changes to **UserListComponent**. Use the following snippet of code:

```
// 1
import { Router, ActivatedRoute } from '@angular/router';

// 2
constructor(
    private userArrayService: UserArrayService,
    private router: Router,
    private route: ActivatedRoute
) { }

// 3
onEditUser(user: UserModel) {
    const link = ['/users/edit', user.id];
    this.router.navigate(link);
    // or
    // const link = ['edit', user.id];
    // this.router.navigate(link, {relativeTo: this.route});
}
```

4. Make changes to **UserFormComponent**. Use the following snippet of code:

```
// 1
import { ActivatedRoute, Router } from '@angular/router';

// 2
constructor(
    private userArrayService: UserArrayService,
    private route: ActivatedRoute,
    private router: Router
) { }

// 3
if (user.id) {
    this.userArrayService.updateUser(user);
}
```

```
} else {
    this.userArrayService.createUser(user);
}
this.originalUser = {...this.user};
this.onGoBack();

// 4
onGoBack() {
    this.router.navigate(['../../'], { relativeTo: this.route});
}
```

## Task 19. Optional Parameters

1. Make changes to the method **onSaveUser** of **UserFormComponent**. Use the following snippet of code:

```
if (user.id) {
  this.userArrayService.updateUser(user);
  this.router.navigate(['/users', {editedUserID: user.id}]);
} else {
  this.userArrayService.createUser(user);
  this.onGoBack();
}
this.originalUser = {...this.user};
this.onGoBack();
```

2. Make changes to **UserListComponent**. Use the following snippet of code:

```
// 1
import { Router, ActivatedRoute, ParamMap } from '@angular/router';
import { catchError, switchMap } from 'rxjs/operators';

// 2
private editedUser: UserModel;

// 3
ngOnInit() {
  this.users$ = this.userArrayService.users$
    .pipe(
      catchError(err => {
        console.log(err);
        return EMPTY;
      })
    );

  const observer = {
    next: (user: UserModel) => {
      this.editedUser = { ...user };
      console.log(
        `Last time you edited user ${JSON.stringify(this.editedUser)}`
      );
    },
    error: (err: any) => console.log(err)
  };
  this.route.paramMap
    .pipe(
      switchMap((params: ParamMap) => this.userArrayService.getUser(+params.get('editedUserID')))
    )
    .subscribe(observer);
}

// 5
isEdited(user: UserModel): boolean {
  if (this.editedUser) {
    return user.id === this.editedUser.id;
  }
  return false;
}
```

3. Make changes to **UserListComponent template**. Use the following snippet of HTML:

```
<app-user
```

```
*ngFor='let user of users$ | async'
[user]="user"
[class.edited]="isEdited(user)"
(editUser)="onEditUser($event)">
</app-user>
```

4. Make changes to **UserComponent style**. Use the following snippet of CSS:

```
:host.edited > div {
  border: 2px dotted red;
}
```

## Task 20. Admin Feature Area

1. Create **AdminModule** and **AdminRoutingModule**. Run the following command from command line:

```
ng g m admin --routing true -m app.module
```

2. Create the following blank components:
  - a. **AdminDashboardComponent**,
  - b. **ManageTasksComponent**,
  - c. **ManageUsersComponent**,
  - d. **AdminComponent**

Run the following commands from command line:

```
ng g c admin/components/admin-dashboard --skip-tests true --skip-import true
ng g c admin/components/manage-tasks --skip-tests true --skip-import true
ng g c admin/components/manage-users --skip-tests true --skip-import true
ng g c admin/admin --skip-tests true --flat true --skip-import true
```

3. Replace the content of **AdminComponent template**. Use the following snippet of HTML:

```
<h3>Admin</h3>
<nav>
  <ul class="nav nav-tabs">
    <li routerLinkActive="active" [routerLinkActiveOptions]="{ exact: true }">
      <a routerLink="./">Dashboard</a>
    </li>
    <li routerLinkActive="active">
      <a routerLink="./tasks">Manage Tasks</a>
    </li>
    <li routerLinkActive="active">
      <a routerLink="./users">Manage Users</a>
    </li>
  </ul>
</nav>
<router-outlet></router-outlet>
```

4. Create the file **admin/components/index.ts**. Use the following snippet of code:

```
export * from './admin-dashboard/admin-dashboard.component';
export * from './manage-tasks/manage-tasks.component';
export * from './manage-users/manage-users.component';
```

5. Create the file **admin/index.ts**. Use the following snippet of code:

```
export * from './components';
```

6. Replace the content of **AdminRoutingModule**. Use the following snippet of code:

```
// 1
import { AdminComponent } from './admin.component';
import { AdminDashboardComponent, ManageTasksComponent, ManageUsersComponent } from './components';

// 2
const routes: Routes = [
  {
    path: 'admin',
    component: AdminComponent,
    children: [
```

```

    {
      path: '',
      children: [
        { path: 'users', component: ManageUsersComponent },
        { path: 'tasks', component: ManageTasksComponent },
        { path: '', component: AdminDashboardComponent }
      ]
    }
  ]
}
];

// 3
export class AdminRoutingModule {
  static components = [
    AdminComponent,
    AdminDashboardComponent,
    ManageTasksComponent,
    ManageUsersComponent
  ];
}

```

7. Make changes to **AdminModule**. Use the following snippet of code:

```

declarations: [
  AdminRoutingModule.components
],

```

8. Make changes to **AppComponent** template. Use the following snippet of HTML:

```

<li routerLinkActive="active">
  <a routerLink="/users">Users</a>
</li>

<li routerLinkActive="active">
  <a routerLink="/admin">Admin</a>
</li>

```

## Task 21. canActivate Guard

1. Create **AuthGuard**. Run the following command from command line:

```
ng g g core/guards/auth --skip-tests true --implements CanActivate
```

2. Make changes to the **AuthGuard**. Use the following snippet of code:

```
canActivate(  
  next: ActivatedRouteSnapshot,  
  state: RouterStateSnapshot): Observable<Boolean | UrlTree> | Promise<boolean | UrlTree> |  
boolean | UrlTree {  
  console.log('CanActivate Guard is called');  
  return true;  
}
```

3. Make changes to the file **core/index.ts**. Use the following snippet of code:

```
export * from './guards/auth.guard';
```

4. Make changes to **AdminRoutingModule**. Use the following snippet of code:

```
import { AuthGuard } from '../core';  
  
const adminRoutes: Routes = [  
  {  
    path: 'admin',  
    component: AdminComponent,  
    canActivate: [AuthGuard],  
    children: [  
      {  
        path: '',  
        children: [  
          { path: 'users', component: ManageUsersComponent },  
          { path: 'tasks', component: ManageTasksComponent },  
          { path: '', component: AdminDashboardComponent }  
        ]  
      }  
    ]  
  }  
];
```

## Task 22. Auth Service

1. Create **AuthService**. Run the following command from command line:

```
ng g s core/services/auth --skip-tests true
```

2. Make changes to the file **core/index.ts**. Use the following snippet of code:

```
export * from './services/auth.service';
```

3. Replace the content of **AuthService**. Use the following snippet of code:

```
import { Injectable } from '@angular/core';

import { Observable, of } from 'rxjs';
import { delay, tap } from 'rxjs/operators';

@Injectable({
  providedIn: 'root'
})
export class AuthService {
  isLoggedIn = false;

  // store the URL so we can redirect after logging in
  redirectUrl: string;

  login(): Observable<boolean> {
    return of(true).pipe(
      delay(1000),
      tap(val => this.isLoggedIn = val)
    );
  }

  logout(): void {
    this.isLoggedIn = false;
  }
}
```

4. Make changes to **AuthGuard**. Use the following snippet of code:

```
// 1
import { CanActivate, ActivatedRouteSnapshot, RouterStateSnapshot, Router, UrlTree } from
 '@angular/router';
import { AuthService } from '../services/auth.service';

// 2
constructor(
  private authService: AuthService,
  private router: Router
) {}

// 3
private checkLogin(url: string): boolean | UrlTree {
  if (this.authService.isLoggedIn) { return true; }

  // Store the attempted URL for redirecting
  this.authService.redirectUrl = url;

  // Navigate to the login page, return UrlTree
  return this.router.parseUrl('/login');
```



```
}
```

5. Make changes to method **canActivate** of **AuthGuard**. Use the following snippet of code:

```
canActivate(next: ActivatedRouteSnapshot, state: RouterStateSnapshot): Observable<boolean | UrlTree>  
| Promise <Boolean | UrlTree> | boolean | UrlTree{  
  console.log('CanActivate Guard is called');  
  const { url } = state;  
  return this.checkLogin(url);  
return true;  
}
```

## Task 23. Login Component

1. Create **LoginComponent**. Run the following command from command line:

```
ng g c layout/components/login --skip-tests true -m layout.module
```

2. Make changes to the file **layout/components/index.ts**. Use the following snippet of code:

```
export * from './login/login.component';
```

3. Make changes to **LayoutModule**. Use the following snippet of code:

```
// 1
import { LoginComponent } from './components/login/login.component';

// 2
import { AboutComponent, LoginComponent, MessagesComponent, PathNotFoundComponent } from
'./components';
```

4. Make changes to **AppRoutingModule**. Use the following snippet of code:

```
// 1
import { AboutComponent, MessagesComponent, LoginComponent, PathNotFoundComponent } from './layout';

// 2
{
  path: 'about',
  component: AboutComponent
},
{
  path: 'login',
  component: LoginComponent
},
```

5. Make changes to **LoginComponent**. Use the following snippet of code:

```
// 1
import { Component, OnInit, OnDestroy } from '@angular/core';
import { Router } from '@angular/router';

// rxjs
import { Subject } from 'rxjs';
import { takeUntil } from 'rxjs/operators';

import { AuthService } from './../../../../core';

// 2
export class LoginComponent implements OnInit, OnDestroy {

// 3
message: string;
private unsubscribe: Subject<void> = new Subject();

// 4
constructor(
  public authService: AuthService,
  private router: Router
) { }
```

```
// 5
ngOnDestroy() {
  console.log('[takeUntil ngOnDestroy]');
  this.unsubscribe.complete();
}

onLogin() {
  this.message = 'Trying to log in ...';
  const observer = {
    next: () => {
      this.setMessage();
      if (this.authService.isLoggedIn) {
        // Get the redirect URL from our auth service
        // If no redirect has been set, use the default
        const redirect = this.authService.redirectUrl
          ? this.authService.redirectUrl
            : '/admin';
        // Redirect the user
        this.router.navigate([redirect]);
      }
    },
    error: (err: any) => console.log(err),
    complete: () => console.log('[takeUntil] complete')
  };
  this.authService
    .login()
    // The TakeUntil subscribes and begins mirroring the source Observable.
    // It also monitors a second Observable that you provide.
    // If this second Observable emits an item or sends a termination notification,
    // the Observable returned by TakeUntil stops mirroring the source Observable and terminates.
    .pipe(takeUntil(this.unsubscribe))
    .subscribe(observer);
}

onLogout() {
  this.authService.logout();
  this.setMessage();
}

private setMessage() {
  this.message = 'Logged ' + (this.authService.isLoggedIn ? 'in' : 'out');
}

// 6
ngOnInit() {
  this.setMessage();
}
```

6. Replace the content of **LoginComponent template**. Use the following snippet of HTML:

```
<h2>LOGIN</h2>
<p>State: {{message}}</p>
<p>
  <button class="btn btn-primary" (click)="onLogout()" *ngIf="authService.isLoggedIn; else
loginBtn">Logout</button>

  <ng-template #loginBtn>
    <button class="btn btn-primary" (click)="onLogin()" >Login</button>
  </ng-template>
```

</p>

7. Make changes to **AppComponent template**. Use the following snippet of code:

```
<li routerLinkActive="active">  
  <a routerLink="/admin">Admin</a>  
</li>  
<li routerLinkActive="active">  
  <a routerLink="/login">Login</a>  
</li>
```

## Task 24. canActivateChild Guard

1. Make changes to **AuthGuard**. Use the following snippet of code:

```
// 1
import {CanActivate, CanActivateChild, ActivatedRouteSnapshot, RouterStateSnapshot, Router } from
 '@angular/router';

// 2
export class AuthGuard implements CanActivate, CanActivateChild {
  ...
}

// 3
canActivateChild(next: ActivatedRouteSnapshot, state: RouterStateSnapshot) : Observable<boolean |
UrlTree> | Promise<boolean | UrlTree> | boolean | UrlTree{
  console.log('CanActivateChild Guard is called');
  const { url } = state;
  return this.checkLogin(url);
}
```

2. Make changes to **AdminRoutingModule**. Use the following snippet of code:

```
{
  path: '',
  canActivateChild: [AuthGuard],
  children: [
    { path: 'users', component: ManageUsersComponent },
    { path: 'tasks', component: ManageTasksComponent },
    { path: '', component: AdminDashboardComponent }
  ]
}
```

## Task 25. canDeactivate Guard

1. Create **DialogService**. Run the following command from command line:

```
ng g s core/services/dialog --skip-tests true
```

2. Replace the content of **DialogService**. Use the following snippet of code:

```
import { Injectable } from '@angular/core';

// rxjs
import { Observable, of } from 'rxjs';

@Injectable({
  providedIn: 'root'
})
export class DialogService {
  confirm(message?: string): Observable<boolean> {
    const confirmation = window.confirm(message || 'Is it OK?');
    return of(confirmation);
  }
}
```

3. Create **interface CanComponentDeactivate**. Run the following command from command line:

```
ng g i core/interfaces/can-component-deactivate --type interface
```

4. Replace the content of **CanComponentDeactivate interface**. Use the following snippet of code:

```
import { UrlTree } from '@angular/router';

// rxjs
import { Observable } from 'rxjs';

export interface CanComponentDeactivate {
  canDeactivate: () =>
    | Observable<boolean | UrlTree>
    | Promise<boolean | UrlTree>
    | boolean
    | UrlTree;
}
```

5. Create **CanDeactivateGuard**. Run the following command from command line:

```
ng g g core/guards/can-deactivate --skip-tests true --implements CanDeactivate
```

6. Replace the content of **CanDeactivateGuard**. Use the following snippet of code:

```
import { Injectable } from '@angular/core';
import { CanDeactivate, UrlTree } from '@angular/router';

// rxjs
import { Observable } from 'rxjs';

import { CanComponentDeactivate } from './../../interfaces/can-component-deactivate.interface';

@Injectable({
  providedIn: 'root'
})
```

```
export class CanDeactivateGuard
implements CanDeactivate<CanComponentDeactivate> {
  canDeactivate(
    component: CanComponentDeactivate
  ):
    | Observable<boolean | UrlTree>
    | Promise<boolean | UrlTree>
    | boolean
    | UrlTree {
    console.log('CanDeactivate Guard is called');
    return component.canDeactivate ? component.canDeactivate() : true;
  }
}
```

7. Make changes to the file **core/index.ts**. Use the following snippet of code:

```
export * from './services/dialog.service';
export * from './interfaces/can-component-deactivate.interface';
export * from './guards/can-deactivate.guard';
```

8. Make changes to **UserFormComponent**. Use the following snippet of code:

```
// 1
import { ActivatedRoute, Router, UrlTree } from '@angular/router';
import { Observable, Subscription } from 'rxjs';
import { DialogService, CanComponentDeactivate } from './../../../../core';

// 2
export class UserFormComponent implements OnInit, OnDestroy, CanComponentDeactivate {

// 3
  constructor(
    ...
    private dialogService: DialogService
  ) { }

// 4
  canDeactivate():
    | Observable<boolean | UrlTree>
    | Promise<boolean | UrlTree>
    | boolean
    | UrlTree {
    const flags = Object.keys(this.originalUser).map(key => {
      if (this.originalUser[key] === this.user[key]) {
        return true;
      }
      return false;
    });

    if (flags.every(el => el)) {
      return true;
    }

    // Otherwise ask the user with the dialog service and return its
    // promise which resolves to true or false when the user decides
    return this.dialogService.confirm('Discard changes?');
  }
}
```

9. Make changes to **UsersRoutingModule**. Use the following snippet of code:

```
import { CanDeactivateGuard } from '../core';

{
  path: 'edit/:userID',
  component: UserFormComponent,
  canDeactivate: [CanDeactivateGuard]
}
```



## Task 26. resolve Guard

1. Create **UserResolveGuard**. Run the following command from command line:

```
ng g g users/guards/user-resolve --skip-tests true --implements Resolve
```

2. Create the file **users/guards/index.ts**. Use the following snippet of code:

```
export * from './user-resolve.guard';
```

3. Make changes to file **users/index.ts**. Use the following snippet of code:

```
export * from './guards';
```

4. Replace the content of **UserResolveGuard**. Use the following snippet of code:

```
import { Injectable } from '@angular/core';
import { Router, Resolve, ActivatedRouteSnapshot } from '@angular/router';

// rxjs
import { Observable, of } from 'rxjs';
import { map, catchError, take } from 'rxjs/operators';

import { UserModel } from './../../models/user.model';
import { UserArrayService } from './../../services/user-array.service';

@Injectable({
  providedIn: 'any'
})
export class UserResolveGuard implements Resolve<UserModel> {
  constructor(
    private userArrayService: UserArrayService,
    private router: Router
  ) {}

  resolve(route: ActivatedRouteSnapshot): Observable<UserModel | null> {
    console.log('UserResolve Guard is called');

    if (!route.paramMap.has('userID')) {
      return of(new UserModel(null, '', ''));
    }

    const id = +route.paramMap.get('userID');

    return this.userArrayService.getUser(id).pipe(
      map((user: UserModel) => {
        if (user) {
          return user;
        } else {
          this.router.navigate(['/users']);
          return null;
        }
      }),
      take(1),
      catchError(() => {
        this.router.navigate(['/users']);
        // catchError MUST return observable
        return of(null);
      })
    );
  }
};
```

```
}
}
```

5. Make changes to **UsersRoutingModule**. Use the following snippet of code:

```
// 1
import { UserResolveGuard } from './guards';

// 2
{
  path: 'edit/:userID',
  component: UserFormComponent,
  canActivate: [CanDeactivateGuard],
  resolve: {
    user: UserResolveGuard
  }
}
```

6. Make changes to **UserFormComponent**. Use the following snippet of code:

```
// 1
import { Component, OnInit, OnDestroy } from '@angular/core';
import { Observable, Subscription } from 'rxjs';
import { pluck } from 'rxjs/operators';

// 2
export class UserFormComponent implements OnInit, OnDestroy, CanComponentDeactivate {

// 3
  private sub: Subscription;

// 4
  ngOnInit(): void {
    this.user = new User(null, '', '');

    this.route.data.pipe(pluck('user')).subscribe((user: UserModel) => {
      this.user = { ...user };
      this.originalUser = { ...user };
    });

    // we should recreate component because this code runs only once
    const id = +this.route.snapshot.paramMap.get('userID');
    const observer = {
      next: (user: UserModel) => {
        this.user = { ...user };
        this.originalUser = { ...user };
      },
      error: (err: any) => console.log(err)
    };
    this.sub = this.userArrayService.getUser(id).subscribe(observer);
  }

// 5
  ngOnDestroy() {
    this.sub.unsubscribe();
  }
}
```

7. Make changes to **UserFormComponent template**. Use the following snippet of HTML:

```
<form *ngIf="user" (ngSubmit)="onSaveUser()" id="user-form" #form="ngForm">
```

## Task 27. Apply Spinner

1. Create **SpinnerModule**, **SpinnerComponent**, **SpinnerService**. Use the following command in the command line:

```
ng g m widgets/spinner
ng g c widgets/spinner/spinner --skip-tests true --flat true --export true -m spinner.module
ng g s widgets/spinner/spinner --skip-tests true
```

2. Create a file **widgets/index.ts**. Use the following snippet of code:

```
export * from './spinner/spinner.component';
export * from './spinner/spinner.service';
```

3. Make changes to **SpinnerModule**. Use the following snippet of code:

```
// 1
import { ModuleWithProviders, NgModule } from '@angular/core';
import { SpinnerService } from './spinner.service';

// 2
static forRoot(): ModuleWithProviders<SpinnerModule> {
  return {
    ngModule: SpinnerModule,
    providers: [SpinnerService]
  };
}
```

4. Replace the content of **SpinnerComponent template**. Use the following snippet of HTML:

```
<div class="spinner"></div>
```

5. Replace the content of **SpinnerComponent css file**. Use the following snippet of CSS:

```
.spinner {
  color: #337ab7;
  font-size: 30px;
  text-indent: -9999em;
  overflow: hidden;
  width: 1em;
  height: 1em;
  border-radius: 50%;
  margin: 72px auto;
  position: relative;
  -webkit-transform: translateZ(0);
  -ms-transform: translateZ(0);
  transform: translateZ(0);
  -webkit-animation: load6 1.7s infinite ease, round 1.7s infinite ease;
  animation: load6 1.7s infinite ease, round 1.7s infinite ease;
}
@-webkit-keyframes load6 {
  0% {
    box-shadow: 0 -0.83em 0 -0.4em, 0 -0.83em 0 -0.42em, 0 -0.83em 0 -0.44em, 0 -0.83em 0 -0.46em, 0
    -0.83em 0 -0.477em;
  }
  5%,
  95% {
    box-shadow: 0 -0.83em 0 -0.4em, 0 -0.83em 0 -0.42em, 0 -0.83em 0 -0.44em, 0 -0.83em 0 -0.46em, 0
    -0.83em 0 -0.477em;
  }
  10%,
```

```

59% {
    box-shadow: 0 -0.83em 0 -0.4em, -0.087em -0.825em 0 -0.42em, -0.173em -0.812em 0 -0.44em, -
0.256em -0.789em 0 -0.46em, -0.297em -0.775em 0 -0.477em;
}
20% {
    box-shadow: 0 -0.83em 0 -0.4em, -0.338em -0.758em 0 -0.42em, -0.555em -0.617em 0 -0.44em, -
0.671em -0.488em 0 -0.46em, -0.749em -0.34em 0 -0.477em;
}
38% {
    box-shadow: 0 -0.83em 0 -0.4em, -0.377em -0.74em 0 -0.42em, -0.645em -0.522em 0 -0.44em, -
0.775em -0.297em 0 -0.46em, -0.82em -0.09em 0 -0.477em;
}
100% {
    box-shadow: 0 -0.83em 0 -0.4em, 0 -0.83em 0 -0.42em, 0 -0.83em 0 -0.44em, 0 -0.83em 0 -0.46em, 0
-0.83em 0 -0.477em;
}
}
@keyframes load6 {
    0% {
        box-shadow: 0 -0.83em 0 -0.4em, 0 -0.83em 0 -0.42em, 0 -0.83em 0 -0.44em, 0 -0.83em 0 -0.46em, 0
-0.83em 0 -0.477em;
    }
    5%,
    95% {
        box-shadow: 0 -0.83em 0 -0.4em, 0 -0.83em 0 -0.42em, 0 -0.83em 0 -0.44em, 0 -0.83em 0 -0.46em, 0
-0.83em 0 -0.477em;
    }
    10%,
    59% {
        box-shadow: 0 -0.83em 0 -0.4em, -0.087em -0.825em 0 -0.42em, -0.173em -0.812em 0 -0.44em, -
0.256em -0.789em 0 -0.46em, -0.297em -0.775em 0 -0.477em;
    }
    20% {
        box-shadow: 0 -0.83em 0 -0.4em, -0.338em -0.758em 0 -0.42em, -0.555em -0.617em 0 -0.44em, -
0.671em -0.488em 0 -0.46em, -0.749em -0.34em 0 -0.477em;
    }
    38% {
        box-shadow: 0 -0.83em 0 -0.4em, -0.377em -0.74em 0 -0.42em, -0.645em -0.522em 0 -0.44em, -
0.775em -0.297em 0 -0.46em, -0.82em -0.09em 0 -0.477em;
    }
    100% {
        box-shadow: 0 -0.83em 0 -0.4em, 0 -0.83em 0 -0.42em, 0 -0.83em 0 -0.44em, 0 -0.83em 0 -0.46em, 0
-0.83em 0 -0.477em;
    }
}
@-webkit-keyframes round {
    0% {
        -webkit-transform: rotate(0deg);
        transform: rotate(0deg);
    }
    100% {
        -webkit-transform: rotate(360deg);
        transform: rotate(360deg);
    }
}
@keyframes round {
    0% {
        -webkit-transform: rotate(0deg);
        transform: rotate(0deg);
    }

```

```

    }
    100% {
      -webkit-transform: rotate(360deg);
      transform: rotate(360deg);
    }
  }
}

```

6. Replace the content of **SpinnerService**. Use the following snippet of code:

```

import { Injectable } from '@angular/core';

@Injectable()
export class SpinnerService {
  private visible = false;

  isVisible(): boolean {
    return this.visible;
  }

  hide(): void {
    this.visible = false;
  }

  show(): void {
    this.visible = true;
  }
}

```

7. Make changes to **AppModule**. Use the following snippet of code:

```

// 1
import { SpinnerModule } from '../widgets/spinner/spinner.module';

// 2
imports: [
  ...
  SpinnerModule.forRoot(),
  AppRoutingModule
],

```

8. Make changes to **AppComponent**. Use the following snippet of code:

```

// 1
import { SpinnerService } from '../widgets';

// 2
constructor(
  ...
  public spinnerService: SpinnerService
) { }

```

9. Make changes to **AppComponent template**. Use the following snippet of HTML:

```

<div class="container">
  <app-spinner *ngIf="spinnerService.isVisible()"></app-spinner>

```

10. Make changes to **UserResolveGuard**. Use the following snippet of code:

```

// 1

```

```

import { map, delay, finalize, catchError, take } from 'rxjs/operators';
import { SpinnerService } from '../../widgets';

// 2
constructor(
  ...
  private spinner: SpinnerService
) {}

// 3
this.spinner.show();
const id = +route.paramMap.get('userID');

// 4
return this.userArrayService.getUser(id).pipe(
  delay(2000),
  map((user: UserModel) => {
    if (user) {
      return user;
    } else {
      this.router.navigate(['/users']);
      return null;
    }
  }),
  take(1),
  catchError(() => {
    this.router.navigate(['/users']);
    return of(null);
  }),
  finalize(() => this.spinner.hide())
);

```

## Task 28. Query Parameters and Fragment

1. Make changes to **AuthGuard**. Use the following snippet of code:

```
// 1
import { CanActivate, CanActivateChild, Router,
  ActivatedRouteSnapshot, RouterStateSnapshot, NavigationExtras, UrlTree
} from '@angular/router';

// 2
private checkLogin(url: string): boolean | UrlTree {
  if (this.authService.isLoggedIn) { return true; }

  // Store the attempted URL for redirecting
  this.authService.redirectUrl = url;

  // Create a dummy session id
  const sessionId = 123456789;

  const navigationExtras: NavigationExtras = {
    queryParams: { sessionId },
    fragment: 'anchor'
  };

  // Navigate to the login page with extras
  this.router.navigate(['/login'], navigationExtras);
  return false;
  return this.router.parseUrl('/login');
}
```

2. Make changes to **LoginComponent**. Use the following snippet of code:

```
// 1
import { Router, NavigationExtras } from '@angular/router';

// 2
if (this.authService.isLoggedIn) {
  const redirect = this.authService.redirectUrl
    ? this.authService.redirectUrl : '/admin';

  const navigationExtras: NavigationExtras = {
    queryParamsHandling: 'preserve',
    preserveFragment: true
  };

  // Redirect the user
  this.router.navigate([redirect], navigationExtras);
}
```

3. Make changes to **AdminDashboardComponent template**. Use the following snippet of HTML:

```
<p>Session ID: {{ sessionId | async }}</p>
<a id="anchor"></a>
<p>Token: {{ token | async }}</p>
```

4. Make changes to **AdminDashboardComponent**. Use the following snippet of code:

```
// 1
```



```

import { Component, OnInit } from '@angular/core';
import { ActivatedRoute } from '@angular/router';

// rxjs
import { Observable } from 'rxjs';
import { map } from 'rxjs/operators';

// 2
sessionId: Observable<string>;
token: Observable<string>;

// 3
constructor(
  private route: ActivatedRoute
) { }

// 4
ngOnInit() {
  // Capture the session ID if available
  this.sessionId = this.route
    .queryParamsMap
    .pipe(
      map(params => params.get('sessionId') || 'None')
    );

  // Capture the fragment if available
  this.token = this.route
    .fragment
    .pipe(
      map(fragment => fragment || 'None')
    );
}

```

5. Make changes to **AdminComponent template**. Use the following snippet of HTML:

```

<nav>
  <ul class="nav nav-tabs">
    <li routerLinkActive="active" [routerLinkActiveOptions]="{ exact: true }">
      <a routerLink="." queryParamsHandling="preserve" preserveFragment>Dashboard</a>
    </li>
    <li routerLinkActive="active">
      <a routerLink="./tasks" queryParamsHandling="preserve" preserveFragment>Manage Tasks</a>
    </li>
    <li routerLinkActive="active">
      <a routerLink="./users" queryParamsHandling="preserve" preserveFragment>Manage Users</a>
    </li>
  </ul>
</nav>

```

## Task 29. Lazy-Loading Route Configuration

1. Make changes to **AppRoutingModule**. Use the following snippet of code:

```
{
  path: 'admin',
  loadChildren: () => import('./admin/admin.module').then(m => m.AdminModule)
},
{
  path: 'users',
  loadChildren: () => import('./users/users.module').then(m => m.UsersModule)
},
```

2. Make changes to **AdminRoutingModule**. Use the following snippet of code:

```
const routes: Routes = [
  {
    path: 'admin',
    path: '',
    component: AdminComponent,
    canActivate: [AuthGuard],
    children: [
      ...
    ]
  }
];
```

3. Make changes to **UsersRoutingModule**. Use the following snippet of code:

```
const routes: Routes = [
  {
    path: 'users',
    path: '',
    component: UsersComponent,
    children: [
      ...
    ]
  }
];
```

4. Make changes to **AppModule**. Use the following snippet of code:

```
import { AdminModule } from './admin/admin.module';
import { UsersModule } from './users/users.module';

imports: [
  ...
  UsersModule,
  AdminModule,
  AppRoutingModule
]
```

## Task 30. canLoad Guard

1. Make changes to **AuthGuard**. Use the following snippet of code:

```
// 1
import {
  CanActivate, CanActivateChild, CanLoad, Router, Route,
  ActivatedRouteSnapshot, RouterStateSnapshot, NavigationExtras, UrlTree, UrlSegment
} from '@angular/router';

// 2
export class AuthGuard implements CanActivate, CanActivateChild, CanLoad {

// 3
  canLoad(route: Route, segments: UrlSegment[]): Observable<boolean | UrlTree> | Promise<boolean |
  UrlTree> | boolean | UrlTree {
    console.log('CanLoad Guard is called');
    const url = `/${route.path}`;
    return this.checkLogin(url) as boolean;
  }
}
```

2. Make changes to **AppRoutingModule**. Use the following snippet of code:

```
// 1
import { AuthGuard } from './core';

// 2
{
  path: 'admin',
  canLoad: [AuthGuard],
  loadChildren: () => import('./admin/admin.module').then(m => m.AdminModule)
},
```

## Task 31. Default Preloading Strategy

1. Make changes to **AppRoutingModule**. Use the following snippet of code:

```
// 1
import { Routes, RouterModule, PreloadAllModules, ExtraOptions } from '@angular/router';

// 2
const extraOptions: ExtraOptions = {
  preloadingStrategy: PreloadAllModules,
  enableTracing: true // Makes the router log all its internal events to the console.
};

// 3
@NgModule({
  imports: [
    RouterModule.forRoot(routes, extraOptions)
  ]
})
```

## Task 32. Custom Preloading Strategy

1. Make changes to **AppRoutingModule**. Use the following snippet of code:

```
{
  path: 'users',
  loadChildren: () => import('./users/users.module').then(m => m.UsersModule),
  data: { preload: true }
},
```

2. Create **CustomPreloadingStrategyService**. Run the following command from command line:

**ng g s core/services/custom-preloading-strategy --skip-tests true**

3. Replace the content of **CustomPreloadingStrategyService**. Use the following snippet of code:

```
import { Injectable } from '@angular/core';
import { PreloadingStrategy, Route } from '@angular/router';

// rxjs
import { Observable, of } from 'rxjs';

@Injectable({
  providedIn: 'root'
})
export class CustomPreloadingStrategyService implements PreloadingStrategy {
  public preloadedModules: string[] = [];

  preload(route: Route, load: () => Observable<any>): Observable<any> {
    if (route.data?.preload) {
      this.preloadedModules.push(route.path);
      return load();
    } else {
      return of(null);
    }
  }
}
```

4. Make changes to the file **core/index.ts**. Use the following snippet of code:

```
export * from './services/custom-preloading-strategy.service';
```

5. Make changes to **AppRoutingModule**. Use the following snippet of code:

```
// 1
import { Routes, RouterModule, PreloadAllModules, ExtraOptions } from '@angular/router';
import { AuthGuard, CustomPreloadingStrategyService } from './core';
// 2
const extraOptions: ExtraOptions = {
  preloadingStrategy: PreloadAllModules CustomPreloadingStrategyService,
  // enableTracing: true // Makes the router log all its internal events to the console.
};
```

6. Make changes to **AppComponent**. Use the following snippet of code:

```
// 1
import { Component, OnInit } from '@angular/core';
import { MessagesService, CustomPreloadingStrategyService } from './core';

// 2
export class AppComponent implements OnInit {
```

```
// 3
constructor(
    ...
    private preloadingStrategy: CustomPreloadingStrategyService
) {}

// 4
ngOnInit() {
    console.log(
        `Preloading Modules: `,
        this.preloadingStrategy.preloadedModules
    );
}
```

## Task 33. Router Events and Title Service

1. Make changes to **AppRoutingModule**. Use the following snippet of code:

```
const routes: Routes = [
  {
    path: 'about',
    component: AboutComponent,
    data: { title: 'About' }
  },
  {
    path: 'login',
    component: LoginComponent,
    data: { title: 'Login' }
  },
  {
    path: 'admin',
    canActivate: [AuthGuard],
    loadChildren: () => import('./admin/admin.module').then(m => m.AdminModule),
    data: { title: 'Admin' }
  },
  {
    path: 'users',
    loadChildren: () => import('./users/users.module').then(m => m.UsersModule),
    data: {
      preload: true,
      title: 'Users'
    }
  },
  {
    path: '',
    redirectTo: '/home',
    pathMatch: 'full'
  },
  {
    // The router will match this route if the URL requested
    // doesn't match any paths for routes defined in our configuration
    path: '**',
    component: PathNotFoundComponent,
    data: { title: 'Page Not Found' }
  }
];
```

2. Make changes to **TasksRoutingModule**. Use the following snippet of code:

```
const routes: Routes = [
  {
    path: 'home',
    component: TaskListComponent,
    data: { title: 'Task Manager' }
  },
  {
    path: 'edit/:taskID',
    component: TaskFormComponent
  }
];
```

3. Make changes to **AppComponent**. Use the following snippet of code:

```
// 1
import { Component, OnInit, OnDestroy } from '@angular/core';
```

```

import { Title } from '@angular/platform-browser';
import { Router, RouterOutlet, NavigationEnd, NavigationStart } from '@angular/router';

// rxjs
import { Subscription } from 'rxjs';
import { filter, map, switchMap } from 'rxjs/operators';

// 2
export class AppComponent implements OnInit, OnDestroy

// 3
private sub: { [key: string]: Subscription } = {};

  constructor(
    ...
    private titleService: Title
  ) { }

  private setPageTitles() {
    this.sub.navigationEnd = this.router.events
      .pipe(
        filter(event => event instanceof NavigationEnd),
        map(() => this.router.routerState.root),
        map(route => {
          while (route.firstChild) {
            route = route.firstChild;
          }
          return route;
        }),
        filter(route => route.outlet === 'primary'),
        switchMap(route => route.data)
      )
      .subscribe(
        data => this.titleService.setTitle(data.title)
      );
  }

  ngOnInit() {
    ...
    this.setPageTitles();
  }

  ngOnDestroy() {
    this.sub.navigationEnd.unsubscribe();
  }

```

Look to page titles.

Another way:

```

// 4
onActivate($event: any, routerOutlet: RouterOutlet) {
  console.log('Activated Component', $event, routerOutlet);
  // another way to set titles
  this.titleService.setTitle(routerOutlet.activatedRouteData.title);
}

// 5

```



```

ngOnInit() {
  ...
  // this.setPageTitles();
}

ngOnDestroy() {
  // this.sub.navigationEnd.unsubscribe();
}

// 6
private setMessageServiceOnRefresh() {
  this.sub.navigationStart = this.router.events
    .pipe(filter(event => event instanceof NavigationStart))
    .subscribe((event: NavigationStart) => {
      this.messagesService.isDisplayed = event.url.includes('messages:');
    });
}

// 7
ngOnInit() {
  ...
  this.setMessageServiceOnRefresh();
}

// 8
ngOnDestroy() {
  this.sub.navigationStart.unsubscribe();
  // this.sub.navigationEnd.unsubscribe();
}

```

## Task 34. Meta Service

1. Make changes to **TasksRoutingModule**. Use the following snippet of code:

```
// 1
import { MetaDefinition } from '@angular/platform-browser';

// 2
const metaTags: Array<MetaDefinition> = [
  {
    name: 'description',
    content: 'Task Manager Application. This is SPA'
  },
  {
    name: 'keywords',
    content: 'Angular tutorial, SPA, Routing'
  }
];

const routes: Routes = [
  {
    path: 'home',
    component: TaskListComponent,
    data: { title: 'Task Manager' }
  },
  {
    path: 'home',
    component: TaskListComponent,
    data: {
      title: 'Task Manager',
      meta: metaTags
    }
  }
];
```

2. Make changes to **AppComponent**. Use the following snippet of code:

```
// 1
import { Title, Meta } from '@angular/platform-browser';

// 2
constructor(
  ...
  private metaService: Meta
) { }

// 3
this.titleService.setTitle(routerOutlet.activatedRouteData.title);
this.metaService.addTags(routerOutlet.activatedRouteData.meta);
```