

Generative Adversarial Networks

11785 Deep Learning
Spring 2022

Topics for the week

- Transformers
- GNNs
- VAEs
- GANs
- Connecting the dots

The problem



- From a large collection of images of faces, can a network learn to *generate* new portrait
 - Generate samples from the distribution of “face” images
 - How do we even characterize this distribution?

What are GANs

Generative Adversarial Networks

What are GANs

Generative Adversarial Networks



Generative Models which generate data similar to the training data .
E.g. Variational Autoencoders (VAE)

What are GANs

Generative **Adversarial** Networks



Generative Models which generate data similar to the training data .
E.g. Variational Autoencoders (VAE)

Adversarial Training

GANs are made up of two competing networks (adversaries) that are trying to beat each other.

What are GANs



Generative Models which generate data similar to the training data .
E.g. Variational Autoencoders (VAE)

Neural Networks


Adversarial Training

GANs are made up of two competing networks (adversaries) that are trying to beat each other.


Generative Adversarial Networks

- Introduced in 2014
- Goal is to model $P(X)$, the distribution of training data
 - Model can generate samples from $P(X)$
- Trained using a pair of models acting as “adversaries”
 - A “Generator” that generates data
 - A “Discriminator” that evaluates it


What are GANs?



What are GANs?




The Generator




- **The generator** produces realistic looking $X = G(z)$ from a latent vector Z
- Generator input Z can be sampled from a known prior, e.g. standard Gaussian
- **Goal:** generated distribution, $P_G(X)$ matches the true data distribution $P_X(X)$
 - $P_G(X)$ is the more “memorable” notation for $P_{\hat{X}}(X)$, the probability that a generated sample \hat{X} takes the value X

The Discriminator




- Discriminator $D(X)$ is trained to tell the difference between real and generated (fake) data
 - Specifically, data produced by the generator
 - If a perfect discriminator is fooled, the generated data cannot be distinguished from real data

Training the discriminator



- **Training the discriminator:**
 - The discriminator is provided training examples of real and synthetic faces
 - The discriminator is trained to minimize its classification loss
 - Minimize error between actual and predicted labels


Training the generator



- **Training the generator:**


- The discriminator's loss is backpropagated to the generator
- The generator is trained to *maximize* the discriminator loss
 - It is trained to “fool” the discriminator

The GAN formulation



- For real data X , the desired output of the discriminator is $D(X) = 1$
 - The log probability that the instance is real, as computed by the discriminator is $\log D(X)$
- For synthetic data \hat{X} , the desired output of the discriminator is $D(\hat{X}) = 0$
 - The log probability that the instance is synthetic, as computed by the discriminator, is $\log(1 - D(\hat{X}))$
 - $= \log(1 - G(Z))$

The GAN formulation




- The original GAN formulation is the following min-max optimization

$$\min_G \max_D E_X \log D(X) + E_Z \log(1 - D(G(Z)))$$

- Objective of D : $D(X) = 1$ and $D(G(Z)) = 0$
- Objective of G : $D(G(Z)) = 1$

Analysis of optimal behavior:

The optimal discriminator




- The **optimal discriminator** would be a Bayesian classifier

$$D(X) = \frac{P_X(X)}{P_X(X) + P_G(X)}$$

– Assuming uniform prior

Analysis of optimal behavior:

The optimal generator



$$\min_G \max_D E_X \log D(X) + E_Z \log(1 - D(G(Z)))$$

- **With a perfect discriminator:**

$$\begin{aligned} L &= E_{X \sim P_X(X)} \log D(X) + E_{X \sim P_G(X)} \log(1 - D(X)) \\ &= E_{X \sim P_X(X)} \frac{P_X(X)}{P_X(X) + P_D(X)} + E_{X \sim P_G(X)} \frac{P_G(X)}{P_X(X) + P_D(X)} \end{aligned}$$

- This is just the Jensen-Shannon divergence between $P_X(X)$ and $P_G(X)$ to within a scaling factor and a constant

$$L = 2JSD(P_X(X), P_D(X)) - \log 4$$

The Jensen Shannon Divergence


$$JSD(P, Q)$$

$$= 0.5 KL(P, 0.5(P + Q)) + 0.5 KL(Q, 0.5(P + Q))$$

- A symmetric variant of KL that does not exaggerate instances to which one of the distributions assigns 0 probability
 - $KL(P, Q) = \sum_X P(X) \log(P(X)/Q(X))$ blows up the contributions of X with $Q(X) = 0$

Analysis of optimal behavior:

The optimal generator



- The optimal generator:

$$\min_G 2JSD(P_X(X), P_G(X)) - \log 4$$

- The optimal generator minimizes the Jensen Shannon divergence between the distributions of the actual and synthetic data!
 - Tries to make the two distributions maximally similar


Min-Max Stationary Point

- There exists a stationary point:
 - If the generated data exactly matches the real data, the discriminator outputs 0.5 for all inputs
 - If discriminator outputs 0.5, the gradients for the generator is flat, so generator does not learn
 - Unfortunately, this is also true of a random discriminator
- Stationary points need not be stable (depends on the exact GANs formulation and other factors)
 - Generator may overshoot some values or oscillate around the optimum
 - A discriminator with unlimited capacity can still assign an arbitrarily large distance to 2 similar distributions

Min-Max Optimization

- Generator and the discriminator need to be trained simultaneously
 - If discriminator is undertrained, it provides sub-optimal feedback to the generator
 - If the discriminator is overtrained, there is no local feedback for marginal improvements

How to Train a GAN?



Optimize: $\min_G \max_D E_X \log D(X) + E_Z \log(1 - D(G(Z)))$

The discriminator is not needed after convergence

Features and Challenges

- GANs can produce clear crisp results for many problems
- But they also have stability issues and are hard to train
 - Problems such as “mode collapse” are frequent
 - Producing outputs with very low variability

Variants and updates

- A number of variations have been proposed to improve the stability and outputs of GANs
 - LAPGAN
 - Wasserstein GAN
 - C-GAN
 - DCGAN
 - CycleGAN
 - StarGAN
 - ...

Evaluate with Discriminative Network

- Inception Score
 - Use the Inception V3 image classifier to classify generated images
 - Inception should produce a variety of labels
 - **As measured by the entropy of the average label distribution**
 - Each label should have high confidence (low entropy)
 - **As measured by the average entropy of the Inception outputs for individual instances**
 - The two scores are combined into a single “inception” score

VAEs vs GANs

VAEs

- Minimizing the KL divergence between distributions of synthetic and true data
- Uses an encoder to predict latent distributions to optimize generator
- More complex formulation
- Simpler optimization. Trains faster and more reliably
- Results are blurry

GANs

- Minimizing the Jensen-Shannon divergence between distributions of synthetic and true data
- Use a discriminator to optimize generator
- Simpler formulation
- Noisy and difficult optimization
- Sharper results

Original paper (GAN, 2014)


Output of original GAN paper, 2014 [GPM⁺14]



a)



b)



c)



d)

GANs with time

- Better quality
- High Resolution



https://twitter.com/goodfellow_ian/status/1084973596236144640?lang=en

StarGAN(2018)

Manipulating Celebrity Faces [CCK⁺17]




Figure 1. Multi-domain image-to-image translation results on the CelebA dataset via transferring knowledge learned from the RaFD dataset. The first and sixth columns show input images while the remaining columns are images generated by StarGAN. Note that the images are generated by a single generator network, and facial expression labels such as angry, happy, and fearful are from RaFD, not CelebA.

Progressive growing of GANs (2018)



Figure 5: 1024×1024 images generated using the CELEBA-HQ dataset. See Appendix F for a larger set of results, and the accompanying video for latent space interpolations.

High fidelity natural images (2019)

Generating High-Quality Images [BDS18]

