CME 213, ME 339—Spring 2021
Introduction to parallel computing using MPI, openMP, and CUDA

Eric Darve, ICME, Stanford

"Computers are useless. They can only give you answers." (Pablo Picasso)

Homework 1

Pre-requisite homework

Topics:

- derived classes
- polymorphism
- standard library
- testing

Submission

1. Submit your PDF on gradescope
2. For your computer code, copy your files to `cardinal`
3. Run a Python script it submit code

Grading is done on gradescope



Deadline is **Friday, April 9**

Why parallel computing?

Parallel computing is omni-present

Any type of non-trivial computing requires parallel computing

- Gordon Moore 1965: "the number of transistors on a chip shall double every 18–24 months."
- Accompanied by an increase in clock speed

Intel microprocessor trends



Original data up to the year 2010 collected and plotted by M. Horowitz, F. Labonte, O. Shacham, K. Olukotun, L. Hammond, and C. Batten
New plot and data collected for 2010-2017 by K. Rupp

But

Increase in transistor density is limited by:

- Leakage current increases
- Power consumption increases
- Heat generated increases

Memory access time has not been reduced at a rate comparable to the processing speed

↓

Go parallel!

Multiple cores on a processor

Multicore

One/few

but

fast core(s)

Manycore

- Many, but slower cores
- GPUs

Core increase; frequency plateau



Historical data on 1403 Intel microprocessors



Historical data on 566 NVIDIA GPUs

Memory wall; bandwidth and latency



Intel microprocessors



NVIDIA GPUs

More info at

https://pure.tue.nl/ws/portalfiles/portal/3942529/771987.pdf

Parallel computing everywhere!

Multi and many core processors



Intel Ice Lake 10 nm

NVIDIA

Turing TU102 architecture





Cloud computing

Summit—Oak Ridge National Laboratory's 200 petaflop supercomputer

Processor: IBM POWER9™ (2/node)

GPUs: 27,648 NVIDIA Volta V100s (6/node)

Nodes: 4,608

Node Performance: 42TF

Memory/node: 512GB DDR4 + 96GB HBM2

NV Memory/node: 1600GB

Total System Memory: >10PB DDR4 + HBM + Non-volatile

Interconnect Topology: Mellanox EDR 100G InfiniBand, Non-blocking Fat Tree

Peak Power Consumption: 13MW

Top 500 Supercomputers

Green 500

Rank	TOP500 Rank	System	Cores	Rmax (TFlop/s)	Power (kW)	Power Efficiency (GFlops/watts)
1	170	**NVIDIA DGX SuperPOD** - NVIDIA DGX A100, AMD EPYC 7742 64C 2.25GHz, NVIDIA A100, Mellanox HDR Infiniband, Nvidia NVIDIA Corporation United States	19,840	2,356.0	90	26.195
2	330	**MN-3** - MN-Core Server, Xeon Platinum 8260M 24C 2.4GHz, Preferred Networks MN-Core, MN-Core DirectConnect, Preferred Networks Preferred Networks Japan	1,664	1,652.9	65	26.039
3	7	**JUWELS Booster Module** - Bull Sequana XH2000 , AMD EPYC 7402 24C 2.8GHz, NVIDIA A100, Mellanox HDR InfiniBand/ParTec ParaStation ClusterSuite, Atos Forschungszentrum Juelich (FZJ) Germany	449,280	44,120.0	1,764	25.008
4	146	**Spartan2** - Bull Sequana XH2000 , AMD EPYC 7402 24C 2.8GHz, NVIDIA A100, Mellanox HDR Infiniband, Atos Atos France	23,040	2,566.0	106	24.262
5	5	**Selene** - NVIDIA DGX A100, AMD EPYC 7742 64C 2.25GHz, NVIDIA A100, Mellanox HDR Infiniband, Nvidia NVIDIA Corporation United States	555,520	63,460.0	2,646	23.983

Vendor shares




Countries - Performance Share
Share
100
90
80
70
60
50
40
30
20
10
0
2012
2013
2014
2015
2016
2017
2018
Jun 01, 2020
Hong Kong 1,649,110 (0.07%)
Israel 0 (0%)
Belgium 0 (0%)
Mexico 0 (0%)
Denmark 0 (0%)
Austria 2,726,077 (0.12%)
Sweden 4,771,700 (0.22%)
Spain 6,470,800 (0.29%)
Poland 1,670,090 (0.08%)
Singapore 6,596,440 (0.30%)
Finland 7,095,250 (0.32%)
Norway 7,718,070 (0.35%)
Russia 9,147,000 (0.41%)
Australia 10,913,420 (0.49%)
India 6,334,340 (0.29%)
Brazil 10,991,000 (0.50%)
Taiwan 10,325,150 (0.47%)
South Korea 18,720,660 (0.85%)
Netherlands 24,736,650 (1.12%)
Switzerland 23,126,750 (1.05%)
Canada 27,926,059 (1.27%)
United Kingdom 30,950,142 (1.40%)
Saudi Arabia 10,109,130 (0.46%)
Others 33,559,020 (1.52%)
Italy 87,188,790 (3.95%)
France 79,878,820 (3.62%)
Germany 68,713,720 (3.11%)
China 565,553,101 (25.64%)
Japan 527,607,512 (23.92%)
United States 621,655,590 (28.18%)

More at

https://www.top500.org/

Example of a Parallel Computation

Parallel programs often look very different from sequential programs





Sequential



Parallel

Example: program to sum numbers

```
for (int i = 0; i < n; ++i)
{
   x = ComputeNextValue();
   sum += x;
}
```

We have p cores that can compute and exchange data

Can we accelerate our calculation by splitting the work among the cores?

```
int r; /* thread number */
int b; /* number of entries processed */
int my_first_i = r * b;
int my_last_i = (r + 1) * b;
for (int my_i = my_first_i; my_i < my_last_i; my_i++) {
    my_x = ComputeNextValue();
    my_sum += my_x;
}
```

Not that simple

Each core has computed a partial sum

All these partial sums need to summed up together

Simplest approach:

have one "master" thread do all the work

```
if (r == 0) /* master thread */
{
   int sum = my_sum;
   for (int ro = 1; ro < p; ++ro)
   {
      int sum_ro;
      ReceiveFrom(&sum_ro, ro);
      sum += sum_ro;
   }
}
else /* worker thread */
{
   SendTo(&my_sum, 0);
}
```

That may not be enough

If we have many cores, this final sum may take a lot of time


10 1 8 -1 0 -2 3 5 -2 -3 2 7 0 11 0 2
0 1 2 3 4 5 6 7
8 -2 10 6 0 9 3 7 -2 -3 2 7 0 11 0 2
0 1 2 3
8 7 13 13 0 9 3 7 -2 -3 2 7 0 11 0 2
0 1
21 20 13 13 0 9 3 7 -2 -3 2 7 0 11 0 2
0
41 20 13 13 0 9 3 7 -2 -3 2 7 0 11 0 2

This simple example illustrates the fact that it is difficult for a compiler to parallelize a program.

Instead the programmer must often re-write his code having in mind that multiple cores will be computing in parallel.

The purpose of this class is to teach you the most common parallel languages used in science and engineering.

Shared Memory Processor

Schematic

- A number of processors or cores
- A shared physical memory (global memory)
- An interconnection network to connect the processors with the memory


Processor
Processor
Processor
Cache
Cache
Cache
Interconnection Network
Memory
I/O

Shared memory NUMA

In many cases, the program views the memory as a single addressable space.

In reality, the memory is physically distributed.

NUMA non-uniform memory access

Why? Faster access to memory

But, special hardware required to move data between memory banks


Processor
Processor
Processor
Cache
Cache
Cache
Single address space
Memory
Memory
Memory
Interconnection Network
I/O

Bulldozer server (AMD)



Cache coherent NUMA (ccNUMA) uses inter-processor communication between cache controllers to keep a consistent memory image when more than one cache stores the same memory location

Motherboard with 2 CPU sockets



Performance tip on multicore

- Memory is key to developing high-performance multicore applications
- Memory traffic and time to access memory are often more important than flops
- Memory is hierarchical and complex


L0:
Regs
L1:
L1 cache
(SRAM)
L2:
L2 cache
(SRAM)
L3:
L3 cache
(SRAM)
L4:
Main memory
(DRAM)
L5:
Local secondary storage
(local disks)
L6:
Remote secondary storage
(distributed file systems, Web servers)
Smaller, faster, and costlier (per byte) storage devices
Larger, slower, and cheaper (per byte) storage devices
CPU registers hold words retrieved from cache memory.
L1 cache holds cache lines retrieved from the L2 cache.
L2 cache holds cache lines retrieved from L3 cache
L3 cache holds cache lines retrieved from memory.
Main memory holds disk blocks retrieved from local disks.
Local disks hold files retrieved from disks on remote network servers.

Memory	Size	Latency	Bandwidth
L1 cache	32 KB	1 nanosecond	1 TB/second
L2 cache	256 KB	4 nanoseconds	1 TB/second Sometimes shared by two cores
L3 cache	8 MB or more	10x slower than L2	>400 GB/second
MCDRAM		2x slower than L3	400 GB/second
Main memory on DDR DIMMs	4 GB-1 TB	Similar to MCDRAM	100 GB/second
Main memory on Intel Omni-Path Fabric	Limited only by cost	Depends on distance	Depends on distance and hardware
I/O devices on memory bus	6 TB	100x-1000x slower than memory	25 GB/second
I/O devices on PCIe bus	Limited only by cost	From less than milliseconds to minutes	GB-TB/hour Depends on distance and hardware