Design Assignment 2:
Assembly Language Programming

Alexis Adie and Madison Mastroberte
ELC 411-01: Embedded Systems

Submitted:
October 11th 2017

Design Assignment 2: Assembly Language Programming

Alexis Adie and Madison Mastroberte

Department of Electrical and Computer Engineering
The College of New Jersey
2000 Pennington Road, Ewing, NJ 08618, USA
(adiea1, mastrom7)@tcnj.edu

I. Introduction

The lab consisted of a dual implementation of 'C' and assembly codes that produce the same results. The programs were coded to simulate the dot product, inner product, of two 16-bit data arrays. A 'C' code was provided to students and the assembly was first created by students. Utilizing the debugger tool in PSoC Creator, students tested and checked the logical behavior of their assembly code. Once the debugger values matched the 'C' language results, this portion of the lab was completed. Next students retrieved the compiler's assembly version of the 'C' code, and analyzed the code. Overall, the lab introduced students to the debugging design environment, while showing how to generate a specific assembly code to mimic a 'C' subroutine code.

II. Methodology

A. Pre-Class: Manual Assembly Code

Students began by generating assembly code by mimicking the 'C' code given in the first step. The parameters were passed in the R0, R1, and R2 registers, however return values were deposited in R0.

B. Part I: Debugging Manual Assembly Code

Students began by downloading the canvas file, main_for_asm_project.c and pasting the code into a main.c file. Once the initial code was replaced, a breakpoint was set at line 34; the location is where the sum is declared. The compiler was then set to an optimization strategy of 'None.' Once set, the project was built and run under debug mode. The debugger will run each step, using F5, until the breakpoint. Next the disassembled code was viewed. The code was then copied and then pasted into "inner_prod_gcc.s."

C. Part II: Analysis of Compiled Assembly Code

Students began the second portion of the lab by creating a new assembly language source file (GNU ARM Assembly file). The initial boilerplate code was changed to implement the inner_prod_asm code. Once tested, and put into debug mode, the six variables were place on the Watchlist. These values are shown in Figure 1.

Once completed, two digital output pins were added to the design. Then using these pins, the time spent in the 'C' code and manual assembly code was measured. The pins were then used to measure triggered waveforms and time for the signal.

Lastly, the code was recompiled with a 'Speed' optimization level. Then the time spent in the optimized 'C' code and manual assembly code was remeasured.

III. Results

A. Matching ARM and C Results

Name	Value
t1	0x0000
t2	0x3FFE
t3	0x3FFF
y1	0x80CC
y2	0x80CC
y3	0x810C

Figure 3.1: Screenshot watchlist for debugged assembly code, including six variables.

B. Speed Optimization

Table 3.1: Time spent in the 'C' version of the function with varying compiler strategies.

'C' Time (No Optimization) (ms)	'C' Time (Speed Optimization) (ms)	Assembly Time (ms)
1316	480	1837



Figure 3.2: Oscilloscope reading with no speed optimization



Figure 3.3: Oscilloscope reading with speed optimization

IV. Discussion

Due to errors within the code created, the developers were unable to achieve a match between the variables as expected. The issues stemmed from the loop section of the code, which the team confirmed by changing the code with each trial.

However, by testing each section of the code with optimization for speed versus no optimization, the team confirmed that the 'C' code was faster than the assembly code written. Optimization with speed also allowed the 'C' code to run much faster.

V. Conclusion

Overall, the lab demonstrated the ability to interface 'C' and assembly to successfully perform the dot product and interact with another. In Part I, students implemented two codes, 'C' and assembly, that produce the dot product. Students then debugged the code to match output values of the 'C' code. Next, students analyzed the various outputted assembly codes with differing optimization strategies. Overall, the lab introduced students to the debugging design environment, while showing how to utilize assembly code to create the same behaviors as a 'C' subroutine. The lab was successful and gave students insight regarding the capabilities of PSoC Creator.

VI. Appendix

Part I: Madison Mastroberte's Assembly Code (Prior to Lab)

```
;Assume:

    R0 = h
    R1 = x
    R2 = n
    R3 = i
    R4 = sum
    R5 = store_1
    R6 = store_2

;set registers to 0

        MOV R3, #0        ; i = 0
```

```
        MOV R4, #0       ; sum = 0
        MOV R5, #0       ; store_1 = 0
        MOV R6, #0       ; store_2 = 0

        PUSH {R4, R5, R6}; Push additional register since past R3

        B check          ; test at top of loop

loop:   LDRSH R2, [R0]   ; Load half into n
        LDRSH R4, [R0]   ; Load half into sum

        MUL R5, R0, R1   ; sum += (h[i] * x[i])
        ADD R6, R5, R4   ; Adding the store_1 with sum into store_2
        ADD R3, #1       ; ++i
        ASR R6 R4 #16    ; sum = sum >> 16   R6

        B endloop

check:  CMP R3, R2       ; i < n

        BLT loop         ; Branch to loop if compared result is less than

endloop:
        BX LR

        POP {R4, R5, R6}

end
```

Part II: Alexis Adie's Assembly Code (Prior to Lab)

```
       /*   Assume
                  R0 = i
                  R1 = x
                  R2 = h
                  R3 = n
                  R4 = sum
                  R5 = temp
      */
      //set registers to 0
            MOV R3, #0        //i = 0
            MOV R4, #0        //sum = 0

            PUSH {R4}
            PUSH {R5}
      loop:
            CMP R0, R3        //i < n
```

```
            LDRSH R2, [R0]    //h[i]
            LDRSH R1, [R0]    //x[i]
            MUL R5, R1, R2    //temp=(h[i] * x[i])
            ADD R4, R4, R5    //sum += (h[i] * x[i])
            ADD R0, #1        //++i
            LSR R1, #16       //sum = sum >> 16
            BX LR
      //end
            .endfunc
            .end
```

Part III: Debugged Assembly Code

```
       //initialize the variables in registers
       /*   Assume
                  R0 = h
                  R1 = x
                  R2 = n
                  R3 = i
                  R4 = sum
                  R5 = temp
      */

      //set registers to 0
            MOV R3, #0        //i = 0
            MOV R4, #0        //sum = 0
      //  B test

            PUSH {R4,R5}
      loop:
            CMP R0, R1        //i < n
            //BEQ
            LDRSH R3, [R0]    //h[1]
            LDRSH R1, [R0]    //x[i]
            MUL R5, R1, R3    //temp=(h[i] * x[i])
            ADD R4, R4, R5    //sum += (h[i] * x[i])
            ADD R0, #1        //++i
            ASR R1, #16       //sum = sum >> 16
            B loop

            POP {R4}
            BX LR
```

Part IV: inner_prod_gcc.s Code with Comments

0x00000084 <inner_prod>:

```
    31: // Inputs:   h - pointer to array of int16_t values, length n
    32: //           x - pointer to array of int16_t values, length n
    33: // Returns:  [x (dot) h] >> 16, as an int16_t value
    34: int16_t inner_prod( int16_t *h, int16_t *x, int n )
    35: {

0x00000084 push    {r7}         //Stores r7 to the top of the stack
0x00000086 sub     sp, #1c      //Creates stack frame
0x00000088 add     r7, sp, #0   //Uses r7 as the "frame pointer"
0x0000008A str     r0, [r7, #c] //Stores r7 into array h with offset of 0x0C
0x0000008C str     r1, [r7, #8] //Stores r7 into array x with offset of 0x08
0x0000008E str     r2, [r7, #4] //Stores r7 into array n with offset of 0x04

    36:     int i;
    37:     int32_t sum = 0;

0x00000090 movs    r3, #0       //r3=sum=0
0x00000092 str     r3, [r7, #10]//Stores r7 into sum at offset of 0x10

    38:
    39:     for (i = 0; i < n; ++i)

0x00000094 movs    r3, #0       //r3=i=0
0x00000096 str     r3, [r7, #14]//Stores i at offset of 0x14
0x00000098 b.n     c4 <CYDEV_PICU_SIZE+0x14>//ignored as per instructions

    40:     {
    41:     sum += (h[i] * x[i]);

0x0000009A ldr     r3, [r7, #14]//Loads i from frame offset 0x14 to r3
0x0000009C lsls    r3, r3, #1   //Logical shift left r3 by 1
0x0000009E ldr     r2, [r7, #c] //Loads h from frame offset 0x0C to r2
0x000000A0 add     r3, r2       //h[i]
0x000000A2 ldrsh.w r3, [r3]     //Loads halfword r3
0x000000A6 mov     r1, r3       //r1=[h[i]
0x000000A8 ldr     r3, [r7, #14]//Loads i from frame offset 0x14 to r3
0x000000AA lsls    r3, r3, #1   //Logical shift left by 1
0x000000AC ldr     r2, [r7, #8] //Loads x from frame offset 0x08 to r2
0x000000AE add     r3, r2       //x[i]
0x000000B0 ldrsh.w r3, [r3]     //Loads halfword r3
0x000000B4 mul.w   r3, r3, r1   //r3=h[i]*x[i]
0x000000B8 ldr     r2, [r7, #10]//Loads sum with offset 0x10 to r2
0x000000BA add     r3, r2       //r3=sum+(h[i]*x[i])
0x000000BC str     r3, [r7, #10]//Stores new sum into array r3 with offset 0x10

    34: int16_t inner_prod( int16_t *h, int16_t *x, int n )
    35: {
    36:     int i;
```

```
    37:     int32_t sum = 0;
    38:
    39:     for (i = 0; i < n; ++i)

0x000000BE ldr     r3, [r7, #14]//Loads i from r3 with offset of 0x14
0x000000C0 adds    r3, #1       //i=i+1
0x000000C2 str     r3, [r7, #14]//Stores i back into r3
0x000000C4 ldr     r2, [r7, #14]//Loads i
0x000000C6 ldr     r3, [r7, #4] //Loads n
0x000000C8 cmp     r2, r3       //Compares i and n
0x000000CA blt.n   9a <inner_prod+0x16>//i<n

    40:     {
    41:     sum += (h[i] * x[i]);   // accumulate each of the 'n' product terms
    42:     }
    43:     sum = sum >> 16;         // right shift to normalize

0x000000CC ldr     r3, [r7, #10]//Loads sum from r3
0x000000CE asrs    r3, r3, #10  //Arithmetic shift right by 16
0x000000D0 str     r3, [r7, #10]//Stores the new sum into r3

    44:
    45:     return (int16_t) sum;

0x000000D2 ldr     r3, [r7, #10]//Loads sum from r3
0x000000D4 sxth    r3, r3        //Returns sum

    46: }

0x000000D6 mov     r0, r3       //Set r0 to sum
0x000000D8 adds    r7, #1c      //Add 1c to r7
0x000000DA mov     sp, r7       //sp=r7
0x000000DC pop     {r7}         //pops r7 from the top of the stack
0x000000DE bx      lr           //branch
```

Part V: inner_prod_asm.s Code with Comments

```
            .syntax unified
            .text

            .global inner_prod_asm
            .func inner_prod_asm, inner_prod_asm
            .thumb_func

      inner_prod_asm:
       //initialize the variables in registers
       /*   Assume
                  R0 = h
```

```
                R1 = x
                R2 = n
                R3 = i
                R4 = sum
                R5 = temp
      */
//set registers to 0

      PUSH  {R4,R5,R6}         //Stores regs to the top of the stack
      MOV   R3, #0       //sum = 0
      MOV   R4, #0       //i=0
      B test

loop:

      LDRSH R0, [R4],#4        //h[i]
      LDRSH R1, [R4], #4       //x[i]
      MUL   R5, R0, R1   //h[i]*x[i]
      ADD   R3, R3, R5   //sum= sum + (h[i]*x[i])
      ADD   R4, R4, #1         //i++
      B test


test:
      CMP   R4, R2       //i < n
      BLT   loop
      ASR   R3, #16      //shift right by 16
      MOV   R0, R3       //r0=sum
      POP   { R4, R5, R6}
      SXTH   R0, R3
      BX    LR
      .endfunc
      .end
```

```
.s code

0x00000084 <inner_prod>:
0x00000084 push    {r7}
0x00000086 sub     sp, #1c
0x00000088 add     r7, sp, #0
0x0000008A str     r0, [r7, #c]
0x0000008C str     r1, [r7, #8]
 537:             CY_LIB_IMO_24MHZ_VALUE) & ((uint8)(~CY_LIB_IMO_USBCLK_ON_SET));
 538:         break;
0x0000008E str     r2, [r7, #4]
  33:     case CY_IMO_FREQ_48MHZ:
  34:         CY_LIB_FASTCLK_IMO_CR_REG = ((CY_LIB_FASTCLK_IMO_CR_REG &
CY_LIB_FASTCLK_IMO_CR_RANGE_MASK) |
0x00000090 movs    r3, #0
0x00000092 str     r3, [r7, #10]
0x00000094 movs    r3, #0
0x00000096 str     r3, [r7, #14]
0x00000098 b.n     c2 <CYDEV_PICU_SIZE+0x12>
0x0000009A ldr     r3, [r7, #14]
0x0000009C lsls    r3, r3, #1
 114:             CY_LIB_IMO_48MHZ_VALUE) & ((uint8)(~CY_LIB_IMO_USBCLK_ON_SET));
 115:         break;
0x0000009E ldr     r2, [r7, #c]
 117:     case CY_IMO_FREQ_62MHZ:
 118:         CY_LIB_FASTCLK_IMO_CR_REG = ((CY_LIB_FASTCLK_IMO_CR_REG &
CY_LIB_FASTCLK_IMO_CR_RANGE_MASK) |
0x000000A0 add     r3, r2
0x000000A2 ldrh    r3, [r3, #0]
0x000000A4 sxth    r3, r3
0x000000A6 ldr     r2, [r7, #14]
0x000000A8 lsls    r2, r2, #1
0x000000AA ldr     r1, [r7, #8]
0x000000AC add     r2, r1
 127:             CY_LIB_IMO_62MHZ_VALUE) & ((uint8)(~CY_LIB_IMO_USBCLK_ON_SET));
 128:         break;
0x000000AE ldrh    r2, [r2, #0]
 550: #if(CY_PSOC5)
 551:     case CY_IMO_FREQ_74MHZ:
 552:         CY_LIB_FASTCLK_IMO_CR_REG = ((CY_LIB_FASTCLK_IMO_CR_REG &
CY_LIB_FASTCLK_IMO_CR_RANGE_MASK) |
0x000000B0 sxth    r2, r2
```

```
0x000000B2 mul.w   r3, r2, r3
0x000000B6 ldr     r2, [r7, #10]
0x000000B8 add     r3, r2
0x000000BA str     r3, [r7, #10]
0x000000BC ldr     r3, [r7, #14]
 553:             CY_LIB_IMO_74MHZ_VALUE) & ((uint8)(~CY_LIB_IMO_USBCLK_ON_SET));
 554:         break;
0x000000BE adds    r3, #1
 130: #endif  /* (CY_PSOC5) */
 131:     case CY_IMO_FREQ_USB:
 132:         CY_LIB_FASTCLK_IMO_CR_REG = ((CY_LIB_FASTCLK_IMO_CR_REG &
CY_LIB_FASTCLK_IMO_CR_RANGE_MASK) |
0x000000C0 str     r3, [r7, #14]
0x000000C2 ldr     r2, [r7, #14]
0x000000C4 ldr     r3, [r7, #4]
0x000000C6 cmp     r2, r3
0x000000C8 blt.n   9a <__cy_region_init_size_ram+0x12>
0x000000CA ldr     r3, [r7, #10]
0x000000CC asrs    r3, r3, #10
 140:             CY_LIB_IMO_24MHZ_VALUE) | CY_LIB_IMO_USBCLK_ON_SET;
 141:         break;
0x000000CE str     r3, [r7, #10]
  41:     default:
  42:         CYASSERT(0u != 0u);
0x000000D0 ldr     r3, [r7, #10]
0x000000D2 uxth    r3, r3
0x000000D4 sxth    r3, r3
  40:         break;
  41:     }
  42:     /* Tu rn onIMO Doubler, if switching to CY_IMO_FREQ_USB */
  43:     if (freq == CY_IMO_FREQ_USB)
0x000000D6 mov     r0, r3
0x000000D8 adds    r7, #1c
 569:     {
 570:         CyIMO_EnableDoubler();
0x000000DA mov     sp, r7
0x000000DC ldr.w   r7, [sp], #4
 571:     }
 572:     else
 573:     {
 574:         CyIMO_DisableDoubler();
0x000000E0 bx      lr
```