

Review Questions

The answers to the chapter review questions can be found in the Appendix.

1. What is output by the following code? (Choose all that apply.)

```
1: public class Fish {  
2:     public static void main(String[] args) {  
3:         int numFish = 4;  
4:         String fishType = "tuna";  
5:         String anotherFish = numFish + 1;  
6:         System.out.println(anotherFish + " " + fishType);  
7:         System.out.println(numFish + " " + 1);  
8:     } }
```

- A. 4 1
- B. 5
- C. 5 tuna
- D. 5tuna
- E. 51tuna

No podemos guardar un int en un String

- F. The code does not compile.

2. Which of these array declarations are not legal? (Choose all that apply.)

- A. `int[][] scores = new int[5][];`
- B. `Object[][][] cubbies = new Object[3][0][5];`
- C. `String beans[] = new beans[6];` usa el nombre de la variable como tipo de dato
- D. `java.util.Date[] dates[] = new java.util.Date[2][];`
- E. `int[][] types = new int[];` omiten el tamaño obligatorio del arreglo
- F. `int[][] java = new int[][];`

3. Note that March 13, 2022 is the weekend when we spring forward, and November 6, 2022 is when we fall back for daylight saving time. Which of the following can fill in the blank without the code throwing an exception? (Choose all that apply.)

```
var zone = ZoneId.of("US/Eastern");  
var date = _____;  
var time = LocalTime.of(2, 15);  
var z = ZonedDateTime.of(date, time, zone);
```

- A. `LocalDate.of(2022, 3, 13)`
- B. `LocalDate.of(2022, 3, 40)`
- C. `LocalDate.of(2022, 11, 6)`

B. un día inexistente

- D.** `LocalDate.of(2022, 11, 7)`
- E.** `LocalDate.of(2023, 2, 29)` no es año bisiesto
- F.** `LocalDate.of(2022, MonthEnum.MARCH, 13);` nombre de enum incorrecto

4. Which of the following are output by this code? (Choose all that apply.)

```
3: var s = "Hello";
4: var t = new String(s);
5: if ("Hello".equals(s)) System.out.println("one");
6: if (t == s) System.out.println("two");
7: if (t.intern() == s) System.out.println("three");
8: if ("Hello" == s) System.out.println("four");
9: if ("Hello".intern() == t) System.out.println("five");
```

- A.** one Comparten la misma dirección de memoria
- B.** two
- C.** three con intern obtienes la referencia compartida
- D.** four
- E.** five
- F.** The code does not compile.
- G.** None of the above

5. What is the result of the following code?

```
7: var sb = new StringBuilder();
8: sb.append("aaa").insert(1, "bb").insert(4, "ccc");
9: System.out.println(sb);
```

- A.** `abbaaccc`
- B.** `abbaccca` `StringBuilder` es mutable y permite encadenar
- C.** `bbaaaccc`
- D.** `bbaaccca`
- E.** An empty line
- F.** The code does not compile.

6. How many of these lines contain a compiler error? (Choose all that apply.)

```
23: double one = Math.pow(1, 2);
24: int two = Math.round(1.0);
25: float three = Math.random();
26: var doubles = new double[] {one, two, three};
```

- A.** 0
- B.** 1

- C.** 2 `Math.round()` devuelve un long y `Math.random()` devuelve un double
D. 3 pero el código los guarda en int y float
E. 4

7. Which of these statements is true of the two values? (Choose all that apply.)

2022-08-28T05:00 GMT-04:00

2022-08-28T09:00 GMT-06:00

- A.** The first date/time is earlier. Si conviertes ambas horas a la zona horaria neutral
B. The second date/time is earlier. la primera ocurre a las 09:00 y la segunda a las 15:00
C. Both date/times are the same.
D. The date/times are two hours apart.
E. The date/times are six hours apart.
F. The date/times are 10 hours apart.

8. Which of the following return 5 when run independently? (Choose all that apply.)

```
var string = "12345";
```

```
var builder = new StringBuilder("12345");
```

Los índices empiezan en 0, en A el índice 4 es 5,

En B y F los reemplazos previos dejan el 5 en el índice solicitado

- A.** `builder.charAt(4)`
B. `builder.replace(2, 4, "6").charAt(3)`
C. `builder.replace(2, 5, "6").charAt(2)`
D. `string.charAt(5)`
E. `string.length`
F. `string.replace("123", "1").charAt(2)`
G. None of the above

9. Which of the following are true about arrays? (Choose all that apply.)

- A.** The first element is index 0.
B. The first element is index 1.
C. Arrays are fixed size. Los Arrays nician en 0, su tamaño es fijo y equals compara su memoria,
D. Arrays are immutable.
E. Calling `equals()` on two different arrays containing the same primitive values always returns true.
F. Calling `equals()` on two different arrays containing the same primitive values always returns false.
G. Calling `equals()` on two different arrays containing the same primitive values can return true or false.

10. How many of these lines contain a compiler error? (Choose all that apply.)

```
23: int one = Math.min(5, 3);  
24: long two = Math.round(5.5);  
25: double three = Math.floor(6.6);  
26: var doubles = new double[] {one, two, three};
```

- ☒ A. 0
- ☐ B. 1 Compila perfecto porque los métodos devuelven tipos de datos compatibles
- ☐ C. 2
- ☐ D. 3
- ☐ E. 4

11. What is the output of the following code?

```
var date = LocalDate.of(2022, 4, 3);  
date.plusDays(2);  
date.plusHours(3);  
System.out.println(date.getYear() + " " + date.getMonth()  
    + " " + date.getDayOfMonth());
```

- ☐ A. 2022 MARCH 4
- ☐ B. 2022 MARCH 6
- ☐ C. 2022 APRIL 3 Falla porque LocalDate solo guarda fechas, no tiene horas
- ☐ D. 2022 APRIL 5
- ☒ E. The code does not compile.
- ☐ F. A runtime exception is thrown.

12. What is output by the following code? (Choose all that apply.)

```
var numbers = "012345678".indent(1);  
numbers = numbers.stripLeading();  
System.out.println(numbers.substring(1, 3));  
System.out.println(numbers.substring(7, 7));  
System.out.print(numbers.substring(7));
```

- ☒ A. 12
- ☐ B. 123 En A y B se corta el texto con substring desde un índice inicial hasta antes del índice final
- ☐ C. 7
- ☒ D. 78
- ☒ E. A blank line
- ☐ F. The code does not compile.
- ☐ G. An exception is thrown.

13. What is the result of the following code?

```
public class Lion {  
    public void roar(String roar1, StringBuilder roar2) {  
        roar1.concat("!!!");  
        roar2.append("!!!");  
    }  
    public static void main(String[] args) {  
        var roar1 = "roar";  
        var roar2 = new StringBuilder("roar");  
        new Lion().roar(roar1, roar2);  
        System.out.println(roar1 + " " + roar2);  
    }  
}
```

- A. roar roar
 - B. roar roar!!!**
 - C. roar!!! roar
 - D. roar!!! roar!!!
 - E. An exception is thrown.
 - F. The code does not compile.
- Los string son intocables pero los StringBuilder se pueden modificar

14. Given the following, which can correctly fill in the blank? (Choose all that apply.)

```
var date = LocalDate.now();  
var time = LocalTime.now();  
var dateTime = LocalDateTime.now();  
var zoneId = ZoneId.systemDefault();  
var zonedDateTime = ZonedDateTime.of(dateTime, zoneId);  
Instant instant = _____;
```

- A. Instant.now()**
 - B. new Instant()**
 - C. date.toInstant()
 - D. dateTime.toInstant()
 - E. time.toInstant()
 - F. zonedDateTime.toInstant()**
- Instant exige un momento exacto en el tiempo, algo que una fecha u hora suelta no tiene

15. What is the output of the following? (Choose all that apply.)

```
var arr = new String[] { "PIG", "pig", "123"};  
Arrays.sort(arr);  
System.out.println(Arrays.toString(arr));  
System.out.println(Arrays.binarySearch(arr, "Pippa"));
```

- A. [pig, PIG, 123]
 - B. [PIG, pig, 123]
 - C. [123, PIG, pig]
 - D. [123, pig, PIG]
 - E. -3
 - F. -2
 - G. The results of `binarySearch()` are undefined in this example.
- Ordena números, mayúsculas, minúsculas como Pippa iría en la posición 2 devuelve -3

16. What is included in the output of the following code? (Choose all that apply.)

```
var base = "ewe\nsheep\\t";  
int length = base.length();  
int indent = base.indent(2).length();  
int translate = base.translateEscapes().length();
```

```
var formatted = "%s %s %s".formatted(length, indent, translate);  
System.out.format(formatted);
```

- A. 10
 - B. 11
 - C. 12
 - D. 13
 - E. 14
 - F. 15
 - G. 16
- Inicia con 11 caracteres, indent le suma 5 y translate le resta 1

17. Which of these statements are true? (Choose all that apply.)

```
var letters = new StringBuilder("abcdefg");
```

- A. `letters.substring(1, 2)` returns a single-character `String`.
 - B. `letters.substring(2, 2)` returns a single-character `String`.
 - C. `letters.substring(6, 5)` returns a single-character `String`.
 - D. `letters.substring(6, 6)` returns a single-character `String`.
 - E. `letters.substring(1, 2)` throws an exception.
 - F. `letters.substring(2, 2)` throws an exception.
 - G. `letters.substring(6, 5)` throws an exception.
 - H. `letters.substring(6, 6)` throws an exception.
- devuelve dos caracteres
el índice de inicio nunca puede ser mayor al final

18. What is the result of the following code? (Choose all that apply.)

```
13: String s1 = ""  
14:   purr"";
```

```
15: String s2 = "";
16:
17: s1.toUpperCase();
18: s1.trim();
19: s1.substring(1, 3);
20: s1 += "two";
21:
22: s2 += 2;
23: s2 += 'c';
24: s2 += false;
25:
26: if ( s2 == "2cfalse") System.out.println("==");
27: if ( s2.equals("2cfalse")) System.out.println("equals");
28: System.out.println(s1.length());
```

A. 2

B. 4

C. 7

D. 10

El texto crece a 7 al sumarle two

E. == equals funciona porque compara su contenido y no la memoria

F. equals

G. An exception is thrown.

H. The code does not compile.

19. Which of the following fill in the blank to print a positive integer? (Choose all that apply.)

```
String[] s1 = { "Camel", "Peacock", "Llama"};
String[] s2 = { "Camel", "Llama", "Peacock"};
String[] s3 = { "Camel"};
String[] s4 = { "Camel", null};
System.out.println(Arrays._____);
```

A. compare(s1, s2)

B. mismatch(s1, s2)

C. compare(s3, s4)

D. mismatch (s3, s4)

E. compare(s4, s4)

F. mismatch (s4, s4)

compare y mismatch buscan diferencias alfabéticas o de posición entre dos arreglos

20. Note that March 13, 2022 is the weekend that clocks spring ahead for daylight saving time. What is the output of the following? (Choose all that apply.)

```
var date = LocalDate.of(2022, Month.MARCH, 13);
var time = LocalTime.of(1, 30);
var zone = ZoneId.of("US/Eastern");
var dateTime1 = ZonedDateTime.of(date, time, zone);
var dateTime2 = dateTime1.plus(1, ChronoUnit.HOURS);

long diff = ChronoUnit.HOURS.between(dateTime1, dateTime2);
int hour = dateTime2.getHour();
boolean offset = dateTime1.getOffset()
    == dateTime2.getOffset();
System.out.println("diff = " + diff);
System.out.println("hour = " + hour);
System.out.println("offset = " + offset);
```

- ☒ A. diff = 1
- ☐ B. diff = 2
- ☐ C. hour = 2 El reloj salta la hora 2:00 por el horario de verano, pasando a las 3:30
- ☒ D. hour = 3
- ☐ E. offset = true
- ☐ F. The code does not compile.
- ☐ G. A runtime exception is thrown.

21. Which of the following can fill in the blank to print `avaJ`? (Choose all that apply.)

```
3: var puzzle = new StringBuilder("Java");
4: puzzle._____;
5: System.out.println(puzzle);
```

- ☒ A. `reverse()` reverse volteja el texto directo
en la c se suma letras y borra las
sobrantes
- ☐ B. `append("vaJ$").substring(0, 4)`
- ☒ C. `append("vaJ$").delete(0, 3).deleteCharAt(puzzle.length() - 1)`
- ☐ D. `append("vaJ$").delete(0, 3).deleteCharAt(puzzle.length())`
- ☐ E. None of the above

22. What is the output of the following code?

```
var date = LocalDate.of(2022, Month.APRIL, 30);
date.plusDays(2);
date.plusYears(3);
System.out.println(date.getYear() + " " + date.getMonth()
    + " " + date.getDayOfMonth());
```


A. 2022 APRIL 30

B. 2022 MAY 2

C. 2025 APRIL 2

D. 2025 APRIL 30

E. 2025 MAY 2

F. The code does not compile.

G. A runtime exception is thrown.

Las fechas son inmutables y no se reasigna la variable, la fecha original se imprime intacta

Review Questions

final sirve para atributos, en valores primitivos congela su valor

The answers to the chapter review questions can be found in the Appendix.

1. Which statements about the `final` modifier are correct? (Choose all that apply.)

- ☒ A. Instance and `static` variables can be marked `final`.
- ☒ B. A variable is effectively `final` only if it is marked `final`.
- ☒ C. An object that is marked `final` cannot be modified.
- ☒ D. Local variables cannot be declared with type `var` and the `final` modifier.
- ☒ E. A primitive that is marked `final` cannot be modified.

2. Which of the following can fill in the blank in this code to make it compile? (Choose all that apply.)

```
public class Ant {  
    _____ void method() {}  
}
```

- ☐ A. `default`
- ☒ B. `final`
- ☒ C. `private`
- ☐ D. `Public`
- ☐ E. `String`
- ☐ F. `zzz:`

el `private` o `final` perfectamente pueden estar

3. Which of the following methods compile? (Choose all that apply.)

- ☒ A. `final static void rain() {}`
- ☐ B. `public final int void snow() {}`
- ☐ C. `private void int hail() {}`
- ☒ D. `static final void sleet() {}`
- ☐ E. `void final ice() {}`
- ☐ F. `void public slush() {}`

el orden de los modificadores no importa,
siempre que vayan antes del retorno

4. Which of the following can fill in the blank and allow the code to compile? (Choose all that apply.)

```
final _____ song = 6;
```

- ☒ A. `int`
- ☒ B. `Integer`
- ☒ C. `long`
- ☐ D. `Long`
- ☒ E. `double`
- ☐ F. `Double`

El 6 encaja como entero, largo, doble, o como su clase wrapper `Integer`

5. Which of the following methods compile? (Choose all that apply.)

- ☐ A. `public void january() { return; }`
- ☐ B. `public int february() { return null; }`
- ☐ C. `public void march() { }` los métodos void aceptan un return,
void, y la D devuelve el entero esperado
- ☐ D. `public int april() { return 9; }`
- ☐ E. `public int may() { return 9.0; }`
- ☐ F. `public int june() { return; }`

6. Which of the following methods compile? (Choose all that apply.)

- ☐ A. `public void violin(int... nums) { }` El vargargs ... debe ser estrictamente el último y único
- ☐ B. `public void viola(String values, int... nums) { }`
- ☐ C. `public void cello(int... nums, String values) { }`
- ☐ D. `public void bass(String... values, int... nums) { }`
- ☐ E. `public void flute(String[] values, ...int nums) { }`
- ☐ F. `public void oboe(String[] values, int[] nums) { }`

7. Given the following method, which of the method calls return 2? (Choose all that apply.)

```
public int juggle(boolean b, boolean... b2) {
    return b2.length;
}
```

- ☐ A. `juggle();` Cumplen pasando el primer booleano, luego dos más sueltos y en arreglo
- ☐ B. `juggle(true);`
- ☐ C. `juggle(true, true);`
- ☐ D. `juggle(true, true, true);`
- ☐ E. `juggle(true, {true, true});`
- ☐ F. `juggle(true, new boolean[2]);`

8. Which of the following statements is correct?

- ☐ A. Package access is more lenient than protected access.
- ☐ B. A public class that has private fields and package methods is not visible to classes outside the package.
- ☐ C. You can use access modifiers so only some of the classes in a package see a particular package class.
- ☐ D. You can use access modifiers to allow access to all methods and not any instance variables.
- ☐ E. You can use access modifiers to restrict access to all classes that begin with the word Test.

Los métodos públicos permiten modificar las variables privadas

9. Given the following class definitions, which lines in the `main()` method generate a compiler error? (Choose all that apply.)

// **Classroom.java**

```
package my.school;

public class Classroom {
    private int roomNumber;
    protected static String teacherName;
    static int globalKey = 54321;
    public static int floor = 3;
    Classroom(int r, String t) {
        roomNumber = r;
        teacherName = t; } }
```

// **School.java**

Desde otro paquete, Java prohíbe ver todo lo que no sea explícitamente público

```
1: package my.city;
2: import my.school.*;
3: public class School {
4:     public static void main(String[] args) {
5:         System.out.println(Classroom.globalKey);
6:         Classroom room = new Classroom(101, "Mrs. Anderson");
7:         System.out.println(room.roomNumber);
8:         System.out.println(Classroom.floor);
9:         System.out.println(Classroom.teacherName); } }
```

- A. None: the code compiles fine.
 - B. Line 5
 - C. Line 6
 - D. Line 7
 - E. Line 8
 - F. Line 9
10. What is the output of executing the Chimp program?

// **Rope.java**

```
1: package rope;
2: public class Rope {
3:     public static int LENGTH = 5;
4:     static {
5:         LENGTH = 10;
6:     }
7:     public static void swing() {
```

```
8:      System.out.print("swing ");
9:  } }
```

// Chimp.java

```
1: import rope.*;
2: import static rope.Rope.*;
3: public class Chimp {
4:     public static void main(String[] args) {
5:         Rope.swing();
6:         new Rope().swing();
7:         System.out.println(LENGTH);
8:     } }
```

El bloque estático reemplaza el 5 por un 10,
sí se pueden llamar métodos estáticos desde instancias

- A. swing swing 5
- B. swing swing 10**
- C. Compiler error on line 2 of Chimp
- D. Compiler error on line 5 of Chimp
- E. Compiler error on line 6 of Chimp
- F. Compiler error on line 7 of Chimp

11. Which statements are true of the following code? (Choose all that apply.)

```
1: public class Rope {
2:     public static void swing() {
3:         System.out.print("swing");
4:     }
5:     public void climb() {
6:         System.out.println("climb");
7:     }
8:     public static void play() {
9:         swing();
10:        climb();
11:    }
12:    public static void main(String[] args) {
13:        Rope rope = new Rope();
14:        rope.play();
15:        Rope rope2 = null;
16:        System.out.print("-");
17:        rope2.play();
18:    } }
```

- A. The code compiles as is. Falla porque un método estático no puede llamar a uno normal
- B.** There is exactly one compiler error in the code.
- C. There are exactly two compiler errors in the code.
- D. If the line(s) with compiler errors are removed, the output is swing-climb.
- E.** If the line(s) with compiler errors are removed, the output is swing-swing.
- F. If the line(s) with compile errors are removed, the code throws a NullPointerException.

12. How many variables in the following method are effectively final?

```
10: public void feed() {  
11:     int monkey = 0;  
12:     if(monkey > 0) {  
13:         var giraffe = monkey++;  
14:         String name;  
15:         name = "geoffrey";  
16:     }  
17:     String name = "milly";  
18:     var food = 10;  
19:     while(monkey <= 10) {  
20:         food = 0;  
21:     }  
22:     name = null;  
23: }
```

- A. 1
- B.** 2 Solo giraffe y el primer name nacen y nunca más se modifica su valor
- C. 3
- D. 4
- E. 5
- F. None of the above. The code does not compile.

13. What is the output of the following code?

```
// RopeSwing.java  
import rope.*;  
import static rope.Rope.*;  
public class RopeSwing {  
    private static Rope rope1 = new Rope();  
    private static Rope rope2 = new Rope();  
    {  
        System.out.println(rope1.length);  
    }  
}
```

```
public static void main(String[] args) {  
    rope1.length = 2;  
    rope2.length = 8;  
    System.out.println(rope1.length);  
}  
}
```

// **Rope.java**

```
package rope;  
public class Rope {  
    public static int length = 0;  
}
```

A. 02

B. 08

Como no hay la palabra new, el bloque de instancia se ignora y la variable se queda en 8

C. 2

D. 8

E. The code does not compile.

F. An exception is thrown.

14. How many lines in the following code have compiler errors?

```
1: public class RopeSwing {  
2:     private static final String leftRope;  
3:     private static final String rightRope;  
4:     private static final String bench;  
5:     private static final String name = "name";  
6:     static {  
7:         leftRope = "left";  
8:         rightRope = "right";  
9:     }  
10:    static {  
11:        name = "name";  
12:        rightRope = "right";  
13:    }  
14:    public static void main(String[] args) {  
15:        bench = "bench";  
16:    }  
17: }
```

A. 0

B. 1

- C. 2
- D. 3
- E. 4** Falla porque falta darle valor a bench y sobra darle valor dos veces a name y rightRope
- F. 5

15. Which of the following can replace line 2 to make this code compile? (Choose all that apply.)

```
1: import java.util.*;
2: // INSERT CODE HERE
3: public class Imports {
4:     public void method(ArrayList<String> list) {
5:         sort(list);
6:     }
7: }
```

importar herramientas estáticas, se usa forzosamente import static

- A. import static java.util.Collections;
- B. import static java.util.Collections.*;**
- C. import static java.util.Collections.sort(ArrayList<String>);
- D. static import java.util.Collections;
- E. static import java.util.Collections.*;
- F. static import java.util.Collections.sort(ArrayList<String>);

16. What is the result of the following statements?

```
1: public class Test {
2:     public void print(byte x) {
3:         System.out.print("byte-");
4:     }
5:     public void print(int x) {
6:         System.out.print("int-");
7:     }
8:     public void print(float x) {
9:         System.out.print("float-");
10:    }
11:    public void print(Object x) {
12:        System.out.print("Object-");
13:    }
14:    public static void main(String[] args) {
15:        Test t = new Test();
16:        short s = 123;
17:        t.print(s);
18:        t.print(true);
```

```
19:         t.print(6.789);
20:     }
21: }
```

short entra en int,
pero boolean y double se vuelven objetos genéricos al no tener método exacto

- A. byte-float-Object-
- B. int-float-Object-
- C. byte-Object-float-
- D. int-Object-float-
- E. int-Object-Object-**
- F. byte-Object-Object-

17. What is the result of the following program?

```
1: public class Squares {
2:     public static long square(int x) {
3:         var y = x * (long) x;
4:         x = -1;
5:         return y;
6:     }
7:     public static void main(String[] args) {
8:         var value = 9;
9:         var result = square(value);
10:        System.out.println(value);
11:    } }
```

- A. -1
 - B. 9**
 - C. 81
 - D. Compiler error on line 9
 - E. Compiler error on a different line
- En el metodo se pasa una copia del valor,
así que cambiar la variable por dentro no afecta a la original

18. Which of the following are output by the following code? (Choose all that apply.)

```
public class StringBuilders {
    public static StringBuilder work(StringBuilder a,
        StringBuilder b) {
        a = new StringBuilder("a");
        b.append("b");
        return a;
    }
    public static void main(String[] args) {
        var s1 = new StringBuilder("s1");
        var s2 = new StringBuilder("s2");
```

```
    var s3 = work(s1, s2);  
    System.out.println("s1 = " + s1);  
    System.out.println("s2 = " + s2);  
    System.out.println("s3 = " + s3);  
}  
}
```

- A.** s1 = a
B. s1 = s1
C. s2 = s2
D. s2 = s2b
E. s3 = a
F. The code does not compile.
- Reasignar el original no sirve, pero usar append sí modifica el contenido

19. Which of the following will compile when independently inserted in the following code? (Choose all that apply.)

```
1: public class Order3 {  
2:     final String value1 = "red";  
3:     static String value2 = "blue";  
4:     String value3 = "yellow";  
5:     {  
6:         // CODE SNIPPET 1  
7:     }  
8:     static {  
9:         // CODE SNIPPET 2  
10:    } }
```

Un bloque estático altera solo estáticas
un bloque normal altera ambas, estáticas y de instancia

- A.** Insert at line 6: value1 = "green";
B. Insert at line 6: value2 = "purple";
C. Insert at line 6: value3 = "orange";
D. Insert at line 9: value1 = "magenta";
E. Insert at line 9: value2 = "cyan";
F. Insert at line 9: value3 = "turquoise";

20. Which of the following are true about the following code? (Choose all that apply.)

```
public class Run {  
    static void execute() {  
        System.out.print("1-");  
    }  
    static void execute(int num) {  
        System.out.print("2-");  
    }  
}
```

```
static void execute(Integer num) {  
    System.out.print("3-");  
}  
static void execute(Object num) {  
    System.out.print("4-");  
}  
static void execute(int... nums) {  
    System.out.print("5-");  
}  
public static void main(String[] args) {  
    Run.execute(100);  
    Run.execute(100L);  
}
```

- ☐ A. The code prints out 2-4-.
 - ☐ B. The code prints out 3-4-. 100 busca su método int, y 100L se envuelve como objeto
 - ☐ C. The code prints out 4-2-.
 - ☐ D. The code prints out 4-4-.
 - ☐ E. The code prints 3-4- if you remove the method `static void execute(int num)`.
 - ☐ F. The code prints 4-4- if you remove the method `static void execute(int num)`.
21. Which method signatures are valid overloads of the following method signature? (Choose all that apply.)
- ```
public void moo(int m, int... n)
```
- ☐ A. `public void moo(int a, int... b)`
  - ☐ B. `public int moo(char ch)`
  - ☐ C. `public void moooo(int... z)`
  - ☐ D. `private void moo(int... x)`
  - ☐ E. `public void moooo(int y)`
  - ☐ F. `public void moo(int... c, int d)`
  - ☐ G. `public void moo(int... i, int j...)`

En la sobrecarga lo único que importa es que el tipo de datos de los parámetros cambie