

DAPNET 2.0 Concept and Interface Definition

Ralf Wilke, DH3WR
Thomas Gatzweiler, DL2IC
Phillip Thiel, DL6PT

July 7, 2018

Abstract

This is the concept and interface description of the version 2 of the DAPNET. It's purpose in comparison to the first version released is a more robust clustering and network interaction solution to cope with the special requirements of IP connections over HAMNET which means that all network connections have to be considered with a WAN character resulting in unreliable network connectivity. In terms of consistence of the database, "eventually consistence" is considered to be the most reachable. There are "always right" database nodes inside the so called HAMCLOUD. In case of database conflicts, the version inside the HAMCLOUD cluster is always to be considered right.

Exchanges:

- dapnet.local_calls
- dapnet.calls
- dapnet.telemetry

Figure 1.2: Node Details

1.4 Transmitter Software

1.4.1 Unipager

1.4.2 DAPNET-Proxy

1.5 DAPNET Network

1.5.1 Overview and Concept

1.5.2 Used third-party Software

1.5.3 HAMCLOUD Description

The HAMCLOUD is a virtual server combination of server central services on the HAMNET and provide short hop connectivity to deployed service on HAMNET towards the Internet. There are three data centers at Essen, Nürnberg and Aachen, which have high bandwidth interlinks over the DFN. There are address spaces for uni- and anycast services. How this concept is deployed is still tbd. More information is here https://www.swiss-artg.ch/fileadmin/Dokumente/HAMNET/HamCloud_-_Angebotene_Dienste_in_der_HamCloud.pdf and here <http://hamnetdb.net/?m=as&q=hamcloud>.

Define if uni- or anycast entry points will exist

1.5.4 Rubric Handling Concept

1.5.5 Queuing Priority Concept

Chapter 2

DAPNET Network Definition

2.1 Cluster Description

2.1.1 Real-time Message delivery with RabbitMQ

2.1.2 Distributed Database with CouchDB

2.1.3 Authentication Concept

2.1.4 Integration of new Nodes

2.2 Interface Definition

2.2.1 RabbitMQ Exchange

2.2.2 CouchDB Interface

2.2.3 Core REST API

2.2.4 Statistic and Telemetry REST API

2.2.5 Websocket for real-time updates on configuration, Statistics and Telemetry API

2.2.6 MQTT Fanout for third-party consumers

Chapter 3

Internal Programming Workflows

3.1 Sent calls

3.2 Add, edit, delete User

Show current users

1. Get current status via REST GET to /users on Core URL
2. Handle updates via Websocket

Add and Edit User

1. If edit: Get current status via REST GET to /users/<username> on Core URL
2. Show edit form and place data
3. On save button event, send REST POST to /users/<username> on Core URL

The core will update the CouchDB and generate a RabbitMQ administration message to inform all other nodes. This information is transmitted by the Stats and Websocket Micro-Service to all connected websocket clients to get them updated. This will also happen for the website instance emitting the edit request, so its content is also updated.

Delete User

1. Ask "Are you sure?"
2. If yes, sent REST DELETE to /users/<username> on Core URL

The core will update the CouchDB and generate a RabbitMQ administration message to inform all other nodes. This information is transmitted by the Stats and Websocket Micro-Service to all connected websocket clients to get them updated. This will also happen for the website instance emitting the edit request, so its content is also updated.

3.3 Add, edit, delete Subscriber

3.4 Add, edit, delete Node (tbd)

3.5 Add, edit, delete Transmitter

3.6 Implementation of Transmitter Groups

3.7 Add, edit, delete Rubrics

Show current configuration

1. Get current status via REST GET to /rubrics on Core URL
2. Handle updates via websocket

Add and Edit rubrics

1. If edit: Get current status via REST GET to /rubrics/<rubricname> on Core URL
2. Show edit form and place data
3. On save button event, send REST POST to /users/<rubricname> on Core URL

The core will update the CouchDB and generate a RabbitMQ administration message to inform all other nodes. This information is transmitted by the Stats and Websocket Micro-Service to all connected websocket clients to get them updated. This will also happen for the website instance emitting the edit request, so its content is also updated.

Delete rubric

1. Ask "Are you sure?"
2. If yes, sent REST DELETE to /users/<rubricname> on Core URL

The core will update the CouchDB and generate a RabbitMQ administration message to inform all other nodes. This information is transmitted by the Stats and Websocket Micro-Service to all connected websocket clients to get them updated. This will also happen for the website instance emitting the edit request, so its content is also updated.

3.8 Add, edit, delete Rubrics content

3.9 Add, edit, delete, assign Rubrics to Transmitter/-Groups

3.10 Ports and Loadbalacing Concept

3.11 Periodic Tasks (Scheduler)

3.12 Plugin Interface

3.13 Transmitter Connection

Transmitter connections consist of two connections to a Node. A REST connection for initial announcement of a new transmitter, heartbeat messages and transmitter configuration and a RabbitMQ connection to receive the data to be transmitted.

The workflow for a transmitter connection is the following:

1. Announce new connecting transmitter via Core REST Interface ([6.1.1](#)).
2. Get as response the transmitter configuration or an error message ([6.1.2](#)).
3. Initiate RabbitMQ connection to get the data to be transmitted ([6.2.1](#)).

The authentication of the transmitter's REST calls consist of the transmitter name and its AuthKey, which is checked against the value in the CouchDB for this transmitter.

3.14 Transmitter connections

If a transmitter wants to connect to DAPNET, the first step is to sign-in and show it's presence via the Core REST interface. This interface is also used for transmitter configuration like enabled timeslots and keep-alive polling.

3.14.1 Authentication of all HTTP-Requests in this context

All HTTP-requests issued from a transmitter have to send a valid HTTP authentication, which is checked against the CouchDB. It consists of the transmitter name and its AuthKey.

3.15 DAPNET-Proxy

Chapter 4

External Usage Workflows

4.1 General Concept of REST and Websocket-Updates

4.2 Website and App

4.2.1 Authentication

4.2.2 Calls

4.2.3 Rubrics

4.2.4 Rubrics content

4.2.5 Transmitters and Telemetry

4.2.6 Nodes

4.2.7 Users

4.2.8 MQTT consumers

4.2.9 Scripts and automated Software for DAPNET-Input

Chapter 5

Setup and Installation

5.1 Unipager

5.2 DAPNET-Proxy

5.3 DAPNET Core

5.4 Special issues for Core running in HAMCLOUD

Chapter 6

Protocol Definitions

6.1 Core REST API

6.1.1 Transmitter sign-on, configuration and heartbeat

POST /transmitter/bootstrap

```
{
  "callsign": "db0avr",
  "auth_key": "<secret>",
  "software": {
    "name": "UniPager",
    "version": "1.0.2"
  }
}
```

6.1.2 Answers to the bootstrap REST call

200 OK

```
{
  "timeslots": [true, true, false, true, ...],
  "nodes": [
    {
      "host": "node1.ampr.org",
      "port": 4000,
      "reachable": true,
      "last_seen": "2018-07-03T07:43:52.783611Z",
      "response_time": 42
    }
  ]
}
```

423 Locked

```
{
  "error": "Transmitter temporarily disabled by config."
}
```

423 Locked

```
{
  "error": "Transmitter software type not allowed due to serious bug."
}
```

6.1.3 Transmitter Heartbeat

POST /transmitter/heartbeat

```
{
  "callsign": "db0avr",
  "auth_key": "<secret>",
  "ntp_synced": true
}
```

Answers to the heartbeat REST call

200 OK

```
{
  "status": "ok"
}
```

If network wants to assign new timeslots without disconnecting (for dynamic timeslots)

200 OK

```
{
  "status": "ok",
  "timeslots": [true, true, false, ...],
  "valid_from": "2018-07-03T08:00:52.786458Z"
}
```

If network wants to initiate handover to other node

503 Service unavailable

```
{
  "error": "Node not available, switch to other node."
}
```

6.2 RabbitMQ

There are 3 exchanges on each RabbitMQ instance available:

1. dapnet.calls: Messages coming from other nodes but the node where the instance is running
2. dapnet.local_calls: Messages coming from the local node instance
3. dapnet.telemetry: Messages containing telemetry from transmitters

6.2.1 Transmitters

Valid Messages are:

dapnet.calls

The messages to transfer data to be transmitted by the Transmitter has the following format. For each transmission, there is a separate RabbitMQ message, as different receivers might need different text encoding. All encoding is already done, when this message is created. The transmitter does no character encoding at all. Both personal pagings and rubric related messages are transmitted with this protocol.

```
{
  "pagingcall" : {
    "ric" : 12342,
    "subric" : 0 to 3,
    "speed" : 1200,
    "type" : "POCSAG",
    "priority" : 3,
    "message" : "ahdjkahskl"
  }
}
```

The selection of the transmitter is done by means of the routing key. Besides, the priority is also used in the RabbitMQ queuing to deliver higher priority messages first.

dapnet.local_calls

Same as for the the network originated calls in section 6.2.1.

6.2.2 Telemetry

On the telemetry exchange, all transmitters publish their telemetry messages. The format the same as in section 6.3.

6.2.3 MQTT API for third-party consumers

In order to allow third-party instances like , or others to get the emitted calls and rubric contents in a real time event driven way, there is an MQTT API. It is not implemented via a dedicated MQTT broker, but uses the existing RabbitMQ instance (<https://www.rabbitmq.com/mqtt.html>). There is no distribution of the messages via this MQTT broker; it is local only. So ever node publishes the messages locally on its own. Each subscriber has an array of enabled third-party applications. This allow to define the user, if call directed to her/his subscriber shall be also sent to third-party services (see 6.6.4.

The currently existing MQTT topics are defined in the CouchDB (see section 6.6.8). This makes it possible to add more third-party services and authorized users during runtime without the need to update the software. The valid users to subscribe to the topic are also listed in the same CouchDB database.

The only permitted access for third-party consumers is read. So the subscribe request from a third-party MQTT-Client must use authentication which is checks against the CouchDB data. If correct, read access is granted.

The encoding of the data is UTF-8.

The format of the data published for **personal paging calls** is

```
{
  "pagingcall" : {
    "callsign" : "dh3wr",
    "priority" : 3,
    "message" : "DAPNET 2.0 rocks dear YL/OM"
  }
}
```

The format of the data published for **rubric_content paging calls** is

```
{
  "rubricmessage" : {
    ???
    "message" : ""
  }
}
```

6.3 Telemetry

Telemetry is sent from transmitters to the RabbitMQ exchange **dapnet.telemetry** as defined in section 6.2. It is also used in the same way on the websocket API to inform the website and the app about the telemetry in real-time in section ??.

This is sent every minute in complete. If there are changes, just a subset is sent. The ñamekey is always mandatory.

```
{
  "name": "db0acb",
  "OnAir" : true,
  "Telemetry" : {
    "ConnectionStatus": {
      "Connected" : true,
      "ConnectedtoNodeName" : "db0xyz"
    }
  }
}
```

```

    "ConnectedtoNodeIP" : "1.2.3.4"
    "ConnectedtoNodePort" : 1234
    "ConnectedSince" : "<timestamp-format>",
        "NTPSynced" : true,
    "NTPOffsetMilliseconds" : 124
    "NTPServerUsedIP" : ["134.130.4.1", "12.2.3.2"]
},
    "QueueStatus" : {
        "QueuedMessages" : {
            "Total" : 1234,
            "Prio1" : 1234,
            "Prio2" : 1234,
            "Prio3" : 1234,
            "Prio4" : 1234,
            "Prio5" : 1234,
            "Prio10" : 1234
        }
    },
    "PrefinedTemperatures" : {
        "Unit" : "C" | "F" | "K",

        "AirInlet" : 12.2,
        "AirOutlet" : 14.2,
        "Transmitter" : 42.2,
        "PowerAmplifier" : 45.2,
        "CPU" : 93.2,
        "PowerSupply" : 32.4
    },
    "CustomTemperatures" : {
        "Unit" : "C" | "F" | "K",
        [
            {"Value" : 12.2, "Description" : "Aircon Inlet"},
            {"Value" : 16.2, "Description" : "Aircon Outlet"},
            {"Value" : 12.3, "Description" : "Fridge Next to Programmer"}
        ],
    },
    "PowerSupply" : {
        "OnBattery" : false,
        "OnEmergencyPower" : false,
        "DCInputVoltage" : 12.4,
        "DCInputCurrent" : 3.23
    },
    "RFOutput" : {
        "OutputPowerForwardinWatts" : 12.2,
        "OutputPowerReturninWatts" : 12.2,
        "OutputVSWR" : 1.2
    }
}
"transmitterconfiguration" : {
    "ConfiguredIP" : "123.4.3.2",
    "timeslots" : [true, false, ..., false],
    "SoftwareType" : "Unipager" | "MMDVM" | "DAPNET-Proxy",
    "SoftwareVersion" : "v1.2.3", | "20180504" | "v2.3.4",
    "CPULHardwareType" : "Raspberry Pi 3B+"
    "RFHardware" : {
        "C9000" : {
            "UnipagerPowered" : true,
            "ArduinoPADummy" : true,
            "ArduinoPADummySettinginWatts" : 123,
            "ArduinoPADummyPort" : "/devttyUSB0"

            "RPC-CardPowered" : false,
            "RPC-Version" : "X0S/2.23pre",
        },
    },
    "Raspager" : {
        "RaspagerMod" : 13,
        "RaspagerPower" : 63,
        "ExternalPowerAmplifier" : false,
        "RaspagerRFVersion" : "V2"
    },
    "Audio" : {
        "TXModel" : ["GM1200", "T7F", "GM340", "FREITEXT"],
        "AudioLevelUnipager" : 83,
        "TxDelayinMilliseconds" : 3
    }
}

```

or

```

    },
    "RFM69" : {
        "Port" : "/dev/ttyUSB0"
    },
    "MMDVM_DualHS..." : {
        "DAPNETExclusive" : true
    }
},
"DAPNET_Proxy" : {
    "ConnectionStatus" : "connected",
    "ConnectionStatus" : "connecting",
    "ConnectionStatus" : "disconnected"
}
}
}

```

6.4 Statistic and Telemetry REST API

6.5 Websocket API

The idea is to provide an API for the website and the app to display real-time information without the need of polling. A websocket server is listing to websocket connections. Authentication is done by a custom JOSN handshake. The connection might be encrypted with SSL if using the Internet or plain if using HAMNET.

6.5.1 Telemetry

URL: `ws://FQDN/telemetry`. The data is the same as received from the `dapnet.telemetry` exchange from the RabbitMQ instance. It is defined in section 6.3.

6.5.2 Database Changes

URL: `ws://FQDN/database_changes`. To inform the website or the app about changes in the CouchDB database, the websocket microservice keeps a connection to the local CouchDB API and receives a stream of updates to the database. As there may be data in the changes that are confidential, the stream is parsed and sent out in a reduced form to the websocket client. Further information: <http://docs.couchdb.org/en/2.0.0/api/database/changes.html>

6.6 CouchDB Documents and Structure

6.6.1 Users

Genaues
Format
der Aus-
gaben
definieren

als
Tabelle
darstellen

Table 6.1: CouchDB: Users			
Key	Value-Type	Valid Value Range	Example
<code>_id</code>	STRING	N/A	dl1abc
<code>password</code>	Bcrypt with rand. salt	N/A	??
<code>admin</code>	boolean	true/false	true
<code>enabled</code>	boolean	true/false	true
<code>created_on</code>	DATEIME		??
<code>last_change_by</code>	STING	valid user name	dh3wr
<code>email_valid</code>	boolean	true/false	true
<code>avatar_picture</code>	couchdb_attachment		

```
{
  "_id": "dl1abc",
  "password": "some hash",
  "email": "user@example.com",
  "admin": true,
  "enabled": true,
  "created_on": <DATETIME>,
  "last_change_by": "dh3wr",
  "email_valid": true
  "avatar_picture": <couchdb attachment??>
}
```

6.6.2 Nodes

Table 6.2: CouchDB: Nodes

Key	Value-Type	Valid Value Range	Example
_id	STRING	N/A	db0abc
status	ENUM/STRING	OFFLINE ONLINE ERROR	ONLINE
version	STRING	???	1.2.3
ip_address	IPv4/STRING		1.2.3.4
latitude	decimal number, 6 dec. digits	-90 ... 90	34.123456
longitude	decimal number, 6 dec. digits	-180 ... 180	34.123456
hamcloudnode	boolean	true/false	true
owners	ARRAY of STRING	N/A	["dl1abc", "dh3wr", "dl2ic"]
avatar_picture	couchdb_attachment		

```
{
  "_id" : "db0abc",
  "status" : "OFFLINE" | "ONLINE" | "ERROR",
  "last_update" : DATETIME,
  "version" : "1.2.3",
  "ip_address" : "1.2.3.4",
  "latitude" : 34.123456,
  "longitude" : -23.123456,
  "hamcloudnode" : true,
  "owners" : ["dl1abc", "dh3wr", "dl2ic"],
  "avatar_picture": <couchdb attachment??>
}
```

6.6.3 Transmitters

```
{
  "_id" : "db0abc",
  "auth_key" : "hdjaskhdlj",
  "enabled" : true,
  "status" : "UNKNOWN" | "OFFLINE" | "ONLINE",
  "site_type" : "PERSONAL" | "WIDERANGE",
  "aprs_reporting_enabled" : true,
  "last_update" : "<DATETIME>",
  "last_connect" : "<DATETIME>",
  "ip_address" : "1.2.3.4",
  "device_type" : "Unipager",
  "device_version" : "1.3.2",
  "latitude" : 23.123456,
  "longitude" : -31.123456
  "rf_power_watt": 12.3,
  "cable_loss_db" : 4.2,
  "antenna_gain_dbi" : 2.34,
  "antenna_agl_m" : 23.4,
  "antenna_type" : "OMNI" | "DIRECTIONAL",
  "antenna_direction" : 123.2,
  "owners" : ["dl1abc", "dh3wr", "dl2ic"],
  "groups" : ["dl-hh", "dl-all"],
}
```

Tabelle
weiter
machen

Table 6.3: CouchDB: Transmitters

Key	Value-Type	Valid Value Range	
<code>_id</code>	STRING	N/A	
<code>auth_key</code>	STRING	N/A	asd:
<code>enabled</code>	boolean	true/false	
<code>status</code>	ENUM/STRING	OFFLINE ONLINE UNKNOWN	
<code>site_type</code>	ENUM/STRING	PERSONAL WIDERANGE	WID
<code>aprs_reporting_enabled</code>	boolean	true/false	
<code>last_update</code>	DATETIME		
<code>last_connect</code>	DATETIME		
<code>ip_address</code>	IPv4/STRING		
<code>device_type</code>	STRING	Unipager DAPNET-Proxy	
<code>device_version</code>	STRING	???	
<code>latitude</code>	decimal number, 6 dec. digits	-90 ... 90	
<code>longitude</code>	decimal number, 6 dec. digits	-180 ... 180	
<code>rf_power_watt</code>	decimal number, 3 dec. digits	0.001 ...	
<code>owners</code>	ARRAY of STRING	N/A	["dl1abc","dh3wr"]
<code>avatar_picture</code>	couchdb_attachment		

```

"frequency_MHz" : 439.9875,
"emergency_power_available" : false,
"infinite_emergency_power" : false,
  "emergency_power_duration_hours" : 23.0
"antenna_pattern" : <couchDB attachment>,
"avatar_picture" : <couchDB attachment>
}

```

6.6.4 Subscribers

```

{
  "_id" : "dl1abc",
  "description" : "Peter",
  "pagers" : [
    {
      "ric" : {123456, "A"} ... "ric" : {123456, "D"},

      "uuid" : "0023-1233-aefe-1234-3423-9812",
      "name" : "Peters Alphapoc",

      "type" : "UNKNOWN" | "Skyper" | "AlphaPoc" | "QUIX" | "Swissphone" | "SCALL_

      "is_enabled" : true
    },
    ...
  ],
  "enabled_third_party_services" : ["APRS", "BM"],
  "owner" : ["dh3wr", "dl1abc"]
}

```

check if
[] is valid
JSON

6.6.5 Subscriber Groups

```

{
  "_id" : "ov-G01",
  "description" : "Ortverband Aachen",
  "member_subscribers" : ["dl1abc", "dh3wr"],
  "owner" : ["dh3wr", "dl1abc"],
}

```

6.6.6 Rubrics List

```

{
  "uuid" : "<UUID>"
  "number" : 14,
  "description" : "Wetter DL-HH",
  "label" : "WX DL-HH",
  "transmitter_groups" : ["dl-hh","dl-ns"],
  "transmitters" : ["db0abc"],
    "cyclic_transmit_enabled" : true,
  "cyclic_transmit_interval_minutes": 123,
  "owner" : ["dh3wr", "dl1abc"]
}

```

6.6.7 Rubric's content

<UUID> of rubric (as defined in [6.6.6](#))

```

{
  "uuid" : "<UUID>",
  ["content_message1",...,"content_message10"],
}

```

6.6.8 MQTT services and subscribers

```

{
  "_id" : "APRS",
  "mqtt_topic_name" : "aprs"
  "allowed_subscribers" : [
    {
      "name" : "example",
      "password" : "<bcrypt hash>"
    },
    ...
  ]
}

```