Reference   Language (//www.arduino.cc/en/Reference/HomePage) | Libraries
(//www.arduino.cc/en/Reference/Libraries) | Comparison
(//www.arduino.cc/en/Reference/Comparison) | Changes
(//www.arduino.cc/en/Reference/Changes)

Wire.available()

Description

Returns the number of bytes available for retrieval with read()
(//www.arduino.cc/en/Reference/WireRead). This should be called on a master device after a call to
requestFrom() (//www.arduino.cc/en/Reference/WireRequestFrom) or on a slave inside the
onReceive() (//www.arduino.cc/en/Reference/WireOnReceive) handler.

available() inherits from the Stream (//www.arduino.cc/en/Reference/Stream) utility class.

Parameters

None

Returns

The number of bytes available for reading.

See Also

- Wire.read() (//www.arduino.cc/en/Reference/WireRead)

- Stream.available (//www.arduino.cc/en/Reference/StreamAvailable)()

  Reference Home (//www.arduino.cc/en/Reference/HomePage)

*Corrections, suggestions, and new documentation should be posted to the Forum
(http://arduino.cc/forum/index.php/board,23.0.html).*

The text of the Arduino reference is licensed under a Creative Commons Attribution-ShareAlike 3.0
License (http://creativecommons.org/licenses/by-sa/3.0/). Code samples in the reference are
released into the public domain.

Share