

Gradient boosting

Vladislav Goncharenko

ML Teamlead, DZEN



MSU, spring 2024

Outline

1. Intuitions
2. Gradient boosting theory
3. Examples
4. Libraries
5. Feature importances
6. Hyperparameter optimization

Ensembling recap


girafe
ai

00

Random Forest



Bagging + RSM = Random Forest




Random Forest



- One of the greatest “universal” models
- There are some modifications: Extremely Randomized Trees, Isolation Forest, etc.

Bias-variance tradeoff



Boosting intuition


girafe
ai

01

Boosting



$$a_n(x) = h_1(x) + \dots + h_n(x)$$





* in case of MSE loss

Boosting: intuition

Binary classification

Use decision stumps





$t = 1$





Boosting: intuition

Binary classification



Use decision stumps.




$t = 1$



$t = 2$



$t = 3$





Boosting: intuition




Binary classification

Use decision stumps.



$$\hat{f}_T(x) = \sum_{t=1}^T \rho_t h_t(x) =$$



Gradient boosting theory

girafe
ai

02

Gradient boosting: theory



Denote dataset $\{(x_i, y_i)\}_{i=1, \dots, n}$, loss function $L(y, f)$

Optimal model:

$$\hat{f}(x) = \arg \min_{f(x)} L(y, f(x)) = \arg \min_{f(x)} \mathbb{E}_{x,y}[L(y, f(x))]$$

Let it be from parametric family:

$$\begin{aligned}\hat{f}(x) &= f(x, \hat{\theta}), \\ \hat{\theta} &= \arg \min_{\theta} \mathbb{E}_{x,y}[L(y, f(x, \theta))]\end{aligned}$$



Gradient boosting: theory


$$\hat{f}(x) = \sum_{i=0}^{t-1} \hat{f}_i(x),$$

$$(\rho_t, \theta_t) = \arg \min_{\rho, \theta} \mathbb{E}_{x,y} [L(y, \hat{f}(x) + \rho \cdot h(x, \theta))],$$

$$\hat{f}_t(x) = \rho_t \cdot h(x, \theta_t)$$

What if we could use gradient descent in space of our models?

Gradient boosting: theory



What if we could use gradient descent in space of our models?



Gradient boosting: theory

$$\hat{f}(x) = \sum_{i=0}^{t-1} \hat{f}_i(x),$$

$$r_{it} = - \left[\frac{\partial L(y_i, f(x_i))}{\partial f(x_i)} \right]_{f(x)=\hat{f}(x)}, \quad \text{for } i = 1, \dots, n,$$

$$\theta_t = \arg \min_{\theta} \sum_{i=1}^n (r_{it} - h(x_i, \theta))^2,$$

$$\rho_t = \arg \min_{\rho} \sum_{i=1}^n L(y_i, \hat{f}(x_i) + \rho \cdot h(x_i, \theta_t))$$

Gradient boosting: theory



In linear regression case with MSE loss:


$$r_{it} = - \left[\frac{\partial L(y_i, f(x_i))}{\partial f(x_i)} \right]_{f(x)=\hat{f}(x)} = -2(\hat{y}_i - y_i) \propto \hat{y}_i - y_i$$

GB examples


girafe
ai

03

Beautiful demo



One tree



Boosting

Gradient boosting



What we need:

- Data
- Loss function and its gradient
- Family of algorithms (with constraints if necessary)
- Number of iterations M
- Initial value (GBM by Friedman): constant





Gradient boosting: example

What we need:

- Data: toy dataset $y = \cos(x) + \epsilon, \epsilon \sim \mathcal{N}(0, \frac{1}{5}), x \in [-5, 5]$
- Loss function: MSE
- Family of algorithms: decision trees with depth 2
- Number of iterations $M = 3$
- Initial value: just mean value



Gradient boosting: example





Left: full ensemble on each step.

Right: additional tree decisions.





Gradient boosting: example




Left: full ensemble on each step.




Right: additional tree decisions



Spam Data





California Housing Data



Boosting with linear classification methods



$t = 40$



Parallelization



Which of the ensembling methods could be parallelized?

- Random Forest: parallel on the forest level (all trees are independent)
- Gradient boosting: parallel on one tree level

Libraries for GB

girafe
ai

04

Main contemporary instruments



1. Catboost by Yandex
2. LightGBM by Microsoft
3. XGboost by community

Definitely not sklearn!



More on boosting

- <https://habr.com/ru/companies/ods/articles/645887/>
- <https://neptune.ai/blog/when-to-choose-catboost-over-xgboost-or-lightgbm>
- <https://towardsdatascience.com/catboost-vs-lightgbm-vs-xgboost-c80f40662924>
- <https://www.springboard.com/blog/data-science/xgboost-random-forest-catboost-lightgbm/>
- <https://towardsdatascience.com/performance-comparison-catboost-vs-xgboost-and-catboost-vs-lightgbm-886c1c96db64>

Feature importances


girafe
ai

05


Shap values



SHAP



Explanation




Hyperparameter optimization

girafe
ai

06

Black box or 0 order optimization



<https://optuna.org/> and <http://hyperopt.github.io/hyperopt/>

Revise



1. Intuitions
2. Gradient boosting theory
3. Examples
4. Libraries
5. Feature importances
6. Hyperparameter optimization

Thanks for attention!

Questions?



girafe
ai

