

1 Our First Java Program

Below is our first Java program of the semester. Next to each line, write out what you think the code will do when run. If you think the line will result in an error, correct it, and proceed through the code as if it is running your corrected version.

This exercise is adapted from Head First Java.

```
1  size = 27;  int
2  name = "Fido"; String
3  Dog myDog = new Dog(name, size);
4  Dog yourDog = new Dog("Scruffy", 1000);
5  Dog[] dogList = new Dog[3];
6  dogList[0] = myDog;
7  dogList[1] = yourDog;
8  dogList[2] = 5; X = new Dog(name, 5)
9  dogList[3] = new Dog("Cutie", 8) X 越界
10 int x;
11 x = size - 5;
12 if (x < 15) {
13     myDog.bark(8);
14 }
```

2 Mystery

This is a function (a.k.a. method). It takes an array of integers and an integer as arguments, and returns an integer.

```

1 public static int mystery(int[] inputArray, int k) {
2     int x = inputArray[k];
3     int answer = k;
4     int index = k + 1;
5     while (index < inputArray.length) {
6         if (inputArray[index] < x) {
7             x = inputArray[index];
8             answer = index;
9         }
10        index = index + 1;
11    }
12    return answer;
13 }
```

(a) Describe what mystery returns if `inputArray = [3, 0, 4, 6, 3]` and `k = 2`.

(b) Can you explain in plain English what mystery does?

找到从k位置到末尾的最小值的下标

Extra: This is another function. It takes an array of integers and returns nothing.

```

1 public static void mystery2(int[] inputArray) {
2     int index = 0;
3     while (index < inputArray.length) {
4         int targetIndex = mystery(inputArray, index);
5         int temp = inputArray[targetIndex];
6         inputArray[targetIndex] = inputArray[index];
7         inputArray[index] = temp;
8         index = index + 1;
9     }
10 }
```

Describe what mystery2 does if `inputArray = [3, 0, 4, 6, 3]`.

0 3 4 6 3
0 3 3 6 4
0 3 3 4 6

3 Writing Your First Program

Implement `fib` which takes in an integer `n` and returns the n th Fibonacci number. You may not need to use all the lines.

The Fibonacci sequence is 0, 1, 1, 2, 3, 5, 8, 13, 21, ... The first two numbers in the sequence are 0 and 1, and every number thereafter it is the sum of the two numbers in the sequence before it.

```
public static int fib(int n) {
```

```
    if(n==1) return 0;
    if(n==2) return 1;
    n-=2
    int a=0, b=1, res=0
    while(n>0) {
        res = a+b
        a=b
        b=res
        n--
    }
    return res
}
```

```
if (n <= 1)
    return n
else
    return fib(n-1) + fib(n-2)
```

Extra: Implement a more efficient version of `fib` in 5 lines or fewer. Here, efficiency might mean making less recursive calls or doing less overall computation. You don't have to make use of the parameter `k` in your solution.

```
public static int fib2(int n, int k, int f0, int f1) {
```

```
    if(n==1) return f0
    if(n==2) return f1
    return fib2(n, k, f0, f1) + fib2(n-2, f0, f1)
    _____
    _____
}
```

```
if(n==k)
    return f0
else
    return fib2(n, k+1, f1,
                f0+f1)
```