

ABRT Project Document

Karel Klíč

March 29, 2012

This is a top-level project document for ABRT.

TODO: What is ABRT doing.

TODO: Purpose of ABRT.

Contents

1	Project Charter	3
1.1	Statement of Work	3
1.2	Business case	3
1.2.1	Related Work	3
2	Stakeholders	5
3	Requirements	5
4	Scope	6
5	Work breakdown structure	6
5.1	ABRT Server Overview	6
5.2	ABRT Server Services Overview	8
5.3	ABRT Server Storage Overview	9
5.4	ABRT Server Interface Overview	11
5.4.1	Summary Page	12
5.4.2	Problems Overview Page	13
5.4.3	Problems Item Summary Page	14
5.4.4	Reports Overview Page	15
5.4.5	Reports List Page	16
5.4.6	Server Tasks Page	16
5.4.7	Server Status Page	17
5.5	ABRT Client Overview	18
5.6	ABRT Client Interface Overview	19
5.6.1	Apology Dialog	19
5.6.2	Detailed Report Dialog	20
5.6.3	Applet	21
5.6.4	Problem Browser	21
5.7	Implementation Phases	21
5.7.1	Already Implemented Components	21
5.7.2	Phase 1	21
5.7.3	Phase 2	21
6	Project Time Management	21
6.1	Activity List	21
7	Project Quality Management	22
8	Project Risk Management	22
9	Project Management Plan	22

1 Project Charter

1.1 Statement of Work

business need, product scope, strategic plan

1.2 Business case

1.2.1 Related Work

There are several existing implementations of problem management systems.

TODO: [4].

Jon McCann of GNOME team envisioned a problem reporting architecture[3] that splits the responsibilities of a problem management system into several components:

1. *System Logger* collects data for anomalous behavior of system such as crash dumps and SELinux access denial logs. It is proposed to include this functionality into **systemd**, a system and service manager for Linux. In internal communication, Jon also proposed to stop using core dumps in favor of minidumps.
2. *Problem Detector* watches the output of System Logger for new events, and runs Report Generator on every new event. Its name should be **problem**d, and this tool is not implemented yet.
3. *Report Generator* gathers supplementary details about a problem, and stores problem data to a non-volatile memory. It should be handled by either **systemd** or **problem**d.
4. *User Problem Notifier* notifies user about a problem. Jon proposes to include this functionality into **gnome-settings-daemon**.
5. *Reporting Mechanism* delivers problem report to a Collection Server, scp, ftp, email...
6. *Problem Reporting and Review* shows problem reports of a system, and allows report submission. Jon designed *Oops!*[1], a graphical user interface for such a component.
7. *Problem Report Collection Server* accepts anonymous submissions, supports filling reports to Bugzilla, scrubs sensitive data from reports, detects duplicates, performs coredump analysis and retracing (generating backtrace from coredump). In internal communication, GNOME team proposes using Socorro, a crash statistics server project of Mozilla, in this role.

Advantages and good aspects of the proposal

1. The idea of pushing generic code to packages that are being used across distributions. Coredump catching can definitely be done by **systemd**. *Problem Detector* and *Report Generator* can also be made portable and shareable across distributions, and it could live in <http://freedesktop.org> as **problem**d.
2. The design of *Oops!*.

Criticism of the proposal

The most important point that should be re-evaluated is the proposed direction of *statistics-based* problem management and bugfixing. This includes the usage of minidumps in all situations, and the deployment of Socorro.

Data from the current problem management system shows that statistics-based bugfixing misfits the operating system level use case (management of full stack of applications). Statistics-based bugfixing is based on the assumption of large amounts of users hitting and reporting the same crash. This assumption is valid for desktop applications, which are quickly changing, contain large amount of bugs (GUI code is difficult to handle well), and have large amount of users (desktop shell, internet browser, e-mail client). Nevertheless, this assumption is *invalid* for most of operating system packages, including server-side software.




Figure 1: Cumulative distribution of ABRT bugs and reports per component





Figure 2: Distribution of ABRT bugs and reports per component

Many packages are used by relatively low number of people, customized and deployed just on a few servers. Crashes in this situation are less frequent, but dangerous.

1. Implementing *User Problem Notifier* into `gnome-settings-daemon` brings the requirement to implement the same functionality for other desktops as well (KDE, XFCE).
2. *Oops!* design is incomplete. It is not clear how the reporting target can be configured (problem report collection server URL, e-mail, FTP, SCP destinations). The window with report details is not presented.

2 Stakeholders

Here is a list of people impacted by the project, and relevant information regarding their interests, involvement.



Stakeholder register

Stakeholder management strategy

3 Requirements


Requirements documentation Requirements management plan Requirements traceability matrix

4 Scope

5 Work breakdown structure

Deliverable oriented decomposition of server project into smaller components.

5.1 ABRT Server Overview



Storage Server's storage is a combination of a database and a file server.

Storage Synchronization Fetches data from external systems, such as RPMs and builds from Koji, bugs, comments, attachments from Red Hat Bugzilla, components, maintainers, releases from Fedora Package Database.

Problem Storage We store all issues reported by users here. Problems can be program crashes, uncaught Python exceptions, Kernel oopses, VM cores, and SELinux denials.

Data Storage We download and store RPMs of all versions of all packages in operating system. This is necessary for correct retracing of both coredumps and minidumps. We require both binaries and debugging information. Static analysis requires data files from RPMs for greater accuracy.

Sanity Checker We measure quality of data (builds, RPMs, bugs) downloaded from Fedora Project. We found quality measurement and defect detection to be necessary to keep any service operational. For example, many packages in Fedora and RHEL lacked proper debugging information, and this issue blocked retracing of many coredumps. We started to track the quality of debugging information and watch for regressions.

Services Separate services working on the top of Problem Storage and Data Storage. They are triggered by creating a new issue, changing the state of the issue, or at a certain time interval.

Retracing Generates full backtrace from a coredump stored in Problem Storage. Generates function names from a minidump (coredump-level backtrace) stored in Problem Storage.

Crash Data Analysis Depends on Retracing.

Anonymization Depends on Crash Data Analysis.

LLVM Depends on Anonymization.

Deduplication Deduplication happens on several levels: minidumps (coredump-level backtraces) are compared when receiving a new issue. Backtraces and/or function names (we call the list of function names from the crash thread *optimized backtrace* in Faf) are compared when Retracing step is done. Analyzed issues are compared when the Crash Type Specific Analysis is done.

Clustering Clustering finds clusters of issues that are close (similar) to each other. Clusters are created from multiple distances. They are used to determine possible components and even program functions that are the root cause of the bug.

Reporting

Analysis Based on static analysis techniques applied to LLVM bitcode, the Analysis framework investigates reported issues and provide insight at the source code level.

Crash Type Specific Analysis

Security Analysis

SELinux Analysis

Interface World-facing communication is implemented in the web-based Human Interface, and JSON-based Machine Interface. Internal interactions between server parts are organized as tasks performed by workers. Task queue is managed by central hub, which also provides the public communication interfaces.


Human Interface

Machine Interface


Central Hub

Tasks and Workers

5.2 ABRT Server Services Overview



5.3 ABRT Server Storage Overview



problem history monthly
month : DATE operating system id : FOREIGN KEY problem id : FOREIGN KEY count : INT

problem history weekly
week : DATE operating system id : FOREIGN KEY problem id : FOREIGN KEY count : INT

problem history daily
day : DATE operating system id : FOREIGN KEY problem id : FOREIGN KEY count : INT

problem coredump
id : PRIMARY KEY problem id : FOREIGN KEY operating system id : FOREIGN KEY

problem backtrace
id : PRIMARY KEY problem id : FOREIGN KEY operating system id : FOREIGN KEY text : STRING

problem binary
id : PRIMARY KEY path : STRING count : INT

problem package
problem id : FOREIGN KEY package id : FOREIGN KEY count : INT

problem
id : PRIMARY KEY AUTOINCREMENT type : ENUM (USERSPACE, KERNEL, PYTHON, SELINUX) first occurence : TIMESTAMP last occurence : TIMESTAMP


problem fingerprint record
fingerprint id : FOREIGN KEY order : INT symbol id : FOREIGN KEY

problem fingerprint
id : PRIMARY KEY AUTOINCREMENT problem id : FOREIGN KEY

problem fingerprint symbol
id : PRIMARY KEY name : STRING normalized source : STRING NOT NULL full source : STRING NOT NULL

problem fingerprint symbol hash
symbol id : FOREIGN KEY hash : STRING NOT NULL build id : STRING NOT NULL offset : INT NOT NULL source file : STRING line number : INT

5.4 ABRT Server Interface Overview



5.4.1 Summary Page

[login](#)

Fedora Problem Tracker

search for problem

Summary

Problems

Reports

Tasks

Status

Operating System:

Fedora 16

▼


All Components

▼

days

weeks

months



New and noteworthy

2012-03-18

GNOME Desktop become unstable in Fedora Rawhide since the last week. The average number of crashes in 5 weeks before that was 10 crashes/week. In the last week it is 86 crashes/week.

Emacs become stable 3 days ago. The average number of crashes in 5 days before that was 12 crashes/day. In last 3 days it is 1.2 crashes/day.

Operating System The available options include Fedora releases, pre-release branched Fedora, Fedora Rawhide, All. The list of releases should be obtained from Fedora Package Database (this is handled by Storage Synchronization).

Components The available options include All Components, the list of all components for the selected Operating System, and selected `comps.xml` groups (such as GNOME Desktop, KDE Desktop, Xfce, Web Server, Electronic Lab, Engineering and Scientific, Font design and packaging, System Tools, Sound and Video, Office/Productivity)

Graph Displays the number of problems (individual events) in time. The underlying data are updated once a day.

Days The graph shows problems in the last 14 days.

Weeks The graph shows problems in the last 12 weeks (3 months).

Months The graph shows problems in the last 12 months.

New and noteworthy Shows automatically discovered interesting trends that can be detected from data. It tells visitor which combinations of Operating System and Component might be worth looking.

5.4.2 Problems Overview Page

[login](#)

Fedora Problem Tracker

search for problem

SummaryProblemsReportsTasksStatus

Hot ProblemsLong-term Problems

Operating System: Fedora 16 ▼ All Components ▼ 7 days 14 days 4 weeks

Rank	Signature	Count	First Appearance	Reports
1	Segmentation fault in gdk_check_xpending()	1253	2012-01-03	gnome#800653
2	Segmentation fault in memmove()	1024	2012-02-05	rhbz#725365
3	Kernel oops - dmar bios	561	2011-03-03	kernel#533214

5.4.3 Problems Item Summary Page

[login](#)

Fedora Problem Tracker

search for problem

Summary

Problems

Reports

Tasks

Status

Segmentation fault in gdk_check_xpending()

Summary

Backtraces

Clusters

History

Environments

Reports

Security

Operating System	Number of Events
Fedora 16	212 (58%)
Fedora 17	113 (30%)
Fedora Rawhide	48 (12%)

Binary	Number of Events
/usr/bin/emacs-23.2	48 (48%)
/usr/bin/emacs-23.1	22 (23%)
/usr/bin/emacs-nox	5 (18%)

Build	Number of Events
emacs-23.1-18.fc15	48 (48%)
emacs-23.2-1.fc16	22 (23%)
emacs-23.2-2.fc16	5 (18%)

Architecture	Number of Events
x86_64	348 (100%)
i686	0 (0%)

Binary objects present in all problem reports:

Binary Object	Component	From	To
/usr/lib64/libgtk-x11-2.0.so.0	gtk	2.2-3.fc15	2.4-4.fc16
/usr/lib64/libatk-1.0.so.0	atk	2.2-3.fc15	2.4-4.fc16
/lib64/libglib-2.0.so.0	glib	2.0-15.fc15	2.0-15.fc16
/lib64/libnss_files.so.2	nss	2.0-15.fc15	2.0-15.fc16

14

5.4.4 Reports Overview Page

[login](#)

Fedora Problem Tracker

search for problem

SummaryProblems**Reports**TasksStatus

OverviewList

absolute

relative

Operating System: Fedora 16▼All Components▼

days

weeks

months

719 x 293

5.4.5 Reports List Page

[login](#)

Fedora Problem Tracker

SummaryProblemsReportsTasksStatus

OverviewList

Operating System: All Components: Destination: Status:

Rank	Report	Status	Last Change	Created
1	rhubz#800653 - Double free in compile()	FIXED	2012-01-03	2012-01-01
2	rhubz#725365 - Buffer overflow in main()	FIXED	2012-02-05	2011-12-06
3	rhubz#565487 - Assert failure in cli.cpp:35	FIXED	2011-03-03	2011-08-23

5.4.6 Server Tasks Page

[login](#)

Fedora Problem Tracker

SummaryProblemsReportsTasksStatus

State: Method:

Id	Name	State	Finished	Arch
65465	LLVM Build of emacs-23.1-16.fc17	FAILED	2012-01-03	x86_64
45554	LLVM Build of btparser-0.17.fc18	FAILED	2012-02-05	x86_64
22455	LLVM Build of abrt-2.2.fc18	FAILED	2011-03-03	x86_64

5.4.7 Server Status Page

[login](#)

Fedora Problem Tracker

search for problem

SummaryProblemsReportsTasksStatus

OverviewBuilds and RPMsLLVM BitcodeDebuginfo CheckIntegration TestsWorkers

Last synchronization with Koji: 2012-03-16 15:36


Last synchronization with Red Hat Bugzilla: 2012-03-16 18:02

Last check of debuginfo issues: 2012-01-10 13:52


Last run of integration tests: 2012-03-17 10:00 [Fedora Rawhide test failed!](#)

Cache: 1.2 TB (31%) used; 3.1 TB available


5.5 ABRT Client Overview




5.6 ABRT Client Interface Overview



5.6.1 Apology Dialog






5.6.2 Detailed Report Dialog



5.6.3 Applet

5.6.4 Problem Browser



5.7 Implementation Phases

5.7.1 Already Implemented Components

5.7.2 Phase 1

5.7.3 Phase 2

6 Project Time Management

6.1 Activity List

1. Implement the problem storage tables in SQLAlchemy. [server]
2. Implement server machine interface for communication with client. [server]
3. Implement saving the received microdump to the database. [server]
4. Set-up and document regular, automatic database backup. [server]
5. Finish the design of minireport and fullreport backup. [server]

6. Implement minireport and fullreport backup. [server]
7. Implement deduplication logic on arrival of a new report. [server]
8. Implement deduplication logic for clustering and merging of existing reports. [server]
9. Implement coredump-level backtraces. [server]
10. Implement retracing of coredump-level backtraces. [server]
11. Implement the basic layout of human interface. [server]
12. Implement graph on the summary page. [server]
13. Implement initial problems overview page. [server]
14. Implement initial problem summary page. [server]
15. Implement both variants of apology dialog. [client]
16. Implement detailed report dialog. [client]
17. Implement ABRT client uploader. [client]
18. Prepare proposal for Anaconda changes. [client]
 - Define Activities – Activity List – Activity attributes – Milestone list
 - Sequence Activities – Project Schedule Network Diagram
 - Estimate Activity Resources – Activity Resource Requirements – Resource Breakdown Structure
 - Estimate Activity Durations – Activity Duration Estimates
 - Develop Schedule – Project Schedule – Schedule baseline – Schedule data

7 Project Quality Management

- Plan Quality – Quality management plan – Quality metrics – Quality checklists – Process improvement plan

8 Project Risk Management

9 Project Management Plan

References

- [1] Jon McCann, *Oops!*. <https://live.gnome.org/Design/Apps/Oops>.
- [2] Jon McCann, *Problem Recovery and Reporting*. <https://live.gnome.org/GnomeOS/Design/Whiteboards/ProblemReporting>.
- [3] Jon McCann, *Problem Reporting Architecture Proposal*. <https://live.gnome.org/GnomeOS/Design/Whiteboards/ProblemReporting/Proposal>.
- [4] *Debugging in the (Very) Large: Ten Years of Implementation and Experience*. <http://msdn.microsoft.com/en-us/windows/hardware/gg487440>.