

Dates and Times in R

Roger D. Peng, Associate Professor of Biostatistics

May 17, 2016

Dates and Times in R

R has developed a special representation of dates and times - Dates are represented by the Date class - Times are represented by the POSIXct or the POSIXlt class - Dates are stored internally as the number of days since 1970-01-01 - Times are stored internally as the number of seconds since 1970-01-01

Dates in R

Dates are represented by the Date class and can be coerced from a character string using the `as.Date()` function.

```
x <- as.Date("1970-01-01")
x
## [1] "1970-01-01"
unclass(x)
## [1] 0
unclass(as.Date("1970-01-02"))
## [1] 1
```

Times in R

Times are represented using the `POSIXct` or the `POSIXlt` class

- ▶ `POSIXct` is just a very large integer under the hood; it use a useful class when you want to store times in something like a data frame
- ▶ `POSIXlt` is a list underneath and it stores a bunch of other useful information like the day of the week, day of the year, month, day of the month

There are a number of generic functions that work on dates and times

- ▶ `weekdays`: give the day of the week
- ▶ `months`: give the month name
- ▶ `quarters`: give the quarter number (“Q1”, “Q2”, “Q3”, or “Q4”)

Times in R

Times can be coerced from a character string using the `as.POSIXlt` or `as.POSIXct` function.

```
x <- Sys.time()
x
## [1] "2013-01-24 22:04:14 EST"
p <- as.POSIXlt(x)
names(unclass(p))
## [1] "sec"    "min"    "hour"   "mday"   "mon"
## [6] "year"   "wday"   "yday"   "isdst"
p$sec
## [1] 14.34
```

Times in R

You can also use the POSIXct format.

```
x <- Sys.time()
x ## Already in 'POSIXct' format
## [1] "2013-01-24 22:04:14 EST"
unclass(x)
## [1] 1359083054
x$sec
## Error: $ operator is invalid for atomic vectors
p <- as.POSIXlt(x)
p$sec
## [1] 14.37
```

Times in R

Finally, there is the `strptime` function in case your dates are written in a different format

```
datestring <- c("January 10, 2012 10:40", "December 9, 2011 09:10")
x <- strptime(datestring, "%B %d, %Y %H:%M")
x
```

```
## [1] "2012-01-10 10:40:00 EST" "2011-12-09 09:10:00 EST"
```

```
class(x)
```

```
## [1] "POSIXlt" "POSIXt"
```

I can *never* remember the formatting strings. Check `?strptime` for details.

Operations on Dates and Times

You can use mathematical operations on dates and times. Well, really just $+$ and $-$. You can do comparisons too (i.e. $==$, $<=$)

```
x <- as.Date("2012-01-01")
y <- strptime("9 Jan 2011 11:34:21", "%d %b %Y %H:%M:%S")
x-y
## Warning: Incompatible methods ("-.Date",
## "-.POSIXt") for "-"
## Error: non-numeric argument to binary operator
x <- as.POSIXlt(x)
x-y
## Time difference of 356.3 days
```


Operations on Dates and Times

Even keeps track of leap years, leap seconds, daylight savings, and time zones.

```
x <- as.Date("2012-03-01") y <- as.Date("2012-02-28")
x-y
## Time difference of 2 days
x <- as.POSIXct("2012-10-25 01:00:00")
y <- as.POSIXct("2012-10-25 06:00:00", tz = "GMT")
y-x
## Time difference of 1 hours
```

Summary

- ▶ Dates and times have special classes in R that allow for numerical and statistical calculations
- ▶ Dates use the `Date` class
- ▶ Times use the `POSIXct` and `POSIXlt` class
- ▶ Character strings can be coerced to Date/Time classes using the `strptime` function or the `as.Date`, `as.POSIXlt`, or `as.POSIXct`