

Creating new variables


Jeffrey Leek

May 18, 2016

Why create new variables?

- ▶ Often the raw data won't have a value you are looking for
- ▶ You will need to transform the data to get the values you would like
- ▶ Usually you will add those values to the data frames you are working with
- ▶ Common variables to create
 - ▶ Missingness indicators
 - ▶ “Cutting up” quantitative variables
 - ▶ Applying transforms

Example data set



OPENBALTIMORE Help Sign Up Sign In

Restaurants
This dataset contains a list of restaurants within Baltimore City. The ▶

Manage More Views Filter Visualize Export Discuss Embed About

| | name | zipCode | neighborhood | councilDistrict | policeDistrict | Location 1 |
|----|-----------------------|---------|-------------------------|-----------------|----------------|----------------------|
| 1 | 410 | 21206 | Frankford | 2 | NORTHEASTERN | 4509 BELAIR ROAD |
| 2 | 1919 | 21231 | Fells Point | 1 | SOUTHEASTERN | 1919 FLEET ST |
| 3 | SAUTE | 21224 | Canton | 1 | SOUTHEASTERN | 2844 HUDSON ST |
| 4 | #1 CHINESE KITCHEN | 21211 | Hampden | 14 | NORTHERN | 3998 ROLAND AVE |
| 5 | #1 chinese restaurant | 21223 | Millhill | 9 | SOUTHWESTERN | 2481 frederick ave |
| 6 | 19TH HOLE | 21218 | Clifton Park | 14 | NORTHEASTERN | 2722 HARFORD RD |
| 7 | 3 KINGS | 21205 | McElderry Park | 13 | SOUTHEASTERN | 2510 MCELDERRY ST |
| 8 | 3 MILES HOUSE, INC. | 21211 | Remington | 7 | NORTHERN | 2701 MILES AVE |
| 9 | 3 WS TAVERN | 21205 | McElderry Park | 13 | SOUTHEASTERN | 2518 MONUMENT ST |
| 10 | 300 SOUTH ANN STREET | 21231 | Upper Fells Point | 1 | SOUTHEASTERN | 300 ANN ST |
| 11 | 438 CLUB | 21226 | Curtis Bay | 10 | SOUTHERN | 1600 HAZEL ST |
| 12 | 5-MILE HOUSE | 21215 | Woodmere | 5 | NORTHWESTERN | 5302 REISTERSTOWN RD |
| 13 | 743 S. MONTFORD, INC. | 21224 | Canton | 1 | SOUTHEASTERN | 743 MONTFORD ST |
| 14 | A & W RESTAURANT | 21224 | Pulaski Industrial Area | 1 | SOUTHEASTERN | 5625 O DONNELL ST |
| 15 | A TASTE OF CHINA | 21202 | Downtown | 11 | CENTRAL | 219 BALTIMORE ST |
| 16 | ABACROMBIE FINE FOODS | 21201 | Mid-Town Belvedere | 11 | CENTRAL | 58 BIDDLE STREET |
| 17 | ABC SUSHI | 21205 | Middle East | 13 | EASTERN | 2003 MONUMENT ST |
| 18 | ACROPOLIS RESTAURANT | 21224 | Greektown | 2 | SOUTHEASTERN | 4718 EASTERN AVE |
| 19 | ADMIRAL FELL INN | 21231 | Fells Point | 1 | SOUTHEASTERN | 818 BROADWAY |

`https://data.baltimorecity.gov/Community/Restaurants/k5ry-ef3g`

Getting the data from the web

```
if(!file.exists("./data")){dir.create("./data")}  
fileUrl <- "https://data.baltimorecity.gov/api/views/k5ry-e  
download.file(fileUrl,destfile="./data/restaurants.csv",met  
restData <- read.csv("./data/restaurants.csv")
```

Creating sequences

Sometimes you need an index for your data set

```
s1 <- seq(1,10,by=2) ; s1
```

```
## [1] 1 3 5 7 9
```

```
s2 <- seq(1,10,length=3); s2
```

```
## [1] 1.0 5.5 10.0
```

```
x <- c(1,3,8,25,100); seq(along = x)
```

```
## [1] 1 2 3 4 5
```

Subsetting variables

```
restData$nearMe = restData$neighborhood %in% c("Roland Park")  
table(restData$nearMe)
```

```
##
```

```
## FALSE TRUE
```

```
## 1314 13
```

Creating binary variables

```
restData$zipWrong = ifelse(restData$zipCode < 0, TRUE, FALSE)  
table(restData$zipWrong, restData$zipCode < 0)
```

```
##  
##           FALSE TRUE  
##  FALSE  1326     0  
##  TRUE     0     1
```

Creating categorical variables

```
restData$zipGroups = cut(restData$zipCode,breaks=quantile(1  
table(restData$zipGroups)
```

```
##
```

```
## (-2.123e+04,2.12e+04] (2.12e+04,2.122e+04] (2.122e+04,2
```

```
## 337 375
```

```
## (2.123e+04,2.129e+04]
```

```
## 332
```

```
table(restData$zipGroups,restData$zipCode)
```

```
##
```

```
##
```

```
## -21226 21201 21202 21205 21206 2
```

```
## (-2.123e+04,2.12e+04] 0 136 201 0 0
```

```
## (2.12e+04,2.122e+04] 0 0 0 27 30
```

```
## (2.122e+04,2.123e+04] 0 0 0 0 0
```

```
## (2.123e+04,2.129e+04] 0 0 0 0 0
```

```
##
```


Easier cutting

```
library(Hmisc)
```

```
## Loading required package: lattice
```

```
## Loading required package: survival
```

```
## Loading required package: Formula
```

```
## Loading required package: ggplot2
```

```
##
```

```
## Attaching package: 'Hmisc'
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      format.pval, round.POSIXt, trunc.POSIXt, units
```

```
restData$zipGroups = cut2(restData$zipCode,g=4)
```

```
table(restData$zipGroups)
```

Creating factor variables

```
restData$zcf <- factor(restData$zipCode)
restData$zcf[1:10]
```

```
## [1] 21206 21231 21224 21211 21223 21218 21205 21211 212
## 32 Levels: -21226 21201 21202 21205 21206 21207 21208 21
```

```
class(restData$zcf)
```

```
## [1] "factor"
```

Levels of factor variables

```
yesno <- sample(c("yes", "no"), size=10, replace=TRUE)
yesnofac = factor(yesno, levels=c("yes", "no"))
relevel(yesnofac, ref="no")
```

```
## [1] yes no yes yes no yes no yes no yes
## Levels: no yes
```

```
as.numeric(yesnofac)
```

```
## [1] 1 2 1 1 2 1 2 1 2 1
```

Cutting produces factor variables

```
library(Hmisc)
restData$zipGroups = cut2(restData$zipCode,g=4)
table(restData$zipGroups)
```

```
##
```

```
## [-21226,21205) [ 21205,21220) [ 21220,21227) [ 21227,212
```

```
##           338           375           300
```

Using the mutate function

```
library(Hmisc); library(plyr)
```

```
##
```

```
## Attaching package: 'plyr'
```

```
## The following objects are masked from 'package:Hmisc':
```

```
##
```

```
##      is.discrete, summarize
```

```
restData2 = mutate(restData,zipGroups=cut2(zipCode,g=4))  
table(restData2$zipGroups)
```

```
##
```

```
## [-21226,21205) [ 21205,21220) [ 21220,21227) [ 21227,212
```

```
##           338           375           300
```

Common transforms

- ▶ `abs(x)` absolute value
- ▶ `sqrt(x)` square root
- ▶ `ceiling(x)` `ceiling(3.475)` is 4
- ▶ `floor(x)` `floor(3.475)` is 3
- ▶ `round(x,digits=n)` `round(3.475,digits=2)` is 3.48
- ▶ `signif(x,digits=n)` `signif(3.475,digits=2)` is 3.5
- ▶ `cos(x)`, `sin(x)` etc.
- ▶ `log(x)` natural logarithm
- ▶ `log2(x)`, `log10(x)` other common logs
- ▶ `exp(x)` exponentiating `x`

http://www.biostat.jhsph.edu/~ajaffe/lec_winterR/Lecture%202.pdf

<http://statmethods.net/management/functions.html>

Notes and further reading

- ▶ A tutorial from the developer of plyr - <http://plyr.had.co.nz/09-user/>
- ▶ Andrew Jaffe's R notes http://www.biostat.jhsph.edu/~ajaffe/lec_winterR/Lecture%202.pdf
- ▶ A nice lecture on categorical and factor variables <http://www.stat.berkeley.edu/classes/s133/factors.html>