

Data Processing with Stata 14.1 Cheat Sheet

For more info see Stata's reference manual (stata.com)

Useful Shortcuts

F2 — keyboard buttons

describe data

Ctrl + **9**

open a new .do file

Ctrl + **8**

open the data editor

clear

delete data in memory

Ctrl + **D**

highlight text in .do file,
then ctrl + d executes it
in the command line

AT COMMAND PROMPT

PgUp

PgDn

scroll through previous commands

Tab

autocompletes variable name after typing part

cls

clear the console (where results are displayed)

Set up

pwd

print current (working) directory

cd "C:\Program Files (x86)\Stata13"

change working drive

dir

display filenames in working directory

fs *.dta

List all Stata files in working directory

capture log close

close the log on any existing do files

log using "myDoFile.do", replace

create a new log file to record your work and results

search mdesc

find the package mdesc to install

ssc install mdesc

install the package mdesc; needs to be done once

underlined parts
are shortcuts –
use "capture"
or "cap"

packages contain
extra commands that
expand Stata's toolkit

Import Data

sysuse auto, clear

load system data (Auto data)

for many examples, we
use the auto dataset.

use "yourStataFile.dta", clear

load a dataset from the current directory

import excel "yourSpreadsheet.xlsx", /*

import an Excel spreadsheet

import delimited "yourFile.csv", /*

import a .csv file

webuse set "https://github.com/GeoCenter/StataTraining/raw/master/Day2/Data"


webuse "wb_indicators_long"

set web-based directory and load data from the web

frequently used
commands are
highlighted in yellow

Basic Syntax

All Stata functions have the same format (syntax):



To find out more about any command – like what options it takes – type **help command**

Basic Data Operations

Arithmetic

+ add (numbers)
combine (strings)

– subtract

***** multiply

/ divide

^ raise to a power

Logic

& and

! or **~** not

| or

if foreign != 1 & price >= 10000

make	foreign	price
Chevy Colt	0	3,984
Buick Riviera	0	10,372
Honda Civic	1	4,499
Volvo 260	1	11,995

== tests if something is equal
= assigns a value to a variable

< less than

<= less than or equal to

> greater than

>= greater or equal to

if foreign != 1 | price >= 10000

make	foreign	price
Chevy Colt	0	3,984
Buick Riviera	0	10,372
Honda Civic	1	4,499
Volvo 260	1	11,995

Explore Data

VIEW DATA ORGANIZATION

describe make price

display variable type, format,
and any value/variable labels

count

count if price > 5000

number of rows (observations)

Can be combined with logic

ds, has(type string)

lookfor "in."

search for variable types,
variable name, or variable label

isid mpg

check if mpg uniquely
identifies the data

SEE DATA DISTRIBUTION

codebook make price

overview of variable type, stats,
number of missing/unique values

summarize make price mpg

print summary statistics
(mean, stdev, min, max)
for variables

inspect mpg

show histogram of data,
number of missing or zero
observations

histogram mpg, **frequency**

plot a histogram of the
distribution of a variable



BROWSE OBSERVATIONS WITHIN THE DATA

browse or **Ctrl** + **8**

open the data editor

list make price **if** price > 10000 & price < .

list the make and price for observations with price > \$10,000

display price[4]

display the 4th observation in price; only works on single values

gsort price mpg (ascending)

sort in order, first by price then miles per gallon

duplicates report

finds all duplicate values in each variable

levelsof rep78

display the unique values for rep78

Missing values are treated as the largest
positive number. To exclude missing values,
ask whether the value is less than "."

clist ... (compact form)

Change Data Types

Stata has 6 data types, and data can also be missing:

no data true/false words numbers
missing **byte** **string** **int** **long** **float** **double**

To convert between numbers & strings:

1 **gen** foreignString = **string**(foreign) "1"
tostring foreign, **gen**(foreignString) "1"
decode foreign, **gen**(foreignString) "foreign"

1 **gen** foreignNumeric = **real**(foreignString) "1"
destring foreignString, **gen**(foreignNumeric) "1"
encode foreignString, **gen**(foreignNumeric) "foreign"

recast double mpg
generic way to convert between types

Summarize Data

include missing values create binary variable for every rep78
value in a new variable, repairRecord

tabulate rep78, **mi** **gen**(repairRecord)

one-way table: number of rows with each value of rep78

tabulate rep78 foreign, **mi**

two-way table: cross-tabulate number of observations
for each combination of rep78 and foreign

bysort rep78: **tabulate** foreign

for each value of rep78, apply the command tabulate foreign

tabstat price weight mpg, **by**(foreign) **stat**(mean sd n)

create compact table of summary statistics displays stats
formats numbers for all data

table foreign, **contents**(mean price sd price) **f**(%9.2fc) **row**

create a flexible table of summary statistics

collapse (mean) price (max) mpg, **by**(foreign) – replaces data

calculate mean price & max mpg by car type (foreign)

Create New Variables

generate mpgSq = mpg^2 **gen** byte lowPr = price < 4000

create a new variable. Useful also for creating binary
variables based on a condition (**generate** byte)

generate id = _n **bysort** rep78: **gen** repairIdx = _n

_n creates a running index of observations in a group

generate totRows = _N **bysort** rep78: **gen** repairTot = _N

_N creates a total count of observations (per group)

pctile mpg Quartile = mpg, **nq** = 4

create quartiles of the mpg data

egen meanPrice = **mean**(price), **by**(foreign)

calculate mean price for each group in foreign see **help egen**
for more options

Data Transformation with Stata 14.1 Cheat Sheet

For more info see Stata's reference manual (stata.com)

Select Parts of Data (Subsetting)

SELECT SPECIFIC COLUMNS

drop make

remove the 'make' variable

keep make price

opposite of drop; keep only columns 'make' and 'price'

FILTER SPECIFIC ROWS

drop if mpg < 20

drop observations based on a condition (left) or rows 1-4 (right)

drop in 1/4

keep in 1/30

opposite of drop; keep only rows 1-30

keep if inrange(price, 5000, 10000)

keep values of price between \$5,000 – \$10,000 (inclusive)

keep if inlist(make, "Honda Accord", "Honda Civic", "Subaru")

keep the specified values of make

sample 25

sample 25% of the observations in the dataset (use **set seed #** command for reproducible sampling)

Replace Parts of Data

CHANGE COLUMN NAMES

rename (rep78 foreign) (repairRecord carType)

rename one or multiple variables

CHANGE ROW VALUES

replace price = 5000 if price < 5000

replace all values of price that are less than \$5,000 with 5000

recode price (0 / 5000 = 5000)

change all prices less than 5000 to be \$5,000

recode foreign (0 = 2 "US")(1 = 1 "Not US"), gen(foreign2)

change the values and value labels then store in a new variable, foreign2

REPLACE MISSING VALUES

mvdecode _all, mv(9999)

useful for cleaning survey datasets

replace the number 9999 with missing value in all variables

mvencode _all, mv(9999)

useful for exporting data

replace missing values with the number 9999 for all variables

Label Data

Value labels map string descriptions to numbers. They allow the underlying data to be numeric (making logical tests simpler) while also connecting the values to human-understandable text.

label define myLabel 0 "US" 1 "Not US"

label values foreign myLabel

define a label and apply it the values in foreign

label list

list all labels within the dataset

Reshape Data

webuse set <https://github.com/GeoCenter/StataTraining/raw/master/Day2/Data>
webuse "coffeeMaize.dta" load demo dataset

MELT DATA (WIDE → LONG)

reshape variables starting with coffee and maize
unique id variable (key)
create new variable which captures the info in the column names
reshape long coffee@ maize@, i(country) j(year) — new variable
convert a wide dataset to long

WIDE					LONG (TIDY)			
country	coffee 2011	coffee 2012	maize 2011	maize 2012	country	year	coffee	maize
Malawi					Malawi	2011		
Rwanda					Malawi	2012		
Uganda					Rwanda	2011		
					Rwanda	2012		
					Uganda	2011		
					Uganda	2012		

TIDY DATASETS have each observation in its own row and each variable in its own column.

CAST DATA (LONG → WIDE)

create new variables named coffee2011, maize2012...
what will be unique id variable (key)
create new variables with the year added to the column name

reshape wide coffee maize, i(country) j(year)
convert a long dataset to wide

xpore, clear varname

transpose rows and columns of data, clearing the data and saving old column names as a new variable called "_varname"

Combine Data

ADDING (APPENDING) NEW DATA

id	blue	pink
□		
○		
△		

+

id	blue	pink
□		
○		
△		

should contain the same variables (columns)

webuse coffeeMaize2.dta, clear
save coffeeMaize2.dta, replace
webuse coffeeMaize.dta, clear

load demo data

append using "coffeeMaize2.dta", gen(filenum)
add observations from "coffeeMaize2.dta" to current data and create variable "filenum" to track the origin of each observation

MERGING TWO DATASETS TOGETHER

ONE-TO-ONE			
id	blue	pink	brown
□			
○			
△			

+

id	brown
□	
○	
△	

=

id	blue	pink	brown	_merge
□				3
○				3
△				3

MANY-TO-ONE

id	blue	pink	brown	_merge
□				3
○				3
△				3
☆				1

_merge code

1 row only (master)	in ind2
2 row only (using)	in hh2
3 row in both (match)	

webuse ind_age.dta, clear
save ind_age.dta, replace
webuse ind_ag.dta, clear

merge 1:1 id using "ind_age.dta"
one-to-one merge of "ind_age.dta" into the loaded dataset and create variable "_merge" to track the origin

webuse hh2.dta, clear
save hh2.dta, replace
webuse ind2.dta, clear

merge m:1 hid using "hh2.dta"
many-to-one merge of "hh2.dta" into the loaded dataset and create variable "_merge" to track the origin

FUZZY MATCHING: COMBINING TWO DATASETS WITHOUT A COMMON ID

reclink match records from different data sets using probabilistic matching **ssc install reclink**
jarowinkler create distance measure for similarity between two strings **ssc install jarowinkler**

Manipulate Strings

GET STRING PROPERTIES

display length("This string has 29 characters")
return the length of the string

charlist make

* user-defined package

display the set of unique characters within a string

display strpos("Stata", "a")

return the position in Stata where a is first found

FIND MATCHING STRINGS

display strmatch("123.89", "1???.9")

return true (1) or false (0) if string matches pattern

display substr("Stata", 3, 5)

return the string located between characters 3-5

list make if regexm(make, "[0-9]")

list observations where make matches the regular expression (here, records that contain a number)

list if regexm(make, "(Cad.|Chev.|Datsun)")

return all observations where make contains "Cad.", "Chev." or "Datsun"

compare the given list against the first word in make

list if inlist(word(make, 1), "Cad.", "Chev.", "Datsun")

return all observations where the first word of the make variable contains the listed words

TRANSFORM STRINGS

display regexr("My string", "My", "Your")

replace string1 ("My") with string2 ("Your")

replace make = substr(make, "Cad.", "Cadillac", 1)

replace first occurrence of "Cad." with Cadillac in the make variable

display strtrim("Too much Space")

replace consecutive spaces with a single space

display trim(" leading / trailing spaces ")

remove extra spaces before and after a string

display strlower("STATA should not be ALL-CAPS")

change string case; see also **strupper**, **strproper**

display strtoname("1Var name")

convert string to Stata-compatible variable name

display real("100")

convert string to a numeric or missing value

Save & Export Data

save "myData.dta", replace Stata 12-compatible file
saveold "myData.dta", replace version(12)

save data in Stata format, replacing the data if a file with same name exists

export excel "myData.xls", /*

***/ firstrow(variables) replace**

export data as an Excel file (.xls) with the variable names as the first row

export delimited "myData.csv", delimiter(",") replace
export data as a comma-delimited file (.csv)