

Percobaan 2A: Konfigurasi Mode Station (STA)

Tabel 1. Pengamatan Koneksi WiFi Mode Station (STA)

No.	Waktu (s)	Status Koneksi	IP Address	MAC Address	RSSI (dBm)	Status LED
1	0					
2	5					
3	10					
4	15					
5	20					
6	25					
7	30					
8	35					
9	40					
10	45					

Tabel 2. Pengujian Mode Station (STA)

No.	Kondisi Pengujian	SSID	Password	Status Koneksi	Output Serial Monitor	Keterangan
1	Kredensial Benar					
2	Password Salah					
3	SSID Salah					

Percobaan 2B: Konfigurasi Mode Access Point (AP)

Tabel 3. Pengamatan Access Point (AP)

No.	Parameter	Nilai Konfigurasi	Hasil Pengamatan
1	SSID	ESP32_AccessPoint	ESP32_AccessPoint
2	Password	12345678	Behasil digunakan
3	IP Address AP	192.168.4.1	192.168.4.1
4	Status Access Point	Aktif	Aktif
5	SSID terdeteksi pada client	Ya	Ya
6	Perangkat berhasil terhubung	-	Ya, 1 smartphone

Tabel 4. Pengamatan Jumlah Perangkat Terhubung ke AP

No.	Waktu (s)	Jumlah Client	Perangkat yang terhubung	Keterangan
1	0			
2	5			
3	10			
4	15			
5	20			
6	25			
7	30			
8	35			
9	40			
10	45			