

Computer Vision HW6, Yokoi Connectivity Report

tags: NTU CS Computer Vision Writeup Report

NTU CSIE, R08922024, Alfons Hwu

Prerequisites and env as the following

pure vim + python3 only

a, Yokoi-connectivity

Just brute-forcelly implement all the possibilities for the answer. (Answer as attached yokoi_ans.txt)

yokoi h op

```
def h(b, c, d, e):
    if b == c and (d != b or e != b):
        return 'q'
    if b == c and (d == b and e == b):
        return 'r'

    return 's'
```

yokoi core

```
def yokoi_core(img_in):
    row, col = img_in.shape

    # down sampling image
    img_down = np.zeros((64, 64), np.int)
    row, col = img_down.shape
    for i in range(row):
        for j in range(col):
            img_down[i, j] = img_in[8 * i, 8 * j]

    for i in range(row):
        for j in range(col):
            if img_down[i, j] > 0:
                if i == 0:
                    if j == 0:
                        # top-left
                        x7, x2, x6 = 0, 0, 0
                        x3, x0, x1 = 0, img_down[i, j], img_down[i, j + 1]
                        x8, x4, x5 = 0, img_down[i + 1, j], img_down[i + 1, j + 1]
                    elif j == col - 1:
                        # top-right
                        x7, x2, x6 = 0, 0, 0
                        x3, x0, x1 = img_down[i, j - 1], img_down[i, j], 0
                        x8, x4, x5 = img_down[i + 1, j - 1], img_down[i + 1, j], 0
                    else:
                        # top-row
                        x7, x2, x6 = 0, 0, 0
                        x3, x0, x1 = img_down[i, j - 1], img_down[i, j], img_down[i, j + 1]
                        x8, x4, x5 = img_down[i + 1, j - 1], img_down[i + 1, j], img_down[i + 1, j + 1]
                elif i == img_down.shape[0] - 1:
                    if j == 0:
                        # bottom-left
                        x7, x2, x6 = 0, img_down[i - 1, j], img_down[i - 1, j + 1]
                        x3, x0, x1 = 0, img_down[i, j], img_down[i, j + 1]
                        x8, x4, x5 = 0, 0, 0
                    elif j == col - 1:
                        # bottom-right
                        x7, x2, x6 = img_down[i - 1, j - 1], img_down[i - 1, j], img_down[i - 1, j + 1]
                        x3, x0, x1 = img_down[i, j - 1], img_down[i, j], 0
```

```

        x8, x4, x5 = 0, 0, 0
    else:
        # bottom-row
        x7, x2, x6 = img_down[i - 1, j - 1], img_down[i - 1, j]
        x3, x0, x1 = img_down[i, j - 1], img_down[i, j], img_down[i, j + 1]
        x8, x4, x5 = 0, 0, 0
    else:
        if j == 0:
            # leftmost-row
            x7, x2, x6 = 0, img_down[i - 1, j], img_down[i - 1, j + 1]
            x3, x0, x1 = 0, img_down[i, j], img_down[i, j + 1]
            x8, x4, x5 = 0, img_down[i + 1, j], img_down[i + 1, j + 1]
            # rightmost-column
        elif j == col - 1:
            x7, x2, x6 = img_down[i - 1, j - 1], img_down[i - 1, j]
            x3, x0, x1 = img_down[i, j - 1], img_down[i, j], 0
            x8, x4, x5 = img_down[i + 1, j - 1], img_down[i + 1, j]
            #the rest, inner
        else:
            x7, x2, x6 = img_down[i - 1, j - 1], img_down[i - 1, j]
            x3, x0, x1 = img_down[i, j - 1], img_down[i, j], img_down[i, j + 1]
            x8, x4, x5 = img_down[i + 1, j - 1], img_down[i + 1, j], img_down[i + 1, j + 1]

    a1 = h(x0, x1, x6, x2)
    a2 = h(x0, x2, x7, x3)
    a3 = h(x0, x3, x8, x4)
    a4 = h(x0, x4, x5, x1)

    if a1 == 'r' and a2 == 'r' and a3 == 'r' and a4 == 'r':
        ans = 5
        print(ans, end='')
    else:
        ans = 0
        for a_i in [a1, a2, a3, a4]:
            if a_i == 'q':
                ans += 1

        if ans != 0:
            print(ans, end='')
        else:
            print(' ', end='')

    else:
        # background
        print(' ', end='')

    if j == col - 1:
        # new line
        print('')

```