Introduction

LogiNext Terminology

LogiNext welcomes you to the world of organized logistics.

In this section, we will cover the elements that make up the LogiNext system and how you can start integrating with the LogiNext APIs.

DELIVERY ASSOCIATE

A Delivery Associate is the resource that would pickup or deliver your customers' orders. Delivery Associates can be maintainence men, repair men, or Delivery Associates.

When a Delivery Associate is created in LogiNext, Login credentails are generated, using which the Delivery Associate can Sign-in to the Driver app.

VEHICLE

A Vehicle can be used to Pick-up and Deliver Orders that are part of the Trip. A Vehicle could be a bike, car, truck, van and more.

DRIVER

A Driver is responsible for driving/riding the Delivery Vehicle.

Depending on the kind of business, the Driver and Delivery Associate could be the same person. In some cases they are different where in addition to a Driver, there is a Delivery Associate delivering the shipments home.

BRANCH

A Branch could be the fulfillment center or warehouse where Orders are either Delivered or Pickedup from.

ORDER

Orders are the base transaction entities in the LogiNext system. An Order has details of shipment you want to pickup from your merchant or deliver to your customer. Pick Up and Delivery could be different depending on the industry you are in. For example, in the Courier Industry, Pick Up and Delivery can be for Customers.

TRIP

A Trip is a run where a Delivery Associate fulfills one or more Orders. A Trip is created in the LogiNext System as a result of Route Planning or Auto-Assignment operations.

SHIPPER

An Shipper is used to represent LogiNext's Customer's Customer. You can create a Shipper in LogiNext to represent different Customers. Orders can be created in LogiNext on behalf of your Shippers using the 'clientCode' field in the APIs that support this functionality. Details will be mentioed in the specific APIs. A shipper can only use the Create Order Request and Shipper Serviceability APIs.

SERVICE TIME

Service Time is the time it takes to service an Order at a particular location. For example - If an Order is to be delivered at a Customer's Home address, the Service time would include the time for parking the Vehicle and accounting for security checks at the location if any. Similarly, if an Order is to be delivered at a warehouse, Service Time will account for parking, loading and unloading at the delivery location.

Integration Details

Using the LogiNext API, you can integrate all the segments of your logistics and supply chain network into our product platform to create a seamless experience for your operations and executive team.

The LogiNext API is designed to allow our client partners to add delivery associates(resources), orders, plan a route, start the trip, track and follow the updates till the trip is completed and shipment is pickedup/delivered at the desired location.

Below are a few important steps that would explain what it takes for you, as our Client partner, to link your system with LogiNext's.

Step 1 – Please read carefully the Request, Responses and Authentication section so that you can configure things on your end to integrate with LogiNext APIs.

Step 2 – You will need to get the username and password which will be provided to you either by our system (in case of auto sign-up) or by your LogiNext Account Manager.

Step 3 – (Optional) If you are planning to consume any of the LogiNext Webhooks, you will need to share the end-point URL of your system to consume the Webhook. This end-point will be configured in the LogiNext system by your Account Manager.

In case of any queries during the integration process, please reach out to us at support@loginextsolutions.com.

Requests

The base URL for all requests to the LogiNext API is:

https://api.loginextsolutions.com/

Our API is REST-based. This means:

1. It makes use of standard HTTP methods like GET, POST, DELETE.
2. The API uses standard HTTP error responses(status codes) to indicate status of your requests – success and error codes.

3. All LogiNext API requests are authenticated with an API Token. Details on how to obtain an authentication Token are mentioned in the Authentication section of this Documentation.

Also,the input dates like 2016-07-01T11:18:00.000Z are accepted in Coordinated Universal Time (UTC) format.

REQUEST HEADERS

Header	Sample Value	Description
Content-Type	application/json	JSON request
WWW-Authenticate	BASIC 51bbe3f7-1671-476c-818a-e7fbbca10202	Authentication token

VERSIONING

Versioning allows us to provide developers a consistent experience. All endpoints are prefixed with a version such as /v1, v2 etc. This version refers to the overall layout of the endpoints and response standards.

Responses

The LogiNext API uses HTTP status codes to indicate the status of your requests. This includes Success and Error codes.

Dates in API responses like 2016-07-01T11:18:00.000Z are sent in Coordinated Universal Time (UTC) format. Get API responses are sent in EPOCH format along with timezones to help the user convert it accordingly.

Code	Message	Description
200	Success	This message means that the request is successfully processed.
201	Created	This message means that the resource is successfully created.
202	Acknowledged	This status code indicates that a request has been received and taken up for processing. It may take some time to complete processing this kind of request, and LogiNext will typically send a webhook notification with the results of the response once the request has been successfully completed.
204	No Content	This status code indicates that an HTTP request has been successfully completed, and there is no message body. When the 204 No Content status code is received, it is in HTTP response to an HTTP operation such as a POST, PUT, or DELETE, where no message body is expected.
207	Partial Success	This status code indicates that some of the entities in the request were successfully processed, while some others failed. The response will provide details regarding the state of each record that was sent in the request.
400	Bad Request	This message means that the request is syntactically incorrect. You will receive this message in a case where the request body sent is not a standard JSON or array object as is expected by LogiNext.
401	Invalid username or password	This message means that invalid credentials are passed.
404	Not Found	This message means that the resource could not be found.
405	Method Not Allowed	This message means that the method used to access the resource is invalid.

409	Request Error	This message means that there is a validation error in the data sent in the request body. This could either be missing out a mandatory field in the API or sending an incorrect branch name in the request body.
415	Unsupported Media Type	This message means that the request is not in the format accepted by this method of target resource.
429	Too Many Requests	This message means that too many resources are requested.
500	Internal Server Error	This message means that there is an issue with the LogiNext server.Please try accessing the request later.
503	Service Unavailable	This message means that the LogiNext applications are down for scheduled maintenance. Please try accessing the request later.
504	Gateway Timed Out	This response is sent when the request has not received a response from LogiNext in over 10 minutes and the connection has timed out.

Authentication

Authenticate

The LogiNext APIs use authentication tokens to provide you an authorized access.

You can generate an authentication token either by using the ‘API Token Management' module under Settings, or by calling the API endpoint provided below. Note that at any given time, a maximum of two active tokens can be generated at the Branch level.

To generate a token, you will need to pass the username and password for your LogiNext Dispatcher Web App account. If required, your Account Manager can assist you with this.

The response will contain the authentication token required to make calls to the LogiNext APIs.

Session Expiry Timeout

To specify the session duration, use the 'sessionExpiryTimeout' parameter. Here are the values you can use:

1 Hour: 1

24 Hours: 24

6 Months: 180 * 24 = 4320

12 Months: 365 * 24 = 8760

5 Years: 365 * 5 * 24 = 43800

10 Years: 365 * 10 * 24 = 87600

If you do not provide a ‘sessionExpiryTimeout’, the default validity of the session token will be 90 days (3 months).

Note:

- Ensure that you include the token in every LogiNext API call.
- Certain API fields, such as the ‘paymentType’ field in the Create Order Request API, depend on the language preferences set for the

user account at the time of API token creation. For a seamless integration experience, we recommend using an English-language user account to create API tokens for integration with the LogiNext platform.

Sample Request

```
{
        "userName":"demouser",
        "password":"Admin#1!",
        "sessionExpiryTimeout": 87600
}
```

Success Response

```
{
  "status": 200,
  "message": "success",
  "data": null,
  "hasError": false
}
```

REQUEST

POST `https://api.loginextsolutions.com/LoginApp/login/authenticate`

REQUEST HEADER

Header	Sample Value	Description
Content-Type	application/json	JSON request

REQUEST PARAMETERS

Parameter	DataType	Length	Required	Description
userName	String	255	Mandatory	Username that you use to log into the Dispatcher Web App.
password	String	255	Mandatory	Password that you use to log into the Dispatcher Web App.
sessionExpiryTimeout	Integer	10	Optional	Number of hours for which you want the session to remain valid.

RESPONSE

The response will consist of parameters described in the ‘Responses’ section, based on the request parameters provided. For example, the response might contain:

200 - Success

401 - Invalid username or password, etc.

RESPONSE HEADER

The response header will consist of an Authentication Token. Note that, by default, this token is valid for 90 days.

Header	Sample Value
WWW-Authenticate	BASIC 075b8961-bd02-454c-83eb-259f965f313f

Authenticate Delivery Associate

Call the Mobile Authenticate API to obtain an authentication token for your delivery associates.

To generate a token, you will need to enter the username and password of the delivery associate (as entered during creation in the LogiNext system) into the request body.

The response header will contain the authentication token required to authenticate the delivery associate. This token is unique to each delivery associate and remains valid for four years from the time of creation.

API TYPE

- Tier 2 API.

Sample Request

```
{
  "userName": "johnc",
  "password": "admin",
  "imei":"854437655912443",
  "latitude": 40.1114131,
  "longitude": 74.9094666,
  "androidId": "ce6448cf20b78483",
  "androidTime": "2017-04-21T05:53:47Z"
}
```

Success Response

```
{
  "status": 200,
  "message": "Login successfully.",
  "hasError": false
}
```

REQUEST

POST `https://api.loginextsolutions.com/LoginApp/login/mobile/auth`

REQUEST HEADER

Header	Sample Value	Description
Content-Type	application/json	JSON request

REQUEST PARAMETERS

Parameter	DataType	Length	Required	Description
userName	String	255	Mandatory	Username that the delivery associate uses to log into the Driver App.
password	String	255	Mandatory	Password that the delivery associate uses to log into the Driver App.
imei	String	50	Mandatory	IMEI number of the delivery associate’s phone.
latitude	Double	10,13	Optional	Latitude coordinates of the delivery associate.

longitude	Double	10,13	Optional	Longitude coordinates of the delivery associate.
androidId	String	10	Optional	Unique ID of the delivery associate's phone/device.
androidTime	Date		Optional	Current date and time (in UTC format). For example - 2017-12-11T07:21:39Z.

RESPONSE

The response will consist of parameters described in the 'Responses' section, based on the request parameters provided. For example, the response might contain:

200 - Success

401 - Invalid username or password, etc.

RESPONSE HEADER

The response header will consist of an Authentication Token. Note that, by default, this token and key are valid for 4 years.

Header	Sample Value
WWW-Authenticate	BASIC 075b8961-bd02-454c-83eb-259f965f313f

Invalidate

You can fetch a fresh authentication token by calling the API below. This call will invalidate the existing token and provide you with a new authentication token, which you will have to pass on to every subsequent API call. Note that this endpoint invalidates a user.

API TYPE

- Tier 1 API.

  Success Response

```
{
  "status": 200,
  "message": "success",
  "data": null,
  "hasError": false
}
```

REQUEST

GET `https://api.loginextsolutions.com/LoginApp/login/token/refresh`

REQUEST HEADERS

Header	Sample Value
Content-Type	application/json
WWW-Authenticate	BASIC 8bce7b1b-9762-4de7-b9cd-976ecf38b6a0

RESPONSE HEADER

Header	Sample Value
WWW-Authenticate	BASIC 075b8961-bd02-454c-83eb-259f965f313f

Rate Limits

LogiNext APIs define rate limits based on the specific API being called. Different APIs have different rate limits depending on their use case and request payload. APIs are categorized according to the following criteria:

API Type	Description	Rate Limit
Tier 1 APIs	These APIs have a specified rate limit to accommodate various operations in the LogiNext system.	5 requests per second.
Tier 2 APIs	These APIs have a more generous rate limit than Tier 1 APIs to support burst behavior.	10 requests per second.
Special Tier APIs	Custom rate limits are defined for Special Tier APIs. For example, the Route Optimization API allows 1 request per minute.	Custom rate limits (As mentioned in the API description).

Note:

- If you are working with multiple shippers that are integrated with the LogiNext API, the rate limit applies collectively across all shippers. For instance, the 5 requests per second limit for a Tier 1 API applies to all your shippers. Rate Limits do not apply to individual shippers.
- Exceeding the rate limit will result in a temporary ban, and your API call will receive a 429 - Max Request Limit Reached error.
- All rate limits apply on a rolling time interval basis. For example, if you are calling a Tier 1 API that supports a rate limit of 5 requests per second, that means you can send a total of 5 requests within a one-second interval of each other.

Batching

The LogiNext APIs support multiple records per request. For example, you can send up to 20 orders to be created in a single call to the Create Order API.

APIs that support batching allow a maximum of 20 records per request. Note that sending more than 20 records in a single API request will result in a failure response.

The rate limit for APIs that support batching depends on the tier of the API.

Best Practices

1. We recommend using webhooks instead of polling GET APIs for real-time event updates. For example, if you wish to get the current status of an order, consume the Update Order Status webhook rather than consistently polling the Get Order API to fetch order request-related details.

2. You can decide whether to leverage the batching functionality of the LogiNext APIs depending on your business operations. For instance, you may choose to send 20 orders in a single request to the Create Order API if you experience large bursts of transactions in your system at certain times. In this case, the Create Order API may return a partial success response, where some orders are successfully created in the LogiNext system while others are not. You will need to understand how to handle this partial success response and define appropriate business logic in your code to manage it.
3. We recommend implementing a retry mechanism in case of the 429 or 500 error responses received from the LogiNext API.
4. Implement logic to respect LogiNext API rate limits. Exceeding these limits will result in API requests receiving a 429 error response from LogiNext.

LogiNext Mile APIs

The Mile Product refers to the first mile and last mile Order Pick-up and Deliveries. The Mile product will help you create -

Pick-up orders thereby catering to your first leg of logistics, wherein shipments are ‘picked’ from your customer / merchants / suppliers / vendors and transported to the hub for aggregation.

Delivery orders by loading the items for different orders from a Single Point of Pick Up (Hub) and deliver the same to your customers (Multiple Drop Points).

Point to Point Orders for variable Pick-up and Delivery locations.

1. Once the resources are created, then you can add shipments or orders in the LogiNext database by calling Create Order API. You need to provide the Order Number, Date and time window on which order should be picked-up / delivered and the pick-up / delivery address details. Additionally you can also specify the Crate level and line item level details contained in that order.The response consists of the Reference ID against each Order ID which needs to be stored in your system for future references.
2. Once the optimization for capacity and route planning is completed, trips will be created by the LogiNext system and you can mark the trip as started by calling the Start Trip API and mark the same trip as stopped by calling Stop Trip API. In both these API you will have to pass the trip reference ID.
3. Finally you can track your pick-up / delivery executive in transit through the Track Last Location API. In this case also you need to pass the Trip Reference Id.
4. You can also mark a particular order as cancelled by calling the Cancel Order API and passing the order reference ID.
5. In case, your account is being configured into the LogiNext system as a pick-up and delivery both, then you can also create the return shipment for the order thereby optimizing you reverse logistics and return planning.

Customer

CREATE

Sample Request

```
[
  {
    "accountCode":"James",
```

```
    "name":"James Wan",
    "mobile":"341245673212",
    "whatsappOptin":"Y",
    "email":"james@ablogs.com",
    "customerType":"Preferred",
    "billingAddress": {
          "apartment":"Suite No. 1, Milsons Towers",
          "streetName":"Michigan Avenue",
          "landmark":"Opp. Subway",
          "locality":"Dowtown Chicago",
          "city":"Chicago",
          "state":"IL",
          "country":"USA",
          "pincode":"10045",
          "latitude": 40.760838,
          "longitude": 79.555
    }
  }
]
```

Success Response

```
{
    "status": 200,
    "message": "Customer(s) created successfully",
    "data": [
        {
            "index": 0,
            "referenceId": "6a34c7274df0489f97c0f891514b488b",
            "accountCode": "cust001"
        }
    ],
    "hasError": false
}
```

Partial Success Response

```
{
    "status": 207,
    "message": "Customer(s) created partially",
    "moreResultsExists": false,
    "data": [
        {
            "index": 0,
            "referenceId": "3a973fdcb1eb41d5ad7408c57e13cc87",
            "accountCode": "cust001"
        }
    ],
    "error": [
        {
            "index": 1,
            "accountCd": "cust001",
            "errorList": [
                {
                    "key": "accountCode",
                    "message": [
                        "Account Code already exists for client"
                    ]
                }
            ]
        }
    ],
```

```
    "hasError": true
}
```

Failure Response

```
{
    "status": 409,
    "message": "Customer(s) creation failed",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "accountCd": "cust001",
            "errorList": [
                {
                    "key": "mobile",
                    "message": [
                        "INVALID Mobile Number"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Create new customers in the LogiNext system with this API.

- This API creates a Customer entity complete with contact information and a billing address.
- Each customer is assigned a unique Reference ID for future identification.
- Call this API along with the provided parameters to push existing customers from your current system to LogiNext.
- This API only accepts inputs if you have enabled the Customer Profiling property within the LogiNext system.

API TYPE

- Tier 1 API.
- Client Rate Limit: 5 requests per second.
- Branch Rate Limit: 1 request per second.
- You can create a maximum of 5 customers in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ClientApp/customer/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
accountCode	String	50	Mandatory	Unique identifier associated with the customer. This is used to identify a customer for future reference.
name	String	255	Mandatory	Name of the customer.
mobile	String	255	Mandatory	Contact number of the customer.
email	String	255	Optional	Email ID of the customer.
customerType	String	255	Optional	Type of customer just in case you want to categorize your customers into different groups. For example, you can create 'Premium' customers and identify them in LogiNext based on values in this field.
			Address	Name of the apartment building/complex in the customer's billing

billingAddress.apartment	String	40	Validations	address.
billingAddress.streetName	String	100	Address Validations	Name of the society or street in the customer's billing address.
billingAddress.landmark	String	255	Address Validations	Landmark of the customer's billing location.
billingAddress.locality	String	255	Address Validations	Name of the locality or area in the customer's billing address.
billingAddress.city	String	20	Address Validations	Name of the city in the customer's billing address.
billingAddress.state	String	20	Address Validations	Name of the state in the customer's billing address. This should be as per the State Codes available in the LogiNext system for the selected country.
billingAddress.country	String	255	Address Validations	Name of the country in the customer's billing address. This should be as per the Country Codes available in the LogiNext system.
billingAddress.pincode	String	255	Address Validations	Pin code of the customer's billing location.
billingAddress.latitude	Double	20	Optional	Latitude coordinates of the customer's billing address.
billingAddress.longitude	Double	20	Optional	Longitude coordinates of the customer's billing address.
clientCode	String	50	Optional	Name of the company associated with the shipper's account. Pass the company name of the shipper's account if you want to create a customer entity on behalf of one of your shippers.
whatsappOptin	Boolean	NULL	Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.

GET

Sample Request

```
https://api.loginextsolutions.com/ClientApp/customer/v1/get/list?ids=cust1,65ba00dbdcf04fb789311df6aa40e3ba
```

Success Response


```
{
    "status": 200,
    "message": "Customer Details fetched successfully",
    "moreResultsExists": false,
    "data": [
        {
            "accountCode": "name1",
            "name": "James Wan",
            "mobile": "5163063377",
            "email": "james@ablogs.com",
            "customerType": "Preferred",
            "billingAddress": {
                "apartment": "Suite No. 1, Milsons Towers",
                "streetName": "Michigan Avenue",
                "landmark": "Opp. Subway",
```

```
                "city": "Chicago",
                "locality": "Dowtown Chicago",
                "state": "NY",
                "country": "USA",
                "pincode": "10045",
                "latitude": 40.760838,
                "longitude": 74.555
            },
            "isActive": "Y",
            "referenceId": "3a973fdcb1eb41d5ad7408c57e13cc87",
            "whatsappOptin": "N",
        }
    ],
    "error": [],
    "hasError": false
}
```


Partial Success Response


```
{
   "status": 207,
   "message": "Customer Details fetched successfully",
   "data": [
       {
            "name":"James Wan",
            "mobile":"341245673212",
            "email":"james@ablogs.com",
            "customerType":"Preferred",
            "billingAddress": {
                  "apartment":"Suite No. 1, Milsons Towers",
                  "streetName":"Michigan Avenue",
                  "landmark":"Opp. Subway",
                  "locality":"Dowtown Chicago",
                  "city":"Chicago 11",
                  "state":"NY",
                  "country":"USA",
                  "pincode":"10045",
                  "latitude": 40.760838,
                  "longitude": 74.555
                   },
           "isActive": "Y",
           "referenceId": "241ccf29a4404046a033f31cc3384ac7"
       }
   ],
   "error": {
       "1": "65ba00dbdcf04fb789311df6aa40e3ba"
   },
   "hasError": true
}
```


Failure Response


```
{
    "status": 400,
    "message": "Incorrect reference id / Customer code",
    "moreResultsExists": false,
    "error": [
        "89889897iyguy"
    ],
    "hasError": true
}
```

Retrieve details of required customers using this API.

- This API retrieves the details of a customer entity, including contact information and a billing address.
- Include the Reference IDs or Customer IDs of the customers you want to search for in the Request Body.
- If you possess the Customer IDs of your customers and need the Customer Reference IDs to update a customer, call this API to obtain the Reference ID.
- If you only have the Customer ID, you can retrieve the customer details by invoking this API.
- Note that this API does not return the shipping addresses associated with a customer.

API TYPE

- Tier 1 API.
- This API accepts up to 20 Customer IDs or Reference IDs in a comma-separated format in the URL.

REQUEST

GET `https://api.loginextsolutions.com/ClientApp/customer/v1/get/list`

UPDATE

Sample Request

```
[
 {
   "referenceId":"65ba00dbdcf04fb789311df6aa40e3ba",
   "name":"James Wan",
   "mobile":"341245673212",
   "whatsappOptin":"N",
   "email":"james@ablogs.com",
   "customerType":"Preferred",
   "billingAddress": {
         "apartment":"Suite No. 1, Milsons Towers",
         "streetName":"Michigan Avenue",
         "landmark":"Opp. Subway",
         "locality":"Dowtown Chicago",
         "city":"Chicago 11",
         "state":"NY",
         "country":"USA",
         "pincode":"10045",
         "latitude": 40.760838,
         "longitude": 74.555
   }
 }
]
```

Success Response

```
{
   "status": 200,
   "message": "Customer(s) updated successfully",
   "data": [
       {
           "index": 0,
           "referenceId": "65ba00dbdcf04fb789311df6aa40e3ba"
       }
   ],
   "hasError": false
}
```

Partial Success Response

```
{
```

```
    "status": 207,
    "message": "Customer(s) updated partially",
    "moreResultsExists": false,
    "data": [
        {
            "index": 0,
            "referenceId": "3a973fdcb1eb41d5ad7408c57e13cc87"
        }
    ],
    "error": [
        {
            "index": 1,
            "errorList": [
                {
                    "key": "referenceId",
                    "message": [
                        "Reference Id does not exists"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Failure Response

```
{
    "status": 409,
    "message": "Customer(s) updation failed",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "errorList": [
                {
                    "key": "referenceId",
                    "message": [
                        "Reference Id does not exists"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Update an existing customer in the LogiNext system with this API.

- This API updates a customer entity with the details provided. It identifies customers using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Customer API response when the associated customer is created in the system.
- This API only accepts inputs if you have enabled the Customer Profiling property within the LogiNext system.

API TYPE

- Tier 1 API.
- Client Rate Limit: 5 requests per second.
- Branch Rate Limit: 2 requests per second.
- You can update a maximum of 5 existing customers in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ClientApp/customer/v1/update`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceID	String	32	Mandatory	Unique reference identifier associated with the customer whose information you want to retrieve.
accountCode	String	50	Optional	Unique identifier associated with the customer.
name	String	255	Optional	Name of the customer.
mobile	String	255	Optional	Contact number of the customer.
email	String	255	Optional	Email ID of the customer.
customerType	String	255	Optional	Type of customer just in case you want to categorize your customers into different groups. For example, you can create 'Premium' customers and identify them in LogiNext based on values in this field.
billingAddress.apartment	String	40	Optional	Name of the apartment building/complex in the customer's billing address.
billingAddress.streetName	String	100	Optional	Name of the society or street in the customer's billing address.
billingAddress.landmark	String	255	Optional	Landmark of the customer's billing location.
billingAddress.locality	String	255	Optional	Name of the locality or area in the customer's billing address.
billingAddress.city	String	20	Optional	Name of the city in the customer's billing address.
billingAddress.state	String	20	Optional	Name of the state in the customer's billing address. This should be as per the State Codes available in the LogiNext system for the selected country.
billingAddress.country	String	255	Optional	Name of the country in the customer's billing address. This should be as per the Country Codes available in the LogiNext system.
billingAddress.pincode	String	255	Optional	Pin code of the customer's billing location.
billingAddress.latitude	Double	20	Optional	Latitude coordinates of the customer's billing address.
billingAddress.longitude	Double	20	Optional	Longitude coordinates of the customer's billing address.
clientCode	String	50	Optional	Name of the company associated with the shipper's account. Pass the company name of the shipper's account if you want to update a customer entity on behalf of one of your shippers.
whatsappOptin	Boolean	NULL	Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.

Address

CREATE

Sample Request

```
[
  {
    "customerReferenceId":"65ba00dbdcf04fb789311df6aa40e3ba",
    "addressId":"HomeAdd",
    "addressType":"Home",
    "addressServiceTime":"5",
    "breakTime":[
      {
        "startTime":"10:00",
        "endTime":"11:30"
      },
      {
        "startTime":"12:00",
        "endTime":"13:30"
      },
      {
        "startTime":"18:00",
        "endTime":"19:00"
      }
    ],
    "preferredStartTime":"11:30",
    "preferredEndTime":"21:30",
    "weeklyOffList":["SUNDAY","WEDNESDAY"],
    "address":{
          "apartment":"1901 Wes",
          "streetName":"t Madison Street",
          "landmark":"United Center",
          "locality":"Dowtown Chicago",
          "city":"Chicago",
          "state":"IL",
          "country":"USA",
          "pincode":"60612",
          "latitude": 41.8807,
          "longitude": -87.6742
    },
    "additionalContactDetails": [
            {
                "name": "James Smith",
                "mobileNumber": "18552306564",
                "whatsappOptin":"Y",
                "emailAddress": "james@ablogistics.com"
            },
            {
                "name": "John Barnes",
                "mobileNumber": "18552306565",
                "whatsappOptin":"Y",
                "emailAddress": "john@ablogistics.com"
            }
        ],
    "isPrimary":"Y",
    "clientCode":"MyKart",
    "timeZone":"America/Chicago"
  }

]
```


Success Response


```
  {
    "status": 200,
    "message": "Address(s) created successfully",
    "data": [
        {
```

```
            "index": 0,
            "addressId":"HomeAdd",
            "referenceId": "6a34c7274df0489f97c0f891514b488b",
            "customerReferenceId": "65ba00dbdcf04fb789311df6aa40e3ba"
        }
    ],
    "hasError": false
}
```


Failure Response


```
{
    "status": 409,
    "message": "Address creation failed",
    "moreResultsExists": false,
    "error": [
        {
            "errorList": [
                {
                    "key": "whatsappOptin",
                    "message": [
                        "Invalid Whatsapp Optin."
                    ],
                    "errorcode": 42020
                }
            ]
        }
    ],
    "hasError": true
}
```


Create new addresses of existing customers in the LogiNext system with this API.

- This API creates new shipping addresses of existing customers and assigns a unique reference ID to each address for future identification.
- Call this API along with the provided parameters to push existing addresses from your current system to LogiNext.
- This API will only accept inputs if you have enabled the Customer Profiling property within the LogiNext system.
- Note that the address field validations are based on the settings configured in the Address Format Configuration within the LogiNext system.
- You can only add a maximum of 5 additional contacts to each address.

API TYPE

- Tier 1 API.
- Client Rate Limit: 5 requests per second.
- Branch Rate Limit: 1 request per second.
- You can create a maximum of 5 addresses in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ClientApp/address/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
customerReferenceId	String	32	Mandatory	Unique reference identifier of a customer for whom you are creating the address.
addressId	String	255	Optional	Unique identifier associated with the customer address. This ID is used to identify the address of a customer. Every address will have a unique ID even if a single customer has multiple addresses tagged to them.

addressType	String	255	Optional	Type of address, i.e., Home, Office, or Other.
addressServiceTime	String	255	Optional	Time taken (in minutes) to service the customer at this particular address.
breakTime.startTime	String	255	Conditional Mandatory	Start time (in HH:MM format) when the customer is unavailable. This field is mandatory if the break end time is provided.
breakTime.endTime	String	40	Conditional Mandatory	End time (in HH:MM format) of the customer break. This field is mandatory if the break start time is provided.
preferredStartTime	String	100	Optional	Start time (in HH:MM format) when the customer prefers the pickup/delivery to be initiated. This will be considered during planning pickups/deliveries at the address location.
preferredEndTime	String	255	Optional	End time (in HH:MM format) when the customer prefers the pickup/delivery to happen. This will be considered during planning pickups/deliveries at the address location.
weeklyOffList	LIST	255	Mandatory	The days on which the customer will not be available at the address.
address.city	String	20	Mandatory	Name of the city in the customer address.
address.state	String	20	Optional	Name of the state in the customer address. This should be as per the State Codes available in the LogiNext system for the selected country.
address.country	String	255	Optional	Name of the country in the customer's address. This should be as per the Country Codes available in the LogiNext system.
address.pincode	String	255	Optional	Pin code of the customer's location.
address.latitude	Double	20	Optional	Latitude coordinates of the customer's address.
address.longitude	Double	20	Optional	Longitude coordinates of the customer's address.
additionalContactDetails.name	String	255	Conditional Mandatory	Name of the additional contact person. This field is required if the additional Contact Details object is being passed.
additionalContactDetails.mobileNumber	String	20	Conditional Mandatory	Mobile number of the additional contact person. Note that if you have provided the name of the additional contact person, it is mandatory to add either a mobile number or email ID of that person.
additionalContactDetails.emailAddress	String	255	Conditional Mandatory	Email ID of the additional contact person. Note that if you have provided the name of the additional contact person, it is mandatory to add either a mobile number or email ID of that person.
additionalContactDetails.whatsappOptin	Boolean	Null	Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
				Whether this address is the primary address of the customer. Specify this parameter as 'Y' if you want to

isPrimary	String	1	Optional	mark this address as primary or 'N' if you do not want to mark it as primary. In the case of multiple customer addresses, you can only mark one active address for each customer as a primary address. If you specify only one address for a customer, it is mandatory to mark that address as primary; if not, you will receive a validation error.Note that the primary address would be considered if you do not pass the Address ID and only include the Customer ID in the accountCode field when creating orders using API, i.e., no additional identifier is required for the address.
clientCode	String	50	Optional	Name of the company associated with the shipper's account. Pass the company name of the shipper's account if you want to create a customer address on behalf of one of your shippers.
timeZone	String		Optional	Timezone of the customer's address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.

UPDATE

Sample Request

```
 [
{ "addressReferenceId": "65ba00dbdcf04fb789311df6aa40e3ba",
 "addressType":"Home",
 "addressServiceTime":"5",
 "breakTime":[
    {
    "startTime":"10:00",
    "endTime":"11:30"
    },
    { "startTime":"12:00",
     "endTime":"13:30"
    },
    {
    "startTime":"18:00",
    "endTime":"19:00"
    }
  ],
  "preferredStartTime":"11:30",
  "preferredEndTime":"21:30",
  "weeklyOffList":["SUNDAY","WEDNESDAY"],
  "address":{
     "apartment":"1901 Wes",
          "streetName":"t Madison Street",
          "landmark":"United Center",
          "locality":"Dowtown Chicago",
          "city":"Chicago",
          "state":"IL",
          "country":"USA",
          "pincode":"60612",
          "latitude": 41.8807,
          "longitude": -87.6742
  },
  "isPrimary":"Y",
  "clientCode":"MyKart",
  "timeZone":"America/Chicago"
  }
]
```

Success Response

```
{
  "status": 200,
  "message": "Address(s) updated successfully",
  "data": [
      {
          "index": 0,
          "addressId":"HomeAdd",
          "referenceId": "6a34c7274df0489f97c0f891514b488b",
          "customerReferenceId": "65ba00dbdcf04fb789311df6aa40e3ba"
      }
  ],
  "hasError": false
}
```

Failure Response

```
{
  "status": 409,
  "message": "Address(s) updation failed",
  "moreResultsExists": false,
  "error": [
      {
          "index": 0,
          "errorList": [
              {
                  "key": "addressReferenceId",
                  "message": [
                      "No address found for referenceId"
                  ]
              }
          ]
      }
  ],
  "hasError": true
}
```

Update an existing customer address with this API.

- This API updates a customer's address with the provided details. It identifies addresses using the Address Reference ID field generated within the LogiNext system. This ID is provided in the Create Address API response when the associated address is created in the system.
- This API only accepts inputs if you have enabled the Customer Profiling property within the LogiNext system.
- Note that the address field validations are based on the settings configured in the Address Format Configuration within the LogiNext system.

API TYPE

- Tier 1 API.
- Client Rate Limit: 5 requests per second.
- Branch Rate Limit: 1 request per second.
- You can only update one customer address in one call of this API, i.e., this API does not support batch operations.

REQUEST

POST `https://api.loginextsolutions.com/ClientApp/address/v1/update`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description

addressReferenceId	String	32	Mandatory	Unique reference identifier associated with the customer's address. This ID is used to identify the address of a customer that you want to update.
addressType	String	255	Optional	Type of address, i.e., Home, Office, or Other.
addressServiceTime	String	255	Optional	Time taken (in minutes) to service the customer at this particular address.
breakTime.startTime	String	255	Conditional Mandatory	Start time (in HH:MM format) when the customer is unavailable. This field is mandatory if the break end time is provided.
breakTime.endTime	String	40	Conditional Mandatory	End time (in HH:MM format) of the customer break. This field is mandatory if the break start time is provided.
preferredStartTime	String	100	Optional	Start time (in HH:MM format) when the customer prefers the pickup/delivery to be initiated. This will be considered during planning pickups/deliveries at the address location.
preferredEndTime	String	255	Optional	End time (in HH:MM format) when the customer prefers the pickup/delivery to happen. This will be considered during planning pickups/deliveries at the address location.
weeklyOffList	LIST	255	Optional	The days on which the customer will not be available at the address.
address.city	String	20	Optional	Name of the city in the customer address.
address.state	String	20	Optional	Name of the state in the customer address. This should be as per the State Codes available in the LogiNext system for the selected country.
address.country	String	255	Optional	Name of the country in the customer's address. This should be as per the Country Codes available in the LogiNext system.
address.pincode	String	255	Optional	Pin code of the customer's location.
address.latitude	Double	20	Optional	Latitude coordinates of the customer's address. If the geo-coordinates are passed, then the address will not be geocoded.
address.longitude	Double	20	Optional	Longitude coordinates of the customer's address. If the geo-coordinates are passed, then the address will not be geocoded.
isPrimary	String	1	Optional	Whether this address is the primary address of the customer. Specify this parameter as 'Y' if you want to mark this address as primary or 'N' if you do not want to mark it as primary. In the case of multiple customer addresses, you can only mark one active address for each customer as a primary address. If you specify only one address for a customer, it is mandatory to mark that address as primary; if not, you will receive a validation error. Note that the primary address would be considered if you do not pass the Address ID and only include the Customer ID in the accountCode field when creating orders using API, i.e., no additional identifier is required for the address.
clientCode	String	50	Optional	Name of the company associated with the shipper's account. Pass the company name of the shipper's account if you want to update a customer address on behalf of one of your shippers.
timeZone	String		Optional	Timezone of the customer's address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.

Shipper

CREATE

Sample Request

```
[
    {
        "shipperName": "Fresh Farm Produce Ltd.",
        "adminContactName": "John Doe",
        "emailAddress": "johnDoe@freshfarm.com",
        "contactNumber": "334567781",
        "userName": "jack.klien@freshfarm.com",
        "branchName":"Marque Downtown Chicago",
        "priority": "high",
        "customerSupportNumber": "5163063377",
        "customerSupportEmail": "support@freshfarm.com",
        "serviceType": ["Express", "Express Plus"],
        "whatsappOptin":"Y",
        "serviceAreaProfileName": "New York City Profile",
        "rateChartName": "Standard Rate Chart",
        "address":{
                "apartment":"Suite No. 99, Milsons Towers",
                "streetName":"Michigan Avenue",
                "landmark":"Opp. Subway",
                "locality":"Downtown Chicago",
                "city":"Chicago",
                "stateShortCode":"IL",
                "countryShortCode":"USA",
                "pincode":"60606",
                "longitude": 40.760838,
                "latitude": 74.9095327
        },
        "billingContactName":"Karen",
        "billingPhoneNumber":"5163063377",
        "billingEmailAddress":"karen@freshfarm.com",
        "billingAddress":{
                "apartment":"Suite No. 99, Milsons Towers",
                "streetName":"Michigan Avenue",
                "landmark":"Opp. Subway",
                "locality":"Downtown Chicago",
                "city":"Chicago",
                "stateShortCode":"IL",
                "countryShortCode":"USA",
                "pincode":"60606"
        },
         "additionalContactDetails": [{
            "contactName": "Mary Joe",
            "contactMobileNumber": "53626365353",
            "whatsappOptin": "Y"
        },{
            "contactName": "Don Joe",
            "contactMobileNumber": "53626365354",
            "contactEmail": "donJoe@mail.com",
            "whatsappOptin": "Y"
        }]
    }
]
```

Success Response

```
{
    "status": 200,
    "message": "Shipper created successfully",
    "data": [
        {
            "referenceId": "6a34c7274df0489f97c0f891514b488b"
        },
    ],
    "hasError": false
}
```


Failure Response


```
{
    "status": 409,
    "message": "Shipper Creation Failed",
    "moreResultsExists": false,
    "error": {
        "shipper_0": [
            {
                "key": "emailAddress",
                "message": [
                    "Email Id is mandatory."
                ],
                "codes": [
                    "10001"
                ]
            },
            {
                "key": "serviceType",
                "message": [
                    "Service Type is invalid"
                ],
                "codes": [
                    "92010"
                ]
            },
            {
                "key": "whatsappOptin",
                "message": [
                    "Whatsapp Optin is invalid."
                ],
                "errorCode": 42020
            },

        ]
    },
    "hasError": true
},
{
    "status": 400,
    "message": "Bad Request",
    "moreResultsExists": false,
    "hasError": true
}
```


Create new shippers in the LogiNext system with this API.

- This API creates a Shipper entity and assigns a unique Reference ID that can be used to identify the shipper later.
- Call this API along with the provided parameters to push/sync existing shippers from your current (CRM or CX) system to LogiNext.
- While creating a new shipper, you can also create a user who can access the Shipper Web App by passing the username in the 'userName' field.

- Additionally, you can include the Shipping Address (shipper's organization address) and Billing Address details in the same API request for auditing and invoicing purposes.
- Note that the address field validations are based on the settings configured in the Address Format Configuration module within the LogiNext system.

API TYPE

- Tier 1 API.
- You can create one shipper in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ClientApp/v1/shipper/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
shipperName	String	255	Mandatory	Name of the Shipper.
adminContactName	String	255	Mandatory	Name of the primary contact person in the organization.
emailAddress	String	255	Mandatory	Email ID of the primary contact person in the organization.
contactNumber	String	255	Mandatory	Contact number of the shipper on which SMS notifications can be sent.
userName	String	255	Optional	Username (i.e., Email ID) that the shipper would use to log into the Shipper Web App. **Note:** This will create a user that can access the Shipper Web App. Skip this if you don't want the shipper to use the Shipper Web App.
branchName	String	255	Mandatory	Branch with which you want to map the new shipper.
priority	String	16	Optional	Priority value applicable to the orders created for this shipper. Note that the priority set when creating an order will precede the priority allotted to a shipper.
customerSupportNumber	String	255	Optional	This is the shipper's customer helpline number which their customers can reach out for any queries/issues. If not provided, the parent branch's support number will be considered as a fallback. In case the support number isn't available at the branch level either, then the support number set at the organization level will be considered.
customerSupportEmail	String	255	Optional	This is the shipper's customer support email ID which their customers can write to for any queries/issues. If not provided, the parent branch's support email will be considered as a fallback. In case the support email isn't available at the branch level either, then the support email set at the organization level will be considered.
serviceType	String	255	Optional	Service Types applicable for this shipper. You can provide multiple service types in the comma-separated format. Only the Service Types provided here will be displayed to the shipper on the Shipper Web App.
serviceAreaProfileName	String	255	Conditional Mandatory	Service Area Profile for this shipper that will govern the serviceability of the pickup/delivery locations at the time of order request creation, i.e., the order request created by the shipper should have a pickup/delivery location within this Service Area Profile.

rateChartName	String	255	Conditional Mandatory	Rate Chart applicable for this shipper. The shipping cost calculated for the shipper is based on the selected Rate Chart. Note that providing a Service Area Profile is mandatory for selecting a rate chart.
Address.apartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the shipper's shipping address. For example - A 203 Richmond Avenue.
Address.streetName	String	255	Conditional Mandatory	Name of the society or street in the shipper's shipping address. For example - Off Highway I96 or Walton Boulevard.
Address.landmark	String	512	Conditional Mandatory	Landmark of the shipper's shipping location. For example - Behind XYZ Hospital.
Address.locality	String	512	Conditional Mandatory	Name of the locality or area in the shipper's shipping address. For example - Southern Industry Park or Dubai Downtown.
Address.city	String	512	Conditional Mandatory	Name of the city in the shipper's shipping address. For example - Atlanta or Kuala Lumpur.
Address.stateShortCode	String	11	Conditional Mandatory	Name of the state in the shipper's shipping address. This should be as per the State Codes available in the LogiNext system for the selected country. If you think that the specific region in which you operate does not have States/Provinces, then raise the support request with your Account Manager to make this non-mandatory.
Address.countryShortCode	String	11	Conditional Mandatory	Name of the country in the shipper's shipping address. This should be as per the Country Codes available in the LogiNext system. For example - For the United States, use USA.
Address.pincode	String	20	Conditional Mandatory	Pin code of the shipper's location. For example - 72712. If you think that the specific region in which you operate does not have postal codes, then raise the support request with your Account Manager to make this non-mandatory.
longitude	Double	15	Optional	Longitude coordinates of the shipper's shipping address.
latitude	Double	15	Optional	Latitude coordinates of the shipper's shipping address.
billingContactName	String	512	Mandatory	Name of the contact person at the shipper's billing location.
billingEmailAddress	String	255	Mandatory	Email ID of the contact person at the shipper's billing location.
billingPhoneNumber	String	20	Optional	Phone number of the contact person at the shipper's billing location.
billingAddress.apartment	String	512	Optional	Name of the apartment building/complex in the shipper's billing address.
billingAddress.streetName	String	255	Optional	Name of the society or street in the shipper's billing address.
billingAddress.landmark	String	512	Optional	Landmark of the shipper's billing location.
				Name of the locality or area in the shipper's billing

billingAddress.locality	String	512	Optional	address.
billingAddress.city	String	512	Optional	Name of the city in the shipper's billing address.
billingAddress.stateShortCode	String	11	Optional	Name of the state in the shipper's billing address. This should be as per the State Codes available in the LogiNext system for the selected country. If you think that the specific region in which you operate does not have States/Provinces, then raise the support request with your Account Manager to make this non-mandatory.
billingAddress.countryShortCode	String	11	Optional	Name of the country in the shipper's billing address. This should be as per the Country Codes available in the LogiNext system. For example - For India, use IND; For China, use CHN.
billingAddress.pincode	String	20	Optional	Pin code of the shipper's billing location.
additionalContactDetails.name	String	255	Conditional Mandatory	Name of the additional contact person being added. This field is required if the additional Contact Details object is being passed.
additionalContactDetails.mobileNumber	String	20	Conditional Mandatory	Mobile Number of the additional contact person being added. Either Mobile Number or email is mandatory if name is passed.
additionalContactDetails.emailAddress	String	255	Conditional Mandatory	Email ID of the additional contact person being added. Either Mobile Number or email is mandatory if name is passed.
additionalContactDetails.whatsappOptin	Boolean	NULL	Optional	Whether the shipper has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.

UPDATE

Sample Request

```
[
    {
    "referenceId": "6a34c7274df0489f97c0f891514b488b",
    "shipperName": "Fresh Farm Produce Ltd.",
    "adminContactName": "John Doe",
    "contactNumber": "334567781",
    "priority": "high",
    "customerSupportNumber": "5163063377",
    "customerSupportEmail": "support@freshfarm.com",
    "emailAddress":"superjames@gmails.com",
    "serviceType": ["Express", "Express Plus"],
    "whatsappOptin":"Y",
    "serviceAreaProfileName": "New York City Profile",
    "rateChartName": "Standard Rate Chart",
    "address":{
            "apartment":"Suite No. 99, Milsons Towers",
            "streetName":"Michigan Avenue",
            "landmark":"Opp. Subway",
            "locality":"Downtown Chicago",
            "city":"Chicago",
            "stateShortCode":"IL",
            "countryShortCode":"USA",
            "pincode":"60606",
            "longitude": 40.760838,
```

```
            "latitude": 74.9095327
    },
    "billingContactName":"Karen",
    "billingPhoneNumber":"5163063377",
    "billingEmailAddress":"karen@freshfarm.com",
    "billingAddress":{
            "apartment":"Suite No. 99, Milsons Towers",
            "streetName":"Michigan Avenue",
            "landmark":"Opp. Subway",
            "locality":"Downtown Chicago",
            "city":"Chicago",
            "stateShortCode":"IL",
            "countryShortCode":"USA",
            "pincode":"60606"
    },
    "additionalContactDetails": [{
                "contactName": "Mary Joe",
                "contactMobileNumber": "53626365353",
                "whatsappOptin": "Y"
            },{
                "contactName": "Don Joe",
                "contactMobileNumber": "53626365354",
                "contactEmail": "donJoe@mail.com",
                "whatsappOptin": "Y"

            }
        ]
    }
]
```


Success Response


```
{
    "status": 200,
    "message": "Shipper updated successfully",
    "data": [
        {
            "referenceId": "6a34c7274df0489f97c0f891514b488b"
        },
    ],
    "hasError": false
}
```


Failure Response


```
{
         "status": 409,
          "message": "Shipper Updation Failed",
"moreResultsExists": false,
"error": [
        {
            "index": 0,
            "errorList": [
                {
                    "key": "serviceAreaProfileName",
                    "message": [
                        "Service Area Profile is invalid"
                    ]
                },
                {
                    "key": "whatsappOptIn",
                    "message": [
```

```
                        "Service Area Profile is invalid"
                    ]
                },
                {
                    "key": "whatsappOptIn",
                    "message": [
                        "Whatsapp Optin is invalid"
                    ],
                    "errorcode": 42020
                },

            ]
        }
    ],
    "hasError": true
}
```


Update an existing shipper with this API.

- This API updates a shipper entity with the details provided. It identifies shippers using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Shipper API response when the associated shipper is created in the system.
- You can provide the Shipping Address and Billing Address details in the same API request for auditing and invoicing purposes.

API TYPE

- Tier 1 API.
- You can update only one shipper in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ClientApp/v1/shipper/update`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceId	String	32	Mandatory	Unique reference identifier associated with the shipper. This ID is used to identify the shipper that you want to update.
shipperName	String	255	Optional	Name of the shipper’s organization.
adminContactName	String	255	Mandatory	Name of the primary contact person in the organization.
emailAddress	String	255	Optional	Email ID of the primary contact person in the organization.
contactNumber	String	255	Optional	Contact number of the shipper.
priority	String	16	Optional	Priority value applicable to the orders created for this shipper. Note that the priority set when creating an order will precede the priority allotted to a shipper.
customerSupportNumber	String	255	Optional	This is the shipper’s customer helpline number which their customers can reach out for any queries/issues. If not provided, the parent branch's support number will be considered as a fallback. In case the support number isn’t available at the branch level either, then the support number set at the organization level will be considered.
customerSupportEmail	String	255	Optional	This is the shipper’s customer support email ID which their customers can write to for any queries/issues. If not provided, the parent branch’s support email will be

				considered as a fallback. In case the support email isn't available at the branch level either, then the support email set at the organization level will be considered.
serviceType	String	255	Optional	Service Types applicable for this shipper. You can provide multiple service types in the comma-separated format. Only the Service Types provided here will be displayed to the shipper on the Shipper Web App.
serviceAreaProfileName	String	255	Conditional Mandatory	Service Area Profile for this shipper that will govern the serviceability of the pickup/delivery locations at the time of order request creation, i.e., the order request created by the shipper should have a pickup/delivery location within this Service Area Profile.
rateChartName	String	255	Conditional Mandatory	Rate Chart applicable for this shipper. The shipping cost calculated for the shipper is based on the selected Rate Chart. Note that providing a Service Area Profile is mandatory for selecting a rate chart.
Address.apartment	String	512	Mandatory	Name of the apartment building/complex in the shipper's address. For example - A 203 Richmond Avenue.
Address.streetName	String	255	Mandatory	Name of the society or street in the shipper's address. For example - Off Highway I96 or Walton Boulevard.
Address.landmark	String	512	Mandatory	Landmark of the shipper's location. Behind XYZ Hospital.
Address.locality	String	512	Mandatory	Name of the locality or area in the shipper's address. For example - Southern Industry Park or Dubai Downtown.
Address.city	String	512	Mandatory	Name of the city in the shipper's address. For example - Atlanta or Kuala Lumpur.
Address.stateShortCode	String	11	Optional	Name of the state in the shipper's address. This should be as per the State Codes available in the LogiNext system for the selected country. If you think that the specific region in which you operate does not have States/Provinces, then raise the support request with your Account Manager to make this non-mandatory.
Address.countryShortCode	String	11	Optional	Name of the country in the shipper's address. This should be as per the Country Codes available in the LogiNext system. For example - For the United States, use USA.
Address.pincode	String	20	Optional	Pin code of the shipper's location. For example - 72712. If you think that the specific region in which you operate does not have postal codes, then raise the support request with your Account Manager to make this non-mandatory.
longitude	Double	15	Optional	Longitude coordinates of the shipper's shipping address
latitude	Double	15	Optional	Latitude coordinates of the shipper's shipping address.
billingContactName	String	512	Mandatory	Name of the contact person at the shipper's billing location.
billingEmailAddress	String	255	Mandatory	Email ID of the contact person at the shipper's billing location.
billingPhoneNumber	String	20	Optional	Phone number of the contact person at the shipper's billing location.

billingAddress.apartment	String	512	Optional	Name of the apartment building/complex in the shipper's billing address.
billingAddress.streetName	String	255	Optional	Name of the society or street in the shipper's billing address.
billingAddress.landmark	String	512	Optional	Landmark of the shipper's billing location.
billingAddress.locality	String	512	Optional	Name of the locality or area in the shipper's billing address.
billingAddress.city	String	512	Optional	Name of the city in the shipper's billing address.
billingAddress.stateShortCode	String	11	Optional	Name of the state in the shipper's billing address. This should be as per the State Codes available in the LogiNext system for the selected country. If you think that the specific region in which you operate does not have States/Provinces, then raise the support request with your Account Manager to make this non-mandatory.
billingAddress.countryShortCode	String	11	Optional	Name of the country in the shipper's billing address. This should be as per the Country Codes available in the LogiNext system. For India, use IND; For China, use CHN.
billingAddress.pincode	String	20	Optional	Pin code of the shipper's billing location.
additionalContactDetails.emailAddress	String	255	Conditional Mandatory	Email ID of the additional contact person being added. Either Mobile Number or email is mandatory if name is passed.
additionalContactDetails.name	String	255	Conditional Mandatory	Name of the additional contact person being added. This field is required if the additional Contact Details object is being passed.
additionalContactDetails.mobileNumber	String	20	Conditional Mandatory	Mobile Number of the additional contact person being added. Either Mobile Number or email is mandatory if name is passed.
additionalContactDetails.whatsappOptin	Boolean	NULL	Optional	Whether the shipper has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.

Delivery Associate

CREATE

Sample Request

```
[
    {
        "employeeId":"ALL123469",
        "userGroupName":"MobileUser",
        "branchName":"California",
        "deliveryMediumMasterName":"James",
        "phoneNumber":9892147969,
        "imei":123456789012123,
```

```
        "emailId":"james@ablogistics.com",
        "userName":"james003",
        "password":"admin",
        "capacityInUnits":10,
        "capacityInVolume":10,
        "capacityInWeight":10,
        "minCapacityUtilizationInUnits" : 30,
        "minCapacityUtilizationInWeight" : 30,
        "minCapacityUtilizationInVolume" : 75,
        "dob":"2016-12-12",
        "gender":"Male",
        "deliveryMediumMasterTypeCd": "Bakery",
        "vehicleNumber":"1AB54F",
        "isOwnVehicleFl":"Company",
        "maxDistance":10,
        "dmPreference":"10035",
        "maritalStatus":"Single",
        "alternateMobileNo":9892134489,
        "landlineNo":28215678,
        "licenseValidity":"2026-12-12",
        "licenseValidityInYears":10,
        "licenseIssuanceDate":"2016-12-12",
        "licenseNumber":2123123123,
        "loadingTimeInMins": 20,
        "unloadingTimeInMins": 20,
        "fixedCost":10,
        "variableCost":10,
        "isPresentFl":"Y",
        "weeklyOffList": [
            "Thursday",
            "Monday"
        ],
        "deliveryMediumMapList": [
            {
                "name": "SPANISH"
            },
            {
                "name": "ENGLISH"
            }
        ],
        "shiftTimeList": [
            {
                "shiftStartTime": "12:30",
                "shiftEndTime": "14:30"
            }
        ],
        "breakTimeList": [
            {
                "breakStartTime": "13:00",
                "breakEndTime": "13:30",
                "breakDurationInMins": 12
            }
        ],
        "addressList": [
            {
                "apartment":"901",
                "streetName":"2142 3rd Ave",
                "landmark":"Opp. McDonalds",
                "countryShortCode":"USA",
                "city":"Ney York",
                "pincode":"10035",
                "addressType":"PERMANENT"
            },
            {
                "apartment":"901",
                "streetName":"2142 3rd Ave",
```

```
                "landmark":"Opp McDonalds",
                "countryShortCode":"USA",
                "city":"New York",
                "pincode":"10035",
                "addressType":"CURRENT"
            }
        ]
    }
]
```


Success Response


```
{
  "status": 201,
  "message": "success",
  "moreResultsExists": false,
  "data": [
    "d7b0f3f8e1174742bd6a8ae451866cb1"
  ],
  "hasError": false
}
```


Failure Response 1


```
{
    "status": 400,
    "message": "Some issue encountered in server",
    "moreResultsExists": false,
    "error": {
        "deliverymedium_0": [
            {
                "key": "employeeId",
                "message": [
                    "Employee Id is required"
                ]
            }
        ],
        "deliverymedium_1": [
            {
                "key": "emailId",
                "message": [
                    "Invalid Email"
                ]
            }
        ]
    },
    "hasError": true
}
```


Failure Response 2


```
{
    "status": 400,
    "message": "Some issue encountered in server",
    "moreResultsExists": false,
    "error": [
        {
            "key": "Invalid client branch name(s) found.",
            "message": [
                "PowaiSd"
```

```
            ]
        },
        {
            "key": "Invalid usergroup name(s) found.",
            "message": [
                "Mobil"
            ]
        },
        {
            "key": "Invalid delivery types(s) found.",
            "message": []
        },
        {
            "key": "Invalid pincodes.",
            "message": [
                "14252"
            ]
        },
        {
            "key": "Invalid country code(s) found.",
            "message": []
        }
    ],
    "hasError": true
}
```


Create new delivery associates in the LogiNext system with this API.

- This API creates a Delivery Associate entity and assigns a unique Reference ID that can be used to identify the delivery associate later.
- Call this API along with the provided parameters to push existing delivery associates from your current system to LogiNext.
- Note that the address field validations are based on the settings configured in the Address Format Configuration module within the LogiNext system.

API TYPE

- Tier 1 API.
- You can create a maximum of 20 delivery associates in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/DeliveryMediumApp/mile/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
employeeId	String	50	Mandatory	Employee ID of the delivery associate.
userGroupName	String	255	Mandatory	The User Group or Role that the delivery associate would belong to. The delivery associate would have all the accesses on the Driver App that are granted to this user group.
branchName	String	255	Mandatory	Branch with which the delivery associate should be linked.
deliveryMediumMasterName	String	50	Mandatory	Full name of the delivery associate.
phoneNumber	String	18	Mandatory	Mobile number of the delivery associate.
imei	String	40	Optional	IMEI number of the delivery associate’s phone.
emailId	String	100	Optional	Email ID of the delivery associate.
				Username using which the delivery associate would log into the

userName	String	25	Mandatory	Driver App.
password	String	255	Mandatory	Password that the delivery associate would need to log into the Driver App.
capacityInUnits	Integer	20	Mandatory	Capacity in terms of order/crate units that the delivery associate can carry in a trip.
capacityInVolume	Integer	20	Optional	Capacity in terms of volume that the delivery associate can carry in a trip.
capacityInWeight	Integer	20	Optional	Capacity in terms of weight that the delivery associate can carry in a trip.
minCapacityUtilizationInUnits	Integer	20	Optional	Minimum percentage capacity utilization in terms of order/crate units that the delivery associate must carry at the start of the trip. The percentage defined cannot be greater than 100.
minCapacityUtilizationInWeight	Integer	20	Optional	Minimum percentage capacity utilization in terms of volume that the delivery associate must carry at the start of the trip.The percentage defined cannot be greater than 100.
minCapacityUtilizationInVolume	Integer	20	Optional	Minimum percentage capacity utilization in terms of weight that the delivery associate must carry at the start of the trip.The percentage defined cannot be greater than 100.
dob	String		Optional	Date of birth of the delivery associate in YYYY-MM-DD format.
gender	ISODate	12	Optional	Gender of the delivery associate. For example - Male, Female.
deliveryMediumMasterTypeCd	String	255	Optional	Skill Sets that the delivery associate possesses to carry out specific orders. For example, you can specify 'Bakery' if your delivery associate can fulfill bakery type of orders or 'Groceries' if your delivery associate can fulfill groceries type of orders. This is mapped to the 'deliveryType' field at the order level.
vehicleNumber	String	255	Optional	Number of the vehicle that should be linked with the delivery associate.
isOwnVehicleFl	String	1	Optional	Whether the vehicle is owned by the delivery associate or by the company.
maxDistance	Integer	20	Optional	Maximum distance that the delivery associate can travel in a trip, from the branch till the last order’s pickup/delivery location. This property can be considered in Trip Planning.
dmPreference	String	255	Optional	Specific postal codes that should be allocated to a delivery associate for pickups/deliveries. The Trip Planning engine will consider this pincode preference when assigning orders to the delivery associate if the Pin Code Preference property is set. Note that this may lead to less optimized planning.
maritalStatus	String	255	Optional	Marital status of the delivery associate.
alternateMobileNo	String	255	Optional	Alternate mobile number of the delivery associate if they carry an additional mobile phone.
landlineNo	String	255	Optional	Fixed line contact number of the delivery associate.
				Date (in YYYY-MM-DD format) on which the delivery associate’s

licenseValidity	String	255	Optional	license would expire.
licenseValidityInYears	String	255	Optional	Years for which the license is valid.
licenseIssuanceDate	String	255	Optional	Date in (YYYY-MM-DD format) when the license was issued for the delivery associate.
licenseNumber	String	255	Optional	License number of the delivery associate in an alphanumeric format.
loadingTimeInMins	Integer	32	Optional	Average time taken by the delivery associate to load all the orders of a trip in their vehicle. This property can be considered in Trip Planning. This can be different for different types of fleets. A larger vehicle may require more time to load, whereas a small vehicle may require only a few minutes.
unloadingTimeInMins	Integer	32	Optional	Average time taken by the delivery associate to unload all the orders of a trip from the vehicle. This property can be considered in Trip Planning. This can be different for different types of fleets. A larger vehicle may require more time to load, whereas a small vehicle may require only a few minutes.
fixedCost	Number	9	Optional	Fixed cost for using the delivery associate. This is considered in Trip Planning when the Planning Objective is Optimize Fleet Capacity.
variableCost	Number	9	Optional	Variable cost associated with each unit of distance travelled by the delivery associate (i.e., per km cost). This is considered in Trip Planning when the Planning Objective is Optimize Fleet Capacity or Optimize Time and Distance.
isPresentFl	String	1	Optional	Whether the delivery associate is present on the day or not. Delivery associates can mark their attendance on the Driver App. You can also update the attendance records on your own. Specify this parameter as ‘Y’ if you want to mark the delivery associate as present or ‘N’ if you want to mark them as absent.
weeklyOffList	String	255	Optional	The day on which the delivery associate would be taking their weekly off. For example - Monday, Tuesday, etc.
deliveryMediumMapList.name	String	255	Optional	List of languages that the delivery associate is able to converse in.
shiftTimeList.shiftStartTime	String		Optional	Shift start time of the delivery associate in HH:MM format.
shiftTimeList.shiftEndTime	String		Optional	Shift end time of the delivery associate in HH:MM format.
breakTimeList	List		Optional	Time when the delivery associate is on break. The Trip Planning engine will not assign orders with service time windows that fall within a delivery associate's break time.
breakTimeList.breakStartTime	String		Optional	Start time (in HH:MM format) when the delivery associate is on break. This field is mandatory if the break end time is provided.
breakTimeList.breakEndTime	String		Optional	End time (in HH:MM format) of the delivery associate break. This field is mandatory if the break start time is provided.
breakTimeList.breakDurationInMins	Integer		Optional	Duration (in minutes) of the delivery associate’s break time.
			Conditional	Enter the address details of the delivery associate within this

addressList	List		Mandatory	parameter.
addressList.apartment	String	255	Optional	Name of the apartment building/complex in the delivery associate's address.
addressList.streetName	String	255	Optional	Name of the society or street in the delivery associate's address.
addressList.landmark	String	255	Optional	Landmark of the delivery associate's location.
addressList.countryShortCode	String	255	Optional	Name of the country in the shipper's billing address. This should be as per the Country Codes available in the LogiNext system.
addressList.city	String	255	Optional	Name of the city in the delivery associate's address.
addressList.pincode	String	255	Optional	Pin code of the delivery associate's location.
addressList.addressType	String	255	Conditional Mandatory	Whether the delivery associate's address is current or permanent. Specify this parameter as 'CURRENT' to mark the entered address as current or 'PERMANENT' to mark it as permanent. Note that you must provide this parameter if you are adding an address for the delivery associate. This field does not accept any other value.

GET

Sample Request

```
["d7f173453bab40cf83dc79bb86ea2edb"]
```

Success Response

```
{
    "status": 200,
    "moreResultsExists": false,
    "data": {
        "totalCount": 1,
        "otherCount": 0,
        "clientBranchId": 0,
        "results": [
            {
                "isActiveFl": true,
                "capacityInUnits": 10,
                "capacityInVolume": 100,
                "capacityInWeight": 1098,
                "deliveryMediumMasterTypeCd": "Truck",
                "imei": "873345632458765",
                "statusCd": "Available",
                "employeeId": "NBVA114",
                "weeklyOff": ["Monday"],
                "maxDistance": 100,
                "licenseValidity": "2018-12-20",
                "dob": "2000-12-01",
                "gender": "Male",
                "phoneNumber": "9215697602",
                "userName": "robin123456",
                "fleetType": "Truck",
                "shiftTimeList": [
                    {
```

```
                    "shiftStartTime": "12:30",
                    "shiftEndTime": "14:30"
                }
            ],
            "breakTimeList": [
                {
                    "breakStartTime": "13:00",
                    "breakEndTime": "13:30",
                    "breakDurationInMins": 12
                }
            ],
            "discardDm": false,
            "considerNearestTripFirstApplied": false,
            "consolidationApplied": false,
            "loadingTimeInMins": 20,
            "branchName": "Snappbox_UAT Main Branch",
            "userGroupName": "Snappbox_UAT Mob",
            "emailId": "abc@d.com",
            "languageList": [
                "HINDI",
                "ENGLISH"
            ],
            "dmPreference": "400010",
            "isOnBreakFl": "N",
            "deliveryMediumLoginDetails": {
                "type": "NOTLOGEDIN"
            },
            "pickupTimeInMinsFromMap": 0,
            "deliverTimeInMinsFromMap": 0,
            "alreadyOfferedCnt": 0,
            "profilePicture": "https://loginext-user-image.s3-ap-southeast-1.amazonaws.com/user32330_209.jpg?X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Date=2018062
            "deliveryMediumName": "Robin Jones",
            "cashPaid": 0,
            "cashCollected": 0,
            "cashBalance": 0,
            "referenceId": "fa7716b25fe5432a96d1a709a28bd6d8",
            "daFromIntransitSearch": false,
            "nearestDm": false,
            "coloaderDa": false
        }
    ]
},
"hasError": false
}
```


Retrieve details of required delivery associates using this API.

- This API retrieves the details of a delivery associate entity, including contact information, profile picture, capacity, and more.
- Include the Reference IDs or Username of the delivery associates you want to search for in the Request Body.
- This API retrieves the profile picture of your delivery associate if updated in the LogiNext system, via the 'profilePicture' field. This image can be displayed on your mobile application, allowing customers to see who is fulfilling their orders. Note that if you store this link in your system, this link has a lifetime of 1-hour post which it will expire and will need to be fetched again.

API TYPE

- Tier 1 API.

REQUEST

POST `https://api.loginextsolutions.com/DeliveryMediumApp/mile/v1/list`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description

referenceId	List	32	Conditional Mandatory	Unique reference identifier associated with the delivery associate whose information you want to retrieve. This ID is generated by the LogiNext system while creating a delivery associate to identify them for future reference. If the 'userName' is not provided, then this field is mandatory.
userName	List	50	Conditional Mandatory	Username associated with the delivery associate whose information you want to retrieve. If the 'referenceId' is not provided, then this field is mandatory.

UPDATE

Sample Request

```
[
  {
      "referenceId":"1cbc69c0fd3e6895acc50b60c93810ce",
      "employeeId":"ALL123469",
      "userGroupName":"MobileUser",
      "branchName":"California",
      "deliveryMediumMasterName":"James",
      "phoneNumber":9892147969,
      "imei":123456789012123,
      "emailId":"james@ablogistics.com",
      "password":"admin",
      "capacityInUnits":10,
      "capacityInVolume":10,
      "capacityInWeight":10,
      "dob":"2016-12-12",
      "gender":"Male",
      "deliveryMediumMasterTypeCd": "Bakery",
      "vehicleNumber":"1AB54F",
      "isOwnVehicleFl":"Company",
      "maxDistance":10,
      "dmPreference":"10035",
      "maritalStatus":"Single",
      "alternateMobileNo":9892134489,
      "landlineNo":28215678,
      "licenseValidity":"2026-12-12",
      "licenseValidityInYears":10,
      "licenseIssuanceDate":"2016-12-12",
      "licenseNumber":2123123123,
      "loadingTimeInMins": 20,
      "unloadingTimeInMins": 20,
      "fixedCost":10,
      "variableCost":10,
      "isPresentFl":"Y",
      "weeklyOffList": [
          "Thursday",
          "Monday"
      ],
      "deliveryMediumMapList": [
          {
              "name": "SPANISH"
          },
          {
              "name": "ENGLISH"
          }
          ],
          "shiftTimeList": [
          {
              "shiftStartTime": "12:30",
              "shiftEndTime": "14:30"
          }
      ],
      "breakTimeList": [
```

```
            {
                "breakStartTime": "13:00",
                "breakEndTime": "13:30",
                "breakDurationInMins": 12
            }
        ],
        "addressList": [
            {
                "apartment":"901",
                "streetName":"2142 3rd Ave",
                "landmark":"Opp. McDonalds",
                "countryShortCode":"USA",
                "city":"Ney York",
                "pincode":"10035",
                "addressType":"PERMANENT"
            },
            {
                "apartment":"901",
                "streetName":"2142 3rd Ave",
                "landmark":"Opp McDonalds",
                "countryShortCode":"USA",
                "city":"New York",
                "pincode":"10035",
                "addressType":"CURRENT"
            }
        ]
    }
]
```

Success Response

```
{
  "status": 200,
  "message": "success",
  "data": [
    "d7b0f3f8e1174742bd6a8ae451866cb1"
  ],
  "hasError": false
}
```

Update an existing delivery associate with this API.

- This API updates a delivery associate entity with the details provided.
- It identifies delivery associates using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Delivery Associate API response when the associated delivery associate is created in the system.

API TYPE

- Tier 1 API.
- You can update a maximum of 20 delivery associates in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/DeliveryMediumApp/mile/v1/update`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceId	String	32	Mandatory	Unique reference ID associated with the delivery associate. This ID is used to identify the delivery associate that you want to update.

employeeId	String	50	Optional	Employee ID of the delivery associate.
userGroupName	String	255	Optional	The User Group or Role that the delivery associate would belong to. The delivery associate would have all the accesses on the Driver App that are granted to this user group.
branchName	String	255	Optional	Branch with which the delivery associate should be linked.
deliveryMediumMasterName	String	255	Optional	Full name of the delivery associate.
phoneNumber	String	255	Optional	Mobile number of the delivery associate.
imei	String	40	Optional	IMEI number of the delivery associate’s phone.
emailId	String	100	Optional	Email ID of the delivery associate.
password	String	255	Optional	Password that the delivery associate would need to log into the Driver App.
capacityInUnits	Integer	20	Mandatory	Capacity in terms of order/crate units that the delivery associate can carry in a trip.
capacityInVolume	Integer	20	Optional	Capacity in terms of volume that the delivery associate can carry in a trip.
capacityInWeight	Integer	20	Optional	Capacity in terms of weight that the delivery associate can carry in a trip.
dob	String		Optional	Date of birth of the delivery associate in YYYY-MM-DD format.
gender	ISODate	12	Optional	Gender of the delivery associate. Example - Male, Female.
deliveryMediumMasterTypeCd	String	255	Optional	Type of delivery associate. For example, you can specify 'Bakery' if your delivery associate can fulfill bakery type of orders or 'Groceries' if your delivery associate can fulfill groceries type of orders. This is mapped to the 'deliveryType' field at the order level.
vehicleNumber	String	255	Optional	Number of the vehicle that should be linked with the delivery associate.
isOwnVehicleFl	String	1	Optional	Whether the vehicle is owned by the delivery associate or by the company.
maxDistance	Integer	20	Optional	Maximum distance that the delivery associate can travel in a trip, from the branch till the last order’s pickup/delivery location. This property can be considered in Trip Planning.
dmPreference	String	255	Optional	Specific postal codes that should be allocated to a delivery associate for pickups/deliveries. The Trip Planning engine will consider this pincode preference when assigning orders to the delivery associate if the Pin Code Preference property is set. Note that this may lead to less optimized planning.
maritalStatus	String	255	Optional	Marital status of the delivery associate.
alternateMobileNo	String	255	Optional	Alternate mobile number of the delivery associate if they carry an additional mobile phone.
landlineNo	String	255	Optional	Fixed line contact number of the delivery associate.

licenseValidity	String	255	Optional	Date (in YYYY-MM-DD format) on which the delivery associate's license would expire.
licenseValidityInYears	String	255	Optional	Years for which the license is valid.
licenseIssuanceDate	String	255	Optional	Date in (YYYY-MM-DD format) when the license was issued for the delivery associate.
loadingTimeInMins	Integer	32	Optional	Average time taken by the delivery associate to load all the orders of a trip in their vehicle. This property can be considered in Trip Planning. This can be different for different types of fleets. A larger vehicle may require more time to load, whereas a small vehicle may require only a few minutes.
unloadingTimeInMins	Integer	32	Optional	Average time taken by the delivery associate to unload all the orders of a trip from the vehicle. This property can be considered in Trip Planning. This can be different for different types of fleets. A larger vehicle may require more time to load, whereas a small vehicle may require only a few minutes.
fixedCost	Number	9	Optional	Fixed cost for using the delivery associate. This is considered in Trip Planning when the Planning Objective is Optimize Fleet Capacity.
variableCost	Number	9	Optional	Variable cost associated with each unit of distance travelled by the delivery associate (i.e., per km cost). This is considered in Trip Planning when the Planning Objective is Optimize Fleet Capacity or Optimize Time and Distance.
weeklyOffList	String	255	Optional	The day on which the delivery associate would be taking their weekly off. For example - Monday, Tuesday, etc.
deliveryMediumMapList.name	String	255	Optional	List of languages that the delivery associate is able to converse in.
shiftTimeList.shiftStartTime	String		Optional	Shift start time of the delivery associate in HH:MM format.
shiftTimeList.shiftEndTime	String		Optional	Shift end time of the delivery associate in HH:MM format.
breakTimeList	List		Optional	Time when the delivery associate is on break. The Trip Planning engine will not assign orders with service time windows that fall within a delivery associate's break time.
breakTimeList.breakStartTime	String		Optional	Start time (in HH:MM format) when the delivery associate is on break. This field is mandatory if the break end time is provided.
breakTimeList.breakEndTime	String		Optional	End time (in HH:MM format) of the delivery associate break. This field is mandatory if the break start time is provided.
breakTimeList.breakDurationInMins	Integer		Optional	Duration (in minutes) of the delivery associate's break time.
addressList	List		Conditional Mandatory	Enter the address details of the delivery associate within this parameter.
addressList.apartment	String	255	Optional	Name of the apartment building/complex in the delivery associate's address.
addressList.streetName	String	255	Optional	Name of the society or street in the delivery associate's address.

addressList.landmark	String	255	Optional	Landmark of the delivery associate's location.
addressList.countryShortCode	String	255	Optional	Name of the country in the shipper's billing address. This should be as per the Country Codes available in the LogiNext system.
addressList.city	String	255	Optional	Name of the city in the delivery associate's address.
addressList.pincode	String	255	Optional	Pin code of the delivery associate's location.
addressList.addressType	String	255	Conditional Mandatory	Whether the delivery associate's address is current or permanent. Specify this parameter as 'CURRENT' to mark the entered address as current or 'PERMANENT' to mark it as permanent. Note that you must provide this parameter if you are adding an address for the delivery associate. This field does not accept any other value.

UPDATE STATUS

Sample Request

```
{
  "newStatus":"ACTIVE",
  "deliveryMediumDetails":
  [
    {
        "referenceId":"fa7716b25fe5432a96d1a709a28bd6d8",
        "reasonCd":"DBUNAVAILABLE",
        "latitude":40.760838,
        "longitude":74.6758
    },
    {
        "referenceId" : "bae83999422211e6860c0653055f4dfd",
        "reasonCd":"DBUNAVAILABLE",
        "latitude":40.760838,
        "longitude":74.67589
    }
  ]
}
```

Success Response

```
{
    "status": 200,
    "message": "Deliverymedium break status update successfully",
    "hasError": false
}
```

Failure Response: If the 'referenceId' is not valid

```
{
    "status": 400,
    "message": "Delivery Mediums status not updated",
    "moreResultsExists": false,
    "error": [
        {
            "key": "699e36b450934ded84adce21ceb3da",
            "message": [
                "No DeliveryMedium with given referenceId"
```

```
            ]
        }
    ],
    "hasError": true
}
```

Failure Response: If the ‘referenceId’ is valid but the ‘reasonCd’ is not valid

```
{
    "status": 400,
    "message": "Delivery Mediums status not updated",
    "moreResultsExists": false,
    "error": [
        {
            "key": "699e36b450934ded84adce21ceb3dab1",
            "message": [
                "reasonCd is not valid"
            ]
        }
    ],
    "hasError": true
}
```

Update the status of an existing delivery associate with this API.

- This API updates the status of delivery associates. You can mark a delivery associate’s status as Active, Inactive, On Break, or Off Break.
- It identifies delivery associates using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Delivery Associate API response when the associated delivery associate is created in the system.
- You can specify a new status for the delivery associate in the 'newStatus' field. Additionally, you can include an optional reason for the status update and the delivery associate's current geocoordinates.
- If you update the delivery associate's status to 'OFFBREAK' using this API, the ETAs for all subsequent 'Not Delivered Orders' in the trip will be revised, if the property ‘Delivery Associate Resuming Duty after Break’ is enabled. The ETA revision logic is as follows:
    - If the delivery associate's geocoordinates (latitude and longitude) are included in the API request, the ETAs will be revised based on these coordinates.
    - If the delivery associate's geocoordinates are not included in the request, but a tracking location for the delivery associate was received in the last 5 minutes, that tracking location will be used to revise the ETAs.
    - If no tracking location was received for the delivery associate in the last 5 minutes, the ETAs for the orders will not be revised.

API TYPE

- Tier 1 API.

REQUEST

PUT `https://api.loginextsolutions.com/DeliveryMediumApp/mile/v1/update/status`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
newStatus	String	50	Mandatory	Current status of the delivery associate. Whether the delivery associate is ‘ACTIVE’, ‘INACTIVE’, ‘ONBREAK’, or ‘OFFBREAK’.
deliveryMediumDetails.referenceID	String	32	Mandatory	Unique reference identifier associated with the delivery associate. This ID is used to identify the delivery associate whose status you want to update.
deliveryMediumDetails.reasonCd	String	255	Optional	Reason to update the status of the delivery associate.
deliveryMediumDetails.latitude	Double		Optional	Latitude coordinates of the delivery associate.
deliveryMediumDetails.longitude	Double		Optional	Longitude coordinates of the delivery associate.

GET PAYOUT

Sample Request

```
{
  "payoutProfileName": "Weekly",
  "startDate": "2023-04-10 18:30:00",
  "endDate": "2023-05-03 18:30:00",
  "deliveryMediumReferenceId": [
    "f40cf4493a59491999b5750a272",
    "f40cf4893a59491treb5750a265"
  ],
  "deliveryMediumUsername": [
    "richard",
    "joshua"
  ]
}
```

Success Response


```
{
 "status":200,
 "message":"SUCCESS",
  "moreResultsExists":false,
 "data":
 [
   {
     "deliveryMediumReferenceId":"f40cf4493a59491999b5750a272",
     "deliveryMediumUsername":"richard",
     "payoutDetails":[
       {
         "payoutProfileName" : "Weekly",
         "payoutStartTime":"1657612590000",
         "payoutEndTime":"1658217389000",
         "payoutAmount":1560.98,
         "earningsAmount":1500.30,
         "bonusAmount":60.68
       },
       {
         "payoutProfileName" : "Weekly",
         "payoutStartTime":"1658217390000",
         "payoutEndTime":"1658822189000",
         "payoutAmount":1660.98,
         "earningsAmount":1500.30,
         "bonusAmount":160.68
       }]
 },
 {
       "deliveryMediumReferenceId":"f40cf4893a59491treb5750a265",
       "deliveryMediumUsername":"joshua",
       "payoutDetails":[
         {
           "payoutProfileName" : "Weekly",
           "payoutStartTime":"1657612590000",
           "payoutEndTime":"1658217389000",
           "payoutAmount":1460.98,
           "earningsAmount":1300.30,
           "bonusAmount":160.68
         },
         {
           "payoutProfileName" : "Weekly",
           "payoutStartTime":"1658217390000",
```

```
            "payoutEndTime":"1658822189000",
            "payoutAmount":660.98,
            "earningsAmount":500.30,
            "bonusAmount":160.68
          }]
        }],
        "hasError":false
  }
```


Failure Response: If any mandatory parameter is missing


```
{
    "status": 409,
    "message": "Failed to retrieve payout data",
    "hasError": true,
    "errorList": [
    {
        "key": "payoutProfileName",
        "message": "Payout Profile Name is Mandatory",
        "errorcode": 140000
    },
    {
        "key": "startDate",
        "message": "Payout Start Date is Mandatory",
        "errorcode": 140001
    },
    {
      "key": "endDate",
      "message": "Payout End Date is Mandatory",
      "errorcode": 140002
    }
    ]
}
```


Failure Response: If any parameter passed is incorrect


```
{
    "status": 409,
    "message": "Failed to retrieve payout data",
    "hasError": true,
    "errorList": [
    {
        "key": "payoutProfileName",
        "message": "Payout Profile Name is invalid",
        "errorcode": 142000
    },
    {
        "key": "startDate",
        "message": "Payout Start Date is invalid",
        "errorcode": 142001
    },
    {
      "key": "deliverMediumUsername",
      "message": "Payout End Date is invalid",
      "errorcode": 142002
    },
    {
      "key": "deliverMediumReferenceId",
      "message": "Delivery Associate Reference is invalid",
      "errorcode": 32003
    },
    {
```

```
      "key": "endDate",
      "message": "Delivery Associate Username is invalid",
      "errorcode": 32001
    }
    ]
}
```

Failure Response: Business Validations

```
{
    "status": 409,
    "message": "Failed to retrieve payout data",
    "hasError": true,
    "errorList": [
    {
        "key": "startDate",
        "message": "Payout Start Date should be less than End Date",
        "errorcode": 148001
    },
    {
      "key": "endDate",
      "message": "Payout Date Range can not be greater than 30 days",
      "errorcode": 148002
    }
    ]
}
```

Retrieve payout details of required delivery associates using this API.

- This API retrieves the payout details of delivery associates, including payout amount, earning amount, and bonus amount within the specified date range.
- Note that this API has a limit of 500 pages and 100 records per page with the maximum accepted date range of 30 days.
- You can access data only from the past three years.

API TYPE

- Tier 1 API.
- This API accepts up to 20 Delivery Associate IDs or Usernames in one call.

REQUEST

POST `https://api.loginextsolutions.com/deliveryMediumApp/mile/v1/payout`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
payoutProfileName	String	255	Conditional Mandatory	Name of the Payout Profile for which you want to retrieve the payout data. Note: If you do not provide the start and end dates, it will return the last payout calculated for the delivery associates under this profile.
startDate	Date		Conditional Mandatory	Start date (in yyyy-MM-dd HH:mm:ss format) from which you need to retrieve the payout. This will return the delivery associate's payout based on the payout period start date. If the 'payoutProfileName' field is not provided in the request, then this field becomes mandatory.
endDate	Date		Conditional Mandatory	End date (in yyyy-MM-dd HH:mm:ss format) until which you need to retrieve the payout. This will return the delivery associate's payout based on the payout period end date. If the 'payoutProfileName' field is not provided in the request, then this field becomes mandatory.

deliveryMediumReferenceId	List		Optional	Unique reference identifier associated with the delivery associate. This ID is used to identify the delivery associate whose payout details you want to view/retrieve.
deliveryMediumUsername	List	255	Optional	Username associated with the delivery associate. This field is not required if the 'deliveryMediumReferenceId' is provided.
pageSize	Integer		Optional	Number of payout records per page that you want to retrieve in one call of this API. The default value is 50 records per page, and the maximum accepted value is 100. If a higher value is provided, only 100 records per page will be returned.

Branch

CREATE

Sample Request

```
[
    {
    "clientParentBranchName": "Reeta Foods Main Branch",
    "branchName": "Marque Downtown Chicago",
    "address": {
        "apartment": "Suite No. 99, Milsons Towers",
        "streetName": "Michigan Avenue",
        "landmark": "Opp. Subway",
        "locality": "Dowtown Chicago",
        "city": "Chicago",
        "stateShortCode": "IL",
        "countryShortCode": "USA",
        "pincode": "60606"
    },
    "division": "ADIV",
    "isOwnBranchFl": "N",
    "isHubFl": "Y",
    "deliveryMediumAutoAllocateFl": "Y",
    "autoAllocateFl": "Y",
    "geoFenceRadius": "2.0",
    "branchDescription": "desc",
    "billingContactName": "name",
    "officeNumber": "2798678712",
    "adminContactName": "John K.",
    "mobileNumber": "9033977123",
    "emailAddress": "superjames@gmails.com",
    "whatsappOptin":"Y",
    "managerDetails": [
        {
        "managerContactName": "John K.",
        "mobileNumber": "9033977123",
        "whatsappOptin":"Y",
        "emailAddress": "superjames@gmail.com",
        "shifts": [
            {
            "daysOfWeek": "Monday",
            "shiftStartTime": "08:00",
            "shiftEndTime": "20:00"
            },
            {
            "daysOfWeek": "Friday",
            "shiftStartTime": "09:00",
```

```
            "shiftEndTime": "21:00"
            }
        ]
        },
        {
        "managerContactName": "John Wick",
        "mobileNumber": "9033977223",
        "whatsappOptin":"Y",
        "emailAddress": "superjohn@gmail.com",
        "shifts": [
            {
            "daysOfWeek": "Tuesday",
            "shiftStartTime": "20:01",
            "shiftEndTime": "08:00"
            },
            {
            "daysOfWeek": "Saturday",
            "shiftStartTime": "21:01",
            "shiftEndTime": "09:00"
            }
        ]
        }
    ],
    "operationTimings": [
        {
        "daysOfWeek": "Monday",
        "operationsStartTime": "08:00",
        "operationsEndTime": "22:00"
        },
        {
        "daysOfWeek": "Friday",
        "operationsStartTime": "00:00",
        "operationsEndTime": "23:45"
        }
    ],
    "longitude": 40.760838,
    "latitude": 74.9095327,
    "timeZone": "America/Chicago",
    "loadingTime": 20,
    "unloadingTime": 20,
    "averagePreparationTime": 20,
    "averagePickupTime": 20,
    "loadMultipliers": [{
        "daysOfWeek": "Monday",
        "startTime": "20:00",
        "endTime": "08:00",
        "loadFactor": 1.2
        },
        {
        "daysOfWeek": "Tuesday",
        "startTime": "20:00",
        "endTime": "08:00",
        "loadFactor": 2.0
        }
    ]
    }
]
```


Success Response


```
{
    "status": 200,
    "message": "Branch created successfully",
    "data": {
```

```
        "referenceId": "fa7716b25fe5432a96d1a709a28bd6d8"
    },
    "hasError": false
}
```

Failure Response

```
{
    "status": 409,
    "message": "Branch creation failed",
    "moreResultsExists": false,
    "error": [
        {
            "errorList": [
                {
                    "key": "whatsappOptin",
                    "message": [
                        "Whatsapp Optin is invalid."
                    ],
                    "errorCode": 42020
                }
            ]
        }
    ],
    "hasError": true
}
```

Create new branches in the LogiNext system with this API.

- This API creates a Branch with contact information, manager details, operation details, and more.
- Each branch is assigned a unique Reference ID for future identification.

API TYPE

- Tier 1 API.

REQUEST

POST `https://api.loginextsolutions.com/ClientApp/v1/branch/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
clientParentBranchName	String	255	Mandatory	Name of the Parent Branch under which you want to create a new branch.
branchName	String	255	Mandatory	Name of the branch you are creating. Be careful while providing the branch name since it cannot be changed later.
Address.apartment	String	512	Mandatory	Name of the apartment building/complex in the branch's address.
Address.streetName	String	255	Mandatory	Name of the society or street in the branch's address.
Address.landmark	String	512	Mandatory	Landmark of the branch's location.
Address.locality	String	512	Mandatory	Name of the locality or area in the branch's address. If you think that the specific region in which you operate does not have localities, raise a support request with your Account Manager to make this non-mandatory.

Address.city	String	512	Mandatory	Name of the city in the branch's address.
Address.stateShortCode	String	11	Mandatory	Name of the state in the branch's address. This should be as per the State Codes available in the LogiNext system for the selected country. If you think that the specific region in which you operate does not have states or provinces, raise a support request with your Account Manager to make this non-mandatory.
Address.countryShortCode	String	11	Mandatory	Name of the country in the branch's address. This should be as per the Country Codes available in the LogiNext system.
Address.pincode	String	20	Mandatory	Pin code of the branch's location. If you think that the specific region in which you operate does not have postal codes, raise a support request with your Account Manager to make this non-mandatory.
division	String	255	Optional	Operational division of the branch, if any. You can add any division or segment of your operations here. It can be a city, region, or state based on your operations.
isOwnBranchFl	String	1	Mandatory	Pass the value as 'N'.
isHubFl	String	1	Mandatory	Pass the value as 'Y'.
geoFenceRadius	String	255	Optional	Specify the geofence radius (in km) applicable to this branch. Specifying a geofence radius is important for applying the settings for branch geofence entry and exit alerts. Note that the default value is set as 2 km if no value is provided. Ideally, a geofence radius should range between 200 m to 2 km.
autoAllocateFl	String	1	Optional	Whether this branch's delivery associates should be considered for auto-assignment of orders. Specify 'Y' to consider for auto-assignment and 'N' otherwise. Note that if you specify 'N', orders will not be auto-assigned to this branch even if the 'autoAllocateFl' parameter in the Create Order API is set to 'Y'. This can be used when you do not want to consider a certain branch and its delivery associates for auto-assignment due to the higher cost implications of using the branch's resources in order fulfillment. You can still manually assign orders to the branch. If no value is provided, the default is 'Y'.
deliveryMediumAutoAllocateFl	String	1	Optional	Whether the delivery associates linked with this branch should be considered for the auto-assignment. Specify 'Y' to consider the delivery associates in the auto-assignment of orders, if you have configured the Resource Pooling property in the Auto Assignment profile. Specify 'N' if you do not want to consider certain delivery associates that are linked to this branch for auto assignment of orders. You can still manually assign orders to the delivery associates. If no value is provided, the default is 'Y'.
branchDescription	String	500	Optional	Provide a short description of the branch.
billingContactName	String	500	Mandatory	Name of the contact person at the branch's billing location.
officeNumber	String	255	Mandatory	Fixed line contact number of the branch.
adminContactName	String	255	Mandatory	Name of the primary contact person/admin/supervisor in the branch.

mobileNumber	String	255	Mandatory	Phone number of the primary contact person in the branch.
emailAddress	String	255	Mandatory	Email ID of the primary contact person in the branch.
managerDetails	List		Mandatory	Enter the branch manager's details within this parameter.
managerDetails.managerContactName	String		Optional	Name of the branch manager.
managerDetails.mobileNumber	String		Optional	Contact number of the branch's manager.
managerDetails.emailAddress	String		Optional	Email address of the branch's manager.
managerDetails.shifts	List		Optional	Shift of the branch's manager.
managerDetails.shifts.daysOfWeek	String		Optional	The days on which the branch's manager is available. This will accept any value from the list of pre-configured days - "Monday", "Tuesday", "Wednesday", "Thursday", "Friday", " Saturday", "Sunday".
managerDetails.shifts.shiftStartTime	Integer		Optional	Shift start time of the branch's manager in HH:MM format. The timezone considered for this field is same as the branch's timezone.
managerDetails.shifts.shiftEndTime	Integer		Optional	Shift end time of the branch's manager in HH:MM format. The timezone considered for this field is same as the branch's timezone.
operationTimings	List		Optional	Operational timing details. This is applicable for carrier branch creation. If the carrier branch has different operation hours for each day of the week, you can configure them here. The LogiNext real-time auto-assignment engine considers the operating hours during order assignment.
operationTimings.daysOfWeek	String		Optional	The days on which the branch's operation is available. This will accept a value from the below list of pre-configured days. Acceptable values - "Monday", "Tuesday", " Wednesday", "Thursday", "Friday", "Saturday", "Sunday".
operationTimings.operationsStartTime	Integer		Optional	This is applicable for carrier branch creation. You can configure branch opening time (in HH:MM format) for each day of the week.
operationTimings.operationsEndTime	Integer		Optional	This is applicable for carrier branch creation. You can configure branch closing time (in HH:MM format) for each day of the week.
longitude	Double	15	Optional	Longitude coordinates of the branch.
latitude	Double	15	Optional	Latitude coordinates of the branch.
timeZone	String		Optional	Timezone applicable to this branch. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your account.
loadingTime	Integer	32	Optional	Total time taken (in min) to load all the orders into the vehicle at the branch. This can be used to consider the time spent in processes like security at the branch to load vehicles.

unloadingTime	Integer	32	Optional	Total time taken (in min) to unload all the orders from the vehicle at the branch. This can be used to consider the time spent in processes like security at the branch to unload vehicles.
averagePreparationTime	Integer	20	Optional	Average time taken to prepare an order at the branch before it can be picked up. This field is used for calculating Pre-Order ETA.
averagePickupTime	Integer	20	Optional	Average time taken by a delivery associate to reach the branch for pickup once an order is created. This field is used for calculating Pre-Order ETA.
loadMultiplier	List		Optional	This is used to factor in additional preparation time during peak hours. Specify the day of the week, peak time duration of the day, and load multiplier factor within this parameter. During the specified peak hours, this Load Multiplier Factor will be multiplied with the Average Preparation Time or the Item Preparation Time to determine the revised preparation time. For example - If the item or average preparation time is 10 min, having a load factor of 1.2 will make the order preparation time as 12 min. These parameters are used for calculating Pre-Order ETA.
loadMultiplier.days	String	20	Optional	This is used to factor in additional preparation time during peak hours. Enter the day(s) of the week when load multipliers are applied.
loadMultiplier.startTime			Optional	This is used to factor in additional preparation time during peak hours. Enter the start time (in HH:MM format) of the load multiplier for the specified day.
loadMultiplier.endTime			Optional	This is used to factor in additional preparation time during peak hours. End time (in HH:MM format) of the load multiplier for the specified day.
loadMultiplier.loadFactor	Double	20	Optional	This is used to factor in additional preparation time during peak hours. Enter the load multiplier factor that will be multiplied with the Average Preparation Time or the Item Preparation Time to determine the revised preparation time. For example - If the item or average preparation time is 10 min, having a load factor of 1.2 will make order preparation time as 12 min.

GET

Sample Request

```
https://api.loginextsolutions.com/ClientApp/v1/branch/get?branchName=Marque%20Downtown%20Chicago&referenceId=8ab93927b98b466fb0b8dd5154fca346
```

Success Response


```
{
    "status": 200,
    "message": "Success",
    "moreResultsExists": false,
    "data": {
        "referenceId": "8ab93927b98b466fb0b8dd5154fca346",
        "clientName": "CLIENTNAME",
        "clientParentBranchName": "Reeta Foods Main Branch",
        "branchName": "Marque Downtown Chicago",
```

```
        "subClientParentBranch": "Not Applicable",
        "division": "DIVISION",
        "address": {
            "apartment":"Suite No. 99, Milsons Towers",
            "streetName":"Michigan Avenue",
            "landmark":"Opp. Subway",
            "locality":"Dowtown Chicago",
            "city":"Chicago",
            "stateShortCode":"IL",
            "countryShortCode":"USA",
            "pincode":"60606"
        },
        "isOwnBranchFl": "N",
        "isHubFl": "Y",
        "skillSet": "Document,Small Box,Mobile Phones & Accesorries,Heavy Goods,Large Appliances,Home Appliances,Clothing",
        "rank": 1,
        "geoFenceRadius": 2.0,
        "adminContactName":"John K.",
        "mobileNumber":"9033977123",
        "emailAddress":"superjames@gmail.com",
         "managerDetails": [
    {
      "managerContactName": "John K.",
      "mobileNumber": "9033977123",
      "emailAddress": "superjames@gmail.com",
      "shifts": [
        {
          "daysOfWeek": "Monday",
          "shiftStartTime": "08:00",
          "shiftEndTime": "20:00"
        },
        {
          "daysOfWeek": "Friday",
          "shiftStartTime": "09:00",
          "shiftEndTime": "21:00"
        }
      ]
    },
    {
      "managerContactName": "John Wick",
      "mobileNumber": "9033977223",
      "emailAddress": "superjohn@gmail.com",
      "shifts": [
        {
          "daysOfWeek": "Tuesday",
          "shiftStartTime": "20:01",
          "shiftEndTime": "08:00"
        },
        {
          "daysOfWeek": "Saturday",
          "shiftStartTime": "21:01",
          "shiftEndTime": "09:00"
        }
      ]
    }
  ],
  "operationTimings": [
    {
      "daysOfWeek": "Monday",
      "operationsStartTime": "08:00",
      "operationsEndTime": "22:00"
    },
    {
      "daysOfWeek": "Friday",
      "operationsStartTime": "00:00",
      "operationsEndTime": "23:45"
```

```
    }
  ],
        "longitude": 40.760838,
        "latitude": 74.9095327,
        "timeZone":"America/Chicago",
        "movementType": "Both",
        "operationalSupportPhoneNumber": "9911111111",
        "operationalSupportEmailID": "",
        "customerSupportPhoneNumber": "",
        "customerSupportEmailID": "",
        "unloadingTime": 10,
        "loadingTime": 10,
        "averagePreparationTime": 20,
        "averagePickupTime":20,
        "loadMultipliers":[
            {
                "daysOfWeek":"Monday",
                "startTime":"20:00",
                "endTime":"08:00",
                "loadFactor": 1.2
            },
            {
                "daysOfWeek":"Tuesday",
                "startTime":"20:00",
                "endTime":"08:00",
                "loadFactor":2.0
            }
        ],
        "customFields": [
            {
                "field": "cf_branchType",
                "value": "Fulfilment Center",
                "type": "text"
            },
            {
                "field": "cf_branchType2",
                "value": "Fulfilment Center2",
                "type": "text"
            }
        ]
    },
    "hasError": false
}
```


Failure Response 1


```
{
    "status": 409,
    "message": "Invalid branchName",
    "moreResultsExists": false,
    "hasError": true
}
```


Failure Response 2


```
{
    "status": 409,
    "message": "Invalid referenceId",
    "moreResultsExists": false,
    "hasError": true
}
```

Retrieve details of the required branch using this API.

- This API retrieves the details of a branch, including contact information, manager details, operation details, and more.
- Include the Reference IDs or Branch Name you want to search for in the Request Body.

API TYPE

- Tier 1 API.
- You can fetch the details of only one branch in one call of this API.

REQUEST

GET `https://api.loginextsolutions.com/ClientApp/v1/branch/get`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceId	String		Conditional Mandatory	Unique reference identifier associated with the branch. This ID is used to identify the branch that you want to retrieve. If the 'branchName' is not provided, then this field is mandatory.
branchName	String		Conditional Mandatory	Name of the branch that you want to retrieve. If the 'referenceId' is not provided, then this field is mandatory.
managerDetails	List		Optional	Enter the branch manager's details within this parameter.
managerDetails.managerContactName	String		Optional	Name of the branch manager.
managerDetails.mobileNumber	String		Optional	Contact number of the branch's manager.
managerDetails.emailAddress	String		Optional	Email address of the branch's manager.
managerDetails.shifts	List		Optional	Shift of the branch's manager.
managerDetails.shifts.daysOfWeek	String		Optional	The days on which the branch's manager is available. This will accept a value from the below list of pre-configured days. Acceptable values - "Monday", "Tuesday", " Wednesday", "Thursday", "Friday", "Saturday", "Sunday".
managerDetails.shifts.shiftStartTime	Integer		Optional	Shift start time of the branch's manager. The timezone considered for this field is same as the branch's timezone.
managerDetails.shifts.shiftEndTime	Integer		Optional	Shift end time of the branch's manager. The timezone considered for this field is same as the branch's timezone.
operationTimings	List		Optional	This is applicable for the carrier branch. If the carrier branch has different operation hours for each day of the week, you can pass them here. The LogiNext real-time auto-assignment engine considers the operating hours during order assignment.
operationTimings.daysOfWeek	String		Optional	The days on which the branch's operation is available. This will accept a value from the below list of pre-configured days. Acceptable values - "Monday", "Tuesday", " Wednesday", "Thursday", "Friday", "Saturday", "Sunday".
operationTimings.operationsStartTime	Integer		Optional	This is applicable for the carrier branch. You can pass the branch opening time for each day of the week.
				This is applicable for the carrier branch. You can pass the

operationTimings.operationsEndTime	Integer	Optional	branch closing time for each day of the week.

UPDATE

Sample Request


```
[
    {
    "referenceId": "fa7716b25fe5432a96d1a709a28bd6d8",
    "address": {
        "apartment": "Himalaya Mall",
        "streetName": "Driving Road",
        "pincode": "380061",
        "locality": "Drive in Road",
        "stateShortCode": "GJ",
        "countryShortCode": "IND"
    },
    "division": "BDIC",
    "isOwnBranchFl": "N",
    "isHubFl": "Y",
    "geoFenceRadius": "4.0",
    "branchDescription": "DEC",
    "billingContactName": "bill",
    "officeNumber": "971545813943",
    "adminContactName": "name",
    "mobileNumber": "971545813943",
    "whatsappOptin":"Y",
    "emailAddress": "hack1@gmail.com",
    "longitude": 40.760838,
    "latitude": 74.9095327,
    "loadingTime": 20,
    "unloadingTime": 20,
    "managerDetails": [
        {
        "managerContactName": "John K.",
        "mobileNumber": "9033977123",
        "emailAddress": "superjames@gmail.com",
        "whatsappOptin": "N",
        "shifts": [
            {
            "daysOfWeek": "Monday",
            "shiftStartTime": "08:00",
            "shiftEndTime": "20:00"
            },
            {
            "daysOfWeek": "Friday",
            "shiftStartTime": "09:00",
            "shiftEndTime": "21:00"
            }
        ]
        },
        {
        "managerContactName": "John Wick",
        "mobileNumber": "9033977223",
        "emailAddress": "superjohn@gmail.com",
        "whatsappOptin": "N",
        "shifts": [
            {
            "daysOfWeek": "Tuesday",
            "shiftStartTime": "20:01",
            "shiftEndTime": "08:00"
            },
            {
            "daysOfWeek": "Saturday",
```

```
            "shiftStartTime": "21:01",
            "shiftEndTime": "09:00"
            }
        ]
        }
    ],
    "operationTimings": [
        {
        "daysOfWeek": "Monday",
        "operationsStartTime": "08:00",
        "operationsEndTime": "22:00"
        },
        {
        "daysOfWeek": "Friday",
        "operationsStartTime": "00:00",
        "operationsEndTime": "23:45"
        }
    ],
    "longitude": 40.760838,
    "latitude": 74.9095327,
    "loadingTime": 20,
    "unloadingTime": 20,
    "timeZone": "America/Chicago",
    "averagePreparationTime": 20,
    "averagePickupTime": 20,
    "loadMultipliers": [{
        "daysOfWeek": "Monday",
        "startTime": "20:00",
        "endTime": "08:00",
        "loadFactor": 1.2
        },
        {
        "daysOfWeek": "Tuesday",
        "startTime": "20:00",
        "endTime": "08:00",
        "loadFactor": 2.0
        }
    ]
    }
]
```


Success Response


```
{
    "status": 200,
    "message": "Branch updated successfully",
    "moreResultsExists": false,
    "data": {
          "referenceId": "8ab93927b98b466fb0b8dd5154fca346",
    },
    "hasError": false
}
```


Failure Response


```
{
    "status": 409,
    "message": "Branch creation failed",
    "moreResultsExists": false,
    "error": [
        {
            "errorList": [
```

```
                {
                    "key": "whatsappOptin",
                    "message": [
                        "Whatsapp Optin is invalid."
                    ],
                    "errorCode": 42020
                }
            ]
        }
    ],
    "hasError": true
}
```

Update an existing branch with this API.

- This API updates a branch with the details provided.
- It identifies branches using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Branch API response when the associated branch is created in the system.

API TYPE

- Tier 1 API.

REQUEST

POST `https://api.loginextsolutions.com/ClientApp/v1/branch/update`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceId	String	255	Mandatory	Unique reference identifier associated with the branch. This ID is used to identify the branch that you want to update.
Address.apartment	String	512	Optional	Name of the apartment building/complex in the branch's address.
Address.streetName	String	255	Optional	Name of the society or street in the branch's address.
Address.landmark	String	512	Optional	Landmark of the branch's location.
Address.locality	String	512	Optional	Name of the locality or area in the branch's address. If you think that the specific region in which you operate does not have localities, raise a support request with your Account Manager to make this non-mandatory.
Address.city	String	512	Optional	Name of the city in the branch's address.
Address.stateShortCode	String	11	Optional	Name of the state in the branch's address. This should be as per the State Codes available in the LogiNext system for the selected country. If you think that the specific region in which you operate does not have states or provinces, raise a support request with your Account Manager to make this non-mandatory.
Address.countryShortCode	String	11	Optional	Name of the country in the branch's address. This should be as per the Country Codes available in the LogiNext system.
Address.pincode	String	20	Optional	Pin code of the branch's location. If you think that the specific region in which you operate does not have postal codes, then please raise the support request with your Account Manager to make this non-mandatory.

division	String	255	Optional	Operational division of the branch, if any. You can add any division or segment of your operations here. It can be a city, region, or state based on your operations.
isOwnBranchFl	String	1	Optional	Pass this parameter as ‘N’.
isHubFl	String	1	Optional	Pass this parameter as ‘Y’.
geoFenceRadius	String	255	Optional	Specify the geofence radius (in km) applicable to this branch. Specifying a geofence radius is important for applying the settings for branch geofence entry and exit alerts. Note that the default value is set as 2 km if no value is provided. Ideally, a geofence radius should range between - 200 m to 2 km.
branchDescription	String	500	Optional	Provide a short description of the branch.
billingContactName	String	500	Optional	Name of the contact person at the branch’s billing location.
officeNumber	String	255	Optional	Fixed line contact number of the branch.
adminContactName	String	255	Optional	Name of the primary contact person/admin/supervisor in the branch.
mobileNumber	String	255	Optional	Phone number of the primary contact person in the branch.
emailAddress	String	255	Optional	Email ID of the primary contact person in the branch.
managerDetails	List	255	Optional	Enter the branch manager's details within this parameter.
managerDetails.managerContactName	String	255	Optional	Name of the branch manager.
managerDetails.mobileNumber	String	255	Optional	Contact number of the branch’s manager.
managerDetails.emailAddress	String	255	Optional	Email address of the branch’s manager.
managerDetails.shifts	List		Optional	Shift of the branch’s manager.
managerDetails.shifts.daysOfWeek	String		Optional	The days on which the branch’s manager is available. This will accept a value from the below list of pre-configured days. Acceptable values - “Monday”, ”Tuesday”, ” Wednesday”, ”Thursday”, ”Friday”, ”Saturday”, ”Sunday”.
managerDetails.shifts.shiftStartTime	Integer		Optional	Shift start time of the branch’s manager in HH:MM format. The timezone considered for this field is same as the branch’s timezone.
managerDetails.shifts.shiftEndTime	Integer		Optional	Shift end time of the branch’s manager in HH:MM format. The timezone considered for this field is same as the branch’s timezone.
operationTimings	List		Optional	Operational timing details. This is applicable for carrier branch. If the carrier branch has different operation hours for each day of the week, you can configure them here. The LogiNext real-time auto-assignment engine considers the operating hours during order assignment.
operationTimings.daysOfWeek	String		Optional	The days on which the branch’s operation is available. This will accept a value from the below list of pre-configured

				days. Acceptable values - “Monday”, ”Tuesday”, ” Wednesday”, ”Thursday”, ”Friday”, ”Saturday”, ”Sunday”.
operationTimings.operationsStartTime	Integer		Optional	This is applicable for the carrier branch. You can configure branch opening time (in HH:MM format) for each day of the week.
operationTimings.operationsEndTime	Integer		Optional	This is applicable for the carrier branch. You can configure branch closing times (in HH:MM format) for each day of the week.
loadingTime	Integer	32	Optional	Timezone applicable to this branch. If you do not provide the timezone, the system will consider the default timezone configured for your account.
unloadingTime	Integer	32	Optional	Total time taken (in min) to load all the orders into the vehicle at the branch. This can be used to consider the time spent in processes like security at the branch to load vehicles.
averagePreparationTime	Integer	20	Optional	Average time taken to prepare an order at the branch before it can be picked up. This field is used for calculating Pre-Order ETA.
averagePickupTime	Integer	20	Optional	Average time taken by a delivery associate to reach the branch for pickup once an order is created. This field is used for calculating Pre-Order ETA.
loadMultiplier	List		Optional	This field is used to factor in additional preparation time during peak hours. Specify the day of the week, peak time duration of the day, and load multiplier factor within this parameter. During the specified peak hours, this Load Factor will be multiplied with the Average Preparation Time or the Item Preparation Time to determine the revised preparation time. For example - If the item or average preparation time is 10 min, having a load factor of 1.2 will makethe order preparation time as 12 min. These fields are used for calculating Pre-Order ETA.
loadMultiplier.days	String	20	Optional	This field is used to factor in additional preparation time during peak hours. Enter the day(s) of the week when load multipliers are applied.
loadMultiplier.startTime			Optional	This field is used to factor in additional preparation time during peak hours. Enter the start time (in HH:MM format) of the load multiplier for the specified day.
loadMultiplier.endTime			Optional	This field is used to factor in additional preparation time during peak hours. End time (in HH:MM format) of the load multiplier for the specified day.
loadMultiplier.loadFactor	Double	20	Optional	This field is used to factor in additional preparation time during peak hours. Enter the load factor that will be multiplied with the Average Preparation Time or the Item Preparation Time to determine the revised preparation time.. For example - If the item or average preparation time is 10 min, having a load factor of 1.2 will make order preparation time as 12 min.

Vehicle

CREATE

Sample Request

```
[
    {
        "vehicleNumber": "1A1CD",
        "branchName": "New York Hub",
        "vehicleMake": "Marker",
        "vehicleModel": "OMNI",
        "vehicleType": "",
        "unladdenWeight": 10,
        "capacityInWeight": 10,
        "capacityInUnits": 10,
        "capacityInVolume": 10,
        "chassisNumber": "CHASIS-123",
        "engineNumber": "A-12353-D1234",
        "markerName": "Marker-1",
        "registrationNumber": "",
        "pucValidity": "2025-07-01T11:18:00.000Z",
        "insuranceValidity": "2025-07-01T11:18:00.000Z",
        "vehiclePermit": "New York, NY",
        "ownership": "company",
        "ownerName": "Mathew Richardson",
        "transporter": "",
        "financer": "",
        "accidentHistory": "",
        "rentStartDate": null,
        "rentEndDate": null,
        "vehicleProductionYear": null,
        "maxDistance": null,
        "loadingTimeInMins": null,
        "deviceId": {
            "barcode": "LN12345678"
        },
        "trackerList": [
            {
                "trackerId" : "TR001"
            }, {
                "trackerId" : "TR002"
            }, {
                "trackerId" : "TR003"
            }
        ]
    }
]
```

Success Response

```
{
    "status": 200,
    "message": "Vehicle created Successfully",
    "data": [
        {
            "referenceId": "6186d5fc6e324c42",
            "vehicleNumber": "MH-111"
        }
    ],
    "hasError": false
}
```

Failure Response: Incorrect Tracker Id

```
{
    "status": 409,
    "message": "Some issue encountered in server",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "key": "trackerList.trackerId",
            "message": [
                "${Tracker_s} Id is invalid."
            ],
            "errorCode": 142001
        }
    ],
    "hasError": true
}
```

Create new vehicles in the LogiNext system with this API.

- This API creates a Vehicle with details such as capacity, loading time, shift time, skill sets, associated costs, and more.
- Each vehicle is assigned a unique Reference ID for future identification.

API TYPE

- Tier 1 API.

REQUEST

POST `https://api.loginextsolutions.com/VehicleApp/mile/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
branchName	String	255	Mandatory	Name of the branch that should be linked with this vehicle.
vehicleNumber	String	255	Mandatory	Unique number of the vehicle.
vehicleMake	String	255	Optional	Name of the manufacturer. For example - Mazda, Volvo, etc.
vehicleModel	String	40	Optional	Model of the vehicle. For example - FH series, MethaneDiesel, etc.
vehicleType	String	40	Optional	Type of the vehicle. Whether the vehicle is 2 wheeler or 4 wheeler.
unladdenWeight	Integer	10	Optional	Weight of the vehicle (in kg) when it is not loaded.
capacityInWeight	Integer	10	Optional	Capacity of the vehicle in weight (in kg).
capacityInUnits	Integer	10	Optional	Capacity of the vehicle in units.
capacityInVolume	Integer	10	Optional	Capacity of the vehicle in volume (in cubic centimeters).
chassisNumber	String	255	Optional	Chassis or VIN (Vehicle Identification Number) of the vehicle.
engineNumber	String	255	Optional	Engine number of the vehicle.
markerName	String	255	Optional	Name of the manufacturer.

registrationNumber	String	255	Optional	Registration number of the vehicle provided by the transportation authority.
pucValidity	Date		Optional	Date until which the vehicle’s PUC certificate is valid. This date must always be later than the current date. Format - YYYY-MM DDTHH:MM:SS.SSSZ. For example - 2025-07-01T11:18:00.000Z.
insuranceValidity	Date		Optional	Date until which the vehicle’s insurance is valid. This date must always be later than the current date. Format - YYYY-MM DDTHH:MM:SS.SSSZ. For example - 2025-07-01T11:18:00.000Z.
vehiclePermit	String	40	Optional	Region where it is permitted to operate a vehicle.
vehicleProductionYear	Date		Optional	Production date of the vehicle. Format - YYYY-MM DDTHH:MM:SS.SSSZ. For example - 2016-07-01T11:18:00.000Z.
ownership	String	50	Optional	Entity that owns the vehicle. Whether the vehicle is owned by a company or vendor.
ownerName	String	255	Optional	Name of the company or vendor who owns the vehicle.
transporter	String	40	Optional	Name of the transporter.
financer	String	40	Optional	Name of the financer, if the vehicle is on loan.
accidentHistory	String	160	Optional	Specify the vehicle's accident history details, if any.
maxDistance	Integer	20	Optional	Maximum distance that the vehicle can travel in a day. This can be considered in Trip Planning.
loadingTimeInMins	Number	32	Optional	Time (in minutes) taken to load orders in the vehicle.
rentStartDate	Date		Optional	Date when the vehicle was rented. This input is valid only if the vehicle’s owner is a vendor. Note that the Rent Start Date should be earlier than the Rent End Date. Format - YYYY-MM-DDTHH:MM:SS.SSSZ. For example - 2016-07-01T11:18:00.000Z.
rentEndDate	Date		Optional	Date till when the vehicle has been rented. This input is valid only if the vehicle’s owner is a vendor. Note that the Rent End Date should be later than the Rent Start Date. Format - YYYY-MM-DDTHH:MM:SS.SSSZ. For example - 2024-07-01T11:18:00.000Z.
deviceId.barcode	String	50	Optional	Specify the barcode of the tracker to map it to the vehicle.
trackerList.trackerId	String	12	Mandatory	Unique identifier(s) associated with the tracker.

GET

Sample Request

```
https://api.loginextsolutions.com/VehicleApp/mile/v1?referenceIds={vehicleReferenceIds}&vehicleNumbers={VehicleNumbers}
```

Success Response

```
{
    "status": 200,
    "message": "Success",
    "data": [
        {
```

```
            "vehicleReferenceId": "6186d5fc6e324c42",
            "vehicleName": null,
            "guid": "1efc418bd9f54bd99955cfdcccdc27a2",
            "vehicleNumber": "1ABC234",
            "vehicleMake": null,
            "vehicleModel": null,
            "vehicleType": null,
            "unladdenWeight": null,
            "capacityInUnits": 12,
            "capacityInVolume": 12,
            "capacityInWeight": 12,
            "chasisNumber": null,
            "engineNumber": null,
            "markerName": null,
            "registrationNumber": null,
            "pucValidity": null,
            "insuranceValidity": null,
            "vehiclePermit": null,
            "ownerName": null,
            "clientBranchId": 1402,
            "rentEndDate": null,
            "rentStartDate": null,
            "transporter": null,
            "financer": null,
            "permit": null,
            "ownership": null,
            "accidentHistory": null,
            "vehicleProductionYear": null,
            "maxDistance": null,
            "loadingTimeInMins": null,
            "deviceId": {
                "deviceId": null,
                "barcode": null,
                "statusCd": null,
                "trackeeId": null
            },
            "registrationCopy": [],
            "pucCopy": [],
            "insuranceCopy": [],
            "registrationCopyExists": null,
            "insuranceCopyExists": null,
            "pucValidityExists": null,
            "clientBranchName": "Jonson Logistics",
            "trackerList": [
                {
                    "trackerId": null,
                    "barcode": null,
                    "status": null,
                },
                {
                    "trackerId": null,
                    "barcode": null,
                    "status": null,
                }
            ]
        }
    ],
    "hasError": false
}
```


Retrieve details of required vehicles using this API.

- This API retrieves the details of a vehicle, including its name, model type, capacity, loading time, permit region, and other necessary information.
- Include the Reference IDs or Vehicle Numbers of the vehicles you want to search for in a comma-separated format in the URL.

API TYPE

- Tier 1 API.

REQUEST

GET `https://api.loginextsolutions.com/VehicleApp/mile/v1`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceIds	String		Optional	Unique reference identifier associated with the vehicle. This ID is used to identify the vehicle that you want to retrieve. If the 'vehicleNumbers' is not provided, then this field is mandatory.
vehicleNumbers	String		Optional	Unique number of the vehicle that you want to retrieve. If the 'referenceIds' is not provided, then this field is mandatory.

UPDATE

Sample Request


```
[
    {
        "vehicleReferenceId": "a9be39b9347911e6829f000d3aa04450",
        "vehicleNumber": "MH-111",
        "branchName": "Powai",
        "vehicleMake": "Marker",
        "vehicleModel": "Chevy",
        "vehicleType": "",
        "unladdenWeight": 1099,
        "capacityInWeight": 1099,
        "capacityInUnits": 1099,
        "capacityInVolume": 1099,
        "chasisNumber": "CHASIS-123",
        "engineNumber": "A-12353-D1234",
        "markerName": "Marker-1",
        "registrationNumber": "",
        "pucValidity": "2025-07-01T11:18:00.000Z",
        "insuranceValidity": "2025-07-01T11:18:00.000Z",
        "vehiclePermit": "New York, NY",
        "ownership": "company",
        "ownerName": "Mathew Richardson",
        "transporter": "",
        "financer": "",
        "accidentHistory": "",
        "rentStartDate": null,
        "rentEndDate": null,
        "vehicleProductionYear": null,
        "maxDistance": null,
        "loadingTimeInMins": null,
        "deviceId": {
            "barcode": ""
        },
        "trackerList": [
            {
                "trackerId" : "TR001"
            }, {
                "trackerId" : "TR002"
            }, {
                "trackerId" : "TR003"
            }
        ]
```

```
    }
]
```

Success Response

```
{
    "status": 200,
    "message": "Success",
    "data": null,
    "hasError": false
}
```

Failure Response: Incorrect Tracker ID

```
{
    "status": 409,
    "message": "Some issue encountered in server",
    "moreResultsExists": false,
    "hasError": true,
    "error": [
      {
          "index": 0,
          "key": "trackerList.trackerId",
          "message": [
             "${Tracker_s} Id is invalid."
          ],
          "errorCode": 142001
      }
  ]
}
```

Failure Response: Incorrect Tracker Branch

```
{
    "status": 409,
    "message": "Some issue encountered in server",
    "moreResultsExists": false,
    "hasError": true,
    "error": [
        {
            "index": 0,
            "key": "trackerList.trackerId",
            "message": [
                "${Tracker_s} branch is invalid."
            ],
            "errorCode": 142012
        }
    ]
}
```

Update an existing vehicle with this API.

- This API updates a vehicle with the details provided.
- It identifies vehicles using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Vehicle API response when the associated vehicle is created in the system.

API TYPE

- Tier 1 API.

REQUEST

PUT `https://api.loginextsolutions.com/VehicleApp/mile/v1/update`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
vehicleReferenceId	String	16	Conditional Mandatory	Unique reference identifier associated with the vehicle. This ID is used to identify the vehicle that you want to update.
branchName	String	255	Optional	Name of the branch that should be linked with this vehicle.
vehicleNumber	String	255	Conditional Mandatory	Unique number of the vehicle.
vehicleMake	String	255	Optional	Name of the manufacturer. For example - Mazda, Volvo, etc.
vehicleModel	String	40	Optional	Model of the vehicle. For example - FH series, MethaneDiesel, etc.
vehicleType	String	40	Optional	Type of the vehicle. Whether the vehicle is 2 wheeler or 4 wheeler.
unladdenWeight	Integer	10	Optional	Weight of the vehicle (in kg) when it is not loaded.
capacityInWeight	Integer	10	Optional	Capacity of the vehicle in weight (in kg).
capacityInUnits	Integer	10	Optional	Capacity of the vehicle in units.
capacityInVolume	Integer	10	Optional	Capacity of the vehicle in volume (in cubic centimeters).
chassisNumber	String	255	Optional	Chassis or VIN (Vehicle Identification Number) of the vehicle.
engineNumber	String	255	Optional	Engine number of the vehicle.
markerName	String	255	Optional	Name of the manufacturer.
registrationNumber	String	255	Optional	Registration number of the vehicle provided by the local transportation authority.
pucValidity	Date		Optional	Date until which the vehicle’s PUC certificate is valid. This date must always be later than the current date. Format - YYYY-MM DDTHH:MM:SS.SSSZ. For example - 2025-07-01T11:18:00.000Z.
insuranceValidity	Date		Optional	Date until which the vehicle’s insurance is valid. This date must always be later than the current date. Format - YYYY-MM DDTHH:MM:SS.SSSZ. For example - 2025-07-01T11:18:00.000Z.
vehiclePermit	String	40	Optional	Region where it is permitted to operate a vehicle.
vehicleProductionYear	Date		Optional	Production date of the vehicle. Format - YYYY-MM DDTHH:MM:SS.SSSZ. For example - 2016-07-01T11:18:00.000Z.
ownership	String	50	Optional	Entity that owns the vehicle. Whether the vehicle is owned by a company or vendor.
ownerName	String	255	Optional	Name of the company or vendor who owns the vehicle.
transporter	String	40	Optional	Name of the transporter.

financer	String	40	Optional	Name of the financer, if the vehicle is on loan.
accidentHistory	String	160	Optional	Specify the vehicle's accident history details, if any.
maxDistance	Integer	20	Optional	Maximum distance that the vehicle can travel in a day. This can be considered in Trip Planning.
loadingTimeInMins	Number	32	Optional	Time (in minutes) taken to load orders in the vehicle.
rentStartDate	Date		Optional	Date when the vehicle was rented. This input is valid only if the vehicle's owner is a vendor. Note that the Rent Start Date should be earlier than the Rent End Date. Format - YYYY-MM-DDTHH:MM:SS.SSSZ. For example - 2016-07-01T11:18:00.000Z.
rentEndDate	Date		Optional	Date till when the vehicle has been rented. This input is valid only if the vehicle's owner is a vendor. Note that the Rent End Date should be later than the Rent Start Date. Format - YYYY-MM-DDTHH:MM:SS.SSSZ. For example - 2024-07-01T11:18:00.000Z.
deviceId.barcode	String	50	Optional	Specify the barcode of the tracker to map it to the vehicle.
trackerList.trackerId	String	12	Mandatory	Unique identifier(s) associated with the tracker.

DELETE

Sample Request

```
["a9be39b9347911e6829f000d3aa04450"]
```

Success Response

```
{
    "status": 200,
    "message": "Success",
    "data": null,
    "hasError": false
}
```

Delete a vehicle with this API.

- If you wish to discontinue using specific vehicles, this API removes or deletes them permanently from the LogiNext system.
- It identifies vehicles using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Vehicle API response when the associated vehicle is created in the system.

API TYPE

- Tier 1 API.

REQUEST

DELETE `https://api.loginextsolutions.com/VehicleApp/mile/v1/delete`

REQUEST PARAMETER

Parameter	Datatype	Length	Required	Description
vehicleReferenceId	String	32	Mandatory	Unique reference identifier associated with the vehicle. This ID is used to identify the vehicle that you want to delete.

Driver

CREATE

Sample Request

```
[
    {
        "driverName": "John Doe",
        "branchName": "Manhattan",
        "phoneNumber": 1653764563,
        "emailId": "johndoe@ablogistics.com",
        "dateOfBirth": "1990-06-13",
        "languageList": [
            {
                "name": "English"
            },
            {
                "name": "Spanish"
            }
        ],
        "salary": "1000",
        "maritalStatus": "married",
        "gender": "male",
        "experience": 10,
        "licenseValidity": "2026-07-01T11:18:00.000Z",
        "licenseNumber": "LIC_104",
        "licenseType": "4 wheeler",
        "licenseIssueBy": "DMV",
        "addressList": [
            {
                "apartment": "10 Suite No. A1901",
                "streetName": "Walton Avenue",
                "landmark": "Opp. Chiptole",
                "countryShortCode": "USA",
                "stateShortCode": "IL",
                "city": "Chicago",
                "pincode": 72712,
                "isCurrentAddress": true
            },
            {
                "apartment": "A-902",
                "streetName": "50 E 78th St",
                "landmark": "Opp. Strand Bookstore",
                "countryShortCode": "USA",
                "stateShortCode": "NY",
                "city": "New York",
                "pincode": 10075,
                "isCurrentAddress": false
            }
        ],
        "driverEmployeeId": "D23",
        "shiftList": [
            {
                "shiftStartTime": "2019-03-26T10:30:00.000Z",
                "shiftEndTime": "2019-03-26T17:30:00.000Z"
            }
        ],
        "previousCompanyName": "ABC",
        "reportingManager": "Chris",
        "managerPhoneNumber": 1234567890,
        "managerEmailId": "chris@ablogistic.com"
    }
```

```
]
```

Success Response

```
{
    "status": 201,
    "message": "Driver Created Successfully",
    "data": [
        {
            "referenceId": "122e948ce6cc40fb85492c4c5a600816",
            "licenseNumber": "LIC_104"
        }
    ],
    "hasError": false
}
```

Create new drivers in the LogiNext system with this API.

- This API creates a Driver and assigns a unique Reference ID that can be used to identify the driver later.

API TYPE

- Tier 1 API.

REQUEST

POST `https://api.loginextsolutions.com/DriverApp/mile/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
driverName	String	255	Mandatory	Name of the driver.
branchName	String	255	Optional	Name of the branch with which the driver should be linked.
phoneNumber	Integer	255	Mandatory	Contact number of the driver.
emailId	String	100	Optional	Email ID of the driver.
dateOfBirth	String		Optional	Date of birth of the driver in YYYY-MM-DD format. For example - 2000-07-01.
vehicleReferenceId	String	32	Optional	Vehicle assigned to the driver.
languageList	List of Objects		Optional	List of language(s) that the driver is able to understand.
languageList.name	String	40	Optional	Name of language(s) that the driver is able to understand.
salary	String	18	Optional	Current salary of the driver.
maritalStatus	String	20	Optional	Marital status of the driver. For example - married, unmarried.
gender	String	12	Optional	Gender of the driver. For example - male, female.
experience	Integer	3	Optional	Total working experience of the driver in years.
licenseValidity	String		Optional	Date until which the license is valid in YYYY-MM DDTHH:MM:SS.SSSZ

				format. For example - 2025-07-01T11:18:00.000Z.
licenseNumber	String	255	Mandatory	Driving license number of the driver.
licenseType	String	40	Optional	Type of the license. Whether the license type is 2 wheeler or 4 wheeler.
licenseIssueBy	String	40	Optional	Entity responsible for issuing the license to the driver.
addressList	List		Conditional Mandatory	Enter the address details of the driver within this parameter.
addressList.apartment	String	512	Mandatory	Name of the apartment building/complex in the driver’s address.
addressList.streetName	String	255	Mandatory	Name of the society or street in the driver’s address.
addressList.landmark	String	512	Mandatory	Landmark of the driver’s location.
addressList.areaName	String	255	Optional	Name of the locality or area in the driver’s address.
addressList.countryShortCode	String	3	Mandatory	Name of the country in the driver’s address. This should be as per the Country Codes available in the LogiNext system.
addressList.stateShortCode	String	3	Mandatory	Name of the state in the driver’s address. This should be as per the State Codes available in the LogiNext system for the selected country.
addressList.city	String	512	Mandatory	Name of the city in the driver’s address.
addressList.pincode	Integer	12	Mandatory	Pin code of the driver’s location.
addressList.isCurrentAddress	Boolean		Mandatory	Indicate whether this address is the current or permanent address of the driver. Specify this parameter as 'true' to mark it as current or 'false' to mark it as permanent.
driverEmployeeId	String	50	Optional	Employee ID of the driver.
shiftList	List		Optional	Enter the shift details of the driver within this parameter.
shiftList.shiftStartTime	String		Mandatory	Shift start time of the driver in YYYY-MM DDTHH:MM:SS.SSSZ format. For example - 2024-07-01T11:18:00.000Z.
shiftList.shiftEndTime	String		Mandatory	Shift end time of the driver in YYYY-MM DDTHH:MM:SS.SSSZ format. For example - 2024-07-01T11:18:00.000Z.
previousCompanyName	String	255	Optional	Name of the previous company the driver worked for.
reportingManager	String	40	Optional	Name of the driver's reporting manager at their previous company.
managerPhoneNumber	Integer	255	Optional	Contact number of the driver's reporting manager at the previous company.
managerEmailId	String	100	Optional	Email ID of the driver’s reporting manager at their previous company.

GET

Sample Request

```
https://api.loginextsolutions.com/DriverApp/mile/v1?referenceIds={1c3a551f47534b98a29d916b0405}&licenseNumbers={LIC_104}
```

Success Response


```
{
    "status": 200,
    "message": "Success",
    "data": [
        {
            "referenceId": "1c3a551f47534b98a29d916b0405",
            "driverName": "John Doe",
            "phoneNumber": "1653023543",
            "emailId": "johndoe@ablogistics.com",
            "licenseNumber": "LIC_104",
            "licenseValidity": 1591986600000,
            "license": null,
            "salary": 10000,
            "capacity": null,
            "addressLine1": null,
            "addressLine2": null,
            "city": null,
            "state": null,
            "pinCode": null,
            "licenseType": "4 wheeler",
            "defaultVehicle": null,
            "vehicleNumber": null,
            "licenseAlertWindow": null,
            "attendance": null,
            "workHour": null,
            "status": null,
            "dateOfBirth": 1465776000000,
            "experience": "11",
            "maritalStatus": "married",
            "gender": "female",
            "languageList": [
                {
                    "name": "English"
                },
                {
                    "name": "Spanish"
                }
            ],
            "licenseIssueBy": "DMV.",
            "tripName": null,
            "previousCompanyName": "AB Logistics",
            "driverEmployeeId": "D23",
            "reportingManager": "Chris",
            "managerPhoneNumber": "1234567890",
            "managerEmailId": "chris@ablogistics.com",
            "deviceId": null,
            "trackingDate": null,
            "deviceBarcode": null,
            "shiftList": [
                {
                    "shiftStartTime": "2017-09-12T14:00:00.000Z",
                    "shiftEndTime": "2017-09-12T15:00:00.000Z",
                    "startTime": null,
                    "endTime": null
                }
            ],
            "addressList": [],
            "lat": null,
            "lng": null,
            "isPresent": null,
            "tripStatus": null,
            "batteryPerc": null,
```

```
            "lastLicenseAlertSentDt": null,
            "clientBranchName": null,
            "previousPhoneNumber": null
        }
    ],
    "hasError": false
}
```


Retrieve details of required drivers using this API.

- This API retrieves the details of a driver, including contact information, license details, attendance, working hours, current status, previous work experience, shift timings, and more.
- Include the Reference IDs or License Numbers of the drivers you want to search for in the Request Body.

API TYPE

- Tier 1 API.
- This API accepts up to 20 Reference IDs or License Numbers in a comma-separated format in the URL.

REQUEST

GET `https://api.loginextsolutions.com/DriverApp/mile/v1`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceIds	String		Conditional Mandatory	Unique reference identifier associated with the driver whose information you want to retrieve. This ID is generated by the LogiNext system while creating a driver to identify them for future reference. If the 'licenseNumbers' is not provided, then this field is mandatory.
licenseNumbers	String		Conditional Mandatory	License number associated with the driver whose information you want to retrieve. If the 'referenceIds' is not provided, then this field is mandatory.

UPDATE

Sample Request


```
[
    {
        "driverReferenceId": "1c3a551f47534b98a29d916b0405fd6d",
        "driverName": "John Doe",
        "branchName": "Manhattan",
        "phoneNumber": 1653764563,
        "emailId": "johndoe@ablogistics.com",
        "dateOfBirth": "1990-06-13",
        "languageList": [
            {
                "name": "English"
            },
            {
                "name": "Spanish"
            }
        ],
        "salary": "1000",
        "maritalStatus": "married",
        "gender": "male",
        "experience": 10,
        "licenseValidity": "2026-07-01T11:18:00.000Z",
        "licenseNumber": "LIC_104",
        "licenseType": "4 wheeler",
        "licenseIssueBy": "DMV",
```

```
        "addressList": [
            {
                "apartment": "10 Suite No. A1901",
                "streetName": "Walton Avenue",
                "landmark": "Opp. Chiptole",
                "countryShortCode": "USA",
                "stateShortCode": "IL",
                "city": "Chicago",
                "pincode": 72712,
                "isCurrentAddress": true
            },
            {
                "apartment": "A-902",
                "streetName": "50 E 78th St",
                "landmark": "Opp. Strand Bookstore",
                "countryShortCode": "USA",
                "stateShortCode": "NY",
                "city": "New York",
                "pincode": 10075,
                "isCurrentAddress": false
            }
        ],
        "driverEmployeeId": "D23",
        "shiftList": [
            {
                "shiftStartTime": "2019-03-26T10:30:00.000Z",
                "shiftEndTime": "2019-03-26T17:30:00.000Z"
            }
        ],
        "previousCompanyName": "ABC",
        "reportingManager": "Chris",
        "managerPhoneNumber": 1234567890,
        "managerEmailId": "chris@ablogistic.com"
    }
]
```

Success Response

```
{
    "status": 200,
    "message": "Success",
    "data": null,
    "hasError": false
}
```

Update an existing driver with this API.

- This API updates a driver with the details provided.
- It identifies drivers using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Driver API response when the associated driver is created in the system.

API TYPE

- Tier 1 API.

REQUEST

PUT `https://api.loginextsolutions.com/DriverApp/mile/v1/update`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description

driverReferenceId	String	32	Mandatory	Unique reference identifier associated with the driver. This ID is used to identify the driver that you want to update.
driverName	String	255	Optional	Name of the driver.
branchName	String	255	Optional	Name of the branch with which the driver should be linked.
phoneNumber	Integer	255	Optional	Contact number of the driver.
emailId	String	100	Optional	Email ID of the driver.
dateOfBirth	String		Optional	Date of birth of the driver in YYYY-MM-DD format. For example - 2000-07-01.
vehicleReferenceId	String	32	Optional	Vehicle assigned to the driver.
languageList	List of Objects		Optional	List of language(s) that the driver is able to understand.
languageList.name	String	40	Optional	Name of language(s) that the driver is able to understand.
salary	String	18	Optional	Current salary of the driver.
maritalStatus	String	20	Optional	Marital status of the driver. For example - married, unmarried.
gender	String	12	Optional	Gender of the driver. For example - male, female.
experience	Integer	3	Optional	Total working experience of the driver in years.
licenseValidity	String		Optional	Date until which the license is valid in YYYY-MM DDTHH:MM:SS.SSSZ format. For example - 2025-07-01T11:18:00.000Z.
licenseNumber	String	255	Optional	Driving license number of the driver.
licenseType	String	40	Optional	Type of the license. Whether the license type is 2 wheeler or 4 wheeler.
licenseIssueBy	String	40	Optional	Entity responsible for issuing the license to the driver.
addressList	List		Conditional Mandatory	Enter the address details of the driver within this parameter.
addressList.apartment	String	512	Optional	Name of the apartment building/complex in the driver’s address.
addressList.streetName	String	255	Optional	Name of the society or street in the driver’s address.
addressList.landmark	String	512	Optional	Landmark of the driver’s location.
addressList.areaName	String	255	Optional	Name of the locality or area in the driver’s address.
addressList.countryShortCode	String	3	Optional	Name of the country in the driver’s address. This should be as per the Country Codes available in the LogiNext system.
addressList.stateShortCode	String	3	Optional	Name of the state in the driver’s address. This should be as per the State Codes available in the LogiNext system for the selected country.
addressList.city	String	512	Optional	Name of the city in the driver’s address.

addressList.pincode	Integer	12	Optional	Pin code of the driver's location.
addressList.isCurrentAddress	Boolean		Optional	Indicate whether this address is the current or permanent address of the driver. Specify this parameter as 'true' to mark it as current or 'false' to mark it as permanent.
driverEmployeeId	String	50	Optional	Employee ID of the driver.
shiftList	List		Optional	Enter the shift details of the driver within this parameter.
shiftList.shiftStartTime	String		Optional	Shift start time of the driver in YYYY-MM DDTHH:MM:SS.SSSZ format. For example - 2024-07-01T11:18:00.000Z.
shiftList.shiftEndTime	String		Optional	Shift end time of the driver in YYYY-MM DDTHH:MM:SS.SSSZ format. For example - 2024-07-01T11:18:00.000Z.
previousCompanyName	String	255	Optional	Name of the previous company the driver worked for.
reportingManager	String	40	Optional	Name of the driver's reporting manager at their previous company.
managerPhoneNumber	Integer	255	Optional	Contact number of the driver's reporting manager at the previous company.
managerEmailId	String	100	Optional	Email ID of the driver's reporting manager at their previous company.

DELETE

Sample Request

```
["e0eaebdd84ac4c40af72d827ab610090"]
```

Success Response

```
{
    "status": 200,
    "message": "Success",
    "data": null,
    "hasError": false
}
```

Delete a driver with this API.

- If you wish to discontinue with specific drivers, this API removes or deletes them permanently from the LogiNext system.
- It identifies drivers using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Driver API response when the associated driver is created in the system.

API TYPE

- Tier 1 API.

REQUEST

DELETE `https://api.loginextsolutions.com/DriverApp/mile/v1/delete`

REQUEST PARAMETER

Parameter	Datatype	Length	Required	Description
driverReferenceId	String	32	Mandatory	Unique reference identifier associated with the driver. This ID is used to identify

the driver that you want to delete.

Geofence

GET

Sample Request

```
https://api.loginextsolutions.com/GeofenceApp/geofence/v1/get?geofenceIds=MMD-White Marsh,MMD-Patapsco High/Dundalk&page_no=1&page_size=50&status=ACTIVE
```

Success Response


```
{
    "status": 200,
    "message": "Geofence details fetched successfully.",
    "data": [
        {
            "isActiveFl": true,
            "customFields": [
                {
                    "field": "cf_deliveryDay",
                    "value": "1533081600000",
                    "type": "date"
                },
                {
                    "field": "cf_deliveryTime",
                    "value": "10:00",
                    "type": "time"
                },
                {
                    "field": "cf_cutOffDay",
                    "value": "1533168000000",
                    "type": "date"
                },
                {
                    "field": "cf_cutOffTime",
                    "value": "11:00",
                    "type": "time"
                }
            ],
            "geofenceName": "MMD-Patapsco High/Dundalk",
            "referenceId": "fa7716b25fe5432a96d1a709a28bd6d8",
            "geofenceShape": "Polygon",
            "geofenceArea": 0,
            "geoCoordinates": [
                {
                    "latitude": 39.2363378,
                    "longitude": -76.53115
                },
                {
                    "latitude": 39.2257375,
                    "longitude": -76.5072441
                },
                {
                    "latitude": 39.2014656,
                    "longitude": -76.5027766
                },
                {
```

```
                    "latitude": 39.1995356,
                    "longitude": -76.4608956
                },
                {
                    "latitude": 39.2201521,
                    "longitude": -76.4421844
                },
                {
                    "latitude": 39.2402943,
                    "longitude": -76.4087104
                }
            ]
        }
    ],
    "hasError": false
}
```


Retrieve details of required geofences using this API.

- If you have configured geofences in the LogiNext system to identify your branches or specific locations, you can call this API to retrieve the geofence details and coordinates.
- Include the Reference IDs, Name, or Status of the geofence you want to retrieve in the Request Body.
- If you provide multiple geofence IDs or names as well as specify the status, the API will retrieve only those geofences that match the given IDs or names and status.

API TYPE

- Tier 2 API.
- This API accepts multiple Geofence IDs or Geofence Names in a comma-separated format in the URL.

REQUEST

GET `https://api.loginextsolutions.com/GeofenceApp/geofence/v1/get`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
geofenceIds	String		Optional	Unique reference identifier or name associated with the geofence. This ID is used to identify the geofence that you want to retrieve. If the geofence name contains special characters, the API accepts encoded values for these characters. For example, a space (' ') will be denoted by '%20'.
status	String		Optional	Status of the geofence. Whether you want to retrieve 'Active', 'Inactive' or 'All' geofences. If this field is not provided, by default the API returns all geofences.
page_no	Integer		Optional	Specify the page number to fetch using this parameter. By default, the value is set to 1.
page_size	Integer		Optional	Specify the number of records to fetch using this parameter. By default, the API returns 100 records.

RESPONSE PARAMETERS

Parameter	Datatype	Length	Required	Description
isActiveFl	Boolean			Specifies whether the geofence is active or not.
referenceId	String			Unique reference identifier associated with the geofence.
geofenceName	String			Name of the geofence specified during creation.
geofenceShape	Date			By default, this field will be 'Polygon'.

geofenceArea	Date	Area of the geofence. This field uses the units configured in the Unit System field under System Preferences in the Settings module. For example, if the units are configured as meters, this field will be in square meters.
geoCoordinates.latitude	Double	Latitude coordinates of the geofence edge or boundary.
geoCoordinates.longitude	Double	Longitude coordinates of the geofence edge or boundary.

Order Request

Create new order requests in the LogiNext system with these Order Request APIs.

- These APIs create an Order Request and assign a unique Reference ID that can be used to identify the order request later.
- If the Customer Profiling property is enabled, enter the Customer ID of an existing customer in the 'accountCode' field to automatically retrieve details such as name, email ID, contact number, and more when creating an order request.
- If the selected customer has multiple addresses, specify the Address ID in the 'AddressId' field to fetch the associated address details when creating an order request.
- If the Customer Profiling property is disabled, enter the necessary customer details, as needed.

Note:

- You can create a maximum of 20 order requests in one call of this API.
- This API does not support partial success responses. If any order request in a batch fails validation check, all order requests in that call will be considered failed.

CREATE PICK UP ONLY

Sample Request

```
[
  {
   "shipmentRequestNo":"SH12432",
   "awbNumber": "435-16685675",
   "shipmentRequestDispatchDate": "2020-05-19T10:30:00.000Z",
   "shipmentRequestType":"PICKUP",
   "packageWeight":"10",
   "packageVolume":"10",
   "originalOrderValue": "500",
   "orderDiscount": "10",
   "packageValue":"450",
   "insuranceRequiredFl": "Y",
   "insuredValue": "450",
   "signatureRequiredFl": "Y",
   "totalShippingCost":"10",
   "packageLength":"10",
   "packageBreadth":"10",
   "packageHeight":"10",
   "priority":"Priority 1",
   "paymentType":"COD",
   "numberOfItems":1,
   "packagingRequiredFl": "Y",
   "deliveryType":"Groceries",
   "serviceType":"Express",
   "distributionCenter":"Main Branch",
   "pickupBranch":"Main Branch",
   "pickupServiceTime": "50",
   "pickupStartTimeWindow": "2020-05-19T14:24:00.000Z",
   "pickupEndTimeWindow": "2020-05-19T14:24:00.000Z",
```

```
    "pickupEmail":"james.w@ablogs.com",
    "pickupPhoneNumber": "5163063377",
    "pickupWhatsappOptin":"Y",
    "pickupAccountCode": "jim001",
    "pickupAddressId": "Home",
    "pickupAddressType":"Home",
    "pickupAccountName": "James Walker",
    "pickupApartment": "901",
    "pickupStreetName": "2142 3rd Ave",
    "pickupLandmark": "Opp. McDonalds",
    "pickupLocality": "East Harlem",
    "pickupCity": "New York",
    "pickupState": "NY",
    "pickupCountry": "USA",
    "pickupPinCode": "10035",
    "pickupLatitude":40.760838,
    "pickupLongitude":-73.96732299999996,
    "pickupAddressTimezone":"America/New_York",
    "pickupNotes":"notes for pickup",
    "clientCode":"ShipGenie",
    "parentOrderNo": "GR432U578577",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
        {
            "crateCd": "CR041",
            "crateName": "Crate501",
            "crateAmount": 100.65,
            "crateType": "case",
            "noOfUnits": 2,
            "crateWeight": 10,
            "crateVolume": 11,
            "crateLength": 12,
            "crateBreadth": 13,
            "crateHeight": 14,
            "shipmentlineitems": [
                {
                    "itemCd": "IT043",
                    "itemName": "Chicken Soup 2X200gm",
                    "itemPrice": 500,
                    "itemQuantity": 1,
                    "itemType": "soup",
                    "itemWeight": 10,
                    "itemVolume": 11,
                    "itemLength": 12,
                    "itemBreadth": 13,
                    "itemHeight": 14
                }
            ]
        }
    ]
    }
]
```


Success Response


```
{
    "status": 200,
    "message": "Shipment Request(s) created successfully",
    "moreResultsExists": false,
    "data": [
        {
            "index": 0,
            "shipmentRequestReferenceId": "2c0dcb93ca494cfc92d5b830c1c8033a",
            "shipmentRequestNo": "SH12432",
```

```
            "shipmentRequestType": "PICKUP"
        }
    ],
    "hasError": false
}
```

Failure Response

```
{
    "status": 409,
    "message": "Shipment Request Creation Failed",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "PICKUP",
            "errorList": [
                {
                    "key": "pickupAccountCode",
                    "message": [
                        "Address not serviceable"
                    ]
                },
                {
                    "key": "deliveryType",
                    "message": [
                        "DeliveryType is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Create requests for Pickup orders in the LogiNext system with this API.

- This API creates a request for a Pickup type of order and assigns a unique Reference ID that can be used to identify the order request later.
- Call this API along with the provided parameters to push existing pickup order requests from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/BookingApp/mile/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
shipmentRequestNo	String	255	Optional	Unique identifier associated with the order request. You can enter any alphanumeric value as an order request number. If not provided, the system will auto-generate an order request number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order request.
shipmentRequestDispatchDate			Optional	Specify the requested dispatch date of the order. This date indicates when the system should start processing/servicing the order request, using the configured service types or zonal capacities. If

				not provided, the system defaults to the current date.
shipmentRequestType	String	40	Mandatory	The value in this field must always be ‘PICKUP’.
distributionCenter	String	255	Optional	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in Order Prioritizing under Order Configuration in the Settings module. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
serviceType	String	16	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.

signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
totalShippingCost	Double	10	Optional	The total cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If the shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+totalShippingCost.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of pickup. If no value is provided, the system considers 'COD' by default.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
deliveryType	String	40	Optional	If your order requires specific skills for pickup, you can specify it here. For example, groceries and food items must be separated from toiletries, or cakes cannot be delivered with flowers. The planning engine takes into account the skill set requirement for the order and assigns a delivery associate who possesses the specified Skill Set. Note that you must only select from the Skill Sets that are linked to the Service Types mapped to the order’s shipper. You can pass multiple Skill Sets in a comma-separated format in this API.
deliveryLocationType	String	255	Optional	Type of customer address, e.g., Residential, Office, etc.
pickupBranch	String	255	Optional	For pickup type of order requests, this field specifies the branch where the delivery associate will deliver the pickup order. It is recommended to leave this field blank so the system can use the branch linked to the pickup location's zone. However, you can provide this information if the shipper creating the order request is not linked to a Service Area Profile in the LogiNext system.
pickupServiceTime	Integer	11	Optional	Specify the time required to pick up the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the pickup time window.
pickupStartTimeWindow	Date		Optional	The opening time of the pickup time window. Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. It is recommended to leave this field blank so the system can calculate the Order Time Windows based on the Service Type or capacity configuration set up in your account. If this field is provided and no Service Area Profile is linked to the shipper, the system will skip the time window calculations and use the provided time windows at the order level. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Optional	The closing time of the pickup time window. It is recommended to leave this field blank so the system can calculate the Order Time Windows based on the Service Type or capacity configuration in your account. If this field is provided and no Service Area Profile is linked to the shipper, the system will skip the time window calculations

				and use the provided time windows at the order level. Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Mandatory	Name of the society or street in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Conditional Mandatory	Landmark of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Conditional Mandatory	Name of the state in the customer's pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer's pickup address.

pickupLongitude	Double		Optional	Longitude coordinates of the customer's pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer's pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify 'Y' to enable cancellations or 'N' to prevent them. If no value is provided, the system considers 'Y' by default.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver a partial order (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify 'Y' to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or 'N' to prevent partial deliveries. If no value is provided, the system considers 'Y' by default.
returnAllowedFl	String	50	Optional	Whether the order is returnable or not. This will let your customer initiate a return order request post delivery, if required. Specify 'Y' to allow return, or 'N' to prevent return requests for this order.
returnBranch	String	255	Conditional Mandatory	Name of return branch. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnPhoneNumber	String	255	Conditional Mandatory	Contact number of the return customer.
returnWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
returnAddressId	String	255	Optional	Identifier assigned to a return customer's address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer's return

				address.
returnStreetName	String	255	Optional	Name of the society or street in the customer's return address.
returnLandmark	String	512	Optional	Landmark of the customer's return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer's return address.
returnCity	String	512	Optional	Name of the city in the customer's return address.
returnState	String	50	Optional	Name of the state in the customer's return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer's return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
returnTimezone	String		Optional	Timezone of the customer's return address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
returnAWB	String	255	Optional	Air Waybill or AWB number associated with a return order request. If not provided, the system will consider the existing AWB as the return AWB.
clientCode	String	32	Optional	Name of the company associated with the shipper's account. Pass the company name of the shipper's account if you want to create an order request on behalf of one of your shippers.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as 'Related Orders'. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z' , 'A to Z', '0 to 9' , '_'(underscore) and '-'(hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt-out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Specify the crate details of the order. In case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.

shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid/semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order request.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.

shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

CREATE DELIVERY ONLY

Sample Request


```
[
  {
   "shipmentRequestNo":"SH12432",
   "awbNumber": "435-16685675",
   "shipmentRequestDispatchDate": "2020-05-19T10:30:00.000Z",
   "shipmentRequestType":"DELIVER",
   "packageWeight":"10",
   "packageVolume":"10",
   "originalOrderValue": "500",
   "orderDiscount": "10",
   "packageValue":"450",
   "insuranceRequiredFl": "Y",
   "insuredValue": "450",
   "signatureRequiredFl": "Y",
   "totalShippingCost":"10",
   "packageLength":"10",
   "packageBreadth":"10",
   "packageHeight":"10",
   "priority":"Priority 1",
   "paymentType":"COD",
   "numberOfItems":1,
   "packagingRequiredFl": "Y",
   "deliveryType":"Groceries",
   "serviceType":"Express",
   "distributionCenter":"New York Main Branch",
   "deliverBranch":"New York Main Branch",
   "deliverServiceTime":"10",
   "deliverStartTimeWindow": "2020-04-10T10:31:00.000Z",
   "deliverEndTimeWindow": "2020-04-10T10:31:00.000Z",
   "deliverAccountCode": "Matt001",
```

```
    "deliverAccountName":"Jane Doe",
    "deliverEmail":"m.richardson@testmail.com",
    "deliverPhoneNumber":"9891234567",
    "deliverWhatsappOptin":"Y",
    "deliverAddressId": "home",
    "deliverAddressType":"Home",
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Towm Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude":41.882702,
    "deliverLongitude":-87.619392,
    "deliverAddressTimezone":"America/Chicago",
    "deliverNotes":"notes for delivery",
    "clientCode":"Ship Logistics",
    "parentOrderNo": "GR432U578577",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
        {
            "crateCd": "CR041",
            "crateAmount": 100.65,
            "crateType": "case",
            "noOfUnits": 2,
            "crateWeight": 10,
            "crateVolume": 11,
            "crateLength": 12,
            "crateBreadth": 13,
            "crateHeight": 14,
            "shipmentlineitems": [
                {
                    "itemCd": "IT043",
                    "itemName": "Chicken Soup 2X200gm",
                    "itemPrice": 500,
                    "itemQuantity": 1,
                    "itemType": "soup",
                    "itemWeight": 10,
                    "itemVolume": 11,
                    "itemLength": 12,
                    "itemBreadth": 13,
                    "itemHeight": 14
                }
            ]
        }
    ]
    }
]
```


Success Response


```
{
    "status": 200,
    "message": "Shipment Request(s) created successfully",
    "moreResultsExists": false,
    "data": [
        {
            "index": 0,
            "shipmentRequestReferenceId": "2c0dcb93ca494cfc92d5b830c1c8033a",
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "PICKUP"
        }
```

```
    ],
    "hasError": false
}
```

Failure Response

```
{
    "status": 409,
    "message": "Shipment Request Creation Failed",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "DELIVER",
            "errorList": [
                {
                    "key": "deliverAccountCode",
                    "message": [
                        "Address not serviceable"
                    ]
                },
                {
                    "key": "deliveryType",
                    "message": [
                        "DeliveryType is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Create requests for Delivery orders in the LogiNext system with this API.

- This API creates a request for a Delivery type of order and assigns a unique Reference ID that can be used to identify the order request later.
- Call this API along with the provided parameters to push existing delivery order requests from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/BookingApp/mile/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
shipmentRequestNo	String	255	Optional	Unique identifier associated with the order request. You can enter any alphanumeric value as an order request number. If not provided, the system will auto-generate an order request number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order request.
shipmentRequestDispatchDate			Optional	Specify the requested dispatch date of the order. This date indicates when the system should start processing/servicing the order request, using the configured service types or zonal capacities. If not provided, the system defaults to the current date.

shipmentRequestType	String	40	Mandatory	The value in this field must always be ‘DELIVER’.
distributionCenter	String	255	Optional	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in Order Prioritizing under Order Configuration in the Settings module. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
serviceType	String	16	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
				Whether you want the signature/adult signature for the order or

signatureRequiredFl	String	16	Optional	not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
totalShippingCost	Double	10	Optional	The total cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If the shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+totalShippingCost.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of delivery. If no value is provided, the system considers 'COD' by default.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
deliveryType	String	40	Optional	If your order requires specific skills for delivery, you can specify it here. For example, groceries and food items must be separated from toiletries, or cakes cannot be delivered with flowers. The planning engine takes into account the skill set requirement for the order and assigns a delivery associate who possesses the specified Skill Set. Note that you must only select from the Skill Sets that are linked to the Service Types mapped to the order’s shipper. You can pass multiple Skill Sets in a comma-separated format in this API.
deliverBranch	String	255	Optional	For the delivery type of order requests, this field specifies the branch where the delivery associate will pick up the order. Note that you must specify the Operation Branch using the Add Branch API or the Add Branch form in the Branch Configuration module. In case of any issues while creating a branch, contact your Account Manager.
deliverServiceTime	Integer	11	Optional	Specify the time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the customer ID, you can fetch several fields.
			Conditional	Name of the delivery customer. This field is optional if the Customer

deliverAccountName	String	255	Mandatory	Profiling property is enabled.
deliverEmail	String	100	Optional	Email ID of the customer.
deliverPhoneNumber	String	255	Optional	Contact number of the customer. This field is optional if the Customer Profiling property is enabled.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String	50	Conditional Mandatory	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer's delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer's delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer's delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
				Whether customers are allowed to initiate a cancel order request

cancellationAllowedFl	String	1	Optional	after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver a partial order (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
returnAllowedFl	String	50	Optional	Whether the order is returnable or not. This will let your customer initiate a return order request post delivery, if required. Specify ‘Y’ to allow return, or ‘N’ to prevent return requests for this order.
returnBranch	String	255	Conditional Mandatory	Name of return branch. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
clientCode	String	32	Optional	Name of the company associated with the shipper’s account. Pass the company name of the shipper’s account if you want to create an order request on behalf of one of your shippers.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as ‘Related Orders’. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z’ , 'A to Z’, '0 to 9’ , ’_’(underscore) and ’-’(hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt-out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Specify the crate details of the order. In case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order request.

shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be

				in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

CREATE PICKUP AND DELIVER

Sample Request


```
[
  {
   "shipmentRequestNo":"SH12432",
   "awbNumber": "435-16685675",
   "shipmentRequestDispatchDate": "2020-05-19T10:30:00.000Z",
   "shipmentRequestType":"BOTH",
   "packageWeight":"10",
   "packageVolume":"10",
   "originalOrderValue": "500",
   "orderDiscount": "10",
   "packageValue":"450",
   "insuranceRequiredFl": "Y",
   "insuredValue": "450",
   "signatureRequiredFl": "Y",
   "totalShippingCost":"10",
   "packageLength":"10",
   "packageBreadth":"10",
   "packageHeight":"10",
   "priority":"Priority 1",
   "paymentType":"COD",
   "numberOfItems":1,
   "packagingRequiredFl": "Y",
   "deliveryType":"Groceries",
   "serviceType":"Express",
   "distributionCenter":"New York Main Branch",
   "pickupBranch":"mea_allmile_sandbox Main Branch",
   "pickupServiceTime": "50",
   "pickupStartTimeWindow": "2020-05-19T14:24:00.000Z",
   "pickupEndTimeWindow": "2020-05-19T14:24:00.000Z",
   "pickupEmail":"james.w@ablogs.com",
   "pickupPhoneNumber": "5163063377",
   "pickupWhatsappOptin":"Y",
   "pickupAccountCode": "jim001",
   "pickupAddressId": "Home",
   "pickupAddressType":"Home",
   "pickupAccountName": "James Walker",
   "pickupApartment": "901",
   "pickupStreetName": "2142 3rd Ave",
   "pickupLandmark": "Opp. McDonalds",
   "pickupLocality": "East Harlem",
   "pickupCity": "New York",
   "pickupState": "NY",
   "pickupCountry": "USA",
```

```
    "pickupPinCode": "10035",
    "pickupLatitude":40.760838,
    "pickupLongitude":-73.96732299999996,
    "pickupAddressTimezone":"America/New_York",
    "deliverBranch":"New York Main Branch",
    "deliverServiceTime":"10",
    "deliverStartTimeWindow": "2020-04-10T10:31:00.000Z",
    "deliverEndTimeWindow": "2020-04-10T10:31:00.000Z",
    "deliverAccountCode": "Matt001",
    "deliverAccountName":"Jane Doe",
    "deliverEmail":"m.richardson@testmail.com",
    "deliverPhoneNumber":"9891234567",
    "deliverWhatsappOptin":"Y",
    "deliverAddressId": "home",
    "deliverAddressType":"Home",
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Towm Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude":41.882702,
    "deliverLongitude":-87.619392,
    "deliverAddressTimezone":"America/Chicago",
    "deliverNotes":"notes for delivery",
    "clientCode":"Ship Logistics",
    "parentOrderNo": "GR432U578577",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
        {
            "crateCd": "CR041",
            "crateAmount": 100.65,
            "crateType": "case",
            "noOfUnits": 2,
            "crateWeight": 10,
            "crateVolume": 11,
            "crateLength": 12,
            "crateBreadth": 13,
            "crateHeight": 14,
            "shipmentlineitems": [
                {
                    "itemCd": "IT043",
                    "itemName": "Chicken Soup 2X200gm",
                    "itemPrice": 500,
                    "itemQuantity": 1,
                    "itemType": "soup",
                    "itemWeight": 10,
                    "itemVolume": 11,
                    "itemLength": 12,
                    "itemBreadth": 13,
                    "itemHeight": 14
                }
            ]
        }
    ]
    }
]
```


Success Response


```
{
    "status": 200,
```

```
    "message": "Shipment Request(s) created successfully",
    "moreResultsExists": false,
    "data": [
        {
            "index": 0,
            "shipmentRequestReferenceId": "2c0dcb93ca494cfc92d5b830c1c8033a",
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "BOTH"
        }
    ],
    "hasError": false
}
```


Failure Response


```
{
    "status": 409,
    "message": "Shipment Request Creation Failed",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "DELIVER",
            "errorList": [
                {
                    "key": "deliverAccountCode",
                    "message": [
                        "Address not serviceable"
                    ]
                },
                {
                    "key": "deliveryType",
                    "message": [
                        "DeliveryType is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```


Create requests for Pickup and Delivery orders in the LogiNext system with this API.

- This API creates a request for a Pickup and Delivery type of order (i.e., An order picked up from the pickup location and brought to your branch before being picked up again and delivered to the delivery location) and assigns a unique Reference ID that can be used to identify the order request later.
- Call this API along with the provided parameters to push existing pickup and delivery order requests from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/BookingApp/mile/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description

shipmentRequestNo	String	255	Optional	Unique identifier associated with the order request. You can enter any alphanumeric value as an order request number. If not provided, the system will auto-generate an order request number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order request.
shipmentRequestDispatchDate			Optional	Specify the requested dispatch date of the order. This date indicates when the system should start processing/servicing the order request, using the configured service types or zonal capacities. If not provided, the system defaults to the current date.
shipmentRequestType	String	40	Mandatory	The value in this field must always be ‘BOTH’.
distributionCenter	String	255	Optional	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in Order Prioritizing under Order Configuration in the Settings module. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
serviceType	String	16	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.

insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
totalShippingCost	Double	10	Optional	The total cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If the shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+totalShippingCost.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of delivery. If no value is provided, the system considers 'COD' by default.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
deliveryType	String	40	Optional	If your order requires specific skill, you can specify it here. For example, groceries and food items must be separated from toiletries, or cakes cannot be delivered with flowers. The planning engine takes into account the skill set requirement for the order and assigns a delivery associate who possesses the specified Skill Set. Note that you must only select from the Skill Sets that are linked to the Service Types mapped to the order’s shipper. You can pass multiple Skill Sets in a comma-separated format in this API.
deliverBranch	String	255	Optional	For the pickup and delivery type of order requests, this field specifies the branch where the delivery associate will pick up the order. Note that you must specify the Operation Branch using the Add Branch API or the Add Branch form in the Branch Configuration module. In case of any issues while creating a branch, contact your Account Manager.
pickupStartTimeWindow	Date		Mandatory	The opening time of the pickup time window. Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Optional	The closing time of the pickup time window. Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing

				customer has placed the order, upon entering the customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Mandatory	Name of the society or street in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Conditional Mandatory	Landmark of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Conditional Mandatory	Name of the state in the customer's pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer's pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer's pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer's pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of

				pickup.
deliverServiceTime	Integer	11	Optional	Specify the time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the customer ID, you can fetch several fields.
deliverAccountName	String	255	Conditional Mandatory	Name of the delivery customer. This field is optional if the Customer Profiling property is enabled.
deliverEmail	String	100	Optional	Email ID delivery of the customer.
deliverPhoneNumber	String	255	Optional	Contact number of the delivery customer.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer’s delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.

deliverState	String	50	Conditional Mandatory	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer's delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer's delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer's delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
clientCode	String	32	Optional	Name of the company associated with the shipper's account. Pass the company name of the shipper's account if you want to create an order request on behalf of one of your shippers.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify 'Y' to enable cancellations or 'N' to prevent them. If no value is provided, the system considers 'Y' by default.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver a partial order (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify 'Y' to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or 'N' to prevent partial deliveries. If no value is provided, the system considers 'Y' by default.
returnAllowedFl	String	50	Optional	Whether the order is returnable or not. This will let your customer initiate a return order request post delivery, if required. Specify 'Y' to allow return, or 'N' to prevent return requests for this order.
returnBranch	String	255	Conditional Mandatory	Name of return branch. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.

returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnPhoneNumber	String	255	Conditional Mandatory	Contact number of the return customer.
returnWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
returnAddressId	String	255	Optional	Identifier assigned to a return customer’s address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer’s return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer’s return address.
returnLandmark	String	512	Optional	Landmark of the customer’s return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer’s return address.
returnCity	String	512	Optional	Name of the city in the customer’s return address.
returnState	String	50	Optional	Name of the state in the customer’s return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer’s return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
returnTimezone	String		Optional	Timezone of the customer’s return address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
returnAWB	String	255	Optional	Air Waybill or AWB number associated with a return order request. If not provided, the system will consider the existing AWB as the return AWB.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as ‘Related Orders’. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z’ , 'A to Z’, '0 to 9’ , ’_’(underscore) and ’-’(hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
				Whether the system should generate a parent order number or not.

generateParentOrderNo	String	50	Optional	Specify 'Y' to auto-generate the parent order number or 'N' to opt-out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Specify the crate details of the order. In case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order request.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
				Unique identifier for the item you are

shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

CREATE POINT-TO-POINT

Sample Request

```
[
    {
    "shipmentRequestNo":"SH12432",
    "awbNumber": "435-16685675",
    "shipmentRequestDispatchDate": "2020-05-19T10:30:00.000Z",
    "shipmentRequestType":"DELIVER",
    "packageWeight":"10",
    "packageVolume":"10",
    "originalOrderValue": "500",
    "orderDiscount": "10",
    "packageValue":"450",
    "insuranceRequiredFl": "Y",
    "insuredValue": "450",
    "signatureRequiredFl": "Y",
    "totalShippingCost":"10",
    "packageLength":"10",
```

```
    "packageBreadth":"10",
    "packageHeight":"10",
    "priority":"Priority 1",
    "paymentType":"COD",
    "numberOfItems":1,
    "packagingRequiredFl": "Y",
    "deliveryType":"Groceries",
    "serviceType":"Express",
    "distributionCenter":"New York Main Branch",
    "pickupServiceTime": "50",
    "pickupStartTimeWindow": "2020-05-19T14:24:00.000Z",
    "pickupEndTimeWindow": "2020-05-19T14:24:00.000Z",
    "pickupEmail":"james.w@ablogs.com",
    "pickupPhoneNumber": "5163063377",
    "pickupWhatsappOptin":"Y",
    "pickupAccountCode": "jim001",
    "pickupAddressId": "Home",
    "pickupAddressType":"Home",
    "pickupAccountName": "James Walker",
    "pickupApartment": "901",
    "pickupStreetName": "2142 3rd Ave",
    "pickupLandmark": "Opp. McDonalds",
    "pickupLocality": "East Harlem",
    "pickupCity": "New York",
    "pickupState": "NY",
    "pickupCountry": "USA",
    "pickupPinCode": "10035",
    "pickupLatitude":40.760838,
    "pickupLongitude":-73.96732299999996,
    "pickupAddressTimezone":"America/New_York",
    "deliverServiceTime":"10",
    "deliverStartTimeWindow": "2020-04-10T10:31:00.000Z",
    "deliverEndTimeWindow": "2020-04-10T10:31:00.000Z",
    "deliverAccountCode": "Matt001",
    "deliverAccountName":"Jane Doe",
    "deliverEmail":"m.richardson@testmail.com",
    "deliverPhoneNumber":"9891234567",
    "deliverWhatsappOptin":"Y",
    "deliverAddressId": "home",
    "deliverAddressType":"Home",
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Towm Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude":41.882702,
    "deliverLongitude":-87.619392,
    "deliverAddressTimezone":"America/Chicago",
    "deliverNotes":"notes for delivery",
    "clientCode":"Ship Logistics",
    "parentOrderNo": "GR432U578577",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
        {
            "crateCd": "CR041",
            "crateAmount": 100.65,
            "crateType": "case",
            "noOfUnits": 2,
            "crateWeight": 10,
            "crateVolume": 11,
            "crateLength": 12,
            "crateBreadth": 13,
            "crateHeight": 14,
```

```
            "shipmentlineitems": [
                {
                    "itemCd": "IT043",
                    "itemName": "Chicken Soup 2X200gm",
                    "itemPrice": 500,
                    "itemQuantity": 1,
                    "itemType": "soup",
                    "itemWeight": 10,
                    "itemVolume": 11,
                    "itemLength": 12,
                    "itemBreadth": 13,
                    "itemHeight": 14
                }
            ]
        }
    ]
    }
]
```


Success Response


```
{
    "status": 200,
    "message": "Shipment Request(s) created successfully",
    "moreResultsExists": false,
    "data": [
        {
            "index": 0,
            "shipmentRequestReferenceId": "035840748a9844c2bf70de49cdd88a3b",
            "shipmentRequestNo": "test4",
            "shipmentRequestType": "DELIVER"
        }
    ],
    "hasError": false
}
```


Failure Response


```
{
    "status": 409,
    "message": "Shipment Request Creation Failed",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "PICKUP",
            "errorList": [
                {
                    "key": "pickupAccountCode",
                    "message": [
                        "Address not serviceable"
                    ]
                },
                {
                    "key": "deliveryType",
                    "message": [
                        "DeliveryType is invalid"
                    ]
                }
            ]
        }
```

```
    ],
    "hasError": true
}
```

Create requests for Point-to-Point orders in the LogiNext system with this API.

- This API creates a request for a Point-to-Point type of order (i.e., An order picked up from the pickup location and delivered to the delivery location, without stops at any intermediate branches) and assigns a unique Reference ID that can be used to identify the order request later.
- Call this API along with the provided parameters to push existing point-to-point order requests from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/BookingApp/mile/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
shipmentRequestNo	String	255	Optional	Unique identifier associated with the order request. You can enter any alphanumeric value as an order request number. If not provided, the system will auto-generate an order request number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order request.
shipmentRequestDispatchDate			Optional	Specify the requested dispatch date of the order. This date indicates when the system should start processing/servicing the order request, using the configured service types or zonal capacities. If not provided, the system defaults to the current date.
shipmentRequestType	String	40	Mandatory	The value in this field must always be ‘DELIVER’.
distributionCenter	String	255	Mandatory	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in Order Prioritizing under Order Configuration in the Settings module. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
serviceType	String	16	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
totalShippingCost	Double	10	Optional	The total cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If the shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+totalShippingCost.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of delivery. If no value is provided, the system considers 'COD' by default.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
deliveryType	String	40	Optional	If your order requires specific skills, you can specify it here. For example, groceries and food items must be separated from toiletries, or cakes cannot be delivered with flowers. The planning engine takes into account the skill set requirement for the order and assigns a delivery associate who possesses the specified Skill Set. Note that you must only select from the Skill Sets that are linked to the Service Types mapped to the order’s shipper. You can pass multiple Skill Sets in a comma-separated format in this API.

pickupStartTimeWindow	Date		Mandatory	The opening time of the pickup time window. Pickup time window is the customer's preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Optional	The closing time of the pickup time window. Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Mandatory	Name of the society or street in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Conditional Mandatory	Landmark of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Conditional Mandatory	Name of the state in the customer's pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.

pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer’s pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer’s pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer’s pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer’s pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
deliverServiceTime	Integer	11	Optional	Specify the time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the customer ID, you can fetch several fields.
deliverAccountName	String	255	Conditional Mandatory	Name of the delivery customer. This field is optional if the Customer Profiling property is enabled.
deliverEmail	String	100	Optional	Email ID of the delivery customer.
deliverPhoneNumber	String	255	Optional	Contact number of the delivery customer.
deliverWhatsappOptin	Boolean	NULL	Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.

deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String	50	Conditional Mandatory	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer's delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer's delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer's delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify 'Y' to enable cancellations or 'N' to prevent them. If no value is provided, the system considers 'Y' by default.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver a partial order (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify 'Y' to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or 'N' to prevent partial deliveries. If no value is provided, the system considers 'Y' by default.
returnAllowedFl	String	50	Optional	Whether the order is returnable or not. This will let your customer initiate a return order request post delivery, if required. Specify 'Y' to allow return, or 'N' to prevent return requests for this order.
returnBranch	String	255	Conditional	Name of return branch. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both

			Mandatory	'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnPhoneNumber	String	255	Conditional Mandatory	Contact number of the return customer.
returnWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
returnAddressId	String	255	Optional	Identifier assigned to a return customer’s address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer’s return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer’s return address.
returnLandmark	String	512	Optional	Landmark of the customer’s return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer’s return address.
returnCity	String	512	Optional	Name of the city in the customer’s return address.
returnState	String	50	Optional	Name of the state in the customer’s return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer’s return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
returnTimezone	String		Optional	Timezone of the customer’s return address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
				Air Waybill or AWB number associated with a return order request. If

returnAWB	String	255	Optional	not provided, the system will consider the existing AWB as the return AWB.
clientCode	String	32	Optional	Name of the company associated with the shipper's account. Pass the company name of the shipper's account if you want to create an order request on behalf of one of your shippers.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as 'Related Orders'. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z' , 'A to Z', '0 to 9' , '_'(underscore) and '-'(hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Specify the crate details of the order. In case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order request.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial

				system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

END-TO-END ACCOUNT: CREATE PICK UP ONLY

Sample Request

```
[
  {
   "shipmentRequestNo":"SH12432",
   "awbNumber": "435-16685675",
   "shipmentRequestDispatchDate": "2020-05-19T10:30:00.000Z",
   "shipmentRequestType":"PICKUP",
   "packageWeight":"10",
   "packageVolume":"10",
   "originalOrderValue": "500",
   "orderDiscount": "10",
   "packageValue":"450",
   "insuranceRequiredFl": "Y",
   "insuredValue": "450",
   "signatureRequiredFl": "Y",
   "totalShippingCost":"10",
   "packageLength":"10",
   "packageBreadth":"10",
   "packageHeight":"10",
   "priority":"Priority 1",
   "paymentType":"COD",
   "numberOfItems":1,
   "packagingRequiredFl": "Y",
   "deliveryType":"Groceries",
   "serviceType":"Express",
   "distributionCenter":"Main Branch",
   "pickupBranch":"Main Branch",
   "pickupServiceTime": "50",
   "pickupStartTimeWindow": "2020-05-19T14:24:00.000Z",
   "pickupEndTimeWindow": "2020-05-19T14:24:00.000Z",
   "pickupEmail":"james.w@ablogs.com",
   "pickupPhoneNumber": "5163063377",
   "pickupWhatsappOptin":"Y",
   "pickupAccountCode": "jim001",
   "pickupAddressId": "Home",
   "pickupAddressType":"Home",
   "pickupAccountName": "James Walker",
   "pickupApartment": "901",
   "pickupStreetName": "2142 3rd Ave",
   "pickupLandmark": "Opp. McDonalds",
   "pickupLocality": "East Harlem",
   "pickupCity": "New York",
   "pickupState": "NY",
   "pickupCountry": "USA",
   "pickupPinCode": "10035",
   "pickupLatitude":40.760838,
   "pickupLongitude":-73.96732299999996,
   "pickupAddressTimezone":"America/New_York",
   "pickupNotes":"notes for pickup",
   "returnAllowedFl":"Y",
   "returnStartTimeWindow":"2022-09-20T14:24:00.000Z",
   "returnEndTimeWindow":"2022-09-20T18:31:00.000Z",
   "returnEmail":"james.w@ablogs.com",
   "returnAccountCode":"jim001",
   "returnAccountName":"James Walker",
   "returnAddressId":"Home",
   "returnApartment":"Cairo",
   "returnStreetName":"Cairo",
   "returnLandmark":"Cairo",
   "returnLocality":"Cairo",
   "returnCity":"Cairo",
   "returnCountry":"EGY",
   "returnPinCode":"10035",
   "returnLatitude":30.047007454581376,
   "returnLongitude":31.235633388494264,
   "returnTimezone":"America/Chicago",
```

```
    "returnAWB":"435-16685675-R",
    "clientCode":"ShipGenie",
    "parentOrderNo": "GR432U578577",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
        {
            "crateCd": "CR041",
            "crateAmount": 100.65,
            "crateType": "case",
            "noOfUnits": 2,
            "crateWeight": 10,
            "crateVolume": 11,
            "crateLength": 12,
            "crateBreadth": 13,
            "crateHeight": 14,
            "shipmentlineitems": [
                {
                    "itemCd": "IT043",
                    "itemName": "Chicken Soup 2X200gm",
                    "itemPrice": 500,
                    "itemQuantity": 1,
                    "itemType": "soup",
                    "itemWeight": 10,
                    "itemVolume": 11,
                    "itemLength": 12,
                    "itemBreadth": 13,
                    "itemHeight": 14
                }
            ]
        }
    ]
    }
]
```


Success Response


```
{
    "status": 200,
    "message": "Shipment Request(s) created successfully",
    "moreResultsExists": false,
    "data": [
        {
            "index": 0,
            "shipmentRequestReferenceId": "2c0dcb93ca494cfc92d5b830c1c8033a",
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "PICKUP"
        }
    ],
    "hasError": false
}
```


Failure Response


```
{
    "status": 409,
    "message": "Shipment Request Creation Failed",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "PICKUP",
```

```
            "errorList": [
                {
                    "key": "pickupAccountCode",
                    "message": [
                        "Address not serviceable"
                    ]
                },
                {
                    "key": "deliveryType",
                    "message": [
                        "DeliveryType is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Create requests for Pickup orders for an End-to-End account in the LogiNext system with this API.

- This API creates a request for a Pickup type of order for an End-to-End account and assigns a unique Reference ID that can be used to identify the order request later.
- Call this API along with the provided parameters to push existing pickup order requests from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/BookingApp/middlemile/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
shipmentRequestNo	String	255	Optional	Unique identifier associated with the order request. You can enter any alphanumeric value as an order request number. If not provided, the system will auto-generate an order request number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order request.
shipmentRequestDispatchDate			Optional	Specify the requested dispatch date of the order. This date indicates when the system should start processing/servicing the order request, using the configured service types or zonal capacities. If not provided, the system defaults to the current date.
shipmentRequestType	String	40	Mandatory	The value in this field must always be ‘PICKUP’.
distributionCenter	String	255	Optional	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
				The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will

packageVolume	Double	10,3	Optional	be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in Order Prioritizing under Order Configuration in the Settings module. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
serviceType	String	16	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
totalShippingCost	Double	10	Optional	The total cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If the shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+totalShippingCost.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Pickup (COP)’ if the delivery associate needs to collect cash at the time of pickup. If no value is provided, the system considers 'COP' by default.

numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
deliveryType	String	40	Optional	If your order requires specific skills for pickup, you can specify it here. For example, groceries and food items must be separated from toiletries, or cakes cannot be delivered with flowers. The planning engine takes into account the skill set requirement for the order and assigns a delivery associate who possesses the specified Skill Set. Note that you must only select from the Skill Sets that are linked to the Service Types mapped to the order’s shipper. You can pass multiple Skill Sets in a comma-separated format in this API.
deliveryLocationType	String	255	Optional	Type of customer address, e.g., Residential, Office, etc.
deliveryMediumUsername	String		Optional	Username of the delivery associate responsible for fulfilling the order.
pickupBranch	String	255	Optional	For pickup type of order requests, this field specifies the branch where the delivery associate will deliver the pickup order. It is recommended to leave this field blank so the system can use the branch linked to the pickup location's zone. However, you can provide this information if the shipper creating the order request is not linked to a Service Area Profile in the LogiNext system.
pickupServiceTime	Integer	11	Optional	Specify the time required to pick up the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the pickup time window.
pickupStartTimeWindow	Date		Optional	The opening time of the pickup time window. Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. It is recommended to leave this field blank so the system can calculate the Order Time Windows based on the Service Type or capacity configuration set up in your account. If this field is provided and no Service Area Profile is linked to the shipper, the system will skip the time window calculations and use the provided time windows at the order level. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Optional	The closing time of the pickup time window. It is recommended to leave this field blank so the system can calculate the Order Time Windows based on the Service Type or capacity configuration in your account. If this field is provided and no Service Area Profile is linked to the shipper, the system will skip the time window calculations and use the provided time windows at the order level. Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.

pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Mandatory	Name of the society or street in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Conditional Mandatory	Landmark of the customer’s pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Conditional Mandatory	Name of the state in the customer’s pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer’s pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer’s pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer’s pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer’s pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer’s pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.

partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver a partial order (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
returnAllowedFl	String	50	Optional	Whether the order is returnable or not. This will let your customer initiate a return order request post delivery, if required. Specify ‘Y’ to allow return, or ‘N’ to prevent return requests for this order.
returnBranch	String	255	Conditional Mandatory	Name of return branch. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnPhoneNumber	String	255	Conditional Mandatory	Contact number of the return customer.
returnWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
returnAddressId	String	255	Optional	Identifier assigned to a return customer’s address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer’s return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer’s return address.
returnLandmark	String	512	Optional	Landmark of the customer’s return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer’s return address.
returnCity	String	512	Optional	Name of the city in the customer’s return address.
returnState	String	50	Optional	Name of the state in the customer’s return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer’s return address. This should be as per the Country Codes available in the LogiNext system.

returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
returnTimezone	String		Optional	Timezone of the customer's return address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
returnAWB	String	255	Optional	Air Waybill or AWB number associated with a return order request. If not provided, the system will consider the existing AWB as the return AWB.
clientCode	String	32	Optional	Name of the company associated with the shipper's account. Pass the company name of the shipper's account if you want to create an order request on behalf of one of your shippers.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as 'Related Orders'. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z' , 'A to Z', '0 to 9' , '_'(underscore) and '-'(hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Specify the crate details of the order. In case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid/semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order request.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be

				in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
				Width of the item. The unit of measurement will be the same as specified

shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

END-TO-END ACCOUNT: CREATE DELIVERY ONLY

Sample Request


```
[
  {
   "shipmentRequestNo":"SH12432",
   "awbNumber": "435-16685675",
   "shipmentRequestDispatchDate": "2020-05-19T10:30:00.000Z",
   "shipmentRequestType":"DELIVER",
   "packageWeight":"10",
   "packageVolume":"10",
   "originalOrderValue": "500",
   "orderDiscount": "10",
   "packageValue":"450",
   "insuranceRequiredFl": "Y",
   "insuredValue": "450",
   "signatureRequiredFl": "Y",
   "totalShippingCost":"10",
   "packageLength":"10",
   "packageBreadth":"10",
   "packageHeight":"10",
   "priority":"Priority 1",
   "paymentType":"COD",
   "numberOfItems":1,
   "packagingRequiredFl": "Y",
   "deliveryType":"Groceries",
   "serviceType":"Express",
   "distributionCenter":"New York Main Branch",
   "deliverBranch":"New York Main Branch",
   "deliverServiceTime":"10",
   "deliverStartTimeWindow": "2020-04-10T10:31:00.000Z",
   "deliverEndTimeWindow": "2020-04-10T10:31:00.000Z",
   "deliverAccountCode": "Matt001",
   "deliverAccountName":"Jane Doe",
   "deliverEmail":"m.richardson@testmail.com",
   "deliverPhoneNumber":"9891234567",
   "deliverWhatsappOptin":"Y",
   "deliverAddressId": "home",
   "deliverAddressType":"Home",
   "deliverApartment": "201",
   "deliverStreetName": "E Randolph St",
   "deliverLandmark": "Opp. Chiptole",
   "deliverLocality": "Down Towm Chicago",
   "deliverCity": "Chicago",
   "deliverState": "IL",
   "deliverCountry": "USA",
   "deliverPinCode": "60602",
   "deliverLatitude":41.882702,
   "deliverLongitude":-87.619392,
   "deliverAddressTimezone":"America/Chicago",
   "deliverNotes":"notes for delivery",
```

```
    "returnAllowedFl":"Y",
    "returnStartTimeWindow":"2022-09-20T14:24:00.000Z",
    "returnEndTimeWindow":"2022-09-20T18:31:00.000Z",
    "returnEmail":"james.w@ablogs.com",
    "returnAccountCode":"jim001",
    "returnAccountName":"James Walker",
    "returnAddressId":"Home",
    "returnApartment":"Cairo",
    "returnStreetName":"Cairo",
    "returnLandmark":"Cairo",
    "returnLocality":"Cairo",
    "returnCity":"Cairo",
    "returnCountry":"EGY",
    "returnPinCode":"10035",
    "returnLatitude":30.047007454581376,
    "returnLongitude":31.235633388494264,
    "returnTimezone":"America/Chicago",
    "returnAWB":"435-16685675-R",
    "clientCode":"Ship Logistics",
    "parentOrderNo": "GR432U578577",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
        {
            "crateCd": "CR041",
            "crateAmount": 100.65,
            "crateType": "case",
            "noOfUnits": 2,
            "crateWeight": 10,
            "crateVolume": 11,
            "crateLength": 12,
            "crateBreadth": 13,
            "crateHeight": 14,
            "shipmentlineitems": [
                {
                    "itemCd": "IT043",
                    "itemName": "Chicken Soup 2X200gm",
                    "itemPrice": 500,
                    "itemQuantity": 1,
                    "itemType": "soup",
                    "itemWeight": 10,
                    "itemVolume": 11,
                    "itemLength": 12,
                    "itemBreadth": 13,
                    "itemHeight": 14
                }
            ]
        }
    ]
    }
]
```


Success Response


```
{
    "status": 200,
    "message": "Shipment Request(s) created successfully",
    "moreResultsExists": false,
    "data": [
        {
            "index": 0,
            "shipmentRequestReferenceId": "2c0dcb93ca494cfc92d5b830c1c8033a",
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "PICKUP"
        }
```

```
    ],
    "hasError": false
}
```

Failure Response

```
{
    "status": 409,
    "message": "Shipment Request Creation Failed",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "DELIVER",
            "errorList": [
                {
                    "key": "deliverAccountCode",
                    "message": [
                        "Address not serviceable"
                    ]
                },
                {
                    "key": "deliveryType",
                    "message": [
                        "DeliveryType is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Create requests for Delivery orders for an End-to-End account in the LogiNext system with this API.

- This API creates a request for a Delivery type of order for an End-to-End account and assigns a unique Reference ID that can be used to identify the order request later.
- Call this API along with the provided parameters to push existing delivery order requests from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/BookingApp/middlemile/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
shipmentRequestNo	String	255	Optional	Unique identifier associated with the order request. You can enter any alphanumeric value as an order request number. If not provided, the system will auto-generate an order request number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order request.
shipmentRequestDispatchDate			Optional	Specify the requested dispatch date of the order. This date indicates when the system should start processing/servicing the order request, using the configured service types or zonal capacities. If not provided, the system defaults to the current date.

shipmentRequestType	String	40	Mandatory	The value in this field must always be ‘DELIVER’.
distributionCenter	String	255	Optional	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in Order Prioritizing under Order Configuration in the Settings module. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
serviceType	String	16	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
				Whether you want the signature/adult signature for the order or

signatureRequiredFl	String	16	Optional	not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
totalShippingCost	Double	10	Optional	The total cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If the shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+totalShippingCost.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of delivery. If no value is provided, the system considers 'COD' by default.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
deliveryType	String	40	Optional	If your order requires specific skills for delivery, you can specify it here. For example, groceries and food items must be separated from toiletries, or cakes cannot be delivered with flowers. The planning engine takes into account the skill set requirement for the order and assigns a delivery associate who possesses the specified Skill Set. Note that you must only select from the Skill Sets that are linked to the Service Types mapped to the order’s shipper. You can pass multiple Skill Sets in a comma-separated format in this API.
deliverBranch	String	255	Optional	For the delivery type of order requests, this field specifies the branch where the delivery associate will pick up the order. Note that you must specify the Operation Branch using the Add Branch API or the Add Branch form in the Branch Configuration module. In case of any issues while creating a branch, contact your Account Manager.
deliverServiceTime	Integer	11	Optional	Specify the time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the customer ID, you can fetch several fields.
			Conditional	Name of the delivery customer. This field is optional if the Customer

deliverAccountName	String	255	Mandatory	Profiling property is enabled.
deliverEmail	String	100	Optional	Email ID of the customer.
deliverPhoneNumber	String	255	Optional	Contact number of the customer. This field is optional if the Customer Profiling property is enabled.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String	50	Conditional Mandatory	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer's delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer's delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer's delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.

cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver a partial order (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
returnAllowedFl	String	50	Optional	Whether the order is returnable or not. This will let your customer initiate a return order request post delivery, if required. Specify ‘Y’ to allow return, or ‘N’ to prevent return requests for this order.
returnBranch	String	255	Conditional Mandatory	Name of return branch. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
clientCode	String	32	Optional	Name of the company associated with the shipper’s account. Pass the company name of the shipper’s account if you want to create an order request on behalf of one of your shippers.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as ‘Related Orders’. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z’ , 'A to Z’, '0 to 9’ , ’_’(underscore) and ’-’(hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Specify the crate details of the order. In case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order

				request.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
				Length of the item. The unit of measurement will be the same as specified in System Preferences in the Settings

shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

END-TO-END ACCOUNT: CREATE POINT-TO-POINT

Sample Request


```
[
  {
   "shipmentRequestNo":"SH12432",
   "awbNumber": "435-16685675",
   "shipmentRequestDispatchDate": "2020-05-19T10:30:00.000Z",
   "shipmentRequestType":"DELIVER",
   "packageWeight":"10",
   "packageVolume":"10",
   "originalOrderValue": "500",
   "orderDiscount": "10",
   "packageValue":"450",
   "insuranceRequiredFl": "Y",
   "insuredValue": "450",
   "signatureRequiredFl": "Y",
   "totalShippingCost":"10",
   "packageLength":"10",
   "packageBreadth":"10",
   "packageHeight":"10",
   "priority":"Priority 1",
   "paymentType":"COD",
   "numberOfItems":1,
   "packagingRequiredFl": "Y",
   "deliveryType":"Groceries",
   "serviceType":"Express",
   "distributionCenter":"New York Main Branch",
   "pickupServiceTime": "50",
   "pickupStartTimeWindow": "2020-05-19T14:24:00.000Z",
   "pickupEndTimeWindow": "2020-05-19T14:24:00.000Z",
   "pickupEmail":"james.w@ablogs.com",
   "pickupPhoneNumber": "5163063377",
   "pickupWhatsappOptin":"Y",
   "pickupAccountCode": "jim001",
   "pickupAddressId": "Home",
   "pickupAddressType":"Home",
   "pickupAccountName": "James Walker",
   "pickupApartment": "901",
   "pickupStreetName": "2142 3rd Ave",
   "pickupLandmark": "Opp. McDonalds",
   "pickupLocality": "East Harlem",
   "pickupCity": "New York",
   "pickupState": "NY",
   "pickupCountry": "USA",
```

```
    "pickupPinCode": "10035",
    "pickupLatitude":40.760838,
    "pickupLongitude":-73.96732299999996,
    "pickupAddressTimezone":"America/New_York",
    "pickupNotes":"notes for pickup",
    "deliverServiceTime":"10",
    "deliverStartTimeWindow": "2020-04-10T10:31:00.000Z",
    "deliverEndTimeWindow": "2020-04-10T10:31:00.000Z",
    "deliverAccountCode": "Matt001",
    "deliverAccountName":"Jane Doe",
    "deliverEmail":"m.richardson@testmail.com",
    "deliverPhoneNumber":"9891234567",
    "deliverWhatsappOptin":"Y",
    "deliverAddressId": "home",
    "deliverAddressType":"Home",
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Towm Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude":41.882702,
    "deliverLongitude":-87.619392,
    "deliverAddressTimezone":"America/Chicago",
    "deliverNotes":"notes for delivery",
    "returnAllowedFl":"Y",
    "returnStartTimeWindow":"2022-09-20T14:24:00.000Z",
    "returnEndTimeWindow":"2022-09-20T18:31:00.000Z",
    "returnEmail":"james.w@ablogs.com",
    "returnAccountCode":"jim001",
    "returnAccountName":"James Walker",
    "returnAddressId":"Home",
    "returnApartment":"Cairo",
    "returnStreetName":"Cairo",
    "returnLandmark":"Cairo",
    "returnLocality":"Cairo",
    "returnCity":"Cairo",
    "returnCountry":"EGY",
    "returnPinCode":"10035",
    "returnLatitude":30.047007454581376,
    "returnLongitude":31.235633388494264,
    "returnTimezone":"America/Chicago",
    "returnAWB":"435-16685675-R",
    "clientCode":"Ship Logistics",
    "parentOrderNo": "GR432U578569",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
        {
            "crateCd": "CR041",
            "crateAmount": 100.65,
            "crateType": "case",
            "noOfUnits": 2,
            "crateWeight": 10,
            "crateVolume": 11,
            "crateLength": 12,
            "crateBreadth": 13,
            "crateHeight": 14,
            "shipmentlineitems": [
                {
                    "itemCd": "IT043",
                    "itemName": "Chicken Soup 2X200gm",
                    "itemPrice": 500,
                    "itemQuantity": 1,
                    "itemType": "soup",
```

```
                    "itemWeight": 10,
                    "itemVolume": 11,
                    "itemLength": 12,
                    "itemBreadth": 13,
                    "itemHeight": 14
                }
            ]
        }
    ]
    }
]
```


Success Response


```
{
    "status": 200,
    "message": "Shipment Request(s) created successfully",
    "moreResultsExists": false,
    "data": [
        {
            "index": 0,
            "shipmentRequestReferenceId": "2c0dcb93ca494cfc92d5b830c1c8033a",
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "PICKUP"
        }
    ],
    "hasError": false
}
```


Failure Response


```
{
    "status": 409,
    "message": "Shipment Request Creation Failed",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "DELIVER",
            "errorList": [
                {
                    "key": "deliverAccountCode",
                    "message": [
                        "Address not serviceable"
                    ]
                },
                {
                    "key": "deliveryType",
                    "message": [
                        "DeliveryType is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```


Create requests for Point-to-Point orders for an End-to-End account in the LogiNext system with this API.

- This API creates a request for a Point-to-Point type of order (i.e., An order picked up from the pickup location and delivered to the delivery location, without stops at any intermediate branches) for an End-to-End account and assigns a unique Reference ID that can be used to identify the order request later.
- Call this API along with the provided parameters to push existing point-to-point order requests from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/BookingApp/middlemile/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
shipmentRequestNo	String	255	Optional	Unique identifier associated with the order request. You can enter any alphanumeric value as an order request number. If not provided, the system will auto-generate an order request number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order request.
shipmentRequestDispatchDate			Optional	Specify the requested dispatch date of the order. This date indicates when the system should start processing/servicing the order request, using the configured service types or zonal capacities. If not provided, the system defaults to the current date.
shipmentRequestType	String	40	Mandatory	The value in this field must always be 'DELIVER'.
distributionCenter	String	255	Mandatory	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
				You can assign a priority to the order as per the values configured in

priority	String	16	Optional	Order Prioritizing under Order Configuration in the Settings module. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
serviceType	String	16	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
totalShippingCost	Double	10	Optional	The total cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If the shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+totalShippingCost.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of delivery. If no value is provided, the system considers 'COD' by default.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
deliveryType	String	40	Optional	If your order requires specific skills, you can specify it here. For example, groceries and food items must be separated from toiletries, or cakes cannot be delivered with flowers. The planning engine takes into account the skill set requirement for the order and assigns a delivery associate who possesses the specified Skill Set. Note that you must only select from the Skill Sets that are linked to the Service Types mapped to the order’s shipper. You can pass multiple Skill Sets in a comma-separated format in this API.
pickupStartTimeWindow	Date		Mandatory	The opening time of the pickup time window. Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2017-07-15T11:30:00.000Z.

pickupEndTimeWindow	Date		Mandatory	The closing time of the pickup time window. Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Mandatory	Name of the society or street in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Conditional Mandatory	Landmark of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Conditional Mandatory	Name of the state in the customer's pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer's pickup address.

pickupLongitude	Double		Optional	Longitude coordinates of the customer’s pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer’s pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
deliverServiceTime	Integer	11	Optional	Specify the time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the customer ID, you can fetch several fields.
deliverAccountName	String	255	Conditional Mandatory	Name of the delivery customer. This field is optional if the Customer Profiling property is enabled.
deliverEmail	String	100	Optional	Email ID of the delivery customer.
deliverPhoneNumber	String	255	Optional	Contact number of the delivery customer.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional	Name of the society or street in the customer’s delivery address.

			Mandatory	This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String	50	Conditional Mandatory	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer's delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer's delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer's delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify 'Y' to enable cancellations or 'N' to prevent them. If no value is provided, the system considers 'Y' by default.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver a partial order (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify 'Y' to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or 'N' to prevent partial deliveries. If no value is provided, the system considers 'Y' by default.
returnAllowedFl	String	50	Optional	Whether the order is returnable or not. This will let your customer initiate a return order request post delivery, if required. Specify 'Y' to allow return, or 'N' to prevent return requests for this order.
returnBranch	String	255	Conditional Mandatory	Name of return branch. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
				The opening time of the return time window in YYYY-MM-

returnStartTimeWindow	Date		Optional	DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnPhoneNumber	String	255	Conditional Mandatory	Contact number of the return customer.
returnWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
returnAddressId	String	255	Optional	Identifier assigned to a return customer's address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer's return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer's return address.
returnLandmark	String	512	Optional	Landmark of the customer's return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer's return address.
returnCity	String	512	Optional	Name of the city in the customer's return address.
returnState	String	50	Optional	Name of the state in the customer's return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer's return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
returnTimezone	String		Optional	Timezone of the customer's return address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
returnAWB	String	255	Optional	Air Waybill or AWB number associated with a return order request. If not provided, the system will consider the existing AWB as the return AWB.
clientCode	String	32	Optional	Name of the company associated with the shipper's account. Pass the company name of the shipper's account if you want to create an order request on behalf of one of your shippers.

parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as ‘Related Orders’. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z’ , 'A to Z’, '0 to 9’ , ’_’(underscore) and ’-’(hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Specify the crate details of the order. In case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid/semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order request.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be

				in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

END-TO-END ACCOUNT: CREATE MULTI-LEG

Sample Request

```
[
  {
   "shipmentRequestNo":"SH12432",
   "awbNumber": "435-16685675",
```

```
    "shipmentRequestDispatchDate": "2020-05-19T10:30:00.000Z",
    "shipmentRequestType":"ALLMILE",
    "packageWeight":"10",
    "packageVolume":"10",
    "originalOrderValue": "500",
    "orderDiscount": "10",
    "packageValue":"450",
    "insuranceRequiredFl": "Y",
    "insuredValue": "450",
    "signatureRequiredFl": "Y",
    "totalShippingCost":"10",
    "packageLength":"10",
    "packageBreadth":"10",
    "packageHeight":"10",
    "priority":"Priority 1",
    "paymentType":"COD",
    "numberOfItems":1,
    "packagingRequiredFl": "Y",
    "deliveryType":"Groceries",
    "serviceType":"Express",
    "distributionCenter":"New York Main Branch",
    "pickupBranch":"New York Main Branch",
    "pickupServiceTime": "50",
    "pickupStartTimeWindow": "2020-05-19T14:24:00.000Z",
    "pickupEndTimeWindow": "2020-05-19T14:24:00.000Z",
    "pickupEmail":"james.w@ablogs.com",
    "pickupPhoneNumber": "5163063377",
    "pickupWhatsappOptin":"Y",
    "pickupAccountCode": "jim001",
    "pickupAddressId": "Home",
    "pickupAddressType":"Home",
    "pickupAccountName": "James Walker",
    "pickupApartment": "901",
    "pickupStreetName": "2142 3rd Ave",
    "pickupLandmark": "Opp. McDonalds",
    "pickupLocality": "East Harlem",
    "pickupCity": "New York",
    "pickupState": "NY",
    "pickupCountry": "USA",
    "pickupPinCode": "10035",
    "pickupLatitude":40.760838,
    "pickupLongitude":-73.96732299999996,
    "pickupAddressTimezone":"America/New_York",
    "deliverBranch":"New York Main Branch",
    "deliverServiceTime":"10",
    "deliverStartTimeWindow": "2020-04-10T10:31:00.000Z",
    "deliverEndTimeWindow": "2020-04-10T10:31:00.000Z",
    "deliverAccountCode": "Matt001",
    "deliverAccountName":"Jane Doe",
    "deliverEmail":"m.richardson@testmail.com",
    "deliverPhoneNumber":"9891234567",
    "deliverWhatsappOptin":"Y",
    "deliverAddressId": "home",
    "deliverAddressType":"Home",
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Towm Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude":41.882702,
    "deliverLongitude":-87.619392,
    "deliverAddressTimezone":"America/Chicago",
    "deliverNotes":"notes for delivery",
```

```
    "returnAllowedFl":"Y",
    "returnStartTimeWindow":"2022-09-20T14:24:00.000Z",
    "returnEndTimeWindow":"2022-09-20T18:31:00.000Z",
    "returnEmail":"james.w@ablogs.com",
    "returnAccountCode":"jim001",
    "returnAccountName":"James Walker",
    "returnAddressId":"Home",
    "returnApartment":"Cairo",
    "returnStreetName":"Cairo",
    "returnLandmark":"Cairo",
    "returnLocality":"Cairo",
    "returnCity":"Cairo",
    "returnCountry":"EGY",
    "returnPinCode":"10035",
    "returnLatitude":30.047007454581376,
    "returnLongitude":31.235633388494264,
    "returnTimezone":"America/Chicago",
    "returnAWB":"435-16685675-R",
    "clientCode":"Ship Logistics",
    "parentOrderNo": "GR432U578569",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
        {
            "crateCd": "CR041",
            "crateAmount": 100.65,
            "crateType": "case",
            "noOfUnits": 2,
            "crateWeight": 10,
            "crateVolume": 11,
            "crateLength": 12,
            "crateBreadth": 13,
            "crateHeight": 14,
            "shipmentlineitems": [
                {
                    "itemCd": "IT043",
                    "itemName": "Chicken Soup 2X200gm",
                    "itemPrice": 500,
                    "itemQuantity": 1,
                    "itemType": "soup",
                    "itemWeight": 10,
                    "itemVolume": 11,
                    "itemLength": 12,
                    "itemBreadth": 13,
                    "itemHeight": 14
                }
            ]
        }
    ]
    }
]
```


Success Response


```
{
    "status": 200,
    "message": "Shipment Request(s) created successfully",
    "moreResultsExists": false,
    "data": [
        {
            "index": 0,
            "shipmentRequestReferenceId": "2c0dcb93ca494cfc92d5b830c1c8033a",
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "BOTH"
        }
```

```
    ],
    "hasError": false
}
```

Failure Response

```
{
    "status": 409,
    "message": "Shipment Request Creation Failed",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "shipmentRequestNo": "SH12432",
            "shipmentRequestType": "DELIVER",
            "errorList": [
                {
                    "key": "deliverAccountCode",
                    "message": [
                        "Address not serviceable"
                    ]
                },
                {
                    "key": "deliveryType",
                    "message": [
                        "DeliveryType is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Create requests for an All Mile (i.e., multi-leg) type of order for an End-to-End account in the LogiNext system with this API.

- This API creates a request for a Multi-Leg type of order for an End-to-End account and assigns a unique Reference ID that can be used to identify the order request later.
- Call this API along with the provided parameters to push existing order requests from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/BookingApp/middlemile/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
shipmentRequestNo	String	255	Optional	Unique identifier associated with the order request. You can enter any alphanumeric value as an order request number. If not provided, the system will auto-generate an order request number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order request.
shipmentRequestDispatchDate			Optional	Specify the requested dispatch date of the order. This date indicates when the system should start processing/servicing the order request, using the configured service types or zonal capacities. If not provided, the system defaults to the current date.

shipmentRequestType	String	40	Mandatory	The value in this field must always be ‘PICKUP’.
distributionCenter	String	255	Optional	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in Order Prioritizing under Order Configuration in the Settings module. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
serviceType	String	16	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
				Whether you want the signature/adult signature for the order or

signatureRequiredFl	String	16	Optional	not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
totalShippingCost	Double	10	Optional	The total cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If the shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+totalShippingCost.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Pickup (COP) or Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of delivery. If no value is provided, the system considers 'COD' by default.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
deliveryType	String	40	Optional	If your order requires specific skills, you can specify it here. For example, groceries and food items must be separated from toiletries, or cakes cannot be delivered with flowers. The planning engine takes into account the skill set requirement for the order and assigns a delivery associate who possesses the specified Skill Set. Note that you must only select from the Skill Sets that are linked to the Service Types mapped to the order’s shipper. You can pass multiple Skill Sets in a comma-separated format in this API.
deliverBranch	String	255	Optional	For the pickup and delivery type of order requests, this field specifies the branch where the delivery associate will pick up the order. Note that you must specify the Operation Branch using the Add Branch API or the Add Branch form in the Branch Configuration module. In case of any issues while creating a branch, contact your Account Manager.
pickupStartTimeWindow	Date		Mandatory	The opening time of the pickup time window. Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Optional	The closing time of the pickup time window. Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.

pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Mandatory	Name of the society or street in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Conditional Mandatory	Landmark of the customer’s pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Conditional Mandatory	Name of the state in the customer’s pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer’s pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer’s pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer’s pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer’s pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer’s pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
deliverServiceTime	Integer	11	Optional	Specify the time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer’s preferred time slot for the delivery associate to reach the

				customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the customer ID, you can fetch several fields.
deliverAccountName	String	255	Conditional Mandatory	Name of the delivery customer. This field is optional if the Customer Profiling property is enabled.
deliverEmail	String	100	Optional	Email ID delivery of the customer.
deliverPhoneNumber	String	255	Optional	Contact number of the delivery customer.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String	50	Conditional Mandatory	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
			Conditional	Pin code of the customer's delivery location. This field is optional if

deliverPinCode	String	12	Mandatory	the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer’s delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer’s delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer’s delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver a partial order (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
returnAllowedFl	String	50	Optional	Whether the order is returnable or not. This will let your customer initiate a return order request post delivery, if required. Specify ‘Y’ to allow return, or ‘N’ to prevent return requests for this order.
returnBranch	String	255	Conditional Mandatory	Name of return branch. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnPhoneNumber	String	255	Conditional Mandatory	Contact number of the return customer.
returnWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.

returnAddressId	String	255	Optional	Identifier assigned to a return customer's address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer's return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer's return address.
returnLandmark	String	512	Optional	Landmark of the customer's return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer's return address.
returnCity	String	512	Optional	Name of the city in the customer's return address.
returnState	String	50	Optional	Name of the state in the customer's return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer's return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
returnTimezone	String		Optional	Timezone of the customer's return address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
returnAWB	String	255	Optional	Air Waybill or AWB number associated with a return order request. If not provided, the system will consider the existing AWB as the return AWB.
pickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for pickup verification.
deliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for delivery verification.
returnPickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for return pickup verification.
returnDeliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for return delivery verification.
clientCode	String	32	Optional	Name of the company associated with the shipper's account. Pass the company name of the shipper's account if you want to create an order request on behalf of one of your shippers.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as 'Related Orders'. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z' , 'A to Z', '0 to 9' , '_'(underscore) and '-'(hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt

out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Specify the crate details of the order. In case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order request.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.

shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

GET SHIPPING QUOTES

Sample Request

```
{
    "shipperReferenceId": "6a34c7274df0489f97c0f891514b488b",
    "clientCode": "Ship Logistics",
    "shipmentRequestDispatchDate": "2020-05-19T10:30:00.000Z",
    "packageWeight": "10",
    "packageVolume": "10",
    "packagingRequiredFl": "Y",
    "originalOrderValue": "500",
    "orderDiscount": "10",
    "packageValue":"450",
    "insuranceRequiredFl": "Y",
    "insuredValue": "450",
    "signatureRequiredFl": "Y",
    "totalShippingCost":"10",
    "deliveryType": "Hazmart, Fragile",
    "pickupApartment": "901",
    "pickupStreetName": "2142 3rd Ave",
    "pickupLandmark": "Opp. McDonalds",
```

```
    "pickupLocality": "East Harlem",
    "pickupCity": "New York",
    "pickupState": "NY",
    "pickupCountry": "USA",
    "pickupPinCode": "10035",
    "pickupLatitude": 40.760838,
    "pickupLongitude": -73.96732299999996,
    "pickupAddressTimezone": "America/New_York",
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Towm Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude": 41.882702,
    "deliverLongitude": -87.619392,
    "deliverAddressTimezone": "America/Chicago",
    "shipmentCrateMappings": [
    {
      "crateCd": "CR041",
      "crateAmount": 100.65,
      "crateType": "case",
      "noOfUnits": 2,
      "crateWeight": 10,
      "crateVolume": 11,
      "crateLength": 12,
      "crateBreadth": 13,
      "crateHeight": 14,
      "shipmentlineitems": [
        {
          "itemCd": "IT043",
          "itemName": "Chicken Soup 2X200gm",
          "itemPrice": 500,
          "itemQuantity": 1,
          "itemType": "soup",
          "itemWeight": 10,
          "itemVolume": 11,
          "itemLength": 12,
          "itemBreadth": 13,
          "itemHeight": 14
        }
      ]
    }
  ]
}
```


Success Response


```
{
    "status": 200,
    "message": "Success",
    "moreResultsExists": false,
    "data":[
        {
            "serviceType": "Express",
            "pickupStartTimeWindow": 1646483400000,
            "pickupEndTimeWindow": 1646494200000,
            "deliverStartTimeWindow": 1646494200000,
            "deliverEndTimeWindow": 1646541000000,
            "requestCutOffTime" : "22:30",
            "estimatedCost": {
            "basicShippingCost_total": 0,
```

```
            "handlingFees_total": 100,
            "handlingFees": [
                {
                    "skillType": "Fragile Delivery",
                    "skillTypeCost": 100
                }
            ],
            "locationFees_total": 0,
            "miscellaneousFees_total": 100,
            "miscellaneousFees": [
                {
                    "miscellaneousFeesName": "Heavy Load",
                    "miscellaneousFeesCost": 100
                }
            ],
            "fuelSurcharge": 6,
            "zoneSurcharge": 0.6,
            "discount": 0,
            "surcharge_total": 6.6,
            "cancellationFees": 0,
            "reAttemptFees": 0,
            "CODFees": 0,
            "insurance": 100,
            "shippingCost_total": 206.6,
        },
        {
            "service Type": "Express Plus",
            "pickupStartTimeWindow": 1646483400000,
            "pickupEndTimeWindow": 1646494200000,
            "deliverStartTimeWindow": 1646494200000,
            "deliverEndTimeWindow": 1646541000000,
            "requestCutOffTime" : "20:30",
            "estimatedCost": {
            "basicShippingCost_total": 0,
            "handlingFees_total": 120,
            "handlingFees": [
                {
                "skillType": "Fragile Delivery",
                "skillTypeCost": 120
                }
            ],
            "locationFees_total": 0,
            "miscellaneousFees_total": 150,
            "miscellaneousFees": [
                {
                "miscellaneousFeesName": "Heavy Load",
                "miscellaneousFeesCost": 150
                }
            ],
            "fuelSurcharge": 6,
            "zoneSurcharge": 0.3,
            "discount": 0,
            "surcharge_total": 6.3,
            "cancellationFees": 0,
            "reAttemptFees": 0,
            "CODFees": 0,
            "insurance": 100,
            "shippingCost_total": 276.3,
        },
        {
            "service Type": "Express Saver",
            "pickupStartTimeWindow": 1646483400000,
            "pickupEndTimeWindow": 1646494200000,
            "deliverStartTimeWindow": 1646494200000,
            "deliverEndTimeWindow": 1646541000000,
            "requestCutOffTime" : "20:00",
```

```
            "estimatedCost": {
            "basicShippingCost_total": 0,
            "handlingFees_total": 150,
            "handlingFees": [
                {
                "skillType": "Fragile Delivery",
                "skillTypeCost": 150
                }
            ],
            "locationFees_total": 0,
            "miscellaneousFees_total": 125,
            "miscellaneousFees": [
                {
                "miscellaneousFeesName": "Heavy Load",
                "miscellaneousFeesCost": 125
                }
            ],
            "fuelSurcharge": 9,
            "zoneSurcharge": 0.4,
            "discount": 0,
            "surcharge_total": 9.4,
            "cancellationFees": 0,
            "reAttemptFees": 0,
            "CODFees": 0,
            "insurance": 150,
            "shippingCost_total": 284.4,
        }
    ],
    "hasError": false
}
```


Failure Response


```
{
    "status": 409,
    "message": "Request Error",
    "moreResultsExists": false,
    "data": [
        {
            "index": 0,
            "errorList": [
                {
                    "key": "shipmentRequestDispatchDate",
                    "message": [
                        "The order request dispatch cannot be less than the current date time."
                    ],
                    "errorCode": 132200
                }
            ]
        }
    ],
    "hasError": true
}
```


Retrieve shipping quotes and delivery time details of required order requests using this API.

- This API retrieves the shipping quotes and delivery time details for the required order request.
- Include the Reference IDs along with the required parameters in the request body.

API TYPE

- Tier 2 API.

REQUEST

POST `https://products.loginextsolutions.com/BookingApp/middlemile/v1/getQuotes`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceId	String	32	Conditional mandatory	Unique reference identifier associated with the order request whose shipping quotes and delivery time details you want to retrieve. This ID is generated by the LogiNext system while creating an order request to identify them for future reference.
clientCode	String	50	Conditional mandatory	Name of the company associated with the shipper's account. Pass the company name of the shipper's account if you want to create an order request on behalf of one of your shippers.
pickupApartment	String	512	Optional	Name of the apartment building/complex in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Optional	Name of the society or street in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Optional	Landmark of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLocality	String	512	Optional	Name of the locality or area in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Optional	Name of the city in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String		Optional	Name of the state in the customer's pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String		Optional	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String		Conditional Mandatory	Pin code of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer's pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer's pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer's pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverApartment	String		Optional	Name of the apartment building/complex in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName				Name of the society or street in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String		Optional	Landmark of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.

deliverLocality	String		Optional	Name of the locality or area in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String		Optional	Name of the city in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String		Optional	Name of the state in the customer’s delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String		Optional	Name of the country in the customer’s delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
deliverPinCode	String		Optional	Pin code of the customer’s delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer’s delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer’s delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer’s delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliveryType	String	40	Optional	If your order requires specific skills, you can specify it here. For example, groceries and food items must be separated from toiletries, or cakes cannot be delivered with flowers. The planning engine takes into account the skill set requirement for the order and assigns a delivery associate who possesses the specified Skill Set. Note that you must only select from the Skill Sets that are linked to the Service Types mapped to the order’s shipper. You can pass multiple Skill Sets in a comma-separated format in this API.
shipmentRequestDispatchDate	Date		Optional	Specify the requested dispatch date of the order. This date indicates when the system should start processing/servicing the order request, using the configured service types or zonal capacities. If not provided, the system defaults to the current date.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the

				order.
totalShippingCost	Double	10	Optional	The total cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If the shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+totalShippingCost.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify 'Y' if packaging service is required for the order, or 'N' if not.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Specify the crate details of the order. In case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order request.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
				Length of the crate. The unit of

shipmentCrateMappings.crateLength	Double	10,3	Optional	measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item. The unit of measurement will be the same as specified in System Preferences in the Settings module. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

Order

Create new orders in the LogiNext system with these Order APIs.

- These APIs create an Order and assign a unique Reference ID that can be used to identify the order later.
- Call this API along with the provided parameters to push existing orders from your current system to LogiNext.
- You can use the Customer Profiling property while creating orders to maintain your customers' profiles and fetch their details while creating orders for these customers.
- If the Customer Profiling property is enabled, enter the Customer ID of an existing customer in the 'accountCode' field to automatically retrieve details such as name, email ID, contact number, and more when creating an order. Note that entering the existing Customer ID will override any other customer information you provide.
- If the selected customer has multiple addresses, specify the Address ID in the 'AddressId' field to fetch the associated address details while creating an order.

CREATE PICK UP ONLY

Sample Request

```
[
 {
   "orderNo": "GR432U5",
   "awbNumber": "435-16685675",
   "shipmentOrderTypeCd": "PICKUP",
   "orderState": "FORWARD",
   "autoAllocateFl": "N",
   "autoAllocateProfileName":"ETAProfile",
   "shipmentOrderDt": "2016-07-15T10:30:00.000Z",
   "pickupStartTimeWindow": "2016-07-16T10:31:00.000Z",
   "pickupEndTimeWindow": "2016-07-18T10:31:00.000Z",
   "pickupServiceTime": "20",
   "deliveryType": "Groceries, Reefer",
   "deliveryLocationType":"HOME",
   "pickupBranch": "East Manhatten",
   "distributionCenter": "Brooklyn",
   "partialDeliveryAllowedFl": "Y",
   "cancellationAllowedFl": "N",
   "returnAllowedFl": "Y",
   "deliveryMediumUsername":"johnc",
   "returnBranch": "Chicago North",
   "numberOfItems": 2,
   "packagingRequiredFl": "Y",
   "packageWeight":"10",
   "packageVolume": "4500",
   "packageLength": 2.5,
   "packageBreadth": 2.5,
   "packageHeight": 2.5,
   "priority": "PRIORITY1",
   "serviceType":"Premium",
   "paymentType": "COD",
   "originalOrderValue": "500",
   "orderDiscount": "10",
   "packageValue":"450",
   "insuranceRequiredFl": "Y",
   "insuredValue": "450",
   "signatureRequiredFl": "Y",
   "shippingCost": "50",
   "pickupNotes": "Please ring my Door Bell",
   "pickupAccountCode": "jim001",
   "pickupAddressId": "home",
   "pickupAccountName": "James Walker",
   "pickupEmail": "james.w@ablogs.com",
   "pickupPhoneNumber": "5163063377",
   "pickupWhatsappOptin":"Y",
```

```
    "pickupApartment": "901",
    "pickupStreetName": "2142 3rd Ave",
    "pickupLandmark": "Opp. McDonalds",
    "pickupLocality": "East Harlem",
    "pickupCity": "New York",
    "pickupState": "NY",
    "pickupCountry": "USA",
    "pickupPinCode": "10035",
    "pickupLatitude":40.760838,
    "pickupLongitude":-73.96732299999996,
    "pickupAddressTimezone":"America/New_York",
    "clientCode": "Salestap",
    "optimizePackingfl":"Y",
    "sendVerificationCd": "Y",
    "pickupVerificationCd": "1112",
    "deliveryVerificationCd": "3333",
    "returnPickupVerificationCd": "3000",
    "returnDeliveryVerificationCd": "1233",
    "parentOrderNo": "GR432U578577",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
      {
        "crateCd": "CR5002",
        "crateTemperatureCategory": "Ambient",
        "crateMinTemperature": 10,
        "crateMaxTemperature": 20,
        "crateAmount":1000,
        "crateType":"Case",
        "noOfUnits":3,
        "crateWeight":10,
        "crateVolume":11,
        "crateLength":12,
        "crateBreadth":13,
        "crateHeight":14,
        "crateTemperatureCategory": "Ambient",
        "crateMinTemperature": 10,
        "crateMaxTemperature": 20,
        "shipmentlineitems": [
          {
            "itemCd": "IT038",
            "itemName": "Milk tetra pack small",
            "itemPrice": 100,
            "itemQuantity": 1,
            "itemType": "dairy",
            "itemWeight": 15,
            "itemVolume":16,
            "itemLength":17,
            "itemBreadth":18,
            "itemHeight":19,
            "temperatureCategory":"Ambient",
            "minTemperature":10,
            "maxTemperature":20

          },
          {
            "itemCd": "IT043",
            "itemName": "Chicken Soup 2X200gm",
            "itemPrice": 500,
            "itemQuantity": 1,
            "itemType": "soup",
            "itemWeight": 10,
            "itemVolume":16,
            "itemLength":17,
            "itemBreadth":18,
            "itemHeight":19,
            "temperatureCategory":"Ambient",
```

```
            "minTemperature":10,
            "maxTemperature":20
          },
          {
            "itemCd": "IT030",
            "itemName": "WholeBeanCoffee 6x1kg",
            "itemPrice": 400,
            "itemQuantity": 1,
            "itemType": "coffee",
            "itemWeight": 10,
            "itemVolume":16,
            "itemLength":17,
            "itemBreadth":18,
            "itemHeight":19,
            "temperatureCategory":"Ambient",
            "minTemperature":10,
            "maxTemperature":20
          }
        ]

      },
      {
        "crateCd": "CR002",
        "crateAmount":200,
        "crateType":"Case",
        "noOfUnits":1,
        "shipmentlineitems": [
          {
            "itemCd": "IT043",
            "itemName": "Chicken Soup 2X200gm",
            "itemPrice": 20,
            "itemQuantity": 2,
            "itemType": "soup",
            "itemWeight": 50
          }
        ]
      }
    ]
  }
]
```


Success Response


```
{
    "status": 200,
    "message": "Order(s) created successfully",
    "data": [
        {
            "index": 0,
            "referenceId": "fa7716b25fe5432a96d1a709a28bd6d8",
            "orderNumber": "GR432U5",
            "shipmentOrderTypeCd": "PICKUP",
            "orderState": "FORWARD"
        }
    ],
    "hasError": false
}
```


Partial Success Response


```
{
    "status": 207,
```

```
    "message": "Order(s) created partially",
    "data": [
        {
            "index": 0,
            "referenceId": "fa7716b25fe5432a96d1a709a28bd6d8",
            "orderNumber": "GR432U5",
            "shipmentOrderTypeCd": "DELIVER",
            "orderState": "FORWARD"
        }
    ],
    "error": [
        {
            "index": 1,
            "orderNo": "GR432U6",
            "orderState": "FORWARD",
            "shipmentOrderTypeCd": "DELIVER",
            "errorList": [
                {
                    "key": "deliverBranch",
                    "message": [
                        "Deliver Branch is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```


Failure Response


```
{
   "status": 409,
   "message": "",
   "moreResultsExists": false,
   "error": [
       {
           "index": 0,
           "orderNo": "GR432U5",
           "orderState": "FORWARD",
           "shipmentOrderTypeCd": "PICKUP",
           "errorList": [
               {
                   "key": "pickupAccountCode",
                   "message": [
                       "Pickup Customer id  is mandatory."
                   ]
               }
           ]
       }
   ],
   "hasError": true
}
```


Create new Pickup orders in the LogiNext system using this API.

- This API creates a Pickup type of order (i.e., an order picked up from the pickup location and delivered to your branch, without stops at any intermediate branches) and assigns a unique Reference ID that can be used to identify the order later.
- Call this API along with the provided parameters to push existing pickup orders from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v2/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderNo	String	40	Conditional Mandatory	Unique identifier of an order. This is a multi-digit number assigned to an order to distinguish it from other orders. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-'(hyphen) as the order number. However, ensure that the order no. is unique for the same order type. For example, two Pickup orders should not have the same order number. If not provided, the system will auto-generate an order number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order.
shipmentOrderTypeCd	String	40	Mandatory	The value in this field must always be 'PICKUP'.
orderState	String	512	Mandatory	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of order whether the order is in forward state or reverse state. Specify 'FORWARD' if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or 'REVERSE' if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
autoAllocateFl	String	50	Optional	Whether the order should be considered for auto-assignment or not. Specify 'Y' to consider the order for auto-assignment (i.e., the order will be automatically assigned to the nearest delivery associate upon creation), 'N' if the order should not be considered for auto-assignment, or 'P' if you want to assign the newly created order to an existing planned trip. Note that selecting 'P' may affect the sequence of previously assigned orders for that trip.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If not provided, the default profile will be considered.
shipmentOrderDt	Date		Mandatory	The date on which you received the pickup order request. Note that the date and time must be in UTC format. For example - 2017-07-15T10:30:00.000Z.
distributionCenter	String	255	Mandatory	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in the System Preferences module under

				Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in the Order Prioritizing section under the Order Configuration module in Settings. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
serviceType	String	16	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.

signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
shippingCost	Double	10	Optional	The cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If a shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+shippingCost.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of pickup. If no value is provided, the system considers 'COD' by default.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
optimizePackingfl	String	1	Optional	Whether packaging optimization is required for this order or not. Specify ‘Y’ if packaging optimization is required for the order, or ‘N’ if not. In case it is required, the optimization process will automatically begin as soon as the order is created.
deliveryType	String	40	Optional	In certain operations, different skill sets or special delivery requirements are needed. For example, groceries or food items must be separated from toiletries orders, or cake orders cannot be combined with flower orders while delivering. In such cases, if you want to classify orders using the Delivery Type, you can use this field to ensure the orders are assigned to delivery associates configured in the LogiNext system with the required skill sets or delivery types. Note that you must define the Skill Sets in the Fleet Configuration module under Settings before passing it here in the orders. Contact your Account Manager to set these values for you. You can pass multiple Skill Sets in a comma-separated format in this API.
deliveryLocationType	String	255	Optional	Type of customer address, e.g., Residential, Office, etc.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver the order partially (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
returnAllowedFl	String	1	Optional	Whether the order is returnable or not. Specify ‘Y’ to allow your customers to initiate a return request post delivery, if needed, or ‘N’ to prevent returns. If no value is provided, the system considers ‘Y’ by default.

cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
deliveryMediumUsername	String		Optional	Username of the delivery associate responsible for fulfilling the order.
pickupBranch	String	255	Mandatory	For pickup type of orders, this field specifies the branch where the delivery associate will deliver the pickup order. Note that you must specify the Operation Branch using the Add Branch API or the Add Branch form in the Branch Configuration module. In case of any issues while creating a branch, contact your Account Manager.
pickupServiceTime	Integer	11	Mandatory	The time required to pick up the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the pickup time window.
pickupStartTimeWindowshipmentOrderTypeCd	Date		Mandatory	The opening time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Optional	The closing time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
				Identifier assigned to a customer’s address. If the

pickupAddressId	String	255	Optional	Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Mandatory	Name of the society or street in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Conditional Mandatory	Landmark of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Conditional Mandatory	Name of the state in the customer's pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer's pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer's pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer's pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	255	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.

returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnAddressId	String	255	Optional	Identifier assigned to a return customer's address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer's return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer's return address.
returnLandmark	String	512	Optional	Landmark of the customer's return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer's return address.
returnCity	String	512	Optional	Name of the city in the customer's return address.
returnState	String	50	Optional	Name of the state in the customer's return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer's return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
returnTimezone	String		Optional	Timezone of the customer's return address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
returnAWB	String	255	Optional	Air Waybill or AWB number associated with a return order request. If not provided, the system will consider the existing AWB as the return AWB.
clientCode	String	32	Optional	Name of the shipper's company associated with the order. Pass the company name of the shipper's account if you want to create an order on behalf of

				one of your shippers.
sendVerificationCd	String	1	Optional	Whether the One Time Password (OTP) verification is required for the order or not. Specify ‘Y’ to consider OTP verification or ‘N’ to not consider. If no value is provided, the system considers ‘Y’ by default.
pickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for pickup verification.
deliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for delivery verification.
returnPickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for return pickup verification.
returnDeliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for return delivery verification.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as ‘Related Orders’. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z’, 'A to Z’, '0 to 9’, ’_’(underscore), and ’-’(hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Within this parameter, enter the crate details of the order, including the crate code, amount, type, number of items, and other relevant details. In the case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid/semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order.
				Volume of the crate. The unit of measurement will be the same as specified in the System

shipmentCrateMappings.crateVolume	Double	10,3	Optional	Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateTemperatureCategory	String	255	Optional	Name of the temperature category for the crate. Provide the value specified in the 'Crate Management and Configuration' module when creating new crates. For example, a frozen temperature type for crates with frozen items such as ice creams.
shipmentCrateMappings.crateMinTemperature	Double	20,2	Optional	Minimum temperature of the crate.
shipmentCrateMappings.crateMaxTemperature	Double	20,2	Optional	Maximum temperature of the crate.
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.

shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item.
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item.
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item.
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item.
shipmentCrateMappings.shipmentlineitems.temperatureCategory	String	255	Optional	Name of the temperature category for the item. Provide the value specified in the 'Crate Management and Configuration' module. For example, a frozen temperature type for crates with frozen items such as ice creams.
shipmentCrateMappings.shipmentlineitems.minTemperature	Double	10,3	Optional	Minimum temperature that the item can be stored in without compromising its quality.
shipmentCrateMappings.shipmentlineitems.maxTemperature	Double	10,3	Optional	Maximum temperature that the item can be stored in without compromising its quality.

CREATE DELIVERY ONLY

Sample Request

```
[
 {
   "orderNo": "GR432U5",
   "awbNumber": "435-16685675",
   "shipmentOrderTypeCd": "DELIVER",
   "orderState": "FORWARD",
   "autoAllocateFl": "N",
   "autoAllocateProfileName":"ETAProfile",
   "shipmentOrderDt": "2016-07-15T10:30:00.000Z",
   "distributionCenter": "Chicago",
   "packageWeight":"10",
   "packageVolume": "4500",
   "packageLength": 2.5,
   "packageBreadth": 2.5,
   "packageHeight": 2.5,
   "priority": "PRIORITY1",
   "preparationTime":20,
   "serviceType":"Premium",
   "paymentType": "Prepaid",
   "originalOrderValue": "500",
   "orderDiscount": "10",
   "packageValue":"450",
   "insuranceRequiredFl": "Y",
   "insuredValue": "450",
   "signatureRequiredFl": "Y",
   "shippingCost":"50",
```

```
    "numberOfItems": 1,
    "packagingRequiredFl": "Y",
    "partialDeliveryAllowedFl": "Y",
    "returnAllowedFl": "Y",
    "cancellationAllowedFl": "N",
    "deliveryMediumUsername":"johnc",
    "deliverBranch": "Boston",
    "deliverServiceTime": "20",
    "deliverEndTimeWindow": "2016-07-18T10:31:00.000Z",
    "deliverStartTimeWindow": "2016-07-16T10:31:00.000Z",
    "deliveryType": "Groceries, Reefer",
    "deliveryLocationType":"Home",
    "deliverAccountCode": "Matt001",
    "deliverAddressId": "Home",
    "deliverAccountName": "Mathew Richardson",
    "deliverEmail":"m.richardson@testmail.com",
    "deliverPhoneNumber":"3125096995",
    "deliverWhatsappOptin":"Y",
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Towm Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude":41.882702,
    "deliverLongitude":-87.619392,
    "deliverAddressTimezone":"America/Chicago",
    "returnBranch": "Chicago",
    "deliverNotes": "Delivered",
    "clientCode": "Salestap",
    "optimizePackingfl":"Y",
    "sendVerificationCd": "Y",
    "pickupVerificationCd": "1112",
    "deliveryVerificationCd": "3333",
    "returnPickupVerificationCd": "3000",
    "returnDeliveryVerificationCd": "1233",
    "parentOrderNo": "GR432U578577",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
      {
        "crateCd": "CR041",
        "crateName": "Crate501",
        "crateAmount":100.65,
        "crateType":"case",
        "noOfUnits":2,
        "crateWeight":10,
        "crateVolume":11,
        "crateLength":12,
        "crateBreadth":13,
        "crateHeight":14,
        "crateTemperatureCategory": "Ambient",
        "crateMinTemperature": 10,
        "crateMaxTemperature": 20,
        "shipmentlineitems": [
          {
            "itemCd": "IT043",
            "itemName": "Chicken Soup 2X200gm",
            "itemPrice": 500,
            "itemQuantity": 1,
            "itemType": "soup",
            "itemWeight": 10,
            "itemVolume":16,
            "itemLength":17,
            "itemBreadth":18,
```

```
            "itemHeight":19,
            "temperatureCategory":"Ambient",
            "minTemperature":10,
            "maxTemperature":15
          },
          {
            "itemCd": "IT030",
            "itemName": "WholeBeanCoffee 6x1kg",
            "itemPrice": 400,
            "itemQuantity": 2,
            "itemType": "coffee",
            "itemWeight": 10,
            "itemVolume":16,
            "itemLength":17,
            "itemBreadth":18,
            "itemHeight":19,
            "temperatureCategory":"Ambient",
            "minTemperature":10,
            "maxTemperature":15
          }
        ]

      }
    ]
  }
]
```


Success Response


```
{
    "status": 200,
    "message": "Order(s) created successfully",
    "data": [
        {
            "index": 0,
            "referenceId": "6a34c7274df0489f97c0f891514b488b",
            "orderNumber": "GR432U5",
            "shipmentOrderTypeCd": "DELIVER",
            "orderState": "FORWARD"
        }
    ],
    "hasError": false
}
```


Partial Success Response


```
{
    "status": 207,
    "message": "Order(s) created partially",
    "data": [
        {
            "index": 0,
            "referenceId": "b032f3e9397343ba812f96370b92d592",
            "orderNumber": "GR432U5",
            "shipmentOrderTypeCd": "DELIVER",
            "orderState": "FORWARD"
        }
    ],
    "error": [
        {
            "index": 1,
            "orderNo": "GR432U6",
```

```
            "orderState": "FORWARD",
            "shipmentOrderTypeCd": "DELIVER",
            "errorList": [
                {
                    "key": "deliverBranch",
                    "message": [
                        "Deliver Branch is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Failure Response

```
{
  "status": 409,
  "message": "",
  "moreResultsExists": false,
  "error": [
      {
          "index": 0,
          "orderNo": "GR432U5",
          "orderState": "FORWARD",
          "shipmentOrderTypeCd": "DELIVER",
          "errorList": [
              {
                  "key": "deliverEndTimeWindow",
                  "message": [
                      "Deliver end-time window is mandatory."
                  ]
              }
          ]
      }
  ],
  "hasError": true
}
```

Create new Delivery orders in the LogiNext system using this API.

- This API creates a Delivery type of order (i.e., an order picked up from your branch and delivered to the delivery location, without stops at any intermediate branches) and assigns a unique Reference ID that can be used to identify the order later.
- Call this API along with the provided parameters to push existing delivery orders from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v2/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderNo	String	40	Conditional Mandatory	Unique identifier of an Order. This is a multi-digit number assigned to an order to distinguish it from other orders. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-'(hyphen) as the order number. However, ensure that the order no. is unique for the same order type. For

				example, two Delivery orders should not have the same order number. If not provided, the system will auto-generate an order number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order.
shipmentOrderTypeCd	String	40	Mandatory	The value in this field must always be ‘DELIVER’.
orderState	String	512	Mandatory	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of order whether the order is in forward state or reverse state. Specify ‘FORWARD’ if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or ‘REVERSE’ if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
autoAllocateFl	String	50	Optional	Whether the order should be considered for auto-assignment or not. Specify 'Y' to consider the order for auto-assignment (i.e., the order will be automatically assigned to the nearest delivery associate upon creation), ‘N’ if the order should not be considered for auto-assignment, or ‘P’ if you want to assign the newly created order to an existing planned trip. Note that selecting 'P' may affect the sequence of previously assigned orders for that trip.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If not provided, the default profile will be considered.
shipmentOrderDt	Date		Mandatory	The date on which you received the order request. Note that the date and time in UTC format. For example - 2017-07-15T10:30:00.000Z.
distributionCenter	String	255	Mandatory	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

priority	String	16	Optional	You can assign a priority to the order as per the values configured in the Order Prioritizing section under the Order Configuration module in Settings. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
preparationTime	Double	10,3	Optional	Time (in minutes) required to prepare the order. This will help your delivery associates reach the pickup location at the right time, thereby minimizing the time spent in waiting for the order to be handed over or compromising the order quality in terms of freshness, etc. Note that you must enable the ‘Consider Order Preparation Time’ property in the Auto-Assignment Profile to enable this.
serviceType	String	16	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
optimizePackingfl	String	1	Optional	Whether packaging optimization is required for this order or not. Specify ‘Y’ if packaging optimization is required for the order, or ‘N’ if not. In case it is required, the optimization process will automatically begin as soon as the order is created.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of delivery. If no value is provided, the system considers 'COD' by default.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to pick up the order partially (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
				The cost incurred in the movement of the order. Shipping cost is also

shippingCost	Double	10	Optional	referred to as delivery charges. If a shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+shippingCost.
returnAllowedFl	String	1	Optional	Whether the order is returnable or not. Specify ‘Y’ to allow your customers to initiate a return request post delivery, if needed, or ‘N’ to prevent returns. If no value is provided, the system considers ‘Y’ by default.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
deliveryMediumUsername	String		Optional	Username of the delivery associate responsible for fulfilling the order.
deliverBranch	String	255	Mandatory	For the delivery type of orders, this field specifies the branch where the delivery associate will pick up the order. Note that you must specify the Operation Branch using the Add Branch API or the Add Branch form in the Branch Configuration module. In case of any issues while creating a branch, contact your Account Manager.
deliverServiceTime	Integer	11	Optional	The time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliveryType	String	40	Optional	In certain operations, different skill sets or special delivery requirements are needed. For example, groceries or food items must be separated from toiletries orders, or cake orders cannot be combined with flower orders while delivering. In such cases, if you want to classify orders using the Delivery Type, you can use this field to ensure the orders are assigned to delivery associates configured in the LogiNext system with the required skill sets or delivery types. Note that you must define the Skill Sets in the Fleet Configuration module under Settings before passing it here in the orders. Contact your Account Manager to set these values for you. You can pass multiple Skill Sets in a comma-separated format in this API.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
deliverAccountName	String	255	Conditional Mandatory	Name of the delivery customer. This field is optional if the Customer Profiling property is enabled.

deliverEmail	String	100	Optional	Email ID of the customer.
deliverPhoneNumber	String	255	Optional	Contact number of the customer. This field is optional if the Customer Profiling property is enabled.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer’s delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String	50	Conditional Mandatory	Name of the state in the customer’s delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer’s delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer’s delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer’s delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer’s delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer’s delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
returnBranch	String	255	Conditional Mandatory	Name of branch where the order should be returned, if needed. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.

deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
clientCode	String	32	Optional	Name of the shipper's company associated with the order. Pass the company name of the shipper's account if you want to create an order on behalf of one of your shippers.
sendVerificationCd	String	1	Optional	Whether the One Time Password (OTP) verification is required for the order or not. Specify 'Y' to consider OTP verification or 'N' to not consider. If no value is provided, the system considers 'Y' by default.
pickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for pickup verification.
deliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for delivery verification.
returnPickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for return pickup verification.
returnDeliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for return delivery verification.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as 'Related Orders'. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-' (hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt-out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Within this parameter, enter the crate details of the order, including the crate code, amount, type, number of items, and other relevant details. In the case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order.
				Volume of the crate. The unit of

shipmentCrateMappings.crateVolume	Double	10,3	Optional	measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in the System Preferences module in Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateTemperatureCategory	String	255	Optional	Name of the temperature category for the crate. Provide the value specified in the 'Crate Management and Configuration' module when creating new crates. For example, a frozen temperature type for crates with frozen items such as ice creams.
shipmentCrateMappings.crateMinTemperature	Double	20,2	Optional	Minimum temperature of the crate.
shipmentCrateMappings.crateMaxTemperature	Double	20,2	Optional	Maximum temperature of the crate.
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.

shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item.
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item.
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item.
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item.
shipmentCrateMappings.shipmentlineitems.temperatureCategory	String	255	Optional	Name of the temperature category for the item. Provide the value specified in the 'Crate Management and Configuration' module. For example, a frozen temperature type for crates with frozen items such as ice creams.
shipmentCrateMappings.shipmentlineitems.minTemperature	Double	10,3	Optional	Minimum temperature that the item can be stored in without compromising its quality.
shipmentCrateMappings.shipmentlineitems.maxTemperature	Double	10,3	Optional	Maximum temperature that the item can be stored in without compromising its quality.

CREATE PICKUP & DELIVER

Sample Request

```
[
 {
   "orderNo": "GR432U5",
   "awbNumber": "435-16685675",
   "shipmentOrderTypeCd": "BOTH",
   "orderState": "FORWARD",
   "autoAllocateFl": "N",
   "autoAllocateProfileName":"ETAProfile",
   "shipmentOrderDt": "2016-07-15T10:30:00.000Z",
   "distributionCenter": "Down Town Chicago",
   "packageWeight":"10",
   "packageVolume": "4500",
   "priority": "PRIORITY3",
   "serviceType":"Premium",
   "paymentType": "Prepaid",
   "originalOrderValue": "500",
   "orderDiscount": "10",
   "packageValue":"450",
   "insuranceRequiredFl": "Y",
   "insuredValue": "450",
   "signatureRequiredFl": "Y",
   "shippingCost":"50",
   "numberOfItems": 1,
   "packagingRequiredFl": "Y",
```

```
    "partialDeliveryAllowedFl": "Y",
    "returnAllowedFl": "Y",
    "cancellationAllowedFl": "N",
    "deliveryMediumUsername":"johnc",
    "deliverBranch": "Boston",
    "deliverServiceTime": "20",
    "deliverEndTimeWindow": "2016-07-18T10:31:00.000Z",
    "deliverStartTimeWindow": "2016-07-16T10:31:00.000Z",
    "deliveryType": "Groceries, Reefer",
    "deliveryLocationType":"Home",
    "deliverEmail":"m.richardson@testmail.com",
    "deliverPhoneNumber":"9891234567",
    "deliverWhatsappOptin":"Y",
    "deliverAccountCode": "Matt001",
    "deliverAddressId": "home",
    "deliverAccountName": "Mathew Richardson",
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Towm Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude":41.882702,
    "deliverLongitude":-87.619392,
    "deliverAddressTimezone":"America/Chicago",
    "pickupBranch":"East Manhattan",
    "pickupServiceTime": "50",
    "pickupStartTimeWindow": "2016-07-16T14:24:00.000Z",
    "pickupEndTimeWindow": "2016-07-17T14:24:00.000Z",
    "pickupEmail":"james.w@ablogs.com",
    "pickupPhoneNumber": "5163063377",
    "pickupWhatsappOptin":"Y",
    "pickupAccountCode": "jim001",
    "pickupAddressId": "Home",
    "pickupAccountName": "James Walker",
    "pickupApartment": "901",
    "pickupStreetName": "2142 3rd Ave",
    "pickupLandmark": "Opp. McDonalds",
    "pickupLocality": "East Harlem",
    "pickupCity": "New York",
    "pickupState": "NY",
    "pickupCountry": "USA",
    "pickupPinCode": "10035",
    "pickupLatitude":40.760838,
    "pickupLongitude":-73.96732299999996,
    "pickupAddressTimezone":"America/New_York",
    "returnBranch": "East Manhatten",
    "returnStartTimeWindow": "2016-05-18T03:00:00.000Z",
    "returnEndTimeWindow": "2016-05-18T16:00:00.000Z",
    "returnAccountCode": "jim001",
    "returnAddressId": "Home",
    "returnAccountName": "James Walker",
    "returnEmail": "james.w@ablogs.com",
    "returnPhoneNumber": "9891234567",
    "returnWhatsappOptin": "Y",
    "returnApartment": "901",
    "returnStreetName": "2142 3rd Ave",
    "returnLandmark": "OOpp. McDonalds",
    "returnLocality": "East Harlem",
    "returnCity": "New York",
    "returnState": "NY",
    "returnCountry": "USA",
    "returnPinCode": "10035",
    "pickupNotes": "PickedUp",
```

```
    "deliverNotes": "Delivered",
    "clientCode": "Salestap",
    "optimizePackingfl":"Y",
    "sendVerificationCd": "Y",
    "pickupVerificationCd": "1112",
    "deliveryVerificationCd": "3333",
    "returnPickupVerificationCd": "3000",
    "returnDeliveryVerificationCd": "1233",
    "parentOrderNo": "GR432U578577",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
      {
        "crateCd": "CR041",
        "crateName": "Crate501",
        "crateAmount":100.65,
        "crateType":"case",
        "noOfUnits":2,
        "crateWeight":10,
        "crateVolume":11,
        "crateLength":12,
        "crateBreadth":13,
        "crateHeight":14,
        "crateTemperatureCategory": "Ambient",
        "crateMinTemperature": 10,
        "crateMaxTemperature": 20,
        "shipmentlineitems": [
          {
            "itemCd": "IT043",
            "itemName": "Chicken Soup 2X200gm",
            "itemPrice": 500,
            "itemQuantity": 1,
            "itemType": "soup",
            "itemWeight": 10,
            "itemVolume":11,
            "itemLength":12,
            "itemBreadth":13,
            "itemHeight":14,
            "temperatureCategory":null,
            "minTemperature":10,
            "maxTemperature":15

          },
          {
            "itemCd": "IT030",
            "itemName": "WholeBeanCoffee 6x1kg",
            "itemPrice": 400,
            "itemQuantity": 2,
            "itemType": "coffee",
            "itemWeight": 15,
            "itemVolume":16,
            "itemLength":17,
            "itemBreadth":18,
            "itemHeight":19,
            "temperatureCategory":"Ambient",
            "minTemperature":10,
            "maxTemperature":15
          }
        ]
      }
    ]
  }
]
```


Success Response

```
{
    "status": 200,
    "message": "Order(s) created successfully",
    "data": [
        {
            "index": 0,
            "referenceId": "6a34c7274df0489f97c0f891514b488b",
            "orderNumber": "GR432U5",
            "shipmentOrderTypeCd": "BOTH",
            "orderState": "FORWARD"
        }
    ],
    "hasError": false
}
```


Partial Success Response


```
{
    "status": 207,
    "message": "Order(s) created partially",
    "data": [
        {
            "index": 0,
            "referenceId": "b032f3e9397343ba812f96370b92d592",
            "orderNumber": "GR432U5",
            "shipmentOrderTypeCd": "DELIVER",
            "orderState": "FORWARD"
        }
    ],
    "error": [
        {
            "index": 1,
            "orderNo": "GR432U6",
            "orderState": "FORWARD",
            "shipmentOrderTypeCd": "DELIVER",
            "errorList": [
                {
                    "key": "deliverBranch",
                    "message": [
                        "Deliver Branch is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```


Failure Response


```
{
   "status": 409,
   "message": "",
   "moreResultsExists": false,
   "error": [
       {
           "index": 0,
           "orderNo": "GR432U5",
           "orderState": "FORWARD",
           "shipmentOrderTypeCd": "BOTH",
           "errorList": [
               {
```

```
                    "key": "returnBranch",
                    "message": [
                        "Return Branch name is mandatory."
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Create new Pickup and Delivery orders in the LogiNext system using this API.

- This API creates a Pickup and Delivery type of order (i.e., an order picked up from the pickup location and brought to your branch before being picked up again and delivered to the delivery location) and assigns a unique Reference ID that can be used to identify the order later.
- Call this API along with the provided parameters to push existing pickup and delivery orders from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v2/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderNo	String	40	Conditional Mandatory	Unique identifier of an Order. This is a multi-digit number assigned to a order to distinguish it from other orders. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-'(hyphen) as the order number. However, ensure that the order no. is unique for the same order type. For example, two Delivery orders should not have the same order number. If not provided, the system will auto-generate an order number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order.
shipmentOrderTypeCd	String	40	Mandatory	The value in this field must always be 'BOTH'.
autoAllocateFl	String	50	Optional	Whether the order should be considered for auto-assignment or not. Specify 'Y' to consider the order for auto-assignment (i.e., the order will be automatically assigned to the nearest delivery associate upon creation), 'N' if the order should not be considered for auto-assignment, or 'P' if you want to assign the newly created order to an existing planned trip. Note that selecting 'P' may affect the sequence of previously assigned orders for that trip.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If not provided, the default profile will be considered.
orderState	String	512	Mandatory	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of order whether the order is in forward state or reverse state. Specify 'FORWARD' if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or 'REVERSE' if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
				The date on which you received the order request. Note that the date

shipmentOrderDt	Date		Mandatory	and time in UTC format. For example - 2017-07-15T10:30:00.000Z.
distributionCenter	String	255	Mandatory	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in the Order Prioritizing section under the Order Configuration module in Settings. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
serviceType	String	16	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
				Whether you want the signature/adult signature for the order or not.

signatureRequiredFl	String	16	Optional	Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
shippingCost	Double	10	Optional	The cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If a shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+shippingCost.
paymentType	String	40	Mandatory	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of delivery. If no value is provided, the system considers 'COD' by default.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
optimizePackingfl	String	1	Optional	Whether packaging optimization is required for this order or not. Specify ‘Y’ if packaging optimization is required for the order, or ‘N’ if not. In case it is required, the optimization process will automatically begin as soon as the order is created.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver the order partially (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
returnAllowedFl	String	1	Optional	Whether the order is returnable or not. Specify ‘Y’ to allow your customers to initiate a return request post delivery, if needed, or ‘N’ to prevent returns. If no value is provided, the system considers ‘Y’ by default.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
deliveryMediumUsername	String		Optional	Username of the delivery associate responsible for fulfilling the order.
deliverBranch	String	255	Mandatory	For the pickup and delivery type of orders, this field specifies the branch where the delivery associate will pick up the order. Note that you must specify the Operation Branch using the Add Branch API or the Add Branch form in the Branch Configuration module. In case of any issues while creating a branch, contact your Account Manager.
deliveryType	String	40	Optional	In certain operations, different skill sets or special delivery requirements are needed. For example, groceries or food items must be separated from toiletries orders, or cake orders cannot be combined with flower orders while delivering. In such cases, if you want to classify orders using different skill sets or delivery types, you can use this field to ensure the orders are assigned to delivery associates configured in the LogiNext system with the required skill sets or delivery types. Note that you must define the Skill Sets in the Fleet Configuration module under Settings before passing it here in the orders. Contact your Account Manager to set these values for you. You can pass multiple Skill Sets in a comma-separated format in this API.

pickupBranch	String	255	Mandatory	For pickup type of orders, this field specifies the branch where the delivery associate will deliver the pickup order. Note that you must specify the Operation Branch using the Add Branch API or the Add Branch form in the Branch Configuration module. In case of any issues while creating a branch, contact your Account Manager.
pickupServiceTime	Integer	11	Mandatory	The time required to pick up the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the pickup time window.
pickupStartTimeWindow	Date		Mandatory	The opening time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Pickup time window is the customer's preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Optional	The closing time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Mandatory	Name of the society or street in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Conditional Mandatory	Landmark of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.

pickupState	String	50	Conditional Mandatory	Name of the state in the customer's pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer's pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer's pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer's pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverServiceTime	Integer	11	Mandatory	The time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
deliverStartTimeWindow	Date		Mandatory	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer's preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2018-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Mandatory	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2018-07-01T11:18:00.000Z.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
deliverAccountName	String	255	Conditional Mandatory	Name of the delivery customer. This field is optional if the Customer Profiling property is enabled.
deliverEmail	String	100	Optional	Email ID delivery of the customer.
deliverPhoneNumber	String	255	Optional	Contact number of the delivery customer.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual

				Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String	50	Conditional Mandatory	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double	100	Optional	Latitude coordinates of the customer's delivery address.
deliverLongitude	Double	100	Optional	Longitude coordinates of the customer's delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer's delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
returnBranch	String	255	Conditional Mandatory	Name of branch where the order should be returned, if needed. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.

returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnPhoneNumber	String	255	Conditional Mandatory	Contact number of the return customer.
returnWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
returnAddressId	String	255	Optional	Identifier assigned to a return customer’s address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer’s return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer’s return address.
returnLandmark	String	512	Optional	Landmark of the customer’s return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer’s return address.
returnCity	String	512	Optional	Name of the city in the customer’s return address.
returnState	String	50	Optional	Name of the state in the customer’s return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer’s return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
sendVerificationCd	String	1	Optional	Whether the One Time Password (OTP) verification is required for the order or not. Specify ‘Y’ to consider OTP verification or ‘N’ to not consider. If no value is provided, the system considers ‘Y’ by default.
pickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for pickup verification.
deliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for delivery verification.
returnPickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for return pickup verification.
returnDeliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for return delivery verification.
clientCode	String	32	Optional	Name of the shipper’s company associated with the order. Pass the company name of the shipper’s account if you want to create an order on behalf of one of your shippers.

parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as ‘Related Orders’. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z’, 'A to Z’, '0 to 9’, ’_’(underscore), and ’-’ (hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Within this parameter, enter the crate details of the order, including the crate code, amount, type, number of items, and other relevant details. In the case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system,

				this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateTemperatureCategory	String	255	Optional	Name of the temperature category for the crate. Provide the value specified in the 'Crate Management and Configuration' module when creating new crates. For example, a frozen temperature type for crates with frozen items such as ice creams.
shipmentCrateMappings.crateMinTemperature	Double	20,2	Optional	Minimum temperature of the crate.
shipmentCrateMappings.crateMaxTemperature	Double	20,2	Optional	Maximum temperature of the crate.
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item.
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item.
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item.
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item.
				Name of the temperature category for the item. Provide the value

shipmentCrateMappings.shipmentlineitems.temperatureCategory	String	255	Optional	specified in the 'Crate Management and Configuration' module. For example, a frozen temperature type for crates with frozen items such as ice creams.
shipmentCrateMappings.shipmentlineitems.minTemperature	Double	10,3	Optional	Minimum temperature that the item can be stored in without compromising its quality.
shipmentCrateMappings.shipmentlineitems.maxTemperature	Double	10,3	Optional	Maximum temperature that the item can be stored in without compromising its quality.

CREATE POINT-TO-POINT

Sample Request


```
[
 {
   "orderNo": "PPPL0001",
   "autoAllocateFl":"N",
   "autoAllocateProfileName":"ETAProfile",
   "awbNumber": "435-16685675",
   "shipmentOrderDt": "2019-02-05T10:30:00.000Z",
   "shipmentOrderTypeCd": "DELIVER",
   "orderState": "FORWARD",
   "distributionCenter": "Lower Manhattan",
   "packageWeight":"10",
   "packageVolume": "4500",
   "packageLength":5,
   "packageBreadth":5,
   "packageHeight":5,
   "priority": "PRIORITY1",
   "preparationTime":20,
   "serviceType":"Premium",
   "paymentType": "Prepaid",
   "originalOrderValue": "500",
   "orderDiscount": "10",
   "packageValue":"450",
   "insuranceRequiredFl": "Y",
   "insuredValue": "450",
   "signatureRequiredFl": "Y",
   "shippingCost":"50",
   "numberOfItems": 1,
   "packagingRequiredFl": "Y",
   "partialDeliveryAllowedFl": "Y",
   "returnAllowedFl": "N",
   "cancellationAllowedFl": "Y",
   "deliverServiceTime": "20",
   "deliverEndTimeWindow": "2018-07-18T10:31:00.000Z",
   "deliverStartTimeWindow": "2018-07-16T10:31:00.000Z",
   "deliveryType": "Groceries, Reefer",
   "deliveryLocationType":"Home",
   "deliverEmail":"m.richardson@testmail.com",
   "deliverPhoneNumber":"9891234567",
   "deliverWhatsappOptin":"Y",
   "deliverAccountCode": "Matt001",
   "deliverAddressId": "home",
   "deliverAccountName": "Mathew Richardson",
   "deliverApartment": "201",
   "deliverStreetName": "E Randolph St",
   "deliverLandmark": "Opp. Chiptole",
   "deliverLocality": "Down Towm Chicago",
```

```
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude":41.882702,
    "deliverLongitude":-87.619392,
    "deliverAddressTimezone":"America/Chicago",
    "deliverNotes": "Leave it with the neighbour",
    "pickupServiceTime": "50",
    "pickupStartTimeWindow": "2018-07-16T14:24:00.000Z",
    "pickupEndTimeWindow": "2018-07-17T14:24:00.000Z",
    "pickupEmail":"james.w@ablogs.com",
    "pickupPhoneNumber": "5163063377",
    "pickupWhatsappOptin":"Y",
    "pickupAccountCode": "jim001",
    "pickupAddressId": "Home",
    "pickupAccountName": "James Walker",
    "pickupApartment": "901",
    "pickupStreetName": "2142 3rd Ave",
    "pickupLandmark": "Opp. McDonalds",
    "pickupLocality": "East Harlem",
    "pickupCity": "New York",
    "pickupState": "NY",
    "pickupCountry": "USA",
    "pickupPinCode": "10035",
    "pickupLatitude":40.760838,
    "pickupLongitude":-73.96732299999996,
    "pickupAddressTimezone":"America/New_York",
    "pickupNotes": "Don't ring the doorbell",
    "clientCode": "Salestap",
    "optimizePackingfl":"Y",
    "pickupVerificationCd": "1112",
    "deliveryVerificationCd": "3333",
    "returnPickupVerificationCd": "3000",
    "returnDeliveryVerificationCd": "1233",
    "parentOrderNo": "GR432U578577",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
      {
        "crateCd": "CR041",
        "crateName": "Crate501",
        "crateAmount":100.65,
        "crateType":"case",
        "noOfUnits":2,
        "crateWeight":10,
        "crateVolume":11,
        "crateLength":12,
        "crateBreadth":13,
        "crateHeight":14,
        "crateTemperatureCategory": "Ambient",
        "crateMinTemperature": 10,
        "crateMaxTemperature": 20,
        "shipmentlineitems": [
          {
            "itemCd": "IT043",
            "itemName": "Chicken Soup 2X200gm",
            "itemPrice": 500,
            "itemQuantity": 1,
            "itemType": "soup",
            "itemWeight": 10,
            "itemVolume":11,
            "itemLength":12,
            "itemBreadth":13,
            "itemHeight":14
          },
          {
```

```
            "itemCd": "IT030",
            "itemName": "WholeBeanCoffee 6x1kg",
            "itemPrice": 400,
            "itemQuantity": 2,
            "itemType": "coffee",
            "itemWeight": 15,
            "itemVolume":16,
            "itemLength":17,
            "itemBreadth":18,
            "itemHeight":19
          }
        ]
      }
      ]
  }
]
```


Success Response


```
{
    "status": 200,
    "message": "ORDER_CREATION_SUCCESS",
    "moreResultsExists": false,
    "data": [
        {
            "index": 0,
            "referenceId": "eb7a0e88612c4e888f04b98387099fd1",
            "orderNumber": "PPPL0001",
            "shipmentOrderTypeCd": "DELIVER",
            "orderState": "FORWARD"
        }
    ],
    "hasError": false
}
```


Partial Success Response


```
{
    "status": 207,
    "message": "Order(s) created partially",
    "data": [
        {
            "index": 0,
            "referenceId": "b032f3e9397343ba812f96370b92d592",
            "orderNumber": "PPPL0001",
            "shipmentOrderTypeCd": "DELIVER",
            "orderState": "FORWARD"
        },
        {
            "index": 1,
            "referenceId": "af7065ad4f3945a889ec25c323aa7b68",
            "orderNumber": "PPPL0002",
            "shipmentOrderTypeCd": "DELIVER",
            "orderState": "FORWARD"
        },
        {
            "index": 2,
            "referenceId": "a4e6dc610c854166a7957b9876aa4ce5",
            "orderNumber": "PPPL0003",
            "shipmentOrderTypeCd": "DELIVER",
            "orderState": "FORWARD"
        }
```

```
    ],
    "error": [
        {
            "index": 3,
            "orderNo": "PPPL0004",
            "orderState": "FORWARD",
            "shipmentOrderTypeCd": "DELIVER",
            "errorList": [
                {
                    "key": "distributionCenter",
                    "message": [
                        "Distribution Center is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```


Failure Response


```
{
    "status": 409,
    "message": "",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "orderNo": "PPPL0001",
            "orderState": "FORWARD",
            "shipmentOrderTypeCd": "DELIVER",
            "errorList": [
                {
                    "key": "deliveryType",
                    "message": [
                        "DeliveryType is invalid"
                    ]
                },
                {
                    "key": "distributionCenter",
                    "message": [
                        "Distribution Center is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```


Create new Point-to-Point orders in the LogiNext system using this API.

- This API creates a Point-to-Point type of order (i.e., an order picked up from the pickup location and delivered to the delivery location, without stops at any intermediate branches) and assigns a unique Reference ID that can be used to identify the order later.
- Call this API along with the provided parameters to push existing point-to-point orders from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v2/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderNo	String	40	Conditional Mandatory	Unique identifier of an Order. This is a multi-digit number assigned to a order to distinguish it from other orders. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-'(hyphen) as the order number. If not provided, the system will auto-generate an order number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order.
shipmentOrderTypeCd	String	40	Mandatory	The value in this field must always be 'DELIVER'.
autoAllocateFl	String	50	Optional	Whether the order should be considered for auto-assignment or not. Specify 'Y' to consider the order for auto-assignment (i.e., the order will be automatically assigned to the nearest delivery associate upon creation), 'N' if the order should not be considered for auto-assignment, or 'P' if you want to assign the newly created order to an existing planned trip. Note that selecting 'P' may affect the sequence of previously assigned orders for that trip.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If not provided, the default profile will be considered.
orderState	String	512	Mandatory	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of order whether the order is in forward state or reverse state. Specify 'FORWARD' if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or 'REVERSE' if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
shipmentOrderDt	Date		Mandatory	The date on which you received the order request. Note that the date and time in UTC format. For example - 2016-07-01T11:18:00.000Z.
distributionCenter	String	255	Mandatory	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in the System Preferences module in Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the

				imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in the Order Prioritizing section under the Order Configuration module in Settings. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
preparationTime	Double	10,3	Optional	Time (in minutes) required to prepare the order. This will help your delivery associates reach the pickup location at the right time, thereby minimizing the time spent in waiting for the order to be handed over or compromising the order quality in terms of freshness, etc. Note that you must enable the ‘Consider Order Preparation Time’ property in the Auto-Assignment Profile to enable this.
serviceType	String	16	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
shippingCost	Double	10	Optional	The cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If a shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+shippingCost.
paymentType	String	40	Mandatory	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of delivery. If no value is provided, the system considers 'COD' by default.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
				Whether packaging optimization is required for this order or not.

optimizePackingfl	String	1	Optional	Specify ‘Y’ if packaging optimization is required for the order, or ‘N’ if not. In case it is required, the optimization process will automatically begin as soon as the order is created.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver the order partially (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
returnAllowedFl	String	1	Optional	Whether the order is returnable or not. Specify ‘Y’ to allow your customers to initiate a return request post delivery, if needed, or ‘N’ to prevent returns. If no value is provided, the system considers ‘Y’ by default.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
pickupServiceTime	Integer	11	Mandatory	The time required to pick up the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the pickup time window.
pickupStartTimeWindow	Date		Mandatory	The opening time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
pickupEndTimeWindow	Date		Optional	The closing time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2016-07-02T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique

				alphanumeric value as the Address ID.
pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Mandatory	Name of the society or street in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Conditional Mandatory	Landmark of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Conditional Mandatory	Name of the state in the customer's pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer's pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer's pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer's pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
deliverServiceTime	Integer	11	Optional	The time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer's preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.

deliveryType	String	40	Optional	In certain operations, different skill sets or special delivery requirements are needed. For example, groceries or food items must be separated from toiletries orders, or cake orders cannot be combined with flower orders while delivering. In such cases, if you want to classify orders using the Delivery Type, you can use this field to ensure the orders are assigned to delivery associates configured in the LogiNext system with the required skill sets or delivery types. Note that you must define the Skill Sets in the Fleet Configuration module under Settings before passing it here in the orders. Contact your Account Manager to set these values for you. You can pass multiple Skill Sets in a comma-separated format in this API.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
deliverAccountName	String	255	Conditional Mandatory	Name of the delivery customer. This field is optional if the Customer Profiling property is enabled.
deliverEmail	String	100	Optional	Email ID of the delivery customer.
deliverPhoneNumber	String	255	Optional	Contact number of the delivery customer.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String	50	Conditional Mandatory	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system. This

				field is optional if the Customer Profiling property is enabled.
deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer's delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer's delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer's delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
clientCode	String	32	Optional	Name of the shipper's company associated with the order. Pass the company name of the shipper's account if you want to create an order on behalf of one of your shippers.
sendVerificationCd	String	1	Optional	Whether the One Time Password (OTP) verification is required for the order or not. Specify 'Y' to consider OTP verification or 'N' to not consider. If no value is provided, the system considers 'Y' by default.
pickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for pickup verification.
deliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for delivery verification.
returnPickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for return pickup verification.
returnDeliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for return delivery verification.
returnAllowedFl	String	50	Optional	Whether the order is returnable or not. This will let your customer initiate a return order request post delivery, if required. Specify 'Y' to allow return, or 'N' to prevent return requests for this order.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnAddressId	String	255	Optional	Identifier assigned to a return customer's address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer's return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer's return address.

returnLandmark	String	512	Optional	Landmark of the customer's return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer's return address.
returnCity	String	512	Optional	Name of the city in the customer's return address.
returnState	String	50	Optional	Name of the state in the customer's return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer's return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
returnTimezone	String		Optional	Timezone of the customer's return address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
returnAWB	String	255	Optional	Air Waybill or AWB number associated with a return order request. If not provided, the system will consider the existing AWB as the return AWB.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as 'Related Orders'. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-' (hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Within this parameter, enter the crate details of the order, including the crate code, amount, type, number of items, and other relevant details. In the case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.

shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateTemperatureCategory	String	255	Optional	Name of the temperature category for the crate. Provide the value specified in the 'Crate Management and Configuration' module when creating new crates. For example, a frozen temperature type for crates with frozen items such as ice creams.
shipmentCrateMappings.crateMinTemperature	Double	20,2	Optional	Minimum temperature of the crate.

shipmentCrateMappings.crateMaxTemperature	Double	20,2	Optional	Maximum temperature of the crate.
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item.
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item.
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item.
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item.
shipmentCrateMappings.shipmentlineitems.temperatureCategory	String	255	Optional	Name of the temperature category for the item. Provide the value specified in the 'Crate Management and Configuration' module. For example, a frozen temperature type for crates with frozen items such as ice creams.
shipmentCrateMappings.shipmentlineitems.minTemperature	Double	10,3	Optional	Minimum temperature that the item can be stored in without compromising its quality.
shipmentCrateMappings.shipmentlineitems.maxTemperature	Double	10,3	Optional	Maximum temperature that the item can be stored in without compromising its quality.

END-TO-END ACCOUNT: CREATE MULTI-LEG

Sample Request

```
[
 {
   "orderNo": "GR432U5",
   "awbNumber": "435-16685675",
   "shipmentOrderTypeCd": "ALLMILE",
   "orderState": "FORWARD",
   "autoAllocateFl": "N",
   "autoAllocateProfileName":"ETAProfile",
   "shipmentOrderDt": "2016-07-15T10:30:00.000Z",
   "distributionCenter": "Down Town Chicago",
   "originBranchName" :"Houston",
   "destinationBranchName" : "Boston",
   "routeConfigurationName": "Houston-Boston",
   "nextBranchName":"Cupertino",
   "nextBranchServiceTime": 5,
```

```
    "nextBranchStartTimeWindow" : "2016-07-15T10:30:00.000Z",
    "nextBranchEndTimeWindow": "2016-07-15T10:30:00.000Z",
    "deliveryType": "Groceries",
    "serviceTypeCd": "Economy",
    "packageWeight":"10",
    "packageVolume": "4500",
    "paymentType": "Prepaid",
    "originalOrderValue": "500",
    "orderDiscount": "10",
    "packageValue":"450",
    "insuranceRequiredFl": "Y",
    "insuredValue": "450",
    "signatureRequiredFl": "Y",
    "shippingCost":"50",
    "numberOfItems": 1,
    "packagingRequiredFl": "Y",
    "partialDeliveryAllowedFl": "Y",
    "cancellationAllowedFl": "N",
    "deliverServiceTime": "20",
    "deliverEndTimeWindow": "2016-07-18T10:31:00.000Z",
    "deliverStartTimeWindow": "2016-07-16T10:31:00.000Z",
    "deliveryLocationType":"Home",
    "deliverEmail":"m.richardson@testmail.com",
    "deliverPhoneNumber":"9891234567",
    "deliverWhatsappOptin":"Y",
    "deliverAccountCode": "Matt001",
    "deliverAddressId": "home",
    "deliverAccountName": "Mathew Richardson",
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Town Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude":41.882702,
    "deliverLongitude":-87.619392,
    "deliverAddressTimezone":"America/Chicago",
    "pickupServiceTime": "50",
    "pickupStartTimeWindow": "2019-07-16T14:24:00.000Z",
    "pickupEndTimeWindow": "2019-07-17T14:24:00.000Z",
    "pickupEmail":"james.w@ablogs.com",
    "pickupPhoneNumber": "5163063377",
    "pickupWhatsappOptin":"Y",
    "pickupAccountCode": "jim001",
    "pickupAddressId": "Home",
    "pickupAccountName": "James Walker",
    "pickupApartment": "901",
    "pickupStreetName": "2142 3rd Ave",
    "pickupLandmark": "Opp. McDonalds",
    "pickupLocality": "East Harlem",
    "pickupCity": "New York",
    "pickupState": "NY",
    "pickupCountry": "USA",
    "pickupPinCode": "10035",
    "pickupLatitude":40.760838,
    "pickupLongitude":-73.96732299999996,
    "pickupAddressTimezone":"America/New_York",
    "pickupNotes": "PickedUp",
    "deliverNotes": "Delivered",
    "clientCode": "Salestap",
    "returnBranch": "New York",
    "returnApartment": "901",
    "returnStreetName": "50 E 78th St",
    "returnLandmark": "Opp. Strand Bookstore",
```

```
    "returnLocality": "Upper East Side",
    "returnCity": "New York",
    "returnState": "NY",
    "returnCountry": "USA",
    "returnPinCode": "10035",
    "returnLatitude": 40.760838,
    "returnLongitude": -73.96732299999996,
    "returnTimezone" : "America/Chicago",
    "returnStartTimeWindow": "2019-07-17T14:24:00.000Z",
    "returnEndTimeWindow": "2019-07-17T14:24:00.000Z",
    "returnAWB" : "435-16685675-R",
    "returnRouteConfigurationName" : "Boston-Houston-R",
    "sendVerificationCd": "Y",
    "pickupVerificationCd": "1112",
    "deliveryVerificationCd": "3333",
    "returnPickupVerificationCd": "3000",
    "returnDeliveryVerificationCd": "1233",
    "parentOrderNo": "GR432U578567",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
      {
        "crateCd": "CR121",
        "crateAmount":100.65,
        "crateType":"case",
        "noOfUnits":10,
        "shipmentlineitems": [
          {
            "itemCd": "IT043",
            "itemName": "Chicken Soup 2X200gm",
            "itemPrice": 500,
            "itemQuantity": 3,
            "itemType": "soup",
            "itemWeight": 10
          },
          {
            "itemCd": "IT030",
            "itemName": "WholeBeanCoffee 6x1kg",
            "itemPrice": 400,
            "itemQuantity": 1,
            "itemType": "coffee",
            "itemWeight": 10
          }
        ]

      }
    ]
  }
]
```


Success Response


```
{
    "status": 200,
    "message": "Order(s) created successfully",
    "data": [
        {
            "index": 0,
            "referenceId": "6a34c7274df0489f97c0f891514b488b",
            "orderNumber": "GR432U5"
        }
    ],
    "hasError": false
}
```

Partial Success Response

```
{
    "status": 207,
    "message": "Order(s) created partially",
    "data": [
        {
            "index": 0,
            "referenceId": "b032f3e9397343ba812f96370b92d592",
            "orderNumber": "GR432U5"
        }
    ],
    "error": [
        {
            "index": 1,
            "orderNo": "GR432U6",
            "errorList": [
                {
                    "key": "deliverBranch",
                    "message": [
                        "Deliver Branch is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Failure Response

```
{
   "status": 409,
   "message": "",
   "moreResultsExists": false,
   "error": [
       {
           "index": 0,
           "orderNo": "GR432U5",
           "errorList": [
               {
                   "key": "returnBranch",
                   "message": [
                       "Return Branch name is mandatory."
                   ]
               }
           ]
       }
   ],
   "hasError": true
}
```

Create new Multi-Leg orders for an End-to-End account in the LogiNext system using this API.

- This API creates a Multi-Leg type of order for an End-to-End account (i.e., an order picked up from the pickup location, brought in at multiple branches midway, and finally delivered to the delivery location) and assigns a unique Reference ID that can be used to identify the order later.
- Call this API along with the provided parameters to push existing orders from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/shipment/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderNo	String	40	Conditional Mandatory	Unique identifier of an Order. This is a multi-digit number assigned to a order to distinguish it from other orders. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-'(hyphen) as the order number. However, ensure that the order no. is unique for the same order type. For example, two Multi-Leg orders should not have the same order number. If not provided, the system will auto-generate an order number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order.
shipmentOrderTypeCd	String	40	Mandatory	Specify 'ALLMILE' to denote the order type code for the order you are creating.
autoAllocateFl	String	50	Optional	Whether the order should be considered for auto-assignment or not. Specify 'Y' to consider the order for auto-assignment (i.e., the order will be automatically assigned to the nearest delivery associate upon creation), 'N' if the order should not be considered for auto-assignment, or 'P' if you want to assign the newly created order to an existing planned trip. Note that selecting 'P' may affect the sequence of previously assigned orders for that trip.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If not provided, the default profile will be considered.
orderState	String	512	Mandatory	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of order whether the order is in forward state or reverse state. Specify 'FORWARD' if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or 'REVERSE' if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
shipmentOrderDt	Date		Mandatory	The date on which you received the order request. Note that the date and time in UTC format. For example - 2016-07-01T11:18:00.000Z.
sendVerificationCd	String	1	Optional	Whether the One Time Password (OTP) verification is required for the order or not. Specify 'Y' to consider OTP verification or 'N' to not consider. If no value is provided, the system considers 'Y' by default.
pickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for pickup verification.
deliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for delivery verification.
returnPickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for return pickup verification.
returnDeliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for return delivery verification.
originBranchName	String	255	Optional	Name of the original branch associated with the order.

destinationBranchName	String	255	Optional	Name of the destination branch associated with the order.
routeConfigurationName	String	255	Optional	Route associated with the order.
deliveryType	String	40	Conditional Mandatory	In certain operations, different skill sets or special delivery requirements are needed. For example, groceries or food items must be separated from toiletries orders, or cake orders cannot be combined with flower orders while delivering. In such cases, if you want to classify orders using the Delivery Type, you can use this field to ensure the orders are assigned to delivery associates configured in the LogiNext system with the required skill sets or delivery types. Note that you must define the Skill Sets in the Fleet Configuration module under Settings before passing it here in the orders. Contact your Account Manager to set these values for you. You can pass multiple Skill Sets in a comma-separated format in this API.
nextBranchName	String		Optional	Name of the next branch that the E2E order will flow through. You only need to pass this if you do not pass a routeConfigurationName.
nextBranchServiceTime	Number		Optional	Time required to deliver the order at the next branch.
nextBranchStartTimeWindow	String		Optional	The opening time of the next branch’s time window. Note that the date and time must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
nextBranchEndTimeWindow	String		Optional	The closing time of the next branch’s time window. Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
serviceTypeCd	String	255	Conditional Mandatory	The type of service that you offer to an order, in terms of how soon the order can be fulfilled. For example, orders with a 'Premium' service type may have shorter SLAs compared to those with a 'Normal' service type. Note that this field is mandatory when creating an 'ALLMILE' order.
distributionCenter	String	255	Mandatory	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in the System Preferences module under Settings module. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
				The total width of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings.

packageBreadth	Double	10,3	Optional	For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in the Order Prioritizing section under the Order Configuration module in Settings. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
shippingCost	Double	10	Optional	The cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If a shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+shippingCost.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
paymentType	String	40	Mandatory	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Pickup (COP) or Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of pickup or delivery. If no value is provided, the system considers 'COD' by default.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver the order partially (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
				Whether the order is returnable or not. Specify ‘Y’ to allow your

returnAllowedFl	String	1	Optional	customers to initiate a return request post delivery, if needed, or ‘N’ to prevent returns. If no value is provided, the system considers ‘Y’ by default.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
pickupServiceTime	Integer	11	Mandatory	The time required to pick up the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the pickup time window.
pickupStartTimeWindow	Date		Mandatory	The opening time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Mandatory	The closing time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Optional	Landmark of the customer’s pickup location. This field is optional if the Customer Profiling property is enabled.

pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Conditional Mandatory	Name of the state in the customer's pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer's pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer's pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer's pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	255	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
deliverServiceTime	Integer	11	Mandatory	The time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
deliverStartTimeWindow	Date		Mandatory	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer's preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2018-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Mandatory	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2018-07-01T11:18:00.000Z.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
deliverAccountName	String	255	Conditional Mandatory	Name of the delivery customer. This field is optional if the Customer Profiling property is enabled.

deliverEmail	String	100	Optional	Email ID delivery of the customer.
deliverPhoneNumber	String	255	Optional	Contact number of the delivery customer.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
deliverAddressId	String	255	Mandatory	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer’s delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String	50	Conditional Mandatory	Name of the state in the customer’s delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer’s delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer’s delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer’s delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer’s delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer’s delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
returnAllowedFl	String	50	Optional	Whether the order is returnable or not. This will let your customer initiate a return order request post delivery, if needed. Specify ‘Y’ to allow return, or ‘N’ to prevent return requests for this order.
				Name of branch where the order should be returned, if needed.

returnBranch	String	255	Conditional Mandatory	This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnAddressId	String	255	Optional	Identifier assigned to a return customer’s address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer’s return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer’s return address.
returnLandmark	String	512	Optional	Landmark of the customer’s return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer’s return address.
returnCity	String	512	Optional	Name of the city in the customer’s return address.
returnState	String	50	Optional	Name of the state in the customer’s return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer’s return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnRouteConfigurationName	String	255	Optional	Route associated with the return order.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
returnTimezone	String		Optional	Timezone of the customer’s return address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
clientCode	String	32	Optional	Name of the shipper’s company associated with the order. Pass the company name of the shipper’s account if you want to create an

				order on behalf of one of your shippers.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as ‘Related Orders’. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z’, 'A to Z’, '0 to 9’, ’_’(underscore), and ’-’(hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Within this parameter, enter the crate details of the order, including the crate code, amount, type, number of items, and other relevant details. In the case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
				Width of the crate. The unit of

shipmentCrateMappings.crateBreadth	Double	10,3	Optional	measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item.
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item.
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item.
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item.

END-TO-END ACCOUNT: CREATE DELIVERY ONLY

Sample Request

```
[
 {
   "orderNo": "GR432U5",
   "awbNumber": "435-16685675",
   "shipmentOrderTypeCd": "LM",
   "orderState": "FORWARD",
   "autoAllocateFl": "N",
   "autoAllocateProfileName":"ETAProfile",
   "shipmentOrderDt": "2019-07-15T10:30:00.000Z",
   "distributionCenter": "Down Town Chicago",
   "serviceTypeCd": "Economy",
   "packageWeight":"10",
   "packageVolume": "4500",
   "paymentType": "Prepaid",
   "originalOrderValue": "500",
   "orderDiscount": "10",
   "packageValue":"450",
   "insuranceRequiredFl": "Y",
   "insuredValue": "450",
   "signatureRequiredFl": "Y",
   "shippingCost":"50",
   "numberOfItems": 1,
   "packagingRequiredFl": "Y",
```

```
    "partialDeliveryAllowedFl": "Y",
    "cancellationAllowedFl": "N",
    "deliverBranch":"Boston Main Hub",
    "deliverServiceTime": "20",
    "deliverEndTimeWindow": "2019-07-18T10:31:00.000Z",
    "deliverStartTimeWindow": "2019-07-16T10:31:00.000Z",
    "deliveryType": "Groceries, Reefer",
    "deliveryLocationType":"Home",
    "deliverEmail":"m.richardson@testmail.com",
    "deliverPhoneNumber":"9891234567",
    "deliverWhatsappOptin":"Y",
    "deliverAccountCode": "Matt001",
    "deliverAddressId": "home",
    "deliverAccountName": "Mathew Richardson",
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Towm Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude":41.882702,
    "deliverLongitude":-87.619392,
    "deliverAddressTimezone":"America/Chicago",
    "deliverNotes": "Leave it with the neighbour",
    "clientCode": "Salestap",
    "sendVerificationCd": "Y",
    "pickupVerificationCd": "1112",
    "deliveryVerificationCd": "3333",
    "returnPickupVerificationCd": "3000",
    "returnDeliveryVerificationCd": "1233",
    "parentOrderNo": "GR432U578569",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
      {
        "crateCd": "CR121",
        "crateAmount":100.65,
        "crateType":"case",
        "noOfUnits":10,
        "shipmentlineitems": [
          {
            "itemCd": "IT043",
            "itemName": "Chicken Soup 2X200gm",
            "itemPrice": 500,
            "itemQuantity": 3,
            "itemType": "soup",
            "itemWeight": 10
          },
          {
            "itemCd": "IT030",
            "itemName": "WholeBeanCoffee 6x1kg",
            "itemPrice": 400,
            "itemQuantity": 1,
            "itemType": "coffee",
            "itemWeight": 10
          }
        ]

      }
    ]
  }
]
```


Success Response

```
{
    "status": 200,
    "message": "Order(s) created successfully",
    "data": [
        {
            "index": 0,
            "referenceId": "6a34c7274df0489f97c0f891514b488b",
            "orderNumber": "GR432U5"
        }
    ],
    "hasError": false
}
```


Partial Success Response


```
{
    "status": 207,
    "message": "Order(s) created partially",
    "data": [
        {
            "index": 0,
            "referenceId": "b032f3e9397343ba812f96370b92d592",
            "orderNumber": "GR432U5"
        }
    ],
    "error": [
        {
            "index": 1,
            "orderNo": "GR432U6"
            "errorList": [
                {
                    "key": "deliverBranch",
                    "message": [
                        "Deliver Branch is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```


Failure Response


```
{
   "status": 409,
   "message": "",
   "moreResultsExists": false,
   "error": [
       {
           "index": 0,
           "orderNo": "GR432U5",
           "errorList": [
               {
                   "key": "returnBranch",
                   "message": [
                       "Deliver Branch name is mandatory."
                   ]
               }
           ]
       }
```

```
    ],
    "hasError": true
}
```

Create new Delivery orders for an End-to-End account in the LogiNext system using this API.

- This API creates a Delivery type of order for an End-to-End account (i.e., an order that is picked up from the final branch in its journey and delivered to the delivery location) and assigns a unique Reference ID that can be used to identify the order later.
- Call this API along with the provided parameters to push existing delivery orders from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/shipment/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderNo	String	40	Conditional Mandatory	Unique identifier of an Order. This is a multi-digit number assigned to a order to distinguish it from other orders. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-'(hyphen) as the order number. However, ensure that the order no. is unique for the same order type. For example, two Delivery orders should not have the same order number. If not provided, the system will auto-generate an order number.
awbNumber	String	100	Optional	Air Waybill or AWB number associated with an order.
shipmentOrderTypeCd	String	40	Mandatory	Specify 'LM' (i.e., Last Mile) to denote the order type code for the order you are creating.
autoAllocateFl	String	50	Optional	Whether the order should be considered for auto-assignment or not. Specify 'Y' to consider the order for auto-assignment (i.e., the order will be automatically assigned to the nearest delivery associate upon creation), 'N' if the order should not be considered for auto-assignment, or 'P' if you want to assign the newly created order to an existing planned trip. Note that selecting 'P' may affect the sequence of previously assigned orders for that trip.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If not provided, the default profile will be considered.
sendVerificationCd	String	1	Optional	Whether the One Time Password (OTP) verification is required for the order or not. Specify 'Y' to consider OTP verification or 'N' to not consider. If no value is provided, the system considers 'Y' by default.
pickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for pickup verification.
deliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for delivery verification.
returnPickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for return pickup verification.
returnDeliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for return delivery verification.
				State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of order whether the order is in forward state or reverse state. Specify 'FORWARD' if the order is in a forward state (i.e., the

orderState	String	512	Mandatory	orders are either to be picked up from the merchants or delivered to the customers) or ‘REVERSE’ if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
shipmentOrderDt	Date		Mandatory	The date on which you received the delivery order request. Note that the date and time in UTC format. For example - 2017-07-15T10:30:00.000Z.
serviceTypeCd	String	255	Conditional Mandatory	The type of service that you offer to an order, in terms of how soon the order can be fulfilled. For example, orders with a 'Premium' service type may have shorter SLAs compared to those with a 'Normal' service type. Note that this field is mandatory when creating an 'ALLMILE' order.
distributionCenter	String	255	Mandatory	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in the Order Prioritizing section under the Order Configuration module in Settings. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.

insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
shippingCost	Double	10	Optional	The cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If a shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+shippingCost.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of delivery. If no value is provided, the system considers 'COD' by default.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver the order partially (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
returnAllowedFl	String	1	Optional	Whether the order is returnable or not. Specify ‘Y’ to allow your customers to initiate a return request post delivery, if needed, or ‘N’ to prevent returns. If no value is provided, the system considers ‘Y’ by default.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
deliverServiceTime	Integer	11	Optional	The time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC

				format. For example - 2016-07-01T11:18:00.000Z.
deliveryType	String	40	Optional	In certain operations, different skill sets or special delivery requirements are needed. For example, groceries or food items must be separated from toiletries orders, or cake orders cannot be combined with flower orders while delivering. In such cases, if you want to classify orders using the Delivery Type, you can use this field to ensure the orders are assigned to delivery associates configured in the LogiNext system with the required skill sets or delivery types. Note that you must define the Skill Sets in the Fleet Configuration module under Settings before passing it here in the orders. Contact your Account Manager to set these values for you. You can pass multiple Skill Sets in a comma-separated format in this API.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
deliverAccountName	String	255	Conditional Mandatory	Name of the delivery customer. This field is optional if the Customer Profiling property is enabled.
deliverEmail	String	100	Optional	Email ID of the customer.
deliverPhoneNumber	String	255	Optional	Contact number of the customer. This field is optional if the Customer Profiling property is enabled.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String	50	Conditional Mandatory	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.

deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer's delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer's delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer's delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
clientCode	String	32	Optional	Name of the shipper's company associated with the order. Pass the company name of the shipper's account if you want to create an order on behalf of one of your shippers.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as 'Related Orders'. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-' (hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Within this parameter, enter the crate details of the order, including the crate code, amount, type, number of items, and other relevant details. In the case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Mandatory	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Mandatory	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Mandatory	Total number of crates in the order.

shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item.
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item.
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item.
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item.

END-TO-END ACCOUNT: CREATE PICK UP ONLY

Sample Request

```
[
  {
    "orderNo": "GR432U5",
    "awbNumber": "435-16685675",
    "shipmentOrderTypeCd": "FM",
    "orderState": "FORWARD",
    "autoAllocateFl": "N",
    "autoAllocateProfileName":"ETAProfile",
    "shipmentOrderDt": "2019-07-15T10:30:00.000Z",
    "distributionCenter": "Down Town Chicago",
    "deliveryType": "Groceries",
    "serviceTypeCd": "Economy",
    "packageWeight":"10",
    "packageVolume": "4500",
    "paymentType": "Prepaid",
    "originalOrderValue": "500",
    "orderDiscount": "10",
    "packageValue":"450",
    "insuranceRequiredFl": "Y",
    "insuredValue": "450",
    "signatureRequiredFl": "Y",
    "shippingCost":"50",
    "numberOfItems": 1,
    "packagingRequiredFl": "Y",
    "partialDeliveryAllowedFl": "Y",
    "cancellationAllowedFl": "N",
    "pickupBranch": "Down Town Chicago",
    "pickupServiceTime": "50",
    "pickupStartTimeWindow": "2019-07-16T14:24:00.000Z",
    "pickupEndTimeWindow": "2019-07-17T14:24:00.000Z",
    "pickupEmail":"james.w@ablogs.com",
    "pickupPhoneNumber": "5163063377",
    "pickupWhatsappOptin":"Y",
    "pickupAccountCode": "jim001",
    "pickupAddressId": "Home",
    "pickupAccountName": "James Walker",
    "pickupApartment": "901",
    "pickupStreetName": "2142 3rd Ave",
    "pickupLandmark": "Opp. McDonalds",
    "pickupLocality": "East Harlem",
    "pickupCity": "New York",
    "pickupState": "NY",
    "pickupCountry": "USA",
    "pickupPinCode": "10035",
    "pickupLatitude":40.760838,
    "pickupLongitude":-73.96732299999996,
    "pickupAddressTimezone":"America/New_York",
    "pickupNotes": "PickedUp",
    "clientCode": "Salestap",
    "sendVerificationCd": "Y",
    "pickupVerificationCd": "1112",
    "deliveryVerificationCd": "3333",
    "returnPickupVerificationCd": "3000",
    "returnDeliveryVerificationCd": "1233",
    "parentOrderNo": "GR432U578569",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
      {
        "crateCd": "CR121",
        "crateAmount":100.65,
        "crateType":"case",
        "noOfUnits":10,
        "shipmentlineitems": [
          {
            "itemCd": "IT043",
            "itemName": "Chicken Soup 2X200gm",
```

```
            "itemPrice": 500,
            "itemQuantity": 3,
            "itemType": "soup",
            "itemWeight": 10
          },
          {
            "itemCd": "IT030",
            "itemName": "WholeBeanCoffee 6x1kg",
            "itemPrice": 400,
            "itemQuantity": 1,
            "itemType": "coffee",
            "itemWeight": 10
          }
        ]

      }
    ]
  }
]
```


Success Response


```
{
    "status": 200,
    "message": "Order(s) created successfully",
    "data": [
        {
            "index": 0,
            "referenceId": "6a34c7274df0489f97c0f891514b488b",
            "orderNumber": "GR432U5"
        }
    ],
    "hasError": false
}
```


Partial Success Response


```
{
    "status": 207,
    "message": "Order(s) created partially",
    "data": [
        {
            "index": 0,
            "referenceId": "b032f3e9397343ba812f96370b92d592",
            "orderNumber": "GR432U5"
        }
    ],
    "error": [
        {
            "index": 1,
            "orderNo": "GR432U6"
            "errorList": [
                {
                    "key": "deliverBranch",
                    "message": [
                        "Deliver Branch is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
```

```
}
```

Failure Response

```
{
  "status": 409,
  "message": "",
  "moreResultsExists": false,
  "error": [
      {
          "index": 0,
          "orderNo": "GR432U5",
          "errorList": [
              {
                  "key": "returnBranch",
                  "message": [
                      "Return Branch name is mandatory."
                  ]
              }
          ]
      }
  ],
  "hasError": true
}
```

Create new Pickup orders for an End-to-End account in the LogiNext system using this API.

- This API creates a Pickup type of order for an End-to-End account (i.e., an order picked up from the pickup location and delivered to the first branch in its journey) and assigns a unique Reference ID that can be used to identify the order later.
- Call this API along with the provided parameters to push existing pickup orders from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/shipment/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderNo	String	40	Conditional Mandatory	Unique identifier of an Order. This is a multi-digit number assigned to a order to distinguish it from other orders. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-'(hyphen) as the order number. However, ensure that the order no. is unique for the same order type. For example, two Pickup orders should not have the same order number. If not provided, the system will auto-generate an order number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order.
shipmentOrderTypeCd	String	40	Mandatory	Specify 'FM' (i.e., First Mile) to denote the order type code for the order you are creating.
autoAllocateFl	String	50	Optional	Whether the order should be considered for auto-assignment or not. Specify 'Y' to consider the order for auto-assignment (i.e., the order will be automatically assigned to the nearest delivery associate upon creation), 'N' if the order should not be considered for auto-assignment, or 'P' if you want to assign the newly created order to an existing planned trip. Note that selecting 'P' may affect the sequence

				of previously assigned orders for that trip.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If not provided, the default profile will be considered.
sendVerificationCd	String	1	Optional	Whether the One Time Password (OTP) verification is required for the order or not. Specify ‘Y’ to consider OTP verification or ‘N’ to not consider. If no value is provided, the system considers ‘Y’ by default.
pickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for pickup verification.
deliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for delivery verification.
returnPickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for return pickup verification.
returnDeliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for return delivery verification.
orderState	String	512	Mandatory	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of order whether the order is in forward state or reverse state. Specify ‘FORWARD’ if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or ‘REVERSE’ if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
shipmentOrderDt	Date		Mandatory	The date on which you received the pickup order request. Note that the date and time in UTC format. For example - 2017-07-15T10:30:00.000Z.
serviceTypeCd	String	255	Conditional Mandatory	The type of service that you offer to an order, in terms of how soon the order can be fulfilled. For example, orders with a 'Premium' service type may have shorter SLAs compared to those with a 'Normal' service type. Note that this field is mandatory when creating an 'ALLMILE' order.
distributionCenter	String	255	Mandatory	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the

				imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in the Order Prioritizing section under the Order Configuration module in Settings. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
shippingCost	Double	10	Optional	The cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If a shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+shippingCost.
paymentType	String	40	Mandatory	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Pickup (COP)’ if the delivery associate needs to collect cash at the time of pickup. If no value is provided, the system considers 'COP' by default.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver the order partially (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
returnAllowedFl	String	1	Optional	Whether the order is returnable or not. Specify ‘Y’ to allow your customers to initiate a return request post delivery, if needed, or ‘N’ to prevent returns. If no value is provided, the system considers ‘Y’ by default.

cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
pickupBranch	String	255	Mandatory	For pickup type of orders, this field specifies the branch where the delivery associate will deliver the pickup order.
pickupServiceTime	Integer	11	Mandatory	The time required to pick up the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the pickup time window.
pickupStartTimeWindow	Date		Mandatory	The opening time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Mandatory	The closing time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Optional	Landmark of the customer’s pickup location. This field is optional if the Customer Profiling property is enabled.

pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Conditional Mandatory	Name of the state in the customer's pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer's pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer's pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer's pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	255	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnAddressId	String	255	Optional	Identifier assigned to a return customer's address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer's return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer's return address.
returnLandmark	String	512	Optional	Landmark of the customer's return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer's return address.
returnCity	String	512	Optional	Name of the city in the customer's return address.
returnState	String	50	Optional	Name of the state in the customer's return address. This should be as per the State Codes available in the LogiNext system for the selected country.

returnCountry	String	100	Optional	Name of the country in the customer's return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
returnTimezone	String		Optional	Timezone of the customer's return address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
returnAWB	String	255	Optional	Air Waybill or AWB number associated with a return order request. If not provided, the system will consider the existing AWB as the return AWB.
clientCode	String	32	Optional	Name of the shipper's company associated with the order. Pass the company name of the shipper's account if you want to create an order on behalf of one of your shippers.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as 'Related Orders'. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-' (hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Within this parameter, enter the crate details of the order, including the crate code, amount, type, number of items, and other relevant details. In the case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid/semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order.
				Volume of the crate. The unit of

shipmentCrateMappings.crateVolume	Double	10,3	Optional	measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item.
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item.
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item.
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item.

END-TO-END ACCOUNT: CREATE POINT-TO-POINT

Sample Request

```
[
  {
    "orderNo": "ORD876543456",
    "awbNumber": "AWS-125432",
    "shipmentOrderTypeCd": "LM",
    "orderState": "FORWARD",
    "autoAllocateFl": "Y",
    "autpAllocateProfileName":"ETAProfile",
    "shipmentOrderDt": "2020-02-19T09:30:00.000Z",
    "distributionCenter": "Middle Mile Main Hub",
    "deliveryType": "Groceries",
    "serviceTypeCd": "Economy",
    "packageWeight": "10.5",
    "packageVolume": "450.12",
    "paymentType": "COD",
    "originalOrderValue": "500",
    "orderDiscount": "10",
    "packageValue":"450",
    "insuranceRequiredFl": "Y",
    "insuredValue": "450",
    "signatureRequiredFl": "Y",
    "shippingCost":"50",
    "numberOfItems": 1,
    "packagingRequiredFl": "Y",
    "partialDeliveryAllowedFl": "N",
    "cancellationAllowedFl": "N",
    "deliverServiceTime": "20",
    "deliverEndTimeWindow": "2016-07-18T10:31:00.000Z",
    "deliverStartTimeWindow": "2016-07-16T10:31:00.000Z",
    "deliveryLocationType":"Home",
    "deliverEmail":"m.richardson@testmail.com",
    "deliverPhoneNumber":"9891234567",
    "deliverWhatsappOptin":"Y",
    "deliverAccountCode": "Matt001",
    "deliverAddressId": "home",
    "deliverAccountName": "Mathew Richardson",
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Town Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude":41.882702,
    "deliverLongitude":-87.619392,
    "deliverAddressTimezone":"America/Chicago",
    "deliverNotes": "Delivered",
    "pickupServiceTime": "50",
    "pickupStartTimeWindow": "2016-07-16T14:24:00.000Z",
    "pickupEndTimeWindow": "2016-07-17T14:24:00.000Z",
    "pickupEmail":"james.w@ablogs.com",
    "pickupPhoneNumber": "5163063377",
    "pickupWhatsappOptin":"Y",
    "pickupAccountCode": "jim001",
    "pickupAddressId": "Home",
    "pickupAccountName": "James Walker",
    "pickupApartment": "901",
    "pickupStreetName": "2142 3rd Ave",
    "pickupLandmark": "Opp. McDonalds",
    "pickupLocality": "East Harlem",
    "pickupCity": "New York",
    "pickupState": "NY",
    "pickupCountry": "USA",
    "pickupPinCode": "10035",
```

```
    "pickupLatitude":40.760838,
    "pickupLongitude":-73.96732299999996,
    "pickupAddressTimezone":"America/New_York",
    "pickupNotes": "PickedUp",
    "deliverNotes": "Delivered",
    "clientCode": "Salestap",
    "parentOrderNo": "GR432U578569",
    "generateParentOrderNo": "N",
    "shipmentCrateMappings": [
      {
        "crateCd": "CR121",
        "crateAmount":100.65,
        "crateType":"case",
        "noOfUnits":10,
        "shipmentlineitems": [
          {
            "itemCd": "IT043",
            "itemName": "Chicken Soup 2X200gm",
            "itemPrice": 500,
            "itemQuantity": 3,
            "itemType": "soup",
            "itemWeight": 10
          },
          {
            "itemCd": "IT030",
            "itemName": "WholeBeanCoffee 6x1kg",
            "itemPrice": 400,
            "itemQuantity": 1,
            "itemType": "coffee",
            "itemWeight": 10
          }
        ]

      }
    ]

  }
]
```


Success Response


```
{
    "status": 200,
    "message": "Order(s) created successfully",
    "data": [
        {
            "index": 0,
            "referenceId": "6a34c7274df0489f97c0f891514b488b",
            "orderNumber": "ORD876543456"
        }
    ],
    "hasError": false
}
```


Partial Success Response


```
{
    "status": 207,
    "message": "Order(s) created partially",
    "data": [
        {
            "index": 0,
```

```
            "referenceId": "b032f3e9397343ba812f96370b92d592",
            "orderNumber": "ORD876543456"
        }
    ],
    "error": [
        {
            "index": 1,
            "orderNo": "ORD876543457"
            "errorList": [
                {
                    "key": "returnBranch",
                    "message": [
                        "Return Branch name is invalid"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```


Failure Response


```
{
   "status": 409,
   "message": "",
   "moreResultsExists": false,
   "error": [
       {
           "index": 0,
           "orderNo": "ORD876543456",
           "errorList": [
               {
                   "key": "returnBranch",
                   "message": [
                       "Return Branch name is mandatory."
                   ]
               }
           ]
       }
   ],
   "hasError": true
}
```


Create new Point-to-Point orders for an End-to-End account in the LogiNext system using this API.

- This API creates a Point-to-Point type of order for an End-to-End account (i.e., an order picked up from the pickup location and delivered to the delivery location, without stops at any intermediate branches) and assigns a unique Reference ID that can be used to identify the order later.
- Call this API along with the provided parameters to push existing point to point orders from your current system to LogiNext.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/shipment/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description

orderNo	String	40	Conditional Mandatory	Unique identifier of an Order. This is a multi-digit number assigned to a order to distinguish it from other orders. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-' (hyphen) as the order number. However, ensure that the order no. is unique for the same order type. For example, two Point-to-Point orders should not have the same order number. If not provided, the system will auto-generate an order number.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order.
shipmentOrderTypeCd	String	40	Mandatory	Specify 'LM' (i.e., Last Mile) to denote the order type code for the order you are creating.
autoAllocateFl	String	50	Optional	Whether the order should be considered for auto-assignment or not. Specify 'Y' to consider the order for auto-assignment (i.e., the order will be automatically assigned to the nearest delivery associate upon creation), 'N' if the order should not be considered for auto-assignment, or 'P' if you want to assign the newly created order to an existing planned trip. Note that selecting 'P' may affect the sequence of previously assigned orders for that trip.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If not provided, the default profile will be considered.
orderState	String	512	Mandatory	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of order whether the order is in forward state or reverse state. Specify 'FORWARD' if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or 'REVERSE' if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
shipmentOrderDt	Date		Mandatory	The date on which you received the order. Note that the date and time in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliveryType	String	40	Conditional Mandatory	In certain operations, different skill sets or special delivery requirements are needed. For example, groceries or food items must be separated from toiletries orders, or cake orders cannot be combined with flower orders while delivering. In such cases, if you want to classify orders using the Delivery Type, you can use this field to ensure the orders are assigned to delivery associates configured in the LogiNext system with the required skill sets or delivery types. Note that you must define the Skill Sets in the Fleet Configuration module under Settings before passing it here in the orders. Contact your Account Manager to set these values for you. You can pass multiple Skill Sets in a comma-separated format in this API.
serviceTypeCd	String	255	Conditional Mandatory	The type of service that you offer to an order, in terms of how soon the order can be fulfilled. For example, orders with a 'Premium' service type may have shorter SLAs compared to those with a 'Normal' service type. Note that this field is mandatory when creating an 'ALLMILE' order.
distributionCenter	String	255	Mandatory	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.

packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in the Order Prioritizing section under the Order Configuration module in Settings. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
shippingCost	Double	10	Optional	The cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges. If a shipping cost is provided, the total amount to be collected from the customer for the order will be packageValue+shippingCost.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of delivery. If no value is provided, the system considers 'COD' by default.
numberOfItems	Integer	20	Optional	The total number of items in the order.

packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver the order partially (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
returnAllowedFl	String	1	Optional	Whether the order is returnable or not. Specify ‘Y’ to allow your customers to initiate a return request post delivery, if needed, or ‘N’ to prevent returns. If no value is provided, the system considers ‘Y’ by default.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
pickupServiceTime	Integer	11	Mandatory	The time required to pick up the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the pickup time window.
pickupStartTimeWindow	Date		Mandatory	The opening time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Optional	The closing time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2016-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.

pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Optional	Landmark of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Conditional Mandatory	Name of the state in the customer's pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer's pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer's pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer's pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer's pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	255	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
deliverServiceTime	Integer	11	Optional	The time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer's preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
				Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as

deliverAccountCode	String	255	Mandatory	their Customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
deliverAccountName	String	255	Conditional Mandatory	Name of the delivery customer. This field is optional if the Customer Profiling property is enabled.
deliverEmail	String	100	Optional	Email ID of the delivery customer.
deliverPhoneNumber	String	255	Optional	Contact number of the delivery customer.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String	50	Conditional Mandatory	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer's delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer's delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer's delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
				Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate

deliverNotes	String	255	Optional	when they view this order in the LogiNext Driver App at the time of delivery.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnAddressId	String	255	Optional	Identifier assigned to a return customer's address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer's return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer's return address.
returnLandmark	String	512	Optional	Landmark of the customer's return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer's return address.
returnCity	String	512	Optional	Name of the city in the customer's return address.
returnState	String	50	Optional	Name of the state in the customer's return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer's return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
returnTimezone	String		Optional	Timezone of the customer's return address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
returnAWB	String	255	Optional	Air Waybill or AWB number associated with a return order request. If not provided, the system will consider the existing AWB as the return AWB.
clientCode	String	32	Optional	Name of the shipper's company associated with the order. Pass the company name of the shipper's account if you want to create an order on behalf of one of your shippers.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as 'Related Orders'. This is especially useful for multiple orders placed by the same customer. You can enter any alphanumeric value, including 'a to

				z’, 'A to Z’, '0 to 9’, ’_’(underscore), and ’-’(hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
shipmentCrateMappings	Array of objects		Optional	Within this parameter, enter the crate details of the order, including the crate code, amount, type, number of items, and other relevant details. In the case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrateMappings.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
shipmentCrateMappings.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrateMappings.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid/semi-liquid items during transportation.
shipmentCrateMappings.noOfUnits	Integer	10	Optional	Total number of crates in the order.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
				Height of the crate. The unit of measurement will be the same as specified in the System Preferences module under

shipmentCrateMappings.crateHeight	Double	10,3	Optional	Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
shipmentCrateMappings.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrateMappings.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrateMappings.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrateMappings.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrateMappings.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item.
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item.
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item.
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item.

END-TO-END ACCOUNT: CREATE RECURRING

Sample Request

```
{
"orderTemplateDetails": {
"orderTemplateNumber": "FM_QWA",
"awbNumber": "435-16685675",
"shipmentOrderTypeCd": "ALLMILE",
"sendVerificationCd": "Y",
"pickupVerificationCd": "1112",
"deliveryVerificationCd": "3333",
"returnPickupVerificationCd": "3000",
"returnDeliveryVerificationCd": "1233",
"orderState": "FORWARD",
"autoAllocateProfileName":"ETAProfile",
"shipmentOrderDt": "2016-07-15T10:30:00.000Z",
"distributionCenter": "Down Town Chicago",
"originBranchName" :"Houston",
"destinationBranchName" : "Boston",
"routeConfigurationName": "Houston-Boston",
"nextBranchName":"Cupertino",
"nextBranchServiceTime": 5,
"nextBranchStartTimeWindow" : "2016-07-15T10:30:00.000Z",
"nextBranchEndTimeWindow": "2016-07-15T10:30:00.000Z",
"deliveryType": "Groceries",
"serviceTypeCd": "Economy",
"packageWeight":"10",
"packageVolume": "4500",
"paymentType": "Prepaid",
"originalOrderValue": "500",
"orderDiscount": "10",
"packageValue":"450",
"insuranceRequiredFl": "Y",
"insuredValue": "450",
"signatureRequiredFl": "Y",
```

```
"numberOfItems": 1,
"packagingRequiredFl": "Y",
"partialDeliveryAllowedFl": "Y",
"cancellationAllowedFl": "N",
"deliverServiceTime": "20",
"deliverEndTimeWindow": "2016-07-18T10:31:00.000Z",
"deliverStartTimeWindow": "2016-07-16T10:31:00.000Z",
"deliveryLocationType":"Home",
"deliverEmail":"m.richardson@testmail.com",
"deliverPhoneNumber":"9891234567",
"deliverWhatsappOptin":"Y",
"deliverAccountCode": "Matt001",
"deliverAddressId": "home",
"deliverAccountName": "Mathew Richardson",
"deliverApartment": "201",
"deliverStreetName": "E Randolph St",
"deliverLandmark": "Opp. Chiptole",
"deliverLocality": "Down Town Chicago",
"deliverCity": "Chicago",
"deliverState": "IL",
"deliverCountry": "USA",
"deliverPinCode": "60602",
"deliverLatitude":41.882702,
"deliverLongitude":-87.619392,
"deliverAddressTimezone":"America/Chicago",
"deliverBranch": "East Manhattan",
"pickupBranch":"East Manhattan",
"pickupServiceTime": "50",
"pickupStartTimeWindow": "2016-07-16T14:24:00.000Z",
"pickupEndTimeWindow": "2016-07-17T14:24:00.000Z",
"pickupEmail":"james.w@ablogs.com",
"pickupPhoneNumber": "5163063377",
"pickupWhatsappOptin":"Y",
"pickupAccountCode": "jim001",
"pickupAddressId": "Home",
"pickupAccountName": "James Walker",
"pickupApartment": "901",
"pickupStreetName": "2142 3rd Ave",
"pickupLandmark": "Opp. McDonalds",
"pickupLocality": "East Harlem",
"pickupCity": "New York",
"pickupState": "NY",
"pickupCountry": "USA",
"pickupPinCode": "10035",
"pickupLatitude":40.760838,
"pickupLongitude":-73.96732299999996,
"pickupAddressTimezone":"America/New_York",
"pickupNotes": "PickedUp",
"deliverNotes": "Delivered",
"clientCode": "Salestap",
"shipmentCrateMappings": []
}
,
"schedulerDetails": {
"startDate": "2019-09-23T11:00:00.000Z",
"endDate": "2019-09-25T15:00:00.000Z",
"frequency": "DAILY",
"weekDays":"Tuesday,Thursday",
"interval": 0,
"numberOfOccurrences": 1
}
}
```


Success Response

```
{
    "status": 200,
    "message": "Order template created successfully",
    "moreResultsExists": false,
    "data": {
        "orderTemplateReferenceId": "ed7cfd8b400b488babebb68d33f1ddbb",
        "orderTemplateNumber": "FM_QWA"
    },
    "hasError": false
}
```

Failure Response

```
{
    "status": 409,
    "message": "Order template creation failed",
    "moreResultsExists": false,
    "error": [
        {
            "errorList": [
                {
                    "key": "orderTemplateNumber",
                    "message": [
                        "Order template number already exists"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Create new Recurring orders for an End-to-End account in the LogiNext system using this API.

- This API creates a Recurring type of order for an End-to-End account. It is suitable for a wide range of operations, including subscription-based services or scenarios where the same order needs to be created multiple times on different dates. You can use this API to automate the creation of recurring orders based on a defined schedule and frequency.
- The API accepts following two objects in its request body:
  - 'orderTemplateDetails': Contains the details of the orders to be created.
  - 'schedulerDetails': Defines the frequency and duration of the recurring orders.
- For example, if an API request is made on a Tuesday with the first order scheduled for Wednesday, the first order for that week is created immediately (i.e., on Tuesday). The orders for subsequent weeks (i.e., in this case, for every Wednesday) will be automatically generated on every Sunday. Note that recurring orders for subsequent weeks are always created on respective Sundays.

API TYPE

- Tier 1 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/shipment/template/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderTemplateNumber	String	100	Mandatory	Unique identifier associated with the order template you are creating. Note that the orders generated using this template will have the date and time of creation appended to the template number which is provided here.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order.

shipmentOrderTypeCd	String	40	Mandatory	Specify the order type code such as ‘FM’, ‘LM’, or ‘ALLMILE’ for the order you are creating. This API lets you create First Mile, Last Mile, or ALLMILE orders. 'ALLMILE' orders involve multiple milestones (i.e., legs of movement).
autoAllocateFl	String	50	Optional	Whether the order should be considered for auto-assignment or not. Specify 'Y' to consider the order for auto-assignment (i.e., the order will be automatically assigned to the nearest delivery associate upon creation), ‘N’ if the order should not be considered for auto-assignment, or ‘P’ if you want to assign the newly created order to an existing planned trip. Note that selecting 'P' may affect the sequence of previously assigned orders for that trip.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If not provided, the default profile will be considered.
orderState	String	512	Mandatory	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of order whether the order is in forward state or reverse state. Specify ‘FORWARD’ if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or ‘REVERSE’ if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
shipmentOrderDt	Date		Mandatory	The date on which you received the order request. Note that the date and time in UTC format. For example - 2016-07-01T11:18:00.000Z.
sendVerificationCd	String	1	Optional	Whether the One Time Password (OTP) verification is required for the order or not. Specify ‘Y’ to consider OTP verification or ‘N’ to not consider. If no value is provided, the system considers ‘Y’ by default.
pickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for pickup verification.
deliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for delivery verification.
returnPickupVerificationCd	Integer	4	Optional	One Time Password (OTP) for return pickup verification.
returnDeliveryVerificationCd	Integer	4	Optional	One Time Password (OTP) for return delivery verification.
originBranchName	String	255	Optional	Name of the original branch associated with the order.
destinationBranchName	String	255	Optional	Name of the destination branch associated with the order.
routeConfigurationName	String	255	Optional	Route associated with the order.
deliveryType	String	40	Conditional Mandatory	In certain operations, different skill sets or special delivery requirements are needed. For example, groceries or food items must be separated from toiletries orders, or cake orders cannot be combined with flower orders while delivering. In such cases, if you want to classify orders using the Delivery Type, you can use this field to ensure the orders are assigned to delivery associates configured in the LogiNext system with the required skill sets or delivery types. Note that you must define the Skill Sets in the Fleet Configuration module under Settings before passing it here in the orders. Contact your Account Manager to set these values for you. You can pass multiple Skill Sets in a comma-separated format in this API.
serviceTypeCd	String	255	Conditional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled. For example, orders with a 'Premium' service type may have shorter SLAs compared to those with a 'Normal'

			Mandatory	service type. Note that this field is mandatory when creating an 'ALLMILE' order.
distributionCenter	String	255	Mandatory	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
packageVolume	Double	10,3	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in the Order Prioritizing section under the Order Configuration module in Settings. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if

				you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
numberOfItems	Integer	20	Optional	The total number of items in the order.
packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order, or ‘N’ if not.
paymentType	String	40	Mandatory	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Pickup (COP) or Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of pickup/delivery. If no value is provided, the system considers 'COD' by default.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver the order partially (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
returnAllowedFl	String	1	Optional	Whether the order is returnable or not. Specify ‘Y’ to allow your customers to initiate a return request post delivery, if needed, or ‘N’ to prevent returns. If no value is provided, the system considers ‘Y’ by default.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
pickupServiceTime	Integer	11	Mandatory	The time required to pick up the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the pickup time window.
pickupStartTimeWindow	Date		Mandatory	The opening time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Mandatory	The closing time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2016-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Mandatory	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
pickupAccountName	String	255	Conditional Mandatory	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.

pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupLandmark	String	512	Optional	Landmark of the customer’s pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupCity	String	512	Conditional Mandatory	Name of the city in the customer’s pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Conditional Mandatory	Name of the state in the customer’s pickup address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
pickupCountry	String	100	Conditional Mandatory	Name of the country in the customer’s pickup address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.
pickupPinCode	String	12	Conditional Mandatory	Pin code of the customer’s pickup location. This field is optional if the Customer Profiling property is enabled.
pickupLatitude	Double		Optional	Latitude coordinates of the customer’s pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer’s pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer’s pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	255	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
deliverServiceTime	Integer	11	Mandatory	The time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading. When the orders are planned, the service time required for the orders is also considered in the delivery time window.
				The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer’s

deliverStartTimeWindow	Date		Mandatory	preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2018-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Mandatory	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2018-07-01T11:18:00.000Z.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
deliverAccountName	String	255	Conditional Mandatory	Name of the delivery customer. This field is optional if the Customer Profiling property is enabled.
deliverEmail	String	100	Optional	Email ID delivery of the customer.
deliverPhoneNumber	String	255	Optional	Contact number of the delivery customer.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
deliverAddressId	String	255	Mandatory	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Conditional Mandatory	Name of the city in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverState	String	50	Conditional Mandatory	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.

deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
deliverLatitude	Double		Optional	Latitude coordinates of the customer's delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer's delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer's delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Mandatory	Unique identifier associated with the return customer.
returnAccountName	String	255	Mandatory	Name of the return customer.
returnEmail	String	100	Conditional Mandatory	Email ID of the return customer.
returnAddressId	String	255	Optional	Identifier assigned to a return customer's address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer's return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer's return address.
returnLandmark	String	512	Optional	Landmark of the customer's return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer's return address.
returnCity	String	512	Optional	Name of the city in the customer's return address.
returnState	String	50	Optional	Name of the state in the customer's return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer's return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double	100	Conditional Mandatory	Latitude coordinates of the return address.
returnLongitude	Double	100	Conditional Mandatory	Longitude coordinates of the return address.
				Timezone of the customer's return address. This should be as per the

returnTimezone	String		Optional	Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
returnAWB	String	255	Optional	Air Waybill or AWB number associated with a return order request. If not provided, the system will consider the existing AWB as the return AWB.
clientCode	String	32	Optional	Name of the shipper's company associated with the order. Pass the company name of the shipper's account if you want to create an order on behalf of one of your shippers.
schedulerDetails	Object			Within this parameter, enter the scheduler details, such as the start date, end date, and other relevant details for generating orders based on this template.
startDate	DateTime		Mandatory	Start date and time from which order instances for this template should be created.
endDate			Optional	End date and time until which order instances for this template should be created. If not provided, the API will generate only one instance of the order using this template.
frequency	String		Conditional Mandatory	Frequency of order occurrences using this template. Specify the value 'DAILY' for daily recurrence, 'WEEKLY' for weekly recurrence, 'MONTHLY' for monthly recurrence, or 'CUSTOM' for a specific recurrance pattern, such as every other day. This field is required if 'weekDays' is not provided.
weekDays	String		Conditional Mandatory	Name of the day(s) in a week for which order occurances should be created using this template. You can enter multiple days in a comma-separated format. This field is mandatory when the 'frequency' is set to 'CUSTOM'.
numberOfOccurrences	Number		Optional	Number of times this order template should occur.
interval	Number		Optional	Interval at which orders should be created using this template. For example, to create order occurrences every two weeks, use this field in conjunction with a 'WEEKLY' frequency.

CREATE MULTI-STOP

Sample Request

```
[{
 "parentOrderNo":"DN987679",
 "awbNumber": "VC7",
 "shipmentOrderDt": "2018-01-10T10:00:00.000Z",
 "autoAllocateFl": "N",
 "shipmentOrderTypeCd": "DELIVER",
 "orderState": "FORWARD",
 "deliverStartTimeWindow": "2016-07-16T10:31:00.000Z",
 "deliverEndTimeWindow": "2016-07-18T10:31:00.000Z",
 "shipmentBranch": "East Manhattan",
 "returnAllowedFl": "Y",
 "cancellationAllowedFl": "N",
 "returnBranch": "East Manhattan",
 "pickupNotes": "PickedUp",
 "optimiseOrderSequenceFl":"N",
 "backToOriginFl": "N",
 "endTimeWindow": "2018-01-17T09:20:00.000Z",
 "startTimeWindow": "2018-01-17T06:30:00.000Z",
```

```
  "generateParentOrderNo": "N",
  "destinations": [
    {
      "orderNo": "DNC987679" ,
      "packageWeight": "10",
      "packageVolume": "450",
      "paymentType": "Prepaid",
      "deliverServiceTime": "10",
      "originalOrderValue": "500",
      "orderDiscount": "10",
      "packageValue":"450",
      "insuranceRequiredFl": "Y",
      "insuredValue": "450",
      "signatureRequiredFl": "Y",
      "numberOfItems": "1",
      "packagingRequiredFl": "Y",
      "partialDeliveryAllowedFl": "Y",
      "deliveryLocationType": "Groceries",
      "deliverAccountCode": "L00981",
      "deliverAccountName": "Dest User 1",
      "deliverEmail": "james.w@ablogs.com",
      "deliverPhoneNumber": "5163063377",
      "deliverWhatsappOptin":"Y",
      "deliverApartment": "901",
      "deliverStreetName": "2142 3rd Ave",
      "deliverLandmark": "Opp. McDonalds",
      "deliverLocality": "Downtown Manhattan",
      "deliverCity": "New York",
      "deliverState": "NY",
      "deliverCountry": "USA",
      "deliverPinCode": "10035",
      "deliverLatitude": 40.760838,
      "deliverLongitude": -73.96732299999996,
      "deliverNotes": "Delivered",
      "shipmentCrateMappings": [
        {
          "crateCd": "CRATE001",
          "crateAmount": 100.65,
          "crateType": "case",
          "noOfUnits": 1,
          "shipmentlineitems": [
            {
            "itemCd": "1_120000256",
            "itemName": "Bourbon 2x400gm",
            "itemPrice": 12,
            "itemQuantity": 12,
            "itemType": "Biscuit",
            "itemWeight": 10,
            "itemVolume":11,
            "itemLength":12,
            "itemBreadth":13,
            "itemHeight":14
          }
        ]
        }
      ]
    }
]
}
]
```


Success Response


```
{
```

```
    "status": 200,
    "message": "Add Orders to manifest success.",
    "data": {
        "manifestId": "hcgsyuc334"
    },
    "hasError": false
}
```

Create new Multi-Stop orders in the LogiNext system using this API.

- This API creates Multi-Stop type of orders, where multiple orders are picked up from a single location at once and delivered to up to 20 different delivery locations. It assigns a unique Reference ID that can be used to identify each order later.
- This Multi-Stop order is identified by its Parent Order Number, and you can use auto-assignment to assign it to a delivery associate.
- This API can also be used for single pickup and single destination/delivery type of orders.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v2/multidestination/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
clientCode	String	255	Optional	Name of the shipper's company associated with the multi-stop order. Pass the company name of the shipper's account if you want to create an order on behalf of one of your shippers.
parentOrderNo	String	100	Mandatory	Identifier of the multi-stop order. This can be used to track the multiple orders within the multi-stop order together. On the tracking link of an order that shares the Parent Order Number with some other orders, those other orders appear as 'Related Orders'. You can enter any alphanumeric value, including 'a to z', 'A to Z', '0 to 9', '_'(underscore), and '-'(hyphen) as a Parent Order Number. If not provided, the system will auto-generate one.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with the multi-stop order.
shipmentOrderDt	Date		Mandatory	The date and time on which you received the order request for the multi-stop order. Note that the date and time must be in UTC format. For example - 2017-07-15T10:30:00.000Z.
shipmentOrderTypeCd	String	10	Mandatory	The value in this field must always be 'DELIVER'.
orderState	String	10	Mandatory	State of the multi-stop order. Order state helps you understand the direction of order whether the order is in forward state or reverse state. Specify 'FORWARD' if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or 'REVERSE' if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
				The opening time of the delivery time window in YYYY-

deliverStartTimeWindow	Date		Mandatory	MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer's preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be greater than the order creation date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z. Also note that if the `autoAllocateFl` parameter is set to 'Y', the pick-up start date and time is also considered as same. If it is set to 'N', the pick-up date and time is not set.
deliverEndTimeWindow	Date		Mandatory	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be later than the delivery start date and time, and must be in UTC format. For example - 2016-07-01T11:18:00.000Z. Also note that if the `autoAllocateFl` parameter is set to 'Y', the pick-up start date and time is also considered as same. If it is set to 'N', the pick-up date and time is not set.
deliveryType	String	40	Optional	In certain operations, different skill sets or special delivery requirements are needed. For example, groceries or food items must be separated from toiletries orders, or cake orders cannot be combined with flower orders while delivering. In such cases, if you want to classify orders using the Delivery Type, you can use this field to ensure the orders are assigned to delivery associates configured in the LogiNext system with the required skill sets or delivery types. Note that you must define the Skill Sets in the Fleet Configuration module under Settings before passing it here in the orders. Contact your Account Manager to set these values for you. You can pass multiple Skill Sets in a comma-separated format in this API.
shipmentBranch	String	255	Mandatory	For pickup type of orders, this field specifies the branch where the delivery associate will deliver the pickup order. For the delivery type of orders, this field specifies the branch where the delivery associate will pick up the order. Note that you must specify the Operation Branch using the Add Branch API or the Add Branch form in the Branch Configuration module. In case of any issues while creating a branch, contact your Account Manager.
returnAllowedFl	String	1	Optional	Whether the orders in a multi-stop order is returnable or not. Specify 'Y' to allow your customers to initiate a return request post-delivery if needed. This way, your OMS/WMS/ERP system (integrated with the LogiNext system) will be able to create a return request for the order. Specify 'N' to prevent a return request referencing this order. However, you will always have the option to create a new order altogether for returns by specifying 'REVERSE' in the 'orderState' field. If no value is provided, the system considers 'N' by default.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate the order cancellation request after placing the orders or not. Specify 'Y' to enable cancellations. This way your OMS/WMS/ERP system (integrated with LogiNext system) will be able to cancel the order. Specify 'N' to prevent cancellations. If no value is provided, the system considers 'N' by default.
				Name of branch where the orders should be returned, if

returnBranch	String	255	Conditional Mandatory	needed. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
pickupNotes	String	255	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
autoAllocateFl	String	1	Optional	Whether the order should be considered for auto-assignment or not. Specify 'Y' to consider the order for auto-assignment (i.e., the order will be automatically assigned to the nearest delivery associate upon creation), ‘N’ if the order should not be considered for auto-assignment, or ‘P’ if you want to assign the newly created order to an existing planned trip. Note that selecting 'P' may affect the sequence of previously assigned orders for that trip.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If not provided, the default profile will be considered.
optimiseOrderSequenceFl	String	1	Mandatory	Whether you want to optimize the order sequence or not. This flag should be used only for Multi-Stop orders. Specify 'Y' if you want the system to optimize the route and rearrange the sequence in which the orders need to be delivered or 'N' if you want the system to plan the delivery routes according to the sequence of the orders you have provided.
backToOrigin	String	1	Mandatory	Whether you want the destination branch to be the same as the pick-up branch from where the delivery associate picked up the order. Specify ‘Y’ to set the destination branch as the pick-up branch, or ‘N’ to keep the destination branch different.
destinations	List		Mandatory	Within this parameter, enter the order destination details, such as the order number, delivery sequence, package details, and other relevant details for generating orders with multiple destinations, or deliveries.
orders.orderNo	String	255	ConditionalMandatory	Unique identifier of an individual order within the multi-stop order. You can enter any alphanumeric value, including 'a to z’, 'A to Z’, '0 to 9’, ’_’(underscore), and ’-’(hyphen) as the order number. To create multi stop orders (i.e., orders with single pickup and multiple destinations), each delivery order must have a unique ‘orders.orderNo’ value, which should be different from the 'parentOrderNo' and to create a single pickup and single destination/delivery order, it is mandatory to specify the ‘orders.orderNo’ value same as the 'parentOrderNo'. If you do not have a separate order number for each delivery order, you can leave this field blank. If this field is not provided, the system will auto-generate an order number for each delivery based on its parent order number. For example: Parent_Order_No_1, Parent_Order_No_2, and so on.

orders.deliverySequence	String	1	Mandatory	Place in the delivery sequence where you want this order to be delivered. For example, if you set this value to 3, the package will be delivered in the 3rd place in the sequence. If you are creating a single destination type of order, set this value as '1', as there would be only 1 order to deliver.
orders.packageWeight	String	10	Optional	The total weight of the order. This information can be critical if the order has a considerable weight. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
orders.packageVolume	String	10	Optional	The total volume of the order. This information can be critical if the order occupies a considerable volume. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
orders.paymentType	String	10	Mandatory	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Delivery (COD)’ if the delivery associate needs to collect cash or card at the time of delivery. If no value is provided, the system considers 'COD' by default. Note that if your delivery associates use mPOS devices to accept card payments during delivery and you want to integrate them with the Driver App, you can raise an integration request with your Account Manager.
orders.originalOrderValue	Float	10	Optional	Cost of the order before applying any discount.
orders.orderDiscount	Float	10	Optional	Discount(in %) applicable for the order. (i.e., discount provided over the Original Order Value.)
orders.packageValue	Double	10	Optional	Final cost of the order after applying the discount, if any.
orders.insuranceRequiredFl	String	16	Optional	Whether you want insurance coverage for this order or not. Specify this parameter as 'Y' if you require insurance coverage, or 'N' if you do not. If you set this parameter to 'Y', the insuredValue parameter becomes mandatory.
orders.insuredValue	Double	10	Optional	Insured amount applicable for the order. You can specify this parameter only if you have set the 'insuranceRequired' parameter to 'Y'. Note that the amount you specify here must be less than or equal to the 'packageValue'.
orders.signatureRequiredFl	String	16	Optional	Whether you want the signature/adult signature for the order or not. Specify this parameter as 'Y' if you want the customer's signature, 'A' if you require an adult's signature (i.e., the signatory must be of legal adult age), or 'N' if no signature is needed for the order.
orders.numberOfItems	String	255	Conditional Mandatory	The total number of items in the order.
orders.packagingRequiredFl	String		Optional	Whether packaging is required for this order or not. Specify ‘Y’ if packaging service is required for the order,

				or ‘N’ if not.
orders.deliverServiceTime	String	10	Mandatory	The time required to deliver the order at the customer's location. This is particularly useful if the order requires a considerable amount of time loading/unloading.
orders.deliveryLocationType	String	50	Optional	Type of customer address, e.g., Residential, Office, etc.
orders.partialDeliveryAllowedFl	String	1	Optional	Whether delivery associates are allowed to deliver the order partially (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
orders.deliverAccountCode	String	255	Mandatory	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn’t belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
orders.deliverAccountName	String	255	Mandatory	Name of the delivery customer. This field is optional if the Customer Profiling property is enabled.
orders.deliverEmail	String	100	Optional	Email ID of the customer.
orders.deliverPhoneNumber	String	100	Optional	Contact number of the customer. This field is optional if the Customer Profiling property is enabled.
orders.deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
orders.deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
orders.deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
orders.deliverLandmark	String	512	Optional	Landmark of the customer’s delivery location. This field is optional if the Customer Profiling property is enabled.
orders.deliverCity	String	512	Conditional Mandatory	Name of the city in the customer’s delivery address. This field is optional if the Customer Profiling property is enabled.
orders.deliverState	String	50	Conditional Mandatory	Name of the state in the customer’s delivery address. This should be as per the State Codes available in the LogiNext system for the selected country. This field is optional if the Customer Profiling property is enabled.
orders.deliverCountry	String	3	Conditional Mandatory	Name of the country in the customer’s delivery address. This should be as per the Country Codes available in the LogiNext system. This field is optional if the Customer Profiling property is enabled.

orders.deliverPinCode	String	12	Conditional Mandatory	Pin code of the customer's delivery location. This field is optional if the Customer Profiling property is enabled.
orders.deliverLatitude	String		Conditional Mandatory	Latitude coordinates of the customer's delivery address.
orders.deliverLongitude	String		Conditional Mandatory	Longitude coordinates of the customer's delivery address.
orders.deliverNotes	String	255	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
shipmentCrateMappings	Array of objects			Within this parameter, enter the crate details of the order, including the crate code, amount, type, number of items, and other relevant details. In the case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
generateParentOrderNo	String	50	Optional	Whether the system should generate a parent order number or not. Specify 'Y' to auto-generate the parent order number or 'N' to opt out.

REQUEST PARAMETERS (CRATES)

Parameter	Datatype	Length	Required	Description
crateCd	String	128	Mandatory	Unique identifier for the crate you are creating.
crateAmount	Double		Mandatory	Cost applicable for the crate. If 'partialDeliveryAllowedFl' is set to 'Y,' this amount is used to recalculate the order amount.
crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
noOfUnits	Integer	10	Conditional Mandatory	Total number of crates in the order.
shipmentlineitems	Array of objects		Optional	Specify the item details of the order.
shipmentCrateMappings.crateVolume	Double	10,3	Optional	Volume of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
shipmentCrateMappings.crateWeight	Double	10,3	Optional	Weight of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.
shipmentCrateMappings.crateLength	Double	10,3	Optional	Length of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

shipmentCrateMappings.crateBreadth	Double	10,3	Optional	Width of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
shipmentCrateMappings.crateHeight	Double	10,3	Optional	Height of the crate. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).

REQUEST PARAMETERS (LINE ITEMS)

Parameter	Datatype	Length	Required	Description
itemCd	String	200	Mandatory	Unique identifier for the item you are creating.
itemName	String	255	Mandatory	Name of the item.
itemPrice	Double		Mandatory	Cost applicable for the item. If 'partialDeliveryAllowedFl' is set to 'Y,' this amount is used to recalculate the order amount.
itemQuantity	Double	10	Optional	Total number of items.
itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
itemWeight	Double	10	Optional	Weight of the item.
shipmentCrateMappings.shipmentlineitems.itemLength	Double	10,3	Optional	Length of the item.
shipmentCrateMappings.shipmentlineitems.itemBreadth	Double	10,3	Optional	Width of the item.
shipmentCrateMappings.shipmentlineitems.itemHeight	Double	10,3	Optional	Height of the item.

CREATE RETURN

Sample Request

```
[
  "863fe69239bc4f738ca275a809c3b2e2",
  "ca275a9239bc4f738ca275a809c35fr3",
  "5a809c239bc4f738ca275a809c3b23e4"
]
```

Success Response

```
{
  "status": 201,
  "message": "success",
  "referenceId": [
    "d7b0f3f8e1174742bd6a8ae451866cb1",
    "8e117a9239bc4f738ca275a809c35fr3",
    "3csefc239bc4f738ca275a209c38e117"
  ],
```

```
 "hasError": false,

}
```

Create return orders for existing orders in the LogiNext system using this API.

- This API creates a Return type of order for an existing order and assigns a unique Reference ID that can be used to identify the return order later.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v1/create/return`

REQUEST PARAMETER

Parameter	Datatype	Length	Required	Description
reference_ids	List		Mandatory	Unique reference identifier of the orders for which you want to create a return order.

END-TO-END ACCOUNT: CREATE RETURN

Sample Request

```
[
  "8e117a9239bc4f738ca275a809c35fr3",
  "d7b0f3f8e1174742bd6a8ae451866cb1",
  "3csefc239bc4f738ca275a209c38e117"
]
```

Success Response

```
{
  "status": 201,
  "message": "success",
  "moreResultsExists": false,
  "data": [
    "df967ed5d9d94719bb728131bc54e911",
    "ca275a9239bc423738ca275a809c35fr",
    "5a809c239bc4f7df8ca275a809c3b23e"
  ],
  "hasError": false,
}
```

Partial Success Response

```
{
   "status": 207,
   "message": "Order(s) created partially",
   "moreResultsExists": false,
   "data": [
       "5a809c239bc4f7df8ca275a809c3b23e"
   ],
   "error": {
       "data": {
           "return order not allowed": [
               "ca275a9239bc423738ca275a809c35fr"
```

```
            ],
            "return order already exists": [
                "df967ed5d9d94719bb728131bc54e911",
            ]
        }
    },
    "hasError": true
}
```

Failure Response

```
{
    "status": 409,
    "message": "Order(s) creation failed",
    "moreResultsExists": false,
    "error": {
        "data": {
            "return order not allowed": [
                "5a809c239bc4f7df8ca275a809c3b23e"
            ],
            "return order already exists": [
                "ca275a9239bc423738ca275a809c35fr",
                "df967ed5d9d94719bb728131bc54e911"
            ]
        }
    },
    "hasError": true
}
```

Create return orders for existing orders in an End-to-End account in the LogiNext system using this API.

- This API creates a Return type of orders for existing orders within the End-to-End account and assigns a unique Reference ID that can be used to identify the return order later.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/middlemile/shipment/order/api/create/return`

REQUEST PARAMETER

Parameter	Datatype	Length	Required	Description
reference_ids	List		Mandatory	Unique reference identifier of the orders for which you want to create a return order.

GET

Sample Request

```
https://api.loginextsolutions.com/ShipmentApp/mile/v1/shipment?end_date=2017-03-07+18:29:59&start_date=2016-02-01+18:30:00&status=ALL&order_no=GKS12567&orderReferer
```

Success Response

```
{
    "status": 200,
    "message": "SUCCESS",
```

```
    "moreResultsExists": false,
    "data": [
        {
            "referenceId": "f40cf4493a5949199775499b5750a272",
            "orderNo": "GR432U5",
            "parentOrderNo": "GKS12",
            "clientName": "UNY Logistics",
            "branchName": "West Brooklyn Hub",
            "origin": "West Brooklyn Hub",
            "destination": "California Hub",
            "shipmentOrderTypeCd": "DELIVER",
            "orderState": "FORWARD",
            "deliveryType": "TRK",
            "deliveryLocationType": "PUP",
            "shipmentOrderDt": 1485153536000,
            "startTimeWindow": 1485174600000,
            "endTimeWindow": 1485181800000,
            "paymentType": "COD",
            "notes": "Order recieved successfully.Thanks",
            "packageValue": 300.0,
            "shippingCost":50,
            "recalculatedValue": 300.0,
            "status": "DELIVERED",
            "serviceTime": 5,
            "deliveryMediumName": "James",
            "deliverMediumPhoneNumber": "9757282492",
            "assignedThrough": "Manually",
            "carrierModeOfAssignment": "Auto-Assigned",
            "tripName": "TRIP-5276",
            "actualStartDt": 1562152130000,
            "actualEndDt": 1562152153000,
            "timeTakenDifferenceInMins": 0,
            "pickupCheckOutTime": 1562152130000,
            "pickupCheckOutLatitude": 40.7520394,
            "pickupCheckOutLongitude": -73.9763424,
            "deliverCheckInTime": 1562152141000,
            "deliverCheckOutTime": 1562152153000,
            "deliverCheckInLatitude": 19.1118182,
            "deliverCheckInLongitude": 72.9094924,
            "deliverCheckOutLatitude": 19.1118182,
            "deliverCheckOutLongitude": 72.9094924,
            "orderSequence": 2,
            "customerCode": "johnsmith",
            "customerName": "John Smith",
            "amountCollected": 300.0,
            "noOfAttempts": 1,
            "isDelayed": false,
            "originLatitude": 40.7520394,
            "originLongitude": -73.9763424,
            "destinationLatitude": 19.1118133,
            "destinationLongitude": 72.9094806,
            "parentOrderNo": "GR432U578569",
            "generateParentOrderNo": "N",
             "shipmentCrateMappings": [
                {
                    "createdOnDt": 1564757907000,
                    "updatedOnDt": 1564757950000,
                    "createdByUserId": 1535,
                    "updatedByUserId": 1535,
                    "isDeleteFl": "N",
                    "isActiveFl": true,
                    "id": 30310923,
                    "shipmentMappingId": 30310923,
                    "crateCd": "ABG001",
                    "statusCd": "LOADED",
                    "crateAmount": 0.0,
```

```
                "shipmentlineitems": [
                    {
                        "createdOnDt": 1564757907000,
                        "updatedOnDt": 1564757939000,
                        "itemCd": "R445",
                        "itemName": "",
                        "itemPrice": 100.0,
                        "itemQuantity": 10.0,
                        "itemType": "Groceries",
                        "itemWeight": 0.0,
                        "amountToCollect": 1000.0,
                        "statusCd": "LOADED",
                        "loadedQuantity": 10.0,
                        "unloadedQuantity": 0.0
                    }
                ],
                "noOfUnits": 1.0,
                "loadedUnits": 10.0,
                "unloadedUnits": 0.0,
                "orderNo": "GR432U5"
            }
        ],
        "fleetEstimatedCost":"100.0",
        "fleetActualCost":"100.0",
        "employeeId": "ABC345",
        "shipmentOrderDtTZ": "America/New_York",
        "startTimeWindowTZ": "America/New_York",
        "endTimeWindowTZ": "America/Los_Angeles",
        "actualStartDtTZ": "America/New_York",
        "actualEndDtTZ": "America/Los_Angeles",
        "pickupCheckOutTimeTZ": "America/New_York",
        "deliverCheckInTimeTZ": "America/Los_Angeles",
        "deliverCheckOutTimeTZ": "America/Los_Angeles"
    },
    {
      "referenceId": "f40cf4493a5949199775499b5750a272",
      "orderNo": "GR432U5",
      "parentOrderNo": "GKS12",
      "awbNumber": "435-16685675",
      "clientName": "UNY Logistics",
      "branchName": "West Brooklyn",
      "origin": "West Brooklyn",
      "destination": "2142 3rd Ave",
      "shipmentOrderTypeCd": "DELIVER",
      "orderState": "FORWARD",
      "preparationTime": 20,
      "shippingCost": 50,
      "deliveryType": "TRK",
      "deliveryLocationType": "PUP",
      "shipmentOrderDt": 1485153536000,
      "startTimeWindow": 1485174600000,
      "endTimeWindow": 1485181800000,
      "priority":"PRIORITY1",
      "serviceType":"Express",
      "paymentType": "COD",
      "orderState":"FORWARD",
      "notes": "Order recieved successfully.Thanks",
      "packageValue": 300.0,
      "shippingCost":50,
      "recalculatedValue": 0,
      "status": "DELIVERED",
      "plannedServiceTime": 5,
      "serviceTime": 2,
      "deliveryMediumName": "5T-ACOM2",
      "deliveryMediumReferenceId": "8ff2cb5ad79f4639b7ecf7563877e09b",
      "deliveryMediumBranch": "West Brooklyn",
```

```
"assignedThrough": "Manually",
"carrierModeOfAssignment": "Auto-Assigned",
"tripName": "T35D33",
"deliverEta": 1597327443000,
"pickupEta": 1597324443000,
"actualTravelledDistance": 0,
"actualStartDt": 1485154380000,
"actualEndDt": 1485155021000,
"plannedDistance": 16.708,
"actualDistance": 6430.184,
"distanceFromHub": null,
"plannedStartDt": 1485154380000,
"plannedEndDt": 1485155640000,
"timeTakenDifferenceInMins": 10,
"originLatitude": 40.760838,
"originLongitude": -73.96732299999996,
"employeeId": 3224567,
"pickupCheckInTime": 1485154765000,
"pickupCheckOutTime": 1485154887000,
"pickupCheckInLatitude": 40.760838,
"pickupCheckInLongitude": -73.96732299999996,
"pickupCheckOutLatitude": 40.760838,
"pickupCheckOutLongitude": -73.96732299999996,
"destinationLatitude": 41.882702,
"destinationLongitude":101.706872,
"deliverCheckInTime": 1485154905000,
"deliverCheckOutTime": 1485155021000,
"deliverCheckInLatitude": 41.882702,
"deliverCheckInLongitude": -87.61939,
"deliverCheckOutLatitude": 41.882702,
"deliverCheckOutLongitude": -87.61939,
"orderSequence": 5,
"pickupAccountCode":"PDT_124",
"customerCode": "CST_ACL1",
"customerName": "Steven Goods",
"amountCollected": 200,
"podCount": 2,
"noOfCrates": 1,
"packageWeight": 0,
"packageVolume": 0,
"customerComments": "",
"deliverNotes": "Order delivered successfully",
"customerRatings": 5,
"customerPhoneNumber": "5163063377",
"whatsappOptin": "N",
"deliveryMediumPhoneNumber":"3125096995",
"reason": null,
"vehicleNumber": "AC2T123",
"noOfAttempts": 1,
"deliveryGeofenceEnterTime": 1484727378000,
"deliveryGeofenceExitTime": 1484727387000,
"isDelayed": false,
"partialDeliveryAllowedFl":false,
"returnAllowedFl":false,
"cancellationAllowedFl":false,
"delayedBy": null,
"pickupEmail":"steve@movenpick.com",
"deliverEmail":"james@ablog.com",
"fleetEstimatedCost":"100.0",
"fleetActualCost":"100.0",
"shipmentCrateMappings": [
  {
    "crateCd": "Crate1",
    "statusCd": "UNLOADED",
    "crateType": "CRATE",
    "crateAmount": 0,
```

```
                "shipmentlineitems": [],
                "noOfUnits": 1,
                "loadedUnits": 1,
                "unloadedUnits": 1,
                "orderNo": "TEST_ACL1",
                "crateQuantity": 0,
                "amountToCollect": 0,
              }
            ]
          }
      ],
      "hasError": false
  }
```


Retrieve details of required orders using this API.

- This API retrieves the details of an order, including its branch name, start time, end time, order type, shipping cost, and other necessary information.
- Include the Order Reference IDs or other necessary parameters in the Request Body to fetch the required orders.
- Note that the order details can only be retrieved for a maximum date range of 7 days at a time; i.e., the duration between the Start Date and End Date must be less than 7 days.
- You can access data only from the past three years.

API TYPE

- Tier 2 API.

REQUEST

GET `https://api.loginextsolutions.com/ShipmentApp/mile/v1/shipment`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
start_date	Date		Conditional Mandatory	Start date of the range (in yyyy-MM-dd HH:mm:ss format) from which you want to retrieve a list of fulfilled orders. Note that only orders whose start time falls within the specified date range will be fetched. This field is mandatory, if ‘order_no’ is not provided.
end_date	Date		Conditional Mandatory	End date of the range (in yyyy-MM-dd HH:mm:ss format) up to which you want to retrieve a list of fulfilled orders. Note that only orders whose end time falls within the specified date range will be fetched. This field is mandatory, if ‘order_no’ is not provided.
status	String	10	Optional	Status of the order you want to retrieve. Whether you want to retrieve ‘NOTDISPATCHED’, ‘INTRANSIT’, ‘COMPLETED’, ‘NOTCOMPLETED’, ‘PICKEDUP (Only for First Mile)’, or ‘CANCELLED’ orders. This field is used to filter the orders you want to retrieve, if ‘order_no’ is not provided.
order_no	String	100	Optional	Unique number of the order that you want to retrieve. Only one order number can be passed at a time. If not provided, all fulfilled orders within the specified date range will be fetched.
orderReferenceId	String	100	Optional	Unique reference identifier associated with the order. This ID is used to identify the specific order that you want to retrieve. Only one Reference ID can be passed at a time. If not provided, all fulfilled orders within the specified date range will be fetched.
page_no	Integer		Optional	The page number of search results from which you want to retrieve the orders using this parameter. For example - if you set the value to '5', orders from the 5th page of search results will be fetched. By default, the value is set to 1. The maximum accepted limit is 500.

page_size	Integer	Optional	The number of records/orders you want to retrieve from the selected 'page_no'. By default, the API returns 50 records. The maximum accepted value is 100; higher values will be accepted but only 100 records will actually be fetched.
customer_code	String	Optional	Unique identifier assigned to a customer's address. Only one Address ID can be passed at a time. This will retrieve the list of all orders created for the specified customer.
employee_id	String	Optional	Employee ID of the delivery associate. Only one delivery associate's Employee ID can be passed at a time. This will retrieve the list of all orders assigned to and fulfilled by the specified delivery associate.
whatsappOptin	Boolean	Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.

GET MULTIPLE

Sample Request

```
[
  "ORD20220420001",
  "ORD20220420002"
]
```

Success Response


```
{
    "status": 200,
    "message": "SUCCESS",
    "moreResultsExists": false,
    "data": [
        {
            "referenceId": "f40cf4493a5949199775499b5750a272",
            "orderNo": "ORD20220420001",
            "parentOrderNo": "GKS12",
            "clientName": "UNY Logistics",
            "branchName": "West Brooklyn Hub",
            "origin": "West Brooklyn Hub",
            "destination": "California Hub",
            "shipmentOrderTypeCd": "DELIVER",
            "orderState": "FORWARD",
            "deliveryType": "TRK",
            "deliveryLocationType": "PUP",
            "shipmentOrderDt": 1485153536000,
            "startTimeWindow": 1485174600000,
            "endTimeWindow": 1485181800000,
            "paymentType": "COD",
            "notes": "Order recieved successfully.Thanks",
            "packageValue": 300.0,
            "shippingCost":50,
            "recalculatedValue": 300.0,
            "status": "DELIVERED",
            "serviceTime": 5,
            "deliveryMediumName": "James",
            "deliverMediumPhoneNumber": "9757282492",
            "assignedThrough": "Manually",
            "carrierModeOfAssignment": "Auto-Assigned",
            "tripName": "TRIP-5276",
            "actualStartDt": 1562152130000,
            "actualEndDt": 1562152153000,
            "timeTakenDifferenceInMins": 0,
```

```
            "pickupCheckOutTime": 1562152130000,
            "pickupCheckOutLatitude": 40.7520394,
            "pickupCheckOutLongitude": -73.9763424,
            "deliverCheckInTime": 1562152141000,
            "deliverCheckOutTime": 1562152153000,
            "deliverCheckInLatitude": 19.1118182,
            "deliverCheckInLongitude": 72.9094924,
            "deliverCheckOutLatitude": 19.1118182,
            "deliverCheckOutLongitude": 72.9094924,
            "orderSequence": 2,
            "customerCode": "johnsmith",
            "customerName": "John Smith",
            "amountCollected": 300.0,
            "noOfAttempts": 1,
            "isDelayed": false,
            "originLatitude": 40.7520394,
            "originLongitude": -73.9763424,
            "destinationLatitude": 19.1118133,
            "destinationLongitude": 72.9094806,
            "parentOrderNo": "GR432U578569",
            "generateParentOrderNo": "N",
             "shipmentCrateMappings": [
                {
                    "createdOnDt": 1564757907000,
                    "updatedOnDt": 1564757950000,
                    "createdByUserId": 1535,
                    "updatedByUserId": 1535,
                    "isDeleteFl": "N",
                    "isActiveFl": true,
                    "id": 30310923,
                    "shipmentMappingId": 30310923,
                    "crateCd": "ABG001",
                    "statusCd": "LOADED",
                    "crateAmount": 0.0,
                    "shipmentlineitems": [
                        {
                            "createdOnDt": 1564757907000,
                            "updatedOnDt": 1564757939000,
                            "itemCd": "R445",
                            "itemName": "",
                            "itemPrice": 100.0,
                            "itemQuantity": 10.0,
                            "itemType": "Groceries",
                            "itemWeight": 0.0,
                            "amountToCollect": 1000.0,
                            "statusCd": "LOADED",
                            "loadedQuantity": 10.0,
                            "unloadedQuantity": 0.0
                        }
                    ],
                    "noOfUnits": 1.0,
                    "loadedUnits": 10.0,
                    "unloadedUnits": 0.0,
                    "orderNo": "GR432U5"
                }
            ],
            "employeeId": "ABC345",
            "shipmentOrderDtTZ": "America/New_York",
            "startTimeWindowTZ": "America/New_York",
            "endTimeWindowTZ": "America/Los_Angeles",
            "actualStartDtTZ": "America/New_York",
            "actualEndDtTZ": "America/Los_Angeles",
            "pickupCheckOutTimeTZ": "America/New_York",
            "deliverCheckInTimeTZ": "America/Los_Angeles",
            "deliverCheckOutTimeTZ": "America/Los_Angeles"
        },
```

```
{
    "referenceId": "hf72g4493a5949199775499b5750dc22",
    "orderNo": "ORD20220420002",
    "parentOrderNo": "GKS12",
    "clientName": "UNY Logistics",
    "branchName": "West Brooklyn Hub",
    "origin": "West Brooklyn Hub",
    "destination": "California Hub",
    "shipmentOrderTypeCd": "DELIVER",
    "orderState": "FORWARD",
    "deliveryType": "TRK",
    "deliveryLocationType": "PUP",
    "shipmentOrderDt": 1485153536000,
    "startTimeWindow": 1485174600000,
    "endTimeWindow": 1485181800000,
    "paymentType": "COD",
    "notes": "Order recieved successfully.Thanks",
    "packageValue": 500.0,
    "shippingCost": 100,
    "recalculatedValue": 500.0,
    "status": "DELIVERED",
    "serviceTime": 5,
    "deliveryMediumName": "James",
    "deliverMediumPhoneNumber": "9757282492",
    "assignedThrough": "Manually",
    "carrierModeOfAssignment": "Auto-Assigned",
    "tripName": "TRIP-5276",
    "actualStartDt": 1562152130000,
    "actualEndDt": 1562152153000,
    "timeTakenDifferenceInMins": 0,
    "pickupCheckOutTime": 1562152130000,
    "pickupCheckOutLatitude": 40.7520394,
    "pickupCheckOutLongitude": -73.9763424,
    "deliverCheckInTime": 1562152141000,
    "deliverCheckOutTime": 1562152153000,
    "deliverCheckInLatitude": 19.1118182,
    "deliverCheckInLongitude": 72.9094924,
    "deliverCheckOutLatitude": 19.1118182,
    "deliverCheckOutLongitude": 72.9094924,
    "orderSequence": 2,
    "customerCode": "johnsmith",
    "customerName": "John Smith",
    "amountCollected": 300.0,
    "noOfAttempts": 1,
    "isDelayed": false,
    "originLatitude": 40.7520394,
    "originLongitude": -73.9763424,
    "destinationLatitude": 19.1118133,
    "destinationLongitude": 72.9094806,
    "parentOrderNo": "GR432U578569",
    "generateParentOrderNo": "N",
     "shipmentCrateMappings": [
        {
            "createdOnDt": 1564757907000,
            "updatedOnDt": 1564757950000,
            "createdByUserId": 1535,
            "updatedByUserId": 1535,
            "isDeleteFl": "N",
            "isActiveFl": true,
            "id": 30310923,
            "shipmentMappingId": 30310923,
            "crateCd": "ABG001",
            "statusCd": "LOADED",
            "crateAmount": 0.0,
            "shipmentlineitems": [
                {
```

```
                            "createdOnDt": 1564757907000,
                            "updatedOnDt": 1564757939000,
                            "itemCd": "R445",
                            "itemName": "",
                            "itemPrice": 100.0,
                            "itemQuantity": 10.0,
                            "itemType": "Groceries",
                            "itemWeight": 0.0,
                            "amountToCollect": 1000.0,
                            "statusCd": "LOADED",
                            "loadedQuantity": 10.0,
                            "unloadedQuantity": 0.0
                        }
                    ],
                    "noOfUnits": 1.0,
                    "loadedUnits": 10.0,
                    "unloadedUnits": 0.0,
                    "orderNo": "GR432U5"
                }
            ],
            "employeeId": "ABC345",
            "shipmentOrderDtTZ": "America/New_York",
            "startTimeWindowTZ": "America/New_York",
            "endTimeWindowTZ": "America/Los_Angeles",
            "actualStartDtTZ": "America/New_York",
            "actualEndDtTZ": "America/Los_Angeles",
            "pickupCheckOutTimeTZ": "America/New_York",
            "deliverCheckInTimeTZ": "America/Los_Angeles",
            "deliverCheckOutTimeTZ": "America/Los_Angeles"
        }
    ],
    "hasError": false
}
```


Retrieve details of multiple required orders using this API.

- This API retrieves the details of orders, including their branch name, start time, end time, order type, shipping cost, and other necessary information.
- Include the unique Order Numbers in the Request Body to fetch the required orders.

API TYPE

- Tier 2 API.
- You can fetch the details of up to 20 Order Numbers in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v1/multipleShipments`

REQUEST PARAMETER

Parameter	Datatype	Length	Required	Description
order_nos	List		Mandatory	Unique number of the order that you want to retrieve.

END-TO-END ACCOUNT: GET

Sample Request

```
https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/shipment?order_no=030202220001&includes=milestones,estimatedCost,actualCost
```

Success Response

```
{
    "status": 200,
    "message": "SUCCESS",
    "moreResultsExists": false,
    "data": [
        {
            "referenceId": "02d8075683f14354a7bc0dcb36e6f453",
            "orderNo": "030202220001",
            "distributionCenter": "San Fransisco Hub",
            "clientName": "Express Logistics",
            "originBranchName": "San Fransisco Hub",
            "destinationBranchName": "Los Angeles",
            "destination": "lon,UNITED KINGDOM",
            "routeName": "San Fransisco Hub_Los Angeles_479",
            "orderStatus": "INTRANSIT",
            "detailedOrderStatusCd": "REACHED_INTERIM_BRANCH",
            "shipmentOrderTypeCd": "ALLMILE",
            "deliveryType": "Large Appliances",
            "orderState": "FORWARD",
            "serviceType": "Economy",
            "startTimeWindow": 1642606200000,
            "endTimeWindow": 1642579200000,
            "eta": 1642609440000,
            "shipmentOrderDt": 1642609140000,
            "estimatedCost": {
                "insurance": {
                    "insurance": 100,
                    "insurancePercent": 5
                }
            },
            "actualCost": {
                "basicShippingCost_total": 10,
                "handlingFees_total": 20,
                "locationFees_total": 30,
                "miscellaneousFees_total": 50,
                "insurancePercent": 5,
                "insurance_total": 100,
                "totalSum": 240,
                "fuelSurchargePercent": 5,
                "fuelSurcharge": 15,
                "zoneSurchargePercent": 5,
                "zoneSurcharge": 15,
                "discount": 0,
                "discount_total": 0,
                "cancellationFees": 0,
                "reAttemptFees": 0,
                "shippingCost_total": 280,
                "calculatedZoneSurchargeTaxes": {},
                "reAttemptedCount": 0,
                "fuelSurcharge_total": 15,
                "zoneSurcharge_total": 15,
            },
            "isPartialDeliveryAllowedFl": "N",
            "isCancelAllowedFl": "N",
            "isReturnAllowedFl": "N",
            "customFields": [
                {
                    "field": "cf_Hold_for_Collectt",
                    "value": "N",
                    "type": "checkbox"
                }
            ],
            "milestones": [
                {
                    "createdOnDt": 1642608936000,
                    "isActiveFl": true,
```

```
"createdOnDtTZ": "Canada/Eastern",
"shipmentId": 113206529,
"orderNo": "lek7_M2",
"orderType": "DELIVER",
"orderStatus": "NOTDISPATCHED",
"orderState": "FORWARD",
"originAddress": "4443  Lochmere Lane, 4443  Lochmere Lane, 4443  Lochmere Lane, 4443  Lochmere Lane, buffalo, New York, UNITED STATES, 95014",
"destinationAddress": "3140 E Jurupa St, Ontario, califonia, California, UNITED STATES, 91761",
"destClientNodeName": "ONTCA",
"deliveryType": "Large Appliances",
"startTimeWindow": 1642797000000,
"endTimeWindow": 1642734000000,
"awbNumber": "220119000004",
"lat": 34.046588,
"lng": -117.58257179999998,
"clientName": "LogiNext Sandbox New York All Mile",
"branchName": "Buffalo Last Mile",
"orderDate": 1642609140000,
"paymentType": "COD",
"isCancelAllowedFl": false,
"isReturnAllowedFl": false,
"isPartialDeliveryAllowedFl": false,
"capacityInWeight": 0,
"capacityInVolume": 0,
"destLatitude": 34.046588,
"destLongitude": -117.58257179999998,
"deliveryOrder": 2,
"customerName": "ONTCA",
"packageValue": 0,
"shippingCost": 0,
"apartment": "",
"streetName": "",
"landmark": "3140 E Jurupa St",
"locality": "Ontario",
"state": "California",
"pincode": "91761",
"country": "UNITED STATES",
"contactNumber": "4695438523",
"emailAddress": "abc@mail.com",
"customerId": "ONTCA",
"city": "califonia",
"clientId": 1927,
"returnClientNodeId": 14354805,
"deliverServiceTime": 0,
"returnToSameAddress": false,
"returnAccountCode": "San Fransisco Hub",
"returnAccountName": "San Fransisco Hub",
"returnEmail": "abc@mail.com",
"returnPhoneNumber": "4695438523",
"returnApartment": "mountain view",
"returnStreetName": "mountain view",
"returnLandmark": "mountain view",
"returnLocality": "mountain view",
"returnCountry": "UNITED STATES",
"returnState": "California",
"returnCity": "San Francisco",
"returnPinCode": "95014",
"returnLatitude": 37.3795659,
"returnLongitude": -122.06871100000001,
"returnServiceTime": 0,
"pickupServiceTime": 0,
"returnAddressId": "2ee4b56e28e142cb874ac3df85069635",
"addressId": "49c32c8ad0854f979a32fb34876d483c",
"customFieldsList": [
    {
        "field": "cf_Hold_for_Collectt",
```

```
                        "value": "N",
                        "type": "checkbox"
                    }
                ],
                "startTimeWindowTZ": "America/New_York",
                "endTimeWindowTZ": "America/New_York",
                "orderDateTZ": "Canada/Eastern",
                "isP2POrder": false,
                "isCurrentMilestoneFl": "Y"
            }
        ],
        "shipmentOrderDtTZ": "America/New_York"
    }
  ],
  "hasError": false
}
```


If you have an End-to-End account, retrieve details of required orders using this API.

- This API retrieves the details of an order for an End-to-End account, including its branch name, start time, end time, order type, shipping cost, delivery associate name, and other necessary information.
- Include the Order Reference IDs or other necessary parameters in the Request Body to fetch the required orders.
- Note that the order details can only be retrieved for a maximum date range of 7 days at a time; i.e., the duration between the Start Date and End Date must be less than 7 days.
- You can access data only from the past three years.

API TYPE

- Tier 2 API.

REQUEST

GET `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/shipment`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
parentOrderNumber	String	40	Optional	Parent Order Number is an identifier used to track multiple orders together. By passing this field, you can retrieve a list of all orders associated with the specified Parent Order Number.
start_date	Date		Conditional Mandatory	Start date of the range (in yyyy-MM-dd HH:mm:ss format) from which you want to retrieve a list of fulfilled orders. Note that only orders whose start time falls within the specified date range will be fetched. This field is mandatory, if ‘order_no’ is not provided.
end_date	Date		Conditional Mandatory	End date of the range (in yyyy-MM-dd HH:mm:ss format) up to which you want to retrieve a list of fulfilled orders. Note that only orders whose end time falls within the specified date range will be fetched. This field is mandatory, if ‘order_no’ is not provided.
order_no	String	100	Optional	Unique number of the order that you want to retrieve. Only one order number can be passed at a time. If not provided, all fulfilled orders within the specified date range will be fetched.
orderReferenceId	String	100	Optional	Unique reference identifier associated with the order. This ID is used to identify the specific order that you want to retrieve. Only one Reference ID can be passed at a time. If not provided, all fulfilled orders within the specified date range will be fetched. For an End-to-End account, pass the unique number associated with the milestone. Note that you can also provide the additional order details such as ‘shipmentCrateMappings’, ‘milestones’, ‘estimatedCost’, and ‘actualCost’ in the Request Body in a comma-separated

			format.
page_no	Integer	Optional	The page number of search results from which you want to retrieve the orders using this parameter. For example - if you set the value to '5', orders from the 5th page of search results will be fetched. By default, the value is set to 1. The maximum accepted limit is 500.
page_size	Integer	Optional	The number of records/orders you want to retrieve from the selected 'page_no'. By default, the API returns 50 records. The maximum accepted value is 100; higher values will be accepted but only 100 records will actually be fetched.

GET STATUS

Sample Request

```
["c8714df4347911e6829f000d3aa04450"]
```

Success Response

```
{
  "status": 200,
  "data": [
    {
      "state": "FORWARD",
      "status": "NOTDISPATCHED",
      "referenceId": "c8714528347911e6829f000d3aa04450"
    }
  ],
  "hasError": false
}
```

Retrieve the status of an order using this API.

- This API retrieves the status of the specified order.
- Include the Order Reference ID in the Request Body to fetch the status of the required order.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v1/status`

REQUEST PARAMETER

Parameter	Datatype	Length	Required	Description
reference_ids	List		Mandatory	Unique reference identifier of the order whose status you want to retrieve.

GET DISPATCH HISTORY

Sample Request

```
https://api.loginextsolutions.com/ShipmentApp/mile/v1/dispatches?start_date=2024-01-01 00:00:00&end_date=2024-01-07 23:59:59
```

Success Response

```
{
  "status": 200,
  "message": "SUCCESS",
  "moreResultsExists": false,
  "data": [
    {
      "orderReferenceId": "f40cf4493a5949199775499b5750a272",
      "orderNo": "GR432U5",
      "shipmentOrderDt": 1485153536000,
      "assignments": [
        {
          "assignedBy": "dispatcher@abc.com",
          "assignedThrough": "Manual assign",
          "fleet": "Delivery Associate",
          "offerTime": "1734355885000",
          "offerExpiryTime": "1734356882000",
          "action": "Accepted",
          "actionTime": "1734356703000",
          "assignedTo": "John",
          "fleetBranch": "Branch A",
          "actionSource": "Driver App"
        },
        {
          "assignedBy": "System",
          "assignedThrough": "Auto assign",
          "fleet": "Carrier",
          "offerTime": "1734359400000",
          "offerExpiryTime": "1734360600000",
          "action": "Rejected",
          "actionTime": "1734360000000",
          "reasonOfRejection": "No fleet available",
          "assignedTo": "Wolt",
          "fleetBranch": "Branch B",
          "actionSource": "External System"
        },
        {
          "assignedBy": "dispatcher@abc.com",
          "assignedThrough": "Manual assign",
          "fleet": "Delivery Associate",
          "offerTime": "1734361200000",
          "offerExpiryTime": "1734362100000",
          "action": "Rejected",
          "actionTime": "1734361500000",
          "reasonOfRejection": "Unavailable",
          "assignedTo": "Bob",
          "fleetBranch": "Branch C",
          "actionSource": "Driver App"
        },
        {
          "assignedBy": "System",
          "assignedThrough": "Auto assign",
          "fleet": "Carrier",
          "offerTime": "1734363000000",
          "offerExpiryTime": "1734363900000",
          "action": "Accepted",
          "actionTime": "1734363600000",
          "assignedTo": "Uber",
          "fleetBranch": "Branch D",
          "actionSource": "External System"
        }
      ]
    }
  ]
}
```

Retrieve historic details of required orders' dispatch using this API.

- This API retrieves the order assignment details, such as the user who offered/assigned the order, whether the order was assigned manually or automatically, who the order was offered/assigned to, time when the order was offered/assigned, action taken on the order, and other relevant information.
- Include the Order Numbers, Order Reference IDs, or other necessary parameters to fetch the relevant details.
- Note that the order dispatch history details can only be retrieved for a maximum date range of 7 days at a time, i.e., the duration between the Start Date and End Date must be less than 7 days.
- You can access data only from the past three years.

API TYPE

- Tier 1 API.
- This API accepts up to 20 Order Numbers or Order Reference IDs in a comma-separated format in one call of this API. However, if you specify date range and page size instead of Order Numbers or Order Reference IDs, you can get data for a maximum of 100 orders.

REQUEST

GET `https://api.loginextsolutions.com/ShipmentApp/mile/v1/dispatches`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
start_date	Date		Conditional Mandatory	Start date (in yyyy-MM-dd HH:mm:ss format) of the date range within which the required orders' start time and end time must fall. This field is mandatory, if 'order_no' and 'orderReferenceIds' are not provided.
end_date	Date		Conditional Mandatory	End date (in yyyy-MM-dd HH:mm:ss format) of the date range within which the required orders' start time and end time must fall. This field is mandatory, if 'order_no' and 'orderReferenceIds' are not provided.
order_nos	List		Conditional Mandatory	The list of order numbers of the orders whose dispatch details you want to retrieve. This field is mandatory if 'start_date' and 'end_date' or 'orderReferenceIds' are not provided.
orderReferenceIds	List		Conditional Mandatory	The list of order reference IDs of the orders whose dispatch details you want to retrieve. This field is mandatory, if 'start_date' and 'end_date' or 'order_nos' are not provided.
page_no	Integer		Optional	The page number of search results from which you want to retrieve the orders using this parameter. For example, if you set the value to '5', orders from the 5th page of search results will be fetched. By default, the value is set to 1. The maximum accepted limit is 500.
page_size	Integer		Optional	The number of records/orders you want to retrieve from the selected 'page_no'. By default, the API returns 10 records. The maximum accepted value is 100; higher values will be accepted but only 100 records will actually be fetched.

END-TO-END ACCOUNT: GET DISPATCH HISTORY

Sample Request

```
https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/dispatches?start_date=2024-01-01T00:00:00Z&end_date=2024-01-15T23:59:59Z
```

Success Response

```
{
  "status": 200,
  "message": "SUCCESS",
```

```
  "moreResultsExists": false,
  "data": [
    {
      "orderReferenceId": "f40cf4493a5949199775499b5750a272",
      "orderNo": "GR432U5",
      "shipmentOrderDt": 1485153536000,
      "milestones": [
        {
          "milestoneNumber": "GR432U5_M1",
          "assignments": [
            {
              "assignedBy": "dispatcher@abc.com",
              "assignedThrough": "Manual assign",
              "fleet": "Delivery Associate",
              "offerTime": "1734355885000",
              "offerExpiryTime": "1734356882000",
              "action": "Accepted",
              "actionTime": "1734356703000",
              "assignedTo": "John",
              "fleetBranch": "Branch A",
              "actionSource": "Driver App"
            }
          ]
        },
        {
          "milestoneNumber": "GR432U5_M2",
          "assignments": [
            {
              "assignedBy": "System",
              "assignedThrough": "Auto assign",
              "fleet": "Carrier",
              "offerTime": "1734359400000",
              "offerExpiryTime": "1734360300000",
              "action": "Accepted",
              "actionTime": "1734360000000",
              "assignedTo": "Wolt",
              "fleetBranch": "Branch B",
              "actionSource": "External System"
            }
          ]
        }
      ]
    },
    {
      "orderReferenceId": "a93cb72a84b34c988f34e4502f11cd31",
      "orderNo": "GR532U6",
      "shipmentOrderDt": 1485153536000,
      "milestones": [
        {
          "milestoneNumber": "GR532U6_M1",
          "assignments": [
            {
              "assignedBy": "dispatcher@abc.com",
              "assignedThrough": "Manual assign",
              "fleet": "Delivery Associate",
              "offerTime": "1734361200000",
              "offerExpiryTime": "1734362100000",
              "action": "Rejected",
              "actionTime": "1734361500000",
              "reasonOfRejection": "Unavailable",
              "assignedTo": "Bob",
              "fleetBranch": "Branch C",
              "actionSource": "Driver App"
            }
          ]
        },
```

```
        {
          "milestoneNumber": "GR532U6_M2",
          "assignments": [
            {
              "assignedBy": "System",
              "assignedThrough": "Auto assign",
              "fleet": "Carrier",
              "offerTime": "1734363000000",
              "offerExpiryTime": "1734363900000",
              "action": "Accepted",
              "actionTime": "1734363600000",
              "assignedTo": "Uber",
              "fleetBranch": "Branch D",
              "actionSource": "External System"
            }
          ]
        }
      ]
    }
  ],
  "hasError": false
}
```


If you have an End-to-End account, retrieve historic details of the required orders' dispatch using this API.

- This API retrieves the order assignment details for an End-to-End account, such as the user who offered/assigned the order, whether the order was assigned manually or automatically, who the order was offered/assigned to, time when the order was offered/assigned, action taken on the order, and other relevant information.
- Include the Order Numbers, Order Reference IDs, or other necessary parameters to fetch the relevant details.
- Note that the order dispatch history details can only be retrieved for a maximum date range of 7 days at a time, i.e., the duration between the Start Date and End Date must be less than 7 days.
- You can access data only from the past three years.

API TYPE

- Tier 1 API.
- This API accepts up to 20 Order Numbers or Order Reference IDs in a comma-separated format in one call of this API. However, if you specify date range and page size instead of Order Numbers or Order Reference IDs, you can get data for a maximum of 100 orders.

REQUEST

GET `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/dispatches`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
start_date	Date		Conditional Mandatory	Start date (in yyyy-MM-dd HH:mm:ss format) of the date range within which the required orders' start time and end time must fall. This field is mandatory, if 'order_no' and 'orderReferenceIds' are not provided.
end_date	Date		Conditional Mandatory	End date (in yyyy-MM-dd HH:mm:ss format) of the date range within which the required orders' start time and end time must fall. This field is mandatory, if 'order_no' and 'orderReferenceIds' are not provided.
order_nos	List		Conditional Mandatory	The list of order numbers of the orders whose dispatch details you want to retrieve. This field is mandatory if 'start_date' and 'end_date' or 'orderReferenceIds' are not provided.
orderReferenceIds	List		Conditional Mandatory	The list of order reference IDs of the orders whose dispatch details you want to retrieve. This field is mandatory, if 'start_date' and 'end_date' or 'order_nos' are not provided.

page_no	Integer	Optional	The page number of search results from which you want to retrieve the orders using this parameter. For example, if you set the value to '5', orders from the 5th page of search results will be fetched. By default, the value is set to 1. The maximum accepted limit is 500.
page_size	Integer	Optional	The number of records/orders you want to retrieve from the selected 'page_no'. By default, the API returns 10 records. The maximum accepted value is 100; higher values will be accepted but only 100 records will actually be fetched.

UPDATE

Sample Request


```
[
 {
   "referenceId": "04c1c0c283a34769a5baca01c987b51a",
   "orderNo": "GR432U5",
   "awbNumber": "435-16685675",
   "shipmentOrderDt": "2016-07-15T10:30:00.000Z",
   "packageWeight": 10,
   "packageVolume": 450,
   "packageValue": 65,
   "shippingCost": 50,
   "priority": "PRIORITY1",
   "serviceType": "Standard",
   "paymentType": "Prepaid",
   "returnAllowedFl": "Y",
   "cancellationAllowedFl": "N",
   "partialDeliveryAllowedFl": "Y",
   "distributionCenter": "Manhattan Branch",
   "pickupBranch": "New York",
   "pickupServiceTime": 50,
   "pickupStartTimeWindow": "2017-07-16T14:24:00.000Z",
   "pickupEndTimeWindow": "2017-07-17T14:24:00.000Z",
   "pickupAccountCode": "jim001",
   "pickupAccountName": "James Walker",
   "pickupEmail": "james.walker@example.com",
   "pickupPhoneNumber": "+1-212-555-7890",
   "pickupWhatsappOptin": "Y",
   "pickupAddressId": "Pickup123",
   "pickupApartment": "901",
   "pickupStreetName": "2142 3rd Ave",
   "pickupLandmark": "Opp. McDonalds",
   "pickupLocality": "East Harlem",
   "pickupCity": "New York",
   "pickupState": "NY",
   "pickupCountry": "USA",
   "pickupPinCode": "10035",
   "pickupLatitude": "40.7957",
   "pickupLongitude": "-73.9389",
   "pickupAddressTimezone": "EST",
   "pickupNotes": "Notes related to pickup",
   "deliverBranch": "test",
   "deliverServiceTime": 20,
   "deliverStartTimeWindow": "2016-07-16T10:31:00.000Z",
   "deliverEndTimeWindow": "2016-07-18T10:31:00.000Z",
   "deliveryType": "RIDER",
   "deliveryLocationType": "PUP",
   "deliverAccountCode": "Matt001",
   "deliverAccountName": "Mathew Richardson",
   "deliverEmail": "mathew.richardson@example.com",
   "deliverPhoneNumber": "+1-312-555-1234",
   "deliverWhatsappOptin": "Y",
   "deliverAddressId": "MattHome",
```

```
    "deliverApartment": "10 Suite No. A1901",
    "deliverStreetName": "Walton Avenue",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Towm Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude": "41.8827",
    "deliverLongitude": "-87.6233",
    "deliverAddressTimezone": "CST",
    "deliverNotes": "Notes related to delivery",
    "returnBranch": "New York",
    "returnStartTimeWindow": "2017-05-18T03:00:00.000Z",
    "returnEndTimeWindow": "2017-05-18T16:00:00.000Z",
    "returnAccountCode": "retAcc123",
    "returnAccountName": "retAcc1234",
    "returnEmail": "james.w@ablogs.com",
    "returnPhoneNumber": "9891235886",
    "returnWhatsappOptin": "N",
    "returnAddressId": "JeffOffice",
    "returnApartment": "901",
    "returnStreetName": "50 E 78th St",
    "returnLandmark": "Opp. Strand Bookstore",
    "returnLocality": "Upper East Side",
    "returnCity": "New York",
    "returnState": "NY",
    "returnCountry": "USA",
    "returnPinCode": "10035",
    "returnLatitude": "40.7957",
    "returnLongitude": "-73.9389",
    "tripOrderFl": "N"
    }
]
```


Success Response


```
{
    "status": 200,
    "message": "Order updated successfully",
    "moreResultsExists": false,
    "data": [
        17055042
    ],
    "hasError": false
}
```


Failure Response


```
{
    "status": 400,
    "message": "Referenceids does not exists",
    "moreResultsExists": false,
    "error": {
        "order_0": [
            {
                "key": "04c1c0c283a34769a5baca01c987b51a",
                "message": [
                    "referenceId.doestnot.exists"
                ],
                "orderReferenceId":"04c1c0c283a34769a5baca01c987b51a"
            }
```

```
        ]
    },
    "hasError": true
}
```

Update an existing order using this API.

- This API updates an existing order with the details provided if the order status is ‘Not Dispatched’ or ‘Intransit’.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.
- This API supports Custom Fields. Apart from the mandatory fields, you only need to pass the data for the Custom Fields you want to add or update in the Request Body. Note that you do not need to pass all the Custom Fields set during order creation here again. For more information on how to include Custom Fields in this API, refer to the ‘Custom Fields’ section of the API documentation.
- Custom Fields can be updated as long as the order status is not in a terminal state (e.g., picked up, delivered, etc.). Additionally, fields like weight and volume can be updated while the order is in transit.
- The pickup and/or delivery address of an in transit order can also be updated. For example, for a delivery type of order, the delivery address can be modified until the delivery associate checks in at the delivery location.
- The payment mode of an in transit order can also be updated. For example, for a delivery type of order, the payment mode (COD or Prepaid) can be modified until the delivery associate checks out.
- Note that all order details can be updated using this API, except for the 'distributionCenter' and 'partialDeliveryAllowedFl' fields associated with the order.

API TYPE

- Tier 2 API.
- You can update multiple orders and one or more parameters of each order in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v1/update`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceId	String	32	Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order that you want to update.
orderNo	String	40	Optional	Unique number of the order that you want to update.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order.
shipmentOrderDt	Date		Optional	The date on which you received the order request (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Note that the date and time must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
packageWeight	Double	10	Optional	The total weight of the order (in kg). This field can be updated even when the order is in transit state.
packageVolume	Double	10,3	Optional	The total volume of the order (in cc). This field can be updated even when the order is in transit state.
packageValue	Double	10	Optional	Total cost of the order.
shippingCost	Double	10	Optional	The cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges.
priority	String	100	Optional	Priority of the order.
serviceType	String	12	Optional	Service type of the order.
				Payment mode of the order. Whether the order is Prepaid or Cash On

paymentType	String	40	Optional	Delivery (COD). Note that the payment type depends on the language preference configured for the user account from which the API token was created. Refer to the 'Authenticate' API documentation for more details.
returnAllowedFl	String	1	Optional	Whether the order is returnable or not. Specify ‘Y’ to allow your customers to initiate a return request post delivery, if needed, or ‘N’ to prevent returns. If no value is provided, the system considers ‘Y’ by default.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
pickupBranch	String	255	Optional	For pickup type of orders, this field specifies the branch where the delivery associate will deliver the pickup order.
pickupServiceTime	Integer	11	Optional	Time required to pick up the order at the customer's location.
pickupStartTimeWindow	Date		Optional	The opening time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Optional	The closing time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Note that the end date and time must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Optional	Unique identifier associated with the pickup customer.
pickupAccountName	String	255	Optional	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Optional	Name of the apartment building/complex in the customer’s pickup address.
pickupStreetName	String	255	Optional	Name of the society or street in the customer’s pickup address.
pickupLandmark	String	512	Optional	Landmark of the customer’s pickup location.
pickupLocality	String	512	Optional	Name of the locality or area in the customer’s pickup address.
pickupCity	String	512	Optional	Name of the city in the customer’s pickup address.
pickupState	String	50	Optional	Name of the state in the customer’s pickup address. This should be as per

				the State Codes available in the LogiNext system for the selected country.
pickupCountry	String	100	Optional	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system.
pickupPinCode	String	12	Optional	Pin code of the customer's pickup location.
pickupLatitude	Double		Optional	Latitude coordinates of the customer's pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer's pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer's pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	255	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
deliverBranch	String	255	Optional	For the delivery type of orders, this field specifies the branch where the delivery associate will pick up the order.
deliverServiceTime	Integer	11	Optional	Specify the time required to deliver the order at the customer's location.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer's preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliveryType	String	40	Optional	If your order requires specific skills for delivery, you can specify it here. The planning engine takes into account the skill set requirement for the order and assigns a delivery associate who possesses the specified Skill Set.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Optional	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
deliverAccountName	String	255	Optional	Name of the delivery customer.
deliverEmail	String	100	Optional	Email ID of the customer.
deliverPhoneNumber	String	255	Optional	Contact number of the customer.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
				Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in

deliverAddressId	String	255	Optional	the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Optional	Name of the apartment building/complex in the customer's delivery address.
deliverStreetName	String	255	Optional	Name of the society or street in the customer's delivery address.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location.
deliverLocality	String	512	Optional	Name of the locality or area in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Optional	Name of the city in the customer's delivery address.
deliverState	String	50	Optional	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country.
deliverCountry	String	100	Optional	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system.
deliverPinCode	String	12	Optional	Pin code of the customer's delivery location.
deliverLatitude	Double		Optional	Latitude coordinates of the customer's delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer's delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer's delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	255	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
returnBranch	String	255	Conditional Mandatory	Name of branch where the order should be returned, if needed. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Optional	Unique identifier associated with the return customer.
returnAccountName	String	255	Optional	Name of the return customer.
returnEmail	String	100	Optional	Email ID of the return customer.
returnPhoneNumber	String	255	Optional	Contact number of the return customer.

returnWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
returnAddressId	String	255	Optional	Identifier assigned to a return customer’s address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer’s return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer’s return address.
returnLandmark	String	512	Optional	Landmark of the customer’s return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer’s return address.
returnCity	String	512	Optional	Name of the city in the customer’s return address.
returnState	String	50	Optional	Name of the state in the customer’s return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer’s return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double		Optional	Latitude coordinates of the return address.
returnLongitude	Double		Optional	Longitude coordinates of the return address.
tripOrderFl	String	50	Optional	Specify ‘Y’ to remove the trip associated with the order and change the order status to ‘Not Dispatched’, if the customer pickup or delivery address is updated, or ‘N’ to continue the trip associated with the order even if the order address is updated. If no value is provided, the system considers ‘N’ by default.

END-TO-END ACCOUNT: UPDATE

Sample Request

```
[
 {
   "referenceId":"04c1c0c283a34769a5baca01c987b51a",
   "orderNo": "GR432U5",
   "orderDt": "2016-07-15T10:30:00.000Z",
   "orderState": "FORWARD",
   "awbNumber": "435-16685675",
   "packageWeight":"10",
   "packageVolume": "450",
   "packageLength":"10",
   "packageBreadth": "450",
   "packageHeight": "450",
   "priority": "P1",
   "paymentType": "Prepaid",
   "packageValue": "65",
   "shippingCost":"50",
   "partialDeliveryAllowedFl": "Y",
   "returnAllowedFl": "Y",
   "cancellationAllowedFl": "N",
   "distributionCenter": "Manhattan Branch",
   "originBranchName" : "Manhattan Branch",
   "destinationBranchName" : "Chicago Branch",
```

```
    "routeConfigurationName" : "Manhattan-Chicago-Route",
    "nextBranchName": "Cleveland Branch",
    "nextBranchServiceTime": "",
    "nextBranchStartTimeWindow" : "",
    "nextBranchEndTimeWindow": "",
    "serviceTypeCd" : "",
    "deliveryType" : "Parcel",
    "autoAllocateFl" : "N",
    "autoAllocateProfileName" : "",
    "deliverServiceTime": "20",
    "deliverEndTimeWindow": "2016-07-18T10:31:00.000Z",
    "deliverStartTimeWindow": "2016-07-16T10:31:00.000Z",
    "deliveryLocationType":"CUSTOMER",
    "deliverAccountCode": "Matt001",
    "deliverAddressId":"MattHome",
    "deliverAccountName": "Mathew Richardson",
    "deliverApartment": "10 Suite No. A1901",
    "deliverStreetName": "Walton Avenue",
    "deliverLandmark": "Opp. Chiptole",
    "deliverLocality": "Down Towm Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude": "41.8827",
    "deliverLongitude": "-87.6233",
    "pickupServiceTime": "50",
    "pickupStartTimeWindow": "2017-07-16T14:24:00.000Z",
    "pickupEndTimeWindow": "2017-07-17T14:24:00.000Z",
    "pickupAccountCode": "jim001",
    "pickupAccountName": "James Walker",
    "pickupApartment": "901",
    "pickupStreetName": "2142 3rd Ave",
    "pickupLandmark": "Opp. McDonalds",
    "pickupLocality": "East Harlem",
    "pickupCity": "New York",
    "pickupState": "NY",
    "pickupCountry": "USA",
    "pickupPinCode": "10035",
    "pickupLatitude": "40.7957",
    "pickupLongitude": "-73.9389",
    "returnBranch": "New York",
    "returnStartTimeWindow": "2017-05-18T03:00:00.000Z",
    "returnEndTimeWindow": "2017-05-18T16:00:00.000Z",
    "returnAccountCode": "retAcc123",
    "returnAddressId":"JeffOffice",
    "returnAccountName": "retAcc1234",
    "returnEmail": "james.w@ablogs.com",
    "returnPhoneNumber": "9891235886",
    "returnWhatsappOptin": "N",
    "returnApartment": "901",
    "returnStreetName": "50 E 78th St",
    "returnLandmark": "Opp. Strand Bookstore",
    "returnLocality": "Upper East Side",
    "returnCity": "New York",
    "returnState": "NY",
    "returnCountry": "USA",
    "returnPinCode": "10035",
    "returnLatitude": "40.7957",
    "returnLongitude": "-73.9389",
    "returnAWB" : "435-16685675-R",
    "manifestId" : "0010-112HYE1",
    "pickupNotes": "Please handle with care.",
    "deliverNotes": "Please leave the package outside.",
    "tripOrderFl": "N",
    "autoAllocateFl": "Y",
```

```
    "autoAllocateProfileName": "Assignment Profile 1"
  }
]
```

Success Response

```
{
    "status": 200,
    "message": "Order updated successfully",
    "moreResultsExists": false,
    "data": [
        {
        "referenceId":"04c1c0c283a34769a5baca01c987b51a"
        }
    ],
    "hasError": false
}
```

Failure Response

```
{
    "status": 400,
    "message": "Referenceids does not exists",
    "moreResultsExists": false,
    "error": {
        "order_0": [
            {
                "key": "04c1c0c283a34769a5baca01c987b51a",
                "message": [
                    "referenceId.doestnot.exists"
                ],
                "orderReferenceId":"04c1c0c283a34769a5baca01c987b51a"
            }
        ]
    },
    "hasError": true
}
```

If you have an End-to-End account, update an existing order using this API.

- This API updates an existing order with the details provided if the order status is ‘Not Dispatched’ or ‘Intransit’.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.
- This API supports Custom Fields. Apart from the mandatory fields, you only need to pass the data for the Custom Fields you want to add or update in the Request Body. Note that you do not need to pass all the Custom Fields set during order creation here again. For more information on how to include Custom Fields in this API, refer to the ‘Custom Fields’ section of the API documentation.
- Custom Fields can be updated as long as the order status is not in a terminal state (e.g., picked up, delivered, etc.). Additionally, fields like weight and volume can be updated while the order is in transit.
- The pickup and/or delivery address of an in transit order can also be updated. For example, for a delivery type of order, the delivery address can be modified until the delivery associate checks in at the delivery location.
- This API can be used to update pickup orders, delivery orders, multi-leg End-to-End (E2E) orders, and point-to-point orders.
- The payment mode of an in transit order can also be updated. For example, for a delivery type of order, the payment mode (COD or Prepaid) can be modified until the delovery associate has checks out.
- Note:
    - Any updates to the order will also be reflected in both the Order Request and the associated Milestones.
    - All address field validations are based on the settings configured in the ‘Address Format Configuration’ module within the LogiNext system.

API TYPE

- Tier 2 API.
- This API does not support partial success responses. If you include multiple IDs in a single request and even one fails validation, the

entire batch will be considered as a failed request.
- You can update multiple orders and one or more parameters of each order in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/middlemile/shipment/order/api/update`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceId	String	32	Conditional Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order that you want to update. This field is mandatory, if 'orderNo' is not provided.
orderNo	String		Conditional Mandatory	Unique number of the order that you want to update. This field is mandatory, if 'referenceId' is not provided.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order.
orderDt	Date		Optional	The date on which you received the order request (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Note that the date and time must be in UTC format. For example - 2017-07-15T10:30:00.000Z.
orderState	String	512	Optional	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of order whether the order is in forward state or reverse state. Specify 'FORWARD' if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or 'REVERSE' if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
packageWeight	Double	10	Optional	The total weight of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings.
packageVolume	Double	10	Optional	The total volume of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings.
packageLength	Double	10	Optional	The total length of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings.
packageBreadth	Double	10	Optional	The total width of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings.
packageHeight	Double	10	Optional	The total height of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings.
packageValue	Double	10	Optional	Total cost of the order.
shippingCost	Double	10	Optional	The cost incurred in the movement of the order. Shipping cost is also referred to as delivery charges.
priority	String	100	Optional	Priority of the order.
paymentType	String	40	Optional	Payment mode of the order. Whether the order is Prepaid or Cash On Pickup/Delivery (COP/COD). Note that the payment type depends on the language preference configured for the user account from which the API token was created. Refer to the 'Authenticate' API documentation for more details.

partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver a partial order (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify 'Y' to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or 'N' to prevent partial deliveries. If no value is provided, the system considers 'Y' by default.
returnAllowedFl	String	1	Optional	Whether the order is returnable or not. Specify 'Y' to allow your customers to initiate a return request post delivery, if needed, or 'N' to prevent returns. If no value is provided, the system considers 'Y' by default.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify 'Y' to enable cancellations or 'N' to prevent them. If no value is provided, the system considers 'Y' by default.
distributionCenter	String	255	Optional	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
originBranchName	String	255	Optional	Name of the original branch associated with the order.
destinationBranchName	String	255	Optional	Name of the destination branch associated with the order.
routeConfigurationName	String	255	Optional	Route associated with the order.
nextBranchName	String		Optional	If 'routeConfigurationName' is not provided in the API during order creation, you must provide the details of the next branch the E2E order will flow through.
nextBranchServiceTime	Number		Optional	Specify the time required to deliver the order at the next branch location. This is particularly useful if the order requires a considerable amount of time loading/unloading.
nextBranchStartTimeWindow	String		Optional	The opening time of the next branch's time window associated with the order. Note that the date and time must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
nextBranchEndTimeWindow	String		Optional	The closing time of the next branch's time window associated with the order. Note that the end date and time must be later than the pickup start date and time, and must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
serviceTypeCd	String	255	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled.
pickupServiceTime	Integer	11	Optional	Time required to pick up the order at the customer's location.
pickupStartTimeWindow	Date		Optional	The opening time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Pickup time window is the customer's preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be in UTC format. For example - 2017-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Optional	The closing time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Note that the end date and time must be in UTC format. For example - 2017-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Optional	Unique identifier associated with the pickup customer.

pickupAccountName	String	255	Optional	Name of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer’s address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Optional	Name of the apartment building/complex in the customer’s pickup address.
pickupStreetName	String	255	Optional	Name of the society or street in the customer’s pickup address.
pickupLandmark	String	512	Optional	Landmark of the customer’s pickup location.
pickupLocality	String	512	Optional	Name of the locality or area in the customer’s pickup address.
pickupCity	String	512	Optional	Name of the city in the customer’s pickup address.
pickupState	String	50	Optional	Name of the state in the customer’s pickup address. This should be as per the State Codes available in the LogiNext system for the selected country.
pickupCountry	String	100	Optional	Name of the country in the customer’s pickup address. This should be as per the Country Codes available in the LogiNext system.
pickupPinCode	String	12	Optional	Pin code of the customer’s pickup location.
pickupLatitude	Double		Optional	Latitude coordinates of the customer’s pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer’s pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer’s pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
pickupNotes	String	255	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
deliverServiceTime	Integer	11	Optional	Specify the time required to deliver the order at the customer's location.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer’s preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be in UTC format. For example - 2016-07-01T11:18:00.000Z.

deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
deliveryType	String	40	Optional	If your order requires specific skills for delivery, you can specify it here. The planning engine takes into account the skill set requirement for the order and assigns a delivery associate who possesses the specified Skill Set.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Optional	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
deliverAccountName	String	255	Optional	Name of the delivery customer.
deliverEmail	String	100	Optional	Email ID of the customer.
deliverPhoneNumber	String	255	Optional	Contact number of the customer.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Optional	Name of the apartment building/complex in the customer's delivery address.
deliverStreetName	String	255	Optional	Name of the society or street in the customer's delivery address.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location.
deliverLocality	String	512	Optional	Name of the locality or area in the customer's delivery address. This field is optional if the Customer Profiling property is enabled.
deliverCity	String	512	Optional	Name of the city in the customer's delivery address.
deliverState	String	50	Optional	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country.
deliverCountry	String	100	Optional	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system.
deliverPinCode	String	12	Optional	Pin code of the customer's delivery location.
deliverLatitude	Double		Optional	Latitude coordinates of the customer's delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer's delivery address.
				Timezone of the customer's delivery address. This should be as per

deliverAddressTimezone	String		Optional	the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	255	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
returnBranch	String	255	Conditional Mandatory	Name of branch where the order should be returned, if needed. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Optional	Unique identifier associated with the return customer.
returnAccountName	String	255	Optional	Name of the return customer.
returnEmail	String	100	Optional	Email ID of the return customer.
returnPhoneNumber	String	255	Optional	Contact number of the return customer.
returnWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
returnAddressId	String	255	Optional	Identifier assigned to a return customer’s address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer’s return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer’s return address.
returnLandmark	String	512	Optional	Landmark of the customer’s return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer’s return address.
returnCity	String	512	Optional	Name of the city in the customer’s return address.
returnState	String	50	Optional	Name of the state in the customer’s return address. This should be as per the State Codes available in the LogiNext system for the selected country.
returnCountry	String	100	Optional	Name of the country in the customer’s return address. This should be as per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double		Optional	Latitude coordinates of the return address.
				Longitude coordinates of the return address.

returnLongitude	Double		Optional	
returnAWB	String	255	Optional	Air Waybill or AWB number associated with a return order request. If no value is provided, the system considers the existing AWB as the return AWB.
manifestId	String	100	Optional	Unique identifier associated with the manifest.
tripOrderFl	String	50	Optional	Specify ‘Y’ to remove the trip associated with the milestone and change the milestone status to ‘Not Dispatched’, if the customer pickup or delivery address is updated, or ‘N’ to continue the trip associated with the milestone even if the address is updated. If no value is provided, the system considers ‘N’ by default.
autoAllocateFl	String	50	Optional	Whether the order should be considered for auto-assignment or not. Specify 'Y' to consider the order for auto-assignment (i.e., the order will be automatically assigned to nearest delivery associate upon creation) based on the settings configured in the 'Auto Assignment Profile' module. Specify ‘N’ if the order should not be considered for autoassignment, or ‘P’ if you want to assign the newly created order to an existing planned trip. Note that selecting 'P' may affect the sequence of previously assigned orders for that trip.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If no value is provided, the system uses the default profile.

END-TO-END ACCOUNT: UPDATE RECURRING

Sample Request

```
{
    "orderTemplateDetails": {
        "orderTemplateReferenceId":"a8462eb3838d4701bf6182de315c0b14",
        "awbNumber": "435-16685675",
        "shipmentOrderTypeCd": "ALLMILE",
        "orderState": "FORWARD",
        "autoAllocateFl": "N",
        "shipmentOrderDt": "2016-07-15T10:30:00.000Z",
        "distributionCenter": "Down Town Chicago",
        "originBranchName" :"Houston",
        "destinationBranchName" : "Boston",
        "routeConfigurationName": "Houston-Boston",
        "nextBranchName":"Cupertino",
        "nextBranchServiceTime": 5,
        "nextBranchStartTimeWindow" : "2016-07-15T10:30:00.000Z",
        "nextBranchEndTimeWindow": "2016-07-15T10:30:00.000Z",
        "deliveryType": "Groceries",
        "serviceTypeCd": "Economy",
        "packageWeight":"10",
        "packageVolume": "4500",
        "paymentType": "Prepaid",
        "packageValue": "5000",
        "numberOfItems": 1,
        "partialDeliveryAllowedFl": "Y",
        "cancellationAllowedFl": "N",
        "deliverServiceTime": "20",
        "deliverEndTimeWindow": "2016-07-18T10:31:00.000Z",
        "deliverStartTimeWindow": "2016-07-16T10:31:00.000Z",
        "deliveryLocationType":"Home",
        "deliverEmail":"m.richardson@testmail.com",
        "deliverPhoneNumber":"9891234567",
        "deliverWhatsappOptin":"Y",
```

```
        "deliverAccountCode": "Matt001",
        "deliverAddressId": "home",
        "deliverAccountName": "Mathew Richardson",
        "deliverApartment": "201",
        "deliverStreetName": "E Randolph St",
        "deliverLandmark": "Opp. Chiptole",
        "deliverLocality": "Down Town Chicago",
        "deliverCity": "Chicago",
        "deliverState": "IL",
        "deliverCountry": "USA",
        "deliverPinCode": "60602",
        "deliverLatitude": "41.8827",
        "deliverLongitude": "-87.6233",
        "deliverAddressTimezone":"America/Chicago",
        "deliverBranch": "East Manhattan",
        "pickupBranch":"East Manhattan",
        "pickupServiceTime": "50",
        "pickupStartTimeWindow": "2016-07-16T14:24:00.000Z",
        "pickupEndTimeWindow": "2016-07-17T14:24:00.000Z",
        "pickupEmail":"james.w@ablogs.com",
        "pickupPhoneNumber": "5163063377",
        "pickupWhatsappOptin":"Y",
        "pickupAccountCode": "jim001",
        "pickupAddressId": "Home",
        "pickupAccountName": "James Walker",
        "pickupApartment": "901",
        "pickupStreetName": "2142 3rd Ave",
        "pickupLandmark": "Opp. McDonalds",
        "pickupLocality": "East Harlem",
        "pickupCity": "New York",
        "pickupState": "NY",
        "pickupCountry": "USA",
        "pickupPinCode": "10035",
        "pickupLatitude": "40.7957",
        "pickupLongitude": "-73.9389",
        "pickupAddressTimezone":"America/New_York",
        "pickupNotes": "Don't ring the doorbell",
        "deliverNotes": "Leave it with the neighbour",
        "returnBranch": "Route1",
        "returnApartment": "901",
        "returnStreetName": "50 E 78th St",
        "returnLandmark": "Opp. Strand Bookstore",
        "returnLocality": "Upper East Side",
        "returnCity": "New York",
        "returnState": "NY",
        "returnCountry": "USA",
        "returnPinCode": "10035",
        "returnLatitude": "40.7957",
        "returnLongitude": "-73.9389",
        "returnTimezone": "America/Chicago",
        "returnStartTimeWindow": "2025-02-18T13:38:57.849Z",
        "returnEndTimeWindow": "2025-02-18T13:38:57.849Z",
        "returnAWB": "435-16685675-R",
        "returnRouteConfigurationName": "Route1_india_allmile_sandbox Main Branch_1637",
        "clientCode": "Salestap",
        "shipmentCrateMappings": []
    },
    "schedulerDetails": {
        "startDate": "2019-09-23T11:00:00.000Z",
        "endDate": "2019-09-25T15:00:00.000Z",
        "frequency": "DAILY",
        "weekDays":"Tuesday,Thursday",
        "interval": 0,
        "numberOfOccurrences": 1
    }
}
```

Success Response

```
{
    "status": 200,
    "message": "Order template updated successfully",
    "moreResultsExists": false,
    "data": {
        "orderTemplateReferenceId": "d5c2add00b9146beb8fce30b257c0e9d",
        "orderTemplateNumber": "FM_AQWA"
    },
    "hasError": false
}
```

Failure Response

```
{
    "status": 409,
    "message": "Order template update failed",
    "moreResultsExists": false,
    "error": [
        {
            "errorList": [
                {
                    "key": "orderTemplateReferenceId",
                    "message": [
                        "orderTemplateReferenceId is mandatory"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

If you have an End-to-End account, update an existing recurring order using this API.

- This API updates an existing recurring order with the details provided.
- It identifies recurring orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Recurring Order API response when the associated recurring order is created in the system.
- The API accepts the following two objects in its Request Body:
  - orderTemplateDetails: Contains the details of the orders to be updated.
  - schedulerDetails: Defines the frequency and duration of the recurring orders.

API TYPE

- Tier 1 API.

REQUEST

PUT `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/shipment/template/update`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderTemplateReferenceId	String	100	Mandatory	Unique identifier associated with the order template you are updating. This ID is used to identify the order template that you want to update.
awbNumber	String	255	Optional	Air Waybill or AWB number associated with an order.

shipmentOrderTypeCd	String	40	Optional	Specify the order type code such as ‘FM’, ‘LM’, or ‘ALLMILE’ for the order you are updating. This API lets you update First Mile, Last Mile, or ALLMILE orders. 'ALLMILE' orders involve multiple milestones (i.e., legs of movement).
autoAllocateFl	String	50	Optional	Whether the order should be considered for auto-assignment or not. Specify 'Y' to consider the order for auto-assignment (i.e., the order will be automatically assigned to the nearest delivery associate upon creation), ‘N’ if the order should not be considered for auto-assignment, or ‘P’ if you want to assign the newly created order to an existing planned trip. Note that selecting 'P' may affect the sequence of previously assigned orders for that trip.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If no value is provided, the system uses the default profile.
orderState	String	512	Optional	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of order whether the order is in forward state or reverse state. Specify ‘FORWARD’ if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or ‘REVERSE’ if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
shipmentOrderDt	Date		Optional	The date on which you received the order request. Note that the date and time must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
originBranchName	String	255	Optional	Name of the original branch associated with the order.
destinationBranchName	String	255	Optional	Name of the destination branch associated with the order.
routeConfigurationName	String	255	Optional	Route associated with the order.
deliveryType	String	40	Optional	In certain operations, different skill sets or special delivery requirements are needed. For example, groceries or food items must be separated from toiletries orders, or cake orders cannot be combined with flower orders while delivering. In such cases, if you want to classify orders using the Delivery Type, you can use this field to ensure the orders are assigned to delivery associates configured in the LogiNext system with the required skill sets or delivery types. Note that you must define the Skill Sets in the Fleet Configuration module under Settings before passing it here in the orders. Contact your Account Manager to set these values for you. You can pass multiple Skill Sets in a comma-separated format in this API.
serviceTypeCd	String	255	Optional	The type of service that you offer to an order, in terms of how soon the order can be fulfilled. For example, orders with a 'Premium' service type may have shorter SLAs compared to those with a 'Normal' service type. Note that this field is mandatory when creating an 'ALLMILE' order.
distributionCenter	String	255	Optional	Name of the branch whose resources would be servicing the order. The order may have different branches for the pickup and delivery legs, but specify one branch that must oversee the entire order fulfillment.
packageWeight	Double	10,3	Optional	The total weight of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in kilograms, and for the imperial system, it will be in pounds.

packageVolume	Double	10,3	Optional	The total volume of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in cubic centimeters (cc), and for the imperial system, it will be in cubic inches (cu in).
packageLength	Double	10,3	Optional	The total length of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageBreadth	Double	10,3	Optional	The total width of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
packageHeight	Double	10,3	Optional	The total height of the order. The unit of measurement will be the same as specified in the System Preferences module under Settings. For the metric system, this will be in centimeters (cm), and for the imperial system, it will be in inches (in).
priority	String	16	Optional	You can assign a priority to the order as per the values configured in the Order Prioritizing section under the Order Configuration module in Settings. The planning engine will consider the order priority for planning, thereby ensuring that orders with higher priority are assigned accordingly. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
packageValue	Double	10	Optional	Total cost of the order.
numberOfItems	Integer	20	Optional	The total number of items in the order.
paymentType	String	40	Optional	Payment mode of the order. Specify ‘Prepaid’ if the order has already been paid for or ‘Cash On Pickup (COP) or Cash On Delivery (COD)’ if the delivery associate needs to collect cash at the time of pickup/delivery. Note that the payment type depends on the language preference configured for the user account from which the API token was created. Refer to the 'Authenticate' API documentation for more details.
partialDeliveryAllowedFl	String	50	Optional	Whether delivery associates are allowed to deliver the order partially (i.e. hold back specific items in the order in case of any item damage, etc.) or not. Specify ‘Y’ to let your delivery associates mark the order as partially delivered using the LogiNext Driver App, or ‘N’ to prevent partial deliveries. If no value is provided, the system considers ‘Y’ by default.
returnAllowedFl	String	1	Optional	Whether the order is returnable or not. Specify ‘Y’ to allow your customers to initiate a return request post delivery, if needed, or ‘N’ to prevent returns. If no value is provided, the system considers ‘Y’ by default.
cancellationAllowedFl	String	1	Optional	Whether customers are allowed to initiate a cancel order request after placing the order or not. Specify ‘Y’ to enable cancellations or ‘N’ to prevent them. If no value is provided, the system considers ‘Y’ by default.
pickupServiceTime	Integer	11	Optional	Specify the time required to pick up the order at the customer's location.
pickupStartTimeWindow	Date		Optional	The opening time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Pickup time window is the customer’s preferred time slot for the delivery associate to reach the customer's

				location and fulfill the order. Note that the date and time must be in UTC format. For example - 2016-07-15T11:30:00.000Z.
pickupEndTimeWindow	Date		Optional	The closing time of the pickup time window (in YYYY-MM-DDTHH:MM:SS.SSSZ format). Note that the end date and time must be in UTC format. For example - 2016-07-15T12:30:00.000Z.
pickupAccountCode	String	255	Optional	Unique identifier associated with the pickup customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
pickupAccountName	String	255	Optional	Name of the pickup customer.
pickupEmail	String	100	Optional	Email ID of the pickup customer.
pickupPhoneNumber	String	255	Optional	Contact number of the pickup customer. This field is optional if the Customer Profiling property is enabled.
pickupWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
pickupAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
pickupApartment	String	512	Optional	Name of the apartment building/complex in the customer's pickup address.
pickupStreetName	String	255	Optional	Name of the society or street in the customer's pickup address.
pickupLandmark	String	512	Optional	Landmark of the customer's pickup location.
pickupLocality	String	512	Optional	Name of the locality or area in the customer's pickup address.
pickupCity	String	512	Optional	Name of the city in the customer's pickup address. This field is optional if the Customer Profiling property is enabled.
pickupState	String	50	Optional	Name of the state in the customer's pickup address. This should be as per the State Codes available in the LogiNext system for the selected country.
pickupCountry	String	100	Optional	Name of the country in the customer's pickup address. This should be as per the Country Codes available in the LogiNext system.
pickupPinCode	String	12	Optional	Pin code of the customer's pickup location.
pickupLatitude	Double		Optional	Latitude coordinates of the customer's pickup address.
pickupLongitude	Double		Optional	Longitude coordinates of the customer's pickup address.
pickupAddressTimezone	String		Optional	Timezone of the customer's pickup address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.

pickupNotes	String	255	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of pickup.
deliverServiceTime	Integer	11	Optional	Specify the time required to deliver the order at the customer's location.
deliverStartTimeWindow	Date		Optional	The opening time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Delivery time window is the customer's preferred time slot for the delivery associate to reach the customer's location and fulfill the order. Note that the date and time must be in UTC format. For example - 2018-07-01T11:18:00.000Z.
deliverEndTimeWindow	Date		Optional	The closing time of the delivery time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. Note that the end date and time must be in UTC format. For example - 2018-07-01T11:18:00.000Z.
deliveryLocationType	String	40	Optional	Type of customer address, e.g., Residential, Office, etc.
deliverAccountCode	String	255	Optional	Unique identifier associated with the delivery customer. If a new customer has placed the order, you can assign any alphanumeric value as their Customer ID while ensuring that the value entered is unique, i.e., it doesn't belong to any other customer. If an existing customer has placed the order, upon entering the Customer ID, you can fetch several fields.
deliverAccountName	String	255	Optional	Name of the delivery customer.
deliverEmail	String	100	Optional	Email ID delivery of the customer.
deliverPhoneNumber	String	255	Optional	Contact number of the delivery customer.
deliverWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter 'Y' to opt in or 'N' to opt out.
deliverAddressId	String	255	Optional	Identifier assigned to a customer's address. If the Customer Profiling property is enabled, and the customer had provided multiple addresses in the past, each of those addresses will have an individual Address ID. You can enter the Address ID which would fetch the address fields. If this is a new customer, you can provide any unique alphanumeric value as the Address ID.
deliverApartment	String	512	Optional	Name of the apartment building/complex in the customer's delivery address.
deliverStreetName	String	255	Optional	Name of the society or street in the customer's delivery address.
deliverLandmark	String	512	Optional	Landmark of the customer's delivery location.
deliverLocality	String	512	Optional	Name of the locality or area in the customer's delivery address.
deliverCity	String	512	Optional	Name of the city in the customer's delivery address.
deliverState	String	50	Optional	Name of the state in the customer's delivery address. This should be as per the State Codes available in the LogiNext system for the selected country.
deliverCountry	String	100	Optional	Name of the country in the customer's delivery address. This should be as per the Country Codes available in the LogiNext system.

deliverPinCode	String	12	Optional	Pin code of the customer’s delivery location.
deliverLatitude	Double		Optional	Latitude coordinates of the customer’s delivery address.
deliverLongitude	Double		Optional	Longitude coordinates of the customer’s delivery address.
deliverAddressTimezone	String		Optional	Timezone of the customer’s delivery address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
deliverNotes	String	512	Optional	Specify any additional instructions/notes that the delivery associate should follow. These notes will be displayed to the delivery associate when they view this order in the LogiNext Driver App at the time of delivery.
returnBranch	String	255	Conditional Mandatory	Name of branch where the order should be returned, if needed. This field is mandatory if the 'returnAllowedFl' is set to 'Y'. If only 'returnBranch' is specified without 'returnAccountCode' or 'returnAccountName', the system will treat the order as a return-to-branch type of order. However, if both 'returnAccountCode' and 'returnAccountName' are provided, the system will treat it as a return-to-customer/merchant or an RTM (Return to Merchant) type of order.
returnStartTimeWindow	Date		Optional	The opening time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnEndTimeWindow	Date		Optional	The closing time of the return time window in YYYY-MM-DDTHH:MM:SS.SSSZ format. For example - 2016-07-01T11:18:00.000Z.
returnAccountCode	String	255	Optional	Unique identifier associated with the return customer.
returnAccountName	String	255	Optional	Name of the return customer.
returnEmail	String	100	Optional	Email ID of the return customer.
returnPhoneNumber	String	255	Optional	Contact number of the return customer.
returnWhatsappOptin	Boolean		Optional	Whether the customer has opted in to receive WhatsApp alerts and notifications on the provided mobile number or not. Enter ‘Y’ to opt in or ‘N’ to opt out.
returnAddressId	String	255	Optional	Identifier assigned to a return customer’s address.
returnApartment	String	512	Optional	Name of the apartment building/complex in the customer’s return address.
returnStreetName	String	255	Optional	Name of the society or street in the customer’s return address.
returnLandmark	String	512	Optional	Landmark of the customer’s return location.
returnLocality	String	512	Optional	Name of the locality or area in the customer’s return address.
returnCity	String	512	Optional	Name of the city in the customer’s return address.
returnState	String	50	Optional	Name of the state in the customer’s return address. This should be as per the State Codes available in the LogiNext system for the selected country.
				Name of the country in the customer’s return address. This should be as

returnCountry	String	100	Optional	per the Country Codes available in the LogiNext system.
returnPinCode	String	12	Optional	Pin code of the return location.
returnLatitude	Double		Optional	Latitude coordinates of the return address.
returnLongitude	Double		Optional	Longitude coordinates of the return address.
returnTimezone	String		Optional	Timezone of the customer's return address. This should be as per the Timezone Codes available in the LogiNext system. If you do not provide the timezone, the system will consider the default timezone configured for your branch.
returnAWB	String	255	Optional	Air Waybill or AWB number associated with a return order request. If not provided, the system will consider the existing AWB as the return AWB.
clientCode	String	32	Optional	Name of the shipper's company associated with the order. Pass the company name of the shipper's account if you want to create an order on behalf of one of your shippers.
schedulerDetails	Object		Optional	Within this parameter, enter the scheduler details, such as the start date, end date, and other relevant details for generating orders based on this template.
startDate	DateTime		Optional	Start date and time from which order instances for this template should be created.
endDate			Optional	End date and time until which order instances for this template should be created. If no value is provided, the API will generate only one instance of the order using this template.
frequency	String		Optional	Frequency of order occurrences using this template. Specify the value 'DAILY' for daily recurrence, 'WEEKLY' for weekly recurrence, 'MONTHLY' for monthly recurrence, or 'CUSTOM' for a specific recurrance pattern, such as every other day. This field is required if 'weekDays' is not provided.
weekDays	String		Optional	Name of the day(s) in a week for which order occurances should be created using this template. You can enter multiple days in a comma-separated format. This field is mandatory when the 'frequency' is set to 'CUSTOM'.
numberOfOccurrences	Number		Optional	Number of times this order template should occur.
interval	Number		Optional	Interval at which orders should be created using this template. For example, to create order occurrences every two weeks, use this field in conjunction with a 'WEEKLY' frequency.

UPDATE STATUS

Sample Request

```
{
 "newStatus":"NOTDELIVERED",
 "orderDetails":
 [{
   "orderReferenceId":"6186d5fc6e324c42abb5ea1a32e05f66",
   "recipientName": "Rahul",
   "customerComment": "User comments",
   "reasonCd":"DBUNAVAILABLE",
```

```
    "otherReason":"",
    "latitude": 40.760838,
    "longitude": 74.910214,
    "updateTime":"2016-07-18T10:31:00.000Z"
  },
  {
    "orderReferenceId":"6186d7r5te324c42abb5ea1a32x45f66",
    "reasonCd":"DBUNAVAILABLE",
    "otherReason":"",
    "latitude": 40.760838,
    "longitude": 74.913214,
    "updateTime":"2016-07-18T10:31:00.000Z"

  },
  {
    "orderReferenceId":"6156ty46e324c42abb5ea1a32y45f66",
    "reasonCd":"Other",
    "otherReason":"Technical Issues",
    "latitude": 40.760838,
    "longitude": 74.910321,
    "updateTime":"2016-07-18T10:31:00.000Z"

  }]

}
```

Success Response

```
{
  "status": 200,
  "message": "Status updated successfully",
  "hasError": false
}
```

Update the status of an existing order using this API.

- This API updates the status of an existing order with the status provided.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.

API TYPE

- Tier 2 API.
- You can update the status of multiple orders and pass the relevant parameters for each order in one call of this API.

REQUEST

PUT `https://api.loginextsolutions.com/ShipmentApp/mile/v1/update/status`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
newStatus	String	20	Mandatory	Update multiple orders with a single status. The orders will be updated with the provided status. Below are the statuses: PICKEDUP - When an order is picked up by the delivery associate. DELIVERED - When an order is delivered by the delivery associate. NOTPICKEDUP - When the delivery associate reached the pick-up location, but could not pick up the order due to some reason. NOTDELIVERED - When the delivery associate reached the delivery location, but could not deliver the order due to some reason. NOTDISPATCHED - When the order has still not been dispatched.
				Unique reference identifier associated with the order. This ID is used to identify

orderReferenceId	String	100	Mandatory	the order whose status you want to update. This is generated when the order is created in the LogiNext system.
reasonCd	String	255	Conditional Mandatory	Specify the reason for updating the order status. This field is mandatory depending on the selected order status (e.g., NOTDELIVERED, NOTPICKEDUP, CANCELLED, or NOTDISPATCHED); otherwise, it is optional. If you have pre-configured reasons for these order status in the LogiNext system, it is mandatory to specify the relevant configured reason here. One of the available options is 'Other' in case the delivery associate selects the reason as 'Others' in the Driver App.
otherReason	String	255	Conditional Mandatory	Specify the reason for updating the order status. This field is mandatory when ‘reasonCd’ is specified as ‘Others’.
latitude	Double	15	Conditional Mandatory	Latitude coordinates where the order status is updated. For example - '17.996'.
longitude	Double	15	Conditional Mandatory	Longitude coordinates where the order status is updated. For example - '17.996'.
updateTime	Date	15	Conditional Mandatory	Timestamp (in UTC format) when the order status is updated. This cannot be greater than the time when the API is called. If no value is provided, the timestamp of the API call will be used as the timestamp for the status change.
recipientName	String	255	Optional	Name of the person who has received the order.
customerComment	String	255	Optional	Feedback comments from the customer.
customerRating	Integer	10	Optional	Feedback ratings from the customer.

Status	Not Dispatched	Intransit	Picked Up	Delivered	Attempted	Cancelled
Not Dispatched	No	No	Yes	Yes	Yes	Yes
Intransit Before Trip Stop	No	No	Yes	Yes	Yes	Yes
Picked Up	No	No	No	Yes	Yes	Yes
Intransit order marked Delivered	Yes	No	No	No	Yes	Yes
NOT DISPTACHED order marked Delivered	Yes	No	No	No	Yes	Yes
Intransit order marked Attempted	Yes	No	No	Yes	No	Yes
NOT DISPTACHED order marked Attempted	Yes	No	No	Yes	No	Yes
Intransit order marked Cancelled	Yes	No	No	Yes	Yes	No
NOT DISPTACHED order marked Cancelled	Yes	No	No	Yes	Yes	No

END-TO-END ACCOUNT: UPDATE STATUS

Sample Request

```
{
  "newStatus":"DELIVERED",
  "orderDetails":
  [{
    "orderReferenceId":"6186d5fc6e324c42abb5ea1a32e05f66",
    "latitude": 40.760838,
```

```
    "longitude": 74.910214,
    "updateTime":"2020-07-18T10:31:00.000Z"
  },
  {
    "orderReferenceId":"6186d7r5te324c42abb5ea1a32x45f66",
    "latitude": 40.760838,
    "longitude": 74.913214,
    "updateTime":"2020-07-18T10:31:00.000Z"

  },
  {
    "orderReferenceId":"6156ty46e324c42abb5ea1a32y45f66",
    "latitude": 40.760838,
    "longitude": 74.910321,
    "updateTime":"2020-07-18T10:31:00.000Z"

  }]

}
```

Success Response

```
{
  "status": 200,
  "message": "Status updated successfully",
  "hasError": false
}
```

If you have an End-to-End account, update the status of an existing order using this API.

- This API updates the status of an existing order with the status provided.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.

API TYPE

- Tier 2 API.
- You can update the status of multiple orders and pass the relevant parameters for each order in one call of this API.

REQUEST

PUT `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/shipment/update/orderstatus`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
newStatus	String	20	Mandatory	Update multiple orders with a single status. The orders will be updated with the provided status. Below are the statuses: DELIVERED - When an order is delivered by the delivery associate. CANCELLED - When the order is cancelled.
orderReferenceId	String	100	Conditional Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order whose status you want to update. This is generated when the order is created in the LogiNext system. This field is mandatory, if 'orderNo' is not provided.
orderNo	String		Conditional Mandatory	Unique number of the order whose status you want to update. This field is mandatory, if 'orderReferenceId' is not provided.
reasonCd	String	255	Conditional	Specify the reason for updating the order status. This field is mandatory depending on the selected order status (e.g., CANCELLED); otherwise, it is optional. If you have pre-configured reasons for CANCELLED order status in the

			Mandatory	LogiNext system, it is mandatory to specify the relevant configured reason here. One of the available options is 'Other' in case the delivery associate selects the reason as 'Others' in the Driver App.
otherReason	String	255	Conditional Mandatory	Specify the reason for updating the order status. This field is mandatory when ‘reasonCd’ is specified as ‘Others’.
latitude	Double	15	Conditional Mandatory	Latitude coordinates where the order status is updated. For example - '17.996'.
longitude	Double	15	Conditional Mandatory	Longitude coordinates where the order status is updated. For example - '17.996'.
updateTime	Date	15	Conditional Mandatory	Timestamp (in UTC format) when the order status is updated. This cannot be greater than the time when the API is called. If no value is provided, the timestamp of the API call will be used as the timestamp for the status change.

END-TO-END ACCOUNT: UPDATE MILESTONE STATUS

Sample Request

```
{
  "newStatus":"NOTDELIVERED",
  "orderDetails":
  [{
    "orderReferenceId":"6186d5fc6e324c42abb5ea1a32e05f66",
    "reasonCd":"DBUNAVAILABLE",
    "otherReason":"",
    "latitude": 40.760838,
    "longitude": 74.910214,
    "updateTime":"2016-07-18T10:31:00.000Z"
  },
  {
    "orderReferenceId":"6186d7r5te324c42abb5ea1a32x45f66",
    "reasonCd":"DBUNAVAILABLE",
    "otherReason":"",
    "latitude": 40.760838,
    "longitude": 74.913214,
    "updateTime":"2016-07-18T10:31:00.000Z"

  },
  {
    "orderReferenceId":"6156ty46e324c42abb5ea1a32y45f66",
    "reasonCd":"Other",
    "otherReason":"Technical Issues",
    "latitude": 40.760838,
    "longitude": 74.910321,
    "updateTime":"2016-07-18T10:31:00.000Z"

  }]

}
```

Success Response

```
{
  "status": 200,
  "message": "Status updated successfully",
  "hasError": false
}
```

If you have an End-to-End account, update the status of current or upcoming milestones associated with the order using this API.

- This API updates the status of current or upcoming milestones associated with the order with the status provided.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.

API TYPE

- Tier 2 API.
- This API does not support partial success responses. If you include multiple IDs in a single request and even one fails validation, the entire batch will be considered as a failed request.
- You can update the status of multiple milestones and pass the relevant parameters for each order in one call of this API.

REQUEST

PUT `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/shipment/update/milestonestatus`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
newStatus	String	20	Mandatory	New status of the current or upcoming milestones that you want to update instead of the previous one.
orderReferenceId	String	100	Conditional Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order whose current or upcoming milestone status you want to update. This field is mandatory, if ‘orderNo’ is not provided.
orderNo	String		Conditional Mandatory	Unique number of the order whose current or upcoming milestone status you want to update. This field is mandatory, if ‘orderReferenceId’ is not provided.
reasonCd	String	255	Conditional Mandatory	Specify the reason for updating the milestone status. This field is mandatory depending on the selected milestone status (e.g., NOTDELIVERED, NOTPICKEDUP, CANCELLED, or NOTDISPATCHED); otherwise, it is optional. If you have pre-configured reasons for these milestone status in the LogiNext system, it is mandatory to specify the relevant configured reason here. One of the available options is 'Other' in case the delivery associate selects the reason as 'Others' in the Driver App.
otherReason	String	255	Conditional Mandatory	Specify the reason for updating the milestone status. This field is mandatory when ‘reasonCd’ is specified as ‘Others’.
latitude	Double	15	Conditional Mandatory	Latitude coordinates where the milestone status is updated. For example - '17.996'.
longitude	Double	15	Conditional Mandatory	Longitude coordinates where the milestone status is updated. For example - '17.996'.
updateTime	Date	15	Conditional Mandatory	Timestamp (in UTC format) when the milestone status is updated. This cannot be greater than the time when the API is called. If no value is provided, the timestamp of the API call will be used as the timestamp for the status change.

Current Status of ongoing/upcoming Milestone	Not Dispatched	Intransit	Picked Up	Delivered	Attempted	Cancelled
Not Dispatched	No	No	Yes	Yes	Yes	Yes
Intransit Before Trip Stop	No	No	Yes	Yes	Yes	Yes
Picked Up	No	No	No	Yes	Yes	Yes
Intransit order marked Delivered	Yes	No	No	No	Yes	Yes

NOT DISPTACHED order marked Delivered	Yes	No	No	No	Yes	Yes
Intransit order marked Attempted	Yes	No	No	Yes	No	Yes
NOT DISPTACHED order marked Attempted	Yes	No	No	Yes	No	Yes
Intransit order marked Cancelled	Yes	No	No	Yes	Yes	No
NOT DISPTACHED order marked Cancelled	Yes	No	No	Yes	Yes	No

UPDATE CRATE / LINE ITEM

Sample Request

```
{
  "referenceId": "ae9a2eed3fc54784905345f9c71b9e5f",
  "shipmentCrates": [
    {
      "crateCd": "00009595951000000492",
      "shipmentlineitems": [
        {
          "itemCd": "1_120000256",
          "itemName": "Bourbon",
          "itemPrice": 12,
          "itemQuantity": 12,
          "itemType": "Biscuit",
          "itemWeight": 50
        }
      ]
    },
    {
      "crateCd": "00009595951000000490",
      "shipmentlineitems": [
        {
          "itemCd": "1_120000244",
          "itemName": "Noodles Chicken 50 Gm",
          "itemPrice": 12,
          "itemQuantity": 3,
          "itemType": "Soup",
          "itemWeight": 30
        },
        {
          "itemCd": "1_120000243",
          "itemName": "Silk Chocolate",
          "itemPrice": 12,
          "itemQuantity": 5,
          "itemType": "Chocolate",
          "itemWeight": 25
        }
      ]
    }
  ]
}
```

Success Response

```
{
  "status": 200,
  "message": "success",
  "hasError": false
}
```

Update the Crates and/or Line Items of an existing order using this API.

- This API updates the Crates and/or Line Items of an existing order based on the details provided.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.
- For this API to work, the order status must be 'Not Dispatched' or 'Intransit', and the crate status must be 'PACKED'.
- You can use this API to add new crates and line items or update existing ones. For example,
  - If you have an order with crate A and crate B and you want to add a new crate C, you only need to pass the information for crate C. Once you receive a success response, the order will now consist of crates A, B, and C.
  - Alternatively, if you have an order with crate A and crate B and you need to update crate A, call this API with ‘crateCd’ parameter set to 'A' and update the properties for that crate.
- Note that this API does not delete existing crates.

API TYPE

- Tier 1 API.
- You can pass multiple crates and line items in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v1/updateCrates`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceId	String	100	Conditional Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order whose crates and/or line items you want to create/update.
shipmentCrates	Array of objects		Optional	Specify the crate details of the order. In case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrates.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating/updating.
shipmentCrates.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrates.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrates.noOfUnits	Integer	10	Optional	Total number of crates in the order.
shipmentCrates.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating/updating.
shipmentCrates.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrates.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrates.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrates.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrates.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item.

END-TO-END ACCOUNT: UPDATE CRATE / LINE ITEM

Sample Request

```
{
  "referenceId": "ae9a2eed3fc54784905345f9c71b9e5f",
  "orderCrates": [
    {
      "crateCd": "00009595951000000492",
      "crateAmount" : "200",
      "crateType": "Grocery",
      "noOfUnits" : 1,
      "orderlineitems": [
        {
          "itemCd": "1_120000256",
          "itemName": "Bourbon",
          "itemPrice": 12,
          "itemQuantity": 12,
          "itemType": "Biscuit",
          "itemWeight": 50
        }
      ]
    },
    {
      "crateCd": "00009595951000000490",
      "crateAmount" : "200",
      "crateType": "Grocery",
      "noOfUnits" : 1,
      "orderlineitems": [
        {
          "itemCd": "1_120000244",
          "itemName": "Noodles Chicken 50 Gm",
          "itemPrice": 12,
          "itemQuantity": 3,
          "itemType": "Soup",
          "itemWeight": 30
        },
        {
          "itemCd": "1_120000243",
          "itemName": "Silk Chocolate",
          "itemPrice": 12,
          "itemQuantity": 5,
          "itemType": "Chocolate",
          "itemWeight": 25
        }
      ]
    }
  ]
}
```

Success Response

```
{
  "status": 200,
  "message": "success",
  "hasError": false
}
```

If you have an End-to-End account, update the Crates and/or Line Items of an existing order using this API.

- This API updates the Crates and/or Line Items of an existing order based on the details provided.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.

- For this API to work, the order status must be 'Not Dispatched' and the crate status must be 'PACKED'.
- You can use this API to add new crates and line items or update existing ones. For example,
  - If you have an order with crate A and crate B and you want to add a new crate C, you only need to pass the information for crate C. Once you receive a success response, the order will now consist of crates A, B, and C.
  - Alternatively, if you have an order with crate A and crate B and you need to update crate A, call this API with 'crateCd' parameter set to 'A' and update the properties for that crate.
- Note that this API does not delete existing crates.

API TYPE

- Tier 1 API.
- You can pass multiple crates and line items in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/order/updateCrates`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceId	String	100	Conditional Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order whose crates and/or line items you want to create/update.
orderCrates	Array of objects		Optional	Specify the crate details of the order. In case of multiple items in a single order, you can bundle similar items together in one crate and allocate multiple crates, as required.
shipmentCrates.crateCd	String	128	Mandatory	Unique identifier for the crate you are creating/updating.
shipmentCrates.crateAmount	Double		Optional	Cost applicable for the crate.
shipmentCrates.crateType	String	100	Optional	Type of the crate. For example, a spill-proof type of crate would be ideal for liquid or semi-liquid items during transportation.
shipmentCrates.noOfUnits	Integer	10	Optional	Total number of crates in the order.
shipmentCrates.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier for the item you are creating/updating.
shipmentCrates.shipmentlineitems.itemName	String	255	Optional	Name of the item.
shipmentCrates.shipmentlineitems.itemPrice	Double		Mandatory	Cost applicable for the item.
shipmentCrates.shipmentlineitems.itemQuantity	Double	10	Mandatory	Total number of items.
shipmentCrates.shipmentlineitems.itemType	String	100	Optional	Type of items. You can specify the category of each item to sort them easily. For example, you can create an Item Type as Beverages.
shipmentCrates.shipmentlineitems.itemWeight	Double	10	Optional	Weight of the item.

DELETE CRATE / LINE ITEM

Sample Request

```
[{
```

```
  "referenceId": "njkgfajsdyugaiysud",
  "shipmentCrates": [
    {
      "crateCd": "crate1"
    },
    {
      "crateCd": "crate3",
      "shipmentlineitems": [
        {
          "itemCd": "item001"
        },
        {
          "itemCd": "item002"
        }
      ]
    }
  ]
}]
```

Success Response

```
{
  "status": 200,
  "message": "Deletion successful",
  "hasError": false
}
```

Failure Response: Incorrect Crate ID

```
{
"status": 409,
"message": "Request Error",
"moreResultsExists": false,
"error": [
{
    "index": 0,
    "referenceId": "65ba00dbdcf04fb789311df6aa40e3ba",
    "orderNo": "order1",
    "errorList": [
        {
            "key": "deleteCrateCd",
            "message": [
                "Crates - Crate1, Crate2 are invalid."
            ],
            "errorCode": 12123,
        }
    ]
}
],
"hasError": true
}
```

Failure Response: Incorrect Line Items

```
{
"status": 409,
"message": "Request Error",
"moreResultsExists": false,
"error": [
{
```

```
    "index": 0,
    "referenceId": "65ba00dbdcf05fb789311df6aa40e3be",
    "orderNo": "order1",
    "crateCd": "Crate1",
    "errorList": [
        {
            "key": "deleteLineItem",
            "message": [
                "LineItems {itemcd_s} are invalid."
            ],
            "errorCode": 12136
        }
    ]
}
],
"hasError": true
}
```


Delete the Crates and/or Line Items from an existing order using this API.

- This API deletes a Crate and/or Line Item from an existing order.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.
- For example:
  - Crate Deletion - If an existing order consists of two crates, Crate A and Crate B, and you want to delete Crate B, call this API and provide the necessary details of Crate B in the Request Body. Once you receive a success response, the order will now only contain Crate A.
  - Line Item Deletion - If an existing order consists of Crate A and Crate B, each with one line item, and you want to delete the line item from Crate B, call this API and provide the necessary details of Crate B and its line item in the Request Body. Once you receive a success response, the order will now only contain Crate A with one line item and Crate B with no line item.

API TYPE

- Tier 1 API.
- Client Rate Limit: 5 requests per second.
- Branch Rate Limit: 1 request per second.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v1/deleteCratesAndLineItems`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceId	String	128	Conditional Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order whose crate and/or line item you want to delete. This field is mandatory, if 'orderNo' is not provided.
orderNo	String	128	Conditional Mandatory	Unique number of the order whose crate and/or line item you want to delete. This field is mandatory, if 'referenceId' is not provided.
shipmentCrates	Array of objects		Mandatory	Specify the crate details of the order.
shipmentCrates.crateCd	String	128	Mandatory	Unique identifier of the crate you want to delete.
shipmentlineitems	Array of objects		Mandatory	Specify the item details for the crate in the order.
			Conditional	

shipmentCrates.shipmentlineitems.itemCd	String	200	Mandatory	Unique identifier of the item you want to delete.

END-TO-END ACCOUNT: DELETE CRATE / LINE ITEM

Sample Request

```
{
  "referenceId": "njkgfajsdyugaiysud",
  "shipmentCrates": [
    {
      "crateCd": "crate1"
    },
    {
      "crateCd": "crate3",
      "shipmentlineitems": [
        {
          "itemCd": "item001"
        },
        {
          "itemCd": "item002"
        }
      ]
    }
  ]
}
```

Success Response

```
{
  "status": 200,
  "message": "Deletion successful",
  "hasError": false
}
```

Failure Response: Incorrect Crate ID

```
{
"status": 409,
"message": "Request Error",
"moreResultsExists": false,
"error": [
{
    "index": 0,
    "referenceId": "65ba00dbdcf04fb789311df6aa40e3ba",
    "orderNo": "order1",
    "errorList": [
        {
            "key": "deleteCrateCd",
            "message": [
                "Crates - Crate1, Crate2 are invalid."
            ],
            "errorCode": 12123,
        }
    ]
}
],
"hasError": true
}
```

Failure Response: Incorrect Line Items


```
{
"status": 409,
"message": "Request Error",
"moreResultsExists": false,
"error": [
{
    "index": 0,
    "referenceId": "65ba00dbdcf05fb789311df6aa40e3be",
    "orderNo": "order1",
    "crateCd": "Crate1",
    "errorList": [
        {
            "key": "deleteLineItem",
            "message": [
                "LineItems {itemcd_s} are invalid."
            ],
            "errorCode": 12136
        }
    ]
}
],
"hasError": true
}
```


Delete the Crates and/or Line Items from an existing order for an End-to-End account using this API.

- This API deletes a Crate and/or Line Item from an existing order in an End-to-End account in the LogiNext system.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.
- For example:
    - Crate Deletion - If an existing order consists of two crates, Crate A and Crate B, and you want to delete Crate B, call this API and provide the necessary details of Crate B in the Request Body. Once you receive a success response, the order will now only contain Crate A.
    - Line Item Deletion - If an existing order consists of Crate A and Crate B, each with one line item, and you want to delete the line item from Crate B, call this API and provide the necessary details of Crate B and its line item in the Request Body. Once you receive a success response, the order will now only contain Crate A with one line item and Crate B with no line item.

API TYPE

- Tier 1 API.
- Client Rate Limit: 5 requests per second.
- Branch Rate Limit: 1 request per second.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/order/deleteCratesAndLineItems`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceId	String	128	Conditional Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order whose crate and/or line item you want to delete. This field is mandatory, if 'orderNo' is not provided.
orderNo	String	128	Conditional Mandatory	Unique number of the order whose crate and/or line item you want to delete. This field is mandatory, if 'referenceId' is not provided.
	Array of			

shipmentCrates	objects		Mandatory	Specify the crate details of the order.
shipmentCrates.crateCd	String	128	Mandatory	Unique identifier of the crate you want to delete.
shipmentlineitems	Array of objects		Mandatory	Specify the item details for the crate in the order.
shipmentCrates.shipmentlineitems.itemCd	String	200	Conditional Mandatory	Unique identifier of the item you want to delete.

ASSIGN

Sample Request

```
{
  "trip":{
    "referenceId":"879098765678909876a87656s"
  },
  "deliveryMedium":{
    "identifier":"employeeId",
    "identifierValue":"77381"
  },
  "orderReferenceIds":["87678909876aa987659876sa","9876789asd98765456712"]
}
```

Success Response

```
{
    "status": 200,
    "message": "Order(s) Assigned Successfully!",
    "hasError": false
}
```

Failure Response

```
{
   "status": 409,
   "message": "Assignment Failed",
   "moreResultsExists": false,
   "error": {
       "order": [
           {
               "key": "orderReferenceIds",
               "message": [
                   "Order Reference ID is invalid"
               ]
           }
       ]
   },
   "hasError": true
}
```

Assign the orders to a specific trip of your choice using this API.

- This API manually assigns or reassigns an order to a specific trip or designated delivery associate.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.
- The API accepts the trip or delivery associate details and the list of orders to be added to that trip. It can be used in the following two

ways:
- If you provide the trip details (via Trip Reference ID), then the delivery associate details are not required. The orders will be added to that trip, regardless of whether the trip has started or not. All other order and trip validations will remain the same.
- If trip details are not provided, the delivery associate details must be passed, either through a Username or Employee ID (unique identifiers), along with a control flag identifying which of these values is being used. The orders will then be added to the delivery associate's default trip, whether started or not.

API TYPE

- Tier 2 API.
- The API will return 'Order Reference ID is invalid' in the following scenarios:
  - Order Reference ID doesn't exist for the client.
  - Order is already dispatched.
  - Order is cancelled.
  - Order has reached a terminal status (Not Completed, Completed).

REQUEST

PUT `https://api.loginextsolutions.com/ShipmentApp/mile/v1/manual/assign`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
trip.referenceId	String	32	Conditional Mandatory	Unique reference identifier of a trip to which you want to assign the order. This field is mandatory, if 'deliveryMedium.identifier' is not provided.
deliveryMedium.identifier	String	32	Conditional Mandatory	Unique identifier associated with the delivery associate. This is used to identify and retrieve the delivery associate details to whom you want to assign the orders. Fields such as 'employeeId', 'phoneNumber', and 'userName' are retrieved using this identifier. This field is mandatory, if 'trip.referenceId' is not provided.
deliveryMedium.identifierValue	String	32	Conditional Mandatory	This field contains the delivery associate details to whom you want to assign the order, based on the flag set above. For example, to assign an order to a delivery associate with an 'employeeId' of 'John1', you would specify 'employeeId' in the 'identifier' field and 'John1' in the 'identifierValue' field.
orderReferenceIds	List		Mandatory	Unique reference identifier of the order you want to assign to the specified trip.

UNASSIGN

Sample Request

```
https://api.loginextsolutions.com/ShipmentApp/mile/v1/manual/unassign?referenceId=6186d5fc6e324c42abb5ea1a32e05f66
```

Success Response


```
{
    "status": 200,
    "message": "Unassignment Successful",
    "moreResultsExists": false,
    "data": {
        "orderReferenceId": "7d7527b351e74159adb05abe9529b0a9",
        "tripReferenceId": "ac4de0a72fa6421e83e00acaeb391d26",
        "deliveryMediumReferenceId": "a2fd9619be204195b8995539e9a946fb",
        "tripStatus": "NOTSTARTED"
    },
    "hasError": false
```

```
}
```

Failure Response

```
{
    "status": 409,
    "message": "Unassignment Failed",
    "moreResultsExists": false,
    "data": {
        "message": "Order Reference Id is invalid",
        "orderReferenceId": "2d971c78f3f1431c91d9ad76db90202b"
    },
    "hasError": true
}
```

Unassign a ‘Not Delivered’ order from a ‘Started’ or ‘Not Started’ trip using this API.

- This API unassigns orders from a trip.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.
- The API accepts a single Order Reference ID and checks if the order is currently assigned to a trip. If yes, it will then verify whether the order is marked as delivered. If the order is not yet marked as 'Delivered,' it will be unassigned from the trip and set to 'Not Dispatched'. The order can then be assigned to another trip, as needed.
- Note that this API will not update the ETAs of other orders in the trip after unassigning the current order, nor will it resequence the remaining orders. To revise ETAs and resequence the orders in a trip, you will need to call the Replan API.

API TYPE

- Tier 2 API.
- The API accepts only one Order Reference ID in one call of this API.

REQUEST

PUT `https://api.loginextsolutions.com/ShipmentApp/mile/v1/manual/unassign`

REQUEST PARAMETER

Parameter	Datatype	Length	Required	Description
referenceId	String	32	Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order that needs to be unassigned from the trip.

CANCEL V2

Sample Request

```
{
  "orderReferenceIds":[
     "9b37e12b3io04aa9b55556cea0b57311",
     "40899fd17f19442f86d9c5cda0h2ed90"
  ],
  "orders":[
     {
        "orderNo":"ORD12345",
        "orderState":"FORWARD",
        "clientCode":"MyKart",
        "shipmentOrderTypeCd":"PICKUP"
     },
     {
        "orderNo":"ORD134546",
        "orderState":"FORWARD",
        "clientCode":"Ship Logistics",
```

```
        "shipmentOrderTypeCd":"PICKUP"
      }
    ]
  }
```


Success Response


```
{
  "status":200,
  "message":"Order(s) cancelled successfully",
  "data":[
    {
      "index":0,
      "referenceId":"6a34c7274df0489f97c0f891514b488b",
      "orderNo":"ww1223",
      "shipmentOrderTypeCd":"PICKUP",
      "orderState":"FORWARD",
      "clientCode":"MyKart"
    },
    {
      "index":1,
      "referenceId":"a0108f976b3b41f1b51e438d4e8c7bf5",
      "orderNo":"ww1225",
      "shipmentOrderTypeCd":"PICKUP",
      "orderState":"FORWARD",
      "clientCode":"Ship Logistics"
    }
  ],
  "hasError":false
}
```


Partial Success Response


```
{
  "status":207,
  "message":"Order(s) cancelled partially",
  "data":[
    {
      "index":0,
      "referenceId":"b032f3e9397343ba817896370b92d592",
      "orderNumber":"ww1220",
      "shipmentOrderTypeCd":"DELIVER",
      "orderState":"FORWARD",
      "clientCode":"MyKart"
    },
    {
      "index":1,
      "referenceId":"af7065ad4f3945a8896525c323aa7b68",
      "orderNumber":"ww1244",
      "shipmentOrderTypeCd":"DELIVER",
      "orderState":"FORWARD",
      "clientCode":"Ship Logistics"
    },
    {
      "index":2,
      "referenceId":"a4e6dc610c854196m7957b9876aa4ce5",
      "orderNumber":"ww1234",
      "shipmentOrderTypeCd":"DELIVER",
      "orderState":"FORWARD",
      "clientCode":"MyKart"
    }
  ],
```

```
  "error":[
    {
      "index":3,
      "orderNo":"ww1229",
      "orderState":"FORWARD",
      "shipmentOrderTypeCd":"DELIVER",
      "clientCode":"Ship Logistics",
      "errorList":[
        {
          "key":"clientCode",
          "message":"Shipper is invalid",
          "errorCode":12095
        },
        {
          "key":"shipmentOrderTypeCd",
          "message":"Order Type is invalid",
          "errorCode":12006
        },
        {
          "key":"orderState",
          "message":"Order State is invalid",
          "errorCode":12004
        }
      ]
    }
  ],
  "hasError":true
}
```


Failure Response: Validation Error


```
{
  "status":409,
  "message":"Order(s) couldn't be cancelled",
  "moreResultsExists":false,
  "error":[
    {
      "index":0,
      "orderReferenceId":"f032f3e89797343ba817896370b92d592",
      "orderNo":"TFC003",
      "orderState":"FORWARD",
      "shipmentOrderTypeCd":"PICKUP",
      "clientCode":"MyKart",
      "errorList":[
        {
          "key":"clientCode",
          "message":"Shipper is invalid",
          "errorCode":12095
        },
        {
          "key":"shipmentOrderTypeCd",
          "message":"Order Type is invalid",
          "errorCode":12006
        },
        {
          "key":"orderState",
          "message":"Order State is invalid",
          "errorCode":12004
        }
      ]
    }
  ],
  "hasError":true
}
```

Failure Response: The orderReferenceIds list is empty.

```
{
    "status": 409,
    "message": "No orders exist for given orderReferenceIds.",
    "moreResultsExists": false,
    "hasError": true
}
```

Failure Response: The orders list is empty.

```
{
    "status": 409,
    "message": "No orders exist.",
    "moreResultsExists": false,
    "hasError": true
}
```

Cancel an order using this API.

- This API cancels the specific orders created in the LogiNext system.
- This API allows you to cancel orders only if the 'cancellationAllowedFl' field is set to 'Y' during order creation. If you attempt to cancel an order with 'cancellationAllowedFl' set to 'N', the API will return an error response.
- Note that if both the 'orderReferenceIds' and 'orders' fields are provided, only the 'orderReferenceIds' field will be considered.

API TYPE

- Tier 2 API.
- This API supports batch operation.
- This API supports partial success response.

REQUEST

PUT `https://api.loginextsolutions.com/ShipmentApp/mile/v2/cancel`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderReferenceIds	List		Conditional Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order that needs to be cancelled. This field is mandatory, if 'orders' is not provided.
orders	List		Conditional Mandatory	Unique reference identifier of orders that you want to cancel. This field is mandatory, if 'reference_ids' is not provided.
orders.orderNo	String		Conditional Mandatory	Unique identifier of the order you want to cancel. This field is mandatory, if 'Orders' is provided.
orders.orderState	String		Optional	State of the order. For example - FORWARD. If not provided, the latest identified order will be considered for cancellation.
orders.clientCode	String		Optional	Name of the company associated with the shipper's account. If not provided, the latest identified order will be considered for cancellation.
orders.shipmentOrderTypeCd	String		Optional	Order type code associated with the order. Specify 'BOTH' for pickup and delivery leg order. If not provided, the latest identified order will be considered for cancellation.

GET EPOD AND ESIGN

Sample Request

```
https://api.loginextsolutions.com/ShipmentApp/mile/v2/epod/list?orderReferenceId=5e7a0f2804f14cd591a4740dfc7abdf1
```

Success Response

```
{
    "status": 202,
    "message": "EPOD-ESign request received successfully",
    "requestId": "fb82b48ba4c44370b48c04dc168f0e68",
    "moreResultsExists": false,
    "hasError": false
}
```

Failure Response

```
{
  "status": 409,
  "message": "Order referenceId does not exist",
  "moreResultsExists": false,
  "hasError": true
}
```

Download the EPOD (Electronic Proof of Delivery) and E-Sign for a specific order using this API.

- This API downloads the EPOD and E-Sign for a specific order.
- The API responds with a 202 success response and provides a unique Request ID for tracking.
- Once the images are retrieved, a webhook is triggered containing a URL link to download the EPOD and E-Sign images. This webhook also includes the same request ID to confirm which order the images belong to.
- Accessing the URL provided in the webhook will download a compressed ZIP file containing the EPOD and E-Sign documents for the requested order.
- Note:
  - The URL in the webhook is valid for 7 days. It is recommended to download the files within one hour of receiving the webhook to ensure timely access.
  - All date and time data must be provided in UTC.

API TYPE

- Tier 2 API.
- This API does not support batch operations, i.e., you can only provide one Order Number or Order Reference ID in one call of this API.

REQUEST

GET `https://api.loginextsolutions.com/ShipmentApp/mile/v2/epod/list`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderNo	String	40	Conditional Mandatory	Unique identifier of the order. This is used to identify the order for which you want to retrieve the EPOD/ESign. This field is mandatory, if 'orderReferenceId' is not provided.
orderReferenceId	String	32	Conditional Mandatory	Unique reference identifier generated by the system, associated with the specific order. This ID is used to identify the order for which you want to retrieve the EPOD/ ESign. This is mandatory, if 'orderNo' is not provided.

GET CUSTOM FORMS

Sample Request

```
{
    "orderReferenceId":["ce9e99c4b4924b23b0692fafa26e4d25"]
}
```

Success Response


```
{
    "status": 200,
    "message": "success",
    "moreResultsExists": false,
    "data": [
        {
            "referenceId": "ce9e99c4b4924b23b0692fafa26e4d25",
            "tripName": "TRIP-19107",
            "orderNo": "ORD_188",
            "deliveryMediumName": "Bishwajeet",
            "status": "DELIVERED",
            "results": [
                {
                    "moduleId": 8043067,
                    "event": "UNLOAD_AFTER",
                    "moduleName": "ORDERS",
                    "formName": "unloadtesrt",
                    "formStatus": "ACTIVE",
                    "formdata": [
                        {
                            "field": "text",
                            "value": "Test Form"
                        }
                    ],
                    "formSubmissionDt": 1552031091965
                },
                {
                    "moduleId": 8043067,
                    "event": "ESIGN_AFTER",
                    "moduleName": "ORDERS",
                    "formName": "datePicker",
                    "formStatus": "ACTIVE",
                    "formdata": [
                        {
                            "field": "date",
                            "value": "1554834600000",
                            "type": "DATE"
                        },
                        {
                            "field": "text",
                            "value": "test"
                        }
                    ],
                    "formSubmissionDt": 1552031112446
                },
                {
                    "moduleId": 8043067,
                    "event": "PAYMENT_AFTER",
                    "moduleName": "ORDERS",
                    "formName": "Customer Feedback",
                    "formStatus": "ACTIVE",
                    "formdata": [
                        {
                            "field": "orderCollectedBy:",
                            "value": "test"
```

```
                        },
                        {
                            "field": "gender",
                            "value": "Male",
                            "type": "RADIO"
                        },
                        {
                            "field": "itemCount",
                            "value": "58"
                        },
                        {
                            "field": "e-Signature",
                            "value": "8043067_PAYMENT_AFTER_e-Signature_2019_03_08_13_15_27.jpg",
                            "type": "IMAGE"
                        },
                        {
                            "field": "image",
                            "value": "ORD_188_PAYMENT_AFTER_image_2019_03_08_13_15_42_211_camera.jpg",
                            "type": "IMAGE"
                        }
                    ],
                    "formSubmissionDt": 1552031146897
                },
                {
                    "moduleId": 8043067,
                    "event": "EPOD_AFTER",
                    "moduleName": "ORDERS",
                    "formName": "Customer Detail",
                    "formStatus": "ACTIVE",
                    "formdata": [
                        {
                            "field": "checkbox",
                            "value": "Options1",
                            "type": "CHECKBOX"
                        }
                    ],
                    "formSubmissionDt": 1552031150616
                }
            ]
        }
    ],
    "hasError": false
}
```


Retrieve the details of Custom Forms associated with an order using this API.

- This API retrieves custom form details for the specified orders.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.
- For example, if you record parking or toll charges for an order using custom forms in the Driver App, you can use this API to access that data.
- The details submitted through a custom form is available in the ‘formdata’ object within the API response. The ‘field’ key represents the code for the field name, the ‘value’ key contains the data entered for that field, and the ‘type’ key indicates the data type of the captured information.
- Note that date fields at the custom form level will be returned in EPOCH format.

API TYPE

- Tier 1 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v1/customform/list`

RESPONSE PARAMETERS

Parameter	Datatype	Description
referenceId	String	Unique identifier generated by the system, associated with the specific order.
tripName	String	Name of the trip associated with the order.
orderNo	String	Unique identifier of the order.
deliveryMediumName	String	Name of the delivery associate.
status	String	Status of the order.
results	List	This parameter contains the result details.
results.event	String	Event that the custom form was associated with. The list of possible events is listed in the table below.
results.moduleName	String	Name of the custom form module. The value is set to 'ORDERS' if the ‘referenceId’ field is provided.
results.formName	String	Name of the custom form set when creating the template in the LogiNext system.
results.formStatus	String	Status of the custom form. The value is set to 'ACTIVE' if the custom form is currently active, or 'INACTIVE' if the custom form is deactivated.
results.formSubmissionDt	String	Date on which the custom form is submitted (in EPOCH format).
results.formdata	List	This parameter contains the list of custom form specific data associated with the order.
results.formdata.field	String	Name or code of the field in the custom form.
results.formdata.value	String	Value entered in the field when submitting the custom form.
results.formdata.type	String	Data type of the input field in the custom form.

Event Key	Description
CHECKIN_AFTER	Custom form filled after the Check-In screen in the Driver App.
LOAD_AFTER	Custom form filled after the Loading screen in the Driver App.
UNLOAD_AFTER	Custom form filled after the Unloading screen in the Driver App.
ESIGN_AFTER	Custom form filled after the ESIGN screen in the Driver App.
PAYMENT_AFTER	Custom form filled after the Payment screen in the Driver App.
EPOP_AFTER	Custom form filled after the E Proof of Pickup screen in the Driver App.
EPOD_AFTER	Custom form filled after the E Proof of Delivery in the Driver App.
PICKEDUP_AFTER	Custom form filled after the Pickup is complete for the Order in the Driver App.
NOTPICKED-UP_AFTER	Custom form filled after the Order is marked ‘Not Picked Up’ in the Driver App.
DELIVERED_AFTER	Custom form filled after the Order is marked ‘Delivered’ in the Driver App.
NOTDELIVER_AFTER	Custom form filled after the Order is marked ‘Not Delivered’ in the Driver App.

PARTIALDELIVER_AFTER	Custom form filled after the Order is marked ‘Partial Delivered’ in the Driver App.
TRIPSTART_AFTER	Custom form filled after the Trip Start screen in the Driver App.
TRIPEND_AFTER	Custom form filled after the Trip End screen in the Driver App.

ADD ORDER COMMENT

Sample Request

```
{
    "orderNo": "24022022000005",
    "comment": "This is a sample comment added to an order",
    "showToDA": "N",
    "showToShipper": "N"

}
```

Success Response

```
{
    "status": 200,
    "message": "Message published successfully!",
    "moreResultsExists": false,
    "hasError": false
}
```

Add comments to an order using this API.

- This API adds comments to an order to mention any specific updates regarding the order.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.
- For example, if you have an external Order Management System where you are making updates to the order and want to update the LogiNext system as well, you can use this API to add comments to the order. These comments will be visible in the Order History or Order Details page and, if specified, to the delivery associate and/or shipper as well.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v1/comment`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderReferenceId	String		Conditional Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order in which you want to add a comment. This field is mandatory, if ‘orderNo’ is not provided.
orderNo	String		Conditional Mandatory	Unique identifier of the orders to which you want to add a comment. This field is mandatory, if ‘orderReferenceId’ is not provided.
comment	String		Mandatory	Specify the comments you want to add to the order.
showToDA	String		Optional	Whether to show the comment to the associated delivery associate or not. Specify ‘Y’ to show the comment to the delivery associate or ‘N’ to hide it from them. If no value is provided, the system considers ‘N’ by default.

showToShipper	String	Optional	Whether to show the comment to the associated shipper or not. Specify 'Y' to show the comment to the shipper or 'N' to hide it from them. If no value is provided, the system considers 'N' by default.

END-TO-END ACCOUNT: ADD ORDER COMMENT

Sample Request

```
{
    "orderNo": "24022022000005",
    "comment": "This is a sample comment added to an order",
    "showToDA": "N",
    "showToShipper": "N"

}
```

Success Response

```
{
    "status": 200,
    "message": "Message published successfully!",
    "moreResultsExists": false,
    "hasError": false
}
```

If you have an End-to-End account, add comments to an order using this API.

- This API adds comments to an order to mention any specific updates regarding the order.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.
- For example, if you have an external Order Management System where you are making updates to the order and want to update the LogiNext system as well, you can use this API to add comments to the order. These comments will be visible in the Order History or Order Details page and, if specified, to the delivery associate and/or shipper as well.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/comment`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderReferenceId	String		Conditional Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order in which you want to add a comment. This field is mandatory, if 'orderNo', 'milestoneNo', or 'milestoneReferenceId' are not provided.
orderNo	String		Conditional Mandatory	Unique identifier of the orders to which you want to add a comment. This field is mandatory, if 'orderReferenceId', 'milestoneNo', or 'milestoneReferenceId' are not provided.
milestoneReferenceId	String		Conditional Mandatory	Unique reference identifier associated with the milestone of the End-to-End order. This field is mandatory, if 'milestoneNo', 'orderNo', or 'orderReferenceId' are not provided.
				Unique identifier associated with the milestone of the End-to-End order. This

milestoneNo	String	Conditional Mandatory	field is mandatory, if 'milestoneReferenceId', 'orderNo', or 'orderReferenceId' are not provided.
comment	String	Mandatory	Specify the comments you want to add to the order.
showToDA	String	Optional	Whether to show the comment to the associated delivery associate or not. Specify 'Y' to show the comment to the delivery associate or 'N' to hide it from them. If no value is provided, the system considers 'N' by default.
showToShipper	String	Optional	Whether to show the comment to the associated shipper or not. Specify 'Y' to show the comment to the shipper or 'N' to hide it from them. If no value is provided, the system considers 'N' by default.

END-TO-END ACCOUNT: ADD MULTIPLE ORDER COMMENTS

Sample Request

```
[
  {
    "orderNo": "Order123",
    "comment": "This is a sample comment added to an order",
    "showToDA": "N",
    "showToShipper": "N"
  },
  {
    "orderReferenceId": "aE948271012821018",
    "comment": "This is a sample comment added to an order",
    "showToDA": "Y",
    "showToShipper": "N"
  },
  {
    "milestoneNo": "Order123_M1",
    "comment": "This is a sample comment added to an order",
    "showToDA": "N",
    "showToShipper": "N"
  },
  {
    "milestoneReferenceId": "5b5c488c714b4a0591319d19eb0bec6e",
    "comment": "This is a sample comment added to an order",
    "showToDA": "N",
    "showToShipper": "N"
  }
]
```

Success Response

```
{
"status": 200,
"message": "Message published successfully",
"moreResultsExists": false,
"data": [
  {
    "index": 0,
    "orderNo": "Order123_M1"
  },
  {
    "index": 1,
    "orderNo": "Order321_M3"
  },
  {
    "index": 2,
```

```
    "orderNo": "Order123_M1"
  },
  {
    "index": 3,
    "orderNo": "Order321_M3"
  }
],
"hasError": false
}
```


Partial Success Response


```
{
"status": 207,
"message": "Message published successfully",
"moreResultsExists": false,
"data": [
  {
    "index": 0,
    "orderNo": "Order123_M1"
  },
],
"error": [
{
    "index": 1,
    "errorList": [
        {
            "key": "orderReferenceId",
            "message": [
                "Order reference ID does not exist"
            ],
            "errorCode": 18002,
        }
    ]
},
{
"index": 2,
"errorList": [
    {
        "key": "milestoneNo",
        "message": [
            "Milestone number does not exist in the system"
        ],
        "errorCode": 12149,
    }
]
},
{
"index": 3,
"errorList": [
    {
        "key": "milestoneReferenceId",
        "message": [
            "Milestone Reference Id does not exist"
        ],
        "errorCode": 12149,
    }
]
}
],
"hasError": true
}
```

Failure Response


```
{
"status": 409,
"message": "Invalid request",
"moreResultsExists": false,
"error": [
{
    "index": 0,
    "errorList": [
        {
            "key": "orderNo",
            "message": [
                "Order number does not exist in the system"
            ],
            "errorCode": 18001,
        }
    ]
},
{
"index": 1,
"errorList": [
    {
        "key": "orderReferenceId",
        "message": [
            "Order reference ID does not exist"
        ],
        "errorCode": 18002,
    }
]
},
{
"index": 2,
"errorList": [
    {
        "key": "milestoneNo",
        "message": [
            "Milestone number does not exist in the system"
        ],
        "errorCode": 12149,
    }
]
},
{
"index": 3,
"errorList": [
    {
        "key": "milestoneReferenceId",
        "message": [
            "Milestone Reference Id does not exist"
        ],
        "errorCode": 12149,
    }
]
}
],
"hasError": true
}
```


If you have an End-to-End account, add multiple comments to an order using this API.

- This API adds multiple comments to an order to mention any specific updates regarding the order.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.

- For example, if you have an external Order Management System where you are making updates to the order and want to update the LogiNext system as well, you can use this API to add comments to the order. These comments will be visible in the Order History or Order Details page and, if specified, to the delivery associate and/or shipper as well.

API TYPE

- Tier 2 API.
- You can add comments to a maximum of 20 orders in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/middlemile/v1/comment/multiOrder`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderReferenceId	String		Conditional Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order in which you want to add a comment. This field is mandatory, if 'orderNo', 'milestoneNo', or 'milestoneReferenceId' are not provided.
orderNo	String		Conditional Mandatory	Unique identifier of the orders to which you want to add a comment. This field is mandatory, if 'orderReferenceId', 'milestoneNo', or 'milestoneReferenceId' are not provided.
milestoneReferenceId	String		Conditional Mandatory	Unique reference identifier associated with the milestone of the End-to-End order. This field is mandatory, if 'milestoneNo', 'orderNo', or 'orderReferenceId' are not provided.
milestoneNo	String		Conditional Mandatory	Unique identifier associated with the milestone of the End-to-End order. This field is mandatory, if 'milestoneReferenceId', 'orderNo', or 'orderReferenceId' are not provided.
comment	String		Mandatory	Specify the comments you want to add to the order.
showToDA	String		Optional	Whether to show the comment to the associated delivery associate or not. Specify 'Y' to show the comment to the delivery associate or 'N' to hide it from them. If no value is provided, the system considers 'N' by default.
showToShipper	String		Optional	Whether to show the comment to the associated shipper or not. Specify 'Y' to show the comment to the shipper or 'N' to hide it from them. If no value is provided, the system considers 'N' by default.

ADD MULTI-ORDER COMMENT

Sample Request

```
[
  {
    "orderNo": "Order123",
    "comment": "This is a sample comment added to an order",
    "showToDA": "N",
    "showToShipper": "N"
  },
  {
    "orderReferenceId": "aE948271012821018",
    "comment": "This is a sample comment added to an order",
    "showToDA": "Y",
    "showToShipper": "N"
  }
]
```

Success Response

```
{
"status": 200,
"message": "Message published successfully",
"moreResultsExists": false,
"data": [
  {
    "index": 0,
    "orderNo": "Order123"
  },
  {
    "index": 1,
    "orderNo": "Order321"
  },
],
"hasError": false
}
```

Partial Success Response

```
{
"status": 207,
"message": "Message published successfully",
"moreResultsExists": false,
"data": [
  {
    "index": 0,
    "orderNo": "Order123"
  },
],
"error": [
{
    "index": 1,
    "errorList": [
        {
            "key": "orderReferenceId",
            "message": [
                "Order reference ID does not exist"
            ]
            "errorCode": 18002,
        }
    ]
}
],
"hasError": true
}
```

Failure Response

```
{
"status": 409,
"message": "Invalid request",
"moreResultsExists": false,
"error": [
{
    "index": 0,
    "errorList": [
        {
            "key": "orderNo",
            "message": [
```

```
                "Order number does not exist in the system"
            ]
            "errorCode": 18001,
        }
    ]
},
{
"index": 1,
"errorList": [
    {
        "key": "orderReferenceId",
        "message": [
            "Order reference ID does not exist"
        ]
        "errorCode": 18002,
    }
]
}
],
"hasError": true
}
```


Add multiple comments to an order using this API.

- This API adds multiple comments to an order to mention any specific updates regarding the order.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.
- For example, if you have an external Order Management System where you are making updates to the order and want to update the LogiNext system as well, you can use this API to add comments to the order. These comments will be visible in the Order History or Order Details page and, if specified, to the delivery associate and/or shipper as well.

API TYPE

- Tier 2 API.
- You can add comments to a maximum of 20 orders in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v1/comment/multiOrder`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderReferenceId	String		Conditional Mandatory	Unique reference identifier associated with the order. This ID is used to identify the order in which you want to add a comment. This field is mandatory, if ‘orderNo’ is not provided.
orderNo	String		Conditional Mandatory	Unique identifier of the orders to which you want to add a comment. This field is mandatory, if ‘orderReferenceId’ is not provided.
comment	String		Mandatory	Specify the comments you want to add to the order.
showToDA	String		Optional	Whether to show the comment to the associated delivery associate or not. Specify ‘Y’ to show the comment to the delivery associate or ‘N’ to hide it from them. If no value is provided, the system considers ‘N’ by default.
showToShipper	String		Optional	Whether to show the comment to the associated shipper or not. Specify ‘Y’ to show the comment to the shipper or ‘N’ to hide it from them. If no value is provided, the system considers ‘N’ by default.

AI Recommended Pre-Order ETA

Sample Request

```
{
    "orderTypeCd":"Deliver",
    "predictiveETAmode":"BestDA",
    "autoAllocateProfileName":"ETAProfile",
    "deliveryType":"Grocery",
    "distributionCenter":["Chicago DownTown"],
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. HappyDent",
    "deliverLocality": "Down Town Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverLatitude":41.882702,
    "deliverLongitude":-87.619392,
    "shipmentlineitems":[
      {
        "itemCd":"IT043",
        "itemQuantity":5
      },
      {
        "itemCd":"IT076",
        "itemQuantity":5
      }
    ]
}
```

Success Response: If ‘predictiveETAmode’ is set to ‘BestDA’ and a delivery associate is found

```
{

    "status": 200,
    "message": "Predictive ETA calculated successfully.",
    "data": [
    {
        "distributionCenter":"Chicago DownTown",
        "predictiveETAinMins" : "38",
        "orderPrepTimeinMins" : "15",
        "deliveryMediums": [
          {
            "deliveryMediumMasterName": "Mathew S",
            "employeeId": "133467",
            "userName": "mathewsandroid",
            "phoneNumber": "9881127443",
            "Latitude":40.882702,
            "Longitude":74.619392,
            "pickupEta": "2021-07-15T10:47:00.000Z",
            "deliverEta": "2021-07-15T11:47:00.000Z",
            "pickupServiceTimeinMin": "20",
            "deliverServiceTimeinMin": "20",
            "distanceInKms": 9.849,
            "timeInMin": 60,
          }
        ]
    }
    ],
```

```
    "hasError":false
}
```

Success Response: If ‘predictiveETAmode’ is set to ‘BestDA’ and no delivery associate is found

```
{

    "status": 200,
    "message": "No DA Found",
    "data": [],
    "hasError":false
}
```

Success Response: If ‘predictiveETAmode’ is set to 'BestEstimate'

```
{
    "status": 200,
    "message": "Predictive ETA calculated successfully.",
    "data":[
        {
            "distributionCenter":"Chicago DownTown",
            "predictiveETAinMins":"38",
            "orderPrepTimeinMins":"15"
        }
    ],
    "hasError":false
}
```

Failure Response

```
{

    "status": 409,
    "message": "Predictive ETA failed",
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "errorList" : [
                {
                    "key": "orderTypeCd",
                    "message": ["Order Type is mandatory."],
                    "errorCode": 10006
                },
                {
                    "key": "predictiveETAmode",
                    "message": ["Predictive ETA mode is mandatory."],
                    "errorCode": 10150
                }
            ]
        }
    ],
    "hasError": true
}
```

Calculate the AI recommended Pre-Order ETA of an order with this API.

- This API calculates the AI recommended Pre-Order ETA of an order based on the details provided.
- Pre-Order ETA (Pre-Order Estimated Time of Arrival) is a prediction of how long an order will take to arrive at the customer’s address

before the order is placed.
- You can integrate this API into your application to display the AI recommended Pre-Order ETA of orders from various serviceable branches.
- Customers browsing your app will be able to view the estimated time of order delivery from different serviceable branches in their area, helping them decide which branch to order from.
- AI can better estimate Pre-Order ETA once the customer adds item details.
- Pre-Order ETA can be calculated using two different modes:
  - **Best Delivery Associate Mode:** This mode identifies the best delivery associate to whom the order can be assigned as per the specified Auto-Assignment Profile and shares the AI recommended Pre-Order ETA considering that delivery associate's details.
  - **Best Estimate Mode:** This mode calculates the best estimate of the AI recommended Pre-Order ETA based on factors such as the availability of delivery associates, other orders waiting to be assigned at the branch, and so on.

API TYPE

- Tier 2 API.
- This API accepts up to 5 branches in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v1/predicteta`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderTypeCd	String		Mandatory	Type of the order. Specify 'PICKUP' for Pick Up Only orders, 'DELIVER' for Delivery Only and Point-to-Point orders, and 'BOTH' for Pickup and Delivery type of orders.
predictiveETAmode	String		Mandatory	Mode of using the pre-order ETA. Specify 'BestDA' to identify the best delivery associate to whom the order can be assigned according to the auto-assignment profile and calculate the estimated time, or 'BestEstimate' to calculate the best estimate of the order based on various factors.
autoAllocateProfileName	String		Optional	Name of the Auto-assignment Profile used to assign orders automatically. If not provided, the default profile will be considered.
distributionCenter	List		Mandatory	Names of the branches that can service the customer.
pickupApartment	String		Conditional Mandatory	Name of the apartment building/complex in the pickup address.
pickupStreetName	String		Conditional Mandatory	Name of the society or street in the pickup address.
pickupLandmark	String		Conditional Mandatory	Landmark of the pickup location.
pickupLocality	String		Conditional Mandatory	Name of the locality or area in the pickup address.
pickupCity	String		Conditional Mandatory	Name of the city in the pickup address.
pickupState	String		Conditional Mandatory	Name of the state in the pickup address. This should be as per the State Codes available in the LogiNext system for the selected country.
pickupCountry	String		Conditional Mandatory	Name of the country in the pickup address. This should be as per the Country Codes available in the LogiNext system.

pickupPinCode	String		Conditional Mandatory	Pin code of the pickup location.
pickupLatitude	String		Conditional Mandatory	Latitude coordinates of the pickup address. This field is mandatory if the longitude is provided.
pickupLongitude	String		Conditional Mandatory	Longitude coordinates of the pickup address. This field is mandatory if the latitude is provided.
deliverApartment	String	512	Conditional Mandatory	Name of the apartment building/complex in the delivery address.
deliverStreetName	String	255	Conditional Mandatory	Name of the society or street in the delivery address.
deliverLandmark	String	512	Conditional Mandatory	Landmark of the delivery location.
deliverLocality	String	512	Conditional Mandatory	Name of the locality or area in the delivery address.
deliverCity	String	512	Conditional Mandatory	Name of the city in the delivery address.
deliverState	String	50	Conditional Mandatory	Name of the state in the delivery address. This should be as per the State Codes available in the LogiNext system for the selected country.
deliverCountry	String	100	Conditional Mandatory	Name of the country in the delivery address. This should be as per the Country Codes available in the LogiNext system.
deliverPinCode	String	12	Conditional Mandatory	Pin code of the delivery location.
deliverLatitude	String		Conditional Mandatory	Latitude coordinates of the delivery address. This field is mandatory if the longitude is provided.
deliverLongitude	String		Conditional Mandatory	Longitude coordinates of the delivery address. This field is mandatory if the latitude is provided.
shipmentlineitems	List		Optional	Enter the item details within this parameter.
shipmentlineitems.itemCd	String		Optional	Unique identifier for the item.
shipmentlineitems.itemQuantity	String		Conditional Mandatory	Total number of items. This field is mandatory if the item code is provided.

Manifest

CREATE / UPDATE

Sample Request

```
{
  "manifestId":"hcgsyuc334",
  "manifestType":"ORDER",
```

```
    "cancelledOrderAllowedFl": false,
    "orderReferenceIds":["843d70885de84d20b46279d0d5149758","5e10b5c270ad46a5969b323d48b60c0a"]
}
```

Success Response

```
{
    "status": 200,
    "message": "Add Orders to manifest success.",
    "data": {
        "manifestId": "hcgsyuc334"
    },
    "hasError": false
}
```

Outscan orders or update the details of outscanned orders with this API.

- This API creates/updates manifests.
- It identifies orders using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system. You can also retrieve this ID using the Get Order API.
- If the manifest is created successfully, the scan status of the specified order will be updated to ‘Outscanned’.
- You can also create manifests for cancelled orders by setting the ‘cancelledOrderAllowedFl’ field to ‘true’, allowing you to return (outscan) the cancelled orders to the merchant or origin.
- When this API is called, it will check if the provided 'manifestId' exists in the LogiNext system.
    - If it exists, the orders (identified using Order Reference IDs) will be updated in the LogiNext system.
    - If it does not exist, a new manifest will be created with the provided Manifest ID.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v1/scan/manifest/addshipment`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
manifestId	String	11	Optional	Unique identifier associated with the manifest. If not provided, the system will auto-generate this field. This ID will also be included in the response parameters for future reference.
manifestType	String	25	Optional	Type of the manifest. The default value of this field is 'ORDER'.
cancelledOrderAllowedFl	String	1	Optional	Whether you want to create a manifest for cancelled orders. Specify ‘true’ if you want to outscan the cancelled orders, or ‘false’ if you do not. By default, the value of this field is ‘false’.
orderReferenceIds	List		Mandatory	Unique reference IDs of the orders you want to outscan or create a manifest for.

INSCAN

Sample Request

```
{
  "branchName": "branch1",
  "orders": [
    {
      "orderNo":"order1",
```

```
      "orderReferenceId":"referenceid1",
      "manifestId":"manifest1",
      "awbNumber":"awbnumber1"
    },
    {
      "orderNo":"order2",
      "orderReferenceId":"referenceid2",
      "manifestId":"manifest2",
      "awbNumber":"awbnumber2"
    }
  ]
}
```

Success Response

```
{
    "status": 200,
    "message": "Order(s) inscanned successfully",
    "data": [
        {
            "index": 0
        },
        {
        "index": 1
    }
    ],
    "hasError": false
}
```

Partial Success Response

```
{
    "status": 207,
    "message": "Order(s) inscanned partially",
    "data": [
        {
        "index": 0
      }
    ],
    "error": [
        {
            "index": 1,
            "errorList": [
                {
                    "key": "orderNo",
                    "message": [
                        "Order does not exist"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```

Failure Response

```
{
   "status": 409,
   "message": "Order(s) inscanned failed",
```

```
    "moreResultsExists": false,
    "error": [
        {
            "index": 0,
            "errorList": [
                {
                    "key": "orderNo",
                    "message": [
                      "Order Number does not exist in the system."
                    ],
                    "codes": [
                      "18001"
                    ]
                }
            ]
        }
    ],
    "hasError": true
}
```


Inscan orders with this API.

- This API inscan the specified orders.
- It identifies orders using the Order Number, Reference ID, Manifest ID, and AWB Number.
- If the order is inscanned successfully, the scan status of the specified order will be updated to ‘Inscanned’.
- When this API is called, if you provide an Order Number, AWB Number, or Manifest ID, the API will check your configured scanning preferences (the parameters that you have allowed to be scanned) in the LogiNext system.
    - If the scanning preference for the specified parameter exists, the order's scan status will be updated to ‘Inscanned’.
    - If the scanning preference for the specified parameter does not exist, the order's scan status will not be updated.

API TYPE

- Tier 2 API.
- This API supports batch operations; you can inscan a maximum of 20 orders in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/mile/v1/scan/inscan`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderNo	String	100	Conditional Mandatory	Unique number of the order. This field is mandatory if the ‘orderReferenceId’ field is not provided.
orderReferenceId	String	100	Conditional Mandatory	Unique reference ID of the order. This field is mandatory if the ‘orderNo’ field is not provided.
manifestId	String	100	Conditional Mandatory	Unique identifier associated with the manifest. This field is mandatory if the ‘orderReferenceId’, ‘orderNo’, or ‘awbNumber’ are not provided.
awbNumber	String	100	Optional	Air Waybill or AWB number associated with an order. Even if you provide this field, the ‘orderNo’ and ‘orderReferenceId’ fields must also be included.
branchName	String	255	Optional	Name of the branch where you want to perform the inscan activity of an order.

Trip

CREATE

Sample Request

```
{
  "tripName":"TRIP-8980",
  "deliveryMediumUserName":"jamesdeen",
  "deliveryMediumReferenceId":"654fg654k76543456",
  "carrierBranchName": "Carrier Branch - New York",
  "fleetType": "Truck",
  "licenseNumber":"LIC_104",
  "driverReferenceId":"2345f76543g76543y87654",
  "vehicleNumber":"M011A1",
  "vehicleReferenceId":"87654gh87654hj8765",
  "orderDetails": [
   {
     "orderNo": "NA12070320191",
     "orderReferenceId": "ed9906f4debe4260a4211b801b3b945c",
     "pickupSequence":"3",
     "deliverSequence": "7"
   },
   {
     "orderNo": "NA12070320191",
     "orderReferenceId": "ed9906f4debe4260a4211b801b3b945c",
     "pickupSequence":"1",
     "deliverSequence": "2"
   }
  ]
}
```

Success Response

```
{
 "status": 200,
 "message": "Trip created successfully",
 "data": {
 "tripReferenceId":"6186d5fc6e324c42" ,
 "tripName" : "23022020-Trip-Central Chicago"
 },
 "hasError": false
}
```

Failure Response

```
{
 "status": 409,
 "message": "Trip creation failed",
 "errorList":
 [
 {
   "key":"licenseNumber",
   "message": "License Number does not exist.",
   "errorCode":20043
 }
 ],
 hasError: true
}
```

Create new trips in the LogiNext system using this API.

- This API creates a new Trip and assigns a unique Reference ID that can be used to identify the trip later.

- Note that the order ETA is calculated based on the sequence provided in the ‘pickupSequence’ and ‘deliverSequence’ fields when creating a trip.

API TYPE

- Tier 2 API.
- You can only create one trip in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/TripApp/mile/v1/create`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
tripName	String	255	Optional	Name of the trip. If this field is not provided, the system will auto-generate a unique trip name.
deliveryMediumUserName	String	255	Conditional Mandatory	Username of the delivery associate linked with the trip. This field is mandatory, if ‘deliveryMediumReferenceId’ is not provided.
deliveryMediumReferenceId	String	32	Conditional Mandatory	Unique reference identifier of the delivery associate linked with the trip. This field is mandatory, if ‘deliveryMediumUserName’ is not provided.
carrierBranchName	String	255	Conditional Mandatory	Name of the carrier branch. This field is mandatory if ‘deliveryMediumReferenceId’ or ‘deliveryMediumUserName’ is not provided. The carrier branch should be linked to a serviceable branch via an active contract with the carrier.
fleetType	String	255	Conditional Mandatory	Name of the Fleet Type. This field is mandatory if 'carrierBranchName' is provided. The Fleet Type must be configured for the serviceable branch in the contract and it must have enough capacity to complete the orders within the trip.
vehicleNumber	String	255	Optional	Unique number of the vehicle associated with the trip. This field is mandatory, if ‘vehicleReferenceId’ is not provided.
vehicleReferenceId	String	32	Optional	Unique reference identifier of the vehicle associated with the trip. This field is mandatory, if ‘vehicleNumber’ is not provided.
licenseNumber	String	255	Optional	Driving license number of the driver. This field is mandatory, if ‘driverReferenceId’ is not provided.
driverReferenceId	String	32	Optional	Unique reference identifier associated with driver. This field is mandatory, if ‘licenseNumber’ is not provided.
orderNo	String	100	Conditional Mandatory	Unique number associated with the order. This field is mandatory, if ‘orderReferenceId’ is not provided.
orderReferenceId	String	32	Conditional Mandatory	Unique reference identifier associated with the order. This field is mandatory, if ‘orderNo’ is not provided.
pickupSequence	String	1	Mandatory	Sequence in which the order should be picked up.
deliverSequence	String	1	Mandatory	Sequence in which the order should be delivered.

GET

Sample Request

```
https://api.loginextsolutions.com/TripApp/mile/v1/trip/get?referenceId=7f389cfa7ae64d85a915ee6297bd9c3f&tripname=TRIP-26516
```

Success Response: For Not Started Trip


```
{
    "status": 200,
    "message": "Success",
    "data": {
    "tripName": "TRIP-13924",
    "referenceId": "2becf481189f4525a23889a35c554e61",
    "status": "NOTSTARTED",
    "plannedStartDt": 1522618200000,
    "plannedEndDt": 1522626600000,
    "totalPlannedDistance": 30.1302,
    "totalPlannedTime": 140,
    "plannedTotalCost": 40,
    "plannedFixedCost": 17,
    "plannedVariableCost": 13,
    "plannedTransportTimeCost": 7,
    "plannedWaitingTimeCost": 3,
    "vehicleNumber": "MH04-HD9389",
    "deliveryMediumName": "tetestrer",
    "deliveryMediumPhoneNumber": "9968995522",
    "deliveryMediumBranch": "AAA0",
    "carrierBranchName": "USA Main Branch",
    "fleetType": "Truck",
    "orderDetails": [
        {
            "referenceId": "3e7262c47a47441295d37dba81425827",
            "orderNo": "Andri55",
            "state": "FORWARD",
            "status": "NOTDISPATCHED",
            "orderSequence": 2,
            "shipmentOrderTypeCd": "DELIVER",
            "startTimeWindow": 1522661400000,
            "endTimeWindow": 1522665000000,
            "plannedStartTime": 1546908814000,
            "plannedEndTime": 1546914874000,
            "revisedStartTime": 1522657800000,
            "revisedEndTime": 1522662000000
        }
    ],
    "plannedStartDtTZ": "Asia/Calcutta",
    "plannedEndDtTZ": "Asia/Calcutta"
    },
    "hasError": false
}
```


Success Response: For Started Trip


```
{
    "status": 200,
    "message": "Success",
    "data": {
    "tripName": "TRIP-13924",
    "referenceId": "2becf481189f4525a23889a35c554e61",
    "status": "STARTED",
    "plannedStartDt": 1522618200000,
    "plannedEndDt": 1522626600000,
    "actualStartDt": 1622195221000,
    "totalPlannedDistance": 30.1302,
```

```
    "totalPlannedTime": 140,
    "plannedTotalCost": 40,
    "plannedFixedCost": 17,
    "plannedVariableCost": 13,
    "plannedTransportTimeCost": 7,
    "plannedWaitingTimeCost": 3,
    "vehicleNumber": "MH04-HD9389",
    "deliveryMediumName": "tetestrer",
    "deliveryMediumPhoneNumber": "9968995522",
    "deliveryMediumBranch": "AAA0",
    "carrierBranchName": "USA Main Branch",
    "fleetType": "Truck",
    "orderDetails": [
        {
            "referenceId": "3e7262c47a47441295d37dba81425827",
            "orderNo": "Andri55",
            "state": "FORWARD",
            "status": "INTRANSIT",
            "orderSequence": 2,
            "shipmentOrderTypeCd": "DELIVER",
            "startTimeWindow": 1522661400000,
            "endTimeWindow": 1522665000000,
            "plannedStartTime": 1546908814000,
            "plannedEndTime": 1546914874000,
            "revisedStartTime": 1522657800000,
            "revisedEndTime": 1522662000000
        }
    ],
    "plannedStartDtTZ": "Asia/Calcutta",
    "plannedEndDtTZ": "Asia/Calcutta",
    "actualStartDtTZ": "Asia/Calcutta"
    },
    "hasError": false
}
```


Success Response: For Ended Trip


```
{
    "status": 200,
    "message": "Success",
    "data": {
    "tripName": "TRIP-13924",
    "referenceId": "2becf481189f4525a23889a35c554e61",
    "status": "ENDED",
    "plannedStartDt": 1522618200000,
    "plannedEndDt": 1522626600000,
    "actualStartDt": 1623423078000,
    "actualEndDt": 1623423078000,
    "totalPlannedDistance": 30.1302,
    "totalActualDistance": 27.76,
    "totalPlannedTime": 140,
    "totalActualTime": 210,
    "plannedTotalCost": 40,
    "plannedFixedCost": 17,
    "plannedVariableCost": 13,
    "plannedTransportTimeCost": 7,
    "plannedWaitingTimeCost": 3,
    "vehicleNumber": "MH04-HD9389",
    "deliveryMediumName": "tetestrer",
    "deliveryMediumPhoneNumber": "9968995522",
    "deliveryMediumBranch": "AAA0",
    "carrierBranchName": "USA Main Branch",
    "fleetType": "Truck",
    "orderDetails": [
```

```
        {
            "referenceId": "3e7262c47a47441295d37dba81425827",
            "orderNo": "Andri55",
            "state": "FORWARD",
            "status": "NOTDISPATCHED",
            "orderSequence": 2,
            "shipmentOrderTypeCd": "DELIVER",
            "startTimeWindow": 1522661400000,
            "endTimeWindow": 1522665000000,
            "plannedStartTime": 1546908814000,
            "plannedEndTime": 1546914874000,
            "revisedStartTime": 1522657800000,
            "revisedEndTime": 1522662000000
        }
    ],
    "plannedStartDtTZ": "Asia/Calcutta",
    "plannedEndDtTZ": "Asia/Calcutta",
    "actualStartDtTZ": "Asia/Calcutta",
    "actualEndDtTZ": "Asia/Calcutta"
    },
    "hasError": false
}
```


Success Response: For Outsource Fleet


```
{
    "status": 200,
    "message": "Success",
    "data": {
    "tripName": "TRIP-13924",
    "referenceId": "2becf481189f4525a23889a35c554e61",
    "status": "ENDED",
    "plannedStartDt": 1522618200000,
    "plannedEndDt": 1522626600000,
    "totalPlannedDistance": 30.1302,
    "totalPlannedTime": 140,
    "plannedTotalCost": 40,
    "plannedFixedCost": 17,
    "plannedVariableCost": 13,
    "plannedTransportTimeCost": 7,
    "plannedWaitingTimeCost": 3,
    "carrierName": "ARL Logistics",
    "fleetBranch": "Santa Cruz",
    "carrierBranchName": "USA Main Branch",
    "fleetType": "Truck",
    "orderDetails": [
        {
            "referenceId": "3e7262c47a47441295d37dba81425827",
            "orderNo": "Andri55",
            "state": "FORWARD",
            "status": "NOTDISPATCHED",
            "orderSequence": 2,
            "shipmentOrderTypeCd": "DELIVER",
            "startTimeWindow": 1522661400000,
            "endTimeWindow": 1522665000000,
            "plannedStartTime": 1546908814000,
            "plannedEndTime": 1546914874000,
            "revisedStartTime": 1522657800000,
            "revisedEndTime": 1522662000000
        }
    ],
    "plannedStartDtTZ": "Asia/Calcutta",
    "plannedEndDtTZ": "Asia/Calcutta",
    "actualStartDtTZ": "Asia/Calcutta",
```

```
    "actualEndDtTZ": "Asia/Calcutta"
    },
    "hasError": false
}
```

Retrieve details of required trips using this API.

- This API retrieves the details of a trip including the trip name, status, planned duration, associated vehicle name, delivery associate name, order details, and more.
- Include the Reference IDs or Trip Names you want to search for in the Request Body.
- You can also use this API to retrieve the ETAs of the orders within a particular trip. It provides both the original and revised ETAs of the orders in a specified trip.

API TYPE

- Tier 2 API.

REQUEST

GET `https://api.loginextsolutions.com/TripApp/mile/v1/trip/get`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
referenceId	String	32	Conditional Mandatory	Unique reference identifier associated with the trip whose information you want to retrieve. This field is mandatory, if 'tripname' is not provided.
tripname	String	255	Conditional Mandatory	Name of the trip whose information you want to retrieve. This field is mandatory, if 'referenceId' is not provided.

START

Sample Request

```
[
    "a9be39b9347911e6829f000d3aa04450",
    "a9be39b9347911e6829f07657aa04450"
]
```

Success Response

```
{
  "status": 200,
  "message": "2 trip(s) started",
  "data": true,
  "hasError": false
}
```

Start trips using this API.

- This API starts the trips for delivery associates.
- Include the Reference IDs of the trips you want to start in the Request Body.

API TYPE

- Tier 2 API.
- This API supports batch operations, i.e., you can provide up to 20 Trip Reference IDs in a single call.

REQUEST

POST `https://api.loginextsolutions.com/TripApp/mile/v1/trip/start`

REQUEST PARAMETER

Parameter	Datatype	Length	Required	Description
reference_ids	List	32	Mandatory	Unique reference identifier of the trip that you want to start.

STOP

Sample Request

```
[{
    "tripReferenceId":"a9be39b9347911e6829f000d3aa04450",
    "notDispatchedOrders":["c8714df4347911e6829f000d3aa04450"],
    "deliveredOrders":["c8714cac347911e6829f000d3aa04450"]
}]
```

Success Response

```
{
  "status": 200,
  "message": "Trips ended successfully",
  "data": true,
  "hasError": false
}
```

Stop trips using this API.

- This API stops the trip for delivery associates.
- Include the Reference IDs of the trip you want to stop in the Request Body.
- This API accepts two lists of Order Reference IDs to update their statuses when the trip is stopped. For example, if there are 5 ‘Not Delivered’ orders when calling this API, you can specify which orders should be marked as 'Delivered' and which should be marked as 'Not Dispatched'.
- Orders marked as 'Not Dispatched' can then be reassigned to another trip for fulfillment later.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/TripApp/mile/v1/trip/stop`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
tripReferenceId	String	32	Mandatory	Unique reference identifier of the trip that you want to stop.
notDispatchedOrders	List		Mandatory	Unique reference identifiers associated with the orders that you want to mark as ‘Not Dispatched’ when the trip stops. If you do not want to mark any order as 'Not Dispatched', you can leave this field blank.
deliveredOrders	List		Mandatory	Unique reference identifiers associated with the orders that you want to mark as ‘Delivered’ when the trip stops. If you do not want to mark any order as 'Delivered', you can leave this field blank.

SUGGEST

Sample Request

```
{
  "orderReferenceId": "737675fc65bd427a8ead5abe95cd2a0f",
  "tripStartTime": "2025-09-29T14:00:00Z",
  "tripEndTime": "2025-10-10T18:00:00Z",
  "radius": 500,
  "tripStatus": ["STARTED", "NOTSTARTED"],
  "considerDeliveryType": true,
  "considerDeliveryMediumCapacity": true,
  "considerTimeConstraints": true
}
```

Success Response

```
{
  "status": 202,
  "message": "Success!",
  "data": "We have accepted your request, it will take some time to suggest the trips. We will push the trips to your system once completed. Thank you!"
}
```

Failure Response 1

```
{
  "status": 400,
  "message": "Bad Request!",
  "errors": [
    {
      "key": "orderReferenceId",
      "message": "Invalid Order Reference Id"
    }
  ]
}
```

Failure Response 2

```
{
  "status": 400,
  "message": "Bad Request!",
  "errors": [
    {
      "key": "tripStatus",
      "data": [
        "STARTE"
      ],
      "message": "Invalid Trip Status"
    }
  ]
}
```

Suggest trips for orders using this API.

- This API requests the most suitable trips for assigning your orders.
- Specify the orders for which you want the system to suggest trips using the 'orderReferenceId' parameter, along with any additional settings or conditions you want to apply (similar to the Trip Suggestion Settings available in the Dispatcher App).
- Once you send the necessary details using this API, the system responds through the Suggest Trip Webhook, which provides a list of suggested trips based on their suitability to fulfill the specified orders. Each suggested trip includes details such as the trip name, reference ID, delivery associate linked with the trip, and the recommended order fulfillment sequence.

- You can then review these suggested trips and assign the orders to the most appropriate trip as needed.

API TYPE

- Special Tier API.
- 1 request per second.

REQUEST

POST `https://api.loginextsolutions.com/TripApp/v1/suggest`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderReferenceId	String	32	Mandatory	Unique reference identifier associated with the order(s) for which you want the system to suggest relevant trips.
tripStartTime	Date		Optional	Trip start date and time (in UTC format). This indicates the start of the time window used to determine which trips are considered. For Not Started trips, the estimated start time is used. The tripEndTime parameter defines the end of this window. The system considers the trips whose start or end time falls within this period.
tripEndTime	Date		Optional	Trip end date and time (in UTC format). This indicates the end of the time window used to determine which trips are considered. For Not Started trips, the estimated end time is used. The tripStartTime parameter defines the start of this window. The system considers the trips whose start time or end time falls within this period.
radius	Number		Optional	Specify the maximum distance (in km) between the delivery associates linked to the trips and the selected order(s).
tripStatus	List		Optional	Specify the status(es) of the trips to be considered, i.e., whether you want the system to consider the 'Started' and/or 'Not Started' trips. Note that, by default, this is set to 'NOTSTARTED'.
considerDeliveryType	Boolean		Optional	Indicates whether you want the system to filter trips by skill sets. Specify true to suggest only trips linked to delivery associates whose skill sets match the orders' skill sets, or false to suggest trips without considering skill sets.
considerDeliveryMediumCapacity	Boolean		Optional	Indicates whether you want the system to consider the capacity of the trips with respect to the selected order or not. Specify 'true' to consider the trip capacity or 'false' to not.
considerTimeConstraints	Boolean		Optional	Indicates whether you want the system to consider time constraints, i.e., the Order Start Time and Order End Time of the selected order with respect to the trips or not. Specify 'true' to consider time constraints, or 'false' to not.

UPDATE

Sample Request

```
{
 "tripReferenceId" : "65ba00dbdcf04fb789311df6aa40e3ba",
 "tripName":"TRIP-8980",
 "deliveryMediumUserName":"jamesdeen",
 "deliveryMediumReferenceId":"654fg654k76543456",
 "licenseNumber":"LIC_104",
 "driverReferenceId":"2345f76543g76543y87654",
```

```
  "vehicleNumber":"M011A1",
  "vehicleReferenceId":"87654gh87654hj8765",
  "plannedStartTime" : "2021-06-22T10:30:00.00Z",
 "carrierBranchName": "USA Main Branch",
  "fleetType": "Truck",
}
```

Success Response

```
{
    "status": 200,
    "message": "Trip Updated Successfully.",
    "moreResultsExists": false,
    "data": {
        "tripReferenceId": "df0496c5fdab4653a0d46f858b7d37a5"
    },
    "hasError": false
}
```

Failure Response

```
{
  "status": 409,
  "message": "Trip Updation Failed.",
  "error": [
    {
      "key": "tripReferenceId",
      "message": "Trip Reference Id is invalid."
    }
  ],
  "hasError": true
}
```

Update an existing trip in the LogiNext system using this API.

- This API updates a trip with the details provided.
- It identifies trips using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Trip API response when the associated trip is created in the system.
- You can also update the trip name or the delivery associate assigned to a trip using this API, as needed.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/TripApp/mile/v1/update`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
tripReferenceId	String	32	Mandatory	Unique reference identifier associated with the trip. This ID is used to identify the trip that you want to update.
tripName	String		Optional	Name of the trip.
deliveryMediumReferenceId	String		Optional	Unique reference identifier of the delivery associate linked with the trip. This field is mandatory, if 'deliveryMediumUserName' is not provided.

deliveryMediumUserName	String		Optional	Username of the delivery associate linked with the trip. This field is mandatory, if 'deliveryMediumReferenceId' is not provided.
carrierBranchName	String	255	Optional	Name of the carrier branch.
fleetType	String	255	Conditional Mandatory	Name of the Fleet Type.
driverReferenceId	String		Optional	Unique reference identifier of the driver. This field is mandatory, if 'licenseNumber' is not provided.
licenseNumber	String		Optional	Driving license number of the driver. This field is mandatory, if 'driverReferenceId' is not provided.
vehicleReferenceId	String		Optional	Unique reference identifier of the vehicle associated with the trip. This field is mandatory, if 'vehicleNumber' is not provided.
vehicleNumber	String		Optional	Unique number of the vehicle associated with the trip. This field is mandatory, if 'vehicleReferenceId' is not provided.
plannedStartTime	String		Optional	Specify the planned start time (in UTC format) at which the trip would start, as per the trip plan. This field is mandatory, if the planned start time of the trip needs to be revised. Note that this is only applicable for the 'Not Started' trips.

Tracking

LAST LOCATION

Sample Request

```
https://api.loginextsolutions.com/TrackingApp/mile/v1/track/lastlocation?shipmentReferences=25a565a9c9d540cd9e6c02fae890cb67,c7afc8b1b97b48468c3417aa425eff81,27121
```

Success Response


```
{
  "status": 200,
  "message": "Latest Location found successfully",
  "data": [
    {
      "lat": 19.1119794,
      "lng": 72.9094968,
      "shipmentReference": "21b538edf7f047028334480036179c70"
    },
    {
      "lat": 19.0668898,
      "lng": 72.8320575,
      "shipmentReference": "25a565a9c9d540cd9e6c02fae890cb67"
    },
    {
      "lat": 19.0741246,
      "lng": 72.824772,
      "shipmentReference": "27121903f4f047bcb378a6457bee2fec"
    },
    {
```

```
      "lat": 19.1200864,
      "lng": 72.9010175,
      "shipmentReference": "c7afc8b1b97b48468c3417aa425eff81"
    }
  ],
  "hasError": false
}
```

Retrieve the last tracked location of an order using this API.

- This API retrieves the last tracked location (i.e., geo coordinates) of an order within the LogiNext system.
- It identifies orders using the Reference ID generated within the LogiNext system. This ID is provided in the Create Order API response when the associated order is created in the system.

API TYPE

- Tier 2 API.
- This API accepts up to 20 Order Reference IDs in a comma-separated format in one call.

REQUEST

GET `https://api.loginextsolutions.com/TrackingApp/mile/v1/track/lastlocation`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
shipmentReferences	String		Mandatory	Unique reference identifier associated with the order whose last tracked location you want to retrieve.

IFRAME

Sample Request

```
https://api.loginextsolutions.com/track/#/order?ordno=1234&aid=4b41a94b-521b-4986-920d-6e4c1cf15fd0b6
```

Display the last tracked location and the current location of an order using this iFrame.

- This iFrame can embed the tracking link in your application or website to display the last tracking information and the current location of an order based on its order number.
- You can integrate this iFrame into your application or website to display real-time order tracking information, enhancing the customers' experience.
- To implement this, embed the URL in your application or website using a 'frame' tag in the webpage's HTML. For example, a 'Track' button on your UI could call the iFrame URL when clicked. The tracking URL can then be opened on your application's or website's subdomain as an iFrame, allowing your customers to view live tracking of their orders.
- **Note:**
  - Specify the order number in the URL request along with the LogiNext token provided for accessing the iFrame.
  - The authentication token for the iFrame is different from the one used to call the LogiNext API. Contact your Account Manager to get the token required to access the iFrame.

REQUEST

GET `https://api.loginextsolutions.com/track/#/order?ordno=<ordno>&aid=<aid>`

REQUEST PARAMETERS

Parameter	Data Type	Length	Required	Description
aid				Authentication token required to access the iFrame. Specify this value without the 'BASIC' keyword. For example - f522631c-490c-46fd-9f79-ca8d14a704d7.

ordno			Conditional Mandatory	Unique number associated with the order that you want to track. This field is mandatory, if ‘orderReferenceId’ is not provided.
type				Type of user you want to display the order tracking information to. Specify ‘ADMIN’ to display the tracking information to the admin user or ‘CUSTOMER’ to display it to the customer associated with the order. If no value is provided, the system considers ‘ADMIN’ by default.
orderReferenceId			Conditional Mandatory	Unique reference identifier associated with the order that you want to track. This field is mandatory, If ‘ordno’ is not provided.
clientCode	String	32	Optional	Name of the shipper’s company associated with the order. Pass the company name of the shipper’s account whose order you want to track.
shipmentOrderTypeCd	String	32	Optional	Type of order you want to track. Whether you want to track the ‘PICKUP’, ‘DELIVER’, or ‘BOTH’ type of order.
orderState	String	512	Optional	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of the order, whether the order is in forward state or reverse state. Specify ‘FORWARD’ if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or ‘REVERSE’ if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).

END-TO-END ACCOUNT: IFRAME

Sample Request

```
https://api.loginextsolutions.com/trackall/#/order?ordno=1234&aid=4b41a94b-521b-4986-920d-6e4c1cf15fd0b6&userType=DELIVERCUSTOMER
```

Display the last tracked location and the current location of an order in the End-to-End account using this iFrame.

- This iFrame can embed the tracking link in your application or website to display the last tracking information and the current location of an order in the End-to-End account based on its order number.
- You can integrate this iFrame into your application or website to display real-time order tracking information, enhancing your customers’ experience.
- To implement this, embed the URL in your application or website using a 'frame' tag in the webpage's HTML. For example, a 'Track' button on your UI could call the iFrame URL when clicked. The tracking URL can then be opened on your application’s or website's subdomain as an iFrame, allowing your customers to view live tracking of their orders.
- **Note:**
  - Specify the order number in the URL request along with the LogiNext token provided for accessing the iFrame.
  - The authentication token for the iFrame is different from the one used to call the LogiNext API. Contact your Account Manager to get the token required to access the iFrame.
  - This iFrame supports multiple user options, allowing you to share different information depending on the user you want to display it to.

REQUEST

GET `https://api.loginextsolutions.com/trackall/#/order?ordno=<ordno>&aid=<aid>&userType=<userType>`

REQUEST PARAMETERS

Parameter	Data Type	Length	Required	Description
aid				Authentication token required to access the iFrame. Specify this value without the 'BASIC' keyword. For example - f522631c-490c-46fd-9f79-ca8d14a704d7.
ordno			Conditional Mandatory	Unique number associated with the order that you want to track. This field is mandatory, if ‘orderReferenceId’ is not provided.

userType				Type of user you want to display the order tracking to. Specify ‘ADMIN’ to display the tracking information to the admin user, ‘PICKUPCUSTOMER’ to display it to the pickup customer, or ‘DELIVERCUSTOMER’ to display it to the delivery customer associated with the order. If no value is provided, the system considers ‘ADMIN’ by default.
orderReferenceId			Conditional Mandatory	Unique reference identifier associated with the order that you want to track. This field is mandatory, if ‘ordno’ is not provided.
clientCode	String	32	Optional	Name of the shipper’s company associated with the order. Pass the company name of the shipper’s account whose order you want to track.
shipmentOrderTypeCd	String	32	Optional	Type of order you want to track. Whether you want to track the ‘FM’, ‘LM’, or ‘ALLMILE’ type of order. This API lets you track First Mile, Last Mile, or ALLMILE orders. 'ALLMILE' orders involve multiple milestones (i.e., legs of movement).
orderState	String	512	Optional	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of the order, whether the order is in forward state or reverse state. Specify ‘FORWARD’ if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or ‘REVERSE’ if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).

CREATE

Sample Request

```
[
   {
   "trackerId": "358899056518932",
   "latitude": 40.760838,
   "longitude": 74.9889999,
   "time": "2018-01-04T07:21:56Z",
   "batteryPerc": 70.5,
   "speed": 40.4,
   "messageType": "REG",
   "temperature": 30.5,
   "reeferActive": true,
   "harshDriving": 63.5,
   "doorStatus":false
   }, {
   "trackerId": "4209917397",
   "latitude": 40.760838,
   "longitude": 74.9889999,
   "time": "2018-01-04T07:21:56Z",
   "batteryPerc": 70.5,
   "speed": 40.4,
   "messageType": "REG",
   "temperature": 30.5,
   "reeferActive": true,
   "harshDriving": 63.5,
   "doorStatus":false
   }
 ]
```

Success Response

```
{
```

```
    "status": 200,
    "message": "Successfully created tracking records!",
    "moreResultsExists": false,
    "data": true,
    "hasError": false
}
```

Failure Response

```
{
"status": 500,
"message": "Error occured!",
"moreResultsExists": false,
"hasError": true
}
```

Add order tracking information from your tracking system to the LogiNext system using this API.

- This API adds new order tracking information from your tracking system to the LogiNext system.
- If you receive tracking data from multiple trackers simultaneously, you can batch the data and send it to the LogiNext system using this API.

Validation:

Mandatory Check:

140001: trackerId is mandatory
140002: latitude is mandatory
140003: longitude is mandatory
140004: time is mandatory
140005: batteryPerc is mandatory
140006: messageType is mandatory

Invalid Check:

142001: trackerId is invalid
142002: latitude is invalid
142003: longitude is invalid
142004: time is invalid
142005: batteryPerc is invalid
142006: speed is invalid
142007: messageType is invalid
142008: temperature is invalid
142009: reeferActive is invalid
142010: harshDriving is invalid
142011: doorStatus is invalid
142012: trackerBranch is invalid

API TYPE

- Tier 2 API.
- This API supports batch operations; you can add a maximum of 20 tracking points in one call of this API.

REQUEST

POST `https://products.loginextsolutions.com/TrackingApp/track/tracker/v1/put`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
trackerId	String	12	Mandatory	Unique identifier of the tracker.
latitude	Double	13,10	Mandatory	Latitude of the vehicle location.
longitude	Double	13,10	Mandatory	Longitude of the vehicle location.
time	DateTime		Mandatory	Date and time (in YYYY-MM-DDTHH:MM:SS.SSSZ format) at which the vehicle is tracked. Note that the date and time must be in UTC format. For example - 2016-07-01T11:18:00.000Z.
batteryPerc	Double	5,2	Mandatory	Battery (in %) of the tracker.
speed	Double	5,2	Optional	Speed of the vehicle (in kmph).
messageType	String	10	Mandatory	Message that is sent by the tracker device to the LogiNext system. For example, regular, higher speed, etc, as needed.
temperature	Double	5,2	Optional	Temperature of the vehicle.
reeferActive	Boolean		Optional	Whether the refrigeration of the vehicle linked with the tracker is ON/OFF. When the refrigeration is switched ON, the reefer active status will update as ‘true’, whereas when the refrigeration is switched OFF, the reefer active status will update as ‘false’.
harshDriving	Double	13,10	Optional	The change in the speed of the vehicle linked with the tracker. Harsh driving can be calculated as the change in speed per second. The SI unit for this is meters per second squared (m/s^2), indicating how much the velocity changes each second. The unit of measurement will be the same as specified in System Preferences in the Settings module. If the vehicle accelerates, the change in speed will be positive, whereas when the vehicle decelerates, the change in speed will be negative.
doorStatus	Boolean		Optional	Whether the door of the vehicle linked with the tracker is open/closed. When the door is open, the door status will update as ‘true’, whereas when the door is closed, the door status will update as ‘false’.

Route

CREATE

Sample Request

```
[
    {
    "routeType":"Forward",
    "routeName":"Pune_Mumbai_2007",
    "routeCode":"Pune_Mumbai_2007",
    "originBranchName": "Pune",
    "destinationBranchName": "Mumbai",
    "serviceTypeName": "Automation",
    "deliveryType": "Document",
    "checkpointCode": "Testcheckpointroutelink01",
    "milestones": [
        {
            "fromBranch": "Pune",
```

```
            "toBranch": "Nashik",
            "milestoneType": "PICKUP",
            "modeOfTransport": "Railways",
            "deliveryDay": 1,
            "loadUnloadTime": 40,
            "startTime": "09:00:00",
            "endTime": "10:00:00"
        },
        {
        "fromBranch": "Nashik",
        "toBranch": "Mumbai",
        "milestoneType": "DELIVER",
        "modeOfTransport": "Roadways",
        "deliveryDay": 2,
        "loadUnloadTime": 20,
        "startTime": "11:00:00",
        "endTime": "16:00:00"
        }
    ]
    }
]
```


Success Response


```
{
  "status": 200,
  "message": "Route created successfully",
  "moreResultsExists": false,
  "data": [
    {
    "index": 0,
    "routeCode": "Pune_Mumbai_2007"
    }
  ],
  "hasError": false
}
```


Partial Success Response


```
{
  "status": 207,
  "message": "Routes created partially",
  "moreResultsExists": false,
  "data": [{
    "index": 0,
    "routeCode": "Pune_Mumbai_2009"
    }],
    "error": [
    {
    "index": 1,
    "errorList": [
      {
      "key": "routeName",
      "message": ["Route Name is already exists"],
      "errorCode": 68012
      },
      {
      "key": "routeCode",
      "message": ["Route code is already exists"],
      "errorCode": 1580000
      }
    ]
```

```
  }],
  "hasError": true
}
```

Failure Response

```
{
      "status": 409,
      "message": "Invalid request",
      "moreResultsExists": false,
      "error": [{
      "index": 0,
      "errorList": [
        {
        "key": "routeName",
        "message": ["Path Name is already exists"],
        "errorCode": 68012
        },
        {
        "milestoneErrorMap": {
        "milestone_0": [{
        "key": "fromBranch",
        "message": ["From Hub is mandatory"],
        "errorCode": 1500002
        }]
        }
        }
      ]
    }
    ],
    "hasError": true
  }
```

Create new routes in the LogiNext system with this API.

- This API creates a new Route (i.e., the path of an order from its origin branch to its destination branch through a set of intermediate branches). You can specify these routes when creating orders for an End-to-End account.
- Routes can be of two types - forward routes and return routes. Forward routes are for deliveries to the end customer whereas return routes are for defining the return path of orders.

API TYPE

- Tier 1 API.
- This API supports batch operations; you can create a maximum of 20 routes in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ClientApp/mile/v1/create/route`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
routeType	String		Mandatory	Type of the route. Specify 'Forward' to create a forward route or 'Return' to create a return route.
routeName	String	250	Mandatory	Name of the route.
routeCode	String	250	Mandatory	Unique identifier for the route in the system.
originBranchName	String		Mandatory	Name of the origin branch.

destinationName	String		Mandatory	Name of the destination branch.
serviceTypeName	String		Mandatory	Service type applicable for this route. Service Types let you specify the different types of services you may want to provide your customers. For example, a one-day delivery, 30-minute delivery, and so on.
deliveryType	String	40	Mandatory	In certain operations, different skill sets or special delivery requirements are needed. For example, groceries or food items must be separated from toiletries orders, or cake orders cannot be combined with flower orders while delivering. In such cases, if you want to classify orders using the Delivery Type, you can use this field to ensure the orders are assigned to delivery associates configured in the LogiNext system with the required skill sets or delivery types. Note that you must define the Skill Sets in the Fleet Configuration module under Settings before passing it here in the orders. Contact your Account Manager to set these values for you. You can pass multiple Skill Sets in a comma-separated format in this API.
checkpointCode	String		Optional	Checkpoints applicable for this route.
fromBranch	String		Mandatory	Branch from which the milestone begins.
toBranch	String		Mandatory	Branch at which the milestone ends.
milestoneType	String		Mandatory	Whether this is a pickup milestone or a delivery milestone.
modeOfTransport	String		Mandatory	Mode of transportation for the milestone. Whether it is Railways, Roadways, Airways, or Waterways.
deliveryDay	Integer		Mandatory	Day on which the milestone begins. For example, if this is set to Day 3, then that milestone will begin 3 days after the first milestone (if the first milestone begins on Day 0) (i.e. on the 4th day).
startTime	String		Mandatory	Start time (in HH:MM:SS format) by which the trip must start for this milestone.
endTime	String		Mandatory	End time (in HH:MM:SS format) by which the trip must be completed for this milestone.
loadUnloadTime	Integer		Optional	Time taken to load/unload the order during the trip. This parameter can be used while planning trips.

Mobile

Push the necessary data from your mobile application into the LogiNext system with these Mobile APIs.

- If you have your own mobile application for order fulfillment, you can send the required data directly into the LogiNext system using these Mobile APIs.
- **Note:** These APIs require the delivery associate's tokens. Refer to the 'Authenticate Delivery Associate' section under the 'Authentication' module for details on acquiring the token.

ACCEPT ORDER

Sample Request

```
{
  "orderReferenceId":"a3bee4486d9f467d72e96f4d32c5569b",
  "parentOrderNo":"1316MDO",
  "orderAcceptTime":"2017-12-27T10:00:00Z",
  "latitude": 40.760838,
```

```
  "longitude": 74.9099327
}
```

Success Response

```
{
  "status": 200,
  "message": "success",
  "hasError": false
}
```

Mark an order as ‘Accepted’ by the delivery associate using this API.

- This API marks an order as ‘Accepted’ by the delivery associate.
- Include the delivery associate's token and key in the header of this API. Note that the account-level token and key differ from the delivery associate’s token and key. You can retrieve the delivery associate's token and key by calling the Delivery Associate Authenticate API.

API TYPE

- Tier 2 API.

REQUEST

PUT `https://api.loginextsolutions.com/ShipmentApp/v1/mobile/order/accept`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderReferenceId	String	32	Mandatory	Unique reference identifier associated with the order. This ID is provided in the Create Order API response when the associated order is created in the system. If your order is Multi-Stop Delivery, you can pass any one Reference ID among the nested orders. To update the status of only one particular order (among many under a Parent Order Number), omit the Parent Order Number and pass only the Reference ID.
parentOrderNo	String	100	Optional	Parent Order Number is an identifier that can be used to track multiple orders together. If your order is Single Pickup - Single Delivery, pass the Parent Order Number associated with that order. If your order is Single Pickup - Multiple Delivery and you want to update the status of all associated orders, you can pass the Parent Order Number in this field. However, if you need to update the status of only one specific order (among many under a Parent Order Number), you can omit this field and specify the Reference ID of that order in the 'orderReferenceId' field.
orderAcceptTime	String	32	Optional	Specify the date and time (in UTC format) when the order is accepted. This timestamp cannot be later than the current time (i.e., the time when the API is called). If not provided, the system will use the current timestamp as the order acceptance time. For example - 2017-12-27T10:00:00Z.
latitude	Double	15	Optional	Latitude coordinates of the location where the order is accepted. Note that this value is not used for ETA calculations, which rely on tracking points.
longitude	Double	15	Optional	Latitude coordinates of the location where the order is accepted. Note that this value is not used for ETA calculations, which rely on tracking points.

REJECT ORDER

Sample Request

```
{
  "orderReferenceIds":["6b106144208243ffb4b8c4114fd44f123d"],
  "checkInLocation":"PICKUP",
  "checkinLatitude":40.760838,
  "checkinLongitude":74.11223,
  "checkInTime":"2018-02-08T09:30:00Z"
}
```

Success Response

```
{
  "status": 200,
  "message": "success",
  "hasError": false
}
```

Mark an order as ‘Rejected’ by the delivery associate using this API.

- This API marks the specified order as ‘Rejected’ by the delivery associate.
- Include the delivery associate's token and key in the header of this API. Note that the account-level token and key differ from the delivery associate’s token and key. You can retrieve the delivery associate's token and key by calling the Delivery Associate Authenticate API.

API TYPE

- Tier 2 API.

REQUEST

PUT `https://api.loginextsolutions.com/ShipmentApp/v1/mobile/checkin`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderReferenceIds	String	100	Mandatory	Unique reference ID associated with the order that you want to mark as rejected. This ID is provided in the Create Order API response when the associated order is created in the system.
checkInLocation	String	32	Mandatory	Location where the delivery associate has checked in. Specify 'PICKUP' for the pickup location and 'DELIVER' for the delivery location.
checkinLatitude	Double	15	Optional	Latitude coordinates of the location where the delivery associate checked in for the pickup/delivery process.
checkinLongitude	Double	15	Optional	Longitude coordinates of the location where the delivery associate checked in for the pickup/delivery process.
checkinTime	Date		Mandatory	Specify the date and time (in UTC format) at which the delivery associate has checked in.

CHECK IN (API)

Sample Request

```
{
  "orderReferenceIds":["6b106144208243ffb4b8c4114fd44f123d"],
  "checkInLocation":"PICKUP",
  "checkinLatitude":"40.760838",
  "checkinLongitude":"74 .11223",
```

```
  "checkInTime":"2018-02-08T09:30:00Z"
}
```

Success Response

```
{
    "status": 200,
    "message": "Check in marked successfully",
    "hasError": false
}
```

Mark the delivery associate's 'Check-in' at the customer's pickup or delivery location within the LogiNext system using this API.

- This API marks the delivery associate's 'Check-in' at the customer's pickup or delivery location.
- Include the delivery associate's token and key in the header of this API. Note that the account-level token and key differ from the delivery associate's token and key. You can retrieve the delivery associate's token and key by calling the Delivery Associate Authenticate API.

API TYPE

- Tier 2 API.

REQUEST

PUT `https://api.loginextsolutions.com/ShipmentApp/v1/mobile/checkin`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderReferenceIds	List	32	Mandatory	Unique reference ID associated with the order for which you want to mark the delivery associate as check-in for. This ID is provided in the Create Order API response when the associated order is created in the system. If your order is Single Pickup - Single Delivery, pass the Reference ID generated for that order. If your order is Single Pickup - Multiple Delivery, you can pass any one Reference ID among the orders.
checkInLocation	String	100	Mandatory	Location where the delivery associate has checked in. Specify 'PICKUP' for the pickup location and 'DELIVER' for the delivery location.
checkinLatitude	Double	100	Optional	Latitude coordinates of the location where the delivery associate checked in for the pickup/delivery process.
checkinLongitude	Double	100	Optional	Longitude coordinates of the location where the delivery associate checked in for the pickup/delivery process.
checkInTime	Date	100	Mandatory	Specify the date and time (in YYYY-MM-DDTHH:MM:SS.SSSZ format) at which the delivery associate has checked in. Note that the date and time must be in UTC format. For example - 2016-07-01T11:18:00.000Z.

CREATE TRACKING

Sample Request

```
{
  "location": [{
    "latitude": 40.760838,
    "longitude": 74.9094089,
    "speed": 0,
    "battery": 100,
    "locationSource": "fused",
```

```
    "trackingDt": "2017-12-11T07:21:39Z",
    "type": "MOBREG",
    "distanceFromLastLocation": 0,
    "accuracy": 23.878000259399414,
    "bearing": 0,
    "altitude": 0,
    "hasAccuracy": "0",
    "hasBearing": "0",
    "hasSpeed": "0",
    "lastLatitude": 40.760838,
    "lastLongitude": 74.9094089,
    "isFirstPointFl": "0",
    "currentTime": 1512976899548,
    "previousTime": 1512976899532,
    "signalStrength": 30,
    "appStatus": "100",
    "networkType": "WIFI",
    "dataNetworkType": "Unknown",
    "isGsmFl": false,
    "isActiveNetworkMetered": false,
    "imei": "911380458661315"
  }, {
    "latitude": 40.760838,
    "longitude": 74.9094089,
    "speed": 0,
    "battery": 100,
    "locationSource": "fused",
    "trackingDt": "2017-12-11T07:21:19Z",
    "type": "MOBREG",
    "distanceFromLastLocation": 0,
    "accuracy": 23.87700080871582,
    "bearing": 0,
    "altitude": 0,
    "hasAccuracy": "0",
    "hasBearing": "0",
    "hasSpeed": "0",
    "lastLatitude": 40.760838,
    "lastLongitude": 74.9094089,
    "isFirstPointFl": "0",
    "currentTime": 1512976879541,
    "previousTime": 1512976879521,
    "signalStrength": 30,
    "appStatus": "100",
    "networkType": "WIFI",
    "dataNetworkType": "Unknown",
    "isGsmFl": false,
    "isActiveNetworkMetered": false,
    "imei": "911380458661315"
  }]
}
```


Success Response


```
{
    "status": 200,
    "data": {
        "msg": [
            "2018-11-11T07:20:59",
            "2018-11-11T07:21:19",
            "2018-11-11T07:21:39"
        ],
        "previousTimes": [
            1512976859528,
            1512976879521,
```

```
            1512976899532
        ]
    },
    "hasError": false
}
```

Failure Response

```
{
    "status": 500,
    "message": "Error occured!",
    "moreResultsExists": false,
    "hasError": true
}
```

Retrieve the current location of your delivery associates using this API when they are not using the Driver App.

- This API retrieves the current location of your delivery associates when they are not using the Driver App.
- Note that the 'msg' field in the success response of this API indicates the time at which the API is called, while the 'previousTime' field indicates the timestamp of the previous tracking event in epoch format.

API TYPE

- Tier 2 API.

REQUEST

POST `https://products.loginextsolutions.com/TrackingApp/track/mobile/put`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
latitude	Double	13,10	Mandatory	Latitude coordinates of the delivery associate's location. For example - 40.760838.
longitude	Double	13,10	Mandatory	Longitude coordinates of the delivery associate's location. For example - 74.9094089.
trackingDt	String		Mandatory	Date and time (in UTC format) at which you want to track the delivery associates' location. For example - 2018-12-11T07:21:39Z.
currentTime	Long		Mandatory	Current time at which the delivery associate’s location is tracked. For example - 1512976879541.
speed	Number		Mandatory	Speed (in m/s) of the delivery associate’s vehicle at the time of location tracking. This value is obtained from the Android system classes. For more details, refer to the ‘Android documentation’.
battery	Integer	3	Mandatory	Battery percentage of the delivery associate's phone at the time of sending the tracking point.
accuracy	Number	13,10	Mandatory	Estimated accuracy (in meters) of the current location. For example - 23.878000259.
altitude	Number	10	Optional	Altitude (in meters) of the delivery associate’s location. For example - 235.
bearing	Number	10	Optional	Horizontal travel distance of the device (in degrees). If the phone supports this sensor, send the value. For example, a value between 0 and 3600, where 0 represents North, considering the clockwise movement.

locationSource	String	32	Optional	Specify the source that provides the location. For example - fused, wifi, GPS.
type	String	40	Mandatory	The tracking type field identifies whether the tracking is from the delivery associate's phone or another device. It should be hardcoded as 'MOBREG' when tracking points are coming from the phone.
isFirstPointFl	Boolean	1	Mandatory	Whether the current tracking data sent from the delivery associate's device is the first update after each login.
lastLatitude	Double	13,10	Mandatory	Last tracked latitude coordinates of the delivery associate's location. Note that if ‘isFirstPointFl’ is set to ‘1’, you can pass zero in this field. For example - 40.760838.
lastLongitude	Double	13,10	Mandatory	Last tracked longitude coordinates of the delivery associate's location. Note that if ‘isFirstPointFl’ is set to ‘1’, you can pass zero in this field. For example - 74.9094089.
distanceFromLastLocation	Number		Mandatory	Distance from the last location update (in meters). If 'isFirstPointFl' is set to '1', you can pass zero as the distance from the previous location. For example - 23.5.
previousTime	Long		Mandatory	Timestamp of the last location update (in milliseconds). For example - 1512976879521.
hasAccuracy	Boolean	1	Optional	Whether the current location is accurate or not. Specify ‘1’, if the current location is accurate (i.e., true), or ‘0’ if it is inaccurate (i.e., false).
hasBearing	Boolean	1	Optional	Whether the current location has bearing or not. Specify ‘1’, if the current location has a bearing (i.e., true), or ‘0’ if it does not have a bearing (i.e., false).
hasSpeed	Boolean	1	Optional	Whether the vehicle is in speed or not. Specify ‘1’ if the vehicle is in speed (i.e., true), or ‘0’ if it is not (i.e., false).
networkType	String		Optional	Network type the delivery associate's phone is connected to when the tracking location is sent. This can be retrieved using Android's core Connectivity Manager APIs. Specify the values as WIFI, MOBILE, or UNKNOWN, as needed.
signalStrength	Integer		Mandatory	Mobile network strength of the delivery associate's phone at the time when the tracking location is sent using WiFi, GSM, or LTE.
dataNetworkType	String		Optional	Data connectivity type of the delivery associate’s phone. For example - 1xRTT, EDGE, LTE, CDMA, GPRS, and HSPA.
isGsmFl	Boolean	1	Optional	Whether the current network connectivity type of the delivery associate’s phone is GSM (Global System for Mobile Communications) or not. This can be retrieved from the Android core Connectivity Manager APIs. Specify ‘True’ if the network type is GSM (i.e., 1) or ‘False’, if it is not (i.e., 0).
isActiveNetworkMetered	Boolean	1	Optional	Whether the currently active data network is metered or not. A network is classified as metered when the user is sensitive to heavy data usage on that connection due to monetary costs, data limitations, or battery/performance issues. This can be retrieved from the Android core Connectivity Manager APIs. Specify ‘True’ if the network is metered (i.e., 1) or ‘False’ if it is not metered (i.e., 0).
				Activity status of the app, indicating whether it is Foreground, Background, Service, Gone, Sleep, Visible, or Unknown. This information

appStatus	Integer		Optional	can be retrieved using the Android Activity Manager documentation. Specify 100 for Foreground, 400 for Background, 500 for Empty, 125 for Foreground_Service, 1000 for Gone, and 200 for Visible.
imei	String	40	Mandatory	IMEI number of the delivery associate's phone. For example - 911380134661315.

ESIGN / EPOD UPLOAD

Sample Request

```
{
    "imageName": "image.png",
    "orderLocation" : "DELIVERYLOCATION",
    "imageType" : "ESIGN",
    "orderReferenceIds":["a3bee2286d9f447d92e96f4d32c5569b", "a3bee2286d9f447d92e96f4d32c5569b"],
    "latitude": 40.760838,
    "longitude": 74.9095327
}
```

Success Response

```
{
  "status": 200,
  "message": "Uploaded successfully",
  "hasError": false
}
```

Upload the ESign or EPOD of the orders using this API.

- This API uploads the ESign or EPOD of the orders within the LogiNext system.
- Pass the Content Type as 'multipart/form-data' in the header of this API.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/v1/mobile/image/upload`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
imageName	String	100	Mandatory	Name of the image that will be used to save it in the application.
orderLocation	Double	15	Mandatory	Type of location where the EPOD/ESIGN is captured for an order. Specify 'PICKUPLOCATION' if the EPOD/ESIGN is uploaded for order's pickup location of the order or 'DELIVERYLOCATION' if it's uploaded for the delivery location.
imageType	String	100	Mandatory	Type of the image. Specify 'ESIGN' for an e-signature image or 'EPOD' for an electronic proof of delivery image.
orderReferenceId	List		Mandatory	Unique reference ID of the order. This ID is provided in the Create Order API response when the associated order is created in the system.
longitude	Double	15	Optional	Latitude coordinates of the location where the EPOD/ESIGN is captured. For example - 17.996.

longitude	Double	15	Optional	Longitude coordinates of the location where the EPOD/ESIGN is captured. For example - 17.996.

Route Planning

PLAN

Sample Request

```
{
  "routeName": "PLAN-1548845037527",
  "startTimeWindow": "2018-12-01T10:43:57.563Z",
  "endTimeWindow": "2018-12-31T10:43:57.560Z",
  "hubReferenceIds": [],
  "orderReferenceIds": ["8dd4e493c715493da182f52eb69d1bcb", "73d57cbe0dc147da8c6b4503b76d5bda"],
  "planningProfile": "1",
  "territoryProfile": "80",
  "mode": "OPTIMIZE_DISTANCE_TIME",
  "deliveryMediumReferenceIds": ["8dd4e493c715493da182f52eb69d1bcb", "73d57cbe0dc147da8c6b4503b76d5bda"]
}
```

Success Response

```
{
  "status": 202,
  "data": "Planning request received successfully.",
 "message": "Success!"
}
```

Failure Response 1

```
{
    "status": 409,
    "message": "Bad Request",
    "errors": [
        {
            "key": "plan",
            "data": [
                "5bc59a848ef4412495012c40af7ac22c"
            ],
            "message": "Delivery Associate(s) does not exist",
            "errorCode": 62005
        }
    ]
}
```

Failure Response 2

```
{
    "status": 409,
    "message": "Bad Request",
    "errors": [
        {
            "key": "delivery medium reference",
```

```
            "message": "In the Sequence planning objective,there should be only one Delivery Associate",
            "errorCode": 60005
        },
        {
            "key": "startTimeWindow/endTimeWindow",
            "message": "No Orders found in the selected time window ",
            "errorCode": 68005
        }
    ]
}
```

Create optimized route plans for orders using this API.

- This API creates optimized route plans in the LogiNext system for your orders. It runs the route planning operation by taking a list of orders, delivery associates, and/or fleet types as input. It accepts details of both your owned and outsourced fleets, allowing you to plan a single route using both.
- Note that if you specify 'SEQUENCE' in the 'mode' field, you can pass only 1 Reference ID of the delivery associate in the 'deliveryMediumReferenceIds' field.
- You can only create route plans for orders from the past three years.

API TYPE

- Special Tier API.
- Rate Limit: 1 request per minute.
- This is an asynchronous API. After making a request, you will receive a 202 status code in the response. The updated route plan, including the new order sequence, will be sent via the Route Planning webhook to the URL configured in your system.

REQUEST

POST `https://api.loginextsolutions.com/TripApp/mile/v1/plan`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
routeName	String	32	Mandatory	Name of the route plan.
startTimeWindow	String	32	Conditional Mandatory	The start time window of the orders that are considered for route planning. This field is mandatory, if 'orderReferenceIds' is not provided.
endTimeWindow	String	32	Conditional Mandatory	The end time window of the orders that are considered for route planning. This field is mandatory, if 'orderReferenceIds' is not provided.
hubReferenceIds	List	32	Optional	List of unique reference identifiers associated with the branches for which the route plan is created or executed. If this field is not provided, the parent branch is considered by default.
orderReferenceIds	List	32	Conditional Mandatory	List of unique reference identifiers of the orders you want to consider for route planning. This field is mandatory, if 'startTimeWindow' and 'endTimeWindow' are not provided.
planningProfile	String	32	Optional	Name of the planning profile you want to use for this route planning operation. You can set up multiple route planning profiles in the LogiNext system. If this field is not provided, the default route planning profile will be considered. Note that this field must not be left blank.
territoryProfile	String	32	Optional	Name of the territory profile you want to use for this route planning operation. You can set up multiple territory profiles in the LogiNext system. If this field is not provided, the default territory profile will be considered. Note that this field must not be left blank.

mode	String	32	Mandatory	The planning objective of the route planning operation. Specify 'CONSIDER_RESOURCE_COST' to optimize fleet capacity, 'OPTIMIZE_DISTANCE_TIME' to optimize time and distance, 'LOADBALANCING' for balanced optimization, or 'SEQUENCE' for sequence optimization.
deliveryMediumReferenceIds	List	32	Optional	List of unique reference identifiers of the delivery associate that you want to consider for this route planning operation. If this field is not provided, all active and present delivery associates will be considered.

REPLAN

Sample Request

```
[
    "8dd4e493c715493da182f52eb69d1bcb"
]
```

Success Response

```
{
    "status": 202,
    "message": "Success",
    "data": "Replanning request received successfully."
}
```

Failure Response

```
{
    "status": 409,
    "message": "Bad Request",
    "errors": [
        {
            "key": "",
            "message": [
                "73d57cbe0dc147da8c6b4503b76d5bda"
            ],
            "code": "Trip does not have any pending shipments to be replanned"
        }
    ]
}
```

Replans a single ‘Not Started’ or ‘Started’ trip using this API.

- This API replans a single ‘Not Started’ or ‘Started’ trip in the LogiNext system. It returns an updated sequence for delivering the remaining orders in the trip.
- It identifies trips using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Trip API response when the associated trip is created in the system.
- For ‘Not Started’ trips, the API considers the branch location as the starting point and for ‘Started’ trips, it uses the last tracked location of the delivery associate who is assigned to this trip. If no tracking information is available, the location of the last delivered order will be used.
- If there are orders that can no longer be fulfilled within their time windows at the time of replanning, those orders will be unassigned from the trip and will be part of the unallocation reasons object in the Route Planning webhook. These orders can then be manually assigned to other trips using the ‘Suggest Trips’ API and the ‘Assign’ API.
- All 'Not Delivered' orders will be considered for replanning with this API. For example, if the delivery associate has a trip with 10 orders and has delivered the 1st and 4th orders when this API is called, the 2nd and 3rd orders will also be replanned. After replanning, the new sequence of orders will start from the 5th order onward, as the 4th order has already been delivered. The sequence for the 2nd and 3rd orders will remain blank.

API TYPE

- Special Tier API.
- Rate Limit: 1 request per 20 seconds.
- This API accepts only one Trip Reference ID in one call.
- This is an asynchronous API. After making a request, you will receive a 202 status code in the response. The updated route plan, including the new order sequence, will be sent via the Route Planning webhook to the URL configured in your system.

REQUEST

POST `https://api.loginextsolutions.com/TripApp/mile/v1/resequence`

REQUEST PARAMETER

Parameter	Datatype	Length	Required	Description
reference ID	String	32	Mandatory	Unique reference identifier of the trip you want to replan.

SEQUENCE OPTIMIZE

Sample Request

```
{
  "routeName": "testRoute",
  "planningProfile": "Default",
  "plan": [
    {
      "deliveryMediumReferenceId": "409fc811b2a043a99f0bc3dde34edb8d",
      "orderReferenceIds": [
        "c3faa036189146b2b1c2636aad6753de"
      ]
    }
  ]
}
```

Success Response

```
{
  "status": 202,
  "message": "Success",
  "data": "Sequencing request received successfully."
}
```

Create an optimized sequence of orders in route plans using this API.

- This API generates an optimized order sequence that delivery associates must follow while fulfilling orders.

API TYPE

- Special Tier API.
- Rate Limit: 3 requests per minute.
- This API accepts up to 20 Delivery Associate Reference IDs in one call.

REQUEST

POST `https://api.loginextsolutions.com/TripApp/mile/v1/optimize`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
routeName	String	32	Mandatory	Name of the route plan.

planningProfile	String	32	Optional	Name of the planning profile you want to use for this route planning operation. You can set up multiple route planning profiles in the LogiNext system. If this field is not provided, the default route planning profile will be considered. Note that this field must not be left blank.
deliveryMediumReferenceIds	List	32	Optional	List of unique reference identifiers of the delivery associate that you want to consider for this route planning operation. If this field is not provided, all active and present delivery associates will be considered.
orderReferenceIds	List	32	Conditional Mandatory	List of unique reference identifiers of the orders you want to consider for route planning. This field is mandatory, if 'startTimeWindow' and 'endTimeWindow' are not provided.

Carrier Assignment

ACCEPT ORDER

Sample Request

```
{
  "orderReferenceId": "a3bee4486d9f467d72e96f4d32c5569b",
  "carrierBranchName": "Best Logistics LLC - NYC"
}
```

Success Response

```
{
  "status": 200,
  "message": "Order Accepted Successfully",
  "hasError": false
}
```

Failure Response

```
{
    "status": 409,
    "message": "Order Accept failed",
    "moreResultsExists" : false,
    "errors": [
        {
            "index": 0,
            "errorList": [
                {
                    "key": "orderReferenceId",
                    "message": ["Order Reference ID is mandatory."],
                    "errorCode": 10001
                },
                {
                    "key": "carrierBranchName",
                    "message": ["Carrier Branch Name is mandatory."]
                    "errorCode": 12000
                }
```

```
            ]
        }
    ]
}
```

Capture a carrier's confirmation of order acceptance in the LogiNext system using this API.

- This API captures the response when an integrated carrier accepts an order offered by the Auto-Assignment engine.
- When the Auto-Assignment engine offers an order to one or more carriers, each offer has an expiration time by which a response is expected. If an integrated carrier accepts the order within the due time, this API records the acceptance.

API TYPE

- Tier 2 API.

REQUEST

PUT `https://api.loginextsolutions.com/ShipmentApp/mile/v1/accept`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderReferenceId	String	32	Conditional Mandatory	Unique reference identifier of the order. This field is mandatory, if the order does not have any milestones or 'milestoneReferenceId' is not provided.
milestoneReferenceId	String	32	Conditional Mandatory	Unique reference identifier associated with the milestone. This field is mandatory for End-to-End account orders.
carrierBranchName	String	255	Mandatory	Name of the branch associated with the carrier.

REJECT ORDER

Sample Request

```
{
  "orderReferenceId": "a3bee4486d9f467d72e96f4d32c5569b",
  "carrierBranchName": "Best Logistics LLC - NYC"
}
```

Success Response

```
{
  "status": 200,
  "message": "Order Rejected Successfully",
  "hasError": false
}
```

Failure Response

```
{
    "status": 409,
    "message": "Order Reject failed",
    "moreResultsExists" : false,
    "errors": [
        {
            "index": 0,
            "errorList": [
                {
```

```
                "key": "orderReferenceId",
                "message": ["Order Reference ID is mandatory."],
                "errorCode": 10001
            },
            {
                "key": "carrierBranchName",
                "message": ["Carrier Branch Name is mandatory."]
                "errorCode": 12000
            }
        ]
    }
  ]
}
```

Capture a carrier's order rejection in the LogiNext system using this API.

- This API captures the response when an integrated carrier rejects an order offered by the Auto-Assignment engine.
- When the Auto-Assignment engine offers an order to one or more carriers, each offer has an expiration time by which a response is expected. If an integrated carrier rejects the order within the due time, this API records the rejection.

API TYPE

- Tier 2 API.

REQUEST

PUT `https://api.loginextsolutions.com/ShipmentApp/mile/v1/reject`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderReferenceId	String	32	Conditional Mandatory	Unique reference identifier of the order. This field is mandatory, if the order does not have any milestones or 'milestoneReferenceId' is not provided.
milestoneReferenceId	String	32	Conditional Mandatory	Unique reference identifier associated with the milestone. This field is mandatory for End-to-End account orders.
carrierBranchName	String	255	Mandatory	Name of the branch associated with the carrier.

Geocoding

GET

Sample Request

```
{
    "apartment": "611",
    "streetName": "5th Ave",
    "landmark": "near Saks",
    "city": "New York City",
    "country": "United States",
    "state": "NY",
    "pincode": "10022"
}
```

Success Response

```
{
  "status": 200,
  "message": "Geocodes Fetched Successfully",
  "moreResultsExists": false,
  "data": [
      {
          "lat": 20.59368,
          "lng": 78.96288,
          "geocodingSource": "GOOGLE_GEOCODING",
          "types": "[country, political]",
          "locationType": "APPROXIMATE",
          "partialMatch": false,
          "isApproximate": true
      }
  ],
  "hasError": false
}
```


Retrieve the geo-coordinates of a specified location using this API.

- This API retrieves the geo-coordinates of a specified location.
- In the Request Body, specify the address whose coordinates you want to retrieve.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/CommonApp/mile/v1/geocode`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
apartment	String		Optional	Name of the apartment building/complex in the address for which you want to retrieve the geocoordinates.
streetName	String		Optional	Name of the society or street in the address for which you want to retrieve the geocoordinates.
landmark	String		Optional	Landmark of the location for which you want to retrieve the geocoordinates.
locality	String		Optional	Name of the locality or area in the address for which you want to retrieve the geocoordinates.
city	String		Optional	Name of the city in the address for which you want to retrieve the geocoordinates.
country	String		Optional	Name of the country in the address for which you want to retrieve the geocoordinates. This should be as per the Country Codes available in the LogiNext system.
state	String		Optional	Name of the state in the address for which you want to retrieve the geocoordinates. This should be as per the State Codes available in the LogiNext system for the selected country.
pincode	String		Mandatory	Pin code of the location for which you want to retrieve the geocoordinates.

Serviceability

LOCATION

Sample Request

```
{
    "latitude" : "40.760838",
    "longitude" : "74.832830",
    "apartmentName": "Inorbit Mall",
    "streetName": "Link Road",
    "locality": "Goregaon West",
    "city": "Mumbai",
    "country": "IND",
    "state": "MH",
    "postalCode": "4000104",
    "geofenceProfileName": "Default"
}
```

Success Response

```
{
    "status": 200,
    "data": {
        "geofenceName": "GeofenceA",
        "geofenceType": "Hub",
        "geofenceShape": "Polygon",
        "geofenceArea": 335.55,
        "geofenceReferenceId": "3e290b46495b482a8e70e1078bd73c3f",
        "deliveryAssociates": [
            {
                "isActiveFl": true,
                "deliveryAssociateName": "John Doe",
                "deliveryAssociateRefId": "5c4fa64a97e24399a6cf91ef9767f980"
            }
        ]
    },
    "hasError": false
}
```

Check whether a particular location is serviceable using this API.

- This API checks whether you service a specific location (i.e., if your operations are available at a given location) or not within the LogiNext system.
- If the location is serviceable, it also provides the associated territory details for that location.
- You can include either the geo-coordinates (latitude and longitude) or the address in the request body to check if a geofence/territory already exists for that location or not.
- If only address details are provided without geo-coordinates, the API will geocode the address and check serviceability for the generated geo-coordinates.
- Additionally, you can also specify a territory profile. If both a territory profile and geo-coordinates are provided, the API will check service availability specifically within the given territory profile.

API TYPE

- Tier 2 API.
- This API does not support batch operations; you can check the serviceability of only one location in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/GeofenceApp/mile/v1/serviceability/get`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
latitude	String		Conditional Mandatory	Latitude coordinates of the location for which you want to check the serviceability. This field is mandatory, if 'longitude' is provided.
longitude	String		Conditional Mandatory	Longitude coordinates of the location for which you want to check the serviceability. This field is mandatory, if 'latitude' is provided.
apartmentName	String		Optional	Name of the apartment building/complex in the address for which you want to check the serviceability.
streetName	String		Optional	Name of the society or street in the address for which you want to check the serviceability.
locality	String		Optional	Name of the locality or area in the address for which you want to check the serviceability.
city	String		Optional	Name of the city in the address for which you want to check the serviceability.
country	String		Optional	Name of the country in the address for which you want to check the serviceability. This should be as per the Country Codes available in the LogiNext system.
state	String		Optional	Name of the state in the address for which you want to check the serviceability. This should be as per the State Codes available in the LogiNext system for the selected country.
postalCode	String		Optional	Pin code of the location for which you want to check the serviceability.
geofenceProfileName	String		Optional	Name of the territory profile in which you want to check serviceability. If this field is not provided, the default territory profile will be considered.

SHIPPER

Sample Request

```
{
    "latitude" : "40.760838",
    "longitude" : "74.832830",
    "apartment": "611",
    "streetName": "5th Ave",
    "landmark": "near Saks",
    "locality": "Mahattan",
    "city": "New York City",
    "country": "United States",
    "state": "NY",
    "pincode": "10022",
    "clientCode": "Salestap"
}
```

Success Response: If address is serviceable

```
{
    "status": 200,
    "message": "Address falls in the Service Area",
    "data": {
        "serviceAreaProfileName": "New York City Profile",
```

```
        "zone": "Manhattan",
        "serviceableBranch":"Manhattan Hub"
    },
    "hasError": false
}
```

Success Response: If address is not serviceable

```
{
    "status": 200,
    "message": "Address doesn't fall in the Service Area",
    "data": {},
    "hasError": false
}
```

Check whether a specific location is serviceable for your shippers using this API.

- This API checks whether your services are available for a shipper at a specific location (i.e., if your operations cover the specified shipper at the given location) or not within the LogiNext system.
- To check serviceability for your shippers, it is essential to link the Service Area Profile to the shipper.
- If the location is serviceable for shippers, the API response includes the associated Service Area Profile, Zone, and the serviceable branch for that location.
- In the Request Body, specify either the geo-coordinates (latitude and longitude) or the address details of the location you want to check.
- If only address details are provided without geo-coordinates, the API will geocode the address and check serviceability for the generated geo-coordinates.
- **Note:**
    - If your zone is created based on the 'Territory' preference, you must specify either geo-coordinates or address details.
    - If your zone is created based on the 'Postal Code' preference in the Service Area Profile linked to the shipper, specify the pincode instead.

API TYPE

- Tier 2 API.
- This API does not support batch operations; you can check the serviceability of only one location in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/ServiceAreaApp/v1/serviceability`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
latitude	String		Conditional Mandatory	Latitude coordinates of the location for which you want to check serviceability for the shippers. This field is mandatory, if 'longitude' is provided.
longitude	String		Conditional Mandatory	Longitude coordinates of the location for which you want to check serviceability for the shippers. This field is mandatory, if 'latitude' is provided.
apartmentName	String		Optional	Name of the apartment building/complex in the address for which you want to check serviceability for the shippers.
streetName	String		Optional	Name of the society or street in the address for which you want to check serviceability for the shippers.
locality	String		Optional	Name of the locality or area in the address for which you want to check serviceability for the shippers.
city	String		Optional	Name of the city in the address for which you want to check serviceability for the shippers.

country	String	Optional	Name of the country in the address for which you want to check serviceability for the shippers. This should be as per the Country Codes available in the LogiNext system.
state	String	Optional	Name of the state in the address for which you want to check serviceability for the shippers. This should be as per the State Codes available in the LogiNext system for the selected country.
pincode	String	Optional	Pin code of the location for which you want to check serviceability for the shippers. This field is mandatory, if the Service Area Profile is linked to the shipper and is based on the postal codes.
clientCode	String	Optional	Name of the company associated with the shipper's account. Pass the company name of the shipper's account if you want to check the serviceability on behalf of one of your shippers.

Cash Transaction

V2

Sample Request

```
[
    {
        "transactionId": "TR43244-5565232",
        "transactionAmount": 100,
        "deliveryMediumReferenceId": "ad42275cc4194c30846ce0eccf776db2",
        "transactionType": "Debit",
        "reason": "Customer does not have change",
        "transactionDate": "",
        "comment": "Comment",
        "transferType": "transferToBranch"
    }
]
```

Success Response

```
{
  "status": 200,
  "message": "Transaction created successfully",
  "moreResultsExists": false,
  "hasError": false
}
```

Failure Response

```
{
  "status": 409,
  "message": "Some issue encountered in server",
  "moreResultsExists": false,
  "error": [
    {
    "index": 0,
    "errorList": [
      {
```

```
        "key": "transactionId",
        "message": "Transaction ID already exists in system.",
        "errorCode": 72000
        }
      ]
    }
  ],
  "hasError": true
  }
```

Record new cash transactions for your delivery associates using this API.

- This API creates a Credit or Debit cash transaction with details such as amount, type, reason, and more.
- It requires the Transaction ID and Reference ID of a delivery associate for whom the transaction is being created.

API TYPE

- Tier 2 API.
- This API does not support batch operations; you can only create one cash transaction in one call of this API.

REQUEST

POST `https://api.loginextsolutions.com/DeliveryMediumApp/mile/v2/create/transaction`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
transactionId	String		Mandatory	Unique identifier associated with the transaction. It is usually mentioned in the acknowledgment receipt. In case there isn't a receipt associated with the transaction, you can provide any alphanumeric value as the Transaction ID while ensuring that the value you are entering isn't associated with another transaction, i.e., it should be unique.
transactionAmount	Double		Mandatory	Amount involved in this particular transaction.
deliveryMediumReferenceId	String		Mandatory	Unique reference identifier of the delivery associate for whom the transaction is being created.
transactionType	String		Mandatory	Whether the record is about a transaction amount being deposited or withdrawn. Specify 'Credit' if the amount is deposited with the delivery associate; select 'Debit' if the amount is deposited by the delivery associate.
reason	String		Optional	Reason for the credit or debit transaction.
comment	String		Optional	Specify any other details related to the transaction.
transactionDate	String		Optional	The date and time of the transaction. If not provided, the system will consider the current date and time by default.
transferType	String		Mandatory	Type of the transaction. Specify 'transferToBranch' if the delivery associate has deposited the amount at a branch or cash deposit center, or specify 'selfExpenses' if they have used the amount for their expenses (e.g., fuel costs).

Exception

CREATE

Sample Request

```
[
    {
        "exceptionMode" : "Manual",
        "exceptionCode" : "XY0035",
        "exceptionName" : "Special Instructions test1",
        "applyToConstituents" : true,
        "displayOnTrackingLink" : true,
        "exceptionMessage" : "Fragile Item. Requires Special Handling",
        "exceptionStage" : ["Load","Unload","Inscan","Outscan"],
        "exceptionType" : "Informational",
        "exceptionAppliesTo" :
          [
            "Orders",
            "Manifests"
          ]
    }
]
```

Success Response

```
{
    "status": 200,
    "message": "Exception created successfully",
    "moreResultsExists": false,
    "data": [
        {
        "applyToConstituents" : true,
        "displayOnTrackingLink" : true,
        "isActiveFl": true,
        "exceptionMode": "Manual",
        "exceptionCode": "XY0035",
        "exceptionName": "Special Instructions test1",
        "exceptionType": "Informational",
        "exceptionStage": [
            "Load",
            "Unload",
            "Inscan",
            "Outscan"
            ],
            "exceptionAppliesTo": [
                "Orders",
                "Manifests"
                ],
            "exceptionMessage": "Fragile Item. Requires Special Handling",
            "exceptionGroupId": "7616432326594fb4a0fc28e58843f953"
        }],
    "hasError": false
}
```

Failure Response

```
 {
    "status": 400,
    "message": "Some issue encountered in server",
    "moreResultsExists": false,
    "error": {
        "exception_0": [
            {
```

```
                "key": "exceptionCode",
                "message": [
                    "Code is required"
                ],
                "codes": [
                    "10001"
                ]
            }
        ]
    },
    "hasError": true
}
```

Create new exceptions in the LogiNext system using this API.

- This API creates a new Exception using the unique alphanumeric identifier provided in the Request Body which can be used to identify the exception later.
- It creates an exception with all necessary details, including the exception name, message, stage, type, and applicable parameters to define the trigger point and nature of the exception.

API TYPE

- Tier 1 API.

REQUEST

POST `https://api.loginextsolutions.com/ClientApp/exception/v1/add`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
exceptionMode	String	32	Mandatory	Mode of the exception. Specify 'Manual' if the exception is to be raised manually by an authorized user for an order/manifest whenever required (e.g., to report broken items in a package), or specify 'Event-Based' if the exception is to be triggered automatically by the system when a specified event occurs for an order/manifest (e.g., if an order gets accidentally delivered to a wrong branch).
exceptionCode	String	32	Mandatory	Unique alphanumeric identifier for the exception.
applyToConstituents	Boolean	5	Optional	Pass 'true' to specify that when this exception is raised against an order or manifest, it will also apply to all the child orders or manifests within it. Pass 'false' if you do not want to raise exceptions for the child orders. If no value is provided, the system considers 'false' by default.
displayOnTrackingLink	Boolean	5	Optional	Pass 'true' to specify that when this exception is raised against an order or manifest, you want to display the exception message on the associated tracking link. Pass 'false' to hide it on the tracking link. If no value is provided, the system considers 'false' by default.
exceptionName	String	255	Mandatory	Name of the exception.
exceptionMessage	String	255	Conditional Mandatory	The message that is displayed when the exception occurs. This field is mandatory, if 'displayOnTrackingLink' is passed as 'true'.
exceptionStage	String		Mandatory	The stage(s) in the lifecycle of an order/manifest where the exception will be validated if added to an order/manifest. You can choose from Load, Unload, Inscan, and Outscan.
				Type of the exception. Specify 'Informational' if the exception is for informational purposes or to acknowledge an event. This is helpful for event

exceptionType	String	Mandatory	that needs to be noted but do not hamper order processing, such as indicating that an order contains fragile items. Alternatively, specify 'Restrictive' if the exception requires action (resolve or reject) before the user can proceed with the task. In such cases, the delivery associate is shown a message to contact the Branch Manager for resolution. This is helpful when an event occurs that must be addressed before the order can be processed further, such as when an order is damaged during the journey.
exceptionAppliesTo	String	Mandatory	Whether the exception is applicable for orders, manifests, or both. Specify 'Orders' for orders, 'Manifests' for manifests, and 'Orders' and 'Manifests' for both.

UPDATE

Sample Request

```
[
    {
        "exceptionReferenceId" : "7616432326594fb4a0fc28e58843f953",
        "exceptionCode" : "XY0035",
        "exceptionName" : "Special Instructions test1",
        "exceptionMessage" : "Fragile Item. Requires Special Handling",
        "exceptionStage" : ["Load","Unload","Inscan","Outscan"],
        "exceptionType" : "Informational",
        "applyToConstituents" : false,
        "displayOnTrackingLink" : true,
        "exceptionAppliesTo" : ["Orders","Manifests"]
    }
]
```

Success Response

```
{
    "status": 200,
    "message": "Exception Updated successfully",
    "moreResultsExists": false,
    "data": [
        {
            "isActiveFl": true,
            "applyToConstituents" : false,
            "displayOnTrackingLink" : true,
            "exceptionMode": "Manual",
            "exceptionCode": "XY0035",
            "exceptionName": "Special Instructions test1",
            "exceptionType": "Informational",
            "exceptionStage": [
                "Load",
                "Unload",
                "Inscan",
                "Outscan"
            ],
            "exceptionAppliesTo": [
                "Orders",
                "Manifests"
            ],
            "exceptionMessage": "Fragile Item. Requires Special Handling",
            "exceptionGroupId": "7616432326594fb4a0fc28e58843f953",
            "exceptionReferenceId": "7616432326594fb4a0fc28e58843f953"
            }
    ],
    "hasError": false
}
```

Failure Response

```
{
    "status": 400,
    "message": "Some issue encountered in server",
    "moreResultsExists": false,
    "error": {
        "0": [
            {
                "key": "exceptionCode",
                "message": [
                    "Code already exist"
                ],
                "errorCode": 10001
            }
        ]
    },
    "hasError": true
}
```

Update an existing exception in the LogiNext system using this API.

- This API updates an exception with the details provided.
- It identifies the exception using the Reference ID field generated within the LogiNext system. This ID is provided in the Create Exception API response when the associated exception is created in the system.
- Note that to update the exception, it must not be in an open (unresolved) state for any order or manifest.

API TYPE

- Tier 1 API.

REQUEST

POST `https://api.loginextsolutions.com/ClientApp/exception/v1/update`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
exceptionReferenceId	String	32	Mandatory	Unique reference identifier of the exception. This ID is used to identify the exception that you want to update.
exceptionCode	String	32	Optional	Unique alphanumeric identifier of the exception.
exceptionName	String	255	Optional	Name of the exception.
applyToConstituents	Boolean	5	Optional	Pass ‘true’ to specify that when this exception is raised against an order or manifest, it will also apply to all the child orders or manifests within it. Pass ‘false’ if you do not want to raise exceptions for the child orders. If no value is provided, the system considers 'false' by default.
displayOnTrackingLink	Boolean	5	Optional	Pass ‘true’ to specify that when this exception is raised against an order or manifest, you want to display the exception message on the associated tracking link. Pass ‘false’ to hide it on the tracking link. If no value is provided, the system considers ‘false’ by default.
exceptionMessage	String	255	Conditional Mandatory	The message that is displayed when the exception occurs. This field is mandatory, if ‘displayOnTrackingLink’ is passed as ‘true’.
exceptionStage	String		Optional	The stage(s) in the lifecycle of an order/manifest where the exception will be validated if added to an order/manifest. You can choose from Load, Unload, Inscan, and Outscan.

exceptionType	String	Optional	Type of the exception. Specify 'Informational' if the exception is for informational purposes or to acknowledge an event. This is helpful for event that needs to be noted but do not hamper order processing, such as indicating that an order contains fragile items. Alternatively, specify 'Action Required' if the exception requires action (i.e., resolve or reject the exception) before the user can proceed with the task. In such cases, the delivery associate is shown a message to contact the Branch Manager for resolution. This is helpful when an event occurs that must be addressed before the order can be processed further, such as when an order is damaged during the journey.
exceptionAppliesTo	String	Optional	Whether the exception is applicable for orders, manifests, or both. Specify 'Orders' for orders, 'Manifests' for manifests, and 'Orders' and 'Manifests' for both.

RAISE

Sample Request: Exception Raised for a Manifest

```
[
    {
        "manifestId": "O-11145411111",
        "exceptionCode" : "XY001",
    }
]
```

Sample Request: Exception Raised for an Order

```
[
    {
        "orderNo": "WUC4_TC001",
        "exceptionCode" : "XY002"
    }
]
```

Success Response

```
{
    "status": 200,
    "message": "Exception Raised successfully",
    "moreResultsExists": false,
    "data": [
        {
            "orderNo": "WUC4_TC001",    //or manifestId : "man_Id_001"
            "exceptionCode": "XY002"
        }
    ],
    "hasError": false
}
```

Failure Response

```
{
    "status": 400,
    "message": "Some issue encountered in server",
    "moreResultsExists": false,
    "error": {
        "0": [
```

```
            {
                "key": "exceptionCode",
                "message": [
                    "Exception already raised for this Exception Code"
                ],
                "errorCode": 10007
            }
        ]
    },
    "hasError": true
}
```

Raise exceptions against the orders or manifests using this API.

- This API lets you raise an exception against an order or manifest.
- It identifies the exception using the Exception Code field provided when the exception was created in the LogiNext system.
- Note that the exception must be configured in the system before it can be raised against a specific order or manifest.

API TYPE

- Tier 2 API.

REQUEST

POST `https://api.loginextsolutions.com/ShipmentApp/exception/v1/raise`

REQUEST PARAMETERS

Parameter	Datatype	Length	Required	Description
orderNo	String		Conditional Mandatory	Unique identifier of the order. This field is mandatory, if ‘manifestId’ is not provided.
manifestId	String		Conditional Mandatory	Unique identifier of the manifest. This field is mandatory, if ‘orderNo’ is not provided.
exceptionCode	String	32	Mandatory	Unique alphanumeric identifier of the exception.

LogiNext Mile Webhooks

Webhooks allow you to build or set up integrations which subscribe to certain events like Order Creation, Route Planning, Trip Start, etc. on LogiNext System. When one of those events is triggered, we'll send a HTTP POST request to the webhook's configured URL (end point).

Note -

1. LogiNext Webhooks are sent via HTTP REST protocol.
2. The default content type for all the LogiNext Webhooks is "application/ json".
3. If you have a request to support the other content types like "application/xml " or "application/x-www-form-urlencoded", then please get in touch with your assigned CSA (Customer Service Associate) and request the same.
4. All the dates and timestamps that are represented in the Webhooks are in the UTC timezones.
5. Please share the end-point on your system to consume the Webhooks with your assigned CSAs.

6. You can choose to configure an additional security parameter in the LogiNext webhooks Header in the 'x-loginext-signature' header. You can choose to have an APP SECRET configured in LogiNext for this header, and LogiNext will send this APP SECRET in all your configured webhooks. You can validate the value of this header to verify that the webhook request originated from LogiNext. In order to configure this additional security parameter, please reach out to your Account Manager.

7. **Webhook Timeouts**
   There are 2 timeouts for LogiNext Webhooks
   a. Connection timeout: The time in seconds the LogiNext webhook will try to make a connection to your system's server. For LogiNext Webhooks, the connection timeout is 10 seconds.
   b. Read timeout: The time in seconds the LogiNext webhook will wait after establishing a connection with your system to receive an HTTP response. For LogiNext Webhooks, the read timeout is 10 seconds.
   c. Total timeout: The time for the total execution of the webhook. LogiNext webhooks have a total timeout of 10 seconds, i.e, LogiNext webhooks must establish a connection and receive a response from your system within 10 seconds, failing which the webhook will be considered to have timed out.For LogiNext Webhooks, the total timeout is 20 seconds.

We recommend that as soon as your system receives the webhook, it sends a 200 success response. Any tasks to be performed on basis of the receipt of a webhook should be done asynchronously. Webhooks that time out are considered to have failed and will be retried as per the standard retry logic.

8. **Webhook retries**
   Webhook execution can fail due to timeouts or errors. Errors are events for which LogiNext receives a 4xx or 5xx HTTP response code from your system. For each event whose webhook call fails, the calls are retried up to 5 times based on the following schedules:

Retry	Time
1	2 minutes
2	4 minutes
3	8 minutes
4	16 minutes
5	32 minutes

Webhooks that fail for 5 retries will be displayed on the Dispatcher Web App as failed in the Webhook History screen. These webhooks can be manually retried as per your convenience.

9. **IP Whitelisting**
   If your system contains firewalls and requires to whitelist LogiNext’s IP Addresses in order to receive our webhook notifications, please note the following IP Addresses that will have to be whitelisted in your system:

IP Address
52.77.99.245
13.228.17.195
18.136.241.16
3.1.127.224
52.76.48.59

10. **Webhook Data**
    The data sent in the Webhook is limited and does not support all fields. If any specific field is not present in the Webhook data you can

hit the corresponding Get API to get the complete information.

11. Currently the LogiNext system also sends a parameter "Authorization" with webhook payload which requires handling from the client side if any checks are put in place or the client system doesn't accept any data other than content-type

---

Order

CREATE

Sample Response

```
{
    "notificationType": "ORDERCREATIONNOTIFICATION",
    "timestamp": "2024-06-25 07:31:39",
    "pickupLatitude": "40.782635",
    "pickupLongitude": "-73.96732299999996",
    "deliverLatitude": "60.782635",
    "deliverLongitude": "-98.96732299999996",
    "orderNo": "CATS487",
    "referenceId": "143b28d87ghf46098de38b0ccce51a5d",
    "awbNumber": "AW234-TG",
    "orderState": "FORWARD",
    "endTimeWindow": "2024-01-18 12:00:00",
    "orderLeg": "DELIVER",
    "pickupAccountCode": "JAMES1",
    "pickupAddressId": "HOME",
    "deliverAccountCode": "WAYNE",
    "packageValue": 100,
    "pickupCity": "New York",
    "pickupNotes": "Handle with care",
    "deliverNotes": "Please leave the package outside",
    "deliverAddressId": "OFFICE",
    "returnAccountCode": "JAMES1",
    "returnAddressId": "P1947",
    "clientCode": "MyKart"
}
```

- This notification is sent when a new order is created in the LogiNext system.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a ‘create order’ event, the value is set to 'ORDERCREATIONNOTIFICATION'.
timestamp	String	Timestamp of the order when it was created in the system.
orderNo	String	Unique identifier assigned to the order during its creation.
referenceId	String	Unique identifier generated by the system, associated with the specific order.
branchName	String	Name of the branch associated with the order.
awbNumber	String	Air Waybill or AWB number associated with the order.
pickupLatitude	String	Latitude coordinates of the customer’s pickup address.

pickupLongitude	String	Longitude coordinates of the customer's pickup address.
deliverLatitude	String	Latitude coordinates of the customer's delivery address.
deliverLongitude	String	Longitude coordinates of the customer's delivery address.
orderState	String	State of the order. Whether the created order is in the 'FORWARD' or 'REVERSE' state.
endTimeWindow	Date	The end date and time before which the delivery associate should reach the customer's location for pickup/delivery of the order.
orderLeg	String	Whether it is a 'PICKUP' or 'DELIVER' leg of the order.
pickupAccountCode	String	Unique identifier associated with the pickup customer. This field is included if the order contains a pickup leg.
pickupAddressId	String	Identifier assigned to a customer's pickup address. This field is included if the order contains a pickup leg.
pickupGeocodingStatus	String	Geocoding status of the customer's pickup address.
deliveryGeocodingStatus	String	Geocoding status of the customer's delivery address.
returnGeocodingStatus	String	Geocoding status of the customer's return address.
deliverAccountCode	String	Unique identifier associated with the delivery customer. This field is included if the order contains a delivery leg.
deliverAddressId	String	Identifier assigned to a customer's delivery address. This field is included if the order contains a delivery leg.
packageValue	Double	Total cost of the order.
pickupNotes	String	Any additional pickup instructions/notes that the delivery associate should follow.
deliverNotes	String	Any additional delivery instructions/notes that the delivery associate should follow.
pickupCity	String	Name of the city in the customer's pickup address.
returnAccountCode	String	Unique identifier associated with the return customer. This field is included if 'returnAllowedFl' was set to 'Y' when creating the order.
returnAddressId	String	Identifier assigned to a customer's return address. This field is included if 'returnAllowedFl' was set to 'Y' when creating the order.
clientCode	String	Name of the shipper's company associated with the order. This field is included if the order was created by one of your shippers or by you on behalf of one of your shippers.

UPDATE

Sample Response


```
{
  "awbNumber": "AWB1001",
  "deliveryMediumName": "johndoe_rider",
  "phoneNumber": "3125557890",
  "orderState": "FORWARD",
  "startTimeWindow": "2023-10-01 08:00:00",
```

```
    "endTimeWindow": "2023-10-01 10:00:00",
    "tripReferenceId": "trip_ref_usa_2023",
    "numberOfItems": 3,
    "packageWeight": 25,
    "packageVolume": 7200,
    "originAddr": "500 W Madison St, Chicago, IL 60661",
    "pickupCity": "Chicago",
    "destinationAddr": "1600 Amphitheatre Parkway, Mountain View, CA 94043",
    "shipmentOrderTypeCd": "PICKUP",
    "clientNodeName": "West Coast Logistics Hub",
    "clientNodeCd": "WCLH001",
    "address": "145 5th Ave, New York, NY 10010",
    "deliveryType": "RIDER",
    "shipmentNotes": "Handle with care",
    "assignmentMethod": "AUTO",
    "calculatedStartDt": "2023-10-01 07:30:00",
    "calculatedEndDt": "2023-10-01 11:00:00",
    "orderStatus": "INTRANSIT",
    "packageValue": 1200,
    "shipmentCrateMapping": [
      {
        "crateCd": "CRATE_US_001",
        "crateAmount": 850.00,
        "shipmentlineitems": [
          {
            "itemCd": "US1001",
            "itemName": "iPhone 15 Pro Max",
            "itemPrice": 1199,
            "itemQuantity": 1,
            "itemType": "ELECTRONICS",
            "itemWeight": 1,
            "statusCd": "PACKED",
            "loadedQuantity": 0,
            "unloadedQuantity": 0,
            "isActiveFl": true
          },
          {
            "itemCd": "US1002",
            "itemName": "MacBook Pro 14\"",
            "itemPrice": 1999,
            "itemQuantity": 1,
            "itemType": "ELECTRONICS",
            "itemWeight": 3,
            "statusCd": "PACKED",
            "loadedQuantity": 0,
            "unloadedQuantity": 0,
            "isActiveFl": true
          }
        ],
        "noOfUnits": 5,
        "loadedUnits": 0,
        "unloadedUnits": 0,
        "orderNo": "US_ORDER_789",
        "eventName": "RELAYORDER",
        "transferFromDeliveryMediumName": "MikeTaylor",
        "transferFromDeliveryMediumUserName": "mtaylor123",
        "transferFromTripReferenceId": "TRIP_US_456XYZ",
        "transferFromTripName": "TRIP-CHICAGO-NYC",
        "isActiveFl": true,
        "customField": [
          {
            "field": "cf_CustomerPriority",
            "value": "High",
            "type": "text"
          },
          {
```

```
          "field": "cf_WarehouseZone",
          "value": "Zone 3A",
          "type": "text"
        },
        {
          "field": "cf_TrackingReference",
          "value": "TRKUS20231001",
          "type": "text"
        }
      ]
    }
  ]
}
```

- This notification is sent when an existing order is updated in the LogiNext system.
- Note that this webhook also includes the custom fields linked to the order module, but only those that have values.
- It is triggered when the following events occur:
  - Order attributes are updated
  - Manual assignment of the order
  - Change in the trip associated with the order
  - Relay of the order

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For an ‘update order’ event, the value is set to 'ORDERUPDATENOTIFICATION'.
timestamp	String	Timestamp of the order when it was updated in the system.
orderNo	String	Unique identifier of the order that is updated.
orderReferenceId	String	Unique identifier generated by the system, associated with the updated order.
pickupLatitude	String	Latitude coordinates of the customer’s pickup address.
pickupLongitude	String	Longitude coordinates of the customer’s pickup address.
pickupGeocodingStatus	String	Geocoding status of the customer’s pickup address.
deliverLatitude	String	Latitude coordinates of the customer’s delivery address.
deliverLongitude	String	Longitude coordinates of the customer’s delivery address.
vehicleNumber	String	Unique identifier of the vehicle linked with the delivery associate who is assigned to fulfill the order.
awbNumber	String	Air Waybill or AWB number associated with the order.
deliveryMediumName	String	Name of the delivery associate assigned to fulfill the order.
phoneNumber	Integer	Contact number of the delivery associate.
orderState	String	State of the order. Whether the order is in the ‘FORWARD’ or ‘REVERSE’ state.
startTimeWindow	String	The start date and time after which the delivery associate should reach the customer's location for pickup/delivery of the order.
endTimeWindow	Date	The end date and time before which the delivery associate should reach the customer’s location for pickup/delivery of the order.

tripReferenceId	String	Unique reference identifier of the trip with which the order is associated. This field is included if the order is currently part of a trip.
numberOfItems	Integer	Total number of items in the order.
packageWeight	Double	Total weight of the order.
packageVolume	Double	Total volume of the order.
originAddr	String	Location from which the delivery associate has to start picking up or delivering the order.
pickupCity	String	Name of the city in the customer's pickup address.
destinationAddr	String	Location where the delivery associate would go for pickup/delivery.
shipmentOrderTypeCd	String	Type of the order. Whether the order is of 'PICKUP' or 'DELIVER' type.
clientNodeName	String	Node name mapped for the order.
clientNodeCd	String	Code mapped for the order node.
address	String	Address.
deliveryType	String	Skill sets or special requirements associated with the order. This field is included if the order requires a specific specific type of pickup/delivery.
shipmentNotes	String	Any additional instructions/notes associated with the order.
assignmentMethod	String	Method using which the order is assigned to a trip. For example - MANUAL.
calculatedStartDt	String	Calculated start date and time for pickup/delivery of the order.
calculatedEndDt	String	Calculated end date and time for pickup/delivery of the order.
orderStatus	String	Current status of the order.
packageValue	Double	Total cost of the order.
shipmentCrateMapping	Array	List of crate details in the order, including the crate code, amount, type, number of items, and other relevant details.
eventName	String	The specific event that caused the webhook to trigger. The value can be 'RELAYORDER', 'MANUALASSIGNMENT', 'UPDATEADDRESS', or 'UPDATEORDERATTRIBUTES'.
transferFromDeliveryMediumName	String	Name of the delivery associate who initiated the order transfer. This field is included only if the 'eventName' is 'RELAYORDER'.
transferFromDeliveryMediumUserName	String	Username of the delivery associate who initiated the order transfer. This field is included only if the 'eventName' is 'RELAYORDER'.
transferFromTripReferenceId	String	Unique reference identifier associated with the trip from which the order is transferred to another delivery associate. This field is included only if the 'eventName' is 'RELAYORDER'.
transferFromTripName	String	Name of the trip from which the order is transferred to another delivery associate. This field is included only if the 'eventName' is 'RELAYORDER'.

STATUS UPDATE

Sample Response


```
{
  "notificationType": "ORDERSTATUSNOTIFICATON",
  "timestamp": "2024-06-25 07:31:39",
  "orderNo": "ScanWithAwbOrOrder4",
  "orderReferenceId": "3a2511a92bac464aa001f75f4ba84b7f",
  "scanStatus": "INSCANNED",
  "orderStatus": "NOTDISPATCHED",
  "orderLeg": "DELIVER",
  "awbNumber": "AwbNoOnly",
  "orderState": "FORWARD",
  "branchName": "Powai Vendor",
  "scanTime": "2019-04-26 07:30:55",

}
```


- This notification is sent when an order status change occurs in the LogiNext system.
- It is triggered in the following events when an order is:
  - Scanned
  - Outscanned
  - Handed Over
  - Closed

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For an ‘order status’ event, the value is set to 'ORDERSTATUSNOTIFICATON'.
orderNo	String	Unique identifier of the order whose status is updated.
orderReferenceId	String	Unique identifier generated by the system, associated with the order whose status is updated.
scanStatus	String	The scanned status of the order that caused the webhook to trigger. The value can be 'INSCANNED', 'OUTSCANNED', 'HANDEDOVER', or 'CLOSED'.
orderStatus	String	Current status of the order.
orderLeg	String	Whether it is a ‘PICKUP’ or ‘DELIVER’ leg of the order.
awbNumber	String	Air Waybill or AWB number associated with the order.
orderState	String	State of the order. Whether the order is in the ‘FORWARD’ or ‘REVERSE’ state.
branchName	String	Name of the branch associated with the order.
scanTime	String	Timestamp when the order was scanned in the system.

ACCEPTED

Sample Response


```
{
  "timestamp": "2024-06-25 07:31:39",
  "clientShipmentId": "Order_001",
```

```
  "status": "ORDER ACCEPTED",
  "awbNumber": "AWB123456789",
  "deliveryMediumName": "Thomas Watson",
  "deliveryMediumUserName": "Thomas",
  "carrierName":"A&C Transporters",
  "carrierBranchName":"Brooklyn",
  "phoneNumber": "9881234567",
  "tripName": "Trip_1227",
  "updatedOn": "2019-06-30 19:43:07",
  "trackUrl": "loginext.co/sKflfevNRAerrFMlr",
  "pickupEndDate": "2019-11-20 10:23:20",
  "adminTrackUrl": "loginext.co/eit1G359L34HnZlfB",
  "deliveryEndDate": "2019-11-20 10:23:20",
  "orderReferenceId": "b7b15a79d6734297a00a93755856e8c8"
}
```

- This notification is sent when an order is accepted by either a delivery associate or a carrier.

RESPONSE PARAMETERS

Parameter	Datatype	Description
clientShipmentId	String	Unique identifier assigned to the order during its creation.
status	String	Current status of the order.
awbNumber	String	Air Waybill or AWB number associated with the order.
deliveryMediumName	String	Name of the delivery associate who has accepted the order. This field is excluded if the order is assigned to a carrier.
deliveryMediumUserName	String	Username of the delivery associate who has accepted the order. This field is excluded if the order is assigned to a carrier.
carrierName	String	Name of the carrier who has accepted the order. This field is excluded if the order is assigned to a delivery associate.
carrierBranchName	String	Name of the branch associated with the carrier who has accepted the order. This field is excluded if the order is assigned to a delivery associate.
latitude	Double	Latitude coordinates of the delivery associate’s location when the order is accepted.
longitude	Double	Longitude coordinates of the delivery associate’s location when the order is accepted.
phoneNumber	String	Contact number of the delivery associate.
tripName	String	Name of the trip associated with the order.
updatedOn	String	Timestamp of the order when it was accepted by a delivery associate or carrier.
trackUrl	String	Tracking link of the order.
deliveryEndDate	String	Planned estimated end date and time for the delivery associate to deliver the order.
pickupEndDate	String	Planned estimated end date and time for the delivery associate to pick up the order.
adminTrackUrl	String	Order track link for admin users. This may include additional information based on tracking link configurations set for admin users.
orderReferenceId	String	Unique identifier generated by the system, associated with the specific order.

REJECTED

Sample Response

```
{
  "timestamp": "2024-06-25 07:31:39",
  "clientShipmentId": "Order_001",
  "status": "ORDER REJECTED",
  "tripName": "Trip_100123",
  "updatedOn": "2016-06-30 20:47:20",
  "reasonOfRejection": "Cannot reach on ETA",
  "orderReferenceId": "b7b15a79d6734297a00a93755856e8c8"
}
```

- This notification is sent when an order is rejected by either a delivery associate.

RESPONSE PARAMETERS

Parameter	Datatype	Description
clientShipmentId	String	Unique identifier assigned to the order during its creation.
status	String	Current status of the order.
tripName	String	Name of the trip associated with the order.
updatedOn	String	Timestamp of the order when it was rejected by a delivery associate.
reasonOfRejection	String	Reason provided by the delivery associate for rejecting the order.
orderReferenceId	String	Unique identifier generated by the system, associated with the specific order.

CANCEL

Sample Response

```
{
  "notificationType": "CANCELLEDNOTIFICATION",
  "cancellationTime": "2016-12-05 12:59:16",
  "orderNo": "CATS487",
  "orderReferenceId": "cd81bd6ab1104dc3841e3ae405b",
  "awbNumber": "AWB123456789",
  "orderLeg": "DELIVER",
  "orderState": "FORWARD",
  "tripName": "TRIP-809",
  "deliveryMediumName": "Abhi.P",
  "customerCode": "Cust122435",
  "customerName": "Name",
  "phoneNumber": "9922904337",
  "reason": "Customer Unavailable",
  "reasonCd": "Customer Unavailable Cd",
  "cancelledBy": "M. Smith",
  "isCancelOccurAfterPickupFl": false
}
```

- This notification is sent when an order is canceled in the LogiNext system.

RESPONSE PARAMETERS

Parameter	Datatype	Description

notificationType	String	Type of event that triggered the webhook. For a ‘cancel order’ event, the value is set to 'CANCELLEDNOTIFICATION'.
cancellationTime	String	Timestamp of the order when it is canceled in the system (in UTC format).
orderNo	String	Unique identifier of the order that is canceled.
orderReferenceId	String	Unique identifier generated by the system, associated with the order that is canceled.
awbNumber	String	Air Waybill or AWB number associated with the order.
orderLeg	String	Whether it is a ‘PICKUP’ or ‘DELIVER’ leg of the order.
orderState	String	State of the order. Whether the order is in the ‘FORWARD’ or ‘REVERSE’ state.
tripName	String	Name of the trip associated with the order.
deliveryMediumName	String	Name of the delivery associate assigned to fulfill the order. This field is included if the order was assigned to a delivery associate at the time of cancellation.
phoneNumber	Long	Contact number of the delivery associate.
customerName	String	Name of the customer associated with the order.
reason	String	Reason for the order being canceled.
reasonCd	String	Unique code associated with the order cancellation reason.
cancelledBy	String	Name of the user who has canceled the order.
isCancelOccurAfterPickupFl	Boolean	Whether the order was canceled after pickup or not. This field specifies ‘true’ if the order was canceled after pickup or ‘false’ if it was canceled before pickup.

CHECK-IN

Sample Response

```
{
  "orderNo": "CATS487",
  "notificationType": "CHECKINPUSHNOTIFICATION",
  "timestamp": "2024-06-25 07:31:39",
  "awbNumber": "435-16685675",
  "tripName": "TRIP-15264",
  "orderReferenceId": "6b106144208243ffb4b8c44fd44f123d",
  "deliveryMediumReferenceId": "ec3dc344ad304bbbba710eb84fd7462b",
  "locationType": "PICKUP",
  "checkInTime": "2018-02-08T15:00:00Z",
  "checkinLatitude": 40.760838,
  "checkinLongitude": -73.96732299999996,
  "parentOrderNo":"GW433F3"
}
```

- This notification is sent when a delivery associate checks in on the Driver App during pickup or delivery of the order.

RESPONSE PARAMETERS

Parameter	Datatype	Description
orderNo	String	Unique identifier associated with the order that is checked in.

notificationType	String	Type of event that triggered the webhook. For a ‘check-in’ event, the value is set to 'CHECKINPUSHNOTIFICATION'.
awbNumber	String	Air Waybill or AWB number associated with the order.
tripName	String	Name of the trip associated with the order.
orderReferenceId	String	Unique identifier generated by the system, associated with the order that is checked in.
deliveryMediumReferenceId	Long	Unique identifier generated by the system, associated with the specific delivery associate assigned to fulfill the order.
locationType	String	Type of customer address. Whether the customer address for the order is ‘PICKUP’ or ‘DELIVER’.
checkInTime	String	Timestamp of the order when it was marked as checked in within the system.
checkinLatitude	String	Latitude coordinates of the delivery associate’s location when the order was marked as checked in.
checkinLongitude	String	Latitude coordinates of the delivery associate’s location when the order is marked as checked in.
parentOrderNo	String	Unique identifier of this order’s parent order, if any.

LOAD ITEMS

Sample Response


```
{
 "orderNo": "CATS487",
 "orderState":"FORWARD",
 "orderLeg":"PICKUP",
 "awbNumber":"AWB123456789",
 "notificationType": "LOADITEMNOTIFICATION",
 "timestamp": "2024-06-25 07:31:39",
 "orderReferenceId": "b7b15a79d6734297a00a93755856e8c8",
  "shipmentCrateMapping": [
     {
       "crateCd": "CRATE001",
       "crateType": "CRATE001",
       "statusCd": "CRATE001",
       "crateAmount": 100.30,
       "crateQuantity":3,
       "loadedUnits": 1,
       "unloadedUnits": 0,
       "shipmentlineitems": [
         {
           "itemCd": "CODE001",
           "statusCd":"StatusCd",
           "itemName": "ITEM1",
           "itemPrice": 100,
           "itemQuantity": 1,
           "isActiveFl": true
         }
       ]
     }
   ],
   "isActiveFl": true
}
```

- This notification is sent when crates are loaded onto the order in the LogiNext system.

RESPONSE PARAMETERS

Parameter	Datatype	Description
orderNo	String	Unique identifier assigned to the order during its creation.
orderState	String	State of the order. Whether the order is in the ‘FORWARD’ or ‘REVERSE’ state.
orderLeg	String	Whether it is a ‘PICKUP’ or ‘DELIVER’ leg of the order.
awbNumber	String	Air Waybill or AWB number associated with the order.
notificationType	String	Type of event that triggered the webhook. For a 'load items' event, the value is set to 'LOADITEMNOTIFICATION'.
timestamp	String	Timestamp (in UTC format) when the item is loaded in the vehicle.
orderReferenceId	String	Unique identifier generated by the system, associated with the order.
shipmentCrateMapping.crateCd	String	Unique identifier assigned to the crate during its creation.
shipmentCrateMapping.crateType	String	Type of the crate.
shipmentCrateMapping.statusCd	String	Current status of the crate. Whether the crate is ‘LOADED’ or not.
shipmentCrateMapping.crateAmount	Double	Cost applicable for the crate.
shipmentCrateMapping.crateQuantity	Integer	Total number of crates loaded onto the order.
shipmentCrateMapping.shipmentlineitems.itemCd	String	Unique identifier assigned to the item during its creation.
shipmentCrateMapping.shipmentlineitems.statusCd	String	Current status of the item. Whether the item is ‘LOADED’ or not.
shipmentCrateMapping.shipmentlineitems.itemName	String	Name of the item.
shipmentCrateMapping.shipmentlineitems.itemPrice	Double	Cost applicable for the item.
shipmentCrateMapping.shipmentlineitems.itemQuantity	Integer	Total number of items loaded.

LOAD COMPLETE

Sample Response

```
{
  "clientShipmentIds": ["TestOrder1","TestOrder2"],
  "timestamp": "2024-06-25 07:31:39",
  "deliveryMediumName":"TestDeliveryMedium",
  "tripName":"TestTrip",
  "startTime":"2016-07-01 09:13:00",
  "phoneNumber":1234567890,
  "driverName":"TestDriverName",
  "vehicleNumber":"MH 03992",
  "revisedEta" : "2016-07-01 10:13:00",
  "notificationType": "LOADINGDONENOTIFICATION"
}
```

- This notification is sent when crates are loaded onto the order in the LogiNext system.
- Note that this webhook will only be triggered if the ‘CALCULATEREVISEDETAONTRIPLOAD’ is enabled.

RESPONSE PARAMETERS

Parameter	Datatype	Description
clientShipmentIds	String	Unique identifier assigned to the order during its creation.
timestamp	String	Timestamp (in UTC format) when the order is loaded in the vehicle.
deliveryMediumName	String	Name of the delivery associate assigned to fulfill the order.
tripName	String	Name of the trip associated with the order.
startTime	Date	Time at which loading is completed.
phoneNumber	Long	Contact number of the delivery associate.
driverName	String	Name of the driver associated with the order.
vehicleNumber	String	Unique identifier of the vehicle linked with the delivery associate who is assigned to fulfill the order.
revisedEta	Date	Revised estimated time of pickup/delivery of the order.
notificationType	String	Type of event that triggered the webhook. For a ‘load complete’ event, the value is set to 'LOADINGDONENOTIFICATION’.

DELIVERED

Sample Response


```
{
    "orderNo": "CATS487",
    "latitude": 41.882702,
    "longitude": -87.619392,
    "notificationType": "DELIVEREDNOTIFICATION",
    "timestamp": "2024-06-25 07:31:39",
    "orderLeg": "DELIVER",
    "awbNumber": "AWB012345678",
    "customerComment": "User comments",
    "customerRating": 5,
    "deliveryMediumName": "Suresh",
    "phoneNumber": 1234567864,
    "orderState": "FORWARD",
    "customerName": "John Watson",
    "reason": "Override status to Delivered to rectify error",
    "deliverAccountCode": "JohnWatson",
    "checkInTime": "2024-01-16 08:10:22",
    "checkOutTime": "2024-01-16 08:16:23",
    "countOfPOD": 0,
    "deliverAddressId": "Home",
    "pickupAccountCode": "JamesDean",
    "pickupAddressId": "Office",
    "deliveryTime": "2016-11-19 06:11:27",
    "cashAmount": 0,
    "deliveryLocationType": "",
    "transactionId": "12456",
    "actualCashAmount": 120,
    "paymentMode": "COD",
    "tripName": "TRIP-195",
    "recipientName": "Rahul",
```

```
    "branchName": "AAA0",
    "paymentSubType": "",
    "orderReferenceId": "733a42098c1946c98aad410a1dcef75e"
}
```

- This notification is sent when a delivery associate delivers an order to the customer.

RESPONSE PARAMETERS

Parameter	Datatype	Description
orderNo	String	Unique identifier assigned to the order that is delivered.
latitude	Double	Latitude coordinates of the delivery associate's location at the time of delivery.
longitude	Double	Longitude coordinates of the delivery associate's location at the time of delivery.
notificationType	String	Type of event that triggered the webhook. For an 'order delivered' event, the value is set to 'DELIVEREDNOTIFICATION'.
timestamp	String	Timestamp (in UTC format) when the order is marked as 'Delivered'.
orderLeg	String	Whether it is a 'PICKUP' or 'DELIVER' leg of the order.
awbNumber	String	Air Waybill or AWB number associated with the order.
customerComment	String	Comments added by the customer to the order.
customerRating	Double	Rating provided by the customer.
deliveryMediumName	String	Name of the delivery associate assigned to fulfill the order.
phoneNumber	Long	Contact number of the delivery associate.
orderState	String	State of the order. Whether the order is in the 'FORWARD' or 'REVERSE' state.
customerName	String	Name of the customer.
reason	String	Reason for overriding the order status.
deliverAccountCode	String	Unique identifier associated with the delivery customer. This field is excluded for pickup type of orders.
checkInTime	Date	Timestamp of the order when it was marked as checked in by the delivery associate during the delivery.
checkOutTime	Date	Timestamp when the delivery associate completes the checkout step of the pickup/delivery process.
countOfPOD	Integer	Total number of POD (proof of delivery) captured.
deliverAddressId	String	Identifier assigned to a customer's delivery address. This field is excluded for pickup type of orders.
pickupAccountCode	String	Unique identifier associated with the pickup customer. This field is excluded for delivery type of orders.
pickupAddressId	String	Identifier assigned to a customer's pickup address. This field is excluded for delivery type of orders.
deliveryTime	String	Timestamp of the order when it is marked as delivered.

cashAmount	Double	Total cash amount that the delivery associate needs to collect.
deliveryLocationType	String	Type of customer address. Whether the address is Residential, Office, etc.
transactionId	String	Unique identification number associated with the transaction.
actualCashAmount	Double	Actual cash amount collected by the delivery associate.
paymentMode	String	Payment mode of the order. Whether the order is 'PREPAID' if the order has already been paid for, or 'Cash On Delivery (COD)' if the delivery associate needs to collect cash at the time of pickup/delivery.
tripName	String	Name of the trip associated with the order.
recipientName	String	Name of the recipient.
branchName	String	Name of the branch.
paymentSubType	String	Type of the payment. Whether the payment is made by 'CASH', 'CARD_AUTO', 'CARD_MANUAL', 'MOMOE', or 'MSWIPE'.
orderReferenceId	String	Unique identifier generated by the system, associated with the delivered order.

PARTIALLY DELIVERED

Sample Response


```
{
 "orderNo": "145129097",
 "statusCd": "PARTIALLYDELIVERED",
 "notificationType": "PARTIALDELIVERYNOTIFICATION",
 "timestamp": "2024-06-25 07:31:39",
 "orderLeg": "DELIVER",
 "awbNumber": "AWB001",
 "customerComment": "Test user comments",
 "customerRating": 0,
 "deliveryMediumName": "Suresh",
 "phoneNumber": 8447608650,
 "orderState": "FORWARD",
 "customerName": "23768",
 "reason": "Product damaged in transit",
 "reasonCd": "PDL001",
 "deliveryTime": "2016-11-19 06:14:34",
 "cashAmount": 0,
 "deliveryLocationType": "",
 "branchName": "Manhattan Main Branch",
 "transactionId": "",
 "paymentMode": "COD",
 "tripName": "TRIP-195",
 "actualCashAmount": 532.55,
 "shipmentCrateMappingList": [
   {
       "crateCd": "CRATE001",
       "crateType": "CRATE001",
       "statusCd": "CRATE001",
       "crateAmount": 100.30,
       "noOfUnits":3,
       "loadedUnits": 0,
       "unloadedUnits": 0,
       "shipmentLineItemsList": [
         {
           "itemCd": "CODE001",
```

```
            "itemType":"Type1",
            "statusCd":"StatusCd",
            "itemName": "ITEM1",
            "itemPrice": 100,
            "itemQuantity": 1,
            "itemWeight": 100,
            "actualItemQuantity": 5,
            "isActiveFl": true
          }
        ],
        "isActiveFl": true
      }
  ],
  "recipientName": "Pratik",
  "apartment": "supreme business park",
  "streetName": "Michigan Avenue",
  "city": "Chicago",
  "state": "NY",
  "country": "USA",
  "pincode": "10045",
  "customerEmailAddress": "",
  "customerPhoneNumber": "",
  "paymentSubType": "CASH"
}
```


- This notification is sent when a delivery associate partially delivers an order to the customer.

RESPONSE PARAMETERS

Parameter	Datatype	Description
orderNo	String	Unique identifier assigned to the order that is partially delivered.
statusCd	String	Current status of the order. This value is set to ‘PARTIALLYDELIVERED’.
notificationType	String	Type of event that triggered the webhook. For a ‘partially delivered’ order event, the value is set to 'PARTIALDELIVERYNOTIFICATION'.
timestamp	String	Timestamp at which the notification is triggered (in UTC format).
orderLeg	String	Whether it is a ‘PICKUP’ or ‘DELIVER’ leg of the order.
awbNumber	String	Air Waybill or AWB number associated with the order.
customerComments	String	Comments added by the customer to the order.
customerRating	Double	Rating provided by the customer.
deliveryMediumName	String	Name of the delivery associate assigned to fulfill the order.
phoneNumber	Long	Contact number of the delivery associate.
orderState	String	State of the order. Whether the order is in the ‘FORWARD’ or ‘REVERSE’ state.
customerName	String	Name of the customer who has received the order.

reason	String	Reason for partial order delivery.
reasonCd	String	Unique code associated with the reason.
deliveryTime	String	Timestamp of the order when it is marked as partially delivered.
cashAmount	Double	Total cash amount that the delivery associate needs to collect.
deliveryLocationType	String	Type of customer address. Whether the address is Residential, Office, etc.
branchName	String	Name of the branch.
transactionId	String	Unique identification number associated with the transaction.
paymentMode	String	Payment mode of the order. Whether the order is 'PREPAID' if the order has already been paid for, or 'Cash On Delivery (COD)' if the delivery associate needs to collect cash at the time of pickup/delivery.
tripName	String	Name of the trip associated with the order.
actualCashAmount	Double	Actual cash amount collected by the delivery associate.
shipmentCrateMappingList	Array of Objects	This parameter provides the crate details of the order, including the crate code, amount, type, number of items, and other relevant details.
shipmentCrateMappingList.crateCd	String	Unique identifier of the crate.
shipmentCrateMappingList.crateType	String	Type of the crate.
shipmentCrateMappingList.statusCd	String	Current status of the crate. This value is set to 'LOADED'.
shipmentCrateMappingList.crateAmount	Double	Total cost applicable for the crate.
shipmentCrateMappingList.noOfUnits	Integer	Total number of crates.
shipmentCrateMappingList.loadedUnits	Integer	Total number of crates loaded.
shipmentCrateMappingList.unloadedUnits	Integer	Total number of crates unloaded.
shipmentCrateMappingList.isActiveFl	Boolean	Whether the crate is active or not. This field specifies 'true' if the crate is active and 'false' if it is inactive.
shipmentCrateMappingList.shipmentlineitems.itemCd	String	Unique identifier of the item.
shipmentCrateMappingList.shipmentlineitems.itemType	String	Type of the item.
shipmentCrateMappingList.shipmentlineitems.statusCd	String	Current status of the item. This value is set to 'LOADED'.
shipmentCrateMappingList.shipmentlineitems.itemName	String	Name of the item.
shipmentCrateMappingList.shipmentlineitems.itemPrice	Double	Cost applicable for the item.
shipmentCrateMappingList.shipmentlineitems.itemQuantity	Integer	Total number of items.

shipmentCrateMappingList.shipmentlineitems.itemWeight	Integer	Weight of the item.
shipmentCrateMappingList.shipmentlineitems.actualItemQuantity	Integer	Total number of items delivered.
shipmentCrateMappingList.shipmentlineitems.isActiveFl	Boolean	Whether the line item is active or not. This field specifies ‘true’ if the item is active and ‘false’ if it is inactive.
recipientName	String	Name of the recipient.
apartment	String	Name of the apartment building/complex in the recipient’s address.
streetName	String	Name of the society or street in the recipient’s address.
city	String	Name of the city in the recipient’s address.
state	String	Name of the state in the recipient’s address. This should be as per the State Codes available in the LogiNext system for the selected country.
country	String	Name of the country in the recipient’s address. This should be as per the Country Codes available in the LogiNext system.
pincode	Integer	Pin code of the recipient’s location. This should be as per the Postal Codes available in the LogiNext system.
customerEmailAddress	String	Email ID of the customer who has received the order partially.
customerPhoneNumber	String	Contact number of the customer who has received the order partially.
paymentSubType	String	Type of the payment. Whether the payment is made by ‘CASH’, ‘CARD_AUTO’, ‘CARD_MANUAL’, ‘MOMOE’, or ‘MSWIPE’.

NOT DELIVERED

Sample Response


```
{
  "orderNo": "CATS487",
  "latitude":41.882702,
  "longitude":-87.619392,
  "notificationType": "NOTDELIVEREDNOTIFICATION",
  "timestamp": "2024-06-25 07:31:39",
  "orderLeg": "DELIVER",
  "clientId": 209,
  "awbNumber": "AWB001",
  "customerComment": "Test user comments",
  "customerRating": 0,
  "deliveryMediumName": "Suresh",
  "phoneNumber": 1234567876,
  "orderState": "FORWARD",
  "customerName": "Rahul",
  "reasonCd": "NDL001",
  "reason": "No customer at delivery location",
  "deliveryTime": "2016-11-19 06:10:32",
  "deliveryLocationType": "",
  "tripName": "TRIP-195",
```

```
  "recipientName": "",
  "branchName": "MUMBAI (VISIONCARE-DW)",
  "orderReferenceId": "b7b15a79d6734297a00a93755856e8c8"
}
```

- This notification is sent when a delivery associate attempts to deliver an order but is unable to complete the delivery.

RESPONSE PARAMETERS

Parameter	Datatype	Description
orderNo	String	Unique identifier assigned to the order that was attempted for delivery but could not be delivered.
latitude	Double	Latitude coordinates of the delivery associate's location when they mark the order as not delivered.
longitude	Double	Longitude coordinates of the delivery associate's location when they mark the order as not delivered.
notificationType	String	Type of event that triggered the webhook. For a 'not delivered order' event, the value is set to 'NOTDELIVEREDNOTIFICATION'.
timestamp	String	Timestamp at which the notification is triggered (in UTC format).
orderLeg	String	Whether it is a 'PICKUP' or 'DELIVER' leg of the order.
awbNumber	String	Air Waybill or AWB number associated with the order.
clientId	String	Name of the shipper's company associated with the order. This field is included if the order was created by one of your shippers or by you on behalf of one of your shippers.
customerComment	String	Comments added by the customer to the order.
customerRating	Double	Rating provided by the customer.
deliveryMediumName	String	Name of the delivery associate assigned to fulfill the order.
phoneNumber	Long	Contact number of the delivery associate.
orderState	String	State of the order. Whether the order is in the 'FORWARD' or 'REVERSE' state.
customerName	String	Name of the customer.
reason	String	Reason the order was not delivered.
reasonCd	String	Unique code associated with the reason.
deliveryTime	String	Timestamp of the order when it is marked as not delivered.
deliveryLocationType	String	Type of customer address. Whether the address is Residential, Office, etc.
tripName	String	Name of the trip associated with the order.
recipientName	String	Name of the recipient.
branchName	String	Name of the branch.
orderReferenceId	String	Unique identifier generated by the system, associated with the order that was not delivered.

PICKEDUP

Sample Response


```
{
    "notificationType": "PICKEDUPNOTIFICATION",
    "timestamp": "2024-06-25 07:31:39",
    "orderNo": "CATS487",
    "orderReferenceId": "b7b15a79d6734297a00a93755856e8c8",
    "checkInTime": "2024-01-16 08:10:22",
    "checkOutTime": "2024-01-16 12:33:05",
    "countOfPOD": 0,
    "awbNumber": "AWB001",
    "pickedUpTime": "2016-11-19 06:33:48",
    "latitude": 41.882702,
    "longitude": -87.619392,
    "status": "PICKEDUP",
    "orderLeg": "PICKUP",
    "deliveryMediumName": "James",
    "customerComment": "Test user comments",
    "customerRating": 0,
    "phoneNumber": 1234565435,
    "orderState": "FORWARD",
    "branchName": "1008"
}
```


- This notification is sent when an order is picked up by a delivery associate.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a ‘picked up order’ event, the value is set to 'PICKEDUPNOTIFICATION'.
timestamp	String	Timestamp (in UTC format) when the order is marked as 'PickedUp'.
orderNo	String	Unique identifier assigned to the order that is picked up.
orderReferenceId	String	Unique identifier generated by the system, associated with the picked-up order.
checkInTime	Date	Timestamp of the order when it was marked as checked in by the delivery associate during the pickup.
checkOutTime	Date	Timestamp of the order when it was fulfilled by the delivery associate.
countOfPOD	Integer	Total number of POD (proof of delivery) captured.
awbNumber	String	Air Waybill or AWB number associated with the order.
pickedUpTime	String	Timestamp of the event when the order was marked as picked up by the delivery associate.
latitude	Double	Latitude coordinates of the delivery associate’s location when they mark the order as picked up.
longitude	Double	Longitude coordinates of the delivery associate’s location when they mark the order as picked up.
status	String	Current status of the order. This value is set to 'PICKEDUP’.
orderLeg	String	Whether it is a ‘PICKUP’ or ‘DELIVER’ leg of the order.
deliveryMediumName	String	Name of the delivery associate assigned to fulfill the order.

customerComment	String	Comments added by the customer to the order.
customerRating	Double	Rating provided by the customer.
phoneNumber	Long	Contact number of the delivery associate.
orderState	String	State of the order. Whether the order is in the ‘FORWARD’ or ‘REVERSE’ state.
branchName	String	Name of the branch.

NOT PICKED UP

Sample Response

```
{
  "orderNo": "Order001",
  "notificationType": "NOTPICKEDUPNOTIFICATION",
  "timestamp": "2024-06-25 07:31:39",
  "orderLeg": "DELIVER",
  "awbNumber": "AWB001",
  "customerComment": "Test user comments",
  "customerRating": 0,
  "deliveryMediumName": "TestDM",
  "phoneNumber": 1234567890,
  "orderState": "FORWARD",
  "customerName": "Customer name",
  "reason": "Product damaged in transit",
  "reasonCd": "",
  "orderReferenceId": "b7b15a79d6734297a00a93755856e8c8"
}
```

- This notification is sent when a delivery associate attempts to pick up an order but is unable to complete the pickup.

RESPONSE PARAMETERS

Parameter	Datatype	Description
orderNo	String	Unique identifier assigned to the order that was attempted for a pickup but could not be picked up.
notificationType	String	Type of event that triggered the webhook. For a ‘not picked up order' event, the value is set to ‘NOTPICKEDUPNOTIFICATION’.
timestamp	String	Timestamp at which the notification is triggered (in UTC format).
orderLeg	String	Whether it is a ‘PICKUP’ or ‘DELIVER’ leg of the order.
awbNumber	String	Air Waybill or AWB number associated with the order.
customerComment	String	Comments added by the customer to the order.
customerRating	Double	Rating provided by the customer.
deliveryMediumName	String	Name of the delivery associate assigned to fulfill the order.
phoneNumber	Long	Contact number of the delivery associate.
orderState	String	State of the order. Whether the order is in the ‘FORWARD’ or ‘REVERSE’ state.
customerName	String	Name of the customer.

reason	String	Reason the order was not picked up.
reasonCd	String	Unique code associated with the reason.
orderReferenceId	String	Unique identifier generated by the system, associated with the order that was not picked up.

GET EPOD/ESIGN

Sample Response

```
{
  "timestamp": "2019-08-29 14:16:13",
  "notificationType": "GETEPODNOTIFICATION",
  "url": "https://bucketname.s3.ap-southeast-1.amazonaws.com/images/EPOD_ESIGN/EPOD2019_08_29_14_16_12.zip?X-...",
  "requestId": "e5d95546b50e45d2b73f9cdad7dbac18"
}
```

- This notification is triggered in response to calling the Get EPOD and ESign API. It includes the URL to the EPOD and ESign images for the orders requested in the API.
- The webhook contains the 'requestId' field, which is also received in the response of the API request. Use this field to verify which request triggered the webhook.
- Call the URL received in the webhook to automatically trigger the download of a compressed file containing all images uploaded against the order.
- Note that the URL is valid for 7 days from the time the request is received.

RESPONSE PARAMETERS

Parameter	Datatype	Description
timestamp	String	Timestamp at which the notification is triggered (in UTC format).
notificationType	String	Type of event that triggered the webhook. For this event, the value is set to 'GETEPODNOTIFICATION'.
url	String	URL of the compressed file that contains the EPOD and ESign images for the order. This URL is valid for 7 days from the time it is triggered.
requestId	String	Unique request identifier to reconcile which API request triggered the webhook.

CUSTOM FORM SUBMITTED

Sample Response

```
{
  "notificationType": "ORDERCUSTOMFORMNOTIFICATION",
  "event": "EPOD_AFTER",
  "formName": "POD",
  "timestamp": "2024-04-26 02:55:24",
  "orderNo": "26752501_0",
  "orderReferenceId": "d7738ffd9508461e80c5aebad2021ae6",
  "orderStatus": "PICKEDUP",
  "deliveryMediumName": "ATL Dallas Pass_15121",
  "formdata": [
    {
      "key": "recipientName",
      "value": "dallas",
      "type": "text"
    },
    {
      "key": "dept-Floor-Suite-Comments",
      "value": "floor 2",
```

```
      "type": "text"
    }
  ]
}
```

- This notification is triggered when any Custom Form related to an order is submitted.
- It contains the details filled in the Custom Form. These details are sent in the formData parameter, which includes the key name, value, and data type of each field filled in the Custom Form.
- **Note:**
  - The ‘Date’ and ‘DateTime’ field values will be in EPOCH format, while the ‘Time’ field values will be in HH:MM format.
  - Editing an existing Custom Form may impact any integration where there is a check on a specific key name.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a ‘Custom Form’ event, the value is set to 'ORDERCUSTOMFORMNOTIFICATION'.
event	String	The specific event that caused the current Custom Form to trigger. This helps identify at what point in the order lifecycle the Custom Form was filled. The list of possible events is provided in the table below.
formName	String	Name of the Custom Form set when creating the template in the LogiNext system.
timestamp	String	Timestamp of the event at which the Custom Form is submitted in ‘YYYY-MM-DD HH:MM:SS’ format. For example - ‘2019-04-26 02:55:24’.
orderNo	String	Unique identifier of the order against which the Custom Form is filled.
orderReferenceId	String	Unique identifier generated by the system, associated with the order against which the Custom Form is filled.
orderStatus	String	Status of the order.
deliveryMediumName	String	Name of the delivery associate.
formData	List	This parameter contains the list of Custom Form-specific details associated with the order.
formData.key		Name or code of the field in the Custom Form.
formData.value		Value entered in the field when submitting the Custom Form.
formData.type	String	Data type of the input field in the Custom Form.

Event Key	Description
CHECKIN_AFTER	Custom Form filled after the Check-In screen in the Driver App.
LOAD_AFTER	Custom Form filled after the Loading screen in the Driver App.
UNLOAD_AFTER	Custom Form filled after the Unloading screen in the Driver App.
ESIGN_AFTER	Custom Form filled after the ESIGN screen in the Driver App.
PAYMENT_AFTER	Custom Form filled after the Payment screen in the Driver App.
EPOP_AFTER	Custom Form filled after the E Proof of Pickup screen in the Driver App.
EPOD_AFTER	Custom Form filled after the E Proof of Delivery in the Driver App.

PICKEDUP_AFTER	Custom Form filled after the Pickup is complete for the Order in the Driver App.
NOTPICKED-UP_AFTER	Custom Form filled after the Order is marked ‘Not Picked Up’ in the Driver App.
DELIVERED_AFTER	Custom Form filled after the Order is marked ‘Delivered’ in the Driver App.
NOTDELIVER_AFTER	Custom Form filled after the Order is marked ‘Not Delivered’ in the Driver App.
PARTIALDELIVER_AFTER	Custom Form filled after the Order is marked ‘Partial Delivered’ in the Driver App.
TRIPSTART_AFTER	Custom Form filled after the Trip Start screen in the Driver App.
TRIPEND_AFTER	Custom Form filled after the Trip End screen in the Driver App.

END-TO-END ACCOUNT: CREATE

Sample Response


```
{
    "notificationType": "MILEE2EORDERCREATIONNOTIFICATION",
    "orderDetails": [
        {
            "orderNo": "MM_Excel_WH47",
            "timestamp": "2024-06-07 10:26:49",
            "awbNumber": "MM_Excel_WH",
            "orderState": "FORWARD",
            "packageValue": 300,
            "pickupLatitude": "40.782635",
            "pickupLongitude": "-73.96732299999996",
            "pickupCity": "New York",
            "deliverLatitude": "60.782635",
            "deliverNotes": "Please leave the package outside",
            "deliverLongitude": "-98.96732299999996",
            "orderReferenceId": "adda676c70fa4be3a6c7d6a72eec7ce3",
            "deliveryType": "Small Box",
            "routeConfigurationName": "LA_NY_2",
            "orderType": "ALLMILE",
            "serviceType": "Economy",
            "distributionCenter": "California Main Hub",
            "originBranchName": "California Main Hub",
            "destinationBranchName": "New York Central Hub",
            "noOfMilestones": 3,
            "nextBranchName": "Boston",
            "milestoneNo": "MM_Excel_WH47_M1",
            "endTimeWindow": "2024-01-21 00:15:00",
            "milestoneType": "PICKUP",
            "movementType": "Customer-to-Branch",
            "milestoneReferenceId": "adda676c70fa4be3a6c7d6a72eec7ce3",
            "pickupNotes": "Handle with Care",
            "orderDate": "2019-06-25 12:45:00"
        },
        {
            "orderNo": "MM_Excel_WH48",
            "timestamp": "2019-06-07 10:26:49",
            "awbNumber": "MM_Excel_WH",
            "orderState": "FORWARD",
            "packageValue": 300,
            "orderReferenceId": "2af1ae80a2424fd8bcc473dd037677bc",
            "deliveryType": "Small Box",
            "routeConfigurationName": "LA_NY_2",
            "orderType": "ALLMILE",
            "serviceType": "Economy",
```

```
            "distributionCenter": "California Main Hub",
            "originBranchName": "California Main Hub",
            "destinationBranchName": "New York Main Hub",
            "noOfMilestones": 3,
            "deliverNotes": "Please leave the package outside",
            "nextBranchName": "Boston",
            "milestoneNo": "MM_Excel_WH48_M1",
            "endTimeWindow": "2024-01-21 00:15:00",
            "milestoneType": "PICKUP",
            "movementType": "Customer-to-Branch",
            "pickupCity": "New York",
            "milestoneReferenceId": "2af1ae80a2424fd8bcc473dd037677bc",
            "pickupNotes": "Handle with Care",
            "orderDate": "2019-06-25 12:45:00"
        }
    ]
}
```


- This notification is sent when a new order is created using an End-to-End account in the LogiNext system.
- Note that a single order creation notification can be sent for up to 20 orders. For example, if 20 orders are created in a single API call, the notification for all 20 orders will be received in a single webhook response.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For an ‘End-to-End order creation’ event, the value is set to 'MILEE2EORDERCREATIONNOTIFICATION'.
orderNo	String	Unique identifier assigned to the order during its creation.
timestamp	String	Timestamp of the order when it was created in the system.
awbNumber	String	Air Waybill or AWB number associated with the order.
orderState	String	State of the order. Whether the order is in the ‘FORWARD’ or ‘REVERSE’ state.
packageValue	Double	Total cost of the order.
pickupLatitude	String	Latitude coordinates of the customer’s pickup address.
pickupLongitude	String	Longitude coordinates of the customer’s pickup address.
pickupCity	String	Name of the city in the customer’s pickup address.
deliverLatitude	String	Latitude coordinates of the customer’s delivery address.
deliverNotes	String	Any additional delivery instructions/notes that the delivery associate should follow.
deliverLongitude	String	Longitude coordinates of the customer’s delivery address.
orderReferenceId	String	Unique identifier generated by the system, associated with the specific order.
deliveryType	String	Skill sets associated with the order.
routeConfigurationName	String	Name of the route configured during order creation.
orderType	String	Type of the order. This value is set to ‘ALLMILE’.
serviceType	String	Service type applicable for the order.

distributionCenter	String	Name of the branch to which the order is assigned.
originBranchName	String	Name of the original branch associated with the order to fulfill the first leg of the order.
destinationBranchName	String	Name of the destination branch associated with the order to fulfill the last leg of the order.
noOfMilestones	Integer	Total number of milestones associated with the order.
nextBranchName	String	Name of the next branch through which the end-to-end order will flow.
milestoneNo	String	Unique identifier associated with the milestone of the end-to-end order.
endTimeWindow	Date	The closing time of the delivery time window.
milestoneType	String	Whether it is a 'PICKUP' or 'DELIVER' milestone of the order.
movementType	String	Whether the movement type of the milestone is 'Branch-to-Branch', 'Customer-to-Branch', or 'Branch-to-Customer'.
milestoneReferenceId	String	Unique identifier assigned to the milestone during its creation.
pickupNotes	String	Any additional pickup instructions/notes that the delivery associate should follow.
orderDate	String	Date and time at which the order is created.

END-TO-END ACCOUNT: STATUS UPDATE

Sample Response


```
{
  "notificationType": "MILEE2EORDERSTATUSUPDATENOTIFICATION",
  "orderDetails": [
    {
      "orderNo": "LastMile_1",
      "timestamp": "2024-06-24 10:46:57",
      "awbNumber": "LastMile_1",
      "orderState": "FORWARD",
      "orderReferenceId": "91c501c223134022a6708df64bc6a8a8",
      "scanStatus": "INSCANNED",
      "orderStatus": "NOTDISPATCHED",
      "detailedOrderStatus" : "Unassigned",
      "orderType": "LM",
      "distributionCenter": "Main Branch",
      "milestoneNo": "LastMile_1_M1",
      "milestoneType": "DELIVER",
      "milestoneReferenceId": "91c501c223134022a6708df64bc6a8a8",
      "detailedOrderStatus": "NOTDISPATCHED_ASSIGNED",
      "milestoneStatus": "NOTDISPATCHED",
      "manifestId": "1120033111_M",
    },
    {
      "orderNo": "LastMile_2",
      "timestamp": "2019-06-24 10:46:58",
      "awbNumber": "LastMile_1",
      "orderState": "FORWARD",
      "orderReferenceId": "91c501c223134022a6708df64bc6a8a8",
      "scanStatus": "INSCANNED",
      "orderStatus": "NOTDISPATCHED",
      "detailedOrderStatus" : "Unassigned",
      "orderType": "LM",
      "distributionCenter": "Main Branch",
```

```
      "milestoneNo": "LastMile_2_M1",
      "milestoneType": "DELIVER",
      "milestoneReferenceId": "94gde42d34022a6708df64bc6a8a8",
      "detailedOrderStatus": "NOTDISPATCHED_ASSIGNED",
      "milestoneStatus": "NOTDISPATCHED",
      "manifestId": "1120033111_M",
    }
  ]
}
```


- This notification is sent when a status change occurs for the active milestone of an order created using an End-to-End account in the LogiNext system.
- It is triggered when the following events occurs:
  - Order assignment
  - Trip start
  - Milestone delivered
- Note that the status update notification can be sent for up to 20 orders in a single webhook.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For an ‘order status update’ event, the value is set to 'MILEE2EORDERUPDATESTATUSNOTIFICATION'.
orderNo	String	Unique identifier of the order whose active milestone status has been updated.
timestamp	String	Timestamp of the order when it was created in the system.
awbNumber	String	Air Waybill or AWB number associated with the order.
orderState	String	State of the order. Whether the order is in the ‘FORWARD’ or ‘REVERSE’ state.
orderReferenceId	String	Unique identifier generated by the system, associated with the order whose active milestone status is updated.
scanStatus	String	The scanned status of the order that caused the webhook to trigger. The value can be 'INSCANNED', 'OUTSCANNED', 'HANDEDOVER', or 'CLOSED'.
orderStatus	String	Current status of the order.
detailedOrderStatus	String	Detailed status of the order.
deliveryType	String	Skill sets associated with the order.
routeConfigurationName	String	Name of the route configured during order creation.
orderType	String	Type of the order. This value is set to ‘ALLMILE’.
serviceType	String	Service type applicable for the order.
distributionCenter	String	Name of the branch to which the order is assigned.
originBranchName	String	Name of the original branch associated with the order to fulfill the first leg of the order.
destinationBranchName	String	Name of the destination branch associated with the order to fulfill the last leg of the order.
nextBranchName	String	Name of the next branch through which the end-to-end order will flow.

milestoneNo	String	Unique identifier associated with the milestone of the end-to-end order.
milestoneType	String	Whether this is a 'PICKUP' or 'DELIVER' milestone of the order.
movementType	String	Whether the movement type of the milestone is 'Branch-to-Branch', 'Customer-to-Branch', or 'Branch-to-Customer'.
milestoneReferenceId	String	Unique identifier assigned to the milestone during its creation.
orderDate	String	Date and time at which the order is created.
manifestId	String	Unique identifier associated with the manifest generated when the order is outscanned.

ORDER COMMENT

Sample Response

```
{
  "notificationType": "NEWCOMMENTNOTIFICATION",
  "timestamp": "2024-02-24 18:20:49",
  "orderNo": "24022022000005",
  "comment": "This is a sample comment added to an order",
  "userType": "Dispatcher",
  "userName": "beta25@loginextsolutions.com",
  "showToDA": "N",
  "showToShipper": "N"

}
```

- This notification is sent when a new comment is added to an order.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For an ‘order comment’ event, the value is set to 'NEWCOMMENTNOTIFICATION'.
orderNo	String	Unique identifier of the order to which a new comment is added.
orderReferenceId	String	Unique identifier generated by the system, associated with the order to which a new comment is added.
milestoneNo	String	Unique identifier associated with the milestone of the order. This applies only to end-to-end orders.
milestoneReferenceId	String	Unique identifier assigned to the milestone during its creation. This applies only to an end-to-end order.
timestamp	String	Timestamp when a new comment is added to the order.
comment	String	Comments added to the order.
userType	String	Type of the user who added the comment. Whether the comment is added by the ‘Dispatcher’, ‘Carrier’, ‘Shipper’, or ‘Delivery Associate’.
userName	String	Username of the user who added the comment.
showToDA	String	Whether the comment is visible to the associated delivery associate or not. This field specifies ‘Y’ if the comment is visible to the delivery associate and ‘N’ if it is not.

showToShipper	String	Whether the comment is visible to you or not. This field specifies ‘Y’ if the comment is visible to you and ‘N’ if it is not.

TIMEFENCE ENTER

Sample Response

```
{
"notificationType": "TIMEFENCEENTER",
"timestamp": "2024-06-25 07:31:39",
"eventName": "PICKUPTIMEFENCEENTER",
"clientName": "LogiNext Solutions INC",
"orderNo": "CATS487",
"orderReferenceId": "143b28d87ghf46098de38b0ccce51a5d",
"status": "INTRANSIT",
"milestoneNo": "CATS487_M1",
"milestoneReferenceId": "143b28d87ghf46098de38b0ccce51a5d",
"milestoneStatus": "PICKEDUP",
"awbNumber": "ORD_1234",
"deliveryMediumName": "Mac Roy",
"deliveryMediumUserName": "mac_1234",
"tripName": "Trip-1234",
"trackUrl": "loginext.co/fgA3nCcAdR6atkry",
"pickupEndDate": "2022-11-20 10:23:20",
"deliveryEndDate": "2022-11-20 10:43:20",
}
```

- This notification is sent when a delivery associate enters the timefence of an order. Note that it is sent only if the Pickup/Delivery Timefence alert is set to active.
- When the Pickup Timefence alert is triggered, this webhook will be triggered with 'eventName' as 'pickupTimefenceEnter'. Similarly, when the Delivery Timefence alert is triggered, this webhook will be triggered with 'eventName' as 'deliveryTimefenceEnter'.
- Note that this webhook will be triggered even if the communication channel (i.e., SMS/Email/IVR/WhatsApp) is not selected for the Pickup/Delivery Timefence alert. However, the alert must be set to 'Active' for this webhook to trigger.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a ‘timefence enter’ event, the value is set to 'TIMEFENCEENTER'.
timestamp	String	Timestamp of the order when it has entered the timefence.
eventName	String	The specific event that caused the webhook to trigger. The value can be ‘PICKUPTIMEFENCEENTER’ or 'DELIVERYTIMEFENCEENTER'.
clientName	String	Name of the shipper’s company associated with the order. This field is included if the order was created by one of your shippers or by you on behalf of one of your shippers.
orderNo	String	Unique identifier assigned to the order during its creation.
orderReferenceId	String	Unique identifier generated by the system, associated with the order.
status	String	Current status of the order.
milestoneNo	String	Unique identifier associated with the milestone of the end-to-end order. This applies only to end-to-end orders. For example - 1316MDO_M1.
milestoneReferenceId	String	Unique identifier assigned to the milestone during its creation. This applies only to end-to-end orders.

milestoneStatus	String	Current status of the milestone. This applies only to end-to-end orders.
awbNumber	String	Air Waybill or AWB number associated with the order.
deliveryMediumName	String	Name of the delivery associate who has entered the timefence for picking up/delivering the order. This field is excluded if the order is assigned to a carrier.
deliveryMediumUserName	String	Username of the delivery associate who ihas entered the timefence for picking up/delivering the order. This field is excluded if the order is assigned to a carrier.
tripName	String	Name of the trip associated with the order.
trackUrl	String	Tracking link of the order.
pickupEndDate	String	Planned estimated end date and time for the delivery associate to pick up the order.
deliveryEndDate	String	Planned estimated end date and time for the delivery associate to deliver the order.

GEOFENCE ENTRY

Sample Response

```
{
"notificationType": "GEOFENCEENTRYNOTIFICATION",
"orderNo": "05092021000001_test",
"timestamp": "2024-09-05T11:13:19Z",
"tripReferenceId": "bbb4509310f048c8acd3a143c40c4396",
"orderReferenceId": "d55c28ccc5634afb9c9633a53cc6d7a6",
"deliveryMediumReferenceId": "521e1654c6ee4911aaa5f1c4bf6dee0b",
}
```

- This notification is sent when a delivery associate enters the geofence of an order. Note that it is sent only if the Pickup/Delivery Territory alert is set to active.
- When the Pickup/Delivery Territory alert is triggered, this webhook will be triggered with ‘eventName’ as ‘GEOFENCEENTRYNOTIFICATION’.
- Note that this webhook will be triggered even if the communication channel (i.e., SMS/Email/IVR/WhatsApp) is not selected for the Pickup/Delivery Territory alert. However, the alert must be set to ‘Active’ for this webhook to trigger.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a 'geofence entry' event, the value is set to 'GEOFENCEENTRYNOTIFICATION'.
orderNo	String	Unique identifier assigned to the order during its creation.
orderReferenceId	String	Unique identifier generated by the system, associated with the order.
tripReferenceId	String	Unique reference identifier of the trip with which the order is associated.
deliveryMediumReferenceId	String	Unique identifier generated by the system, associated with the specific delivery associate assigned to fulfill the order.
timestamp	String	Timestamp of the order when it has entered the geofence.

Order Request

CREATE

Sample Response

```
{
    "notificationType": "ORDERREQUESTNOTIFICATION",
    "timestamp": "2024-05-18 07:31:39",
    "referenceId": "143b28d87ghf46098de38b0ccce51a5d",
    "shipmentRequestNo":"SH12432",
    "shipmentRequestDispatchDate": "2020-05-19 10:30:00",
    "shipmentRequestType":"PICKUP",
    "serviceType":"Express",
    "pickupAccountCode": "JAMES1",
    "pickupAddressId": "HOME",
    "deliverAccountCode": "WAYNE",
    "deliverAddressId": "P1123",
    "returnAccountCode": "JAMES1",
    "returnAddressId": "P1947",
    "clientCode":"MyKart"
}
```

- This notification is sent when a new order request is created in the LogiNext system.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a 'create order request' event, the value is set to 'ORDERREQUESTNOTIFICATION'.
timestamp	String	Timestamp of the order request when it was created in the system.
referenceId	String	Unique identifier generated by the system, associated with the specific order request.
shipmentRequestNo	String	Unique identifier assigned to the order request during its creation.
shipmentRequestDispatchDate	String	The dispatch date of the order.
shipmentRequestType	String	Type of order request. For All Mile accounts, this specifies whether the order is created for 'PICKUP,' 'DELIVER,' or 'ALLMILE' type. For Other accounts (i.e., Pickup Only, Delivery Only, and Pickup and Delivery accounts), it specifies whether the order is created for 'PICKUP,' 'DELIVER,' or 'BOTH' types.
serviceType	String	Type of service specified for the order request.
pickupAccountCode	String	Unique identifier associated with the pickup customer. This field is included if the order contains a pickup leg.
pickupAddressId	String	Identifier assigned to a customer’s pickup address. This field is included if the order contains a pickup leg.
deliverAccountCode	String	Unique identifier associated with the delivery customer. This field is included if the order contains a delivery leg.
deliverAddressId	String	Identifier assigned to a customer’s delivery address. This field is included if the order contains a delivery leg.

returnAccountCode	String	Unique identifier associated with the return customer. This field is included if ‘returnAllowedFl’ was set to ‘Y’ when creating the order request.
returnAddressId	String	Identifier assigned to a customer’s return address. This field is included if ‘returnAllowedFl’ was set to ‘Y’ when creating the order request.
clientCode	String	Name of the shipper’s company associated with the order request. This field is included if the order request was created by one of your shippers or by you on behalf of one of your shippers.

Trip

START

Sample Response

```
{
  "notificationType": "STARTTRIP",
  "timestamp": "2024-06-25 07:31:39",
  "latitude":41.882702,
  "longitude":-87.619392,
  "deliveryMediumName": "Jack Thomas",
  "phoneNumber": 1234567546,
  "startTime": "2016-11-19 06:42:44",
  "tripName": "TRIP-84",
  "vehicleNumber":"MH084819",
  "clientShipmentIds": [
    "Order001",
    "Order002"
  ],
  "branchName": "Vikhroli",
  "tripReferenceId": "a847130c5ef6467681270e29da6d9bf",
  "deliveryMediumReferenceId": "49e529f9d1af41dc9a31baf910888615"
}
```

- This notification is sent when a trip is started in the LogiNext system.

RESPONSE PARAMETERS

Parameter	DataType	Description
latitude	Long	Latitude coordinates of the location where the trip was started.
longitude	Long	Longitude coordinates of the location where the trip was started.
clientShipmentIds	List	Unique identifier assigned to the order during its creation.
notificationType	String	Type of event that triggered the webhook. For a ‘start trip’ event, the value is set to 'STARTTRIP’.
timestamp	String	Timestamp (in UTC format) when the trip is marked as 'Start'.
tripName	String	Name of the started trip.
vehicleNumber	String	Unique identifier of the vehicle linked with the trip.

driverName	String	Name of the driver associated with the trip.
branchName	String	Name of the branch associated with the trip.
deliveryMediumName	String	Name of the delivery associate assigned to fulfill orders in the trip.
phoneNumber	Long	Contact number of the delivery associate assigned to fulfill orders in the trip.
startTime	String	Date and time when the trip started.
deliveryMediumReferenceId	String	Unique identifier generated by the system, associated with the specific delivery associate assigned to fulfill orders in the trip.
tripReferenceId	String	Unique identifier generated by the system, associated with the trip that has started.

STOP

Sample Response

```
{
  "notificationType": "DELIVEREDNOTIFICATION",
  "timestamp": "2024-06-25 07:31:39",
  "deliveryMediumName": "John",
  "endTime": "2016-11-19 06:45:10",
  "tripName": "TRIP-95",
  "vehicleNumber": "MH014841",
  "latitude": 28.6360695,
  "longitude": 77.1233109,
  "clientShipmentIds": [
    "Order001",
    "Order002"
   ],
  "tripReferenceId": "a847130c5ef6467681270e29da6d9bf",
  "deliveryMediumReferenceId": "49e529f9d1af41dc9a31baf910888615"
}
```

- This notification is sent when a trip ends in the LogiNext system.

RESPONSE PARAMETERS

Parameter	DataType	Description
clientShipmentIds	List	Unique identifier assigned to the order during its creation.
notificationType	String	Type of event that triggered the webhook. For a ‘stop trip’ event, the value is set to 'DELIVEREDNOTIFICATION’.
timestamp	String	Timestamp (in UTC format) when the trip is marked as 'Stop'.
tripName	String	Name of the ended trip.
vehicleNumber	String	Unique identifier of the vehicle linked with the trip.
driverName	String	Name of the driver associated with the trip.
deliveryMediumName	String	Name of the delivery associate assigned to fulfill orders in the trip.
endTime	String	Date and time when the trip ended.
		Unique identifier generated by the system, associated with the specific delivery associate

deliveryMediumReferenceId	String	assigned to fulfill orders in the trip.
tripReferenceId	String	Unique identifier generated by the system, associated with the trip that has ended.
phoneNumber	Long	Contact number of the delivery associate assigned to fulfill orders in the trip.
startTime	String	Date and time when the trip started.
deliveryMediumReferenceId	String	Unique identifier generated by the system, associated with the specific delivery associate assigned to fulfill orders in the trip.
tripReferenceId	String	Unique identifier generated by the system, associated with the trip that has started.

SUGGEST

Sample Response

```
{
  "notificationType": "SUGGEST_TRIPS",
  "orderReferenceId": "873f0a86c18343fe83f0d0760b113c99",
  "suggestedTrips": [
    {
      "tripName": "TRIP-7784963",
      "tripReferenceId": "c3161e36df1547c1929ae4193059f6f4",
      "deliveryMediumName": "JANE ROBERTS",
      "deliveryMediumReferenceId": "DM-123456",
      "sequence": 1
    },
    {
      "tripName": "TRIP-7784964",
      "tripReferenceId": "d4272f47ef2658d2039bf5204160g7g5",
      "deliveryMediumName": "JOHN DOE",
      "deliveryMediumReferenceId": "DM-123457",
      "sequence": 2
    }
  ]
}
```

- This notification is sent in response to the Suggest Trip API. It provides the most suitable trips that can efficiently accommodate the requested orders while satisfying any conditions specified in the API.
- The 'suggestedTrips' parameter contains the details of each suggested trip, including the trip name, reference ID, delivery associate name, and other relevant information.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a ‘suggest trips’ event, the value is set to 'SUGGEST_TRIPS'.
orderReferenceId	String	Unique identifier generated by the system, associated with the order(s) for which you requested trip suggestions.
suggestedTrips	String	List of trips suggested that can efficiently accommodate the orders.
tripName	String	Name of the suggested trip.
tripReferenceId	String	Unique identifier generated by the system, associated with the suggested trip.
deliveryMediumName	String	Name of the delivery associate linked with the trip.

deliveryMediumReferenceId	String	Unique reference identifier of the delivery associate linked with the trip.
sequence	String	Sequence in which the order should be picked up/delivered. For example, if this is set to 3, the order will be picked up/delivered in the 3rd place in the sequence.

REVISE ETA

Sample Response


```
{
 "notificationType": "REVISEETANOTIFICATION",
 "timestamp": "2024-06-25 07:31:39",
 "eventName": "MANUALASSIGNMENT",
 "tripDetails": [
   {
     "tripName": "TRIP-152",
     "tripReferenceId": "26ba0ccxd3c743a6848e2377aea5c2ef",
     "tripStatus": "STARTED",
     "deliveryMediumName": "trampolin",
     "deliveryMediumReferenceId": "9391fbc28a6b4b12923477fc301334ca",
     "phoneNumber": "93189490",
     "branchName": "California Main Branch",
     "orderDetails": [
       {
         "orderStatusCd": "PICKEDUP",
         "orderTypeCd": "DELIVER",
         "orderNo": "GR432U5",
         "orderReferenceId": "d9a0febe56264bbc8b9d43273c53ge75",
         "paymentType": "COD",
         "pickupDetails": [
           {
             "latitude": 40.319291,
             "longitude": 72.89481899999998,
             "startTimeWindow": "2019-05-20 10:00:00",
             "endTimeWindow": "2019-05-23 00:00:00",
             "plannedStartDate": "2019-05-20 14:22:42",
             "plannedEndDate": "2019-05-20 14:22:42",
             "calculatedStartDate": "2019-05-20 14:23:22",
             "calculatedEndDate": "2019-05-20 14:23:22",
             "plannedDistance": 0,
             "sequence": 2
           }
         ],
         "deliverDetails": [
           {
             "latitude": 40.344959,
             "longitude": 72.963202,
             "startTimeWindow": "2019-05-20 10:00:00",
             "endTimeWindow": "2019-05-23 00:00:00",
             "plannedStartDate": "2019-05-20 14:27:59",
             "plannedEndDate": "2019-05-20 14:32:59",
             "calculatedStartDate": "2019-05-20 16:31:50",
             "calculatedEndDate": "2019-05-20 16:36:50",
             "plannedDistance": 0,
             "sequence": 4
           }
         ]
       },
       {
         "orderStatusCd": "INTRANSIT",
         "orderTypeCd": "DELIVER",
         "orderNo": "GR432U7",
         "orderReferenceId": "1df561c31fd24be621aa816836a90127",
         "paymentType": "COD",
```

```
          "pickupDetails": [
            {
              "latitude": 40.319291,
              "longitude": 72.89481899999998,
              "startTimeWindow": "2019-05-20 10:00:00",
              "endTimeWindow": "2019-05-23 00:00:00",
              "calculatedStartDate": "2019-05-20 16:42:28",
              "calculatedEndDate": "2019-05-20 16:42:49",
              "plannedDistance": 0.11,
              "sequence": 7
            }
          ],
          "deliverDetails": [
            {
              "latitude": 40.339693,
              "longitude": 72.954843,
              "startTimeWindow": "2019-05-20 10:00:00",
              "endTimeWindow": "2019-05-23 00:00:00",
              "calculatedStartDate": "2019-05-20 16:42:49",
              "calculatedEndDate": "2019-05-20 16:48:06",
              "plannedDistance": 0.11,
              "sequence": 8
            }
          ]
        }
      ]
    }
  ]
}
```


- This notification is sent when the Estimated Time of Arrival (ETA) for a specific order is updated.
- It is triggered when the following events occurs:
  - A new order is manually assigned to a trip.
  - An order in the trip is canceled.
  - An order is rearranged within a trip (i.e., when there is a change in the DRS).
  - Trip Starts.
  - An order in the trip is fulfilled.
  - Delivery associate resumes their operations after a break.
  - ETAs for subsequent orders in an ongoing trip are revised periodically based on the defined frequency.
- **Note:** When an order is transferred from one trip to another, the ETA is revised for both trips separately, and the notification is triggered twice.

RESPONSE PARAMETERS

Parameter	DataType	Description
notificationType	String	Type of event that triggered the webhook. For a 'revise ETA' event, the value is set to 'REVISEETANOTIFICATION'.
timestamp	String	Date and time when the ETA of the order is revised.
eventName	String	The specific event that caused the webhook to trigger. The value can be 'MANUALASSIGNMENT', 'TRIPSTART', 'ORDERCHECKOUT', 'DELIVERYMEDIUMOFFBREAK', or 'SCHEDULED'.
tripDetails	List	List of trip details, including the trip name, reference ID, status, delivery associate name, and other relevant details
tripDetails.tripName	String	Name of the trip associated with the order.
tripDetails.tripReferenceId	String	Unique identifier generated in the system, associated with the trip for which the order ETA has been updated.

tripDetails.tripStatus	String	Current status of the trip.
tripDetails.deliveryMediumName	String	Name of the delivery associate assigned to fulfill the order whose ETA is revised.
tripDetails.deliveryMediumReferenceId	String	Unique identifier generated by the system, associated with the specific delivery associate assigned to fulfill the orders.
notificationDetails.deliveryMediumName	String	Name of the delivery associate assigned to fulfill the orders.
tripDetails.phoneNumber	String	Contact number of the delivery associate assigned to fulfill the orders.
tripDetails.branchName	String	Name of the branch associated with the order whose ETA is revised.
tripDetails.orderDetails	List	List of order details in the current trip, including order number, type, reference ID, payment type, and other relevant details.
tripDetails.orderDetails.orderTypeCd	String	Type of the order. Whether it is a 'PICKUP' or 'DELIVER' type of order.
tripDetails.orderDetails.orderNo	String	Unique identifier associated with the order whose ETA is revised.
tripDetails.orderDetails.orderReferenceId	String	Unique identifier generated by the system, associated with the order whose ETA is revised.
tripDetails.orderDetails.paymentType	String	Type of the payment. Whether the payment is made by 'CASH', 'CARD_AUTO', 'CARD_MANUAL', 'MOMOE', or 'MSWIPE'.
tripDetails.orderDetails.pickupDetails	List	List of details for the pickup leg of the order, including latitude, longitude, start and end time window, order sequence, and other relevant details.
tripDetails.orderDetails.pickupDetails.latitude	Double	Latitude coordinates of the pickup location.
tripDetails.orderDetails.pickupDetails.longitude	Double	Longitude coordinates of the pickup location.
tripDetails.orderDetails.pickupDetails.startTimeWindow	String	The start date and time after which the delivery associate should reach the customer's location for pickup of the order.
tripDetails.orderDetails.pickupDetails.endTimeWindow	String	The end date and time before which the delivery associate should reach the customer's location for pickup of the order.
tripDetails.orderDetails.pickupDetails.calculatedStartDate	List	Planned estimated start date and time of the pickup of the order.
tripDetails.orderDetails.pickupDetails.calculatedEndDate	List	Planned estimated end date and time of the pickup of the order.
tripDetails.orderDetails.pickupDetails.plannedDistance	List	Planned estimated distance for the pickup of the order.
tripDetails.orderDetails.pickupDetails.sequence	List	Sequence in which the order should be picked up.
tripDetails.orderDetails.deliverDetails.latitude	Double	Latitude coordinates of the delivery location.
tripDetails.orderDetails.deliverDetails.longitude	Double	Longitude coordinates of the delivery location.
tripDetails.orderDetails.deliverDetails.startTimeWindow	String	The start date and time after which the delivery associate should reach the customer's location for delivery of the order.

tripDetails.orderDetails.deliverDetails.endTimeWindow	String	The end date and time before which the delivery associate should reach the customer's location for delivery of the order.
tripDetails.orderDetails.deliverDetails.calculatedStartDate	List	Planned estimated start date and time of the delivery of the order.
tripDetails.orderDetails.deliverDetails.calculatedEndDate	List	Planned estimated end date and time of the delivery of the order.
tripDetails.orderDetails.deliverDetails.plannedDistance	List	Planned estimated distance for the delivery of the order.
tripDetails.orderDetails.deliverDetails.sequence	List	Sequence in which the order should be delivered.

UPDATE

Sample Response


```
{
  "timestamp": "1758637680553",
  "notificationType": "TRIPUPDATENOTIFICATION",
  "eventName": "ORDER_UPDATE",
  "tripName": "TRIP-107077",
  "branchName": "Marque Downtown Chicago",
  "currentPageIndex": 1,
  "totalPages": 1,
  "trip": {
    "tripReferenceId": "ec6f164e57154686bd23f58b65102e10",
    "status": "STARTED",
    "plannedStartDt": 1758637410000,
    "plannedEndDt": 1758640050000,
    "totalPlannedDistance": 0,
    "totalPlannedTime": 44,
    "carrierBranchName": "Fast Courier NYC",
    "carrierName": "ABC Logistics Ltd.",
    "fleetType": "Truck",
    "vehicleNumber": "1AB54F",
    "vehicleReferenceId": "87654gh87654hj8765",
    "licenseNumber": "LIC_104",
    "driverReferenceId": "2345f76543g76543y87654",
    "deliveryMedium": {
      "userName": "mathewsandroid",
      "name": "Mathew S",
      "phoneNumber": "9968995522",
      "alternateNumber": "9029873464",
      "referenceId": "03d809772802463591 06d920ed5c5a17",
      "branch": "AAA0"
    },
    "orderDetails": [
      {
        "state": "FORWARD",
        "status": "INTRANSIT",
        "orderNo": "NA12070320191",
        "orderReferenceId": "58ce28007a644ca0a743397c4897ccdc",
        "pickupSequence": "1",
        "deliverSequence": "2",
        "orderSequence": 2,
        "shipmentOrderTypeCd": "DELIVER",
        "startTimeWindow": 1758715118000,
        "endTimeWindow": 1758715118000,
        "plannedStartTime": 1546908814000,
        "plannedEndTime": 1546914874000,
        "revisedStartTime": 1758637410000,
        "revisedEndTime": 1758640050000
      },
```

```
      {
        "state": "FORWARD",
        "status": "INTRANSIT",
        "orderNo": "NA12070320192",
        "orderReferenceId": "9d209106631c4e13bcb7c825699bd971",
        "pickupSequence": "3",
        "deliverSequence": "4",
        "orderSequence": 4,
        "shipmentOrderTypeCd": "DELIVER",
        "startTimeWindow": 1758622269000,
        "endTimeWindow": 1758708669000,
        "plannedStartTime": 1546908814000,
        "plannedEndTime": 1546914874000,
        "revisedStartTime": 1522657800000,
        "revisedEndTime": 1522662000000
      }
    ]
  }
}
```


- This notification is sent when an existing trip is updated in the LogiNext system.
- It is triggered when any of the following events occur:
  - Trip starts, ends, or is deleted
  - Trip attributes are updated
  - Order attributes are updated
  - Orders are added/removed from the trip
  - Sequence of orders within the trip is updated
  - ETA is revised
  - Delivery associate is assigned
  - Carrier is assigned
  - Fleet details are updated
- Additionally, the webhook includes pagination details through the 'currentPageIndex' and 'totalPages' parameters.

RESPONSE PARAMETERS

Parameter	Datatype	Description
timestamp	Long	Timestamp (in epoch milliseconds) when the trip was updated in the system.
notificationType	String	Type of event that triggered the webhook. For an ‘update trip’ event, the value is set to 'TRIPUPDATENOTIFICATION'.
eventName	String	The specific event that caused the webhook to trigger.
tripName	String	Name of the trip.
branchName	String	Name of the branch associated with the trip.
currentPageIndex	Number	Page index of the current update trip webhook.
totalPages	Number	Total number of pages generated for the current update trip webhook.
trip.tripReferenceId	String	Unique identifier generated by the system, associated with the updated trip.
trip.status	String	Current status of the trip (e.g., NOTSTARTED, STARTED, ENDED).
trip.plannedStartDt	Long	Planned start date and time (in epoch milliseconds) of the trip.
trip.plannedEndDt	Long	Planned end date and time (in epoch milliseconds) of the trip.
trip.totalPlannedDistance	Float	Total planned distance for the trip.

trip.totalPlannedTime	Integer	Total planned time (in minutes) to complete the trip.
trip.carrierBranchName	String	Name of the carrier branch.
trip.carrierName	String	Name of the carrier associated with the trip.
trip.fleetType	String	Name of the Fleet Type.
trip.vehicleNumber	String	Unique identifier of the vehicle linked with the trip.
trip.vehicleReferenceId	String	Unique reference identifier of the vehicle associated with the trip.
trip.licenseNumber	String	Driving license number of the driver.
trip.driverReferenceId	String	Unique reference identifier of the driver.
trip.deliveryMedium.userName	String	Username of the delivery associate linked with the trip.
trip.deliveryMedium.name	String	Name of the delivery associate.
trip.deliveryMedium.phoneNumber	String	Contact number of the delivery associate.
trip.deliveryMedium.alternateNumber	String	Alternate mobile number of the delivery associate, if they carry an additional mobile phone.
trip.deliveryMedium.referenceId	String	Unique reference identifier associated with the delivery associate.
trip.deliveryMedium.branch	String	Branch with which the delivery associate is linked.
trip.orderDetails.state	String	State of the order. Whether the order is in the 'FORWARD' or 'REVERSE' state.
trip.orderDetails.status	String	Current status of the order.
trip.orderDetails.orderNo	String	Unique identifier of an order.
trip.orderDetails.orderReferenceId	String	Unique reference identifier associated with the order.
trip.orderDetails.pickupSequence	String	Sequence in which the order should be picked up.
trip.orderDetails.deliverSequence	String	Sequence in which the order should be delivered.
trip.orderDetails.orderSequence	Integer	Numeric order sequence.
trip.orderDetails.shipmentOrderTypeCd	String	Type of order.
trip.orderDetails.startTimeWindow	Long	The start date and time (in epoch milliseconds) after which the delivery associate should reach the customer's location for pickup of the order.
trip.orderDetails.endTimeWindow	Long	The end date and time (in epoch milliseconds) before which the delivery associate should reach the customer's location for pickup of the order.
trip.orderDetails.plannedStartTime	Long	Planned start time (in epoch milliseconds) of the order.
trip.orderDetails.plannedEndTime	Long	Planned end time (in epoch milliseconds) of the order.
trip.orderDetails.revisedStartTime	Long	Revised start time (in epoch milliseconds) of the order.
trip.orderDetails.revisedEndTime	Long	Revised end time (in epoch milliseconds) of the order.

CUSTOM FORM SUBMITTED

Sample Response


```
{
  "notificationType": "TRIPCUSTOMFORMNOTIFICATION",
  "event": "TRIPSTART_AFTER",
  "formName": "Trip Start",
  "timestamp": "2025-08-20 12:42:24",
  "tripName": "TRIP-7784963",
  "tripReferenceId": "c3161e36df1547c1929ae4193059f6f4",
  "tripStatus": "NOTSTARTED",
  "deliveryMediumName": "JANE ROBERTS (GLP)",
  "formdata": [
    {
      "key": "geotagging",
      "value": "A-902, 50 E 78th St, Opp. Strand Bookstore, New York, USA, 10075",
      "type": "geocode"
    },
    {
      "key": "indusEmployeeID",
      "value": "107742",
      "type": "text"
    },
    {
      "key": "employeeName",
      "value": "JANE ROBERTS",
      "type": "text"
    },
    {
      "key": "e-Signature",
      "value": "https://loginextmobilelive-userfiles-mobilehub-816578465.s3.ap-southeast-1.amazonaws.com/uploads/images",
      "type": "IMAGE"
    }
  ]
}
```


- This notification is triggered when a Custom Form, set to be collected at the start or end of a trip, is submitted.
- It contains the details entered in the Custom Form. These details are sent in the ‘formData’ parameter, which includes the key name, value, and data type of each field.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a ‘trip custom form’ event, the value is set to 'TRIPCUSTOMFORMNOTIFICATION'.
event	String	The specific event that caused the current Custom Form to trigger. This helps identify at what point in the trip the Custom Form was filled. The value can be ‘TRIPSTART_AFTER’ or 'TRIPEND_AFTER'.
formName	String	Name of the Custom Form set when creating the template in the LogiNext system.
timestamp	String	Timestamp of the event when the Custom Form is submitted, in ‘YYYY-MM-DD HH:MM:SS’ format. For example - ‘2019-04-26 02:55:24’.
tripName	String	Name of the trip against which the Custom Form is filled.
tripReferenceId	String	Unique identifier generated by the system, associated with the trip against which the Custom Form is filled.
tripStatus	String	Status of the trip.

deliveryMediumName	String	Name of the delivery associate.
formdata	List	This parameter contains the list of Custom Form-specific details associated with the trip.
key		Name or code of the field in the Custom Form.
value		Value entered in the field when submitting the Custom Form.
type	String	Data type of the input field in the Custom Form.

Route Planning

ROUTE PLANNING(API)

Sample Response


```
{
    "status": 200,
    "message": null,
    "data": {
        "routeName": "TEST_ROUTE",
        "routes": [
            {
                "vehicle": "cc",
                "shipments": [
                    {
                        "name": "Shipment 1",
                        "start": "2017-10-27T16:00:00Z",
                        "end": "2017-10-27T18:00:00Z",
                        "shipmentType": "DELIVER"
                    },

                    {
                        "name": "Shipment 2",
                        "start": "2017-10-27T16:00:00Z",
                        "end": "2017-10-27T18:00:00Z",
                        "shipmentType": "PICKUP"
                    }
                ],
                "start": "2017-10-27T15:59:13Z",
                "end": "2017-10-27T16:19:13Z"
            }
        ],
        "unassigned": ["Shipment 3", "Shipment 4", "Shipment 5"]
    },
    "hasError": false
}
```


- This notification is sent only when the Route Planning API is triggered.

RESPONSE PARAMETERS

Parameter	DataType	Description
status	String	Standard HTTP Status Code.

message	String	Response message displayed in case of an error.
data	JSON	Response JSON body.
routeName	String	Name of the Route.
routes	List	List of optimised routes/trips through which the orders will be picked up/delivered, including start/end time, vehicle details, and other relevant details.
routes.start	String	Start date and time of the trip/route (in UTC format).
routes.end	String	End date and time of the trip/route (in UTC format).
route.vehicle	String	Unique identifier of the vehicle linked with the trip/route.
route.shipments	List	List of order details, including the order name, start time, end time, and type of the order.
route.shipment.name	String	Unique identifier assigned to the order during its creation.
route.shipments.start	String	The start date and time (in UTC format) after which the delivery associate should reach the customer's location for pickup/delivery of the order.
route.shipments.end	String	The end date and time (in UTC format) before which the delivery associate should reach the customer's location for pickup/delivery of the order.
route.shipments.shipmentType	String	Type of the order. Whether it is a 'PICKUP' or 'DELIVER' type of the order.
unassigned	List	List of orders that were not assigned to any trip due to constraints.
hasError	Boolean	Whether the request was successful or failed. Specifies 'true' if any error occurs while processing the request, and 'false' if the request is processed successfully.

V2

- This notification is generated during the Route Planning operation. It contains details of the trips created and the orders assigned to each trip.
- Note that a single Route Planning operation can have multiple Route Planning webhooks generated for it. This will happen in a case where more than 30 trips are created as part of a Route Planning operation. Each Route Planning webhook will include details for up to 30 trips.
- This webhook also provides information on the total number of pages generated for the Route Planning operation. This is indicated by the 'currentPageIndex' and 'totalPages' parameters. Each page will be sent to the URL configured in the LogiNext system to receive the webhook.
- The list of unassigned orders will be sent in the 'unassignmentReasons' list, in the first, which will be sent in the first page of the webhook. Look for the 'currentPageIndex' key with a value of 1 to find this list. (i.e., currentPageIndex = 1).
- If all orders are assigned and no orders are left unassigned, the 'unassignmentReasons' list will not be included in the webhook.

  Sample Response

```
{
 "notificationType": "PLANNINGNOTIFICATION",
 "timestamp": "2024-06-25 07:31:39",
 "routeName": "AS_2703",
 "unassignmentReasons":[
   {
    "reasonCd": "NOT_GEOCODED",
    "orderCount": 1,
    "orderReferenceIds": [
         "444820b3361d4e4e8e484060f9b15625"
    ]
   }
 ],
```

```
  "totalTripCount": 1,
  "currentTripCount": 1,
  "currentPageIndex": 1,
  "totalPages": 1,
  "totalOrderCount": 4,
  "assignedOrderCount": 4,
  "unassignedOrderCount": 0,
  "tripDetails": [
    {
      "tripName": "TRIP-1550",
      "tripReferenceId": "a24ffe5dcdd94e8c8ca7c2d1b2f6489b",
      "tripStatus": "NOTSTARTED",
      "deliveryMediumName": "James",
      "deliveryMediumReferenceId": "b725204fs5a945ea908abacadd1e352b",
      "phoneNumber": "93462027",
      "branchName": "LB01",
      "plannedTotalCost": 40,
      "plannedFixedCost": 17,
      "plannedVariableCost": 13,
      "plannedTransportTimeCost": 7,
      "plannedWaitingTimeCost": 3,
      "orderDetails": [
        {
          "orderStatusCd": "NOTDISPATCHED",
          "orderTypeCd": "DELIVER",
          "orderNo": "NA12070320191",
          "orderReferenceId": "ed9906f4debe4260a4211b801b3b945c",
          "paymentType": "COD",
          "packageValue": 200,
          "pickupDetails": [
            {
              "accountName": "John Wick",
              "phoneNumber": "+18876765348",
              "latitude": 40.319291,
              "longitude": 72.89481899999998,
              "startTimeWindow": "2019-03-27 00:00:00",
              "endTimeWindow": "2019-03-27 12:00:00",
              "plannedStartDate": "2019-03-26 23:42:53",
              "plannedEndDate": "2019-03-26 23:42:53",
              "calculatedStartDate": "2019-03-26 23:42:53",
              "calculatedEndDate": "2019-03-26 23:42:53",
              "plannedDistance": 0,
              "sequence": 3
            }
          ],
          "deliverDetails": [
            {
              "accountName": "Bruce Wick",
              "phoneNumber": "+18876765349",
              "latitude": 40.344959,
              "longitude": 72.963202,
              "startTimeWindow": "2019-03-27 00:00:00",
              "endTimeWindow": "2019-03-27 12:00:00",
              "plannedStartDate": "2019-03-27 00:15:40",
              "plannedEndDate": "2019-03-27 00:28:36",
              "calculatedStartDate": "2019-03-27 00:15:40",
              "calculatedEndDate": "2019-03-27 00:28:36",
              "plannedDistance": 2.692,
              "sequence": 7
            }
          ]
        },
        {
          "orderStatusCd": "NOTDISPATCHED",
          "orderTypeCd": "DELIVER",
          "orderNo": "NA12070320191",
```

```
          "orderReferenceId": "a4592e15a4d44436ae761bc47bf332a0",
          "paymentType": "COD",
          "packageValue": 210,
          "pickupDetails": [
            {
              "accountName": "John Wick",
              "phoneNumber": "+18876765348",
              "latitude": 40.319291,
              "longitude": 72.89481899999998,
              "startTimeWindow": "2019-03-27 00:00:00",
              "endTimeWindow": "2019-03-27 12:00:00",
              "plannedStartDate": "2019-03-26 23:42:53",
              "plannedEndDate": "2019-03-26 23:42:53",
              "calculatedStartDate": "2019-03-26 23:42:53",
              "calculatedEndDate": "2019-03-26 23:42:53",
              "plannedDistance": 0,
              "sequence": 4
            }
          ],
          "deliverDetails": [
            {
              "accountName": "Bruce Wick",
              "phoneNumber": "+18876765349",
              "latitude": 40.339693,
              "longitude": 72.954843,
              "startTimeWindow": "2019-03-27 00:00:00",
              "endTimeWindow": "2019-03-27 12:00:00",
              "plannedStartDate": "2019-03-27 00:28:36",
              "plannedEndDate": "2019-03-27 00:38:47",
              "calculatedStartDate": "2019-03-27 00:28:36",
              "calculatedEndDate": "2019-03-27 00:38:47",
              "plannedDistance": 2.029,
              "sequence": 8
            }
          ]
        },
      ]
    },
    {
        "tripName": "TRIP-1407",
        "tripReferenceId": "b2696d4412c142d09457dc588b973e92",
        "tripStatus": "NOTSTARTED",
        "fleetType" : "18Ft",
        "carrierName": "ABC Logistics Ltd.",
        "carrierReferenceID": "3622c618479e456b9da15f9263b28304",
        "branchName": "LOS",
        "plannedTotalCost": 40,
        "plannedFixedCost": 17,
        "plannedVariableCost": 13,
        "plannedTransportTimeCost": 7,
        "plannedWaitingTimeCost": 3,
        "orderDetails": [
        {
          "orderStatusCd": "NOTDISPATCHED",
          "orderTypeCd": "DELIVER",
          "orderNo": "NA12070320191",
          "orderReferenceId": "3d1dc7bdb0c44e63991f112956f37843",
          "paymentType": "Prepaid",
          "packageValue": 100,
          "pickupDetails": [
            {
              "accountName": "John Wick",
              "phoneNumber": "+18876765348",
              "latitude": 40.319291,
              "longitude": 72.89481899999998,
              "startTimeWindow": "2019-03-27 00:00:00",
```

```
            "endTimeWindow": "2019-03-27 12:00:00",
            "plannedStartDate": "2019-03-26 23:42:53",
            "plannedEndDate": "2019-03-26 23:42:53",
            "calculatedStartDate": "2019-03-26 23:42:53",
            "calculatedEndDate": "2019-03-26 23:42:53",
            "plannedDistance": 0,
            "sequence": 1
          }
        ],
        "deliverDetails": [
          {
            "accountName": "Bruce Wick",
            "phoneNumber": "+18876765349",
            "latitude": 40.329154,
            "longitude": 72.967634,
            "startTimeWindow": "2019-03-27 00:00:00",
            "endTimeWindow": "2019-03-27 12:00:00",
            "plannedStartDate": "2019-03-26 23:42:53",
            "plannedEndDate": "2019-03-27 00:05:00",
            "calculatedStartDate": "2019-03-26 23:42:53",
            "calculatedEndDate": "2019-03-27 00:05:00",
            "plannedDistance": 11.397,
            "sequence": 5
          }
        ]
      },
      {
        "orderStatusCd": "NOTDISPATCHED",
        "orderTypeCd": "DELIVER",
        "orderNo": "TestAS_NA12070320191_CNSGS0002704403",
        "orderReferenceId": "7584a114bd3447759898ea8c823045ad",
        "paymentType": "COD",
        "packageValue": 300,
        "pickupDetails": [
          {
            "accountName": "John Wick",
            "phoneNumber": "+18876765348",
            "latitude": 40.319291,
            "longitude": 72.89481899999998,
            "startTimeWindow": "2019-03-27 00:00:00",
            "endTimeWindow": "2019-03-27 12:00:00",
            "plannedStartDate": "2019-03-26 23:42:53",
            "plannedEndDate": "2019-03-26 23:42:53",
            "calculatedStartDate": "2019-03-26 23:42:53",
            "calculatedEndDate": "2019-03-26 23:42:53",
            "plannedDistance": 0,
            "sequence": 2
          }
        ],
        "deliverDetails": [
          {
            "accountName": "Bruce Wick",
            "phoneNumber": "+18876765349",
            "latitude": 40.3421429,
            "longitude": 72.9641279,
            "startTimeWindow": "2019-03-27 00:00:00",
            "endTimeWindow": "2019-03-27 12:00:00",
            "plannedStartDate": "2019-03-27 00:05:00",
            "plannedEndDate": "2019-03-27 00:15:40",
            "calculatedStartDate": "2019-03-27 00:05:00",
            "calculatedEndDate": "2019-03-27 00:15:40",
            "plannedDistance": 2.023,
            "sequence": 6
          }
        ]
      }
```

```
        ]
      }
    ]
  }
```

RESPONSE PARAMETERS

Parameter	DataType	Description
notificationType	String	Type of event that triggered the webhook. For a 'Route Planning' event, the value is set to 'PLANNINGNOTIFICATION'.
timestamp	String	Date and time (in UTC format) when the route is planned.
routeName	String	Name of the route.
unassingmentReasons	List	List of details, including the count of unassigned orders, their reference IDs, and the reason for unassignment.
unassignmentReasons.reasonCd	String	Unique identifier associated with the order unassignment reason. This should be as per the reason code table provided below.
unassignmentReasons.orderCount	Number	Total number of orders that were unassigned.
unassignmentReasons.orderReferenceIds	List	List of order reference IDs that remained unassigned.
totalTripCount	Number	Total number of trips created as part of the route planning operation. This value represents the total number of trips across all webhooks generated for the current route plan.
currentTripCount	Number	Number of trips in the current webhook.
currentPageIndex	Number	Page index of the current route planning webhook.
totalPages	Number	Total number of pages generated for the current route planning webhook. For example, this will be 4 if 100 trips were created as part of the route planning operation.
totalOrderCount	Number	Total number of orders considered in the route planning.
assignedOrderCount	Number	Number of orders assigned after the current route planning operation.
unassignedOrderCount	Number	Number of orders that remained unassigned after the current route planning operation.
tripDetails	List	List of trip details, including the trip name, status, reference ID, delivery associate name, and other relevant details.
tripDetails.tripName	String	Name of the trip associated with the route planning operation.
tripDetails.tripReferenceId	String	Unique identifier generated by the system, associated with the trip.
tripDetails.tripStatus	String	Current status of the trip.
tripDetails.deliveryMediumName	String	Name of the delivery associate assigned to the trip.

tripDetails.deliveryMediumReferenceId	String	Unique identifier generated by the system, associated with the specific delivery assigned to to fulfill the orders in a trip.
tripDetails.fleetType	String	Fleet type associated with the trip.
tripDetails.carrierName	String	Name of the carrier associated with the trip.
tripDetails.carrierReferenceID	String	Unique identifier generated by the system, associated with the carrier.
tripDetails.phoneNumber	String	Contact number of the delivery associate assigned to the trip.
tripDetails.branchName	String	Name of the branch associated with the trip which is used for route planning.
tripDetails.plannedTotalCost	Integer	Total cost associated with the vehicle linked to the trip.
tripDetails.plannedFixedCost	Integer	Fixed cost associated with the vehicle linked to the trip. This is reflected only when the trip is planned with the Planning Objective set as Optimize Fleet Capacity.
tripDetails.plannedVariableCost	Integer	Per unit distance cost associated with the vehicle linked to the trip. This is reflected only when the trip is planned with the Planning Objective set as Optimize Fleet Capacity or Optimize Time and Distance.
tripDetails.plannedTransportTimeCost	Integer	Cost incurred while the vehicle is on a trip. This is reflected only when the trip is planned with the Planning Objective set as Optimize Fleet Capacity or Optimize Time and Distance.
plannedWaitingTimeCost	Integer	Cost incurred while waiting for order completion. Total waiting time is calculated as Total Trip Time – (Total Transit Time between Orders + Total Service Time of all Orders in a Trip). This is reflected only when the trip is planned with the Planning Objective set as Optimize Fleet Capacity or Optimize Time and Distance.
tripDetails.orderDetails	List	List of order details associated with the current trip, including order type, order number, and other relevant details.
tripDetails.orderDetails.orderTypeCd	String	Type of the order. Whether it is a 'PICKUP' or 'DELIVER' type of order.
tripDetails.orderDetails.orderNo	String	Unique identifier associated with the order as a part of route planning.
tripDetails.orderDetails.orderReferenceId	String	Unique identifier generated by the system, associated with the specific order as a part of route planning.
tripDetails.orderDetails.paymentType	String	Type of the payment. Whether the payment is made by 'CASH', 'CARD_AUTO', 'CARD_MANUAL', 'MOMOE', or 'MSWIPE'.
tripDetails.orderDetails.packageValue	Double	Total cost of the order associated with the trip for route planning.
tripDetails.orderDetails.pickupDetails	List	List of details for the pickup leg of the order, including latitude, longitude, start and end time window, order sequence, and other relevant details.
tripDetails.orderDetails.pickupDetails.accountName	String	Customer name at the pickup location.

tripDetails.orderDetails.pickupDetails.phoneNumber	String	Contact number of the customer at the pickup location.
tripDetails.orderDetails.pickupDetails.latitude	Double	Latitude coordinates of the pickup location.
tripDetails.orderDetails.pickupDetails.longitude	Double	Longitude coordinates of the pickup location.
tripDetails.orderDetails.pickupDetails.startTimeWindow	String	The start date and time after which the delivery associate should reach the customer's location for pickup of the order.
tripDetails.orderDetails.pickupDetails.endTimeWindow	String	The end date and time before which the delivery associate should reach the customer's location for pickup of the order.
tripDetails.orderDetails.pickupDetails.calculatedStartDate	String	Planned estimated start date and time of the pickup of the order.
tripDetails.orderDetails.pickupDetails.calculatedEndDate	String	Planned estimated end date and time of the pickup of the order.
tripDetails.orderDetails.pickupDetails.plannedDistance	List	Planned estimated distance for the pickup of the order.
tripDetails.orderDetails.pickupDetails.sequence	List	Sequence in which the order should be picked up.
tripDetails.orderDetails.deliverDetails	List	List of trip details for the delivery leg of the order, including account name, contact details, and other relevant details.
tripDetails.orderDetails.deliverDetails.accountName	String	Customer name at the delivery location.
tripDetails.orderDetails.deliverDetails.phoneNumber	String	Customer contact number at the delivery location
tripDetails.orderDetails.deliverDetails.latitude	Double	Latitude coordinates of the delivery location of the order.
tripDetails.orderDetails.deliverDetails.longitude	Double	Longitude coordinates of the delivery location of the order.
tripDetails.orderDetails.deliverDetails.startTimeWindow	String	The start date and time after which the delivery associate should reach the customer's location for delivery of the order.
tripDetails.orderDetails.deliverDetails.endTimeWindow	String	The end date and time before which the delivery associate should reach the customer's location for delivery of the order.
tripDetails.orderDetails.deliverDetails.calculatedStartDate	String	Planned estimated start date and time of the delivery of the order.
tripDetails.orderDetails.deliverDetails.calculatedEndDate	String	Planned estimated end date and time of the delivery of the order.
tripDetails.orderDetails.deliverDetails.plannedDistance	List	Planned estimated distance for the delivery of the order.
tripDetails.orderDetails.deliverDetails.sequence	List	Sequence in which the order should be delivered.

Unassignment Key	Description
REQUIRED_SKILL_NOT_FULLFILLED	No delivery associates were found with the required skill set to fulfill these orders.
INSUFFICIENT_TIME_WINDOW	The unassigned orders could not be fulfilled within the specified time windows.
INSUFFICIENT_CAPACITY	Insufficient fleet capacity to fulfill these orders.
MAX_DISTANCE_NOT_FULFILLED	If a maximum distance check was applied to the delivery associate, orders that remained unassigned due to this reason were those that exceeded the allowed distance.

BRANCH_DM_NA	No delivery associates of the relevant branch were found to fulfill these orders
NOT_GEOCODED	Orders were unassigned as they were not geocoded in the LogiNext system.
GEOFENCE_DM_NA	For orders that were mapped to a particular geofence, if no delivery associates were found to fulfill them, those orders will remain unassigned due to this reason.
DM_NA	For orders that are not mapped to any geofence, if no relevant delivery associates were found to fulfill these orders, they will remain unassigned due to this reason
ROUTE_MAX_DISTANCE_NOT_FULLFILLED	The distance constraint between the first order location and the last order location was not met.
PINCODE_MISMATCH	No delivery associates were found with the same pincode preference as the orders.
CUSTOMER_BREAK_OVERLAP_TIMEWINDOW	Orders unassigned due to this reason could be delivered to customer locations during the break times of those customers.
ORDER_TIMEWINDOW_EXCEEDED	Orders unassigned due to this reason could not be fulfilled within their respective time windows.

Real-Time Auto-Assignment

DELIVERY ASSOCIATE ASSIGNMENT

Sample Response


```
{
  "originAddr": "Client Name Main Branch",
  "originLatitude":40.882702,
  "originLongitude":72.619392,
  "notificationType":"ORDERALLOCATION",
  "parentOrderNo": "Customer1_Parent_Order",
  "orderNo": "Customer1_Parent_Order_1",
  "orderReferenceId": "d1c196e8bf384c40ae7f7ca0fd1a3d58",
  "allocationTimeStamp": "2017-07-15T10:30:00.000Z",
  "deliveryMediums": [
    {
       "deliveryMediumMasterName": "Mathew S",
       "employeeId": "133467",
       "userName": "mathewsandroid",
       "phoneNumber": "9881127443",
       "latitude":40.882702,
       "longitude":74.619392,
       "pickupEta": "2016-07-15T10:47:00.000Z",
       "distanceInKms": 0.849,
       "timeInMin": 29,
       "expiryTime": "2016-07-15T10:30:45.000Z",
       "statusCd": "DISPATCHED",
       "tripStatus": "STARTED",
       "referenceId": "3622c618479e456b9da15f9263b28304"
    }
  ]
}
```


- This notification is sent when the Auto-Assignment engine identifies one or more delivery associates, based on your set preferences, to efficiently deliver on-demand (point-to-point) orders.

- Note that this webhook is triggered only when the 'Accept or Reject Assigned Order' option is enabled in the Auto-Assignment preference for delivery associates. if this option is not enabled, the webhook will not be triggered.

RESPONSE PARAMETERS

Parameter	DataType	Required	Description
originAddr	String	Mandatory	Branch from which the delivery associate would start picking up or delivering the order.
originLatitude	String	Mandatory	Latitude coordinates of the pickup location. For example - 17.996.
originLongitude	String	Mandatory	Longitude coordinates of the pickup location. For example - 82.34.
parentOrderNo	String	Mandatory	Unique identifier of this order's parent order, if any. This field is included only for orders with a single pickup and multiple destinations and is excluded for orders with a single pickup and single destination.
orderNo	String	Mandatory	Unique identifier assigned to the order during its creation.
orderReferenceId	String	Mandatory	Unique identifier generated by the system, associated with the specific order.
allocationTimeStamp	String	Mandatory	Date and time (in UTC format) when the Auto-Assignment engine identified the nearest delivery associate. For example - 2017-07-15T10:30:00.000Z.
deliveryMediums	Array Of Object		List of nearest delivery associates details identified to fulfill the orders through Auto-Assignment, including user group name, employee ID, contact number, and other relevant details. Based on your configuration, this field will include the details of one or more delivery associates, as needed.
deliveryMediums.userGroupName	String	Mandatory	Name of the user group to which the delivery associate belongs. Each delivery associate must be a part of a user group, which determines their access level.
deliveryMediums.employeeId	String	Mandatory	Employee ID of the delivery associate. For example - 133478.
deliveryMediums.userName	String	Mandatory	Username of the delivery associate that they use to log into the Driver App. For example - Joshua.Anderson.
deliveryMediums.phoneNumber	String	Mandatory	Contact number of the delivery associate. For example - 9999999999
deliveryMediums.latitude	Double	Optional	Latitude coordinates of the delivery associate's location. For example - 17.897.
deliveryMediums.longitude	Double	Optional	Longitude coordinates of the delivery associate's location. For example - 85.897.
deliveryMediums.pickupEta	String	Mandatory	Estimated time at which the delivery associate should reach the pick-up location. For example - 2016-07-15T10:47:00.000Z.
deliveryMediums.distanceInKms	Double	Mandatory	Estimate distance (in kms) that the delivery associate needs to cover between the pick-up and delivery location.
deliveryMediums.timeInMin	Integer	Mandatory	Estimated time period (in minutes) in which the Driver / Delivery Associate / Field Executive will take to reach the Pick-up Location.
deliveryMediums.expiryTime	String	Mandatory	Time before which the Driver / Delivery Associate / Field Executive must "accept" the order on their mobile app. If they do not accept it, the system will remove the order and allocate it to the next available Delivery Associate. For example, a sample value might be "2016-07-

			15T10:30:00.000Z." You can configure the duration for which you want to display the orders in the delivery associate's app through the Settings screen in the LogiNext application.
deliveryMediums.statusCd	String	Mandatory	Unique code associated with the current status of the delivery associate, indicating their availability based on the configuration. If the delivery associate is configured to handle only one order at a time, the status code will be 'AVAILABLE'. However, if the configuration allows delivery associate to manage multiple orders simultaneously, the status code will be 'DISPATCHED' while they are actively delivering another order.
deliveryMediums.tripStatus	String	Mandatory	Current status of the trip linked with the delivery associate based on the configuration. If the delivery associate is configured to handle only one order at a time, the status code will be 'NOT STARTED'. However, if the configuration allows delivery associate to manage multiple orders simultaneously, the status code will be 'DISPATCHED', while the delivery associate is actively delivering another order.
deliveryMediums.referenceId	String	Mandatory	Unique identifier generated by the system, associated with the delivery associate.

CARRIER ASSIGNMENT

Sample Response


```
[
 {
   "orderNo": "5ff3bf3d-a2a0-40da-b1f7-27bfda97be03",
   "notificationType": "CARRIERORDERALLOCATION",
   "awbNumber": "250923002474",
   "orderState": "FORWARD",
   "paymentMode": "Prepaid",
   "shipmentCrateMapping": [
     {
       "isActiveFl": true,
       "crateCd": "0793",
       "crateAmount": 19.15,
       "shipmentlineitems": [
         {
           "isActiveFl": true,
           "itemCd": "183105",
           "itemName": "Filet-O-Fish® Meal",
           "itemPrice": 12.3,
           "itemQuantity": 1,
           "weightDecimal": false
         },
         {
           "isActiveFl": true,
           "itemCd": "101928",
           "itemName": "- Crispy®",
           "itemPrice": 0,
           "itemQuantity": 1,
           "weightDecimal": false
         },
         {
           "isActiveFl": true,
           "itemCd": "101755",
           "itemName": "- Chicken Nuggets® (4pc)",
           "itemPrice": 0,
           "itemQuantity": 1,
           "weightDecimal": false
         },
         {
           "isActiveFl": true,
```

```
            "itemCd": "101842",
            "itemName": "-- Curry Sauce",
            "itemPrice": 0,
            "itemQuantity": 1,
            "weightDecimal": false
          },
          {
            "isActiveFl": true,
            "itemCd": "100451",
            "itemName": "- Medium French Fries™",
            "itemPrice": 0,
            "itemQuantity": 1,
            "weightDecimal": false
          },
          {
            "isActiveFl": true,
            "itemCd": "506292",
            "itemName": "- Iced Milo® Medium",
            "itemPrice": 1.2,
            "itemQuantity": 1,
            "weightDecimal": false
          },
          {
            "isActiveFl": true,
            "itemCd": "505700",
            "itemName": "Apple Pie",
            "itemPrice": 2.05,
            "itemQuantity": 1,
            "weightDecimal": false
          },
          {
            "isActiveFl": true,
            "itemCd": "435",
            "itemName": "MDS Surcharge $4.80",
            "itemPrice": 4.8,
            "itemQuantity": 1,
            "weightDecimal": false
          }
        ],
        "noOfUnits": 3,
        "loadedUnits": 0,
        "unloadedUnits": 0
      }
    ],
    "orderReferenceId": "fbf742e275d4414eb199fc4a8a77efb3",
    "allocationTimeStamp": "2025-09-23 14:14:42",
    "originLatitude": 1.3042348661513925,
    "originLongitude": 103.80203605776096,
    "transformedCustomFields": {
      "cf_LargeOrder": "False",
      "cf_RiderCheckinCode": "0793",
      "cf_DropoffType": "MEETATDOOR"
    },
    "clientName": "Hanbaobao Pte Ltd.",
    "distanceInKms": 0.84,
    "noOfItems": 1,
    "packageValue": 19.15,
    "originAddress": "39, Essex Street, Opp McDonalds, South Ozone Park, New York, NY 11420",
    "pickupAccountName": "James Walker",
    "pickupPhoneNumber": "5163063377",
    "pickupEmailId": "james.w@ablogs.com",
    "pickupApartment": "39",
    "pickupStreetName": "Essex Street",
    "pickupLandmark": "Opp. McDonalds",
    "pickupLocality": "South Ozone Park",
    "pickupCity": "New York",
```

```
    "pickupCountry": "USA",
    "pickupPinCode": "11420",
    "pickupStartTimeWindow": "2025-09-23 14:13:03",
    "pickupEndTimeWindow": "2025-09-23 14:43:03",
    "pickupAddressTimezone": "America/New_York",
    "destinationLatitude": 1.3107346,
    "destinationLongitude": 103.7982107,
    "destinationAddress": "201, E Randolph St, Opp. Chipotle, Downtown Chicago, Chicago, IL, 60602",
    "deliveryAccountName": "nick tan",
    "deliverPhoneNumber": "+6581397979",
    "deliverEmailId": "m.richardson@testmail.com",
    "deliverServiceTime": 3,
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chipotle",
    "deliverLocality": "Downtown Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverStartTimeWindow": "2025-09-23 14:13:03",
    "deliverEndTimeWindow": "2025-09-23 14:43:03",
    "deliverAddressTimezone": "America/Chicago",
    "deliverNotes": "+6581397979 MEETATDOOR",
    "carriers": [
      {
        "carrierName": "GrabExpress",
        "carrierBranchName": "GrabE_SG",
        "carrierReferenceId": "38d5cf0c699843738edd8ceea9edbd61",
        "expirationTime": "2025-09-23 14:25:42",
        "discardFl": "N",
        "undeliverableAction": "return",
        "alloweSignature": false,
        "allowOtpVerification": false,
        "signerName": false,
        "signerAdditionalDetails": false,
        "branchNotes": "",
        "returnSignature": false,
        "returnSignerName": false,
        "returnSignerDetails": false,
        "carrierCode": "GrabExpress"
      }
    ],
    "preparationTime": 0,
    "riderCheckinCode": "0793",
    "weightMeasurementUnit": "KGS",
    "sizeMeasurementUnit": "CM"
  }
]
```


- This notification is triggered when an order is offered or assigned to one or more carrier branches.
- The following are the event types and their corresponding assignment modes:
  - Auto-assign to nearest carrier: ‘AUTOALLOCATION’
  - Force auto-assign to nearest carrier: ‘FORCEAUTOALLOCATE’
  - Manual assign to carrier (Assign): ‘SUGGESTANDFORCE’
  - Manual assign to carrier (Offer): ‘SUGGESTANDOFFER’

RESPONSE PARAMETERS

Parameter	Datatype	Description
orderNo	String	Unique identifier assigned to the order during its creation.
notificationType	String	Type of event that triggered the webhook. For a 'Carrier Allocation' event, the value is set to 'CARRIERORDERALLOCATION'.

awbNumber	String	Air Waybill or AWB number associated with the order offered/assigned to the carrier.
orderState	String	State of the order. Whether the order is in the 'FORWARD' or 'REVERSE' state.
paymentMode	String	Payment mode of the order. Whether the mode of payment is ‘COP’ (i.e., Cash On Pickup), 'COD' (i.e., Cash On Delivery), or 'Prepaid'.
shipmentCrateMapping	Array of Objects	This parameter provides crate details of the order, including the crate code, amount, type, number of items, and other relevant details.
shipmentCrateMapping.isActiveFl	Boolean	Whether the crate is active or not. This field specifies ‘true’ if the crate is active and ‘false’ if it is inactive.
shipmentCrateMapping.crateCd	String	Unique identifier of the crate.
shipmentCrateMapping.crateAmount	Double	Total cost applicable for the crate.
shipmentCrateMapping.shipmentlineitems	Array of Objects	This parameter provides item details of the crate/order, including the item code, name, price, quantity, and other relevant details.
shipmentCrateMapping.shipmentlineitems.isActiveFl	Boolean	Whether the line item is active or not. This field specifies ‘true’ if the item is active and ‘false’ if it is inactive.
shipmentCrateMapping.shipmentlineitems.itemCd	String	Unique identifier of the item.
shipmentCrateMapping.shipmentlineitems.itemName	String	Name of the item.
shipmentCrateMapping.shipmentlineitems.itemPrice	Double	Cost applicable for the item.
shipmentCrateMapping.shipmentlineitems.itemQuantity	Integer	Total number of items.
shipmentCrateMappings.noOfUnits	Integer	Total number of crates.
shipmentCrateMappings.loadedUnits	Integer	Total number of crates loaded.
shipmentCrateMappings.unloadedUnits	Integer	Total number of crates unloaded.
orderReferenceId	String	Unique identifier generated by the system, associated with the order offered/assigned to the carrier.
allocationTimeStamp	String	Timestamp (in UTC format) at which the allocation engine identified the suitable carrier branch for the order offer/assignment. For example - 2021-07-15T10:30:00.000Z.
originLatitude	Double	Latitude coordinates of the origin location.
originLongitude	Double	Longitude coordinates of the origin location.
transformedCustomFields		This parameter provides the list of Custom Fields associated with the order and their details.
clientName	String	Name of the shipper's company associated with the order. This field is included if the order was created by one of your shippers or by you on behalf of one of your shippers.
		Estimated distance (in km) that the carrier needs to cover between

distanceInKms	Double	the pickup and delivery location.
noOfItems	Integer	Total number of crates in the order.
packageValue	Double	Total cost of the order.
originAddress	String	Address of the origin location.
pickupAccountName	String	Unique identifier associated with the pickup customer. For delivery type of orders, this will be the branch name.
pickupPhoneNumber	String	Contact number associated with the pickup customer. For delivery type of orders, this will be the branch admin's contact number.
pickupEmailId	String	Email ID associated with the pickup customer. For delivery type of orders, this will be the branch admin’s email ID.
pickupApartment	String	Name of the apartment building/complex in the customer's pickup address. For delivery type of orders, this will be the origin branch details.
pickupStreetName	String	Name of the society or street in the customer's pickup address. For delivery type of orders, it will be the society or street of the origin branch.
pickupLandmark	String	Landmark of the customer's pickup location. For delivery type of orders, it will be the landmark of the origin branch.
pickupLocality	String	Name of the locality or area in the pickup address. For delivery type of orders, it will be the locality or area of the origin branch.
pickupCity	String	Name of the city of the pickup customer. For delivery type of orders, it will be the city of the origin branch.
pickupState	String	Name of the state of the pickup customer. This should be as per the State Codes available in the LogiNext system for the selected country. For delivery type of orders, it will be the state of the origin branch.
pickupCountry	String	Name of the country of the pickup customer. This should be as per the Country Codes available in the LogiNext system. For delivery type of orders, it will be the country of the origin branch.
pickupPinCode	String	Postal code of the customer’s pickup location. For delivery type of orders, it will be the postal code of the origin branch.
pickupStartTimeWindow	String	Start date and time (in UTC format) after which the delivery associate should reach the customer's location for pickup. This field is excluded for the delivery type of orders.
pickupEndTimeWindow	String	End date and time (in UTC format) before which the delivery associate should reach the customer's location for pickup. This field is excluded for the delivery type of orders.
pickupAddressTimezone	String	Timezone of the pickup location. For delivery type of orders, it will be the timezone of the origin branch. This should be as per the Timezone Codes available in the LogiNext system.
destinationLatitude	Double	Latitude coordinates of the delivery location.

destinationLongitude	Double	Longitude coordinates of the delivery location.
destinationAddress	String	Address of the order's destination location.
deliveryAccountName	String	Unique identifier associated with the delivery customer. For pickup type of orders, this will be the branch name.
deliverPhoneNumber	String	Contact number associated with the delivery customer. For pickup type of orders, this will be the branch admin's contact number.
deliverEmailId	String	Email ID associated with the delivery customer. For pickup type of orders, this will be the branch admin’s email ID.
deliverServiceTime	Integer	Time taken (in minutes) to service the customer at this particular address.
deliverApartment	String	Name of the apartment building/complex in the customer's delivery address. For pickup type of orders, this will be the origin branch details.
deliverStreetName	String	Name of the society or street in the customer's delivery address. For pickup type of orders, this will be the name of the society or street in the origin branch address.
deliverCity	String	Name of the city of the delivery customer. For pickup type of orders, it will be the city of the origin branch.
deliverCountry	String	Name of the country of the pickup customer. This should be as per the Country Codes available in the LogiNext system for the selected country. For pickup type of orders, it will be the country of the origin branch.
deliverPinCode	String	Postal code of the delivery customer. For pickup type of orders, it will be the postal code of the origin branch.
deliverStartTimeWindow	String	Start date and time (in UTC format) after which the delivery associate should reach the customer's location for delivery. This field is excluded for the pickup type of orders.
deliverEndTimeWindow	String	End date and time (in UTC format) after which the delivery associate should reach the customer's location for delivery. This field is excluded for the pickup type of orders.
deliverAddressTimezone	String	Timezone of the delivery location. For pickup type of orders, it will be the timezone of the origin branch. This should be as per the Timezone Codes available in the LogiNext system.
deliverNotes	String	Any additional delivery instructions/notes that the delivery associate should follow.
carriers	Array of Object	This parameter contains a list of one or more carrier branch details identified to offer/assign the order. It includes information such as the carrier name, branch name, branch code, and other relevant details.
carriers.carrierName	String	Name of the carrier to whom the order was offered/assigned.
carriers.carrierBranchName	String	Name of the branch associated with the carrier to whom the order was offered/assigned.
		Unique identifier generated by the system, associated with the

carriers.carrierReferenceId	String	carrier.
carriers.expirationTime	String	Timestamp when the order offer expires. Carriers must accept the offered order before this expiration time.
carriers.discardFl	String	Whether the carrier branch is allowed to discard undeliverable orders instead of returning them to the origin or not. This field specifies ‘Y’ if carriers are allowed to discard undeliverable orders, or ‘N’ if they must return them. Note that this is applicable only when the ‘paymentMode’ is set to ‘COP’ or ‘COD’. For ‘Prepaid’ orders, standard return handling applies.
carriers.undeliverableAction		This field is interdependent on the ‘carriers.discardFl’ parameter. This specifies ‘discard’ if ‘carriers.discardFl’ is ‘Y’ (i.e., carriers are allowed to discard undeliverable orders), or ‘return’ if ‘carriers.discardFl’ is ‘N’ (i.e., carriers must return the undeliverable orders to the origin address/location).
carriers.alloweSignature	String	Specifies whether carriers are allowed to capture an e-signature for verification during order pickup/delivery.
carriers.allowOtpVerification	String	Specifies whether carriers are allowed to verify an OTP during order pickup/delivery.
carriers.signerName		Specifies whether carriers are allowed to capture the signer's name during e-signature verification at the time of order pickup or delivery.
carriers.signerAdditionalDetails		Specifies whether carriers are allowed to capture the signer's additional details during e-signature verification at the time of order pickup/delivery.
carriers.branchNotes	String	Specifies any branch-specific additional instructions/notes that the carrier’s delivery associate should follow during pickup/delivery.
carriers.returnSignature		Specifies whether carriers are allowed to capture a signature during the return of an order.
carriers.returnSignerName		Specifies whether carriers should capture the signer's name during signature verification for return orders.
carriers.returnSignerDetails		Specifies whether carriers must capture the signer's additional details during signature verification for return orders.
carriers.carrierCode		Unique identifier associated with the carrier when created in the system.
preparationTime	Integer	Time (in minutes) required to prepare the order. This helps delivery associates reach the pickup/delivery location at the right time, minimizing the wait time and preserving order quality.
riderCheckinCode		Unique check-in code that the delivery associate must show when picking up an order from the branch.
weightMeasurementUnit		Unit of measurement for the order’s weight. This information can be critical if the order has a considerable weight. For the metric system, this will be in kilograms (kg), and for the imperial system, it will be in pounds (lb).
sizeMeasurementUnit		Unit of measurement for the order’s size/length. For the metric system, this will be in centimeters (cm), and for the imperial

	system, it will be in inches (in).

ORDER ASSIGNMENT STOPPED

Sample Response: When No Delivery Associate Is Found

```
{
  "orderNo": "Alcn_test33",
  "notificationType": "ORDERALLOCATIONSTOP",
  "timestamp": "2024-06-25 07:31:39",
  "reason": "No Delivery Medium found",
  "orderReferenceId": "844dae0deeea4ac69ead4f542e542b69",
  "lastRunDt": "2022-07-27T14:32:24Z",
  "isMaxAttemptsExhausted": true
}
```

Sample Response: When No Carrier Is Found

```
{
  "orderNo": "Alcn_test33",
  "notificationType": "ORDERALLOCATIONSTOP",
  "timestamp": "2024-06-25 07:31:39",
  "reason": "No Carrier found",
  "orderReferenceId": "844dae0deeea4ac69ead4f542e542b69",
  "lastRunDt": "2022-07-27T14:32:24Z",
  "isMaxAttemptsExhausted": true
}
```

Sample Response: When No Delivery Associate and Carrier Is Found

```
{
  "orderNo": "Alcn_test33",
  "notificationType": "ORDERALLOCATIONSTOP",
  "timestamp": "2024-06-25 07:31:39",
  "reason": "No Delivery Medium and Carrier found",
  "orderReferenceId": "844dae0deeea4ac69ead4f542e542b69",
  "lastRunDt": "2022-07-27T14:32:24Z",
  "isMaxAttemptsExhausted": true
}
```

- This notification is triggered when the real-time Auto-Assignment process for an order ends without assigning a delivery associate or carrier.

RESPONSE PARAMETERS

Parameter	Datatype	Description
orderNo	String	Unique identifier assigned to the order during its creation.
notificationType	String	Type of event that triggered the webhook. For an 'order allocation stopped' event, the value is set to 'ORDERALLOCATIONSTOP'.
timestamp	String	Timestamp at which the notification is triggered (in UTC format).
		Reason for triggering this webhook. This webhook is triggered based on the Auto-Assignment Objective set in the Auto-Assignment Profile. If the Auto-Assignment Objective is set as 'Auto-Assign to Delivery Associate' only, this webhook is triggered when the Auto-Assignment engine fails to find a delivery associate. The specified reason will be 'No Delivery Medium found'. If the Auto-Assignment Objective is set as 'Auto-Assign to Carrier' only, this webhook is triggered when the

reason	String	Auto-Assignment engine fails to find a carrier. The specified reason will be ‘No Carrier found’. If the Auto-Assignment Objective is set as both ‘Auto-Assign to Delivery Associate’ and ‘Auto-Assign to Carrier’, this webhook is triggered twice: first when the Auto-Assignment engine fails to find a delivery associate, and second when it fails to find a carrier. The specified reason will be ‘No Delivery Medium and Carrier Found’.
orderReferenceId	String	Unique identifier generated by the system, associated with the order.
lastRunDt	String	The date and time when the Auto-Assignment engine last ran.
isMaxAttemptsExhausted	String	Whether the maximum number of attempts has been exhausted. This field specifies 'true' if the attempts are exhausted, or 'false' if they are not.

Carrier Assignment

CARRIER ORDER LAPSE

Sample Response

```
{
    "notificationType": "ORDERLAPSE",
    "clientName" : "LogiNext Solutions Inc.",
    "parentOrderNo": "ORD1023401",
    "orderNo":"OD123123",
    "orderReferenceId":"d1c196e8bf384c40ae7f7ca0fd1a3d58",
    "milestoneNo":"OD123123_M1",
    "milestoneReferenceId":"adda676c70fa4be3a6c7d6a72eec7ce3",
    "awbNumber":"AWB10234",
    "lapseTimestamp":"2021-07-15T10:35:00.000Z",
    "carriers":[
        {
            "carrierName":"Fast Courier LLC",
            "carrierBranchName":"Fast Courier NYC",
            "carrierBranchCd":"Fast Courier NYC",
            "carrierReferenceId":"a3465bsdjfbv3458aowern",
        },
        {
            "carrierName":"Best Courier LLC",
            "carrierBranchName":"Best Courier NYC",
            "carrierBranchCd":"Best Courier NYC",
            "carrierReferenceId":"a331ibsdhdvv3978aowmdn",
        }
    ]
}
```

- This notification is sent to notify the integrated carriers about an order lapse event.
- The Auto-Assignment engine for carriers can broadcast an order to multiple carrier branches.
- In the case of a broadcast:
  - One of the many carriers can accept the order.
  - When this happens, all other active offers lapse and any actions on them become invalid.
- This webhook informs the remaining integrated carriers about the lapse event, preventing them from taking further action on the order.
- Note that this webhook is triggered in both Auto-Assignment and Manual Assignment processes.

RESPONSE PARAMETERS

Parameter	DataType	Description

notificationType	String	Type of event that triggered the webhook. For a ‘carrier assignment’ event, the value is set to 'ORDERLAPSE’.
clientName	String	Name of the shipper’s company associated with the order. This field is included if the order was created by one of your shippers or by you on behalf of one of your shippers.
parentOrderNo	String	Unique identifier of this order’s parent order, if any.
orderNo	String	Unique identifier assigned to the order during its creation. In case of a single pickup and multiple destinations, this is the first order number in the sequence. In case of a single pickup and single destination, this is the associated order number.
orderReferenceId	String	Unique identifier generated by the system, associated with the specific order. Note that this reference ID is for the ‘orderNo’ and not for the ‘parentOrderNo’.
milestoneNo	String	Milestone number associated with an end-to-end order. This field is included only for orders created using an end-to-end account and is excluded for orders created with other account types.
milestoneReferenceId	String	Unique identifier generated by the system, associated with the specific milestone. This field is included only for orders created using an end-to-end account and is excluded for orders created with other account types.
awbNumber	String	Air Waybill or AWB number associated with the order.
lapseTimestamp	String	Timestamp (in UTC format) at which the order has been accepted by one of the carriers and has lapsed for the remaining identified carriers.
carriers	Array	List of one or more carrier branches for which the order has lapsed, including carrier name, branch name, branch code, and other relevant details.
carriers.carrierName	String	Name of the carrier for which the order has lapsed.
carriers.carrierBranchName	String	Name of the branch associated with the carrier for which the order has lapsed.
carriers.carrierBranchCd	String	Unique identifier of the branch associated with the carrier.

CARRIER ORDER TIMEOUT

Sample Response


```
{
    "notificationType": "ORDERTIMEOUT",
    "clientName" : "LogiNext Solutions Inc.",
    "parentOrderNo": "ORD1023401",
    "orderNo":"OD123123",
    "orderReferenceId":"d1c196e8bf384c40ae7f7ca0fd1a3d58",
    "milestoneNo":"OD123123_M1",
    "milestoneReferenceId":"adda676c70fa4be3a6c7d6a72eec7ce3",
    "awbNumber":"AWB10234",
    "expiredTimestamp":"2021-07-15T10:35:00.000Z",
    "carriers":[
        {
            "carrierName":"Fast Courier LLC",
            "carrierBranchName":"Fast Courier NYC",
            "carrierBranchCd":"Fast Courier NYC",
            "carrierReferenceId":"a3465bsdjfbv3458aowern",
        },
        {
            "carrierName":"Best Courier LLC",
            "carrierBranchName":"Best Courier NYC",
```

```
            "carrierBranchCd":"Best Courier NYC",
            "carrierReferenceId":"a331ibsdhdvv3978aowmdn",
        }
    ]
}
```

- This notification is sent to notify the integrated carriers about a carrier order offer timeout event.
- The Auto-Assignment engine for carriers can broadcast an order to multiple carrier branches.
- In the case of a broadcast:
  - Each order offer contains an expiration time by which a response is expected.
  - When this happens, all other active offers are timed out and any actions on them become invalid.
- This webhook informs the remaining integrated carriers about the timeout event, preventing them from taking further action on the order.
- Note that this webhook is triggered in both Auto-Assignment and Manual Assignment processes.

RESPONSE PARAMETERS

Parameter	DataType	Description
notificationType	String	Type of event that triggered the webhook. For the 'carrier order timeout' event, the value is set to 'ORDERTIMEOUT'.
clientName	String	Name of the shipper's company associated with the order. This field is included if the order was created by one of your shippers or by you on behalf of one of your shippers.
parentOrderNo	String	Unique identifier of this order's parent order, if any.
orderNo	String	Unique identifier assigned to the order during its creation. In case of a single pickup and multiple destinations, this is the first order number in the sequence. In case of a single pickup and single destination, this is the associated order number.
orderReferenceId	String	Unique identifier generated by the system, associated with the specific order. Note that this reference ID is for the 'orderNo' and not for the 'parentOrderNo'.
milestoneNo	String	Milestone number associated with an end-to-end order. This field is included only for orders created using an end-to-end account and is excluded for orders created with other account types.
milestoneReferenceId	String	Unique identifier generated by the system, associated with the specific milestone. This field is included only for orders created using an end-to-end account and is excluded for orders created with other account types.
awbNumber	String	Air Waybill or AWB number associated with the order.
expiredTimestamp	String	Timestamp (in UTC format) at which the order has expired for the integrated carriers.
carriers	Array	List of one or more carrier branches for which the order has timed out, including carrier name, branch name, branch code, and other relevant details.
carriers.carrierName	String	Name of the carrier for which the order has timed out.
carriers.carrierBranchName	String	Name of the branch associated with the carrier for which the order has timed out.
carriers.carrierBranchCd	String	Unique identifier of the branch associated with the carrier.
carriers.carrierReferenceId	String	Unique identifier generated by the system, associated with the specific carrier.

CARRIER ORDER OFFER

Sample Response

```
{
    "notificationType": "CARRIERORDEROFFER",
    "timestamp": "2024-06-25 07:31:39",
    "clientName" : "LogiNext Solutions Inc.",
    "parentOrderNo":"ORD1023401",
    "orderNo":"OD123123",
    "orderReferenceId":"d1c196e8bf384c40ae7f7ca0fd1a3d58",
    "milestoneNo":"OD123123_M1",
    "milestoneReferenceId":"adda676c70fa4be3a6c7d6a72eec7ce3",
    "awbNumber":"AWB10234",
    "allocationTimestamp":"2024-07-15T10:30:00.000Z",
    "distanceInKms": 10.3,
    "orderState":"FORWARD",
    "priority":"High",
    "deliveryType":"Groceries",
    "serviceType":"Express",
    "packageWeight":10,
    "packageVolume":10,
    "packageLength":10,
    "packageBreadth":10,
    "packageHeight":10,
    "noOfItems":4,
    "paymentMode":"COD",
    "packageValue": 120,
    "shippingCost": 25,
    "originLatitude":40.7520394,
    "originLongitude":-73.9763424,
    "originAddress":"39, Essex Street, Opp McDonalds, South Ozone Park, New York, NY 11420",
    "pickupAccountName": "James Walker",
    "pickupPhoneNumber":"5163063377",
    "pickupEmailId":"james.w@ablogs.com",
    "pickupServiceTime":50,
    "pickupApartment": "39",
    "pickupStreetName":"Essex Street",
    "pickupLandmark":"Opp. McDonalds",
    "pickupLocality":"South Ozone Park",
    "pickupCity":"New York",
    "pickupState":"NY",
    "pickupCountry":"USA",
    "pickupPinCode": "11420",
    "pickupStartTimeWindow": "2024-07-19T14:24:00.000Z",
    "pickupEndTimeWindow": "2024-07-19T14:30:00.000Z",
    "pickupAddressTimezone":"America/New_York",
    "pickupNotes": "PickedUp",
    "destinationLatitude": 41.882702,
    "destinationLongitude": -87.619392,
    "destinationAddress": "201, E Randolph St, Opp. Chipotle, Downtown Chicago, Chicago, IL, 60602",
    "deliveryAccountName":"Jane Doe",
    "deliverPhoneNumber":"9891234567",
    "deliverEmailId":"m.richardson@testmail.com",
    "deliverServiceTime": 10,
    "deliverApartment": "201",
    "deliverStreetName": "E Randolph St",
    "deliverLandmark": "Opp. Chipotle",
    "deliverLocality": "Downtown Chicago",
    "deliverCity": "Chicago",
    "deliverState": "IL",
    "deliverCountry": "USA",
    "deliverPinCode": "60602",
    "deliverStartTimeWindow": "2024-07-19T14:30:00.000Z",
    "deliverEndTimeWindow": "2024-07-19T15:30:00.000Z",
    "deliverAddressTimezone":"America/Chicago",
    "deliverNotes":"Notes for delivery",
    "deliveryTypeDesc": "ADHOC",
    "preparationTime": 10,
    "shipmentCrateMapping": [
```

```
        {
            "crateCd": "CR041",
            "crateAmount": 100.65,
            "crateType": "case",
            "noOfUnits": 2,
            "crateWeight": 10,
            "crateVolume": 11,
            "crateLength": 12,
            "crateBreadth": 13,
            "crateHeight": 14,
            "shipmentlineitems": [
                {
                    "itemCd": "IT043",
                    "itemName": "Chicken Soup 2X200gm",
                    "itemPrice": 500,
                    "itemQuantity": 1,
                    "itemType": "soup",
                    "itemWeight": 10,
                    "itemVolume": 11,
                    "itemLength": 12,
                    "itemBreadth": 13,
                    "itemHeight": 14
                }
            ]
        }
    ],
    "carriers":[
        {
            "carrierName":"Fast Courier LLC",
            "carrierBranchName":"Fast Courier NYC",
            "carrierBranchCd":"Fast Courier NYC",
            "carrierReferenceId":"a3465bsdjfbv3458aowern",
            "expirationTime":"2021-07-15T10:30:45.000Z",
            "orderPoolDetails":[
                {
                    "orderNo":"OD123456",
                    "orderReferenceId":"d1c96e8bf384c40aea0fd1a3d58",
                    "additionalDistanceInKms": 0.876
                }
            ]
        }
    ],
}
```


- This notification is sent to the carrier branch to which the order is offered. It is triggered only when configured in the branch webhook profile.

RESPONSE PARAMETERS

Parameter	DataType	Description
notificationType	String	Type of event that triggered the webhook. For an 'order offer' event, the value is set to 'CARRIERORDEROFFER'.
timestamp	String	Timestamp (in UTC format) when an order is assigned to a suitable carrier.
clientName	String	Name of the shipper's company associated with the order. This field is included if the order was created by one of your shippers or by you on behalf of one of your shippers.
parentOrderNo	String	Unique identifier of this order's parent order, if any. This field is included only for orders with a single pickup and multiple destinations and is excluded for orders with a single pickup and single destination.
		Unique identifier assigned to the order during its creation. In case of a single pickup and multiple

orderNo	String	destinations, this is the first order number in the sequence. In case of a single pickup and single destination, this is the associated order number.
orderReferenceId	String	Unique identifier generated by the system, associated with the order which is offered to the carrier.
milestoneNo	String	Milestone number associated with an end-to-end order. This field is included only for orders created using an end-to-end account and is excluded for orders created with other account types.
milestoneReferenceId	String	Unique identifier generated by the system, associated with the specific milestone. This field is included only for orders created using an end-to-end account and is excluded for orders created with other account types.
awbNumber	String	Air Waybill or AWB number associated with the order that is offered to the carrier.
allocationTimestamp	String	Timestamp (in UTC format) at which the auto-assignment engine has identified the suitable carrier.
distanceInKms	String	Estimated distance (in kms) that the carrier needs to cover between the pick-up and delivery location.
orderState	String	State of the order. Whether the order is in the 'FORWARD' or 'REVERSE' state.
priority	String	Priority value applicable to the order. For example, this could be 'PRIORITY1', 'PRIORITY2', or 'PRIORITY3'.
deliveryType	String	Skill sets or special requirements associated with the order. This field is included if the order requires a specific type of pickup/delivery.
serviceType	String	Service type applicable for the order.
packageWeight	Double	Total weight of the order.
packageVolume	Double	Total volume of the order.
packageLength	Double	Total length of the order.
packageBreadth	Double	Total breadth of the order.
packageHeight	Double	Total height of the order.
noOfItems	Integer	Total number of crates in the order.
paymentMode	String	Payment mode of the order. Whether the mode of payment is 'COD' (i.e., Cash On Delivery) or 'Prepaid'.
packageValue	Double	Total cost of the order.
shippingCost	Double	The total cost incurred in the movement of the order.
originLatitude	Double	Latitude coordinates of the origin location.
originLongitude	Double	Longitude coordinates of the origin location.
originAddress	String	Address of the origin location.
pickupAccountName	String	Unique identifier associated with the pickup customer. For delivery type of orders, this will be the branch name.
		Contact number associated with the pickup customer. For delivery type of orders, this will be the

pickupPhoneNumber	String	branch admin's contact number.
pickupEmailId	String	Email ID associated with the pickup customer. For delivery type of orders, this will be the email ID of the branch admin.
pickupServiceTime	Integer	Time taken (in minutes) to service the customer at this particular address.
pickupApartment	String	Name of the apartment building/complex in the customer's pickup address. For delivery type of orders, this will be the origin branch details.
pickupLandmark	String	Landmark of the customer's pickup location. For delivery type of orders, this will be the landmark of the origin branch location.
pickupCity	String	Name of the city of the pickup customer. For delivery type of orders, it will be the city of the origin branch.
pickupState	String	Name of the state of the pickup customer. This should be as per the State Codes available in the LogiNext system for the selected country. For delivery type of orders, it will be the state of the origin branch.
pickupCountry	String	Name of the country of the pickup customer. For delivery type of orders, it will be the country of the origin branch. This should be as per the Country Codes available in the LogiNext system.
pickupPinCode	String	Postal code of the pickup customer. For delivery type of orders, it will be the postal code of the origin branch.
pickupStartTimeWindow	String	The start date and time (in UTC format) after which the delivery associate should reach the customer's location for pickup of the order. This field is excluded for the delivery type of orders.
pickupEndTimeWindow	String	The end date and time (in UTC format) before which the delivery associate should reach the customer's location for pickup of the order. This field is excluded for the delivery type of orders.
pickupAddressTimezone	String	Timezone of the pickup location. For delivery type of orders this will be of the origin branch. This should be as per the Timezone Codes available in the LogiNext system.
pickupNotes	String	Any additional pickup instructions/notes that the delivery associate should follow.
destinationLatitude	Double	Latitude coordinates of the delivery location.
destinationLongitude	Double	Latitude coordinates of the delivery location.
destinationAddress	String	Address of the order's destination location.
deliveryAccountName	String	Unique identifier associated with the delivery customer. For pickup type of orders, this will be the branch name.
deliverPhoneNumber	String	Contact number associated with the delivery customer. For pickup type of orders, this will be the branch admin's contact number.
deliverEmailId	String	Email ID associated with the delivery customer. For pickup type of orders, this will be the email ID of the branch admin.
deliverServiceTime	Integer	Time taken (in minutes) to service the customer at this particular address.
deliverApartment	String	Name of the apartment building/complex in the customer's delivery address. For pickup type of orders, this will be the origin branch details.
deliverStreetName	String	Name of the society or street in the customer's delivery address. For pickup type of orders, this will be the name of the society or street in the origin branch address.

deliverLandmark	String	Landmark of the customer's delivery location. For pickup type of orders, this will be the landmark of the origin branch location.
deliverLocality	String	Name of the locality or area in the customer's delivery address. For pickup type of orders, this will be the locality or area in the origin branch location.
deliverCity	String	Name of the city of the delivery customer. For pickup type of orders, it will be the city of the origin branch.
deliverState	String	Name of the state of the delivery customer. This should be as per the State Codes available in the LogiNext system for the selected country. For pickup type of orders, it will be the state of the origin branch.
deliverCountry	String	Name of the country of the pickup customer. This should be as per the Country Codes available in the LogiNext system for the selected country. For pickup type of orders, it will be the state of the origin branch.
deliverPinCode	String	Postal code of the delivery customer. For pickup type of orders, it will be the postal code of the origin branch.
deliverStartTimeWindow	String	The start date and time (in UTC format) after which the delivery associate should reach the customer's location for delivery of the order. This field is excluded for the pickup type of orders.
deliverEndTimeWindow	String	The end date and time (in UTC format) after which the delivery associate should reach the customer's location for delivery of the order. This field is excluded for the pickup type of orders.
deliverAddressTimezone	String	Timezone of the delivery location. For pickup type of orders, this will be of the origin branch. This should be as per the Timezone Codes available in the LogiNext system.
deliveryTypeDesc	String	Delivery type description (or specifically, skill set description)
preparationTime	Integer	Preparation time of the order. This is determined by the system based on the following factors, listed in order of priority: 1. Order preparation time. 2. 'Item Preparation Time' along with the 'Branch Load Factor'. 3. Maximum of item preparation time vs. branch preparation time if 'Item Preparation Time' is configured only for selected items. 4. 'Branch's Average Preparation Time' along with the 'Branch Load Factor'. 5. Default value of 0 if none of the above sources are available.
deliverNotes	String	Any additional delivery instructions/notes that the delivery associate should follow.

CARRIER INFORMATION

Parameter	Data Type	Description
carrierName	String	Name of the carrier to whom the order was offered.
carrierBranchName	String	Name of the branch associated with the carrier to whom the order was offered.
carrierBranchCd	String	Unique identifier of the branch associated with the carrier to whom the order was offered.
carrierReferenceId	String	Unique identifier generated by the system, associated with the carrier.
expirationTime	String	Time duration when the offer expires.
orderPoolDetails	List	List of order details, including the order number, reference ID, and the additional distance that needs to be covered to complete the order.

orderPoolDetails.orderNo	String	Unique identifier associated with the order that was offered to the carrier.
orderPoolDetails.orderReferenceId	String	Unique identifier generated by the system, associated with the order that was offered to the carrier.
orderPoolDetails.additionalDistanceInKms	String	Additional distance (in kms) that the carrier's delivery associate needs to cover to complete the order.

CARRIER TRIP ASSIGNMENT

Sample Response


```
{
 "notificationType": "CARRIERTRIPASSIGNMENT",
 "tripName": "TRIP-181934",
 "branchName": "CITYSPRINT_LONDON1_qa",
 "tripReferenceId": "61f130bd2ac14fcc9b4f69c770dda793",
 "tripStatus": "NOTSTARTED",
 "carrierName": "CITYSPRINT1_qa",
 "carrierBranchName": "CITYSPRINT_LONDON1_qa",
 "carrierReferenceId": "f164ace6a11a418e9dbc6d63048f2c03",
 "clientName": "Loginext Test India First Last Mile",
 "fleetType": "DV",
 "orderDetails": [
   {
     "orderNo": "ProdCall_007",
     "orderReferenceId": "4f3bd079985d4a7994a13331666c7c68",
     "awbNumber": "AWBPD-6360702114",
     "packageValue": 100,
     "orderState": "FORWARD",
     "deliveryType": "APIM1",
     "noOfItems": 1,
     "paymentMode": "Prepaid",
     "deliveryTypeDesc": "APIM1",
     "clientName": "Loginext Test India First Last Mile",
     "pickupDetails": {
       "accountName": "Nearby_City_Branch_qa",
       "phoneNumber": "2269622",
       "stopId": "stop12345",
       "stopSequence": "0",
    "addressID": "adressId000012345",
       "latitude": 51.5225922,
       "longitude": -0.08423409999999999,
       "startTimeWindow": "2025-05-29 11:39:16",
       "endTimeWindow": "2025-05-30 11:39:16",
       "pickupAddressID": "adressId000012345",
       "address": " 8-10 Paul Street, London EC2A 4JH, London, UNITED KINGDOM, ",
       "emailId": "testk@m.com",
       "apartment": " 8-10 Paul Street",
       "streetName": "London EC2A 4JH",
       "landmark": "",
       "locality": "",
       "city": "London",
       "country": "UNITED KINGDOM",
       "pinCode": "EC2A 4JH",
       "addressTimezone": "Europe/London"
     },
     "deliverDetails": {
       "accountName": "Deliver1-6360702114",
       "phoneNumber": "-",
"stopId": "stop12345"
       "stopSequence": "1",
"addressId": "adressId000012346",
       "latitude": 55.378051,
```

```
        "longitude": -3.435973,
        "startTimeWindow": "2025-05-29 11:39:16",
        "endTimeWindow": "2025-05-30 11:39:16",
        "delivrAddressId": "adressId000012346",
        "address": "Welsh Blood,Glamorgan,Talbot,Welsh Blood,Talbot,UNITED KINGDOM,CF72 9WB",
        "emailId": "DeliverCustomerAutomationTest@mailinator.com",
        "serviceTime": 10,
        "apartment": "Welsh Blood",
        "streetName": "Glamorgan",
        "landmark": "Welsh Blood",
        "locality": "Talbot",
        "city": "Talbot",
        "country": "UNITED KINGDOM",
        "pinCode": "CF72 9WB",
        "addressTimezone": "Europe/London"
      },
      "customFields": {
        "cf_AccountCodes": "Blood Manchester",
        "cf_VehicleType": "DV"
      }
    }
  ]
```


- This notification is sent to a carrier branch when a trip is assigned.

RESPONSE PARAMETERS

Parameter	DataType	Description
notificationType	String	Type of event that triggered the webhook. For a 'trip assignment' event, the value is set to ‘CARRIERTRIPASSIGNMENT’.
timestamp	String	Timestamp (in UTC format) when the trip is assigned to a suitable carrier.
tripName	String	Name of the trip.
branchName	String	Name of the branch associated with the trip.
tripReferenceId	String	Unique identifier generated by the system, associated with the trip.
tripStatus	String	Current status of the trip (e.g., NOT STARTED, STARTED, ENDED).
carrierName	String	Name of the carrier to whom the trip has been assigned.
carrierBranchName	String	Name of the branch associated with the carrier to whom the trip has been assigned.
carrierReferenceId	String	Unique identifier generated by the system, associated with the carrier.
AddressId	String	Unique identifier assigned to a customer’s pickup/delivery address.
stopId	String	Unique identifier associated with a stop within the trip assigned to the carrier. If multiple pickups or deliveries are scheduled in sequence at the same address, they are grouped into a single stop.
stopSequence	String	The sequence in which the stop will be visited during the trip is assigned to the carrier based on the Delivery Run Sheet (DRS). For example, if the value is set to 3 in the DRS, the carrier will visit this stop in the 3rd place in the sequence.
clientName	String	Name of the shipper's company associated with the trip. This field is included if the order was created by one of your shippers or by you on behalf of one of your shippers.

fleetType	String	Name of the Fleet Type associated with the trip.
orderDetails	Array of Objects	List of order details in the current trip, including order number, type, reference ID, payment type, and other relevant details.
orderDetails.orderNo	String	Unique identifier associated with the order in the trip.
orderDetails.orderReferenceId	String	Unique identifier generated by the system, associated with the order in the trip.
orderDetail.awbNumber	String	Air Waybill or AWB number associated with an order in the trip.
orderDetails.packageValue	Integer	Final cost of the order after applying the discount, if any.
orderDetails.orderState	String	State of the order. This is the kind of operational model that a particular order belongs to. Order state helps you understand the direction of order, whether the order is in forward state or reverse state. Specify ‘FORWARD’ if the order is in a forward state (i.e., the orders are either to be picked up from the merchants or delivered to the customers) or ‘REVERSE’ if the order is in a reverse state (i.e., the orders are return orders that are scheduled to be picked up from end customers and delivered back to the branch or merchant, or picked up from the branch and delivered back to the merchant).
orderDetails.deliveryType	String	Skill sets or special requirements associated with the order. This field is included if the order requires a specific type of pickup/delivery..
orderDetails.noOfItems	Integer	Total number of crates in the order.
orderDetails.paymentMode	String	Payment mode of the order. Whether the mode of payment is 'COD' (i.e., Cash On Delivery), ‘COP’ (i.e., Cash On Pickup) or 'Prepaid'.
orderDetails.deliveryTypeDesc	String	Delivery type description (or specifically, skill set description)
orderDetails.clientName	String	Name of the organization configured in Organization Profile.
orderDetails.pickupDetails	Object	Details for the pickup leg of the order, including latitude, longitude, start and end time window, order sequence, and other relevant details.

Delivery Associate

CREATE

Sample Response


```
{
    "referenceId": "f40cf4493a5949199775499b5750a272",
    "notificationType": "CREATEDELIVERYMEDIUMNOTIFICATION",
    "timestamp": "2024-06-25 07:31:39",
    "employeeId":"1001",
    "deliveryMediumName": "James",
    "phoneNumber": "63865471261",
    "imei": "123456789012645",
    "emailId": "james@ablogistics.com",
    "userName": "james003",
    "capacityInUnits": 10,
    "capacityInVolume": 0,
    "capacityInWeight": 0,
    "dob": "2016-12-12",
    "deliveryMediumLanguageList": ["ENGLISH","SPANISH"],
```

```
    "gender": "Male",
    "deliveryMediumTypeCd": ["Delivery Associate"],
    "isOwnVehicleFl": "Company",
    "vehicleNumber": "MH034506",
    "dmPreference": ["10035"],
    "cashInHand":"4000",
    "shiftList": [
      {
        "shiftStart": "13:30:00",
        "shiftEnd": "14:30:00"
      }
    ],
    "maxDistance": 100,
    "licenseValidity": "2018-12-12T13:30:00Z",
    "weeklyOffList": ["Thursday","Monday"],
    "fixedCost":"500",
    "variableCost":"30"
}
```

- This notification is sent when the delivery associate is created in the LogiNext system.

RESPONSE PARAMETERS

Parameter	DataType	Description
referenceId	String	Unique identifier generated by the system, associated with delivery associate.
notificationType	String	Type of event that triggered the webhook. For a ‘create delivery associate’ event, the value is set to 'CREATEDELIVERYMEDIUMNOTIFICATION’.
deliveryMediumName	String	Name of the delivery associate.
employeeId	String	Employee ID of the delivery associate.
phoneNumber	String	Contact number of the delivery associate.
imei	String	IMEI number of the delivery associate’s phone.
emailId	String	Email ID of the delivery associate.
userName	String	Username using which the delivery associate would log into the Driver App.
capacityInUnits	Integer	Capacity in terms of order/crate units that the delivery associate can carry in a trip.
capacityInVolume	Integer	Capacity in terms of volume that the delivery associate can carry in a trip.
capacityInWeight	Integer	Capacity in terms of weight that the delivery associate can carry in a trip.
dob	String	Date of birth of the delivery associate in YYYY-MM-DD format.
deliveryMediumLanguageList	List	List of languages that the delivery associate is able to converse in.
gender	String	Gender of the delivery associate. For example - Male, Female.
deliveryMediumTypeCd	String	Skill sets that the delivery associate possesses to carry out specific orders.
isOwnVehicleFl	String	Whether the vehicle is owned by the delivery associate or by the company.
vehicleNumber	String	Number of the vehicle linked with the delivery associate.

dmPreference	String	Specific postal codes allocated to a delivery associate for pickups/deliveries. Note that the delivery associates will not be assigned orders outside these postal codes.
cashInHand	Double	Total amount of cash collected by the delivery associate during the pickups/deliveries.
shiftList	List	List of delivery associate's shift details, including shift start time, end time, license validity, and other relevant details.
shiftList.shiftStart	String	Shift start time of the delivery associate in HH:MM:SS format.
shiftList.shiftEnd	String	Shift end time of the delivery associate in HH:MM:SS format.
maxDistance	Integer	Maximum distance (in kms) that the delivery associate can travel in a trip, from the branch till the last order's pickup/delivery location.
licenseValidity	String	Date on which the delivery associate's license would expire.
reasonCd	String	Unique code associated with the reason for delivery associate's activation or deactivation.
updateTime	String	Timestamp (in UTC format) when the delivery associate is marked as Active or Inactive.
weeklyOffList	List	List of day(s) on which the delivery associate takes their weekly off.
fixedCost	Integer	Fixed cost associated with delivery associate.
variableCost	Integer	Variable cost associated with each unit of distance travelled by the delivery associate.

ACTIVE/INACTIVE STATUS

Sample Response

```
{
  "referenceId":"6186d5fc6e324c42abb5ea1a32e05f66",
  "deliveryMediumName":"Thomas Walton",
  "employeeId":"133456",
  "phoneNumber":"9881134567",
  "newStatus":"ACTIVE",
  "reasonCd":"DBUNAVAILABLE",
  "updateTime":"2018-07-18T10:31:00.000Z"
}
```

- This notification is sent when the delivery associate is marked as Active or Inactive.

RESPONSE PARAMETERS

Parameter	DataType	Description
referenceId	String	Unique identifier generated by the system, associated with delivery associate.
deliveryMediumName	String	Name of the delivery associate.
employeeId	String	Employee ID of the delivery associate.
phoneNumber	String	Contact number of the delivery associate.
newStatus	String	Current status of the delivery associate. Whether the delivery associate is marked as 'ACTIVE' or 'INACTIVE'.
reasonCd	String	Unique code associated with the reason for delivery associate's activation or deactivation.

updateTime	String	Timestamp (in UTC format) when the delivery associate is marked as Active or Inactive.

BREAK STATUS

Sample Response

```
{
  "latitude":40.882702,
  "longitude":74.619392,
  "timestamp":"2024-07-05 13:22:32",
  "deliveryMediumName":"Sam",
  "tripName":"TRIP-17774",
  "referenceId":"dde5a971e67c4256af48436fe51f23c2",
  "employeeId":"7324567",
  "userName":"Sam1234",
  "breakStatus":"ONBREAK"

}
```

- This notification is sent when the delivery associate is marked as ONBREAK or OFFBREAK.

RESPONSE PARAMETERS

Parameter	DataType	Description
latitude	String	Latitude coordinates of the delivery associate when they are marked as on break.
longitude	String	Longitude coordinates of the delivery associate when they are mnarked as on break.
timestamp	String	Timestamp when the delivery associate is marked as 'ONBREAK' or 'OFFBREAK.
deliveryMediumName	String	Name of the delivery associate.
clientId	String	Name of the shipper's company associated with the order. This field is included if the order was created by one of' your shippers or by you on behalf of one of your shippers.
referenceId	String	Unique identifier generated by the system, associated with delivery associate.
employeeId	String	Employee ID of the delivery associate.
userName	String	Username using which the delivery associate would log into the Driver App.
breakStatus	String	Current break status of the delivery associate. Whether the delivery associate is marked as 'ONBREAK' or 'OFFBREAK'.

LOGIN/LOGOUT STATUS

Sample Response

```
{
  "latitude": 19.12156087,
  "longitude": 72.91752408,
  "timestamp": "2024-02-24 09:33:05",
  "notificationType": "LOGNOTIFICATION",
  "deliveryMediumName": "kjstage4",
  "tripName": "TRIP-27830",
  "referenceId": "77b958b204974c6d995d3df154a7d763",
  "employeeId": "KJstage4",
```

```
  "userName": "kjstage4",
  "loginStatus": "LOGGEDOUT"
}
```

- This notification is sent when the delivery associate logs in or out of the Driver App.

RESPONSE PARAMETERS

Parameter	DataType	Description
latitude	String	Latitude coordinates of the delivery associate when they logs in or out of the Driver App.
longitude	String	Longitude coordinates of the delivery associate when they logs in or out of the Driver App.
timestamp		Timestamp (in UTC format) when the delivery associate logs in or out of the Driver App.
notificationType	String	Type of event that triggered the webhook. For a ‘delivery associate’s login/logout’ event, the value is set to 'LOGNOTIFICATION’.
deliveryMediumName	String	Name of the delivery associate.
tripName	String	Name of the trip associated with the delivery associate.
referenceId	String	Unique identifier generated by the system, associated with delivery associate.
employeeId	String	Employee ID of the delivery associate.
userName	String	Username using which the delivery associate would log into the Driver App.
loginStatus	String	Current login status of the delivery associate. Whether the delivery associate is ‘LOGGEDIN’ or ‘LOGGEDOUT’ of the Driver App.

BONUS ACHIEVED

Sample Response

```
{
  "deliveryMediumReferenceId": "e29f11598a4e4878a01gwg3cfbc0112b",
  "notificationType": "BONUSACHIEVED",
  "deliveryMediumUserName": "denise_rud",
  "deliveryMediumEmployeeId": "Denise12",
  "bonusName": "Daily 15 orders",
  "bonusCode": "Daily_15",
  "bonusStartTime": "2023-05-05 00:00:00",
  "bonusEndTime": "2023-05-30 23:59:59",
  "bonusAmount": 57.2,
  "totalBonusAmount": 472.5,
  "timestamp": "2024-05-12 15:00:00"
}
```

- This notification is sent when a delivery associate earns an additional amount through a bonus initiative.

RESPONSE PARAMETERS

Parameter	DataType	Description
notificationType	String	Type of event that triggered the webhook. For a ‘bonus achieved’ event, the value is set to 'BONUSACHIEVED’.
deliveryMediumReferenceId	String	

		Unique identifier generated by the system, associated with delivery associate.
deliveryMediumUsername	String	Username using which the delivery associate would log into the Driver App.
deliveryMediumEmployeeId	String	Employee ID of the delivery associate.
bonusCode	String	Unique code associated with the bonus through which the delivery associate earns an additional amount.
bonusName	String	Name of the bonus through which the delivery associate earns an additional amount.
bonusStartTime		Start date and time (in UTC format) of the bonus when it is aaplicable to the delivery associate.
bonusEndTime		End date and time (in UTC format) of the bonus until when it is aaplicable to the delivery associate.
bonusAmount	Decimal, upto 3 decimal places	Additional bonus amount earned by the delivery associate.
totalBonusAmount	Decimal, upto 3 decimal places	Total bonus amount earned by the delivery associate.
timestamp		Timestamp (in UTC format) when the delivery associate earns the bonus.

Route

CREATE (MILE)

Sample response: For Forward Route


```
{
  "notificationType": "CREATEROUTENOTIFICATION",
  "timestamp": "2024-06-25 07:31:39",
  "routeType": "FORWARD",
  "routeDetails": {
    "originHub": "Mumbai",
    "destinationHub": "Pune",
    "routeName": "Mumbai_Pune_786",
    "routeCode": "Mumbai_Pune_786",
    "serviceType": "Express",
    "serviceTime": "2 Days",
    "skillSet": "Delivery,Install,Clothing,Helper,Small Box,Document",
    "serviceDays": "Mon, Tue, Wed, Thurs, Fri",
    "milestones": [
      {
        "fromBranch": "Mumbai",
        "toBranch": "Mumbai Air Hub",
        "milestoneType": "DELIVER",
        "modeOfTransport": "Roadways",
        "deliveryDay": "Day 0",
        "unloadingTime": 20,
        "startTime": "14:00",
        "endTime": "02:00"
      },
      {
```

```
        "fromBranch": "Mumbai Air Hub",
        "toBranch": "Mumbai",
        "milestoneType": "DELIVER",
        "modeOfTransport": "Roadways",
        "deliveryDay": "Day 1",
        "unloadingTime": 10,
        "startTime": "22:00",
        "endTime": "22:30"
      }
    ]
  }
}
```


Sample Response: For Reverse Route


```
{
"notificationType": "CREATEROUTENOTIFICATION",
"timestamp": "2024-06-25 07:31:39",
"routeType": "RETURN",
"routeDetails": {
  "originHub": "Mumbai",
  "destinationHub": "Pune",
  "routeName": "Mumbai_Pune_786",
  "routeCode": "Mumbai_Pune_786",
  "serviceType": "Express",
  "serviceTime": "2 Days",
  "skillSet": "Delivery,Install,Clothing,Helper,Small Box,Document",
  "serviceDays": "Mon, Tue, Wed, Thurs, Fri",
  "milestones": [
    {
      "fromBranch": "Mumbai",
      "toBranch": "Mumbai Air Hub",
      "milestoneType": "DELIVER",
      "modeOfTransport": "Roadways",
      "deliveryDay": "Day 0",
      "unloadingTime": 20,
      "startTime": "14:00",
      "endTime": "02:00"
    },
    {
      "fromBranch": "Mumbai Air Hub",
      "toBranch": "Mumbai",
      "milestoneType": "DELIVER",
      "modeOfTransport": "Roadways",
      "deliveryDay": "Day 1",
      "unloadingTime": 10,
      "startTime": "22:00",
      "endTime": "22:30"
    }
  ]
}
}
```


- This notification is sent when a new route is created in the LogiNext system.

RESPONSE PARAMETERS

Parameter	DataType	Description
notificationType	String	Type of event that triggered the webhook. For the 'create route' event, the value is set to 'CREATEROUTENOTIFICATION'.
timestamp	String	Timestamp when the route is created in the system.

routeType	String	Type of the route. Whether the route is 'Forward' or 'Reverse'.
routeDetails	Object	List of route details, including origin branch, destination branch, route name, code, and other relevant details.
originHub	String	Name of the origin branch.
destinationHub	String	Name of the destination branch.
routeName	String	Name of the route.
routeCode	String	Unique identifier for the route in the system.
serviceType	Long	Service type applicable for this route. For example, a one-day delivery, 30-minute delivery, and so on.
skillSet	String	Skill sets or special requirements associated with the service type or route.
serviceDays	List	Service days associated with the service type or route.
milestones	Object	List of milestone details, including the branch from which the route starts/ends, milestone type, mode of transport, and other relevant details.
fromBranch	String	Branch from which the milestone begins.
toBranch	String	Branch at which the milestone ends.
milestoneType	String	Whether this is a pickup milestone or a delivery milestone.
modeOfTransport	String	Mode of transportation for the milestone. Whether it is Railways, Roadways, Airways, or Waterways.
deliveryDay	String	Day on which the milestone begins.
startTime	String	Start time by which the trip must start for this milestone.
endTime	String	End time by which the trip must be completed for this milestone.

Cash Transaction

Sample Response

```
{
  "notificationType": "CASHTRANSACTIONNOTIFICATION",
  "timestamp": "2024-06-25 07:31:39",
  "reason": "Personal use",
  "transactionId": "Tx9921",
  "transactionType": "Debit",
  "transactionAmount": 900,
  "transactionDate": "2024-08-05 10:37:18",
  "deliveryMediumReferenceId": "9827b7cf535f424fb90c81381165fe2c",
  "employeeId": "ProdDA",
  "comments": "user comments",
  "url": "https://loginextmobilelive-userfiles.com/uploads/cashtransactions/998ba566aeece5cfba1.zip",
  "transferType":"selfExpenses"
}
```

- This notification is sent when a cash transaction has been recorded successfully.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a 'cash transaction' event, the value is set to 'CASHTRANSACTIONNOTIFICATION'.
transactionId	String	Unique identification associated with the transaction.
transactionDate	String	Timestamp (in UTC format) of the cash transaction.
deliveryMediumReferenceId	String	Unique identifier generated by the system, associated with the specific delivery associate assigned for whom the transaction is recorded.
employeeId	String	Employee ID of the delivery associate for whom the transaction is recorded.
transactionType	String	Whether the transaction amount is a 'Credit' or 'Debit'.
transactionAmount	Double	Amount involved in this particular transaction.
reason	String	Reason for depositing less than the pending amount, based on the reasons configured in the system.
comments	String	Any additional details related to the cash transaction.
url	String	Link to download the transaction proof.
transferType	String	Type of the transaction. Whether it is 'selfExpense', 'transferToOtherDeliveryAssociate', or 'transferToBranch'.

Exception

CREATE

Sample Response

```
{
  "notificationType": "CREATEEXCEPTIONNOTIFICATION",
  "timestamp": "2024-04-25 00:00:00",
  "createdByUserId": 519829,
  "exceptionCode": "M-0941",
  "exceptionName": "Damaged Packaging",
  "exceptionMessage": "Need to Repack this Order",
  "exceptionStage": [
    "Inscan",
    "Outscan"
  ],
  "exceptionType": "Informational"
}
```

- This notification is sent when a new exception is created in the LogiNext system.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a ‘create exception’ event, the value is set to 'CREATEEXCEPTIONNOTIFICATION'.
timestamp	String	Timestamp of the exception when it is created in the system (in UTC format).
createdByUserId	String	Unique identifier associated with the user who created the exception.
exceptionCode	String	Unique identifier associated with the new exception.
exceptionName	String	Name of the exception.
exceptionMessage	String	The message that is displayed when the exception occurs.
exceptionStage	String	The stage(s) in the lifecycle of an order/manifest where the exception is validated. This could be at the ‘Load’, ‘Unload’, ‘Inscan’, or ‘Outscan’ stage.
exceptionType	String	Type of the exception. Whether the exception raised is ‘Informational’ or ‘Action Required’.

RAISE

Sample Response

```
{
  "orderNo": "18042022000001",
  "timestamp": "2024-04-25 11:25:54",
  "notificationType": "RAISEEXCEPTIONNOTIFICATION",
  "exceptionCode": "M-0941",
  "exceptionName": "Damaged Packaging",
  "exceptionMessage": "Need to Repack this Order",
  "exceptionStage": [
    "Inscan",
    "Outscan"
  ],
  "exceptionType": "Informational",
  "exceptionMode": "Manual",
  "exceptionAppliesTo": "Orders",
  "createdBy": "pushkar.s@loginextsolutions.com"
}
```

- This notification is sent when a new exception is raised against an order/manifest.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a ‘raise exception’ event, the value is set to 'RAISEEXCEPTIONNOTIFICATION'.
orderNo	String	Unique identifier of the order against which the exception is raised. This field is included only if the exception is raised against the order.
manifestId	String	Unique identifier of the manifest against which the exception is raised. This field is included only if the exception is raised against the manifest.
timestamp	String	Timestamp of the exception when it is raised against the order/manifest (in UTC format).
exceptionCode	String	Unique identifier of the exception raised against the order/manifest.

exceptionName	String	Name of the exception.
exceptionMessage	String	The message that is displayed when the exception occurs.
exceptionStage	String	The stage(s) in the lifecycle of an order/manifest where the exception is validated. This could be at the 'Load', 'Unload', 'Inscan', or 'Outscan' stage.
exceptionType	String	Type of the exception. Whether the exception raised is 'Informational' or 'Action Required'.
exceptionMode	String	Mode of the exception. Whether the exception is 'Manual' or 'Event Based'.
exceptionAppliesTo	String	Whether the exception is applicable to the 'Orders', 'Manifests', or both 'Orders' and 'Manifests'.
createdBy	String	Email ID of the user who raised the exception.

RESOLVE

Sample Response

```
{
  "orderNo": "18042022000001",
  "timestamp": "2024-04-25 11:25:55",
  "notificationType": "RESOLVEEXCEPTIONNOTIFICATION",
  "exceptionCode": "M-0941",
  "exceptionName": "Damaged Packaging",
  "exceptionMessage": "Need to Repack this Order",
  "exceptionStatus": "CLOSED",
  "exceptionNotes": "Resolved comment",
  "updatedBy": "support@loginextsolutions.com"
}
```

- This notification is sent when an exception is resolved against an order/manifest.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a 'resolve exception' event, the value is set to 'RESOLVEEXCEPTIONNOTIFICATION'.
orderNo	String	Unique identifier of the order against which the exception is resolved. This field is included only if the exception is resolved against the order.
manifestId	String	Unique identifier of the manifest against which the exception is resolved. This field is included only if the exception is resolved against the manifest.
timestamp	String	Timestamp of the exception when it is resolved against the order/manifest (in UTC format).
exceptionCode	String	Unique identifier of the exception resolved against the order/manifest.
exceptionName	String	Name of the exception.
exceptionMessage	String	The message that is displayed when the exception occurs.
exceptionStatus	String	Current status of the exception.
exceptionNotes	String	Any additional notes added by the user when resolving the exception.
updatedBy	String	Email ID of the user who resolved the exception.

REJECT

Sample Response

```
{
  "orderNo": "18042022000001",
  "timestamp": "2024-04-25 11:44:01",
  "notificationType": "REJECTEXCEPTIONNOTIFICATION",
  "exceptionCode": "M-0941",
  "exceptionName": "Damaged Packaging",
  "exceptionMessage": "Need to Repack this Order",
  "exceptionStatus": "REJECTED",
  "exceptionNotes": "Rejected Notes",
  "updatedBy": "support@loginextsolutions.com"
}
```

- This notification is sent when an exception is rejected against an order/manifest.

RESPONSE PARAMETERS

Parameter	Datatype	Description
notificationType	String	Type of event that triggered the webhook. For a 'reject exception' event, the value is set to 'REJECTEXCEPTIONNOTIFICATION'.
orderNo	String	Unique identifier of the order against which the exception is rejected. This field is included only if the exception is rejected against the order.
manifestId	String	Unique identifier of the manifest against which the exception is rejected. This field is included only if the exception is rejected against the manifest.
timestamp	String	Timestamp of the exception when it is rejected against the order/manifest (in UTC format).
exceptionCode	String	Unique identifier of the exception rejected against the order/manifest.
exceptionName	String	Name of the exception.
exceptionMessage	String	The message that is displayed when the exception occurs.
exceptionStatus	String	Current status of the exception.
exceptionNotes	String	Any additional notes added by the user when rejecting the exception.
updatedBy	String	Email ID of the user who rejected the exception.

Custom Fields

Request

```
"customFields":[
    {
        "field":"cf_cutOffDate",
        "value":"2018-06-25T07:31:39Z.000",
```

```
        "type":"datetime"
    }

]
```

If you require certain additional fields to store information regarding your Orders or Resources in LogiNext, you can use our Custom Fields features.

With Custom Fields, you can enter information for reporting and analytics purposes specific to your business use case.

For eg - If you need to look for specific servicability constraints like cut off times within with a certain area/ geofence can be serviced, you can configure a cut off time custom field in LogiNext that will display the availability timelines for that area/ geofence.

To configure Custom Fields for your account, You can do so from the Custom Fields section of your Admin module.

Once configured, you can enter data for the custom fields like any other field in LogiNext. These fields are currently available in the APIs and UI. Please note that when passing a Custom Field name in the API request object, the Custom Field name would have be preceeded by 'cf_' to signify that this is a Custom Field.

Please Note that if you send these fields in the API without first configuring them in your LogiNext account, the LogiNext API will NOT create a new Custom Field. You will receive a success response from such an API call, but the data sent in the 'customField object will not be considered. The data passed in the API can only be associated with an already existing Custom Field with the identifier specified in the request.

If using the API, you will need to add the Custom Fields object on the right as part of the API request body to create the new fields in LogiNext.

For eg - If you have Custom Fields configured for the Orders module, you will need to append the request on the right to the request body of the create order API.

For a Custom Field you must define the following attributes

Attribute	Description
Type	Data Type of the Custom field.
Field	the name of the custom field.

LogiNext currently supports the following field types -

Text.

Number.

Dropdown.

DateTime.

Date.

Time.

Note that Date and DateTime type of type of Custom Fields will be sent in UTC format in POST API calls, and will be fetched in Epoch format in Get API calls. For example, In the Create Order API, you could pass "shipmentOrderDt": "2016-07-15T10:30:00.000Z". In Custom fields a DateTime field would have the sample value '1485153536000', which will represent a timestamp.

You can include the following validations in your custom fields at the time of creating them -

Mandatoy/ Optional.

Min length/ Man length.

Country Codes

When creating entities in LogiNext that require country-specific location information associated with them, use the country codes listed below. For example, if you want to create an order that needs to be picked up from a pickup location in the United States, you should pass the code ‘USA’ in the 'pickupCountry' parameter of the Create Order API.

If you wish to use the code for a country not listed below, reach out to your Account Manager or write to us at: support@loginextsolutions.com

Country	Code
AFGHANISTAN	AFG
ALBANIA	ALB
ALGERIA	DZA
AMERICAN SAMOA	ASM
ANDORRA	AND
ANGOLA	AGO
ANGUILLA	AIA
ANTARCTICA	ATA
ANTIGUA AND BARBUDA	ATG
ARGENTINA	ARG
ARMENIA	ARM
ARUBA	ABW
AUSTRALIA	AUS
AUSTRIA	AUT
AZERBAIJAN	AZE
BAHAMAS	BHS
BAHRAIN	BHR
BANGLADESH	BGD
BARBADOS	BRB
BELARUS	BLR

BELGIUM	BEL
BELIZE	BLZ
BENIN	BEN
BERMUDA	BMU
BHUTAN	BTN
BOLIVIA	BOL
BOSNIA AND HERZEGOWINA	BIH
BOTSWANA	BWA
BOUVET ISLAND	BVT
BRAZIL	BRA
BRITISH INDIAN OCEAN TERRITORY	IOT
BRUNEI	BRN
BULGARIA	BGR
BURKINA FASO	BFA
BURUNDI	BDI
CAMBODIA	KHM
CAMEROON	CMR
CANADA	CAN
CAPE VERDE	CPV
CAYMAN ISLANDS	CYM
CENTRAL AFRICAN REPUBLIC	CAF
CHAD	TCD
CHILE	CHL
CHINA	CHN
CHRISTMAS ISLAND	CXR
COCOS (KEELING) ISLANDS	CCK
COLOMBIA	COL
COMOROS	COM
CONGO	COG

CONGO, THE DRC	COD
COOK ISLANDS	COK
COSTA RICA	CRI
COTE D.IVOIRE	CIV
CROATIA	HRV
CUBA	CUB
CURACAO	CUW
CYPRUS	CYP
CZECH REPUBLIC	CZE
DENMARK	DNK
DJIBOUTI	DJI
DOMINICA	DMA
DOMINICAN REPUBLIC	DOM
EAST TIMOR	TMP
ECUADOR	ECU
EGYPT	EGY
EL SALVADOR	SLV
EQUATORIAL GUINEA	GNQ
ERITREA	ERI
ESTONIA	EST
ETHIOPIA	ETH
FALKLAND ISLANDS (MALVINAS)	FLK
FAROE ISLANDS	FRO
FIJI	FJI
FINLAND	FIN
FRANCE	FRA
FRANCE, METROPOLITAN	FXX
FRENCH GUIANA	GUF
FRENCH POLYNESIA	PYF

FRENCH SOUTHERN TERRITORIES	ATF
GABON	GAB
GAMBIA	GMB
GEORGIA	GEO
GERMANY	DEU
GHANA	GHA
GIBRALTAR	GIB
GREECE	GRC
GREENLAND	GRL
GRENADA	GRD
GUADELOUPE	GLP
GUAM	GUM
GUATEMALA	GTM
GUINEA	GIN
GUINEA-BISSAU	GNB
GUYANA	GUY
HAITI	HTI
HEARD AND MC DONALD ISLANDS	HMD
HOLY SEE (VATICAN CITY STATE)	VAT
HONDURAS	HND
HONG KONG	HKG
HUNGARY	HUN
ICELAND	ISL
INDIA	IND
INDONESIA	IDN
IRAN	IRN
IRAQ	IRQ
IRELAND	IRL
ISRAEL	ISR

ITALY	ITA
JAMAICA	JAM
JAPAN	JPN
JORDAN	JOR
KAZAKHSTAN	KAZ
KENYA	KEN
KIRIBATI	KIR
NORTH KOREA	PRK
SOUTH KOREA	KOR
KUWAIT	KWT
KYRGYZSTAN	KGZ
LAOS	LAO
LATVIA	LVA
LEBANON	LBN
LESOTHO	LSO
LIBERIA	LBR
LIBYAN ARAB JAMAHIRIYA	LBY
LIECHTENSTEIN	LIE
LITHUANIA	LTU
LUXEMBOURG	LUX
MACAU	MAC
MACEDONIA	MKD
MADAGASCAR	MDG
MALAWI	MWI
MALAYSIA	MYS
MALDIVES	MDV
MALI	MLI
MALTA	MLT
MARSHALL ISLANDS	MHL

MARTINIQUE	MTQ
MAURITANIA	MRT
MAURITIUS	MUS
MAYOTTE	MYT
MEXICO	MEX
MICRONESIA, FEDERATED STATES OF	FSM
MOLDOVA, REPUBLIC OF	MDA
MONACO	MCO
MONGOLIA	MNG
MONTENEGRO	MNE
MONTSERRAT	MSR
MOROCCO	MAR
MOZAMBIQUE	MOZ
MYANMAR (Burma)	MMR
NAMIBIA	NAM
NAURU	NRU
NEPAL	NPL
NETHERLANDS	NLD
NETHERLANDS ANTILLES	ANT
NEW CALEDONIA	NCL
NEW ZEALAND	NZL
NICARAGUA	NIC
NIGER	NER
NIGERIA	NGA
NIUE	NIU
NORFOLK ISLAND	NFK
NORTHERN MARIANA ISLANDS	MNP
NORWAY	NOR
OMAN	OMN

PAKISTAN	PAK
PALAU	PLW
PALESTINIAN TERRITORIES	PSE
PANAMA	PAN
PAPUA NEW GUINEA	PNG
PARAGUAY	PRY
PERU	PER
PHILIPPINES	PHL
PITCAIRN	PCN
POLAND	POL
PORTUGAL	PRT
PUERTO RICO	PRI
QATAR	QAT
REUNION	REU
ROMANIA	ROM
RUSSIAN FEDERATION	RUS
RWANDA	RWA
SAINT KITTS AND NEVIS	KNA
SAINT LUCIA	LCA
SAINT VINCENT AND THE GRENADINES	VCT
SAMOA	WSM
SAN MARINO	SMR
SAO TOME AND PRINCIPE	STP
SAUDI ARABIA	SAU
SENEGAL	SEN
SERBIA	SRB
SEYCHELLES	SYC
SIERRA LEONE	SLE
SINGAPORE	SGP

SLOVAKIA (Slovak Republic)	SVK
SLOVENIA	SVN
SOLOMON ISLANDS	SLB
SOMALIA	SOM
SOUTH AFRICA	ZAF
SOUTH SUDAN	SSD
SOUTH GEORGIA AND SOUTH S.S.	SGS
SPAIN	ESP
SRI LANKA	LKA
ST. HELENA	SHN
ST. PIERRE AND MIQUELON	SPM
SUDAN	SDN
SURINAME	SUR
SVALBARD AND JAN MAYEN ISLANDS	SJM
SWAZILAND	SWZ
SWEDEN	SWE
SWITZERLAND	CHE
SYRIA	SYR
TAIWAN	TWN
TAJIKISTAN	TJK
TANZANIA	TZA
THAILAND	THA
TOGO	TGO
TOKELAU	TKL
TONGA	TON
TRINIDAD AND TOBAGO	TTO
TUNISIA	TUN
TURKEY	TUR
TURKMENISTAN	TKM

TURKS AND CAICOS ISLANDS	TCA
TUVALU	TUV
UGANDA	UGA
UKRAINE	UKR
UNITED ARAB EMIRATES	UAE
UNITED KINGDOM	GBR
UNITED STATES	USA
U.S. MINOR ISLANDS	UMI
URUGUAY	URY
UZBEKISTAN	UZB
VANUATU	VUT
VENEZUELA	VEN
VIETNAM	VNM
VIRGIN ISLANDS (BRITISH)	VGB
VIRGIN ISLANDS (U.S.)	VIR
WALLIS AND FUTUNA ISLANDS	WLF
WESTERN SAHARA	ESH
YEMEN	YEM
ZAMBIA	ZMB
ZIMBABWE	ZWE

State Codes

When creating entities in LogiNext that require state-specific location information associated with them, use the state codes listed below. For example, if you want to create an order that needs to be picked up from a pickup location in New York, you should pass the code 'NY' in the 'pickupState' parameter of the Create Order API.

Note that the state code entered should map to the country code specified in the corresponding country parameter. For instance, you cannot use the state code for London if you have specified 'USA' as the country.

If you wish to use the code for a state not listed below, reach out to your Account Manager or write to us at: support@loginextsolutions.com

Argentina

State	Code
Ciudad Autónoma de Buenos Aires	AR-C
Buenos Aires	AR-B
Catamarca	AR-K
Chaco	AR-H
Chubut	AR-U
Córdoba	AR-X
Corrientes	AR-W
Entre Ríos	AR-E
Formosa	AR-P
Jujuy	AR-Y
La Pampa	AR-L
La Rioja	AR-F
Mendoza	AR-M
Misiones	AR-N
Neuquén	AR-Q
Río Negro	AR-R
Salta	AR-A
San Juan	AR-J
San Luis	AR-D
Santa Cruz	AR-Z
Santa Fe	AR-S
Santiago del Estero	AR-G
Tierra del Fuego	AR-V
Tucumán	AR-T

Aruba

State	Code
Aruba	ARUBA

Australia

State	Code
New South Wales	New South
Victoria	Victoria
Queensland	Queensland
South Australia	South Aust
Tasmania	Tasmania
Australian Capital Territory	ACT
Jervis Bay Territory	
Northern Territory	NT
Western Australia	WA
Ashmore and Cartier Islands	
Coral Sea Islands Territory	

Bahrain

State	Code
Al Manamah	Al Manamah
Sitrah	Sitrah
Al Mintaqah al Gharbiyah	Al Mintaqa
Al Mintaqah al Wusta	Al Mintaqa
Al Mintaqah ash Shamaliyah	Al Mintaqa

Al Muharraq	Al Muharra
Al Asimah	Al Asimah
Ash Shamaliyah	Ash Shamal
Jidd Hafs	Jidd Hafs
Madinat	Madinat
Madinat Hamad	Madinat Ha
Mintaqat Juzur Hawar	Mintaqat J
Ar Rifa	Ar Rifa
Al Hadd	Al Hadd

Bangladesh

State	Code
Dhaka	Dhaka
Khulna	Khulna
Rājshāhi	Rajshahi
Chattogram	Chittagong
Sylhet	Sylhet
Barisāl	Barisal
Rangpur	GI
Mymensingh	MY

Brazil

State	Code
Acre	BR-AC
Alagoas	BR-AL
Amapá	BR-AP
Amazonas	BR-AM

Bahia	BR-BA
Ceará	BR-CE
Distrito Federal	BR-DF
Espírito Santo	BR-ES
Goiás	BR-GO
Maranhão	BR-MA
Mato Grosso	BR-MT
Mato Grosso do Sul	BR-MS
Minas Gerais	BR-MG
Pará	BR-PA
Paraíba	BR-PB
Paraná	BR-PR
Pernambuco	BR-PE
Piauí	BR-PI
Rio de Janeiro	BR-RJ
Rio Grande do Norte	BR-RN
Rio Grande do Sul	BR-RS
Rondônia	BR-RO
Roraima	BR-RR
Santa Catarina	BR-SC
São Paulo	BR-SP
Sergipe	BR-SE
Tocantins	BR-TO

Canada

State	Code
Alberta	CA-AB

British Columbia	CA-BC
Manitoba	CA-MB
New Brunswick	CA-NB
Newfoundland and Labrador	CA-NL
Nova Scotia	CA-NS
Northwest Territory	CA-NT
Nunavut Territory	CA-NU
Ontario	CA-ON
Prince Edward Island	CA-PE
Quebec	CA-QC
Saskatchewan	CA-SK
Yukon	CA-YT

Chile

State	Code
Aisén del General Carlos Ibañez del Campo	CL-AI
Antofagasta	CL-AN
Arica y Parinacota	CL-AP
Atacama	CL-AT
Biobío	CL-BI
Coquimbo	CL-CO
La Araucanía	CL-AR
Libertador General Bernardo O'Higgins	CL-LI
Los Lagos	CL-LL
Los Ríos	CL-LR
Magallanes	CL-MA
Maule	CL-ML
Ñuble	CL-NB

Región Metropolitana de Santiago	CL-RM
Tarapacá	CL-TA
Valparaíso	CL-VS

Colombia

State	Code
Cundinamarca	Cundinamar
Antioquia	Antioquia
Valle del Cauca	Valle del Cauca
Atlántico	Atlántico
Bolivar Department	Bolivar De
Santander	Santander
Norte de Santander	Norte de S
Magdalena Department	Magdalena
Tolima	Tolima
Nariño	Nariño
Risaralda	Risaralda
Caldas Department	Caldas Dep
Boyaca Department	Boyaca Dep
Cesar	Cesar
Córdoba	Córdoba
Huila	Huila
Sucre	Sucre
Quindío	Quindío
Meta	Meta
La Guajira	La Guajira
Cauca	Cauca
Caquetá	Caquetá

Chocó	Chocó
Casanare	Casanare
Arauca	Arauca
Putumayo	Putumayo
San Andres y Providencia	San Andres
Guaviare	Guaviare
Amazonas	Amazonas
Guainía	Guainía
Vaupés	Vaupés
Vichada	Vichada
Caldas	Caldas
Magdalena	Magdalena
Bolívar	Bolívar
Boyacá	Boyacá
Distrito Especial	Distrito E

Costa Rica

State	Code
Alajuela	CR-A
Cartago	CR-C
Guanacaste	CR-G
Heredia	CR-H
Limón	CR-L
Puntarenas	CR-P
San José	CR-SJ

Curacao

State	Code
Curacao	CURACAO

Dominican Republic

State	Code
Azua	AZ
Bahoruco	BR
Barahona	BH
Dajabón	DA
Distrito Nacional	NC
Duarte	DU
Elías Piña	EP
El Seibo	SE
Espaillat	ES
Hato Mayor	HM
Hermanas Mirabal	SC
Independencia	IN
La Altagracia	AL
La Romana	RO
La Vega	VE
María Trinidad Sánchez	MT
Monseñor Nouel	MN
Monte Cristi	MC
Monte Plata	MP
Pedernales	PN
Peravia	PV
Puerto Plata	PP
Samaná	SM

Sánchez Ramírez	SZ
San Cristóbal	CR
San José de Ocoa	JO
San Juan	JU
San Pedro de Macorís	PM
Santiago	ST
Santiago Rodríguez	SR
Santo Domingo	SD
Valverde	VA

Ecuador

State	Code
Azuay	EC-A
Bolívar	EC-B
Cañar	EC-F
Carchi	EC-C
Chimborazo	EC-H
Cotopaxi	EC-X
El Oro	EC-O
Esmeraldas	EC-E
Galápagos	EC-W
Guayas	EC-G
Imbabura	EC-I
Loja	EC-L
Los Ríos	EC-R
Manabí	EC-M
Morona Santiago	EC-S
Napo	EC-N

Orellana	EC-D
Pastaza	EC-Y
Pichincha	EC-P
Santa Elena	EC-SE
Santo Domingo de los Tsáchilas	EC-SD
Sucumbíos	EC-U
Tungurahua	EC-T
Zamora Chinchipe	EC-Z

Egypt

State	Code
Ad Daqahliyah	EG-DK
Al Bahr al Ahmar	EG-BA
Al Buhayrah	EG-BH
Al Fayyum	EG-FYM
Al Gharbiyah	EG-GH
Al Iskandariyah	EG-ALX
Al Isma'iliyah	EG-IS
Al Jizah	EG-GZ
Al Minufiyah	EG-MNF
Al Minya	EG-MN
Al Qahirah	EG-C
Al Qalyubiyah	EG-KB
Al Uqsur	EG-LX
Al Wadi al Jadid	EG-WAD
As Suways	EG-SUZ
Ash Sharqiyah	EG-SHR

Aswan	EG-ASN
Asyut	EG-AST
Bani Suwayf	EG-BNS
Bur Sa'id	EG-PTS
Dumyat	EG-DT
Janub Sina	EG-JS
Kafr ash Shaykh	EG-KFS
Matruh	EG-MT
Qina	EG-KN
Shamal Sina	EG-SIN
Suhaj	EG-SHG

El Salvador

State	Code
Ahuachapan	SV-AH
Cabanas	SV-CA
Chalatenango	SV-CH
Cuscatlan	SV-CU
La Libertad	SV-LI
La Paz	SV-PA
La Union	SV-UN
Morazan	SV-MO
San Miguel	SV-SM
San Salvador	SV-SS
San Vicente	SV-SV
Santa Ana	SV-SA
Sonsonate	SV-SO
Usulutan	SV-US

France

State	Code
Île-de-Fra	Île-de-France
Bretagne	Bretagne
Rhône-Alpe	Rhône-Alpes
Provence-A	Provence-Alpes-Cote-dAzur
Nord-Pas-d	Nord-Pas-de-Calais
Pays-de-la	Pays-de-la-Loire
Aquitaine	Aquitaine
Midi-Pyrén	Midi-Pyrénées
Languedoc-	Languedoc-Roussillon
Centre	Centre
Lorraine	Lorraine
Picardie	Picardie
Alsace	Alsace
Haute-Norm	Haute-Normandie
Poitou-Cha	Poitou-Charentes
Bourgogne	Bourgogne
Basse-Norm	Basse-Normandie
Champagne-	Champagne-Ardenne
Auvergne	Auvergne
Franche-Co	Franche-Comté
Corse	Corse
Limousin	Limousin
Fort-de-Fr	Fort-de-France
Haut-Ogoou	Haut-Ogooue
Goa	Goa
Ontario	Ontario

Grand Port	Grand Port
Piemonte	Piemonte
New Hampsh	New Hampshire
Indiana	Indiana
Sector cla	Sector claimed by France

Guatemala

State	Code
Alta Verapaz	GT-AV
Baja Verapaz	GT-BV
Chimaltenango	GT-CM
Chiquimula	GT-CQ
El Progreso	GT-PR
Escuintla	GT-ES
Guatemala	GT-GU
Huehuetenango	GT-HU
Izabal	GT-IZ
Jalapa	GT-JA
Jutiapa	GT-JU
Peten	GT-PE
Quetzaltenango	GT-QZ
Quiche	GT-QC
Retalhuleu	GT-RE
Sacatepequez	GT-SA
San Marcos	GT-SM
Santa Rosa	GT-SR
Solola	GT-SO
Suchitepequez	GT-SU

Totonicapan	GT-TO
Zacapa	GT-ZA

Honduras

State	Code
Atlantida	HN-AT
Choluteca	HN-CH
Colon	HN-CL
Comayagua	HN-CM
Copan	HN-CP
Cortes	HN-CR
El Paraiso	HN-EP
Francisco Morazan	HN-FM
Gracias A Dios	HN-GD
Intibuca	HN-IN
Islas de la Bahia	HN-IB
La Paz	HN-LP
Lempira	HN-LE
Ocotepeque	HN-OC
Olancho	HN-OL
Santa Barbara	HN-SB
Valle	HN-VA
Yoro	HN-YO

India

State	Code

Delhi	DL
Andhra Pradesh	AP
Goa	GA
Jharkhand	JH
Manipur	MN
Punjab	PB
Uttar Pradesh	UP
Arunachal Pradesh	AR
Gujarat	GJ
Karnataka	KA
Meghalaya	ML
Rajasthan	RJ
Uttaranchal	UT
Assam	AS
Haryana	HR
Kerala	KL
Mizoram	MZ
Sikkim	SK
West Bengal	WB
Bihar	BR
Himachal Pradesh	HP
Madhya Pradesh	MP
Nagaland	NL
Tamil Nadu	TN
Chhattisgarh	CH
Jammu and Kashmir	JK
Maharashtra	MH
Odisha	OR
Tripura	TR

Telangana	TG
Andaman and Nicobar Islands	AN
Chandigarh	CD
Dadra and Nagar Haveli	DN
Daman and Diu	DD
Lakshadweep	LD
Puducherry	PC
Uttarakhand	UK
Ladakh	LA

Indonesia

State	Code
Jawa Barat	JB
Jakarta Raya	JK
Jawa Timur	JI
Jawa Tengah	JT
Sumatera Utara	SU
Yogyakarta	YO
Kalimantan Timur	KI
Sumatera Barat	SB
Banten	BT
Lampung	LA
Kalimantan Selatan	KS
Sulawesi Utara	SA
Bali	BA
Kalimantan Barat	KB
Jambi	JA
Nusa Tenggara Timur	NT

Nusa Tenggara Barat	NB
Aceh	AC
Sulawesi Tengah	ST
Bengkulu	BE
Sulawesi Tenggara	SG
Kalimantan Tengah	KT
Papua	PA
Riau	RI
Sulawesi Barat	SR
Maluku	MA
Irian Jaya Barat	PB
Sumatera Selatan	SS
Gorontalo	GO
Sulawesi Selatan	SN
Maluku Utara	MU
Kepulauan Riau	KR
Kepulauan Bangka Belitung	BB
Kalimantan Utara	KU
Papua Barat	PB

Japan

State	Code
Aichi	Aichi
Aiti	JP-23
Akita	JP-05
Aomori	JP-02
Chiba	Chiba
Ehime	JP-38

Fukuoka	Fukuoka
Fukushima	Fukushima
Fukui	Fukui
Gifu	JP-21
Gunma	JP-10
Hiroshima	JP-34
Hokkaido	JP-01
Hukui	JP-18
Hukuoka	JP-40
Hukusima	JP-07
Hyogo	JP-28
Ibaraki	JP-08
Ishikawa	JP-17
Iwate	JP-03
Kagawa	JP-37
Kagoshima	JP-46
Kanagawa	JP-14
Kōchi	Kōchi
Kumamoto	JP-43
Kyoto	JP-26
Kôti	JP-39
Mie	JP-24
Miyagi	JP-04
Miyazaki	JP-45
Nagano	JP-20
Nagasaki	JP-42
Nara	JP-29
Niigata	JP-15
Oita	JP-44

Okayama	JP-33
Okinawa	JP-47
Saga	JP-41
Saitama	JP-11
Siga	JP-25
Simane	JP-32
Sizuoka	JP-22
Tiba	JP-12
Tochigi	JP-09
Tokushima	JP-36
Tokyo	JP-13
Totigi	JP-09
Tottori	JP-31
Toyama	JP-16
Tôkyô	JP-13
Wakayama	JP-30
Yamagata	JP-06
Yamaguchi	JP-35
Yamanashi	JP-19
Ôita	JP-44
Ôsaka	JP-27

Kuwait

State	Code
Al Ahmadi	AH
Al Farwaniyah	FA
Al Jahra	JA
Al Kuwayt	KU

Auckland	AUK
Bay of Plenty	BOP
Canterbury	CAN
Chatham Islands	CIT
Gisborne	GIS
Hawalli	HA
Hawke.s Bay	HKB
Manawatu-Wanganui	MWT
Marlborough	MBH
Mubarak al Kabir	MU
Nelson	NSN
Northland	NTL
Otago	OTA
Southland	STL
Taranaki	TKI
Tasman	TAS
Waikato	WKO
Wellington	WGN
West Coast	WTC

Malaysia

State	Code
Johor	JHR
Kedah	KDH
Kelantan	KTN
Kuala Lumpur	KUL
Labuan	LBN
Melaka	MLK

Negeri Sembilan	NSN
Pahang	PHG
Perak	PRK
Perlis	PLS
Pulau Pinang	PNG
Putrajaya	PJY
Sabah	SBH
Sarawak	SWK
Selangor	SGR
Terengganu	TRG

Mexico

State	Code
Aguascalientes	AGU
Baja California	BCN
Baja California Sur	BCS
Campeche	CAM
Colima	CHH
Coahuila De Zaragoza	CHP
Chiapas	COA
Chihuahua	COL
Distrito Federal	DIF
Durango	DUR
Guerrero	GRO
Guanajuato	GUA
Hidalgo	HID
Jalisco	JAL
Mexico	MEX

Michoacan De Ocampo	MIC
Morelos	MOR
Nayarit	NAY
Nuevo Leon	NLE
Oaxaca	OAX
Puebla	PUE
Queretaro De Arteaga	QUE
Quintana Roo	ROO
Sinaloa	SIN
San Luis Potosi	SLP
Sonora	SON
Tabasco	TAB
Tamaulipas	TAM
Tlaxcala	TLA
Veracruz Llave	VER
Yucatan	YUC
Zacatecas	ZAC

Myanmar

State	Code
Mandalay	MA
Irrawaddy	IR
Mon State	MS
Sagaing	SG
Shan State	SS
Pegu	PG
Rakhine State	RS
Kachin State	KCS

Magway	MG
Kayah State	KYS
Chin State	CS
Karan State	KRS
Rangoon	RN
Yangon	YA
Tanintharyi	TA
Kayin	KA
Bago	BA

Nepal

State	Code
Janakpur	JA
Bheri	BH
Dhawalagiri	DH
Gandaki	GA
Karnali	KA
Kosi	KO
Lumbini	LU
Mahakali	MA
Mechi	ME
Narayani	NA
Rapti	RA
Sagarmatha	SA
Bagmati	BA
Seti	SE

Pakistan

State	Code
Punjab	PB
Sindh	SD
North-West Frontier	KP
Balochistan	BA
Northern Areas	GB
Azad Kashmir	JK
Federally Administered Tribal Areas	TA
Islamabad	IS
Khyber Pakhtunkhwa	KP
Gilgit-Baltistan	GB

Panama

State	Code
Bocas del Toro	PA-1
Chiriquí	PA-4
Coclé	PA-2
Colón	PA-3
Darién	PA-5
Emberá	PA-EM
Guna Yala (local variant is Kuna Yala)	PA-KY
Herrera	PA-6
Los Santos	PA-7
Naso Tjër Di	PA-NT
Ngöbe-Buglé	PA-NB
Panamá	PA-8

Panamá Oeste	PA-10
Veraguas	PA-9

Peru

State	Code
Municipalidad Metropolitana de Lima	PE-LMA
Amazonas	PE-AMA
Ancash	PE-ANC
Apurímac	PE-APU
Arequipa	PE-ARE
Ayacucho	PE-AYA
Cajamarca	PE-CAJ
Cusco (local variant is Cuzco)	PE-CUS
El Callao	PE-CAL
Huancavelica	PE-HUV
Huánuco	PE-HUC
Ica	PE-ICA
Junín	PE-JUN
La Libertad	PE-LAL
Lambayeque	PE-LAM
Lima	PE-LIM
Loreto	PE-LOR
Madre de Dios	PE-MDD
Moquegua	PE-MOQ
Pasco	PE-PAS
Piura	PE-PIU
Puno	PE-PUN
San Martín	PE-SAM

Tacna	PE-TAC
Tumbes	PE-TUM
Ucayali	PE-UCA

Philippines

State	Code
Isabela	PH-ISA
Abra	ABR
Agusan del Norte	AGN
Agusan del Sur	AGS
Aklan	AKL
Albay	ALB
Antique	ANT
Apayao	APA
Aurora	AUR
Basilan	BAS
Bataan	BAN
Batanes	BTN
Batangas	BTG
Benguet	BEN
Biliran	BIL
Bohol	BOH
Bukidnon	BUK
Bulacan	BUL
Cagayan	CAG
Camarines Norte	CAN
Camarines Sur	CAS
Camiguin	CAM

Capiz	CAP
Catanduanes	CAT
Cavite	CAV
Cebu	CEB
Compostela Valley	COM
Cotabato	NCO
Davao del Norte	DAV
Davao del Sur	DAS
Davao Occidental	DVO
Davao Oriental	DAO
Dinagat Islands	DIN
Eastern Samar	EAS
Guimaras	GUI
Ifugao	IFU
Ilocos Norte	ILN
Ilocos Sur	ILS
Iloilo	ILI
Kalinga	KAL
Laguna	LAG
Lanao del Norte	LAN
Lanao del Sur	LAS
La Union	LUN
Leyte	LEY
Maguindanao	MAG
Marinduque	MAD
Masbate	MAS
Metropolitan Manila	MNL
Misamis Occidental	MSC
Misamis Oriental	MSR

Mountain	MOU
Negros Occidental	NEC
Negros Oriental	NER
Northern Samar	NSA
Nueva Ecija	NUE
Nueva Vizcaya	NUV
Occidental Mindoro	MDC
Oriental Mindoro	MDR
Palawan	PLW
Pampanga	PAM
Pangasinan	PAN
Quezon	QUE
Quirino	QUI
Rizal	RIZ
Romblon	ROM
Samar	WSA
Sarangani	SAR
Siquijor	SIG
Sorsogon	SOR
South Cotabato	SCO
Southern Leyte	SLE
Sultan Kudarat	SUK
Sulu	SLU
Surigao del Norte	SUN
Surigao del Sur	SUR
Tarlac	TAR
Tawi-Tawi	TAW
Zambales	ZMB
Zamboanga del Norte	ZAN

Zamboanga del Sur	ZAS
Zamboanga-Sibugay	ZSI
Davao City	Davao City
Cebu City	Cebu City
Davao	Davao
Zamboanga	Zamboanga
General Santos	General Sa
Iloilo City	Iloilo Cit
Iligan	Iligan
Mandaue	Mandaue
Lipa	Lipa
North Cotabato	North Cota
Mindoro Oriental	Mindoro Or
Lapu-Lapu	Lapu-Lapu
Lucena	Lucena
Mindoro Occidental	Mindoro Oc
San Pablo	San Pablo
Olongapo	Olongapo
Legaspi	Legaspi
Tacloban	Tacloban
Toledo	Toledo
Puerto Princesa	Puerto Pri
Naga	Naga
Marawi	Marawi
Ormoc	Ormoc
San Carlos	San Carlos
Roxas	Roxas
Cavite City	Cavite Cit
Dumaguete	Dumaguete

Silay	Silay
Ozamis	Ozamis
Laoag	Laoag
Dipolog	Dipolog
Iriga	Iriga
Surigao	Surigao
Tagbilaran	Tagbilaran
Danao	Danao
Tawitawi	Tawitawi
Gingoog	Gingoog
Kalinga-Apayao	Kalinga-Ap
Dapitan	Dapitan
Tagaytay	Tagaytay
Oroquieta	Oroquieta
La Carlota	La Carlota
Tangub	Tangub
Palayan	Palayan
Pagadian	Pagadian
Trece Martires	Trece Mart
Quezon City	Quezon Cit
Pasay	Pasay
Dagupan	Dagupan
Western Samar	PH-WSA
Kalookan	PH-CAC
Las Pinas	PH-PNS
Makati	PH-MTI
Malabon	PH-MBL
Mandaluyong	PH-MDL
Marikina	PH-MAR

Muntinlupa	PH-MNT
Navotas	PH-NAV
Paranaque	PH-PPA
Pasig	PH-PSG
Pateros	PH-PAT
San Juan	PH-NJU
Taguig	PH -TUI
Valenzuela	PH-VZA

Saudi Arabia

State	Code
Ha'il	Ha'il
Qassim	Qassim
Riyadh Province	Riyadh
Tabuk Province	Tabuk
Madinah	Madinah
Makkah Province	Makkah
Bahah	Bahah
Northern Borders Province	Northern B
Jawf	Jawf
Jizan	Jizan
Aseer Province	Asir
Najran	Najran
Eastern Province	Eastern Pr
Al Bahah Province	BA
Al Ḥudūd ash Shamāliyah	HS
Al Jowf	JA
Al Madinah Province	MD

Al Qassim	QS
Ar Riyāḍ	RI
Ash Sharqīyah	SH
Ḥā.il	HA
Al Qurayyat	Al Qurayya
Hail Province	Hail

Sri Lanka

State	Code
Southern	SO
North Central	NC
Uva	UV
Sabaragamuwa	SB
North Western	NW
Jaffna	JF
Kalutara	KL
Kandy	KA
Kegalla	Kegalla
Kurunegala	KU
Mannar	MN
Matale	MT
Amparai	AM,
Moneragala	MO
Mullaittivu	MU
Nuwara Eliya	NE
Polonnaruwa	PO
Puttalam	PU
Ratnapura	RA

Trincomalee	TR
Vavuniya	VA
Matara	MA
Anuradhapura	AN
Badulla	BD
Batticaloa	BT
Colombo	CO
Galle	GL
Gampaha	GM
Hambantota	HA
Western	WE
Northern	NO
Eastern	EA
Central	CE

Taiwan

State	Code
Changhua	TW-CHA
Chiayi	TW-CYI
Chiayi	TW-CYQ
Hsinchu	TW-HSZ
Hsinchu	TW-HSQ
Hualien	TW-HUA
Kaohsiung	TW-KHH
Keelung	TW-KEE
Kinmen	TW-KIN
Lienchiang	TW-LIE
Miaoli	TW-MIA

Nantou	TW-NAN
New Taipei	TW-NWT
Penghu	TW-PEN
Pingtung	TW-PIF
Taichung	TW-TXG
Tainan	TW-TNN
Taipei	TW-TPE
Taitung	TW-TTT
Taoyuan	TW-TAO
Yilan	TW-ILA
Yunlin	TW-YUN

Tanzania

State	Code
Dar es salaam Tz	Dar es sal
Arusha Tz	Arusha Tz
Mbeya Tz	Mbeya Tz
Mtwara Tz	Mtwara Tz
Dodoma Tz	Dodoma Tz
Other States Tz	Other Stat
Arusha	Arusha
Dar es Salaam	Dar es Sal
Dodoma	Dodoma
Geita	Geita
Iringa	Iringa
Kagera	Kagera
Katavi	Katavi
Kigoma	Kigoma

Kilimanjaro	Kilimanjar
Lindi	Lindi
Manyara	Manyara
Mara	Mara
Mbeya	Mbeya
Morogoro	Morogoro
Mtwara	Mtwara
Mwanza	Mwanza
Njombe	Njombe
Pemba North	Pemba Nort
Pemba South	Pemba Sout
Pwani	Pwani
Rukwa	Rukwa
Ruvuma	Ruvuma
Shinyanga	Shinyanga
Simiyu	Simiyu
Singida	Singida
Tabora	Tabora
Tanga	Tanga
Zanzibar North	Zanzibar N
Zanzibar South and Central	Zanzibar S
Zanzibar West	Zanzibar W

Thailand

State	Code
Amnat Charoen	TH-37
Ang Thong	TH-15

Bangkok	TH-10
Bueng Kan	TH-38
Buriram	TH-31
Chachoengsao	TH-24
Chai Nat	TH-18
Chaiyaphum	TH-36
Chanthaburi	TH-22
Chiang Mai	TH-50
Chiang Rai	TH-57
Chonburi	TH-20
Chumphon	TH-86
Kalasin	TH-46
Kalimantan Utara	KU
Kamphaeng Phet	TH-62
Kanchanaburi	TH-71
Khon Kaen	TH-40
Krabi	TH-81
Krung Thep Maha Nakhon	TH-10
Krung Thep	BKK
Lampang	TH-52
Lamphun	TH-51
Loei	TH-42
Lopburi	TH-16
Mae Hong Son	TH-58
Maha Sarakham	TH-44
Mukdahan	TH-49
Nakhon Nayok	TH-26
Nakhon Pathom	TH-73
Nakhon Phanom	TH-48

Nakhon Ratchasima	TH-30
Nakhon Sawan	TH-60
Nakhon Si Thammarat	TH-80
Nan	TH-55
Narathiwat	TH-96
Nong Bua Lam Phu	TH-39
Nong Bua Lamphu	NBP
Nong Khai	TH-43
Nonthaburi	TH-12
Papua Barat	PB
Pathum Thani	TH-13
Pattani	TH-94
Phangnga	TH-82
Phatthalung	TH-93
Phatthaya	TH-S
Phayao	TH-56
Phetchabun	TH-67
Phetchaburi	TH-76
Phichit	TH-66
Phitsanulok	TH-65
Phra Nakhon Si Ayutthaya	TH-14
Phrae	TH-54
Phuket	TH-83
Prachinburi	TH-25
Prachuap Khiri Khan	TH-77
Ranong	TH-85
Ratchaburi	TH-70
Rayong	TH-21
Roi Et	TH-45

Sa Kaeo	TH-27
Sakon Nakhon	TH-47
Samut Prakan	TH-11
Samut Sakhon	TH-74
Samut Songkhram	TH-75
Saraburi	TH-19
Satun	TH-91
Sisaket	TH-33
Sing Buri	TH-17
Songkhla	TH-90
Sukhothai	TH-64
Suphan Buri	TH-72
Surat Thani	TH-84
Surin	TH-32
Tak	TH-63
Trang	TH-92
Trat	TH-23
Ubon Ratchathani	TH-34
Udon Thani	TH-41
Uthai Thani	TH-61
Uttaradit	TH-53
Yala	TH-95
Yasothon	TH-35

Trinidad and Tobago

State	Code
Arima	TT-ARI
Chaguanas	TT-CHA

Couva-Tabaquite-Talparo	TT-CTT
Diego Martin	TT-DMN
Mayaro-Rio Claro	TT-MRC
Penal-Debe	TT-PED
Port of Spain	TT-POS
Princes Town	TT-PRT
Point Fortin	TT-PTF
San Fernando	TT-SFO
Sangre Grande	TT-SGE
Siparia	TT-SIP
San Juan-Laventille	TT-SJL
Tobago	TT-TOB
Tunapuna-Piarco	TT-TUP

United Arab Emirates

State	Code
Abu Dhabi	AZ
Dubai	DU
Sharjah	SH
Ajman	AJ
Umm Al Quwain	UQ
Ras Al Khaimah	RK
Fujairah	FU

United Kingdom

LONDON (SOUTH)

Boroughs/Province	Code
Pimlico, St james	SW1
Brixton	SW2
Chelsea	SW3
Clapham	SW4
Earls Court	SW5
Fulham	SW6
Kensington	SW7
Knightsbridge	SW8
Oval, Stockwell	SW9
Brompton	SW10
Battersea	SW11
Balham	SW12
Barnes	SW13
Sheen	SW14
Putney	SW15
Streatham	SW16
Tooting	SW17
Wandsworth, Earlsfield , Southfields	SW18
Wimbledon, Colliers wood	SW19
Raynes Park	SW20
South Bank	SE1
Abbey Wood	SE2
Blackheath	SE3
Brockley	SE4
Camberwell	SE5
Catford	SE6
Charlton	SE7
Deptford	SE8

Eltham	SE9
Greenwich	SE10
Kennington	SE11
Lee	SE12
Lewisham	SE13
New Cross	SE14
Peckham	SE15
Rotherhithe	SE16
Walworth	SE17
Woolwich	SE18
Norwood	SE19
Anerley	SE20
Dulwich	SE21
East Dulwich	SE22
Forest Hill	SE23
Herne Hill	SE24
South Norwood	SE25
Sydenham	SE26
West Norwood	SE27
Thamesmead	SE28
Twickenham	TW1
Twickenham	TW2
Hounslow	TW3
Hounslow	TW4
Heston	TW5
Heathrow	TW6
Isleworth	TW7
Brentford	TW8
Kew	TW9

Richmond	TW10

United States

State	Code
Alabama	AL
Alaska	AK
Arizona	AZ
Arkansas	AR
California	CA
Colorado	CO
Connecticut	CT
Delaware	DE
District of Columbia	DC
Florida	FL
Georgia	GA
Hawaii	HI
Idaho	ID
Illinois	IL
Indiana	IN
Iowa	IA
Kansas	KS
Kentucky	KY
Louisiana	LA
Maine	ME
Maryland	MD
Massachusetts	MA
Michigan	MI
Minnesota	MN

Mississippi	MS
Missouri	MO
Montana	MT
Nebraska	NE
Nevada	NV
New Hampshire	NH
New Jersey	NJ
New Mexico	NM
New York	NY
North Carolina	NC
North Dakota	ND
Ohio	OH
Oklahoma	OK
Oregon	OR
Pennsylvania	PA
Rhode Island	RI
South Carolina	SC
South Dakota	SD
Tennessee	TN
Texas	TX
Utah	UT
Vermont	VT
Virginia	VA
Washington	WA
West Virginia	WV
Wisconsin	WI
Wyoming	WY

Uruguay

State	Code
Artigas	UY-AR
Canelones	UY-CA
Cerro Largo	UY-CL
Colonia	UY-CO
Durazno	UY-DU
Flores	UY-FS
Florida	UY-FD
Lavalleja	UY-LA
Maldonado	UY-MA
Montevideo	UY-MO
Paysandú	UY-PA
Río Negro	UY-RN
Rivera	UY-RV
Rocha	UY-RO
Salto	UY-SA
San José	UY-SJ
Soriano	UY-SO
Tacuarembó	UY-TA
Treinta y Tres	UY-TT

Venezuela

State	Code
Amazonas	VE-Z
Anzoátegui	VE-B
Apure	VE-C

Aragua	VE-D
Barinas	VE-E
Bolívar	VE-F
Carabobo	VE-G
Cojedes	VE-H
Delta Amacuro	VE-Y
Dependencias Federales	VE-W
Distrito Capital	VE-A
Falcón	VE-I
Guárico	VE-J
La Guaira	VE-X
Lara	VE-K
Mérida	VE-L
Miranda	VE-M
Monagas	VE-N
Nueva Esparta	VE-O
Portuguesa	VE-P
Sucre	VE-R
Táchira	VE-S
Trujillo	VE-T
Yaracuy	VE-U
Zulia	VE-V

Virgin Islands (U.S.)

State	Code
St. Croix	St. Croix
St. Thomas	St. Thomas

Timezone Codes

When creating entities in LogiNext that require timezone-specific information associated with them, use the timezone codes listed below. For example, if you want to create an order that needs to be picked up from a pickup location in New York, you should pass the code 'America/New_York' in the 'pickupAddressTimezone' parameter of the Create Order API.

If you wish to use the code for a timezone not listed below, reach out to your Account Manager or write to us at: support@loginextsolutions.com

Country Name	Timezone	DST (Daylight Saving Time)	Canonical ID
AFGHANISTAN	(GMT+04:30) Afghanistan		Asia/Kabul
ALAND ISLANDS	(GMT-04:00) ALAND ISLANDS		Europe/Helsinki
ALAND ISLANDS	(GMT-04:00) ALAND ISLANDS		Europe/Mariehamn
ALBANIA	(GMT+01:00) Albania	ALBANIA(GMT+02:00)	Europe/Tirane
ALGERIA	(GMT+01:00) Algeria		Africa/Algiers
AMERICAN SAMOA	(GMT-11:00) American Samoa		Pacific/Pago_Pago
ANDORRA	(GMT+01:00) Andorra	ANDORRA(GMT+02:00)	Europe/Andorra
ANGOLA	(GMT+01:00) Angola		Africa/Luanda
ANGOLA	(GMT+01:00) Angola		Africa/Lagos
ANGUILLA	(GMT-04:00) Anguilla		America/Anguilla
ANGUILLA	(GMT-04:00) Anguilla		America/Port_of_Spain
ANTARCTICA	(GMT-03:00) Antarctica		Antarctica/Palmer
ANTARCTICA	(GMT+08:00) Antarctica		Antarctica/Casey
ANTARCTICA	(GMT+07:00) Antarctica		Antarctica/Davis
ANTARCTICA	(GMT+10:00) Antarctica		Antarctica/DumontDUrville
ANTARCTICA	(GMT+05:00) Antarctica		Antarctica/Mawson
ANTARCTICA	(GMT+13:00) Antarctica		Antarctica/McMurdo
ANTARCTICA	(GMT-03:00) Antarctica		Antarctica/Rothera
ANTARCTICA	(GMT+03:00) Antarctica		Antarctica/Syowa
ANTARCTICA	(GMT+00:00) Antarctica		Antarctica/Troll
ANTARCTICA	(GMT+06:00) Antarctica		Antarctica/Vostok
ANTARCTICA	(GMT+13:00) Antarctica		Pacific/Auckland

ANTIGUA AND BARBUDA	(GMT-04:00) Antigua And Barbuda		America/Antigua
ANTIGUA AND BARBUDA	(GMT-04:00) Antigua And Barbuda		America/Port_of_Spain
ARGENTINA	(GMT-03:00) Argentina		America/Argentina/Buenos_Aires
ARGENTINA	(GMT-03:00) Argentina		America/Argentina/Catamarca
ARGENTINA	(GMT-03:00) Argentina		America/Argentina/Cordoba
ARGENTINA	(GMT-03:00) Argentina		America/Argentina/Jujuy
ARGENTINA	(GMT-03:00) Argentina		America/Argentina/La_Rioja
ARGENTINA	(GMT-03:00) Argentina		America/Argentina/Mendoza
ARGENTINA	(GMT-03:00) Argentina		America/Argentina/Rio_Gallegos
ARGENTINA	(GMT-03:00) Argentina		America/Argentina/Salta
ARGENTINA	(GMT-03:00) Argentina		America/Argentina/San_Juan
ARGENTINA	(GMT-03:00) Argentina		America/Argentina/San_Luis
ARGENTINA	(GMT-03:00) Argentina		America/Argentina/Tucuman
ARGENTINA	(GMT-03:00) Argentina		America/Argentina/Ushuaia
ARMENIA	(GMT-04:00) Armenia		Asia/Yerevan
ARUBA	(GMT-04:00) Aruba		America/Aruba
ARUBA	(GMT-04:00) Aruba		America/Curacao
AUSTRALIA	(GMT+08:00) Western Australia	-	Australia/Perth
AUSTRALIA	(GMT+10:30) Lord Howe Island	Lord Howe Island(GMT+11:00)	Australia/Lord_Howe
AUSTRALIA	(GMT+11:00) Macquarie Island		Antarctica/Macquarie
AUSTRALIA	(GMT+09:30) South Australia	South Australia(GMT+10:30)	Australia/Adelaide
AUSTRALIA	(GMT+09:30) Northern Territory		Australia/Darwin
AUSTRALIA	(GMT+10:00) Tasmania	Tasmania(GMT+11:00)	Australia/Hobart
AUSTRALIA	(GMT+10:00) Victoria	Victoria(GMT+11:00)	Australia/Melbourne
AUSTRALIA	(GMT+10:00) Australian Capital Territory	Australian Capital Territory(GMT+11:00)	Australia/Sydney
AUSTRALIA	(GMT+10:00) Queensland		Australia/Brisbane
AUSTRALIA	(GMT+10:00) Lindeman		Australia/Lindeman
AUSTRALIA	(GMT+08:45) Eucla		Australia/Eucla

AUSTRIA	(GMT+01:00) Austria	AUSTRIA(GMT+02:00)	Europe/Vienna
AZERBAIJAN	(GMT+04:00) Azerbaijan		Asia/Baku
BAHAMAS	(GMT-05:00) Bahamas	BAHAMAS(GMT-04:00)	America/Nassau
BAHAMAS.THE	(GMT-05:00) Bahamas.The	BAHAMAS.THE(GMT-04:00)	America/Nassau
BAHRAIN	(GMT+03:00) Bahrain		Asia/Bahrain
BAHRAIN	(GMT+03:00) Bahrain		Asia/Qatar
BANGLADESH	(GMT+06:00) Bangladesh		Asia/Dhaka
BARBADOS	(GMT-04:00) Barbados		America/Barbados
BELARUS	(GMT+03:00) Belarus		Europe/Minsk
BELGIUM	(GMT+01:00) Belgium	BELGIUM(GMT+02:00)	Europe/Brussels
BELIZE	(GMT-06:00) Belize		America/Belize
BENIN	(GMT+01:00) Benin		Africa/Porto-Novo
BENIN	(GMT+01:00) Benin		Africa/Lagos
BERMUDA	(GMT-04:00) Bermuda	BERMUDA(GMT-03:00)	Atlantic/Bermuda
BHUTAN	(GMT+06:00) Bhutan		Asia/Thimphu
BOLIVIA	(GMT-04:00) Bolivia		America/La_Paz
BOSNIA AND HERZEGOVINA	(GMT+01:00) Bosnia And Herzegovina		Europe/Sarajevo
BOSNIA AND HERZEGOWINA	(GMT+01:00) Bosnia And Herzegowina	BOSNIA AND HERZEGOWINA(GMT+02:	Europe/Sarajevo
BOSNIA AND HERZEGOWINA	(GMT+01:00) Bosnia And Herzegowina		Europe/Belgrade
BOTSWANA	(GMT+02:00) Botswana		Africa/Gaborone
BOTSWANA	(GMT-03:30) Newfoundland		Canada/Newfoundland
BOTSWANA	(GMT-04:00) Atlantic		Canada/Atlantic
BOTSWANA	(GMT-05:00) Eastern		Canada/Eastern
BOTSWANA	(GMT-06:00) Central		Canada/Central
BOTSWANA	(GMT-07:00) Mountain		Canada/Mountain
BOTSWANA	(GMT-08:00) Pacific		Canada/Pacific
BOUVET ISLAND	(GMT-05:00) Bouvet Island		Etc/GMT+5
BRAZIL	(GMT-03:00) Brasilia Standard Time		America/Sao_Paulo

BRAZIL	(GMT-03:00) Brazil		America/Araguaina
BRAZIL	(GMT-03:00) Brazil		America/Bahia
BRAZIL	(GMT-03:00) Brazil		America/Belem
BRAZIL	(GMT-04:00) Brazil		America/Boa_Vista
BRAZIL	(GMT-04:00) Brazil		America/Campo_Grande
BRAZIL	(GMT-04:00) Brazil		America/Cuiaba
BRAZIL	(GMT-05:00) Brazil		America/Eirunepe
BRAZIL	(GMT-03:00) Brazil		America/Fortaleza
BRAZIL	(GMT-04:00) Brazil		America/Maceio
BRAZIL	(GMT-04:00) Brazil		America/Manaus
BRAZIL	(GMT-02:00) Brazil		America/Noronha
BRAZIL	(GMT-04:00) Brazil		America/Porto_Velho
BRAZIL	(GMT-03:00) Brazil		America/Recife
BRAZIL	(GMT-05:00) Brazil		America/Rio_Branco
BRAZIL	(GMT-03:00) Brazil		America/Santarem
BRITISH INDIAN OCEAN TERRITORY	(GMT+06:00) British Indian Ocean Territory		Indian/Chagos
BRUNEI	BRUNEI(GMT+08:00)		Asia/Brunei
BRUNEI DARUSSALAM	(GMT+08:00) Brunei Darussalam		Asia/Brunei
BULGARIA	(GMT+02:00) Bulgaria	BULGARIA(GMT+03:00)	Europe/Sofia
BURKINA FASO	(GMT±00:00) Burkina Faso		Africa/Ouagadougou
BURKINA FASO	(GMT±00:00) Burkina Faso		Africa/Abidjan
BURUNDI	(GMT+02:00) Burundi		Africa/Bujumbura
BURUNDI	(GMT+02:00) Burundi		Africa/Maputo
CAMBODIA	(GMT+07:00) Cambodia		Asia/Phnom_Penh
CAMEROON	(GMT+01:00) Cameroon		Africa/Douala
CAMEROON	(GMT+01:00) Cameroon		Africa/Lagos
CANADA	(GMT-04:00) Canada(Atlantic)		America/Halifax
CANADA	(GMT-07:00) Canada(Mountain)		America/Edmonton
CANADA	(GMT-05:00) Canada(Eastern)		America/Toronto

CANADA	(GMT-03:30) Canada(Newfoundland)		America/St_Johns
CANADA	(GMT-08:00) Canada(Pacific)		America/Vancouver
CANADA	(GMT-06:00) Canada(Central)		America/Regina
CANADA	(GMT-04:00) Canada(Atlantic Standard Time)		America/Blanc-Sablon
CANADA	(GMT-05:00) Canada(Eastern Standard Time)		America/Atikokan
CANADA	(GMT-06:00) Canada(Central Standard Time)		America/Winnipeg
CANADA	(GMT-07:00) Canada(Mountain Standard Time)		America/Creston
CAPE VERDE	(GMT-01:00) Cape Verde		Atlantic/Cape_Verde
CAPE VERDE	(GMT-04:00) Curacao		America/Curacao
CAYMAN ISLANDS	(GMT-05:00) Cayman Islands		America/Cayman
CAYMAN ISLANDS	(GMT-05:00) Cayman Islands		America/Panama
CENTRAL AFRICAN REPUBLIC	(GMT+01:00) Central African Republic		Africa/Bangui
CHAD	(GMT+01:00) Chad		Africa/Ndjamena
CHILE	(GMT-04:00) Chile	CHILE(GMT-03:00)	America/Santiago
CHILE	(GMT-06:00) Chile	CHILE(GMT-05:00)	Pacific/Easter
CHINA	(GMT+08:00) China		Asia/Shanghai
CHINA	(GMT+06:00) China		Asia/Urumqi
CHRISTMAS ISLAND	(GMT+07:00) Christmas Island		Indian/Christmas
COCOS (KEELING) ISLANDS	(GMT+06:30) Cocos (Keeling) Islands		Indian/Cocos
COLOMBIA	(GMT-05:00) Colombia		America/Bogota
COMOROS	(GMT+03:00) Comoros		Indian/Comoro
CONGO	(GMT+01:00) Congo		Africa/Brazzaville
CONGO	(GMT+01:00) Congo		Africa/Lagos
CONGO, DEMOCRATIC REPUBLIC OF THE	(GMT+01:00) Congo, Democratic Republic Of		Africa/Brazzaville
CONGO, THE DRC	(GMT+01:00) Congo, The Drc		Africa/Kinshasa
CONGO, THE DRC	(GMT+01:00) Congo, The Drc		Africa/Lagos
CONGO, THE DRC	(GMT+02:00) Congo, The Drc		Africa/Lubumbashi

CONGO, THE DRC	(GMT+02:00) Congo, The Drc		Africa/Maputo
COOK ISLANDS	(GMT-10:00) Cook Islands		Pacific/Rarotonga
COSTA RICA	(GMT-06:00) Costa Rica		America/Costa_Rica
COTE D.IVOIRE	(GMT+00:00) COTE D.IVOIRE		Africa/Abidjan
CROATIA	(GMT+01:00) Croatia	CROATIA(GMT+02:00)	Europe/Belgrade
CROATIA	(GMT+01:00) Croatia	CROATIA(GMT+02:00)	Europe/Zagreb
CUBA	(GMT-05:00) Cuba	CUBA(GMT-04:00)	America/Havana
CYPRUS	(GMT+02:00) Cyprus	CYPRUS(GMT+03:00)	Asia/Nicosia
CYPRUS	(GMT+02:00) Cyprus	CYPRUS(GMT+03:00)	Asia/Famagusta
CZECH REPUBLIC	(GMT+01:00) Czech Republic	CZECH REPUBLIC(GMT+02:00)	Europe/Prague
DENMARK	(GMT+01:00) Denmark	DENMARK(GMT+02:00)	Europe/Copenhagen
DJIBOUTI	(GMT+03:00) Djibouti		Africa/Djibouti
DJIBOUTI	(GMT+03:00) Djibouti		Africa/Nairobi
DOMINICA	(GMT-04:00) Dominica		America/Dominica
DOMINICAN REPUBLIC	(GMT-04:00) Dominican Republic		America/Santo_Domingo
EAST TIMOR	(GMT+9:00) East Timor		Asia/Dili
ECUADOR	(GMT-05:00) Ecuador		America/Guayaquil
ECUADOR	(GMT-06:00) Ecuador		Pacific/Galapagos
EGYPT	(GMT+02:00) Egypt		Africa/Cairo
EL SALVADOR	(GMT-06:00) El Salvador		America/El_Salvador
EQUATORIAL GUINEA	(GMT+01:00) Equatorial Guinea		Africa/Malabo
ERITREA	(GMT+03:00) Eritrea		Africa/Asmara
ERITREA	(GMT+03:00) Eritrea		Africa/Nairobi
ESTONIA	(GMT+02:00) Estonia	ESTONIA(GMT+03:00)	Europe/Tallinn
ETHIOPIA	(GMT+03:00) Ethiopia		Africa/Addis_Ababa
FALKLAND ISLANDS (MALVINAS)	(GMT-03:00) Falkland Islands (Malvinas)		Atlantic/Stanley
FAROE ISLANDS	(GMT±00:00) Faroe Islands	FAROE ISLANDS(GMT+01:00)	Atlantic/Faroe
FIJI	(GMT+12:00) Fiji	FIJI(GMT+13:00)	Pacific/Fiji

FINLAND	(GMT+02:00) Finland	FINLAND(GMT+03:00)	Europe/Helsinki
FRANCE	(GMT+01:00) France	FRANCE(GMT+02:00)	Europe/Paris
FRANCE, METROPOLITAN	(GMT+01:00) France, Metropolitan	FRANCE, METROPOLITAN(GMT+02:00	Europe/Paris
FRENCH GUIANA	(GMT-03:00) French Guiana		America/Cayenne
FRENCH POLYNESIA	(GMT-10:00) French Polynesia		Pacific/Tahiti
FRENCH POLYNESIA	(GMT-9:00) French Polynesia(Mangareva)		Pacific/Gambier
FRENCH POLYNESIA	(GMT-8:30) French Polynesia(Marquesas Islands)		Pacific/Marquesas
FRENCH SOUTHERN TERRITORIES	(GMT+05:00) French Southern Territories	FRENCH SOUTHERN TERRITORIES(GM	Indian/Kerguelen
GABON	(GMT+01:00) Gabon		Africa/Libreville
GAMBIA	(GMT±00:00) Gambia		Africa/Banjul
GEORGIA	(GMT+04:00) Georgia		Atlantic/South_Georgia
GERMANY	(GMT+01:00) Germany	GERMANY(GMT+02:00)	Europe/Berlin
GERMANY	(GMT+01:00) Germany	GERMANY(GMT+02:00)	Europe/Busingen
GERMANY	(GMT+01:00) Germany	GERMANY(GMT+02:00)	Europe/Zurich
GHANA	(GMT±00:00) Ghana		Africa/Accra
GIBRALTAR	(GMT+01:00) Gibraltar	GIBRALTAR(GMT+02:00)	Europe/Gibraltar
GREECE	(GMT+02:00) Greece	GREECE(GMT+03:00)	Europe/Athens
GREENLAND	(GMT-03:00) Greenland	GREENLAND(GMT-02:00)	America/Nuuk
GREENLAND	(GMT-01:00) Greenland	GREENLAND(GMT-00:00)	America/Scoresbysund
GREENLAND	(GMT-04:00) Greenland	GREENLAND(GMT-03:00)	America/Thule
GREENLAND	(GMT+00:00) Guinea-Bissau		Africa/Bissau
GRENADA	(GMT-04:00) Grenada		America/Grenada
GUADELOUPE	(GMT-04:00) Guadeloupe		America/Guadeloupe
GUAM	(GMT+10:00) Guam		Pacific/Guam
GUATEMALA	(GMT-06:00) Guatemala		America/Guatemala
GUERNSEY	(GMT+00:00) Guernsey		Europe/Guernsey
GUERNSEY	(GMT+00:00) Guernsey		Europe/London
GUINEA	(GMT±00:00) Guinea		Africa/Conakry

GUYANA	(GMT-04:00) Guyana		America/Guyana
HAITI	(GMT-05:00) Haiti		America/Port-au-Prince
HOLY SEE (VATICAN CITY STATE)	(GMT+01:00) Vatican		Europe/Vatican
HONDURAS	(GMT-06:00) Honduras		America/Tegucigalpa
HONG KONG	(GMT+08:00) Hong Kong		Asia/Hong_Kong
HUNGARY	(GMT+01:00) Hungary	HUNGARY(GMT+02:00)	Europe/Budapest
ICELAND	(GMT±00:00) Iceland		Atlantic/Reykjavik
INDIA	(GMT+05:30) India		Asia/Calcutta
INDONESIA	(GMT+07:00) Indonesia		Asia/Jakarta
INDONESIA	(GMT+08:00) Indonesia		Asia/Makassar
INDONESIA	(GMT+09:00) Indonesia		Asia/Jayapura
INDONESIA	(GMT+07:00) Indonesia		Asia/Pontianak
INDONESIA	(GMT±00:00) Isle of Man	ISLEOFMAN(GMT+01:00)	Europe/Isle_of_Man
INDONESIA	(GMT±00:00) Isle of Man	ISLEOFMAN(GMT+01:00)	Europe/London
INDONESIA	(GMT±00:00) Jersey	JERSEY(GMT+01:00)	Europe/Jersey
INDONESIA	(GMT±00:00) Jersey	JERSEY(GMT+01:00)	Europe/London
IRAN	(GMT+03:30) Iran (Islamic Republic Of)	IRAN (ISLAMIC REPUBLIC OF) (GMT	Asia/Tehran
IRAQ	(GMT+03:00) Iraq		Asia/Baghdad
IRAQ	(GMT+03:30) Iraq		Asia/Tehran
IRELAND	(GMT±00:00) Ireland	IRELAND(GMT+01:00)	Europe/Dublin
ISRAEL	(GMT+02:00) Israel	ISRAEL(GMT+03:00)	Asia/Jerusalem
ITALY	(GMT+01:00) Italy	ITALY(GMT+02:00)	Europe/Rome
JAMAICA	(GMT-05:00) Jamaica		America/Jamaica
JAPAN	(GMT+09:00) Japan		Asia/Tokyo
JORDAN	(GMT+02:00) Jordan	JORDAN(GMT+03:00)	Asia/Amman
KAZAKHSTAN	(GMT+05:00) Kazakhstan		Asia/Aqtau
KAZAKHSTAN	(GMT+06:00) Kazakhstan		Asia/Almaty
KAZAKHSTAN	(GMT+06:00) Kazakhstan		Asia/Qostanay

KAZAKHSTAN	(GMT+05:00) Kazakhstan		Asia/Aqtobe
KAZAKHSTAN	(GMT+05:00) Kazakhstan		Asia/Atyrau
KAZAKHSTAN	(GMT+05:00) Kazakhstan		Asia/Qyzylorda
KENYA	(GMT+03:00) Kenya		Africa/Nairobi
KIRIBATI	(GMT+12:00) Kiribati		Pacific/Tarawa
KIRIBATI	(GMT+13:00) Kiribati		Pacific/Kiritimati
KIRIBATI	(GMT+14:00) Kiribati		Pacific/Enderbury
KUWAIT	(GMT+03:00) Kuwait		Asia/Kuwait
KYRGYZSTAN	(GMT+06:00) Kyrgyzstan		Asia/Bishkek
LAOS	(GMT+07:00) Laos		Asia/Vientiane
LAOS	(GMT+07:00) Laos		Asia/Bangkok
LATVIA	(GMT+02:00) Latvia	LATVIA(GMT+03:00)	Europe/Riga
LEBANON	(GMT+02:00) Lebanon	LEBANON(GMT+03:00)	Asia/Beirut
LESOTHO	(GMT+02:00) Lesotho		Africa/Maseru
LIBERIA	(GMT±00:00) Liberia		Africa/Monrovia
LIBYAN ARAB JAMAHIRIYA	(GMT+02:00) Libya		Africa/Tripoli
LIECHTENSTEIN	(GMT+01:00) Liechtenstein	LIECHTENSTEIN(GMT+02:00)	Europe/Vaduz
LIECHTENSTEIN	(GMT+01:00) Liechtenstein	LIECHTENSTEIN(GMT+02:00)	Europe/Zurich
LITHUANIA	(GMT+02:00) Lithuania	LITHUANIA(GMT+03:00)	Europe/Vilnius
LUXEMBOURG	(GMT+01:00) Luxembourg	LUXEMBOURG(GMT+02:00)	Europe/Luxembourg
MACAU	(GMT+08:00) Macau		Asia/Macau
MACEDONIA	(GMT+01:00) Macedonia	MACEDONIA(GMT+02:00)	Europe/Skopje
MADAGASCAR	(GMT+03:00) Madagascar		Indian/Antananarivo
MALAWI	(GMT+02:00) Malawi		Africa/Blantyre
MALAYSIA	(GMT+08:00) Malaysia		Asia/Kuala_Lumpur
MALDIVES	(GMT+05:00) Maldives		Indian/Maldives
MALI	(GMT±00:00) Mali		Africa/Bamako
MALTA	(GMT+01:00) Malta	MALTA(GMT+02:00)	Europe/Malta
MARSHALL ISLANDS	(GMT+12:00) Marshall Islands		Pacific/Majuro

MARSHALL ISLANDS	(GMT+12:00) Marshall Islands		Pacific/Kwajalein
MARTINIQUE	(GMT-04:00) Martinique		America/Martinique
MAURITANIA	(GMT±00:00) Mauritania		Africa/Nouakchott
MAURITIUS	(GMT+04:00) Mauritius		Indian/Mauritius
MAYOTTE	(GMT+03:00) Mayotte		Indian/Mayotte
MEXICO	(GMT-05:00) Mexico(State Of Quintana Roo)	MEXICO(GMT-04:00)	America/Cancun
MEXICO	(GMT-06:00) Mexico(Baja California Sur (South), Chihuahua,Nayarit, Sinaloa	MEXICO(GMT-05:00)	America/Mexico_City
MEXICO	(GMT-07:00) Mexico(State Of Sonora)		America/Hermosillo
MEXICO	(GMT-08:00) Mexico(State Of Baja California)	Mexico(state of Baja California)(GMT-07:00)	America/Tijuana
MICRONESIA	(GMT+11:00) Micronesia		Pacific/Kosrae
MICRONESIA	(GMT+11:00) Micronesia		Pacific/Pohnpei
MICRONESIA, FEDERATED STATES OF	(GMT+10:00) Micronesia, Federated States Of		Pacific/Chuuk
MOLDOVA, REPUBLIC OF	(GMT+02:00) Moldova, Republic Of	MOLDOVA, REPUBLIC OF(GMT+03:00	Europe/Chisinau
MONACO	(GMT+01:00) Monaco	MONACO(GMT+01:00)	Europe/Monaco
MONGOLIA	(GMT+08:00) Mongolia	MONGOLIA(GMT+09:00)	Asia/Ulaanbaatar
MONGOLIA	(GMT+07:00) Mongolia		Asia/Hovd
MONGOLIA	(GMT+08:00) Mongolia		Asia/Choibalsan
MONTENEGRO	(GMT+01:00) Montenegro	MONTENEGRO(GMT+02:00)	Etc/GMT-1
MONTSERRAT	(GMT-04:00) Montserrat		America/Montserrat
MOROCCO	(GMT+01:00) Morocco	MOROCCO(GMT+01:00)	Africa/Casablanca
MOZAMBIQUE	(GMT+02:00) Mozambique		Africa/Maputo
MYANMAR (BURMA)	(GMT+06:30) Myanmar (Burma)		Asia/Yangon
NAMIBIA	(GMT+01:00) Namibia	NAMIBIA(GMT+02:00)	Africa/Windhoek
NAURU	(GMT+12:00) Nauru		Pacific/Nauru
NEPAL	(GMT+05:45) Nepal		Asia/Kathmandu
NETHERLANDS	(GMT+01:00) Netherlands	NETHERLANDS(GMT+02:00)	Europe/Amsterdam
NETHERLANDS ANTILLES	(GMT+01:00) Netherlands Antilles	NETHERLANDS ANTILLES(GMT+02:00	Europe/Amsterdam

NEW CALEDONIA	(GMT+11:00) New Caledonia		Pacific/Noumea
NEW ZEALAND	(GMT+12:00) New Zealand	NEW ZEALAND(GMT+13:00)	Pacific/Auckland
NEW ZEALAND	(GMT+13:45) New Zealand	NEW ZEALAND(GMT+14:45)	Pacific/Chatham
NICARAGUA	(GMT-06:00) Nicaragua		America/Managua
NIGER	(GMT+01:00) Niger		Africa/Niamey
NIGERIA	(GMT+01:00) Nigeria		Africa/Lagos
NIUE	(GMT-11:00) Niue		Pacific/Niue
NORFOLK ISLAND	(GMT+12:00) Norfolk Island		Pacific/Norfolk
NORTH KOREA	(GMT+09:00) Korea, D.P.R.O.		Asia/Pyongyang
NORTHERN MARIANA ISLANDS	(GMT+10:00) Northern Mariana Islands		Pacific/Saipan
NORWAY	(GMT+01:00) Norway	NORWAY(GMT+02:00)	Europe/Oslo
OMAN	(GMT+04:00) Oman		Asia/Muscat
PAKISTAN	(GMT+05:00) Pakistan		Asia/Karachi
PALAU	(GMT+09:00) Palau		Pacific/Palau
PALESTINIAN TERRITORIES	(GMT+2:00) Palestine		Asia/Gaza
PALESTINIAN TERRITORIES	(GMT+2:00) Palestine		Asia/Hebron
PANAMA	(GMT-05:00) Panama		America/Panama
PAPUA NEW GUINEA	(GMT+10:00) Papua New Guinea		Pacific/Port_Moresby
PAPUA NEW GUINEA	(GMT+11:00) Papua New Guinea		Pacific/Bougainville
PARAGUAY	(GMT-04:00) Paraguay	PARAGUAY(GMT-03:00)	America/Asuncion
PERU	(GMT-05:00) Peru		America/Lima
PHILIPPINES	(GMT+08:00) Philippines		Asia/Manila
PITCAIRN	(GMT-08:00) Pitcairn		Pacific/Pitcairn
POLAND	(GMT+01:00) Poland	POLAND(GMT+02:00)	Europe/Warsaw
PORTUGAL	(GMT±00:00) Portugal	PORTUGAL(GMT+01:00)	Europe/Lisbon
PUERTO RICO	(GMT-04:00) Puerto Rico		America/Puerto_Rico
QATAR	(GMT+03:00) Qatar		Asia/Qatar
REUNION	(GMT+04:00) Reunion		Indian/Reunion

ROMANIA	(GMT+02:00) Romania	ROMANIA(GMT+03:00)	Europe/Bucharest
RUSSIA	(GMT+02:00) Russia(Kaliningrad)	RUSSIA()	Europe/Moscow
RUSSIA	(GMT+03:00) Russia(Moscow)		Europe/Moscow
RUSSIA	(GMT+04:00) Russia(Samara)		Europe/Samara
RUSSIA	(GMT+05:00) Russia(Yekaterinburg)		Asia/Yekaterinburg
RUSSIA	(GMT+06:00) Russia(Omsk)		Asia/Omsk
RUSSIA	(GMT+07:00) Russia(Krasnoyarsk)		Asia/Krasnoyarsk
RUSSIA	(GMT+08:00) Russia(Irkutsk)		Asia/Irkutsk
RUSSIA	(GMT+09:00) Russia(Yakutsk)		Asia/Yakutsk
RUSSIA	(GMT+10:00) Russia(Vladivostok)		Asia/Vladivostok
RUSSIA	(GMT+11:00) Russia(Magadan)		Asia/Magadan
RUSSIA	(GMT+12:00) Russia(Kamchatka)		Asia/Kamchatka
RUSSIAN FEDERATION	(GMT+12:00) Russia		Asia/Anadyr
RUSSIAN FEDERATION	(GMT+7:00) Russia		Asia/Barnaul
RUSSIAN FEDERATION	(GMT+9:00) Russia		Asia/Chita
RUSSIAN FEDERATION	(GMT+8:00) Russia		Asia/Irkutsk
RUSSIAN FEDERATION	(GMT+12:00) Russia		Asia/Kamchatka
RUSSIAN FEDERATION	(GMT+9:00) Russia		Asia/Khandyga
RUSSIAN FEDERATION	(GMT+7:00) Russia		Asia/Krasnoyarsk
RUSSIAN FEDERATION	(GMT+11:00) Russia		Asia/Magadan
RUSSIAN FEDERATION	(GMT+7:00) Russia		Asia/Novokuznetsk
RUSSIAN FEDERATION	(GMT+7:00) Russia		Asia/Novosibirsk
RUSSIAN FEDERATION	(GMT+6:00) Russia		Asia/Omsk
RUSSIAN FEDERATION	(GMT+11:00) Russia		Asia/Sakhalin
RUSSIAN FEDERATION	(GMT+11:00) Russia		Asia/Srednekolymsk
RUSSIAN FEDERATION	(GMT+7:00) Russia		Asia/Tomsk
RUSSIAN FEDERATION	(GMT+10:00) Russia		Asia/Ust-Nera
RUSSIAN FEDERATION	(GMT+10:00) Russia		Asia/Vladivostok
RUSSIAN FEDERATION	(GMT+9:00) Russia		Asia/Yakutsk

RUSSIAN FEDERATION	(GMT+5:00) Russia		Asia/Yekaterinburg
RUSSIAN FEDERATION	(GMT+4:00) Russia		Europe/Astrakhan
RUSSIAN FEDERATION	(GMT+2:00) Russia		Europe/Kaliningrad
RUSSIAN FEDERATION	(GMT+3:00) Russia		Europe/Kirov
RUSSIAN FEDERATION	(GMT+3:00) Russia		Europe/Moscow
RUSSIAN FEDERATION	(GMT+4:00) Russia		Europe/Samara
RUSSIAN FEDERATION	(GMT+4:00) Russia		Europe/Saratov
RUSSIAN FEDERATION	(GMT+3:00) Russia		Europe/Simferopol
RUSSIAN FEDERATION	(GMT+4:00) Russia		Europe/Ulyanovsk
RUSSIAN FEDERATION	(GMT+4:00) Russia		Europe/Volgograd
RWANDA	(GMT+02:00) Rwanda		Africa/Kigali
SAINT BARTHELEMY	(GMT-04:00) St Barthelemy		America/Port_of_Spain
SAINT BARTHELEMY	(GMT-04:00) St Barthelemy		America/St_Barthelemy
SAINT KITTS AND NEVIS	(GMT-04:00) Saint Kitts And Nevis		America/St_Kitts
SAINT LUCIA	(GMT-04:00) Saint Lucia		America/St_Lucia
SAINT MARTIN (FRENCH PART)	(GMT-04:00) St Martin (French)		America/Marigot
SAINT MARTIN (FRENCH PART)	(GMT-04:00) St Martin (French)		America/Port_of_Spain
SAINT VINCENT AND THE GRENADINES	(GMT-04:00) Saint Vincent And The Grenadin		America/St_Vincent
SAMOA	(GMT+13:00) Samoa	SAMOA(GMT+14:00)	Pacific/Apia
SAN MARINO	(GMT+01:00) San Marino	SAN MARINO(GMT+02:00)	Europe/San_Marino
SAO TOME AND PRINCIPE	(GMT±00:00) Sao Tome And Principe		Africa/Sao_Tome
SAUDI ARABIA	(GMT+03:00) Saudi Arabia		Asia/Riyadh
SENEGAL	(GMT±00:00) Senegal		Africa/Dakar
SERBIA	(GMT+01:00) Serbia	SERBIA(GMT+02:00)	Europe/Belgrade
SEYCHELLES	(GMT+04:00) Seychelles		Indian/Mahe
SIERRA LEONE	(GMT±00:00) Sierra Leone		Africa/Freetown
SINGAPORE	(GMT+08:00) Singapore		Asia/Singapore

SINT MAARTEN (DUTCH PART)	(GMT-4:00) St Maarten (Dutch)		America/Curacao
SINT MAARTEN (DUTCH PART)	(GMT-4:00) St Maarten (Dutch)		America/Lower_Princes
SLOVAKIA (Slovak Republic)	(GMT+01:00) Slovakia	SLOVAKIA(GMT+02:00)	Europe/Bratislava
SLOVENIA	(GMT+01:00) Slovenia	SLOVENIA(GMT+02:00)	Europe/Ljubljana
SOLOMON ISLANDS	(GMT+11:00) Solomon Islands		Pacific/Guadalcanal
SOMALIA	(GMT+03:00) Somalia		Africa/Mogadishu
SOUTH AFRICA	(GMT+02:00) South Africa		Africa/Johannesburg
SOUTH GEORGIA AND SOUTH S.S.	(GMT-02:00) South Georgia And South S.S.		Atlantic/South_Georgia
SOUTH KOREA	(GMT+09:00) Korea, Republic Of		Asia/Seoul
SOUTH SUDAN	(GMT+03:00) South Sudan		Africa/Juba
SPAIN	(GMT+01:00) Spain	SPAIN(GMT+02:00)	Europe/Madrid
SPAIN	(GMT+00:00) Spain		Atlantic/Canary
SPAIN	(GMT+01:00) Spain		Africa/Ceuta
SRI LANKA	(GMT+05:30) Sri Lanka		Asia/Colombo
ST. HELENA	(GMT±00:00) St Helena		Atlantic/St_Helena
ST. PIERRE AND MIQUELON	(GMT-3:00) St Pierre & Miquelon		America/Miquelon
SUDAN	(GMT+03:00) Sudan		Africa/Khartoum
SURINAME	(GMT-03:00) Suriname		America/Paramaribo
SVALBARD AND JAN MAYEN ISLANDS	(GMT+01:00) Svalbard And Jan Mayen Islands	SVALBARD AND JAN MAYEN ISLANDS	Arctic/Longyearbyen
SWAZILAND	(GMT+02:00) Swaziland		Africa/Mbabane
SWEDEN	(GMT+01:00) Sweden	SWEDEN(GMT+02:00)	Europe/Stockholm
SWITZERLAND	(GMT+01:00) Switzerland	SWITZERLAND(GMT+02:00)	Europe/Zurich
SYRIA	(GMT+2:00) Syria		Asia/Damascus
SYRIAN ARAB REPUBLIC	(GMT+02:00) Syrian Arab Republic	SYRIAN ARAB REPUBLIC(GMT+03:00	Asia/Damascus
TAIWAN	(GMT+8:00) Taiwan		Asia/Taipei
TAJIKISTAN	(GMT+05:00) Tajikistan		Asia/Dushanbe

TANZANIA	(GMT+03:00) Tanzania		Africa/Dar_es_Salaam
THAILAND	(GMT+07:00) Thailand		Asia/Bangkok
TOGO	(GMT±00:00) Togo		Africa/Lome
TOKELAU	(GMT+13:00) Tokelau		Pacific/Fakaofo
TONGA	(GMT+13:00) Tonga	TONGA(GMT+14:00)	Pacific/Tongatapu
TRINIDAD AND TOBAGO	(GMT-04:00) Trinidad And Tobago		America/Port_of_Spain
TUNISIA	(GMT+01:00) Tunisia		Africa/Tunis
TURKEY	(GMT+03:00) Turkey		Europe/Istanbul
TURKMENISTAN	(GMT+05:00) Turkmenistan		Asia/Ashgabat
TURKS AND CAICOS ISLANDS	(GMT-05:00) Turks And Caicos Islands		America/Grand_Turk
TUVALU	(GMT+12:00) Tuvalu		Pacific/Funafuti
U.S. MINOR ISLANDS	(GMT-10:00) Ukraine		Pacific/Honolulu
U.S. MINOR ISLANDS	(GMT-11:00) Ukraine		Pacific/Midway
U.S. MINOR ISLANDS	(GMT+12:00) Ukraine		Pacific/Wake
UGANDA	(GMT+03:00) Uganda		Africa/Kampala
UKRAINE	(GMT+02:00) Ukraine	UKRAINE(GMT+03:00)	Europe/Kiev
UKRAINE	(GMT+03:00) Ukraine	UKRAINE(GMT+04:00)	Europe/Simferopol
UNITED ARAB EMIRATES	(GMT+04:00) United Arab Emirates		Asia/Dubai
UNITED KINGDOM	(GMT±00:00) United Kingdom	UNITED KINGDOM(GMT+01:00)	Europe/London
UNITED STATES	(GMT-05:00) United States(Eastern)	UNITED STATES(GMT-04:00)	America/New_York
UNITED STATES	(GMT-07:00) United States(Mountain)		America/Denver
UNITED STATES	(GMT-08:00) United States(Pacific)		America/Los_Angeles
UNITED STATES	(GMT-09:00) United States(Alaska)		America/Anchorage
UNITED STATES	(GMT-10:00) United States(Hawaii-Aleutian)		Pacific/Honolulu
UNITED STATES	(GMT-06:00) United States(Central)		America/Chicago
UNITED STATES	(GMT-07:00) United States(Arizona)		America/Phoenix
URUGUAY	(GMT-03:00) Uruguay		America/Montevideo
UZBEKISTAN	(GMT+05:00) Uzbekistan		Asia/Tashkent

VANUATU	(GMT+11:00) Vanuatu	Pacific/Efate
VENEZUELA	(GMT-04:00) Venezuela	America/Caracas
VIETNAM	(GMT+07:00) Vietnam	Asia/Ho_Chi_Minh
VIRGIN ISLANDS (BRITISH)	(GMT-04:00) Virgin Islands (UK)	America/Tortola
VIRGIN ISLANDS (U.S.)	(GMT-04:00) Virgin Islands (US)	America/St_Thomas
WALLIS AND FUTUNA ISLANDS	(GMT+12:00) Wallis And Futuna Islands	Pacific/Wallis
WESTERN SAHARA	(GMT+01:00) Western Sahara	Africa/El_Aaiun
YEMEN	(GMT+03:00) Yemen	Asia/Aden
ZAMBIA	(GMT+02:00) Zambia	Africa/Lusaka
ZIMBABWE	(GMT+02:00) Zimbabwe	Africa/Harare

Postal Codes

If you are looking for a postal code/zip code list for your country, reach out to your Account Manager to get it configured, or write to us at: support@loginextsolutions.com

Delivery Associate Status

The current status of your delivery associate. Note that you can update the status of your delivery associates by calling the **Update Delivery Associate Status** API.

Status	Code	Description
Active	ACTIVE	The delivery associate is ‘Active’, you will be able to assign orders. Such delivery associates can sign in to the Driver App.
Inactive	INACTIVE	The delivery associate is ‘Inactive’, you will not be able to assign any orders. Such delivery associates will not be able to sign in to the Driver App.
On Break	ONBREAK	The delivery associate is currently on break (i.e., temporarily unavailable) and is not fulfilling any orders. New orders cannot be assigned to delivery associates who are ‘On Break’. Note that only ‘Active’ delivery associates can go ‘On Break’.
Off Break	OFFBREAK	The delivery associate is back from break and ready to fulfill orders. Note that only ‘Active’ delivery associates can go ‘On Break’.

Trip Status

Status	Description
Not Started	The trip has been created in the LogiNext system, but the delivery associate has not yet started the trip or begun the pickup and delivery of orders.
In Transit	The orders associated with the trip are currently being fulfilled.
Ended	The orders associated with the trip have been fulfilled, and their statuses have been updated.