

zyerr

NAME

Error Dequeue Abstraction Library

LIBRARY

zyerr (-lzyerr)

SYNOPSIS

```
#include <zyerr.h>

typedef struct zyerrbx_s zyerrbx_t;
typedef struct zyerr_s zyerr_t;

int zyerr_construct(zyerr_t **err, const zyalloc_t *alloc);
void zyerr_destruct(zyerr_t **err);
void zyerr_clear(zyerr_t *err);
int zyerr_push_first(zyerr_t *err, int64_t code, const char *file,
                    size_t line, const char *function,
                    const void *opaque, size_t opaque_size);
int zyerr_push_last(zyerr_t *err, int64_t code, const char *file,
                   size_t line, const char *function,
                   const void *opaque, size_t opaque_size);
void zyerr_discard_first(zyerr_t *err);
void zyerr_discard_last(zyerr_t *err);
zyerrbx_t *zyerr_peek_first(const zyerr_t *err);
zyerrbx_t *zyerr_peek_last(const zyerr_t *err);
size_t zyerr_size(const zyerr_t *err);
bool zyerr_is_empty(const zyerr_t *err);

int64_t zyerrbx_code(const zyerrbx_t *bx);
const char *zyerrbx_file(const zyerrbx_t *bx);
size_t zyerrbx_line(const zyerrbx_t *bx);
const char *zyerrbx_function(const zyerrbx_t *bx);
const void *zyerrbx_opaque(const zyerrbx_t *bx, size_t *size);
```

DESCRIPTION

zyerr_construct()

`zyerr_construct` allocates a `zyerr_t` data structure using `alloc` and stores the result in `*err`. All function arguments must be non-null.

zyerr__destruct()

zyerr__destruct deallocates a **zyerr_t** data structure and sets ***err** to **nullptr**. Note that **err** must be non-null.

zyerr__clear()

zyerr__clear deallocates and unlinks all **zyerrbx_t** data structures stored in **err**. Note that **err** must be non-null.

zyerr__push_*()

zyerr__push_first and **zyerr__push_last** allocate a **zyerrbx_t** and store **code**, **file**, **line**, **function**, **opaque**, and **opaque_size**.

The resulting data structure is stored at the *front* and *back* of **err** for **zyerr__push_first** and **zyerr__push_last**, respectively.

Note that **err**, **file**, and **function** must be non-null and **line** must be non-zero. **opaque** may be set to **nullptr** and **opaque_size** to zero in order to indicate that there is no auxiliary data; however, if **opaque** is non-null, then **opaque_size** must be non-zero.

zyerr__discard_first()

zyerr__discard_first deallocates and unlinks the *front-most* **zyerrbx_t** data structure from **err**. Note that **err** must be non-null.

zyerr__discard_last()

zyerr__discard_last deallocates and unlinks the *back-most* **zyerrbx_t** data structure from **err**. Note that **err** must be non-null.

zyerr__peek_first()

zyerr__peek_first retrieves the *front-most* **zyerrbx_t** data structure from **err** if it exists. All function arguments must be non-null.

zyerr__peek_last()

zyerr__peek_last retrieves the *back-most* **zyerrbx_t** data structure from **err** if it exists. All function arguments must be non-null.

zyerr__size()

zyerr__size returns the number of elements stored in **err**. Note that **err** must be non-null.

zyerr__is__empty()

zyerr__is__empty returns a **true** if and only if there are no elements stored in **err**. Note that **err** must be non-null.

zyerrbx__code()

zyerrbx__code returns the *error code* associated with **bx**. Note that **bx** must be non-null.

zyerrbx__file()

zyerrbx__file returns the *file* associated with **bx**. Note that **bx** must be non-null.

zyerrbx__line()

zyerrbx__line returns the *line number* associated with **bx**. Note that **bx** must be non-null.

zyerrbx__function()

zyerrbx__function returns the *function name* associated with **bx**. Note that **bx** must be non-null.

zyerrbx__opaque()

zyerrbx__opaque returns the memory address of the opaque data associated with **bx** and stores its size in ***size**. Note that **bx** must be non-null. **size** may be **nullptr** to indicate that the size is known ahead of time and is unneeded.

RETURN VALUE

On success, **zyerr_construct**, **zyerr_push_first**, **zyerr_push_last** return 0. Otherwise, an error code is returned.

ERRORS

zyerr_construct, **zyerr_push_first**, and **zyerr_push_last** can fail with the following error.

ZYALLOC__ENOMEM Out of memory.

NOTES

It is undefined behavior to violate any preconditions of these functions (e.g. passing **nullptr** to a function argument that is specified as non-null).