

Práctica de Laboratorio 5

Christofer Fabián Chávez Carazas

Universidad Nacional de San Agustín de Arequipa

Escuela Profesional de Ciencia de la Computación

Computación Gráfica

16 de noviembre de 2017

1. Desarrollar un programa para mostrar las primitivas de OpenGL

```
#include <GL/glut.h>
#include <iostream>

using namespace std;

GLsizei winWidth = 1200, winHeight = 800;
int primitiva = -1;

enum Primitivas {POINTS = 1, LINES, STRIP, LINE_LOOP, POLYGON, TRIANGLE_STRIP, TRIANGLES, ←
    TRIANGLE_FAN, QUADS, QUAD_STRIP};

void init(void){
    glClearColor(1.0,1.0,1.0,1.0);
    glMatrixMode(GL_PROJECTION);
    gluOrtho2D(0.0, 1200.0, 0.0, 800.0);
}

void drawString(string s, int x, int y){
    glColor3f(0.0, 0.0, 0.0);
    glRasterPos2i(x,y);
    for(char c : s){
        glutBitmapCharacter(GLUT_BITMAP_HELVETICA_12,c);
    }
    glColor3f(1.0, 0.0, 0.0);
}

void display(void){
    glClear(GL_COLOR_BUFFER_BIT);
    glColor3f(1.0, 0.0, 0.0);
    glPointSize(5);
    glBegin(GL_POINTS);
        glVertex2i(70,770);
        glVertex2i(90,770);
        glVertex2i(80,750);
        glVertex2i(90,760);
    glEnd();
    drawString("GL_POINTS", 50, 730);
    glBegin(GL_LINES);
        glVertex2i(200, 730);
        glVertex2i(250, 800);
        glVertex2i(240, 760);
        glVertex2i(270, 730);
    glEnd();
    drawString("GL_LINES", 205, 700);
    glBegin(GL_LINE_STRIP);
        glVertex2i(500, 700);
        glVertex2i(400, 780);
        glVertex2i(350, 740);
        glVertex2i(600, 760);
        glVertex2i(500, 780);
        glVertex2i(560, 670);
        glVertex2i(450, 650);
    glEnd();
    drawString("GL_LINE_STRIP", 450, 620);
    glBegin(GL_LINE_LOOP);
        glVertex2i(700, 750);
        glVertex2i(800, 790);
        glVertex2i(750, 780);
        glVertex2i(750, 730);
    glEnd();
}
```

```

        glVertex2i(790, 720);
        glVertex2i(740, 670);
    glEnd();
    drawString("GL_LINE_LOOP", 700, 640);
    glBegin(GL_POLYGON);
        glVertex2i(900, 750);
        glVertex2i(950, 800);
        glVertex2i(1000, 750);
        glVertex2i(1000, 700);
        glVertex2i(950, 650);
        glVertex2i(900, 700);
    glEnd();
    drawString("GL_POLYGON", 910, 620);
    glBegin(GL_TRIANGLE_STRIP);
        glVertex2i(100, 550);
        glVertex2i(250, 540);
        glVertex2i(130, 450);
        glColor3f(0.0, 1.0, 0.0);
        glVertex2i(220, 460);
        glVertex2i(110, 400);
        glColor3f(0.0, 0.0, 1.0);
        glVertex2i(210, 390);
        glVertex2i(150, 350);
        glColor3f(0.0, 0.0, 0.0);
        glVertex2i(220, 360);
    glEnd();
    drawString("GL_TRIANGLE_STRIP", 120, 320);
    glBegin(GL_TRIANGLES);
        glVertex2i(350, 500);
        glVertex2i(400, 550);
        glVertex2i(420, 490);
        glVertex2i(460, 470);
        glVertex2i(480, 520);
        glVertex2i(550, 470);
    glEnd();
    drawString("GL_TRIANGLES", 390, 450);
    glBegin(GL_TRIANGLE_FAN);
        glVertex2i(400, 340);
        glVertex2i(420, 400);
        glVertex2i(500, 405);
        glColor3f(0.0, 1.0, 0.0);
        glVertex2i(520, 370);
        glColor3f(0.0, 0.0, 1.0);
        glVertex2i(570, 350);
        glColor3f(0.0, 0.0, 0.0);
        glVertex2i(520, 320);
    glEnd();
    drawString("GL_TRIANGLE_FAN", 400, 300);
    glBegin(GL_QUADS);
        glVertex2i(650, 520);
        glVertex2i(660, 570);
        glVertex2i(720, 550);
        glVertex2i(690, 500);
        glVertex2i(650, 450);
        glVertex2i(730, 450);
        glVertex2i(720, 420);
        glVertex2i(630, 380);
    glEnd();
    drawString("GL_QUADS", 650, 350);
    glBegin(GL_QUAD_STRIP);
        glVertex2i(800, 570);
        glVertex2i(900, 580);
        glVertex2i(820, 500);
        glVertex2i(880, 510);
        glColor3f(0.0, 1.0, 0.0);
        glVertex2i(810, 460);
        glVertex2i(875, 440);
        glColor3f(0.0, 0.0, 1.0);
        glVertex2i(850, 400);
        glVertex2i(900, 420);
    glEnd();
    drawString("GL_QUAD_STRIP", 800, 380);

    glFlush();
}

int main(int argc, char **argv){
    glutInit(&argc, argv);
    glutInitDisplayMode(GLUT_SINGLE | GLUT_RGB);
    glutInitWindowSize(winWidth, winHeight);
    glutInitWindowPosition(100, 100);
    glutCreateWindow("Programa Primitivas");
    init();
    glutDisplayFunc(display);

    glutMainLoop();
    return 0;
}

```




Figura 1: Resultados

2. Probar el siguiente código que muestra los modos de dibujar un polígono




Figura 2: Resultados

3. Dibuje los polígonos con colores interpolados “glShadeModel(GL_SMOOTH)”

```
#include <GL/glut.h>
#include <iostream>

using namespace std;

GLsizei winWidth = 800, winHeight = 600;

void init(void){
    glClearColor(1.0,1.0,1.0,1.0);
    glMatrixMode(GL_PROJECTION);
    gluOrtho2D(0.0, 800.0, 0.0, 600.0);
}

void display(){
    glClear(GL_COLOR_BUFFER_BIT);
    glColor3f(1.0, 0.0, 0.0);
    glShadeModel(GL_SMOOTH);
    glPolygonMode(GL_FRONT, GL_FILL);
    glBegin(GL_POLYGON);
        glVertex2i(10, 10);
        glVertex2i(100, 10);
        glColor3f(0.0, 1.0, 0.0);
        glVertex2i(150, 50);
        glVertex2i(100, 100);
```

```

        glColor3f(0.0, 0.0, 1.0);
        glVertex2i(50, 80);
        glVertex2i(10, 10);
    glEnd();
    glFlush();
}

int main(int argc, char **argv){
    glutInit(&argc, argv);
    glutInitDisplayMode(GLUT_SINGLE | GLUT_RGB);
    glutInitWindowSize(winWidth, winHeight);
    glutInitWindowPosition(100, 100);
    glutCreateWindow("Ejercicio 2");
    init();
    glutDisplayFunc(display);
    glutMainLoop();
    return 0;
}

```




Figura 3: Resultados

4. Probar el siguiente código que muestra un polígono con patrones



Figura 4: Resultados

5. Realice un diseño artístico utilizando polígonos, aplicando patrones y colores

```

#include <GL/glut.h>
#include <iostream>
#include <tuple>
#include <cstdlib>
#include <ctime>

using namespace std;

GLsizei winWidth = 1200, winHeight = 800;
typedef tuple<float, float, float> Color;
enum COLORES {ROJO, VERDE, AZUL, BLANCO, NEGRO, GRIS_CLARO, CORAL, ORO, CELESTE, NARANJA, ROSADO, ←
    CELESTE2, VIOLETA, AMARILLO,
    CYAN, MAGENTA};

GLubyte fly[] = {
    0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00,
    0x03, 0x80, 0x01, 0xc0, 0x06, 0xc0, 0x03, 0x60,
    0x04, 0x60, 0x06, 0x20, 0x04, 0x30, 0x0c, 0x20,
    0x04, 0x18, 0x18, 0x20, 0x04, 0x0c, 0x30, 0x20,
    0x04, 0x06, 0x60, 0x20, 0x44, 0x03, 0xc0, 0x22,
    0x44, 0x01, 0x80, 0x22, 0x44, 0x01, 0x80, 0x22,
    0x44, 0x01, 0x80, 0x22, 0x44, 0x01, 0x80, 0x22,
    0x44, 0x01, 0x80, 0x22, 0x44, 0x01, 0x80, 0x22,
    0x66, 0x01, 0x80, 0x66, 0x33, 0x01, 0x80, 0xcc,
    0x19, 0x81, 0x81, 0x98, 0x0c, 0xc1, 0x83, 0x30,
    0x07, 0xe1, 0x87, 0xe0, 0x03, 0x3f, 0xfc, 0xc0,
    0x06, 0x64, 0x26, 0x60, 0x0c, 0xcc, 0x33, 0x30,
    0x18, 0xcc, 0x33, 0x18, 0x10, 0xc4, 0x23, 0x08,
    0x10, 0x63, 0xc6, 0x08, 0x10, 0x30, 0x0c, 0x08,
    0x10, 0x18, 0x18, 0x08, 0x10, 0x00, 0x00, 0x08};

```

```

Color getColor(int color){
    switch(color){
        case ROJO: return make_tuple(1.0,0.0,0.0);
        case VERDE: return make_tuple(0.0,1.0,0.0);
        case AZUL: return make_tuple(0.0,0.0,1.0);
        case BLANCO: return make_tuple(1.0,1.0,1.0);
        case NEGRO: return make_tuple(0.0,0.0,0.0);
        case GRIS_CLARO: return make_tuple(0.658824,0.658824,0.658824);
        case CORAL: return make_tuple(1.0, 0.498039, 0.0);
        case ORO: return make_tuple(0.8, 0.498039, 0.196078);
        case CELESTE: return make_tuple(0.74902, 0.847059, 0.847059);
        case NARANJA: return make_tuple(1.0, 0.5, 0.0);
        case ROSADO: return make_tuple(0.737255, 0.560784, 0.560784);
        case CELESTE2: return make_tuple(0.196078, 0.6, 0.8);
        case VIOLETA: return make_tuple(0.309804, 0.184314, 0.309804);
        case AMARILLO: return make_tuple(1.0,1.0,0.0);
        case CYAN: return make_tuple(0.0,1.0,1.0);
        case MAGENTA: return make_tuple(1.0,0.0,1.0);
    }
}

void init(void){
    glClearColor(1.0,1.0,1.0,1.0);
    glMatrixMode(GL_PROJECTION);
    gluOrtho2D(0.0, 1200.0, 0.0, 800.0);
}

void drawString(string s, int x, int y){
    glColor3f(0.0, 0.0, 0.0);
    glRasterPos2i(x,y);
    for(char c : s){
        glutBitmapCharacter(GLUT_BITMAP_HELVETICA_12,c);
    }
    glColor3f(1.0, 0.0, 0.0);
}

void display(void){
    glClear(GL_COLOR_BUFFER_BIT);
    glColor3f(0.658824, 0.658824, 0.658824);
    int colX = 50;
    int colY = 600;
    int piso = 50;

    glBegin(GL_QUAD_STRIP);
        glVertex2i(colX, colY);
        glVertex2i(colX + 100, colY);
        glVertex2i(colX + 20, colY - 50);
        glVertex2i(colX + 80, colY - 50);
        glVertex2i(colX + 20, colY - (colY - 100));
        glVertex2i(colX + 80, colY - (colY - 100));
        glVertex2i(colX, piso);
        glVertex2i(colX + 100, piso);
    glEnd();

    glFlush();

    glColor3f(0.0 ,0.0, 0.0);
    glEnable(GL_POLYGON_STIPPLE);
    glPolygonStipple(fly);
    glBegin(GL_QUAD_STRIP);
        glVertex2i(colX, colY);
        glVertex2i(colX + 100, colY);
        glVertex2i(colX + 20, colY - 50);
        glVertex2i(colX + 80, colY - 50);
        glVertex2i(colX + 20, colY - (colY - 100));
        glVertex2i(colX + 80, colY - (colY - 100));
        glVertex2i(colX, piso);
        glVertex2i(colX + 100, piso);
    glEnd();
    glDisable(GL_POLYGON_STIPPLE);
    glColor3f(0.658824, 0.658824, 0.658824);
    colX = 1050;

    glBegin(GL_QUAD_STRIP);
        glVertex2i(colX, colY);
        glVertex2i(colX + 100, colY);
        glVertex2i(colX + 20, colY - 50);
        glVertex2i(colX + 80, colY - 50);
        glVertex2i(colX + 20, colY - (colY - 100));
        glVertex2i(colX + 80, colY - (colY - 100));
        glVertex2i(colX, piso);
        glVertex2i(colX + 100, piso);
    glEnd();

    glColor3f(0.0 ,0.0, 0.0);
    glEnable(GL_POLYGON_STIPPLE);
    glPolygonStipple(fly);
    glBegin(GL_QUAD_STRIP);
        glVertex2i(colX, colY);
        glVertex2i(colX + 100, colY);
        glVertex2i(colX + 20, colY - 50);
        glVertex2i(colX + 80, colY - 50);
        glVertex2i(colX + 20, colY - (colY - 100));

```

```

        glVertex2i(colX + 80, colY - (colY - 100));
        glVertex2i(colX, piso);
        glVertex2i(colX + 100, piso);
    glEnd();
    glDisable(GL_POLYGON_STIPPLE);

    glColor3f(0.658824, 0.658824, 0.658824);
    glBegin(GL_TRIANGLES);
        glVertex2i(50, colY);
        glVertex2i(600, 800);
        glVertex2i(1150, colY);
    glEnd();

    glColor3f(0.0, 0.0, 0.0);
    glEnable(GL_POLYGON_STIPPLE);
    glPolygonStipple(fly);
    glBegin(GL_TRIANGLES);
        glVertex2i(50, colY);
        glVertex2i(600, 800);
        glVertex2i(1150, colY);
    glEnd();
    glDisable(GL_POLYGON_STIPPLE);

    glColor3f(1.0, 1.0, 1.0);
    glBegin(GL_POLYGON);
        glVertex2i(600, 750);
        glVertex2i(550, 700);
        glVertex2i(600, 650);
        glVertex2i(650, 700);
    glEnd();

    glColor3f(0.0, 0.0, 0.0);
    glBegin(GL_POLYGON);
        glVertex2i(600, 720);
        glVertex2i(570, 700);
        glVertex2i(600, 680);
        glVertex2i(630, 700);
    glEnd();

    glPointSize(3);
    glColor3f(1.0, 1.0, 1.0);
    glBegin(GL_POINTS);
        glVertex2i(600, 700);
    glEnd();

    int limiteIzq = 150;
    int limiteDer = 1050;
    int limiteArr = colY;
    int limiteAbj = 50;
    int espacioX = limiteDer - limiteIzq;
    int espacioY = limiteArr - limiteAbj;

    int numeroPuntos = 20;
    int puntoX, puntoY;
    int color;
    float R, G, B;

    glColor3f(0.0, 0.0, 0.0);
    glBegin(GL_LINE_LOOP);
        glVertex2i(limiteIzq, limiteAbj);
        glVertex2i(limiteIzq, limiteArr);
        glVertex2i(limiteDer, limiteArr);
        glVertex2i(limiteDer, limiteAbj);
    glEnd();

    glBegin(GL_QUAD_STRIP);
    glVertex2i(limiteIzq, limiteArr);
    glVertex2i(limiteDer, limiteArr);
    for(int i = 0; i < numeroPuntos; i++){
        for(int j = 0; j < 2; j++){
            puntoX = rand() % espacioX + limiteIzq;
            puntoY = rand() % espacioY + limiteAbj;
            color = rand() % (MAGENTA + 1);
            tie(R, G, B) = getColor(color);
            glColor3f(R, G, B);
            glVertex2i(puntoX, puntoY);
        }
    }
    glVertex2i(limiteIzq, limiteAbj);
    glVertex2i(limiteDer, limiteAbj);
    glEnd();

    glFlush();
}

int main(int argc, char **argv){
    srand (time(NULL));
    glutInit(&argc, argv);
    glutInitDisplayMode(GLUT_SINGLE | GLUT_RGB);
    glutInitWindowSize(winWidth, winHeight);
    glutInitWindowPosition(100, 100);

```

```
glutCreateWindow("Programa Primitivas");  
init();  
glutDisplayFunc(display);  
  
glutMainLoop();  
return 0;  
}
```




Figura 5: Resultados