

Pseudo Code:

```
page_fifo.cpp X
page_fifo.cpp > main()
1  #include <bits/stdc++.h>
2  using namespace std;
3
4  int main() {
5      int pages[100], frames[100];
6      int n, f;
7
8      cout << "Enter number of pages: ";
9      cin >> n;
10
11     cout << "Enter page reference string: ";
12     for (int i = 0; i < n; i++) {
13         cin >> pages[i];
14     }
15
16     cout << "Enter number of frames: ";
17     cin >> f;
18
19     for (int i = 0; i < f; i++) {
20         frames[i] = -1;
21     }
22
23     int miss = 0, hit = 0;
24     int idx = 0;
25
26     for (int i = 0; i < n; i++) {
27         int found = 0;
28
29         // HIT
30         for (int j = 0; j < f; j++) {
31             if (frames[j] == pages[i]) {
32                 found = 1;
33                 hit++;
34                 break;
35             }
36         }
37     }
```

```

37
38     if (found == 0) {
39         // MISS
40         frames[idx] = pages[i];
41         idx = (idx + 1) % f;
42         miss++;
43         cout << "Page " << pages[i] << " -> FAULT -> ";
44     } else {
45         cout << "Page " << pages[i] << " -> HIT -> ";
46     }
47
48     // Page Status
49     for (int j = 0; j < f; j++) {
50         if (frames[j] == -1)
51             cout << "-1 ";
52         else
53             cout << frames[j] << " ";
54     }
55     cout << endl;
56 }
57
58 cout << "\nPage Miss = " << miss << endl;
59 cout << "Page Hits = " << hit << endl;
60
61 return 0;
62 }

```

Input/Output:

```
C:\WINDOWS\system32\cmd.  X  +  v

Enter number of pages: 7
Enter page reference string: 1 3 0 3 5 6 3
Enter number of frames: 3
Page 1 -> FAULT -> 1 -1 -1
Page 3 -> FAULT -> 1 3 -1
Page 0 -> FAULT -> 1 3 0
Page 3 -> HIT -> 1 3 0
Page 5 -> FAULT -> 5 3 0
Page 6 -> FAULT -> 5 6 0
Page 3 -> FAULT -> 5 6 3

Page Miss = 6
Page Hits = 1

Press any key to continue . . . |
```