CLAMS - The Quest for Portability and Audio

# CLAMS - The Quest for Portability and Audio Forth Day 2024

M. Edward (Ed) Borasky

2023-11-16

# Previously on CLAMS

#### The original concept - early 2022

- Forth for the Electro-Smith Daisy Seed
  - https://electro-smith.com/products/daisy-seed
  - Microcontroller board designed for digital music
  - ARM Cortex-M7 MCU, running at 480MHz
  - ► Hardware floating point and DSP instructions
  - 64MB of SDRAM for up to 10 minute long audio buffers
  - ► 8MB external flash
  - Stereo audio output 96kHz / 24-bit audio hardware
  - No WiFi or Bluetooth
  - ▶ \$29.95US quantity one
  - Available in various packaged modules
  - User interface and synthesis both done in Forth

### Revised concept - early 2023

- Forth for the Raspberry Pi Pico (WH)
  - https://www.raspberrypi.com/documentation/ microcontrollers/pico-series.html
  - Microcontroller board designed for general applications
  - ▶ Dual-core ARM Cortex-M0+, running at 133 Mhz
  - Co-processor for division, interpolation and I/O
  - No floating point or DSP instructions
  - 262KB RAM
  - 2 MB flash
  - No SD card
  - ▶ No audio hardware, I2S audio expansion packs available
  - 2.4 GHz WiFi and Bluetooth
  - ▶ \$7.00 US
  - User interface and synthesis both done in Forth

# Stepping up a level - what does a digital synthesizer need?

- Accurately-timed PCM samples
- Digital-analog conversion for recording / performance
- ► A user interface for the composer / performer

## Previous concepts problem 1: Lack of portability:

- Need to hand-port Forth to individual MCUs
- Other desirable boards:
  - Raspberry Pi Zero 2 W
  - (https://www.raspberrypi.com/products/raspberry-pi-zero-2-w/)
  - Teensy 4.1
  - (https://www.pjrc.com/store/teensy41.html)
  - ► ESP32-S3, -C3 and -C6
  - (https://www.espressif.com/en/products/socs/esp32)

# Previous concepts problem 2: Limited audio capability

- Limited audio capability
  - Only built-in DAC or I2S audio is practical in Forth
  - Other desirable interfaces:
    - Class-compliant USB audio and MIDI
    - Bluetooth audio and MIDI
    - Specs too complex for easy Forth implementation

CLAMS - The Quest for Portability and Audio  $\$  CLAMS - The New Design

# CLAMS - The New Design

## Arduino or Linux for portability

- Target MCU boards all have Arduino support
- Raspberry Pi Zero 2 W has Linux support
- ► I2S audio is supported on all boards
  - ▶ DAC is either onboard or expansion hardware
- ▶ Bluetooth audio is supported on boards with hardware
- USB MIDI is supported on all boards
- USB audio is supported on Teensy and Zero 2 W
  - Others in alpha testing

## Shore Pine Sound Systems AMY synthesizer

- Open source on GitHub (shore pine sound systems 2024a)
- Highly portable written in C
- Has Arduino library
- Has a Python interface for both Linux and MCUs
- ► Handles synthesis and I2S audio
- Very capable synthesizer saves me months of Forth coding!
- Heart of the Tulip Creative Computer (shore pine sound systems 2024b)

CLAMS - The Quest for Portability and Audio  $\hfill \Box$  Forth base: C3

Forth base: C3

#### C3 Forth

- Open source on GitHub (Christopher Curl 2024a)
- ► Token-threaded Forth written in C/C++
- Runs on Linux (native), Raspberry Pi Pico and Teensy 4.1 (Arduino)
- Under active development
- Well-documented

#### Bonus Forth content - C4!

- Open source on GitHub (Christopher Curl 2024b)
- Uses concepts from Tachyon Forth and colorForth
- Arduino support in progress!

CLAMS - The Quest for Portability and Audio
Road map - Tasks mostly in Priority Order

Road map - Tasks mostly in Priority Order

# Integrate C3 and AMY on Raspberry Pi Zero 2 W

- Devlopment cycle is easier on Linux
- Linux USB audio and MIDI are well understood
- Many supportingsoftware tools available
- Total hardware cost is \$54.00US
- https://vilros.com/products/vilros-raspberry-pi-zero-w-2-port-n-play-ready-to-use-kit

#### Make an album

- Adding AMY synthesizer has shortened development time
- ▶ The dogfooding process will hone the Forth user interface

## Integrate C3 and AMY on Pico I2S

 Backporting of album to small system will stress-test the system

## Integrate C3 and AMY and USB audio on Teensy 4.1

- ► Teensy has no native I2S / DAC hardware
- Teensy does have native USB audio and MIDI in Arduino
- ► More powerful MCU than the Pico

## Add CLAMS to Experimental Music Toolbox

- Another project of mine
- Open source on GitHub (AlgoCompSynth by znmeb 2024)
- ► Collection of open source tools for experimental music

CLAMS - The Quest for Portability and Audio Road map - Tasks mostly in Priority Order

# Longer range

- ► Electrosmith Daisy port
- ► ESP32 port
- ► USB MIDI
- ► USB audio on non-Teensy boards

# **Back Matter**

#### CLAMS on the web

- GitHub: https://github.com/AlgoCompSynth/CLAMS
- blog: https://www.algocompsynth.com/#category:CLAMS
- this presentation: https://github.com/AlgoCompSynth/ CLAMS/blob/main/presentations/CLAMS-quest.pdf

CLAMS - The Quest for Portability and Audio

#### Me on the web

- ► Mastodon: https://ravenation.club/@AlgoCompSynth
- ► LinkedIn: https://www.linkedin.com/in/znmeb
- ► Bandcamp: https://algocompsynth.bandcamp.com

#### References

- AlgoCompSynth by znmeb. 2024. "Experimental Music Toolbox on GitHub." https://github.com/AlgoCompSynth/Experimental-Music-Toolbox; AlgoCompSynth by znmeb.
- Christopher Curl. 2024a. "C3 on GitHub." https://github.com/CCurl/c3/; Christopher Curl.
- ——. 2024b. "C4 on GitHub." https://github.com/CCurl/c4/; Christopher Curl.
- shore pine sound systems. 2024a. "AMY Synth on GitHub." https://github.com/shorepine/amy; shore pine sound systems.
- ———. 2024b. "Tulip Creative Computer on GitHub." https://github.com/shorepine/tulipcc; shore pine sound systems.