

Processed Text

advance smart material application aerospace industry alarshbasheer
departmentofmechanicalandaerospaceengineering stateuniversityofnewyork buffalo newyork usaand
researchanddevelopmentdivision oetikerinc lancaster buffalo newyork usa abstract purpose smartmate
rialsalsocalledintelligentmaterialsaregainingimportancecontinuouslyinmanyindustriesincludingaerospac
eone itis unique feature material asself sensing self adaptability memory capabilitiesand manifold
function long time thereisnoreviewofsmartmaterials therefore
itisconsideredworthwhiletowriteareviewonthissubject design methodology approach
athoroughsearchoftheliteraturewascarriedoutthroughscifinder sciencedirect springerlink wileyonline
libraryandreputedandpeer reviewedjournals theliteraturewascriticallyanalyzedandareviewwaswritten
finding
thisstudydescribestheadvancesinsmartmaterialsconcerningtheirapplicationsinaerospaceindustries
theclassification working principleandrecentdevelopments nano smartmaterials
ofsmartmaterialsarediscussed besides thefutureperspectivesofthesematerialsare alsohighlighted
muchresearchhasnotbeendoneinthisarea whichneedsmoreextensivestudy originality value certainly
thisstudywillbehighlyusefulforacademicians researchersandtechnocratsworkinginaerospaceindustries
keywords smart intelligent material classification application nano smartmaterials futureperspectives
papertypeliteraturereview 1 introduction temperature stress magnetic field chemical electricity nuclear
radiation acidity hydrostatic pressure itis interesting note thenumberof passenger change may size
shape object rigidity approximately doubled 2036 totaling 7 8 billion yearly restrainingandviscosity
schwartz 2002 allthesealterations perinternationalairtransportassociation tocompletethis
areresponsibleforprovidingthevariousnecessaryfunctionsof requirement aerospace industry supposed
great smart material per environmental change effort continuously july 2018 airbus predicted need
common smart material related stimulus response approximately 37 400 new aircraft 5 8tn cost
showninfigure1 next 20years matthew 2018 huge smart material also called intelligent one
numberofpassengersandthedemandfortheaircraft thereisa intellectual performance great need
advanced technology meet environmentalvariations thesmartnessofthesematerialslied requirement
economically safety among various part fact manifold application structural
componentsoftheaerospaceindustries thematerialisoneof aerospace bionics mechanical environment
engineering themostimportant component many typesofmaterials bashir 2017 addington daniel 2005
besides beingusedinaerospaceindustriesbutthesmartmaterialsare
materials candetecttheerrorsandfissuresandareworkingas gaining importance continuously unique
diagnostictoolsand consequently self repairingcapabilities feature basically smart material new
generation calledaself repairingeffect inaerospaceengineering mostof constituent exceeding
conventional functional theapplicationsarecarriedoutintheopenenvironmentwith structural material
material called smart one exposure various change hence smart material self sensing self adaptability
memory gaininggreat attention aerospace industry way capability manifold function ritter 2007 self
thereisagreatdemandforsmartmaterials relatedstructuresand adaptation feature smart material great
value instrumentsintheaerospaceindustries athoroughsearchofthe embedding adaptation smart
material nowadays literature carried article found great demand smart material various advancement
smart material aerospace industry industry capability alter physical duringthepastdecade
itwasalsorealizedthattherearesome property precise way reaction change
advancesinthesmartmaterialsinaerospaceindustriesduringthe environmental factor stimulus response
factor pastfewyears therefore theeffortsaremadetowriteanarticle
onthelatestdevelopmentsandapplicationsofsmartmaterials in theaerospaceindustries
thisarticledescribestheclassification thecurrentissueandfulltextarchiveofthisjournalisavailableonemerald
insightat <http://www.emerald.com/insight/1748-8842.htm> working principle application recent
development nano smart material future perspective certainly article
aircraftengineeringandaerospacetechnology 92 7 2020 1027 1035 received10march2020
emeraldpublishinglimited issn1748 8842 revised23april2020 doi 10 1108 aeat 02 2020 0040
accepted28april2020 1027advancesinthesmartmaterialsapplications

aircraft engineering and aerospace technology alarshbasheer volume 92 number 7 2020 1027 1035
 figure 1 the common smart materials and related stimulus responses lead zirconate titanate pzt lead
 magnesium niobate polyvinylidene fluoride polymer piezoelectric material pbzr_{0.52}ti_{0.48}o pzt bi_{0.3}ti_{0.3}bit_{0.4}
 3 12 pzt bit composite frequently presented thin sheet may easily anchored fixed composite
 structures or loaded to form separate piezoelectric actuators 2 2 magnetostrictive materials material reacting
 change magnetic properties these materials are mono polar and non linear showing hysteresis lesser
 piezoelectric material these materials undergo mechanical strain and work as actuators and sensors
 these materials produce low strains and modest forces across a varied frequency range these are
 the best materials for the actuators because of the required coil highly useful academician researcher
 magnetic return path generally material contain technocrats working in the aerospace industries
 sensors and actuators and are of nickel iron and cobalt briefly material work permanent magnetic bars
 the major 2 classification of smart materials application material include motor hydraulic classification
 smart material based actuator small frequency high power sonar transducer best known
 magnetostrictive material terfenol property important property exploited
 which longates on exposing to the magnetic field thermal electric magnetic etc smart material classified
 per approach adding ton schodek ritter material classified based change 2 3 thermo responsive materials
 material reacting change occurring in shape phase color energy matter adhesion and temperature
 material also called temperature rheology possible discuss material responsive generally polymer show
 classification important material used miscibility gap temperature composition diagram
 aerospace industries are discussed in brief material shape memory polymer shape memory alloys smas
 and can be changed in different shapes 2 1 piezoelectric materials by changing temperature
 nitinol is a nickel and titanium alloy these are the materials reacting against the change in electric work anti
 corrosion comparable stainless steel property these are relatively linear at low fields and bipolar useful many
 application major application positive negative strain exhibiting hysteresis
 types of alloys are in superelastics spectacle frames and hot pot material polymeric ceramic type thermostat
 major application include thermostat air property wide bandwidth electromechanical response vehicle
 shock absorbers breaks and automotive dampers high generative force comparatively low power
 requirement these materials undergo mechanical alterations 2 4 shape memory alloys changing electric
 field figure 2 produce smas material belonging thermo responsive voltages when stress is applied
 contrarily if voltage is applied material class material react response stress is produced the materials
 consequently structure temperature change shape changing made material bent expand fold
 temperature they deform to their martensitic conditions and applying voltage
 these have good applications in the magnetic regain their original shape to their austenite conditions when
 head optical tracking device dot matrix printer high heated
 the remarkable feature of these materials is their large frequency stereo speakers computer keyboards
 microphone change modulus elasticity heating phase transducer sensor actuator igniter gas grills
 change temperature e two four time low temperature
 most widely used piezoelectric materials are piezoceramics e.g. value
 a variety of alloys have been found to show this effect by recurrent heat treatment example nitinol ni ti figure 2
 piezoelectric materials showing the exchange of electrical and alloy niticu cualni cuznal fe pt au cd
 mechanical energy 1980s and early 1990s some companies started to produce ni ti material different
 component many product desroches 2002 these are the best materials for manufacturing actuator option
 attaining large displacements and excitation forces these materials are available the standard stock wire
 rod tube spring band strips and sheets 2 5 electrostrictive materials piezoelectric material mechanical
 change directly proportional square electric 1028 advances in the smart materials applications
 aircraft engineering and aerospace technology alarshbasheer volume 92 number 7 2020 1027 1035 field
 these are also very sensitive to temperature but show tiny acidity mechanical load response smart hysteresis
 in these materials the dislocations are always in the material observed term change shape viscosity
 direction important example magnesium composition color etc fundamentally smart structure niobate
 it requires an electric field to cause induced stress and include five key essential e structural material
 distributed induced stress ability piezoelectric material sensor actuator power conditioning electronics
 these are available in the form of stacks which may be used to control strategy material work changing
 for many devices easily physical property first smart material transformation

observation was recorded in 1932 on gold cadmium later on Hodgson Brown 2000 observed transformation
 2.6 rheological materials shape memory effect nickel titanium alloy naval
 these are liquid materials reacting against the change in electric or ordinary laboratory magnetic property
 also termed electro rheological fluid and magneto rheological fluids as per the changes basically material
 may exist two different phase various temperature austenite exists high
 because of change in electric and magnetic fields the reactions of temperature and martensite
 exist at low temperature these materials against stimuli are very fast the changes are in the
 two phase structure transform into each other at the external temperature dynamic liquid solid phase major
 application stress condition alters besides martensite exists two include shock absorbers
 breaks and automotive dampers different form e twinned detwinned figure 3 smart material show special
 feature 2.7 photochromic materials these are the materials reacting against the change in the optical property
 major application include liquid crystal figure 3 the different phases of smart materials display lithium
 battery electrochromic device the most important photochromic materials are spiropyranes
 naphthopyranes spirooxazines chromenes spirodihydro indolizines fulgides diarylethenes
 bacteriorhodopsin azo compound the different types of smart materials with input
 and output are given in table 1.3 working in the smart materials fundamentally the smart materials act
 against certain effect such as electricity pressure temperature light magnetic fields table 1
 the different types of smart materials with input and output sl types of smart materials input output type 1
 property changing 1 mechanochromics twist color variations 2 electrochromics electric potential variations
 color variations 3 photochromics light radiation color variations 4 thermochromics temperature changes
 color variations 5 liquid crystals electric potential variations color variations 6 chemochromics
 chemical quantities color variations 7 suspended particles electric potential variations color variations 8
 magneto rheological electric potential variations stiffness and viscosity variations 9 electrorheological
 electric potential variations stiffness and viscosity variations type 2 energy exchanging reversible 10
 piezoelectric deformation electric potential difference 11 thermoelectric temperature difference
 electric potential difference 12 pyroelectric temperature difference electric potential difference 13 magneto
 restrictive magnetic field twist 14 electro restrictive electric potential difference twist type 2
 energy exchanging reversible 15 photoluminescence radiation light 16 electroluminescence
 electric potential difference radiation light 17 thermoluminescence radiation light 18 chemoluminescence
 radiation light 19 light emitting diodes electric potential difference radiation light 20 photovoltaics radiation
 light electric potential difference 10.2.9 advances in the smart materials applications
 aircraft engineering and aerospace technology alarsh basheer volume 92 number 7 2020 1027 1035
 transformation super elasticity effect shape 3.4 active structures memory effect and two way memory effect
 the super elasticity structure distribution material also significant property integrated sensor actuator
 load bearing hysteretic damping excellent fatigue properties very dependable capacity i.e.
 structural functionality energy dissipation ability repeatable phase conversion
 and good corrosion resistance the austenite occurs at low stress 3.5 intelligent smart structures converted
 detwinned martensite high stress these are the structures having a sub set of active structures figure 4
 depicts a usual stress strain curve of smart materials these are used for the extremely integrated control
 logic and two phase figure 4 b depicts stress strain power electronics
 relationship of the usual phase changes of super elasticity smart materials under pressure
 the upper plateau shows an alteration 4 application
 from austenite to martensite in pressure while the lower plateau application smart material structure
 shows the reverse phenomenon with pressure release the super elasticity material also significant property
 increasing continuously various sector civil structure automotive systems robotics systems space vehicles
 hysteretic damping fatigue property reliable energy rotary wing aircraft fixed wing aircraft machine tools
 marine intemperance capability via repeatable phase transformation and systems and medical systems
 the increased uses are through excellent resistance to corrosion technological revolution actuator sensor
 damping case piezoelectric material transducer
 between mechanical stress and electricity property is because of vibration shock absorption shape control
 stability the crystalline structure in a crystal each molecule is polarized damping increase structural integrity
 operational one end negatively charged positively maintenance automatic switch image processing
 charged e just like a dipole this arrangement is affected by

coatings because of special features of these materials such as the changes in the mechanical stress and electric field leading self adaptation self sensing self adaptability memory transducer property briefly simple piezoelectricity multiple functionalities these materials can detect faults and concept alter alignment polarization crack hence useful diagnostic tool molecule it is well known that smart structures are made of materials may be used to repair the fault during any mechanical different combination smart material basically operation the phenomenon is called the self repairing effect smart structure involve distribution actuator liang and rogers 1992 ghandi 1995 soroushian and hsu sensor processor control logic power electronics 1997 lagouda et al 1999 of course these materials have a various smart structures are discussed below wider range of applications but in this article the efforts will be made to restrict their applications in aerospace industries only

1 adaptive structures

the features of aircraft applications are given in table 2 while these are the structures having the distribution of the actuators table 3 summarizes various smart materials used in aerospace to change the characteristics in a prescribed way they include industry conventional aircraft wing aileron flap rotor the aerospace industries are facing greater economic pressure blades with servo flaps to lower down the costs with augmenting the performance and sustaining important protection standard therefore defense commercial airline space exploration industry

2 sensory structures

are researching smart materials for these purposes these should these are the structures having the distribution of the sensors consistent robust meet requirement highly screen characteristic structure e strain specialized application smart material good temperature electromagnetic property displacement industrial commercial application engineering damage and acceleration applications may be categorized into sensors sensing devices and motors and actuators the smartness of these materials is

3 controlled structures

developed by changing their compositions special processing these are the structures having the distribution of the sensors inducing defects and modification of microstructures actuator used actively regulate smart material used load bearing characteristics of the structure actuator composite structure aircraft wing and rotor blades lian et al 1996 garner et al 1999 jardine figure 4 strain stress relationship of austenite and martensite et al 1996 smart material used over power vibration variation helicopter rotor blade shape smart material actuated rotor technology is being used boeing reduces 80 vibration improving flight performance airbus helicopter sa formerly eurocopter group also developed similar system similarly various adaptive regulators surfaces are produced for airplane wing also recently research going emphasize the new control techniques for smart materials and design procedure location actuator sensor the other applications deal with the ability to regulate

1030 advances in the smart materials applications

aircraft engineering and aerospace technology alarshbasheer volume 92 number 7 2020 1027 1035 table 2 the features requirements and the effects of aircraft applications

1 requirement applicability effect

1 lightweight all aerospace schemes and semi monocoque fabrication thin

walled boxes or reinforced structures program use of low density materials wood alloys and composites high strength weight and high stiffness weight

2 passengers safety passengers carriers

use of fire retardant materials extensive testing crashworthiness

3 high reliability all aerospace schemes and strict quality control program extensive testing for consistent data certification proof of design

4 degradation radiation and thermal spacecraft damage issues and lifespan and extensive testing for varied environment thin materials with high reliability

5 sturdiness exhaustion and corrosion aircraft extensive exhaustion testing analysis alloys do not have exhaustion limit corrosion inhibition plans

6 aerodynamic presentation reusable spacecraft deformed shape aero elasticity dynamic compound contoured shapes manufacturability molding and machining

7 aerodynamic presentation aircraft greatly complex loading thin bendable wings and regulating surface

8 weather operation aircraft lightning protection erosion resistance

9 multi role functions all aerospace schemes and efficient design program composites with varied functions

10 fly wire fighter and passenger configuration control exchanges aero servo elasticity aircraft wide use of computers and electronics electromagnetic shielding

11 stealth specific military aerospace specific surface and shape of aircraft us stealth coating table 3 various smart materials used in aerospace industries

1 requirement material purpose

design of smart materials for magneto responsive materials cyclic and active control actuators for rotor control
 lead to reduced maneuver envelope because of weight and volume constraints 2
 control panel as extending wings smart materials to solve limits of aircraft wing design of aircraft 3 shape
 changing technology shape altering smart materials for military aircraft next to new generation aircraft 4
 shape changing technology smart materials
 engineering bending and stretching abilities in wings and hingeless systems 5 shape changing technology
 piezoelectric engineering bending and stretching abilities in wings and hingeless systems the aero
 elastic form of an aircraft wing to decrease the pull and temperature variation used manufacture increase
 working efficiency regulate vibration satellite various aircraft part fuel line assembly lightweight structure
 observe structural reliability thermocouples and gas turbine engines alumina is used to
 space structures and aircraft make aircraft part thermal shock resistance high
 the piezoelectric and dielectric materials electroceramic temperature occur plasma ignition besides
 material used make aerospace sensor alumina is lightweight and decreases the costs related to
 transducer gyroscope accelerometer launching satellite piezoelectric actuator may gyroscope used
 measuring pitch aircraft execute team mechanism of the control system by increasing the acceleration satellite
 missile accelerometer maneuverability and performance owing to good flexibility used vibration
 measurement sensor used besides material used reduce vibration to measure the level of fuel tanks
 for example boeing 777 and noise in the aircraft the ceramic fibers are used as heat piezo ceramic material 60
 ultrasonic fuel tank shields for fire protection thermal insulation in aircraft
 smart ceramic materials are used in aircraft because of their space shuttle resist heat
 capability to bear high vibration and mechanical shock and lightweight corrode significant
 1031 advances in the smart materials applications aircraft engineering and aerospace technology
 alarshbasheer volume 92 number 7 2020 1027 1035 characteristics include high melting temperature
 resiliency combination nanomaterials property smart tensile strength chemical inertness besides
 aircraft material features are the best combination to achieve the heights
 windshields are heated by a transparent electric conducting success material create innovation aerospace
 ceramic coating embedded glass keep clear engineering for example
 the body of aircraft and satellites made from fog and ice of a nano smart material could possibly
 alter the surface texture smart materials used overcome limit normal depending temperature pressure electric
 current airplane wing designs generally wings for high speeds fail to feature smart nanomaterials especially
 composite work low speed vice versa smart materials integration
 comprising sensors and actuators in the layers of composites may airplane wings may solve this problem
 the smart materials have a good detect any crack in the aircraft the smart nanomaterials can be future used wing
 structure minimize prepared layered composition printed circuit board
 aerodynamic losses and to maximize speed wing concordance technique in h. n. chang 2004 developed sort
 may exploited sound reduction load reduction
 technique using smart layer to detect and monitor hidden fatigue meet motion necessity helicopter dong
 crack growth using built piezoelectric sensor actuator et al 2008
 reported the application of smart materials as an actuator for network similarly akhbar 2012 used smart and nano system
 an adaptive airfoil smart springs are used to actuate precisely for applications in non
 destructive evaluation and perspectives point skin reach target airfoil system actuator stimulate
 composite material observed that smart materials could get good actuating results based on
 produce waves when a crack is developed these waves are sensed the simulation studies similarly
 hutapea et al 2008 reported and detected by the pilot for alarming the necessary action
 as a sample of smart actuation structure for an adaptive airfoil by smart materials are being made in a nano
 frame for wings for flapping in regulating the flaps smart springs were stationary at one terminal
 manners similar to birds figure 5 li et al 2009 described the
 to the wing box toward the primary edge of the airfoil whereas the different way prepare polymer modified gold
 nanoparticles other end was involved tangentially to a revolving cylinder fixed author studied thermal ph
 sensitivity to the flap the spring actuators were controlled by supplying a nanomaterials may important
 designing developing applied current as per the authors the sample prepared showed future nano
 electronics nano sensor author described a study prospective for future uses change morphology gold
 nanoparticles ph change response figure 6 5 nanotechnology and smart materials kuilla et al 2010

prepared graphene based piezoresistive smart nanomaterial tested piezoresistive feature course nanotechnology emerged independent finding possible application graphene based research area ali 2012 2018 but recently there is growing sensor author compared result cnts strain interest apply nanotechnology smart material sensor per author observed strain augment performance new design response of the graphene epoxy sensor was better than cnts application nanotechnology is a tool to take smart materials also symmetrical along reversible behavior next level nanotechnology enabled smart material furthermore graphene composite exhibited higher exhibit superior performance function coyle et al gauge factor than strain gauge made of high quality graphene 2007 stimulus response nanomaterials better film high gauge factor may larger inter conventional smart material small size contact area among the graphene nano fillers because of their surface active site sometimes larger surface area two dimensional structure csetnek et al 2006 develop new dahman et al 2017 these features sense the change in the environment even at low magnitude the advantages of smart figure 5 embedding smart nanomaterials composite and nano materials are as given below structure using printed circuit technology cid 1 optimization of the responses of complex systems this is carried creating early cautionary system increasing range survivability situation giving adaptive response manage unexpected situations and conditions cid 1 minimizing alteration response augmenting exactness providing good control system might lead improving design performance for special applications cid 1 improvement functionality system appropriate defensive maintenance presentation optimization cid 1 noteworthy influence engineering processing technique cid 1 improvement in the health monitoring of the system and good control of its dynamic and addictiveness cid 1 feature open entry use nano smart material multifold application aerospace industry 1032 advances in the smart materials applications aircraft engineering and aerospace technology alarshbasheer volume 92 number 7 2020 1027 1035 figure 6 change in morphology of gold nanoparticles composite gel membrane nano channel exfoliated graphite nano platelet xgnps nano graphene regulate membrane permeability response external platelet ngps author prepared sheet various stimulus increased temperature membrane lateral dimension length using different composition permeability increased the channel have a well ordered array combination material showed piezoresistive of the magnetic polystyrene latex particles which underwent to characteristics and indicated a variation in electrical resistance on alteration in volume in reaction to outside stimuli ventura et al applying the strain the dependence resistance variation on strain 2017 described stimulus responsive material digitization via were directional nature different mixture of xgnps size integration network conductive nanomaterials mwcnt length mwcnt xgnp ngp ratio showed elastomer matrix the sensors wide range of detection various specific surface area nanoparticle interaction ability become promising author monitored rate authors claimed these serving as important factors for regulating and degree of material sexpansion down hole such as ins and sensitivity hybrid sheet sensitivity inversely screen packer author claimed developed proportional to the thicknesses of the sheets approach may be used to detect degradation tool deployment status and chemical detection besides it was observed that the 5 1 synthesis of nano smart materials author claimed the detection the presence water oil smart nanoparticles produced physical process precise chemicals using their work based manufacturing particle pre synthesized hwang et al 2013 reported preparation nano smart polymer cross linking among polymer core material multi walled carbon nanotube mwcnts second method chemical synthesis nanoparticles table 4 the advantages and disadvantages of the synthesis of nano smart materials sl method advantage disadvantage reference 1 microwave reduced reaction or synthesis sometimes poor dispersion liu et al 2007 time small particles sized dispersal 2 electron beam lithography well managed inter particle high complex paraphernalia lin and samia 2006 spacing 3 gas phase deposition practical approach size control of nanoparticles cuenya 2010 4 supercritical fluids good control of nanoparticles need critical temperature and pressure zhang and erkey 2006 no use of toxic chemicals 5 pulsed laser ablation laser ablation facile and simple method low manufacturing rate zenget al 2012 in liquid geometry control possible no need of any other chemical 6 flow injection reproducible and homogeneous continuous mixing of solvents salazar alvarez et al 2006 7 biological microbial incubation reproducible scalable good time consuming narayanan and saktivel 2010 yield and low cost 1033 advances in the smart materials applications aircraft engineering and aerospace technology

alarshbasheer volume92 number7 2020 1027 1035 heterogeneous polymerization method discussed
 the smart nanomaterials may be used in smart materials these may be highly useful material changing shape wing
 flapping the need for smooth and economic performance 5 1 1 polymer adsorption on nanoparticles smart
 nanomaterials need future this is the classical and simple method for the preparation of
 should be prepared in a more advanced way to meet the needs stimulus responsive nanoparticles
 in this approach a polymer is future aerospace technology future looking
 sorbed on the particle surface and it controls interactions in the automatic damage arrest shock absorber self
 healing colloidal suspension owing different effect electrostatic thermal mitigation nano smart material
 nano steric depletion bridging and mechanisms smart material highly beneficial useful future 5 1
 2 amphiphilic block copolymers and micelles self assembly space mission certainly help make dream block
 copolymer make different type self assembled true nano smart material new one thus arrangement
 micelle constant bilayers subject industrial product available market solvent selectivity swelling packing
 particle patent restriction may take many year occurred solvent compatibility common proposed
 nanomaterial go conception desired physical deviations within the particles are in the collective size
 application the change to the collective architecture structure and stimuli response to ionic strength pH
 thermal and redox stimuli are 7 conclusion among those which are usually measured most examples are of
 shear flow ionic exchange and osmotic shock the advantages
 the development of smart materials is an interdisciplinary area and disadvantages of the synthesis of nano
 smart materials are smart materials are the new generation materials which have summarized in table 4
 great latent to introduce a revolution in many areas including aerospace industry manufacturing nano smart
 6 future perspectives material understanding working mechanism improve property application
 aerospace the smart materials are probably to be the most recent opening industry nano smart material
 highly useful humankind significant leap hopeful future space mission may starting material
 century will be dominated by a wide variety of smart materials initiate life on other planets
 these smart materials are the hope these will be the frontier materials in the aerospace industries future
 certainly enhance quality there is a need to develop smart materials for manufacturing living true revolution
 aerospace industry air vehicles with the capabilities of altering their shapes as per collaborative effort
 necessary among academicians requirement specification also great researcher engineers and designers
 demand elastomeric matrix material cmt structure morphing technology property smart material accept
 challenge aerospace industry therefore reference research smart material promising field certainly
 adding ton and daniel I 2005 smart materials and the market for smart materials will increase in the future
 new technologies elsevier importance smart material attract researcher akhras g 2012 smart and nano
 system applications for toward solving aerospace engineering problem innovative and perspectives
 4th international candu in service research expected making control surface adaptive wing may
 significantly augment inspection workshop ndt canada 2012 conference maneuverability great need
 develop compact toronto ontario june 18 21 smart materials for controlling noise and vibration control ali
 2012 new generation adsorbent water despite great demand future application smart treatment
 chemical review vol 112 10 material certain challenge development pp 5073 5091 smart material
 quality inexpensiveness ali 2018 microwave assisted the economic synthesis of researcher supposed
 improve quality without multi walled carbon nanotubes for arsenic species removal in increase in cost still
 there is a need to make smart structures water batch column operation journal molecular feasible
 developing excellent smart material ease liquid vol 271 pp 677 682 anchoring laminated structure
 coupling bashir 2017 smart materials and their applications in mechanical electrical property increase
 performance civil engineering an overview international journal of civil low price advance microelectronics
 information engineering and construction science vol 4 pp 11 20 processing and sensor technology coyle
 wu lau k derossi wallace g g nowadays nanotechnology is gaining importance in almost diamond 2007
 smart nano textile review every sphere life oil gas industry already us material application mr bulletin
 vol 32 5 stimulus responsive nano smart material numerous pp 434 442
 technologies including swellable elastomers in reactive packers csetneki filipcsei g zrinyi 2006 smart heat
 fluid activated expandable screen smart nanocomposite polymer membrane switching environmentally
 sensitive nano hydrogel ability control macromolecule vol 39 no 5 pp 1939 1942 sense change pH
 temperature concentration cuenya b r 2010 synthesis catalytic property
 metabolite can release their load as a result of such a change metal nanoparticles size shape support

composition 1034 advances in the smart materials applications
 aircraft engineering and aerospace technology alarshbasheer volume 92 number 7 2020 1027 1035
 oxidation state effect thin solid film vol 518 12 liang c davidson f schetky l straub f k pp 3127 3150 1996
 application torsional shape memory alloy dahman kamil baena 2017 smart actuator active rotor blade
 control opportunity nanomaterials dahman ed nanotechnology limitation
 spie proceedings of mathematics and controls in functional materials for engineers elsevier smart structures
 vol 2717 pp 91 100 desroches r 2002 application of shape memory alloys in liang c rogers c 1992 one
 dimensional seismic rehabilitation of bridges technical report nchrp thermomechanical constitutive relation
 shape memory idea project 65 feb material journal intelligent material system dong boming z jun l 2008
 changeable structure vol 1 no 2 pp 207 234 aerofoil actuated by shape memory alloy springs material lin x
 and samia c 2006 synthesis assembly and science and engineering vol 485 nos 1 2 pp 243 250 physical
 property magnetic nanoparticles journal garner l j wilson l n lagoudas c and rediniotis magnetism
 magnetic material vol 305 1 k 1999 development of a shape memory alloy actuated pp 100 109 biomimetic
 vehicle smart material structure vol 9 liu z ling x guo b hong l and lee j 2007 5 pp 673 683
 pt and p trun nanoparticles deposited on single wall carbon ghandi k 1995 shape memory ceramic actuation
 nanotubes for methanol electro oxidation journal of power adaptive structures master thesis mit source vol
 167 no 2 pp 272 280 hodgson e and brown j w 2000 using nitinol alloys matthew p 2018 current emerging
 trend report of shape memory applications in aerospace sector shifting priority developing hutapea p kim
 j guion hanna c heulitt n technology shaping industry today 2008 development of a smart wing
 aircraft engineering future snc laval in satkins and aerospace technology vol 80 no 4 pp 439 444
 narayanan k b sakthivel n 2010 biological hwang h park h w park b 2013 synthesis metal nanoparticles
 microbe advance piezoresistive behavior and multi directional strainsensing colloid and interface science
 vol 156 nos 1 2 pp 1 13 ability carbon nanotube graphene nanoplatelet hybrid ritter 2007 smart material
 architecture interior sheet smart mater smart materials and structures vol 22 architecture and design
 birkhäuser basel frankfurt 1 p 015013 salazar alvarez g muhammed zagorodni i h n j b and chang f k 2004
 detection and monitoring 2006 novel flow injection synthesis iron oxide
 of hidden fatigue crack growth using a built in piezoelectric nanoparticles narrow size distribution chemical
 sensor actuator network ii validation using riveted joint engineering science vol 61 no 14 pp 4625 4633
 and repair patches smart materials and structures vol 13 schwartz 2002 preface smart material 3 pp 621
 630 encyclopedia john wiley son pp 5 7 jardine p kudva j martin c and appa k 1996 soroushian p hsu j w
 1997 superelasticity based shape memory alloy ti ni actuator twist control rehabilitation post tensioning
 bridge structure smart wing design spie proceeding mathematics nchrp 96 ido 29 nchrp idea aug
 controls in smart structures vol 2717 pp 160 165 ventura dolog r darugar q khabashesku v kuilla bhadra
 yao kim n h bose and lee j hughes b 2017 nano enabled smart material h 2010 recent advance
 graphene based polymer sensor oil gas application document id spe composite progress polymer
 science vol 35 11 188345 m society of petroleum engineers pp 1350 1375 zeng h du x w singh c kulunich
 yang lagoudas rediniotis k khan 1999 j 2012 nanomaterials via laser ablation irradiation
 applications of shape memory alloy to bioengineering and liquid review advanced functional material vol 22
 biomedical technology proceeding 4th international 7 pp 1333 1353 workshop mathematical method
 scattering theory zhang erkey c 2006 preparation supported biomedical application perdika greece pp
 195 207 metallic nanoparticles using supercritical fluid review li q li j 2009 smart core shell
 journal of supercritical fluids vol 38 no 2 pp 252 267 nanocomposites intelligent polymer modified gold
 nanoparticles advance colloid interface science corresponding author vol 149 nos 1 2 pp 28 38
 alarshbasheer can be contacted at alarshba yahoo com for instructions on how to order reprint of this article
 please visit our website www.emeraldgroupublishing.com licensing reprint htm
 or contact us for further details permission emeraldinsight.com 1035

Top Keywords

material: 0.5952163775899308
 smart: 0.3859095195363288
 application: 0.1504393042260265
 pp: 0.1504393042260265

vol: 0.14389846491185143
nano: 0.12427594696932623
property: 0.12427594696932623
shape: 0.12427594696932623
temperature: 0.1111942683409761
actuator: 0.10465342902680104
aerospace: 0.09811258971262597
change: 0.09811258971262597
structure: 0.09811258971262597
industry: 0.0915717503984509
sensor: 0.0915717503984509
used: 0.07849007177010077
aircraft: 0.07194923245592572
future: 0.07194923245592572
1035: 0.06540839314175065
2020: 0.06540839314175065
may: 0.06540839314175065
polymer: 0.06540839314175065
self: 0.06540839314175065
1027: 0.05886755382757558
aircraftengineeringandaerospacetechnology: 0.05886755382757558
alarshbasheer: 0.05886755382757558
also: 0.05886755382757558
composite: 0.05886755382757558
different: 0.05886755382757558
light: 0.05886755382757558
memory: 0.05886755382757558
nanomaterials: 0.05886755382757558
nanoparticles: 0.05886755382757558
piezoelectric: 0.05886755382757558
response: 0.05886755382757558
2006: 0.05232671451340052
author: 0.05232671451340052
control: 0.05232671451340052
number7: 0.05232671451340052
radiation: 0.05232671451340052
system: 0.05232671451340052
various: 0.05232671451340052
volume92: 0.05232671451340052
2012: 0.04578587519922545
based: 0.04578587519922545
besides: 0.04578587519922545
colorvariations: 0.04578587519922545
electricpotentialdifference: 0.04578587519922545
feature: 0.04578587519922545
great: 0.04578587519922545
high: 0.04578587519922545
requirement: 0.04578587519922545
stimulus: 0.04578587519922545
wing: 0.04578587519922545
2007: 0.039245035885050385
2010: 0.039245035885050385
2017: 0.039245035885050385

cid: 0.039245035885050385
effect: 0.039245035885050385
elasticity: 0.039245035885050385
graphene: 0.039245035885050385
magnetic: 0.039245035885050385
performance: 0.039245035885050385
phase: 0.039245035885050385
smas: 0.039245035885050385
strain: 0.039245035885050385
useful: 0.039245035885050385
vibration: 0.039245035885050385
2018: 0.032704196570875324
ability: 0.032704196570875324
advance: 0.032704196570875324
certainly: 0.032704196570875324
chemical: 0.032704196570875324
composition: 0.032704196570875324
design: 0.032704196570875324
electric: 0.032704196570875324
electricpotentialvariations: 0.032704196570875324
engineering: 0.032704196570875324
highly: 0.032704196570875324
important: 0.032704196570875324
new: 0.032704196570875324
one: 0.032704196570875324
smartmaterials: 0.032704196570875324
stress: 0.032704196570875324
structural: 0.032704196570875324
synthesis: 0.032704196570875324
technology: 0.032704196570875324
transducer: 0.032704196570875324
two: 0.032704196570875324
10: 0.02616335725670026
11: 0.02616335725670026
1996: 0.02616335725670026
1999: 0.02616335725670026
2002: 0.02616335725670026
2008: 0.02616335725670026
al: 0.02616335725670026
alloy: 0.02616335725670026
ceramic: 0.02616335725670026
changing: 0.02616335725670026
com: 0.02616335725670026
et: 0.02616335725670026
field: 0.02616335725670026
figure: 0.02616335725670026
include: 0.02616335725670026
intelligent: 0.02616335725670026
liquid: 0.02616335725670026
load: 0.02616335725670026
low: 0.02616335725670026
major: 0.02616335725670026
make: 0.02616335725670026

many: 0.02616335725670026
mechanical: 0.02616335725670026
membrane: 0.02616335725670026
method: 0.02616335725670026
nanotechnology: 0.02616335725670026
need: 0.02616335725670026
ph: 0.02616335725670026
physical: 0.02616335725670026
power: 0.02616335725670026
researcher: 0.02616335725670026
responsive: 0.02616335725670026
review: 0.02616335725670026
significant: 0.02616335725670026
size: 0.02616335725670026
sl: 0.02616335725670026
space: 0.02616335725670026
surface: 0.02616335725670026
therefore: 0.02616335725670026
thermal: 0.02616335725670026
ti: 0.02616335725670026
time: 0.02616335725670026
twist: 0.02616335725670026
using: 0.02616335725670026
work: 0.02616335725670026
working: 0.02616335725670026
12: 0.019622517942525192
13: 0.019622517942525192
adaptability: 0.019622517942525192
adaptation: 0.019622517942525192
addington: 0.019622517942525192
ali: 0.019622517942525192
allaerospaceschemesand: 0.019622517942525192
among: 0.019622517942525192
basically: 0.019622517942525192
called: 0.019622517942525192
changingtechnology: 0.019622517942525192
classification: 0.019622517942525192
combination: 0.019622517942525192
continuously: 0.019622517942525192
conventional: 0.019622517942525192
damping: 0.019622517942525192
demand: 0.019622517942525192
developed: 0.019622517942525192
developing: 0.019622517942525192
distribution: 0.019622517942525192
electronics: 0.019622517942525192
energy: 0.019622517942525192
factor: 0.019622517942525192
function: 0.019622517942525192
generally: 0.019622517942525192
gold: 0.019622517942525192
good: 0.019622517942525192
heat: 0.019622517942525192

helicopter: 0.019622517942525192
hysteresis: 0.019622517942525192
increase: 0.019622517942525192
journal: 0.019622517942525192
lead: 0.019622517942525192
lightweight: 0.019622517942525192
manifold: 0.019622517942525192
manufacturing: 0.019622517942525192
meet: 0.019622517942525192
multi: 0.019622517942525192
network: 0.019622517942525192
observed: 0.019622517942525192
oil: 0.019622517942525192
part: 0.019622517942525192
particle: 0.019622517942525192
per: 0.019622517942525192
piezoresistive: 0.019622517942525192
prepared: 0.019622517942525192
pressure: 0.019622517942525192
program: 0.019622517942525192
pzt: 0.019622517942525192
quality: 0.019622517942525192
regulate: 0.019622517942525192
research: 0.019622517942525192
reversible: 0.019622517942525192
ritter: 0.019622517942525192
rotor: 0.019622517942525192
satellite: 0.019622517942525192
screen: 0.019622517942525192
sensing: 0.019622517942525192
sensitivity: 0.019622517942525192
sheet: 0.019622517942525192
shock: 0.019622517942525192
similarly: 0.019622517942525192
thin: 0.019622517942525192
transformation: 0.019622517942525192
value: 0.019622517942525192
water: 0.019622517942525192
way: 0.019622517942525192
100: 0.01308167862835013
14: 0.01308167862835013
1992: 0.01308167862835013
1995: 0.01308167862835013
1997: 0.01308167862835013
20: 0.01308167862835013
2000: 0.01308167862835013
2004: 0.01308167862835013
2005: 0.01308167862835013
2009: 0.01308167862835013
2013: 0.01308167862835013
207: 0.01308167862835013
22: 0.01308167862835013
2717: 0.01308167862835013

8842: 0.01308167862835013
academician: 0.01308167862835013
accelerometer: 0.01308167862835013
acidity: 0.01308167862835013
active: 0.01308167862835013
adaptive: 0.01308167862835013
aerodynamicpresentation: 0.01308167862835013
airbus: 0.01308167862835013
akhras: 0.01308167862835013
alter: 0.01308167862835013
andlee: 0.01308167862835013
approach: 0.01308167862835013
approximately: 0.01308167862835013
area: 0.01308167862835013
article: 0.01308167862835013
assembly: 0.01308167862835013
augment: 0.01308167862835013
automatic: 0.01308167862835013
available: 0.01308167862835013
bashir: 0.01308167862835013
bearing: 0.01308167862835013
biological: 0.01308167862835013
bit: 0.01308167862835013
blade: 0.01308167862835013
breaksandautomotivedampers: 0.01308167862835013
briefly: 0.01308167862835013
buffalo: 0.01308167862835013
capability: 0.01308167862835013
carbon: 0.01308167862835013
carried: 0.01308167862835013
challenge: 0.01308167862835013
charged: 0.01308167862835013
claimed: 0.01308167862835013
classified: 0.01308167862835013
color: 0.01308167862835013
commercial: 0.01308167862835013
common: 0.01308167862835013
component: 0.01308167862835013
consequently: 0.01308167862835013
core: 0.01308167862835013
coyle: 0.01308167862835013
crack: 0.01308167862835013
cuenya: 0.01308167862835013
current: 0.01308167862835013
dahman: 0.01308167862835013
described: 0.01308167862835013
desroches: 0.01308167862835013
detwinned: 0.01308167862835013
development: 0.01308167862835013
device: 0.01308167862835013
dong: 0.01308167862835013
dynamic: 0.01308167862835013
effort: 0.01308167862835013

electro: 0.01308167862835013
elsevier: 0.01308167862835013
embedding: 0.01308167862835013
enabled: 0.01308167862835013
energyexchanging: 0.01308167862835013
engineeringbendingandstretchingabilitiesinwingsandhingelessystems: 0.01308167862835013
environmental: 0.01308167862835013
etc: 0.01308167862835013
example: 0.01308167862835013
exists: 0.01308167862835013
exploited: 0.01308167862835013
figure4: 0.01308167862835013
figure6: 0.01308167862835013
film: 0.01308167862835013
finding: 0.01308167862835013
fixed: 0.01308167862835013
fluid: 0.01308167862835013
forexample: 0.01308167862835013
fuel: 0.01308167862835013
fundamentally: 0.01308167862835013
futureperspectives: 0.01308167862835013
gas: 0.01308167862835013
generation: 0.01308167862835013
ghandi: 0.01308167862835013
gyroscope: 0.01308167862835013
hence: 0.01308167862835013
hodgson: 0.01308167862835013
htm: 0.01308167862835013
hwang: 0.01308167862835013
hybrid: 0.01308167862835013
ihn: 0.01308167862835013
importance: 0.01308167862835013
improve: 0.01308167862835013
improving: 0.01308167862835013
increasing: 0.01308167862835013
industrial: 0.01308167862835013
integration: 0.01308167862835013
itis: 0.01308167862835013
jardine: 0.01308167862835013
kim: 0.01308167862835013
kuilla: 0.01308167862835013
lagoudas: 0.01308167862835013
larger: 0.01308167862835013
length: 0.01308167862835013
li: 0.01308167862835013
liang: 0.01308167862835013
magnesium: 0.01308167862835013
magneto: 0.01308167862835013
maintenance: 0.01308167862835013
martensite: 0.01308167862835013
matrix: 0.01308167862835013
matthew: 0.01308167862835013
microwave: 0.01308167862835013

mission: 0.01308167862835013
modified: 0.01308167862835013
mwcnt: 0.01308167862835013
nanomaterial: 0.01308167862835013
nanotube: 0.01308167862835013
nchrp: 0.01308167862835013
newyork: 0.01308167862835013
next: 0.01308167862835013
ni: 0.01308167862835013
niobate: 0.01308167862835013
nowadays: 0.01308167862835013
operation: 0.01308167862835013
oxidation: 0.01308167862835013
park: 0.01308167862835013
platelet: 0.01308167862835013
possible: 0.01308167862835013
preparation: 0.01308167862835013
proceeding: 0.01308167862835013
processing: 0.01308167862835013
produced: 0.01308167862835013
product: 0.01308167862835013
promising: 0.01308167862835013
purpose: 0.01308167862835013
range: 0.01308167862835013
reacting: 0.01308167862835013
recent: 0.01308167862835013
reduction: 0.01308167862835013
reference: 0.01308167862835013
repairingeffect: 0.01308167862835013
reported: 0.01308167862835013
responsivematerials: 0.01308167862835013
restrictive: 0.01308167862835013
revolution: 0.01308167862835013
salazar: 0.01308167862835013
schwartz: 0.01308167862835013
science: 0.01308167862835013
sector: 0.01308167862835013
show: 0.01308167862835013
showed: 0.01308167862835013
small: 0.01308167862835013
smartmaterialsandstructures: 0.01308167862835013
solid: 0.01308167862835013
solvent: 0.01308167862835013
stiffnessandviscosityvariations: 0.01308167862835013
supposed: 0.01308167862835013
technique: 0.01308167862835013
temperaturedifference: 0.01308167862835013
thermostat: 0.01308167862835013
theseare: 0.01308167862835013
thesearethestructureshavingthedistributionofthesensors: 0.01308167862835013
thesuper: 0.01308167862835013
treatment: 0.01308167862835013
true: 0.01308167862835013

type: 0.01308167862835013
type2: 0.01308167862835013
unique: 0.01308167862835013
us: 0.01308167862835013
variation: 0.01308167862835013
vehicle: 0.01308167862835013
via: 0.01308167862835013
wide: 0.01308167862835013
wingaircraft: 0.01308167862835013
wire: 0.01308167862835013
workshop: 0.01308167862835013
www: 0.01308167862835013
0040: 0.006540839314175065
015013: 0.006540839314175065
02: 0.006540839314175065
1027advancesinthesmartmaterialsapplications: 0.006540839314175065
1028advancesinthesmartmaterialsapplications: 0.006540839314175065
1029advancesinthesmartmaterialsapplications: 0.006540839314175065
1030advancesinthesmartmaterialsapplications: 0.006540839314175065
1031advancesinthesmartmaterialsapplications: 0.006540839314175065
1032advancesinthesmartmaterialsapplications: 0.006540839314175065
1033advancesinthesmartmaterialsapplications: 0.006540839314175065
1034advancesinthesmartmaterialsapplications: 0.006540839314175065
109: 0.006540839314175065
1108: 0.006540839314175065
112: 0.006540839314175065
1333: 0.006540839314175065
1350: 0.006540839314175065
1353: 0.006540839314175065
1375: 0.006540839314175065
149nos1: 0.006540839314175065
15: 0.006540839314175065
156nos1: 0.006540839314175065
16: 0.006540839314175065
160: 0.006540839314175065
165: 0.006540839314175065
167no: 0.006540839314175065
17: 0.006540839314175065
1748: 0.006540839314175065
18: 0.006540839314175065
188345: 0.006540839314175065
19: 0.006540839314175065
1939: 0.006540839314175065
1942: 0.006540839314175065
195: 0.006540839314175065
1980sandearly1990s: 0.006540839314175065
1adaptivestructures: 0.006540839314175065
1no: 0.006540839314175065
1piezoelectricmaterials: 0.006540839314175065
1polymeradsorptiononnanoparticles: 0.006540839314175065
1synthesisofnano: 0.006540839314175065
2036: 0.006540839314175065
20years: 0.006540839314175065

21: 0.006540839314175065
234: 0.006540839314175065
243: 0.006540839314175065
250: 0.006540839314175065
252: 0.006540839314175065
267: 0.006540839314175065
271: 0.006540839314175065
272: 0.006540839314175065
28: 0.006540839314175065
280: 0.006540839314175065
2amphiphilicblockcopolymersandmicellesself: 0.006540839314175065
2magnetostrictivematerials: 0.006540839314175065
2sensorystructures: 0.006540839314175065
305: 0.006540839314175065
3127: 0.006540839314175065
3150: 0.006540839314175065
32: 0.006540839314175065
35: 0.006540839314175065
37: 0.006540839314175065
38: 0.006540839314175065
38no: 0.006540839314175065
39no: 0.006540839314175065
3controlledstructures: 0.006540839314175065
3thermo: 0.006540839314175065
400: 0.006540839314175065
434: 0.006540839314175065
439: 0.006540839314175065
442: 0.006540839314175065
444: 0.006540839314175065
4625: 0.006540839314175065
4633: 0.006540839314175065
485nos1: 0.006540839314175065
48o: 0.006540839314175065
4activestructures: 0.006540839314175065
4shapememoryalloys: 0.006540839314175065
4th: 0.006540839314175065
4thinternationalcanduin: 0.006540839314175065
5073: 0.006540839314175065
5091: 0.006540839314175065
518: 0.006540839314175065
52tiO: 0.006540839314175065
5electrostrictivematerials: 0.006540839314175065
5intelligentorsmartstructures: 0.006540839314175065
60: 0.006540839314175065
61no: 0.006540839314175065
621: 0.006540839314175065
630: 0.006540839314175065
673: 0.006540839314175065
677: 0.006540839314175065
682: 0.006540839314175065
683: 0.006540839314175065
6rheologicalmaterials: 0.006540839314175065
7photochromicmaterials: 0.006540839314175065

80: 0.006540839314175065
80no: 0.006540839314175065
8tn: 0.006540839314175065
91: 0.006540839314175065
92: 0.006540839314175065
96: 0.006540839314175065
ablation: 0.006540839314175065
absorber: 0.006540839314175065
absorption: 0.006540839314175065
abstract: 0.006540839314175065
acceleration: 0.006540839314175065
accept: 0.006540839314175065
accepted28april2020: 0.006540839314175065
act: 0.006540839314175065
activated: 0.006540839314175065
actively: 0.006540839314175065
actuatedrotortechonologyisbeingused: 0.006540839314175065
actuation: 0.006540839314175065
actuatorsforrotorcontrol: 0.006540839314175065
adaptivestructures: 0.006540839314175065
adhesionand: 0.006540839314175065
adsorbent: 0.006540839314175065
advanced: 0.006540839314175065
advancedfunctional: 0.006540839314175065
advancement: 0.006540839314175065
advancesinthesmartmaterialsinaerospaceindustriesduringthe: 0.006540839314175065
advantage: 0.006540839314175065
aeat: 0.006540839314175065
aero: 0.006540839314175065
aerodynamiclossesandtomaximizespeed: 0.006540839314175065
aerofoilactuatedbyshapememoryalloysprings: 0.006540839314175065
aerospaceindustriesarediscussedinbrief: 0.006540839314175065
againstcertain: 0.006540839314175065
aileron: 0.006540839314175065
air: 0.006540839314175065
aircraftengineering: 0.006540839314175065
airfoil: 0.006540839314175065
airline: 0.006540839314175065
airplane: 0.006540839314175065
airplanewingdesigns: 0.006540839314175065
airplanewingsmaysolvethisproblem: 0.006540839314175065
airvehicleswiththecapabilitiesofalteringtheirshapesasper: 0.006540839314175065
alarshba: 0.006540839314175065
alarshbasheercanbecontactedat: 0.006540839314175065
alignment: 0.006540839314175065
alloysandcomposites: 0.006540839314175065
alloysdonothaveexhaustionlimit: 0.006540839314175065
allthesealterations: 0.006540839314175065
along: 0.006540839314175065
already: 0.006540839314175065
alsohighlighted: 0.006540839314175065
alteration: 0.006540839314175065
alterationinvolumeinreactiontooutside stimuli: 0.006540839314175065

alteringsmartmaterials: 0.006540839314175065
alters: 0.006540839314175065
alterthesurfacetexture: 0.006540839314175065
aluminaislightinweightanddecreasesthecostsrelatedto: 0.006540839314175065
aluminaisusedto: 0.006540839314175065
alvarez: 0.006540839314175065
alvarezetal: 0.006540839314175065
amongthosewhichareusuallymeasuredmost: 0.006540839314175065
anadaptiveairfoil: 0.006540839314175065
analysis: 0.006540839314175065
anchored: 0.006540839314175065
anchoring: 0.006540839314175065
andaerospacetechnology: 0.006540839314175065
andappa: 0.006540839314175065
andbrown: 0.006540839314175065
andcanbechangedindifferentshapes: 0.006540839314175065
andchang: 0.006540839314175065
anddaniel: 0.006540839314175065
anddegreeofmaterial: 0.006540839314175065
anddetectedbythepilotforalarmintheneccessaryaction: 0.006540839314175065
anddisadvantagesofthesynthesisofnano: 0.006540839314175065
andgoodcorrosionresistance: 0.006540839314175065
andmartensite: 0.006540839314175065
andmodestforcesacrossavariedfrequencyrange: 0.006540839314175065
andmotorsandactuators: 0.006540839314175065
andnano: 0.006540839314175065
andnoiseintheaircraft: 0.006540839314175065
andoutputaregivenintable1: 0.006540839314175065
andrediniotis: 0.006540839314175065
andrepairpatches: 0.006540839314175065
androtorblades: 0.006540839314175065
andsamia: 0.006540839314175065
anoverview: 0.006540839314175065
anti: 0.006540839314175065
apolymeris: 0.006540839314175065
applicability: 0.006540839314175065
applicationofshapememoryalloysin: 0.006540839314175065
applicationsfor: 0.006540839314175065
applicationsmaybecategorizedintosensorsensingdevices: 0.006540839314175065
applicationsofshapememoryalloystobioengineeringand: 0.006540839314175065
appliedcurrent: 0.006540839314175065
apply: 0.006540839314175065
applyingthestrain: 0.006540839314175065
applyingvoltage: 0.006540839314175065
approachmaybeusedtodetectdegradation: 0.006540839314175065
appropriate: 0.006540839314175065
architecture: 0.006540839314175065
architectureanddesign: 0.006540839314175065
areresponsibleforprovidingthevariousnecessaryfunctionsof: 0.006540839314175065
aresearchingsmartmaterialsforthesepurposes: 0.006540839314175065
areused: 0.006540839314175065
arrangement: 0.006540839314175065
arrest: 0.006540839314175065

asactuatorsandsensors: 0.006540839314175065
asampleofasmartactuationstructureforanadaptiveairfoilby: 0.006540839314175065
aspertheauthors: 0.006540839314175065
asself: 0.006540839314175065
assembled: 0.006540839314175065
assemblyand: 0.006540839314175065
assistedtheeconomicsynthesisof: 0.006540839314175065
asturdyprospectiveforfutureuses: 0.006540839314175065
athoroughsearchofthe: 0.006540839314175065
athoroughsearchoftheliteraturewascarriedoutthroughscifinder: 0.006540839314175065
attaining: 0.006540839314175065
attention: 0.006540839314175065
attract: 0.006540839314175065
au: 0.006540839314175065
aug: 0.006540839314175065
augmenting: 0.006540839314175065
austenite: 0.006540839314175065
authorsclaimedtheseservingasimportantfactorsforregulating: 0.006540839314175065
automotivesystems: 0.006540839314175065
avarietyofalloyshavebeenfoundtoshowthiseffectby: 0.006540839314175065
azo: 0.006540839314175065
bacteriorhodopsin: 0.006540839314175065
baena: 0.006540839314175065
band: 0.006540839314175065
bandwidth: 0.006540839314175065
basedon: 0.006540839314175065
batch: 0.006540839314175065
battery: 0.006540839314175065
becauseofchangeinelectricandmagneticfields: 0.006540839314175065
become: 0.006540839314175065
behavior: 0.006540839314175065
beingusedinaerospaceindustriesbutthesmartmaterialsare: 0.006540839314175065
belonging: 0.006540839314175065
beneficial: 0.006540839314175065
bent: 0.006540839314175065
best: 0.006540839314175065
better: 0.006540839314175065
betweenmechanicalstressandelectricitypropertyisbecauseof: 0.006540839314175065
bhadra: 0.006540839314175065
bi: 0.006540839314175065
bilayers: 0.006540839314175065
billion: 0.006540839314175065
biomedical: 0.006540839314175065
biomedicalapplication: 0.006540839314175065
biomimetic: 0.006540839314175065
bionics: 0.006540839314175065
birkhäuserbasel: 0.006540839314175065
bladeswithservoflaps: 0.006540839314175065
block: 0.006540839314175065
board: 0.006540839314175065
boeing: 0.006540839314175065
boeing777: 0.006540839314175065
boming: 0.006540839314175065

bose: 0.006540839314175065
bridge: 0.006540839314175065
brown: 0.006540839314175065
built: 0.006540839314175065
bulletin: 0.006540839314175065
butrecently: 0.006540839314175065
bychangingtemperature: 0.006540839314175065
cadmium: 0.006540839314175065
calledaself: 0.006540839314175065
canada: 0.006540839314175065
capabilitiesand: 0.006540839314175065
capabilitytobearhighvibrationandmechanicalshockand: 0.006540839314175065
capacityi: 0.006540839314175065
case: 0.006540839314175065
catalytic: 0.006540839314175065
cautionary: 0.006540839314175065
cd: 0.006540839314175065
centurywillbedominatedbyawidevarietyofsmartmaterials: 0.006540839314175065
certain: 0.006540839314175065
certification: 0.006540839314175065
chang: 0.006540839314175065
changeable: 0.006540839314175065
changeinmorphologyofgoldnanoparticles: 0.006540839314175065
changeresponse: 0.006540839314175065
channel: 0.006540839314175065
characteristic: 0.006540839314175065
characteristicsandindicatedavariationinelectricalresistanceon: 0.006540839314175065
characteristicsincludehighmeltingtemperature: 0.006540839314175065
characteristicsofthestructure: 0.006540839314175065
chemicalquantities: 0.006540839314175065
chemochromics: 0.006540839314175065
chemoluminescence: 0.006540839314175065
chromenes: 0.006540839314175065
circuit: 0.006540839314175065
civil: 0.006540839314175065
civilengineering: 0.006540839314175065
class: 0.006540839314175065
classificationofsmartmaterials: 0.006540839314175065
clear: 0.006540839314175065
cmt: 0.006540839314175065
cnts: 0.006540839314175065
coating: 0.006540839314175065
coatingsbecauseofspecialfeaturesofthesematerialssuchas: 0.006540839314175065
collaborative: 0.006540839314175065
colloid: 0.006540839314175065
colloidal: 0.006540839314175065
colloidandinterfacescience: 0.006540839314175065
column: 0.006540839314175065
compact: 0.006540839314175065
comparable: 0.006540839314175065
comparatively: 0.006540839314175065
compared: 0.006540839314175065
compatibility: 0.006540839314175065

components of the aerospace industries: 0.006540839314175065
composites with varied functions: 0.006540839314175065
compound: 0.006540839314175065
compound contoured shapes: 0.006540839314175065
comprising sensors and actuators in the layers of composites may: 0.006540839314175065
computer keyboards: 0.006540839314175065
concentration: 0.006540839314175065
concept: 0.006540839314175065
conception: 0.006540839314175065
conclusion: 0.006540839314175065
condition: 0.006540839314175065
conditioning: 0.006540839314175065
conducting: 0.006540839314175065
conductive: 0.006540839314175065
conference: 0.006540839314175065
configuration control exchanges: 0.006540839314175065
consistent: 0.006540839314175065
constant: 0.006540839314175065
constituent: 0.006540839314175065
constitutive: 0.006540839314175065
consuming: 0.006540839314175065
contact areas among the graphene nano: 0.006540839314175065
contain: 0.006540839314175065
continuous mixing of solvents: 0.006540839314175065
contrarily: 0.006540839314175065
control panel as extending towings: 0.006540839314175065
controls in smart structures: 0.006540839314175065
conversion: 0.006540839314175065
converted: 0.006540839314175065
copolymer: 0.006540839314175065
corresponding author: 0.006540839314175065
corrode: 0.006540839314175065
corrosion: 0.006540839314175065
corrosion inhibition plans: 0.006540839314175065
cost: 0.006540839314175065
coupling: 0.006540839314175065
course: 0.006540839314175065
crashworthiness: 0.006540839314175065
create: 0.006540839314175065
creating: 0.006540839314175065
cross: 0.006540839314175065
crystal: 0.006540839314175065
csetneki: 0.006540839314175065
csetneki et al: 0.006540839314175065
cualni: 0.006540839314175065
cuznal: 0.006540839314175065
cyclic and active control: 0.006540839314175065
dahman et al: 0.006540839314175065
damage: 0.006540839314175065
damage and acceleration: 0.006540839314175065
damage issues and life span and extensive testing for varied environment: 0.006540839314175065
daniel: 0.006540839314175065
darugar: 0.006540839314175065

davidson: 0.006540839314175065
defense: 0.006540839314175065
defensive: 0.006540839314175065
deformation: 0.006540839314175065
deformedshapeaero: 0.006540839314175065
degradation: 0.006540839314175065
densitymaterials: 0.006540839314175065
departmentofmechanicalandaerospaceengineering: 0.006540839314175065
depending: 0.006540839314175065
depicts: 0.006540839314175065
depictsasusualstress: 0.006540839314175065
depletionbridgingandmechanisms: 0.006540839314175065
derossi: 0.006540839314175065
describedthe: 0.006540839314175065
designing: 0.006540839314175065
designofsmartmaterialsfor: 0.006540839314175065
desired: 0.006540839314175065
despite: 0.006540839314175065
destructiveevaluationandperspectives: 0.006540839314175065
detectanycrackintheaircraft: 0.006540839314175065
detectionandmonitoring: 0.006540839314175065
develop: 0.006540839314175065
developedbychangingtheircompositions: 0.006540839314175065
developmentofashapememoryalloyactuated: 0.006540839314175065
developmentofasmartwing: 0.006540839314175065
developnew: 0.006540839314175065
diagnostic: 0.006540839314175065
diagnostictoolsand: 0.006540839314175065
diagram: 0.006540839314175065
diamond: 0.006540839314175065
diarylethenes: 0.006540839314175065
digitization: 0.006540839314175065
dimension: 0.006540839314175065
dimensional: 0.006540839314175065
dimensionalstructure: 0.006540839314175065
direction: 0.006540839314175065
directionalstrainsensing: 0.006540839314175065
directly: 0.006540839314175065
disadvantage: 0.006540839314175065
discus: 0.006540839314175065
discussed: 0.006540839314175065
displacement: 0.006540839314175065
display: 0.006540839314175065
dissipation: 0.006540839314175065
distributed: 0.006540839314175065
document: 0.006540839314175065
doi: 0.006540839314175065
dolog: 0.006540839314175065
dot: 0.006540839314175065
doubled: 0.006540839314175065
dream: 0.006540839314175065
du: 0.006540839314175065
duringthepastdecade: 0.006540839314175065

eachmoleculeispolarized: 0.006540839314175065
early: 0.006540839314175065
ease: 0.006540839314175065
easily: 0.006540839314175065
economically: 0.006540839314175065
ed: 0.006540839314175065
efficiency: 0.006540839314175065
efficientdesign: 0.006540839314175065
elasticformofanaircraftwingtodecreasethepulland: 0.006540839314175065
elasticitysmart: 0.006540839314175065
elastomeric: 0.006540839314175065
elastomermatrix: 0.006540839314175065
electrical: 0.006540839314175065
electricity: 0.006540839314175065
electroceramic: 0.006540839314175065
electrochromic: 0.006540839314175065
electrochromics: 0.006540839314175065
electroluminescence: 0.006540839314175065
electromagnetic: 0.006540839314175065
electromagneticshielding: 0.006540839314175065
electromechanical: 0.006540839314175065
electronbeam lithography: 0.006540839314175065
electrorheological: 0.006540839314175065
electrostatic: 0.006540839314175065
embedded: 0.006540839314175065
emerald: 0.006540839314175065
emeraldgroup publishing: 0.006540839314175065
emeraldinsight: 0.006540839314175065
emerald publishing limited: 0.006540839314175065
emerged: 0.006540839314175065
emerging: 0.006540839314175065
emitting diodes: 0.006540839314175065
emphasizethenewcontroltechniquesforsmartmaterialsand: 0.006540839314175065
encyclopedia: 0.006540839314175065
end: 0.006540839314175065
engineeringandconstructionscience: 0.006540839314175065
engineering science: 0.006540839314175065
engineersanddesigners: 0.006540839314175065
enhance: 0.006540839314175065
entry: 0.006540839314175065
environment: 0.006540839314175065
environmentally: 0.006540839314175065
environmental variations: 0.006540839314175065
environmentevenatlowmagnitude: 0.006540839314175065
epoxysensorwasbetterthancnts: 0.006540839314175065
erkey: 0.006540839314175065
erosionresistance: 0.006540839314175065
especially: 0.006540839314175065
essential: 0.006540839314175065
etal: 0.006540839314175065
eurocopter: 0.006540839314175065
every: 0.006540839314175065
exactness: 0.006540839314175065

examplesareof: 0.006540839314175065
exceeding: 0.006540839314175065
excellent: 0.006540839314175065
excellentfatigueproperties: 0.006540839314175065
excellentresistancetocorrosion: 0.006540839314175065
executeamechanismofthecontrolsystembyincreasingthe: 0.006540839314175065
exfoliated: 0.006540839314175065
exhaustionandcorrosion: 0.006540839314175065
exhibit: 0.006540839314175065
exhibited: 0.006540839314175065
exhibiting: 0.006540839314175065
exist: 0.006540839314175065
existsatlowtemperature: 0.006540839314175065
expand: 0.006540839314175065
expandable: 0.006540839314175065
expected: 0.006540839314175065
exploration: 0.006540839314175065
exposure: 0.006540839314175065
extensiveexhaustiontesting: 0.006540839314175065
extensivetesting: 0.006540839314175065
extensivetestingforconsistentdata: 0.006540839314175065
external: 0.006540839314175065
facileandsimplemethod: 0.006540839314175065
fact: 0.006540839314175065
fatigue: 0.006540839314175065
fe: 0.006540839314175065
feasible: 0.006540839314175065
featuresarethebestcombinationstoachievetheheights: 0.006540839314175065
feb: 0.006540839314175065
fighterandpassenger: 0.006540839314175065
figure1: 0.006540839314175065
figure2: 0.006540839314175065
figure3: 0.006540839314175065
figure5: 0.006540839314175065
filipcsei: 0.006540839314175065
fillersbecauseoftheir: 0.006540839314175065
first: 0.006540839314175065
five: 0.006540839314175065
flap: 0.006540839314175065
flappingtheneedforsmoothandeconomicperformance: 0.006540839314175065
flight: 0.006540839314175065
flow: 0.006540839314175065
flowinjection: 0.006540839314175065
fluoride: 0.006540839314175065
fly: 0.006540839314175065
fold: 0.006540839314175065
forapplicationsinnon: 0.006540839314175065
force: 0.006540839314175065
forinstructionsonhowtoorderreprintsofthisarticle: 0.006540839314175065
form: 0.006540839314175065
formanydeviceeasily: 0.006540839314175065
formerly: 0.006540839314175065
formilitaryaircraft: 0.006540839314175065

forspecialapplications: 0.006540839314175065
fortheextremelyintegratedcontrol: 0.006540839314175065
found: 0.006540839314175065
four: 0.006540839314175065
frameforwingsforflappingin: 0.006540839314175065
frankfurt: 0.006540839314175065
frequency: 0.006540839314175065
frequencystereospeakers: 0.006540839314175065
frequently: 0.006540839314175065
fromaustenitetomartensiteinpressurewhilethelowerplateau: 0.006540839314175065
fromfogandice: 0.006540839314175065
fulgides: 0.006540839314175065
functional: 0.006540839314175065
functionality: 0.006540839314175065
functionalmaterialsforengineers: 0.006540839314175065
furthermore: 0.006540839314175065
gaining: 0.006540839314175065
gaininggreat: 0.006540839314175065
gap: 0.006540839314175065
garner: 0.006540839314175065
garneretal: 0.006540839314175065
gasgrills: 0.006540839314175065
gasphasedeposition: 0.006540839314175065
gauge: 0.006540839314175065
gaugefactorthan: 0.006540839314175065
gel: 0.006540839314175065
generative: 0.006540839314175065
geometrycontrolpossible: 0.006540839314175065
giving: 0.006540839314175065
glass: 0.006540839314175065
go: 0.006540839314175065
going: 0.006540839314175065
goodcontrolofitsdynamicandaddictiveness: 0.006540839314175065
goodcontrolofnanoparticles: 0.006540839314175065
graphite: 0.006540839314175065
greatlatenttointroducearevolutioninmanyareasincluding: 0.006540839314175065
greatlycomplexloading: 0.006540839314175065
greece: 0.006540839314175065
group: 0.006540839314175065
growth: 0.006540839314175065
guion: 0.006540839314175065
guo: 0.006540839314175065
hanna: 0.006540839314175065
head: 0.006540839314175065
healing: 0.006540839314175065
heated: 0.006540839314175065
heating: 0.006540839314175065
help: 0.006540839314175065
heterogeneous: 0.006540839314175065
heulitt: 0.006540839314175065
highcomplexparaphernalia: 0.006540839314175065
higher: 0.006540839314175065
highreliability: 0.006540839314175065

highstrength: 0.006540839314175065
hong: 0.006540839314175065
hopeful: 0.006540839314175065
hsu: 0.006540839314175065
http: 0.006540839314175065
huge: 0.006540839314175065
hughes: 0.006540839314175065
humankind: 0.006540839314175065
hutapea: 0.006540839314175065
hutapeaetal: 0.006540839314175065
hydraulic: 0.006540839314175065
hydrogel: 0.006540839314175065
hydrostatic: 0.006540839314175065
hysteretic: 0.006540839314175065
hystereticdamping: 0.006540839314175065
id: 0.006540839314175065
idea: 0.006540839314175065
ideaproject65: 0.006540839314175065
ido29: 0.006540839314175065
ifvoltageisapplied: 0.006540839314175065
igniter: 0.006540839314175065
ignition: 0.006540839314175065
ii: 0.006540839314175065
image: 0.006540839314175065
improvement: 0.006540839314175065
improvementinthehealthmonitoringofthesystemand: 0.006540839314175065
inacrystal: 0.006540839314175065
inaerospaceengineering: 0.006540839314175065
includeshockabsorbers: 0.006540839314175065
increased: 0.006540839314175065
increaseincost: 0.006540839314175065
independent: 0.006540839314175065
indolizines: 0.006540839314175065
induced: 0.006540839314175065
inducingdefectsandmodificationofmicrostructures: 0.006540839314175065
inertness: 0.006540839314175065
inexpensiveness: 0.006540839314175065
influence: 0.006540839314175065
information: 0.006540839314175065
initiatelifeonotherplanets: 0.006540839314175065
injection: 0.006540839314175065
inliquid: 0.006540839314175065
innovation: 0.006540839314175065
innovative: 0.006540839314175065
inpiezoelectric: 0.006540839314175065
input: 0.006540839314175065
insight: 0.006540839314175065
insightat: 0.006540839314175065
inspection: 0.006540839314175065
instrumentsintheaerospaceindustries: 0.006540839314175065
integrated: 0.006540839314175065
integrity: 0.006540839314175065
intellectual: 0.006540839314175065

intemperancecapabilityviarepeatablephasetransformationand: 0.006540839314175065
inter: 0.006540839314175065
interaction: 0.006540839314175065
interest: 0.006540839314175065
interesting: 0.006540839314175065
interface: 0.006540839314175065
interior: 0.006540839314175065
international: 0.006540839314175065
internationaljournalofcivil: 0.006540839314175065
inthesematerials: 0.006540839314175065
inthisapproach: 0.006540839314175065
introduction: 0.006540839314175065
inversely: 0.006540839314175065
involve: 0.006540839314175065
ionicexchangeandosmoticshock: 0.006540839314175065
iron: 0.006540839314175065
ironandcobalt: 0.006540839314175065
irradiation: 0.006540839314175065
iscalled: 0.006540839314175065
issn1748: 0.006540839314175065
itisconsideredworthwhiletowriteareviewonthissubject: 0.006540839314175065
itiswell: 0.006540839314175065
itrequiresanelectricfieldtocauseinducedstressand: 0.006540839314175065
itwasalsorealizedthattherearesome: 0.006540839314175065
itwasobservedthatthe: 0.006540839314175065
johnwiley: 0.006540839314175065
joint: 0.006540839314175065
journalofpower: 0.006540839314175065
journalofsupercriticalfluids: 0.006540839314175065
july: 0.006540839314175065
jun: 0.006540839314175065
june18: 0.006540839314175065
justlikeadipole: 0.006540839314175065
kamil: 0.006540839314175065
keep: 0.006540839314175065
key: 0.006540839314175065
keywords: 0.006540839314175065
khabashesku: 0.006540839314175065
khan: 0.006540839314175065
known: 0.006540839314175065
knownthat: 0.006540839314175065
kudva: 0.006540839314175065
kulunich: 0.006540839314175065
lagoudasetal: 0.006540839314175065
laminated: 0.006540839314175065
lancaster: 0.006540839314175065
largedisplacementsandexcitationforces: 0.006540839314175065
laser: 0.006540839314175065
laserablation: 0.006540839314175065
lateral: 0.006540839314175065
lateron: 0.006540839314175065
lau: 0.006540839314175065
launching: 0.006540839314175065

lavalin: 0.006540839314175065
layered: 0.006540839314175065
leading: 0.006540839314175065
lead to reduced maneuver envelop because of weight and volume constraints: 0.006540839314175065
leap: 0.006540839314175065
lesser: 0.006540839314175065
level: 0.006540839314175065
liang and rogers: 0.006540839314175065
liang et al: 0.006540839314175065
library and reputed and peer: 0.006540839314175065
licensing: 0.006540839314175065
li et al: 0.006540839314175065
life: 0.006540839314175065
lightning protection: 0.006540839314175065
limit: 0.006540839314175065
limitation: 0.006540839314175065
lin: 0.006540839314175065
lin and samia: 0.006540839314175065
line: 0.006540839314175065
linear: 0.006540839314175065
ling: 0.006540839314175065
linking: 0.006540839314175065
liquid crystals: 0.006540839314175065
literature: 0.006540839314175065
lithium: 0.006540839314175065
liu: 0.006540839314175065
liu et al: 0.006540839314175065
living: 0.006540839314175065
location: 0.006540839314175065
logic: 0.006540839314175065
logic and: 0.006540839314175065
long: 0.006540839314175065
looking: 0.006540839314175065
low manufacturing rate: 0.006540839314175065
machine tools: 0.006540839314175065
macromolecule: 0.006540839314175065
made: 0.006540839314175065
made to restrict their applications in aerospace industries only: 0.006540839314175065
magnato: 0.006540839314175065
magnetic bars: 0.006540839314175065
magnetic field: 0.006540839314175065
magnetic fields: 0.006540839314175065
magnetic properties: 0.006540839314175065
magnetism: 0.006540839314175065
magnetostriuctive: 0.006540839314175065
making: 0.006540839314175065
manage: 0.006540839314175065
maneuverability: 0.006540839314175065
maneuverability and performance owing to good flexibility: 0.006540839314175065
manners similar to birds: 0.006540839314175065
manufacturability: 0.006540839314175065
manufacture: 0.006540839314175065
marine: 0.006540839314175065

market: 0.006540839314175065
martin: 0.006540839314175065
masterthesis: 0.006540839314175065
materialcouldpossibly: 0.006540839314175065
materialsareasgivenbelow: 0.006540839314175065
materials candetect the errors and fissures and are working as: 0.006540839314175065
materials may be used to repair the fault during any mechanical: 0.006540839314175065
materials under pressure: 0.006540839314175065
mathematical: 0.006540839314175065
mathematics: 0.006540839314175065
matter: 0.006540839314175065
measurement: 0.006540839314175065
measuring: 0.006540839314175065
mechanical energy: 0.006540839314175065
mechanism: 0.006540839314175065
mechanochromics: 0.006540839314175065
memory alloys: 0.006540839314175065
memory effect and two: 0.006540839314175065
metabolite can release their load as a result of such a: 0.006540839314175065
metal: 0.006540839314175065
metallic: 0.006540839314175065
metal nanoparticles: 0.006540839314175065
methodology: 0.006540839314175065
micelle: 0.006540839314175065
microbe: 0.006540839314175065
microbial incubation: 0.006540839314175065
microelectronics: 0.006540839314175065
microphone: 0.006540839314175065
might: 0.006540839314175065
minimize: 0.006540839314175065
minimizing: 0.006540839314175065
miscibility: 0.006540839314175065
missile: 0.006540839314175065
mit: 0.006540839314175065
mitigation: 0.006540839314175065
mixture: 0.006540839314175065
modulus: 0.006540839314175065
molding and machining: 0.006540839314175065
molecular: 0.006540839314175065
molecule: 0.006540839314175065
monitored: 0.006540839314175065
monocoque fabrication: 0.006540839314175065
morphing: 0.006540839314175065
morphology: 0.006540839314175065
most of: 0.006540839314175065
most widely used piezoelectric materials are piezoceramics: 0.006540839314175065
motion: 0.006540839314175065
motor: 0.006540839314175065
mr: 0.006540839314175065
much research has not been done in this area: 0.006540839314175065
muhammed: 0.006540839314175065
multifold: 0.006540839314175065
multiple functionalities: 0.006540839314175065

mwcnts: 0.006540839314175065
nanocomposite: 0.006540839314175065
nanocomposites: 0.006540839314175065
nanoparticle: 0.006540839314175065
nanoplatelet: 0.006540839314175065
nanotechnologyandsmartmaterials: 0.006540839314175065
nanotechnologyisatooltotakesmartmaterials: 0.006540839314175065
nanotechnologyisgainingimportanceinalmost: 0.006540839314175065
nanotubesformethanoelectro: 0.006540839314175065
naphthopyranes: 0.006540839314175065
narayanan: 0.006540839314175065
narayananandsakthivel: 0.006540839314175065
narrow: 0.006540839314175065
nature: 0.006540839314175065
naval: 0.006540839314175065
ndeandperspectives: 0.006540839314175065
ndt: 0.006540839314175065
necessary: 0.006540839314175065
necessity: 0.006540839314175065
needcriticaltemperatureandpressure: 0.006540839314175065
negative: 0.006540839314175065
negatively: 0.006540839314175065
newtechnologies: 0.006540839314175065
nexttonewgenerationaircraft: 0.006540839314175065
ngp: 0.006540839314175065
ngps: 0.006540839314175065
nickel: 0.006540839314175065
niticu: 0.006540839314175065
nitinol: 0.006540839314175065
nitinolisnickelandtitaniumalloy: 0.006540839314175065
noneedofanyotherchemical: 0.006540839314175065
normal: 0.006540839314175065
note: 0.006540839314175065
noteworthy: 0.006540839314175065
nouseoftoxicchemicals: 0.006540839314175065
novel: 0.006540839314175065
nuclear: 0.006540839314175065
numberofpassengersandthedemandfortheaircraft: 0.006540839314175065
numerous: 0.006540839314175065
object: 0.006540839314175065
observationwasrecordedin1932ongold: 0.006540839314175065
observe: 0.006540839314175065
observedthatsmacouldgetgoodactuatingresults: 0.006540839314175065
occur: 0.006540839314175065
occurred: 0.006540839314175065
occurringinshape: 0.006540839314175065
oetikerinc: 0.006540839314175065
ofactivestructures: 0.006540839314175065
ofaircraft: 0.006540839314175065
ofanano: 0.006540839314175065
ofcourse: 0.006540839314175065
ofdetection: 0.006540839314175065
ofhiddenfatiguecrackgrowthusingabuilt: 0.006540839314175065

ofsmartmaterialsarediscussed: 0.006540839314175065
ofthemagneticpolystyrenelatexparticles: 0.006540839314175065
ofxgnpsize: 0.006540839314175065
ontario: 0.006540839314175065
onthelatestdevelopmentsandapplicationsofsmartmaterials: 0.006540839314175065
open: 0.006540839314175065
operational: 0.006540839314175065
opportunity: 0.006540839314175065
optical: 0.006540839314175065
optimization: 0.006540839314175065
optimizationoftheresponsesofcomplexsystems: 0.006540839314175065
option: 0.006540839314175065
orcontactusforfurtherdetails: 0.006540839314175065
orderedarray: 0.006540839314175065
ordinancelaboratory: 0.006540839314175065
originality: 0.006540839314175065
otherendwasinvolvedtangentiallytoarevolvingcylinderfixed: 0.006540839314175065
output: 0.006540839314175065
overcome: 0.006540839314175065
overpower: 0.006540839314175065
owing: 0.006540839314175065
oxide: 0.006540839314175065
packer: 0.006540839314175065
packing: 0.006540839314175065
papertypeliteraturereview: 0.006540839314175065
passenger: 0.006540839314175065
passengersafety: 0.006540839314175065
passengerscarriers: 0.006540839314175065
pastfewyears: 0.006540839314175065
patent: 0.006540839314175065
path: 0.006540839314175065
pbzr0: 0.006540839314175065
perdika: 0.006540839314175065
perinternationalairtransportassociation: 0.006540839314175065
permanent: 0.006540839314175065
permeability: 0.006540839314175065
permeabilityincreased: 0.006540839314175065
permission: 0.006540839314175065
perspective: 0.006540839314175065
photochromics: 0.006540839314175065
photoluminescence: 0.006540839314175065
photovoltaics: 0.006540839314175065
physicaldeviationswithintheparticlesareinthecollectivesize: 0.006540839314175065
piezo: 0.006540839314175065
piezoelectricity: 0.006540839314175065
piezoelectricmaterialshowingtheexchangeofelectricaland: 0.006540839314175065
piezoresistivebehaviorandmulti: 0.006540839314175065
pitch: 0.006540839314175065
plasma: 0.006540839314175065
pleasevisitourwebsite: 0.006540839314175065
point: 0.006540839314175065
polarandnon: 0.006540839314175065
polarization: 0.006540839314175065

polymeric: 0.006540839314175065
polymerization: 0.006540839314175065
polyvinylidene: 0.006540839314175065
positive: 0.006540839314175065
positively: 0.006540839314175065
post: 0.006540839314175065
pot: 0.006540839314175065
powerelectronics: 0.006540839314175065
practicalapproach: 0.006540839314175065
pre: 0.006540839314175065
precise: 0.006540839314175065
precisechemicalsusingtheirwork: 0.006540839314175065
predicted: 0.006540839314175065
preface: 0.006540839314175065
prepare: 0.006540839314175065
presentation: 0.006540839314175065
presented: 0.006540839314175065
price: 0.006540839314175065
principle: 0.006540839314175065
principleandrecentdevelopments: 0.006540839314175065
printed: 0.006540839314175065
printer: 0.006540839314175065
priority: 0.006540839314175065
problem: 0.006540839314175065
procedure: 0.006540839314175065
process: 0.006540839314175065
processingandsensortechnology: 0.006540839314175065
processor: 0.006540839314175065
produce: 0.006540839314175065
producewaveswhenacrackisdeveloped: 0.006540839314175065
progress: 0.006540839314175065
proofofdesign: 0.006540839314175065
propertychanging: 0.006540839314175065
proportional: 0.006540839314175065
proportionaltothethicknessesofthesheets: 0.006540839314175065
proposed: 0.006540839314175065
protection: 0.006540839314175065
providing: 0.006540839314175065
pt: 0.006540839314175065
ptandptrunanoparticlesdepositedonsingle: 0.006540839314175065
pulsedlayerablation: 0.006540839314175065
pyroelectric: 0.006540839314175065
qualitygraphene: 0.006540839314175065
radiationandthermal: 0.006540839314175065
rate: 0.006540839314175065
ratio: 0.006540839314175065
reach: 0.006540839314175065
react: 0.006540839314175065
reaction: 0.006540839314175065
received10march2020: 0.006540839314175065
recently: 0.006540839314175065
recurrent: 0.006540839314175065
rediniotitis: 0.006540839314175065

reduce: 0.006540839314175065
reducedreactionorsynthesis: 0.006540839314175065
reduces: 0.006540839314175065
regaintheiroriginalshapetotheirausteniteconditionswhen: 0.006540839314175065
regulatingtheflaps: 0.006540839314175065
rehabilitation: 0.006540839314175065
related: 0.006540839314175065
relatedstructuresand: 0.006540839314175065
relation: 0.006540839314175065
relationshipoftheusualphasechangesofsuper: 0.006540839314175065
reliability: 0.006540839314175065
reliable: 0.006540839314175065
repairingcapabilities: 0.006540839314175065
repeatable: 0.006540839314175065
reportedtheapplicationofasmaasanactuatorfor: 0.006540839314175065
reportofshapememoryapplicationsinc: 0.006540839314175065
reprint: 0.006540839314175065
reproducible: 0.006540839314175065
reproducibleandhomogeneous: 0.006540839314175065
requirementsandtheeffectsofaircraftapplications: 0.006540839314175065
researchanddevelopmentdivision: 0.006540839314175065
researcharea: 0.006540839314175065
researchersandtechnocratsworkinginaerospaceindustries: 0.006540839314175065
resiliency: 0.006540839314175065
resist: 0.006540839314175065
resistance: 0.006540839314175065
responseofthegraphene: 0.006540839314175065
responsestoionicstrength: 0.006540839314175065
responsivenanoparticles: 0.006540839314175065
restrainingandviscosity: 0.006540839314175065
restriction: 0.006540839314175065
result: 0.006540839314175065
return: 0.006540839314175065
reusablepacecraft: 0.006540839314175065
reviewedjournals: 0.006540839314175065
revised23april2020: 0.006540839314175065
rheological: 0.006540839314175065
rheologicalfluidandmagneto: 0.006540839314175065
rheologicalfluidsasperthechanges: 0.006540839314175065
rheology: 0.006540839314175065
rigidity: 0.006540839314175065
riveted: 0.006540839314175065
roboticsystems: 0.006540839314175065
robust: 0.006540839314175065
rod: 0.006540839314175065
rogers: 0.006540839314175065
rolefunctions: 0.006540839314175065
rotary: 0.006540839314175065
sa: 0.006540839314175065
safety: 0.006540839314175065
sakthivel: 0.006540839314175065
satkins: 0.006540839314175065
scalable: 0.006540839314175065

scattering: 0.006540839314175065
schetky: 0.006540839314175065
schodek: 0.006540839314175065
scienceandengineering: 0.006540839314175065
sciencedirect: 0.006540839314175065
second: 0.006540839314175065
seismicrehabilitationofbridges: 0.006540839314175065
selectivity: 0.006540839314175065
semi: 0.006540839314175065
sense: 0.006540839314175065
sensitive: 0.006540839314175065
sensorsandactuatorsandareofnickel: 0.006540839314175065
service: 0.006540839314175065
servo: 0.006540839314175065
set: 0.006540839314175065
sexpansiondownhole: 0.006540839314175065
shaping: 0.006540839314175065
shearflow: 0.006540839314175065
sheetssmartmater: 0.006540839314175065
shell: 0.006540839314175065
shieldsforfireprotection: 0.006540839314175065
shifting: 0.006540839314175065
shockabsorbers: 0.006540839314175065
shouldbepreparedinamoreadvancedwaytomeettheneeds: 0.006540839314175065
showing: 0.006540839314175065
showninfigure1: 0.006540839314175065
showsthereversephenomenonwithpressurerelease: 0.006540839314175065
shuttle: 0.006540839314175065
significantly: 0.006540839314175065
similar: 0.006540839314175065
simple: 0.006540839314175065
singh: 0.006540839314175065
site: 0.006540839314175065
situation: 0.006540839314175065
situationsandconditions: 0.006540839314175065
sizecontrolofnanoparticles: 0.006540839314175065
skin: 0.006540839314175065
smallparticlesizedispersal: 0.006540839314175065
smartandnano: 0.006540839314175065
smartceramicmaterialsareusedinaircraftbecauseoftheir: 0.006540839314175065
smartmaterial: 0.006540839314175065
smartmaterialsalsocalledintelligentmaterialsaregainingimportancecontinuouslyinmanyindustriesincludin
gaerospaceone: 0.006540839314175065
smartmaterialsand: 0.006540839314175065
smartmaterialsandtheirapplicationsin: 0.006540839314175065
smartmaterialsare: 0.006540839314175065
smartmaterialsarethethenewgenerationmaterials: 0.006540839314175065
smartmaterialsforcontrollingnoiseandvibrationcontrol: 0.006540839314175065
smartstructures: 0.006540839314175065
smartstructuresaremadeof: 0.006540839314175065
smasarebeingmadeinanano: 0.006540839314175065
smasprings: 0.006540839314175065
smaspringswerestationaryatoneterminal: 0.006540839314175065

snc: 0.006540839314175065
societyofpetroleumengineers: 0.006540839314175065
solving: 0.006540839314175065
somecompaniesstartedtoproduceni: 0.006540839314175065
sometimes: 0.006540839314175065
sometimespoordispersion: 0.006540839314175065
son: 0.006540839314175065
sonar: 0.006540839314175065
sorbedontheparticlesurfaceanditcontrolsinteractionsinthe: 0.006540839314175065
soroushian: 0.006540839314175065
soroushianandhsu: 0.006540839314175065
sort: 0.006540839314175065
sound: 0.006540839314175065
source: 0.006540839314175065
spacecraft: 0.006540839314175065
spacestructuresandaircraft: 0.006540839314175065
spacevehicles: 0.006540839314175065
spacing: 0.006540839314175065
spe: 0.006540839314175065
special: 0.006540839314175065
specialized: 0.006540839314175065
specialprocessing: 0.006540839314175065
specific: 0.006540839314175065
specification: 0.006540839314175065
specificmilitaryaerospace: 0.006540839314175065
specificsurfaceandshapeofaircraft: 0.006540839314175065
speed: 0.006540839314175065
sphere: 0.006540839314175065
spie: 0.006540839314175065
spieproceedingsofmathematicsandcontrols: 0.006540839314175065
spirodihydro: 0.006540839314175065
spirooxazines: 0.006540839314175065
spring: 0.006540839314175065
springerlink: 0.006540839314175065
square: 0.006540839314175065
stability: 0.006540839314175065
stainless: 0.006540839314175065
standard: 0.006540839314175065
starting: 0.006540839314175065
state: 0.006540839314175065
stateuniversityofnewyork: 0.006540839314175065
statusandchemicaldetection: 0.006540839314175065
stealth: 0.006540839314175065
stealthcoating: 0.006540839314175065
steel: 0.006540839314175065
steric: 0.006540839314175065
still: 0.006540839314175065
stimulate: 0.006540839314175065
stock: 0.006540839314175065
straincurveofsmartmaterials: 0.006540839314175065
straingaugemadeofhigh: 0.006540839314175065
strategy: 0.006540839314175065
straub: 0.006540839314175065

strength: 0.006540839314175065
stressis: 0.006540839314175065
stressrelationshipofausteniteandmartensite: 0.006540839314175065
strictqualitycontrol: 0.006540839314175065
stripsandsheets: 0.006540839314175065
structuralfunctionality: 0.006540839314175065
structureandstimuli: 0.006540839314175065
structuresorloadedtoformseparatepiezoelectricactuators: 0.006540839314175065
structureusingprintedcircuittechnology: 0.006540839314175065
studied: 0.006540839314175065
sturdiness: 0.006540839314175065
sub: 0.006540839314175065
subject: 0.006540839314175065
success: 0.006540839314175065
suchaselectricity: 0.006540839314175065
suchasinsand: 0.006540839314175065
summarizedintable4: 0.006540839314175065
super: 0.006540839314175065
supercritical: 0.006540839314175065
supercriticalfluids: 0.006540839314175065
superelasticity: 0.006540839314175065
superior: 0.006540839314175065
support: 0.006540839314175065
supported: 0.006540839314175065
survivability: 0.006540839314175065
suspendedparticles: 0.006540839314175065
suspension: 0.006540839314175065
sustaining: 0.006540839314175065
swelling: 0.006540839314175065
switch: 0.006540839314175065
switching: 0.006540839314175065
symmetrical: 0.006540839314175065
synthesized: 0.006540839314175065
systemsandmedicalsysteams: 0.006540839314175065
table1: 0.006540839314175065
table2: 0.006540839314175065
table3: 0.006540839314175065
table3summarizesvarioussmartmaterialsusedinaerospace: 0.006540839314175065
table4: 0.006540839314175065
take: 0.006540839314175065
tank: 0.006540839314175065
target: 0.006540839314175065
technicalreportnchrp: 0.006540839314175065
techniqueusingsmartlayerstodetectandmonitorhiddenfatigue: 0.006540839314175065
technocratsworkingintheaerospaceindustries: 0.006540839314175065
technological: 0.006540839314175065
technologiesincludingwellableelastomersinreactivepackers: 0.006540839314175065
temperaturechanges: 0.006540839314175065
tensile: 0.006540839314175065
tensioning: 0.006540839314175065
terfenol: 0.006540839314175065
term: 0.006540839314175065
termed: 0.006540839314175065

tested: 0.006540839314175065
textile: 0.006540839314175065
theadvantages: 0.006540839314175065
theadvantagesanddisadvantagesofthesynthesisofnano: 0.006540839314175065
theadvantagesofsmart: 0.006540839314175065
theaero: 0.006540839314175065
theaerospaceindustries: 0.006540839314175065
theaerospaceindustriesarefacinggreateconomicpressure: 0.006540839314175065
theapplicationsarecarriedoutintheopenenvironmentwith: 0.006540839314175065
theausteniteoccursatlowstress: 0.006540839314175065
thebestmaterialsfortheactuatorsbecauseoftherequiredcoil: 0.006540839314175065
thebodyofaircraftandsatellitesmade: 0.006540839314175065
theceramicfibersareusedasheat: 0.006540839314175065
thechangesareinthe: 0.006540839314175065
thechangesinthemechanicalstressandelectricfield: 0.006540839314175065
thechangestothecollectivearchitecture: 0.006540839314175065
thechannelshaveawell: 0.006540839314175065
theclassification: 0.006540839314175065
thecommonsmartmaterialsandrelatedstimulusresponses: 0.006540839314175065
thecrystallinestructure: 0.006540839314175065
thecurrentissueandfulltextarchiveofthisjournalisavailableonemerald: 0.006540839314175065
thedependenceresistancevariationsonstrain: 0.006540839314175065
thedetection: 0.006540839314175065
thedevelopmentofsmartmaterialsisaninterdisciplinaryarea: 0.006540839314175065
thedifferent: 0.006540839314175065
thedifferentphasesofsmartmaterials: 0.006540839314175065
thedifferenttypesofsmartmaterialswithininputandoutput: 0.006540839314175065
thedislocationsarealwaysinthe: 0.006540839314175065
theeffortsaremadetowriteanarticle: 0.006540839314175065
theeffortswillbe: 0.006540839314175065
thefeatures: 0.006540839314175065
thefeaturesofaircraftapplicationsaregivenintable2while: 0.006540839314175065
thefutureperspectivesofthesematerialsare: 0.006540839314175065
theincreasedusesarethrough: 0.006540839314175065
theliteraturewascriticallyanalyzedandareviewwaswritten: 0.006540839314175065
themajor: 0.006540839314175065
themarketforsmartmaterialswillincreaseinthefuture: 0.006540839314175065
thematerialisoneof: 0.006540839314175065
thematerials: 0.006540839314175065
themostimportant: 0.006540839314175065
themostimportantphotochromicmaterialsarespiropyranes: 0.006540839314175065
thenumberof: 0.006540839314175065
theory: 0.006540839314175065
theotherapplicationsdealwiththeabilitytoregulate: 0.006540839314175065
thephenomenon: 0.006540839314175065
thepiezoelectricanddielectricmaterials: 0.006540839314175065
thepresence: 0.006540839314175065
thereactionsof: 0.006540839314175065
thereisa: 0.006540839314175065
thereisagreatdemandforsmartmaterials: 0.006540839314175065
thereisaneedtodevelopsmartmaterialsformanufacturing: 0.006540839314175065
thereisaneedtomakesmartstructures: 0.006540839314175065
thereisgrowing: 0.006540839314175065

thereisnoreviewofsmartmaterials: 0.006540839314175065
theremarkablefeatureofthesematerialsistheirlarge: 0.006540839314175065
thermalandredoxstimuliare: 0.006540839314175065
thermalinsulationinaircraft: 0.006540839314175065
thermo: 0.006540839314175065
thermochromics: 0.006540839314175065
thermocouplesandgasturbineengines: 0.006540839314175065
thermoelectric: 0.006540839314175065
thermoluminescence: 0.006540839314175065
thermomechanical: 0.006540839314175065
thesamplepreparedshowed: 0.006540839314175065
thesearealsoverysensitiveto temperaturebutshowtiny: 0.006540839314175065
theseareavailableintheformofstacks: 0.006540839314175065
theseareliquidmaterialsreactingagainstthechangeinelectricor: 0.006540839314175065
thesearerelativelylinearatlowfieldsandbipolar: 0.006540839314175065
thesearethebestmaterialsfor: 0.006540839314175065
thesearethematerialsreactingagainstthechangeinelectric: 0.006540839314175065
thesearethematerialsreactingagainstthechangeintheoptical: 0.006540839314175065
thesearethestructureshavingthedistributionoftheactuators: 0.006540839314175065
theseareused: 0.006540839314175065
thesefeaturessensethechangeinthe: 0.006540839314175065
thesehavegoodapplicationsinthemagnetic: 0.006540839314175065
theself: 0.006540839314175065
thesematerialsagainststimuliareveryfast: 0.006540839314175065
thesematerialsare: 0.006540839314175065
thesematerialsaremono: 0.006540839314175065
thesematerialscandetectfaultsand: 0.006540839314175065
thesematerialshavea: 0.006540839314175065
thesematerialsproducelowstrains: 0.006540839314175065
thesematerialsundergomechanicalalterations: 0.006540839314175065
thesematerialsundergomechanicalstrainandwork: 0.006540839314175065
thesemaybe: 0.006540839314175065
thesensors: 0.006540839314175065
theseshould: 0.006540839314175065
thesesmartmaterialsarethethehope: 0.006540839314175065
thesewavesaresensed: 0.006540839314175065
thesewillbethefrontiermaterialsintheaerospaceindustries: 0.006540839314175065
thesimulationstudies: 0.006540839314175065
thesmartmaterials: 0.006540839314175065
thesmartmaterialsareprobablytobethemostrecentopening: 0.006540839314175065
thesmartnanomaterialscanbe: 0.006540839314175065
thesmartnanomaterialsmaybeusedinsmas: 0.006540839314175065
thesmartnessofthesematerialsis: 0.006540839314175065
thesmartnessofthesematerialslies: 0.006540839314175065
thesmashaveagood: 0.006540839314175065
thespringactuatorswerecontrolledbysupplyingan: 0.006540839314175065
thestandard: 0.006540839314175065
thestructureshavinga: 0.006540839314175065
theupperplateaushowsanalteration: 0.006540839314175065
theydeformtotheirmartensiticconditionsand: 0.006540839314175065
theyinclude: 0.006540839314175065
thinbendablewingsandregulating surface: 0.006540839314175065
thinmaterialswithhighreliability: 0.006540839314175065

this arrangement is affected by: 0.006540839314175065
this article describes the classification: 0.006540839314175065
this is: 0.006540839314175065
this is the classical and simple method for the preparation of: 0.006540839314175065
this study describes the advances in smart materials concerning their applications in aerospace industries: 0.006540839314175065
this study will be highly useful for academicians: 0.006540839314175065
thus: 0.006540839314175065
titanate: 0.006540839314175065
titanium: 0.006540839314175065
to actuate precisely: 0.006540839314175065
to change the characteristics in a prescribed way: 0.006540839314175065
to complete this: 0.006540839314175065
today: 0.006540839314175065
to lower down the costs: 0.006540839314175065
to measure the level of fuel tanks: 0.006540839314175065
tool: 0.006540839314175065
tool deployment: 0.006540839314175065
toronto: 0.006540839314175065
torsional: 0.006540839314175065
to solve limits of aircraft wing design: 0.006540839314175065
totaling: 0.006540839314175065
to the flap: 0.006540839314175065
to the wing box toward the primary edge of the airfoil whereas the: 0.006540839314175065
toward: 0.006540839314175065
tracking: 0.006540839314175065
trend: 0.006540839314175065
tube: 0.006540839314175065
twinning: 0.006540839314175065
two phase strain transform into each other at the external temperature: 0.006540839314175065
type 1: 0.006540839314175065
types of: 0.006540839314175065
types of alloys are in superelastic spectacle frames and hot: 0.006540839314175065
types of materials: 0.006540839314175065
types of smart materials: 0.006540839314175065
ultrasonic: 0.006540839314175065
understanding: 0.006540839314175065
unexpected: 0.006540839314175065
usa: 0.006540839314175065
usa and: 0.006540839314175065
use: 0.006540839314175065
used smart and nano: 0.006540839314175065
use of fire retardant materials: 0.006540839314175065
use of flow: 0.006540839314175065
using nitinol alloys: 0.006540839314175065
validation: 0.006540839314175065
various adaptive regulators surfaces are reproduced for: 0.006540839314175065
various smart materials used in aerospace industries: 0.006540839314175065
various smart structures are discussed below: 0.006540839314175065
ventura: 0.006540839314175065
ventura et al: 0.006540839314175065
versa: 0.006540839314175065
very dependable: 0.006540839314175065

vice: 0.006540839314175065
viscosity: 0.006540839314175065
voltageswhenstressisapplied: 0.006540839314175065
wallace: 0.006540839314175065
wallcarbon: 0.006540839314175065
walled: 0.006540839314175065
walledboxesorreinforcedstructures: 0.006540839314175065
walledcarbonnanotubesforarsenicspeciesremovalin: 0.006540839314175065
waymemoryeffect: 0.006540839314175065
weatheroperation: 0.006540839314175065
weight: 0.006540839314175065
weightandhighstiffness: 0.006540839314175065
wellmanagedinter: 0.006540839314175065
weredirectional: 0.006540839314175065
whichelongatesonexposingtothemagneticfield: 0.006540839314175065
whichhave: 0.006540839314175065
whichmaybeusedto: 0.006540839314175065
whichneedsmoreextensivestudy: 0.006540839314175065
whichunderwentto: 0.006540839314175065
widerangeofapplicationsbutinthisarticle: 0.006540839314175065
wideuseofcomputersandelectronics: 0.006540839314175065
wileyonline: 0.006540839314175065
wilson: 0.006540839314175065
windshieldsareheatedbyatransparent: 0.006540839314175065
wingconcordance: 0.006540839314175065
wingsforhighspeedsfailto: 0.006540839314175065
withaugmentingtheperformanceand: 0.006540839314175065
withinput: 0.006540839314175065
without: 0.006540839314175065
wood: 0.006540839314175065
workinginthesmartmaterials: 0.006540839314175065
wu: 0.006540839314175065
xgnp: 0.006540839314175065
xgnps: 0.006540839314175065
yahoo: 0.006540839314175065
yang: 0.006540839314175065
yao: 0.006540839314175065
year: 0.006540839314175065
yearly: 0.006540839314175065
yieldandlowcost: 0.006540839314175065
zagorodni: 0.006540839314175065
zeng: 0.006540839314175065
zengetal: 0.006540839314175065
zhang: 0.006540839314175065
zhanganderkey: 0.006540839314175065
zirconate: 0.006540839314175065
zrinyi: 0.006540839314175065