WL2 Firewall™

Excellent purifying performance, easy operation and stylish design



Simply pure water for the workplace

With cold and ambient water, the WL2 Firewall™ (WL2 FW) is the preferred solution for any small or medium size workplace looking for great tasting water, reliability and guaranteed quality.

Advanced technology

The WL2 FW features three core technologies:

High performance filtration
Waterlogic's filters are certified to stringent standards by IAPMO R&T, carrying the Water Quality Platinum Seal, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.

Firewall purification
Waterlogic's patented and certified Firewall UVC purification system thoroughly purifies the water all the way through to the point of dispense, for microbiologically safe water. Guaranteed free from: up to 99.9999% bacteria, 99.99% viruses and 99.9% cysts.

BioCote® antimicrobial product protection[1]
The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides continuous antimicrobial protection against a broad spectrum of bacteria, mould and fungi, and reduces the risks of cross-contamination.

Certified purity for peace of mind

The Firewall technology has been certified by IAPMO R&T to NSF/ANSI-55 Class A and NSF P231 protocol, which is unique – no other water cooler features these standards of certification together. This means that Firewall technology delivers the safest water possible for the workplace.

[1] Exclusive to Waterlogic in the category for commercial use mains-fed drinking water dispensers and solutions.

Features

NSF 55 Class A and NSF P231 certified Firewall, patented UVC technology, that reduces the risks of viruses and pathogenic bacteria, purifying the water up to 99.9999%

Dispensing area suitable to accommodate average size (500 ml) reusable bottles

Touch-less dispensing enabled by IR module or foot pedal controls for greater hygiene and piece of mind (optional)

Generous drip tray capacity for collecting accidental spillage

LED UV fault indicator for easier servicing and peace of mind

BioCote® protected dispensing area (including drip tray and dispensing buttons)

Water options

	cold	sparkling	ambient
1			

Number of users: up to 30

Technical specifications

Types available
Freestanding and countertop

Dimensions
Freestanding
349 mm (W) x 1024 mm (H) x 363 mm (D)

Countertop
349 mm (W) x 453 mm (H) x 363 mm (D)

Dispensing area height
230 mm

Drip tray capacity
380 ml

Weight
Freestanding: 22.5 kg (Net)
Countertop: 17.3 kg (Net)

Recommended filtration
Dependent on SKU and local water conditions

Storage capacity
Cold tank (Freestanding): 4 litres
Cold tank (Countertop): 2 litres

Compressor
(R600a): 220V-240V/50Hz
(R134a): 120V/60Hz

Water temperatures settings
Cold: 3°C

Contact the export team today

Waterlogic Trading Ltd
+ 353 1 293 1960
exportsales@waterlogic.com

For more information, visit
www.waterlogic.com

Tested and certified

Firewall technology is certified by IAPMO R&T to **NSF/ANSI 55 Class A, NSF P231, US EPA Microbiological Guide Standard, NSF/ANSI 372 and CSA B483.1.**

*certificate may vary depending on different models or products

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

WLT2413-28/06/24