

let m be the length of the expression and n be the length of the string.

1. DP. $O(nm)$.
2. $O(\frac{nm \log \log n}{\log^{3/2} n} + n + m)$ for general regular expression matching [2]. for a fixed size alphabet, we can shave the $\log \log n$.

this is the $\circ|*$ -membership problem. conditional lower bound based on SETH: $\Omega((nm)^{1-o(1)})$ [1, 3].

note. for deterministic regular expressions, the running time can be improved [4].

References

- [1] Arturs Backurs and Piotr Indyk. Which regular expression patterns are hard to match? In *2016 IEEE 57th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 457–466. IEEE, 2016.
- [2] Philip Bille and Mikkel Thorup. Faster regular expression matching. In *International Colloquium on Automata, Languages, and Programming*, pages 171–182. Springer, 2009.
- [3] Karl Bringmann, Allan Grønlund, and Kasper Green Larsen. A dichotomy for regular expression membership testing. In *2017 IEEE 58th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 307–318. IEEE, 2017.
- [4] Benotit Groz, Sebastian Maneth, and Slawek Staworko. Deterministic regular expressions in linear time. In *Proceedings of the 31st ACM SIGMOD-SIGACT-SIGAI symposium on Principles of Database Systems*, pages 49–60. ACM, 2012.