



Índice

1. algorithm	2
2. Estructuras	2
2.1. RMQ (static)	2
2.2. RMQ (dynamic)	2
2.3. RMQ (lazy)	3
2.4. Fenwick Tree	3
2.5. Union Find	4
2.6. Disjoint Intervals	4
2.7. RMQ (2D)	4
2.8. Big Int	4
2.9. Modnum	6
2.10. Bittrie	6
3. Strings	6
3.1. Trie	6
3.2. Suffix Array	7
3.3. String Matching With Suffix Array	7
3.4. LCP (Longest Common Prefix)	7

3.5. Corasick	8
4. Geometría	8
4.1. Punto	8
4.2. Line	9
4.3. Segment	9
4.4. Rectangle	9
4.5. Polygon Area	9
4.6. Circle	9
4.7. Point in Poly	10
4.8. Convex Check CHECK	10
4.9. Convex Hull	10
4.10. Cut Polygon	10
4.11. Bresenham	10
4.12. Rotate Matrix	11
5. Math	11
5.1. Exp. de Matrices en log(n)	11
5.2. Criba	11
5.3. Factorizacion	11
5.4. GCD	11
5.5. LCM	11
5.6. Simpson	11
5.7. Fraction	11
5.8. Polinomio	12
6. Grafos	12
6.1. Dijkstra	12
6.2. Bellman-Ford	13
6.3. Floyd-Warshall	13
6.4. 2-SAT + Tarjan SCC	13
6.5. Articulation Points	14
6.6. LCA + Climb	14
7. Network Flow	14
7.1. Dinic	14
7.2. Edmonds Karp's	15
7.3. Push-Relabel	16
8. Ayudamemoria	16

## 1. algorithm

`#include <algorithm> #include <numeric>`

Algo	Params	Funcion
sort, stable_sort	f, l	ordena el intervalo
nth_element	f, nth, l	void ordena el n-esimo, y particiona el resto
fill, fill_n	f, l / n, elem	void llena [f, l) o [f, f+n) con elem
lower_bound, upper_bound	f, l, elem	it al primer / ultimo donde se puede insertar elem para que quede ordenada
binary_search	f, l, elem	bool esta elem en [f, l)
copy	f, l, resul	hace resul+i=f+i $\forall i$
find, find_if, find_first_of	f, l, elem / pred / f2, l2	it encuentra i $\in [f, l)$ tq. i=elem, pred(i), i $\in [f2, l2)$
count, count_if	f, l, elem/pred	cuenta elem, pred(i)
search	f, l, f2, l2	busca [f2, l2) $\in [f, l)$
replace, replace_if	f, l, old / pred, new	cambia old / pred(i) por new
reverse	f, l	da vuelta
partition, stable_partition	f, l, pred	pred(i) ad, !pred(i) atras
min_element, max_element	f, l, [comp]	it min, max de [f, l)
lexicographical_compare	f1, l1, f2, l2	bool con [f1, l1] i [f2, l2]
next/prev_permutation	f, l	deja en [f, l) la perm sig, ant
set_intersection, set_difference, set_union, set_symmetric_difference,	f1, l1, f2, l2, res	[res, ...) la op. de conj
push_heap, pop_heap, make_heap	f, l, e / e /	mete/saca e en heap [f, l), hace un heap de [f, l)
is_heap	f, l	bool es [f, l) un heap
accumulate	f, l, i, [op]	$T = \sum / \text{oper de } [f, l)$
inner_product	f1, l1, f2, i	$T = i + [f1, l1) \cdot [f2, \dots)$
partial_sum	f, l, r, [op]	$r+i = \sum / \text{oper de } [f, f+i] \forall i \in [f, l)$
__builtin_ffs	unsigned int	Pos. del primer 1 desde la derecha
__builtin_clz	unsigned int	Cant. de ceros desde la izquierda.
__builtin_ctz	unsigned int	Cant. de ceros desde la derecha.
__builtin_popcount	unsigned int	Cant. de 1's en x.
__builtin_parity	unsigned int	1 si x es par, 0 si es impar.
__builtin_XXXXXXll	unsigned ll	= pero para long long's.

## 2. Estructuras

### 2.1. RMQ (static)

Dado un arreglo y una operación asociativa *idempotente*, get(i, j) opera sobre el rango [i, j). Restricción:  $LVL \geq \text{ceil}(\log n)$ ; Usar [ ] para llenar arreglo y luego build().

```

1 struct RMQ{
2     #define LVL 10
3     tipo vec[LVL] [1<<(LVL+1)];
4     tipo &operator[] (int p){return vec[0] [p];}
5     tipo get(int i, int j) {//intervalo [i,j)
6         int p = 31-__builtin_clz(j-i);
7         return min(vec[p] [i], vec[p] [j-(1<<p)]);
8     }
9     void build(int n) {//O(nlogn)
10        int mp = 31-__builtin_clz(n);
11        forn(p, mp) forn(x, n-(1<<p))
12            vec[p+1] [x] = min(vec[p] [x], vec[p] [x+(1<<p)]);
13    }
14 };

```

### 2.2. RMQ (dynamic)

```

1 //Dado un arreglo y una operacion asociativa con neutro, get(i, j) opera
   sobre el rango [i, j).
2 #define MAXN 100000
3 #define operacion(x, y) max(x, y)
4 const int neutro=0;
5 struct RMQ{
6     int sz;
7     tipo t[4*MAXN];
8     tipo &operator[] (int p){return t[sz+p];}
9     void init(int n){//O(nlgn)
10        sz = 1 << (32-__builtin_clz(n));
11        forr(i, sz, 2*sz) t[i]=neutro;
12    }
13     void updall(){//O(n)
14        dforsn(i, 0, sz) t[i]=operacion(t[2*i], t[2*i+1]);}
15     tipo get(int i, int j){return get(i, j, 1, 0, sz);}
16     tipo get(int i, int j, int n, int a, int b){//O(lgn)
17         if(j<=a || i>=b) return neutro;
18         if(i<=a && b<=j) return t[n];

```

```

19     int c=(a+b)/2;
20     return operacion(get(i, j, 2*n, a, c), get(i, j, 2*n+1, c, b));
21 }
22 void set(int p, tipo val){//0(lgn)
23     for(p+=sz; p>0 && t[p]!=val;){
24         t[p]=val;
25         p/=2;
26         val=operacion(t[p*2], t[p*2+1]);
27     }
28 }
29 }rmq;
30 //Usage:
31 cin >> n; rmq.init(n); forn(i, n) cin >> rmq[i]; rmq.updall();

```

### 2.3. RMQ (lazy)

```

1 //Dado un arreglo y una operacion asociativa con neutro, get(i, j) opera
  sobre el rango [i, j].
2 typedef int tipo; //tipo de los elementos del arreglo
3 typedef int tipo2; //tipo de la alteracion
4 #define operacion(x,y) x+y
5 const tipo neutro=0; const tipo2 neutro2=0;
6 #define MAXN 100000
7 struct RMQ{
8     int sz;
9     tipo t[4*MAXN];
10    tipo2 dirty[4*MAXN]; //las alteraciones pueden ser de distinto tipo
11    tipo &operator[] (int p){return t[sz+p];}
12    void init(int n){//0(nlgn)
13        sz = 1 << (32-__builtin_clz(n));
14        forr(i, sz, 2*sz) t[i]=neutro;
15        forn(i, 2*sz) dirty[i]=neutro2;
16    }
17    tipo f(tipo v, tipo2 k){//la alteracion
18        return v+k;}
19    tipo2 acum(tipo2 k1, tipo2 k2){//acumula dos alteraciones
20        return k1+k2;}
21    tipo predict(tipo v, tipo2 k, int n){//sobre un arreglo de tamaño n
22        return v+k*n; }
23
24    void modify(tipo2 v, int cant, int n){
25        t[n]=predict(t[n], v, cant); //altera un nodo
26        if(n<sz){//y marca sucio sus hijos

```

```

27        dirty[2*n]=acum(dirty[2*n], v);
28        dirty[2*n+1]=acum(dirty[2*n+1], v);
29    }
30 }
31 void correct(int cant, int n){
32     modify(dirty[n], cant, n);
33     dirty[n]=neutro2;}
34 tipo get(int i, int j){return get(i,j,1,0,sz);}
35 tipo get(int i, int j, int n, int a, int b){//0(lgn)
36     correct(n, b-a); //corrige el valor antes de usarlo
37     if(j<=a || i>=b) return neutro;
38     if(i<=a && b<=j) return t[n];
39     int c=(a+b)/2;
40     return operacion(get(i, j, 2*n, a, c), get(i, j, 2*n+1, c, b));
41 }
42 //altera los valores en [i, j] con una alteracion de val
43 void set(tipo2 val, int i, int j){set(val,i,j,1,0,sz);}
44 void set(tipo2 val, int i, int j, int n, int a, int b){//0(lgn)
45     correct(n, b-a);
46     if(j<=a || i>=b) return;
47     if(i<=a && b<=j){
48         modify(val, b-a, n);
49         return;
50     }
51     int c=(a+b)/2;
52     set(val, i, j, 2*n, a, c), set(val, i, j, 2*n+1, c, b);
53     t[n]=operacion(t[2*n], t[2*n+1]);
54 }
55 }rmq;

```

### 2.4. Fenwick Tree

```

1 //For 2D threat each column as a Fenwick tree, by adding a nested for in
  each operation
2 struct Fenwick{
3     static const int sz=1000001;
4     tipo t[sz];
5     tipo sum(int a, int b){return sum(b)-sum(a-1);}
6     void adjust(int p, tipo v){//valid with p in [1, sz), 0(lgn)
7         for(; p<sz; p+=(p&-p)) t[p]+=v; }
8     tipo sum(int p){//cumulative sum in [1, p], 0(lgn)
9         tipo s=0;
10        for(; p; p-=(p&-p)) s+=t[p];

```

```

11     return s;
12 }
13 //get largest value with cumulative sum less than or equal to x;
14 //for smallest, pass x-1 and add 1 to result
15 int getind(tipo x) { //O(lgn)
16     int idx = 0, mask = N;
17     while(mask && idx < N) {
18         int t = idx + mask;
19         if(x >= tree[t])
20             idx = t, x -= tree[t];
21         mask >>= 1;
22     }
23     return idx;
24 }
25 };

```

## 2.5. Union Find

```

1 struct UnionFind{
2     vector<int> f; //the array contains the parent of each node
3     void init(int n){f.clear(); f.insert(f.begin(), n, -1);}
4     int comp(int x){return (f[x]==-1?x:f[x]=comp(f[x]));} //O(1)
5     bool join(int i, int j) {
6         bool con=comp(i)==comp(j);
7         if(!con) f[comp(i)] = comp(j);
8         return con;
9     }
10 };

```

## 2.6. Disjoint Intervals

```

1 bool operator< (const ii &a, const ii &b) {return a.fst<b.fst;}
2 //Stores intervals as [first, second]
3 //in case of a collision it joins them in a single interval
4 struct disjoint_intervals {
5     set<ii> segs;
6     void insert(ii v) { //O(lgn)
7         if(v.snd-v.fst==0.) return; //OJO
8         set<ii>::iterator it, at;
9         at = it = segs.lower_bound(v);
10        if (at!=segs.begin() && (--at)->snd >= v.fst)
11            v.fst = at->fst, --it;
12        for(; it!=segs.end() && it->fst <= v.snd; segs.erase(it++))
13            v.snd=max(v.snd, it->snd);

```

```

14     segs.insert(v);
15 }
16 };

```

## 2.7. RMQ (2D)

```

1 struct RMQ2D{
2     static const int sz=1024;
3     RMQ t[sz];
4     RMQ &operator[] (int p){return t[sz/2+p];}
5     void build(int n, int m){ //O(nm)
6         forr(y, sz/2, sz/2+m)
7             t[y].build(m);
8         forr(y, sz/2+m, sz)
9             forn(x, sz)
10                t[y].t[x]=0;
11        dforn(y, sz/2)
12            forn(x, sz)
13                t[y].t[x]=max(t[y*2].t[x], t[y*2+1].t[x]);
14    }
15    void set(int x, int y, tipo v){ //O(lgm.lgn)
16        y+=sz/2;
17        t[y].set(x, v);
18        while(y/=2)
19            t[y].set(x, max(t[y*2][x], t[y*2+1][x]));
20    }
21    //O(lgm.lgn)
22    int get(int x1, int y1, int x2, int y2, int n=1, int a=0, int b=sz/2){
23        if(y2<=a || y1>=b) return 0;
24        if(y1<=a && b<=y2) return t[n].get(x1, x2);
25        int c=(a+b)/2;
26        return max(get(x1, y1, x2, y2, 2*n, a, c),
27                  get(x1, y1, x2, y2, 2*n+1, c, b));
28    }
29 };
30 //Example to initialize a grid of M rows and N columns:
31 RMQ2D rmq;
32 forn(i, M)
33     forn(j, N)
34         cin >> rmq[i][j];
35 rmq.build(N, M);

```

## 2.8. Big Int

```

1  #define BASEXP 6
2  #define BASE 1000000
3  #define LMAX 1000
4  struct bint{
5      int l;
6      ll n[LMAX];
7      bint(ll x=0){
8          l=0;
9          forn(i, LMAX){
10             n[i]=x%BASE;
11             x/=BASE;
12             l+=!!x||!i;
13         }
14     }
15     bint(string x){
16         l=(x.size()-1)/BASEXP+1;
17         fill(n, n+LMAX, 0);
18         ll r=1;
19         forn(i, sz(x)){
20             n[i / BASEXP] += r * (x[x.size()-1-i]-'0');
21             r*=10; if(r==BASE)r=1;
22         }
23     }
24     void out(){
25         cout << n[l-1];
26         dforsn(i, 0, l-1) printf("%6.6llu", n[i]); //6=BASEXP!
27     }
28     void invar(){
29         fill(n+l, n+LMAX, 0);
30         while(l>1 && !n[l-1]) l--;
31     }
32 };
33 bint operator+(const bint&a, const bint&b){
34     bint c;
35     c.l = max(a.l, b.l);
36     ll q = 0;
37     forn(i, c.l) q += a.n[i]+b.n[i], c.n[i]=q %BASE, q/=BASE;
38     if(q) c.n[c.l++] = q;
39     c.invar();
40     return c;
41 }
42 pair<bint, bool> lresta(const bint& a, const bint& b) // c = a - b
43 {

```

```

44     bint c;
45     c.l = max(a.l, b.l);
46     ll q = 0;
47     forn(i, c.l) q += a.n[i]-b.n[i], c.n[i]=(q+BASE) %BASE, q=(q+BASE)/
48         BASE-1;
49     c.invar();
50     return make_pair(c, !q);
51 }
52 bint& operator-= (bint& a, const bint& b){return a=lresta(a, b).first;}
53 bint operator- (const bint&a, const bint&b){return lresta(a, b).first;}
54 bool operator< (const bint&a, const bint&b){return !lresta(a, b).second
55     ;}
56 bool operator<= (const bint&a, const bint&b){return lresta(b, a).second
57     ;}
58 bool operator==(const bint&a, const bint&b){return a <= b && b <= a;}
59 bint operator*(const bint&a, ll b){
60     bint c;
61     ll q = 0;
62     forn(i, a.l) q += a.n[i]*b, c.n[i] = q %BASE, q/=BASE;
63     c.l = a.l;
64     while(q) c.n[c.l++] = q %BASE, q/=BASE;
65     c.invar();
66     return c;
67 }
68 bint operator*(const bint&a, const bint&b){
69     bint c;
70     c.l = a.l+b.l;
71     fill(c.n, c.n+b.l, 0);
72     forn(i, a.l){
73         ll q = 0;
74         forn(j, b.l) q += a.n[i]*b.n[j]+c.n[i+j], c.n[i+j] = q %BASE, q
75             /=BASE;
76         c.n[i+b.l] = q;
77     }
78     c.invar();
79     return c;
80 }
81 pair<bint, ll> ldiv(const bint& a, ll b){// c = a / b ; rm = a % b
82     bint c;
83     ll rm = 0;
84     dforsn(i, 0, a.l){
85         rm = rm * BASE + a.n[i];
86         c.n[i] = rm / b;

```

```

83         rm %= b;
84     }
85     c.l = a.l;
86     c.invar();
87     return make_pair(c, rm);
88 }
89 bint operator/(const bint&a, ll b){return ldiv(a, b).first;}
90 ll operator%(const bint&a, ll b){return ldiv(a, b).second;}
91 pair<bint, bint> ldiv(const bint& a, const bint& b){
92     bint c;
93     bint rm = 0;
94     dforsn(i, 0, a.l){
95         if (rm.l==1 && !rm.n[0])
96             rm.n[0] = a.n[i];
97         else{
98             dforsn(j, 0, rm.l) rm.n[j+1] = rm.n[j];
99             rm.n[0] = a.n[i];
100            rm.l++;
101        }
102        ll q = rm.n[b.l] * BASE + rm.n[b.l-1];
103        ll u = q / (b.n[b.l-1] + 1);
104        ll v = q / b.n[b.l-1] + 1;
105        while (u < v-1){
106            ll m = (u+v)/2;
107            if (b*m <= rm) u = m;
108            else v = m;
109        }
110        c.n[i]=u;
111        rm-=b*u;
112    }
113    c.l=a.l;
114    c.invar();
115    return make_pair(c, rm);
116 }
117 bint operator/(const bint&a, const bint&b){return ldiv(a, b).first;}
118 bint operator%(const bint&a, const bint&b){return ldiv(a, b).second;}

```

## 2.9. Modnum

```

1 struct mnum{
2     static const tipo mod=12582917;
3     tipo v;
4     mnum(tipo v=0): v(v%mod) {}

```

```

5     mnum operator+(mnum b){return v+b.v;}
6     mnum operator-(mnum b){return v>=b.v? v-b.v : mod-b.v+v;}
7     mnum operator*(mnum b){return v*b.v;}
8     mnum operator^(int n){
9         if(!n) return 1;
10        return n%2? (*this)^(n/2)*(*this) : (*this)^(n/2);}
11 };

```

## 2.10. Bittrie

```

1 struct bitrie{
2     static const int sz=1<<5;//5=ceil(log(n))
3     int V;//valor del nodo
4     vector<bitrie> ch;//childs
5     bitrie():V(0){} //NEUTRO
6     void set(int p, int v, int bit=sz>>1){ //O(log sz)
7         if(bit){
8             ch.resize(2);
9             ch[(p&bit)>0].set(p, v, bit>>1);
10            V=max(ch[0].V, ch[1].V);
11        }
12        else V=v;
13    }
14    int get(int i, int j, int a=0, int b=sz){ //O(log sz)
15        if(j<=a || i>=b) return 0; //NEUTRO
16        if(i<=a && b<=j) return V;
17        if(!sz(ch)) return V;
18        int c=(a+b)/2;
19        return max(ch[0].get(i, j, a, c), ch[1].get(i, j, c, b));
20    }
21 };

```

## 3. Strings

### 3.1. Trie

```

1 struct trie{
2     map<char, trie> m;
3     void add(const string &s, int p=0){
4         if(s[p]) m[s[p]].add(s, p+1);
5     }
6     void dfs(){
7         //Do stuff

```

```

8     forall(it, m)
9         it->second.dfs();
10 }
11 };

```

### 3.2. Suffix Array

```

1 #define MAX_N 1000
2 #define RABOUND(x) (x<n? RA[x] : 0)
3 //SA will hold the suffixes in order.
4 int SA[MAX_N], RA[MAX_N], n;
5 string s; //input string, n=sz(s)
6
7 void countingSort(int k){
8     int f[MAX_N], tmpSA[MAX_N];
9     zero(f);
10    forn(i, n) f[RABOUND(i+k)]++;
11    int sum=0;
12    forn(i, max(255, n)){
13        int t=f[i]; f[i]=sum; sum+=t;}
14    forn(i, n)
15        tmpSA[f[RABOUND(SA[i]+k)]++] = SA[i];
16    memcpy(SA, tmpSA, sizeof(SA));
17 }
18 void constructSA(){//O(n log n)
19     n=sz(s);
20     forn(i, n) SA[i]=i, RA[i]=s[i];
21     for(int k=1; k<n; k<=1){
22         countingSort(k), countingSort(0);
23         int r, tmpRA[MAX_N];
24         tmpRA[SA[0]]=r=0;
25         forr(i, 1, n)
26             tmpRA[SA[i]]=(RA[SA[i]]==RA[SA[i-1]] && RA[SA[i]+k]==RA[SA[i-1]+k])
27                 ? r : ++r;
28         memcpy(RA, tmpRA, sizeof(RA));
29         if(RA[SA[n-1]]==n-1) break;
30     }
31 }
32 void print(){//for debug
33     forn(i, n)
34         cout << i << ' ' <<
35         s.substr(SA[i], s.find( '$', SA[i])-SA[i]) << endl;}

```

### 3.3. String Matching With Suffix Array

```

1 //returns (lowerbound, upperbound) of the search
2 ii stringMatching(string P){ //O(sz(P)lgn)
3     int lo=0, hi=n-1, mid=lo;
4     while(lo<hi){
5         mid=(lo+hi)/2;
6         int res=s.compare(SA[mid], sz(P), P);
7         if(res>=0) hi=mid;
8         else lo=mid+1;
9     }
10    if(s.compare(SA[lo], sz(P), P)!=0) return ii(-1, -1);
11    ii ans; ans.fst=lo;
12    lo=0, hi=n-1, mid;
13    while(lo<hi){
14        mid=(lo+hi)/2;
15        int res=s.compare(SA[mid], sz(P), P);
16        if(res>0) hi=mid;
17        else lo=mid+1;
18    }
19    if(s.compare(SA[hi], sz(P), P)!=0) hi--;
20    ans.snd=hi;
21    return ans;
22 }

```

### 3.4. LCP (Longest Common Prefix)

```

1 //Calculates the LCP between consecutives suffixes in the Suffix Array.
2 //LCP[i] is the length of the LCP between SA[i] and SA[i-1]
3 int LCP[MAX_N];
4 void computeLCP(){//O(n)
5     int phi[MAX_N], PLCP[MAX_N];
6     phi[SA[0]]=-1;
7     forr(i, 1, n) phi[SA[i]]=SA[i-1];
8     int L=0;
9     forn(i, n){
10        if(phi[i]==-1) {PLCP[i]=0; continue;}
11        while(s[i+L]==s[phi[i]+L]) L++;
12        PLCP[i]=L;
13        L=max(L-1, 0);
14    }
15    forn(i, n) LCP[i]=PLCP[SA[i]];
16 }

```



### 3.5. Corasick

```

1 struct trie{
2     map<char, trie> next;
3     trie* tran[256]; //transiciones del automata
4     int idhoja, szhoja; //id de la hoja o 0 si no lo es
5     //link lleva al sufijo mas largo, nxthoja lleva al mas largo pero que
6     //es hoja
7     trie *padre, *link, *nxthoja;
8     char pch; //caracter que conecta con padre
9     trie(): tran(), idhoja(), padre(), link() {}
10    void insert(const string &s, int id=1, int p=0){ //id>0!!!
11        if(p<sz(s)){
12            trie &ch=next[s[p]];
13            tran[(int)s[p]]=&ch;
14            ch.padre=this, ch.pch=s[p];
15            ch.insert(s, id, p+1);
16        }
17        else idhoja=id, szhoja=sz(s);
18    }
19    trie* get_link() {
20        if(!link){
21            if(!padre) link=this; //es la raiz
22            else if(!padre->padre) link=padre; //hijo de la raiz
23            else link=padre->get_link()->get_tran(pch);
24        }
25        return link;
26    }
27    trie* get_tran(int c) {
28        if(!tran[c])
29            tran[c] = !padre? this : this->get_link()->get_tran(c);
30        return tran[c];
31    }
32    trie *get_nxthoja(){
33        if(!nxthoja) nxthoja = get_link()->idhoja? link : link->nxthoja;
34        return nxthoja;
35    }
36    void print(int p){
37        if(idhoja)
38            cout << "found_" << idhoja << "_at_position_" << p-szhoja << endl
39            ;
40        if(get_nxthoja()) get_nxthoja()->print(p);

```

```

40    }
41    void matching(const string &s, int p=0){
42        print(p);
43        if(p<sz(s)) get_tran(s[p])->matching(s, p+1);

```

## 4. Geometría

#define EPS 1e-9

### 4.1. Punto

```

1 struct pto{
2     tipo x, y;
3     pto(tipo x=0, tipo y=0):x(x),y(y){}
4     pto operator+(pto a){return pto(x+a.x, y+a.y);}
5     pto operator-(pto a){return pto(x-a.x, y-a.y);}
6     pto operator+(tipo a){return pto(x+a, y+a);}
7     pto operator*(tipo a){return pto(x*a, y*a);}
8     pto operator/(tipo a){return pto(x/a, y/a);}
9     //dot product, producto interno:
10    tipo operator*(pto a){return x*a.x+y*a.y;}
11    //module of the cross product or vectorial product:
12    //if a is less than 180 clockwise from b, a^b>0
13    tipo operator^(pto a){return x*a.y-y*a.x;}
14    //returns true if this is at the left side of line qr
15    bool left(pto q, pto r){return ((q-*this)^(r-*this))>0;}
16    bool operator<(const pto &a) const{return x<a.x || (abs(x-a.x)<EPS &&
17        y<a.y);}
18    bool operator==(pto a){return abs(x-a.x)<EPS && abs(y-a.y)<EPS;}
19    double norm(){return sqrt(x*x+y*y);}
20    tipo norm_sq(){return x*x+y*y;}
21 };
22 double dist(pto a, pto b){return (b-a).norm();}
23 typedef pto vec;
24 double angle(pto a, pto o, pto b){
25     vec oa=a-o, ob=b-o;
26     return acos((oa*ob) / sqrt(oa.norm_sq()*ob.norm_sq()));}
27
28 //rotate p by theta rads CCW w.r.t. origin (0,0)
29 pto rotate(pto p, double theta){
30     return pto(p.x*cos(theta)-p.y*sin(theta),
31         p.x*sin(theta)+p.y*cos(theta));

```



32 | }

## 4.2. Line

```

1 struct line{
2     line() {}
3     double a,b,c;//Ax+By=C
4     //pto MUST store float coordinates!
5     line(double a, double b, double c):a(a),b(b),c(c){}
6     line(pto p, pto q): a(q.y-p.y), b(p.x-q.x), c(a*p.x+b*p.y) {}
7 };
8 bool parallels(line l1, line l2){return abs(l1.a*l2.b-l2.a*l1.b)<EPS;}
9 pto inter(line l1, line l2){//intersection
10     double det=l1.a*l2.b-l2.a*l1.b;
11     if(abs(det)<EPS) return pto(INF, INF);//parallels
12     return pto(l2.b*l1.c-l1.b*l2.c, l1.a*l2.c-l2.a*l1.c)/det;
13 }
```

## 4.3. Segment

```

1 struct segm{
2     pto s,f;
3     segm(pto s, pto f):s(s), f(f) {}
4     pto closest(pto p) {//use for dist to point
5         double l2 = dist_sq(s, f);
6         if(l2==0.) return s;
7         double t=((p-s)*(f-s))/l2;
8         if (t<0.) return s;//not write if is a line
9         else if(t>1.)return f;//not write if is a line
10        return s+((f-s)*t);
11    }
12    bool inside(pto p){
13        return ((s-p)^(f-p))==0 && min(s, f)< *this && *this<max(s, f);}
14 };
15
16 bool insidebox(pto a, pto b, pto p) {
17     return (a.x-p.x)*(p.x-b.x)>-EPS && (a.y-p.y)*(p.y-b.y)>-EPS;
18 }
19 pto inter(segm s1, segm s2){
20     pto r=inter(line(s1.s, s1.f), line(s2.s, s2.f));
21     if(insidebox(s1.s,s1.f,p) && insidebox(s2.s,s2.f,p))
22         return r;
23     return pto(INF, INF);
24 }
```

## 4.4. Rectangle

```

1 struct rect{
2     //lower-left and upper-right corners
3     pto lw, up;
4 };
5 //returns if there's an intersection and stores it in r
6 bool inter(rect a, rect b, rect &r){
7     r.lw=pto(max(a.lw.x, b.lw.x), max(a.lw.y, b.lw.y));
8     r.up=pto(min(a.up.x, b.up.x), min(a.up.y, b.up.y));
9     //check case when only a edge is common
10    return r.lw.x<r.up.x && r.lw.y<r.up.y;
11 }
```

## 4.5. Polygon Area

```

1 double area(vector<tipo> &p){//0(sz(p))
2     double area=0;
3     forn(i, sz(p)) area+=p[i]^p[(i+1)%sz(p)];
4     //if points are in clockwise order then area is negative
5     return abs(area)/2;
6 }
7 //Area ellipse = M_PI*a*b where a and b are the semi axis lengths
8 //Area triangle = sqrt(s*(s-a)(s-b)(s-c)) where s=(a+b+c)/2
```

## 4.6. Circle

```

1 vec perp(vec v){return vec(-v.y, v.x);}
2 line bisector(pto x, pto y){
3     line l=line(x, y); pto m=(x+y)/2;
4     return line(-l.b, l.a, -l.b*m.x+l.a*m.y);
5 }
6 struct Circle{
7     pto o;
8     double r;
9     //circle determined by three points, uses line
10    Circle(pto x, pto y, pto z){
11        o=inter(bisector(x, y), bisector(y, z));
12        r=dist(o, x);
13    }
14    pair<pto, pto> ptosTang(pto p){
15        pto m=(p+o)/2;
16        tipo d=dist(o, m);
17        tipo a=r*r/(2*d);
```

```

18     tipo h=sqrt(r*r-a*a);
19     pto m2=o+(m-o)*a/d;
20     vec per=perp(m-o)/d;
21     return mkp(m2-per*h, m2+per*h);
22 }
23 };
24 //finds the center of the circle containing p1 and p2 with radius r
25 //as there may be two solutions swap p1, p2 to get the other
26 bool circle2PtsRad(pto p1, pto p2, double r, pto &c){
27     double d2=(p1-p2).norm_sq(), det=r*r/d2-0.25;
28     if(det<0) return false;
29     c=(p1+p2)/2+perp(p2-p1)*sqrt(det);
30     return true;
31 }

```

#### 4.7. Point in Poly

```

1 //checks if v is inside of P, using ray casting
2 //works with convex and concave.
3 //excludes boundaries, handle it separately using segment.inside()
4 bool inPolygon(pto v, vector<pto>& P) {
5     bool c = false;
6     forn(i, sz(P)){
7         int j=(i+1)%sz(P);
8         if((P[j].y>v.y) != (P[i].y > v.y) &&
9 (v.x < (P[i].x - P[j].x) * (v.y-P[j].y) / (P[i].y - P[j].y) + P[j].x))
10             c = !c;
11     }
12     return c;
13 }

```

#### 4.8. Convex Check CHECK

```

1 bool isConvex(vector<int> &p){//O(N)
2     int N=sz(p);
3     if(N<3) return false;
4     bool isLeft=p[0].left(p[1], p[2]);
5     forr(i, 1, N)
6         if(p[i].left(p[(i+1)%N], p[(i+2)%N])!=isLeft)
7             return false;
8     return true; }

```

#### 4.9. Convex Hull

```

1 //stores convex hull of P in S, CCW order
2 void CH(vector<pto>& P, vector<pto> &S){
3     S.clear();
4     sort(P.begin(), P.end());
5     forn(i, sz(P)){
6         while(sz(S)>= 2 && S[sz(S)-1].left(S[sz(S)-2], P[i])) S.pop_back();
7         S.pb(P[i]);
8     }
9     S.pop_back();
10    int k=sz(S);
11    dforn(i, sz(P)){
12        while(sz(S) >= k+2 && S[sz(S)-1].left(S[sz(S)-2], P[i])) S.pop_back
13            ();
14        S.pb(P[i]);
15    }
16    S.pop_back();
17 }

```

#### 4.10. Cut Polygon

```

1 //cuts polygon Q along the line ab
2 //stores the left side (swap a, b for the right one) in P
3 void cutPolygon(pto a, pto b, vector<pto> Q, vector<pto> &P){
4     P.clear();
5     forn(i, sz(Q)){
6         double left1=(b-a)^(Q[i]-a), left2=(b-a)^(Q[(i+1)%sz(Q)]-a);
7         if(left1>=0) P.pb(Q[i]);
8         if(left1*left2<0)
9             P.pb(inter(line(Q[i], Q[(i+1)%sz(Q)]), line(a, b)));
10    }
11 }

```

#### 4.11. Bresenham

```

1 //plot a line approximation in a 2d map
2 void bresenham(pto a, pto b){
3     pto d=b-a; d.x=abs(d.x), d.y=abs(d.y);
4     pto s(a.x<b.x? 1: -1, a.y<b.y? 1: -1);
5     int err=d.x-d.y;
6     while(1){
7         m[a.x][a.y]=1;//plot
8         if(a==b) break;
9         int e2=2*err;
10        if(e2 > -d.y){

```

```

11     err-=d.y, a.x+=s.x;
12     if(e2 < d.x)
13         err+= d.x, a.y+= s.y;
14 }
15 }

```

#### 4.12. Rotate Matrix

```

1 //rotates matrix t 90 degrees clockwise
2 //using auxiliary matrix t2(faster)
3 void rotate(){
4     forn(x, n) forn(y, n)
5         t2[n-y-1][x]=t[x][y];
6     memcpy(t, t2, sizeof(t));
7 }

```

### 5. Math

#### 5.1. Exp. de Matrices en log(n)

```

1 struct M22{        // |a b|
2     double a,b,c,d; // |c d|
3     M22 operator*(const M22 &p) const {
4         return (M22){a*p.a+b*p.c, a*p.b+b*p.d, c*p.a+d*p.c,c*p.b+d*p.d};}
5 };
6 M22 operator^(const M22 &p, int n){
7     if(!n) return (M22){1, 0, 0, 1}; //identidad
8     M22 q=p^(n/2); q=q*q;
9     return n%2? p * q : q;}

```

#### 5.2. Criba

```

1 #define MAXP 80000 //no necesariamente primo
2 int criba[MAXP+1];
3 vector<int> primos;
4
5 void buscarprimos(){
6     int sq=sqrt(MAXP)+2;
7     forr(p, 2, sq) if(!criba[p]){
8         for(int m=p*p; m<=MAXP; m+=p) //borro los multiplos de p
9             if(!criba[m]) criba[m]=p;
10    }
11 }

```

### 5.3. Factorizacion

Sea  $n = \prod p_i^{k_i}$ , fact(n) genera un map donde a cada  $p_i$  le asocia su  $k_i$

```

1 //factoriza bien numeros hasta (maximo primo)^2
2 map<ll,ll> fact(ll n){
3     map<ll,ll> ret;
4     forall(p, primos){
5         while(!(n%p)){
6             ret[*p]++; //divisor found
7             n/=p;
8         }
9     }
10    if(n>1) ret[n]++;
11    return ret;
12 }

```

#### 5.4. GCD

```

1 tipo gcd(tipo a, tipo b){return a?gcd(b %a, a):b;}

```

#### 5.5. LCM

```

1 tipo lcm(tipo a, tipo b){return a / gcd(a,b) * b;}

```

#### 5.6. Simpson

```

1 double integral(double a, double b, int n=10000) { //0(n), n=cantdiv
2     double area=0, h=(b-a)/n, fa=f(a), fb;
3     forn(i, n){
4         fb=f(a+h*(i+1));
5         area+=fa+ 4*f(a+h*(i+0.5)) +fb, fa=fb;
6     }
7     return area*h/6.;}

```

#### 5.7. Fraction

```

1 struct frac{
2     tipo p,q;
3     frac(tipo p=0, tipo q=1):p(p),q(q) {norm();}
4     tipo mcd(tipo a, tipo b){return a?mcd(b %a, a):b;}
5     void norm(){
6         tipo a = mcd(p,q);
7         if(a) p/=a, q/=a;

```

```

8     else q=1;
9     if (q<0) q=-q, p=-p;}
10    frac operator+(const frac& o){
11        tipo a = mcd(q,o.q);
12        return frac(p*(o.q/a)+o.p*(q/a), q*(o.q/a));}
13    frac operator-(const frac& o){
14        tipo a = mcd(q,o.q);
15        return frac(p*(o.q/a)-o.p*(q/a), q*(o.q/a));}
16    frac operator*(frac o){
17        tipo a = mcd(q,o.p), b = mcd(o.q,p);
18        return frac((p/b)*(o.p/a), (q/a)*(o.q/b));}
19    frac operator/(frac o){
20        tipo a = mcd(q,o.q), b = mcd(o.p,p);
21        return frac((p/b)*(o.q/a), (q/a)*(o.p/b));}
22    bool operator<(const frac &o) const{return p*o.q < o.p*q;}
23    bool operator==(frac o){return p==o.p&&q==o.q;}
24 };

```

## 5.8. Polinomio

```

1  #define MAX_GR 20
2  struct poly {
3      tipo p[MAX_GR]; //guarda los coeficientes del polinomio
4      poly(){zero(p);}
5      int gr(){//calculates grade of the polynomial
6          dforn(i,MAX_GR) if(p[i]) return i;
7          return 0; }
8      bool isnull() {return gr()==0 && !p[0];}
9      poly operator+(poly b) { // - is analogous
10         poly c=THIS;
11         forn(i,MAX_GR) c.p[i]+=b.p[i];
12         return c;
13     }
14     poly operator*(poly b) {
15         poly c;
16         forn(i,MAX_GR) forn(k,i+1) c.p[i]+=p[k]*b.p[i-k];
17         return c;
18     }
19     tipo eval(tipo v) {
20         tipo sum = 0;
21         dforsn(i, 0, MAX_GR) sum=sum*v + p[i];
22         return sum;
23     }

```

```

24 //the following function generates the roots of the polynomial
25 //it can be easily modified to return float roots
26 set<tipo> roots(){
27     set<tipo> roots;
28     tipo a0 = abs(p[0]), an = abs(p[gr()]);
29     vector<tipo> ps,qs;
30     forr(p,1,sqrt(a0)+1) if (a0%p==0) ps.pb(p),ps.pb(a0/p);
31     forr(q,1,sqrt(an)+1) if (an%q==0) qs.pb(q),qs.pb(an/q);
32     forall(pt,ps)
33         forall(qt,qs) if ( (*pt) % (*qt)==0 ) {
34             tipo root = abs((*pt) / (*qt));
35             if (eval(root)==0) roots.insert(root);
36         }
37     return roots;
38 }
39 };
40 //the following functions allows parsing an expression like
41 //34+150+4*45
42 //into a polynomial(el numero en funcion de la base)
43 #define LAST(s) (sz(s)? s[sz(s)-1] : 0)
44 #define POP(s) s.erase(--s.end());
45 poly D(string &s) {
46     poly d;
47     for(int i=0; isdigit(LAST(s)); i++) d.p[i]=LAST(s)-'0', POP(s);
48     return d;}
49
50 poly T(string &s) {
51     poly t=D(s);
52     if (LAST(s)=='*'){POP(s); return T(s)*t;}
53     return t;
54 }
55 //main function, call this to parse
56 poly E(string &s) {
57     poly e=T(s);
58     if (LAST(s)=='+'){POP(s); return E(s)+e;}
59     return e;
60 }

```

## 6. Grafos

### 6.1. Dijkstra

```

1  #define INF 1e9

```

```

2 int N;
3 #define MAX_V 250001
4 vector<ii> G[MAX_V];
5 //To add an edge use
6 #define add(a, b, w) G[a].pb(mkp(w, b))
7
8 ll dijkstra(int s, int t){//O(|E| log |V|)
9     priority_queue<ii, vector<ii>, greater<ii> > Q;
10     vector<ll> dist(N, INF); vector<int> dad(N, -1);
11     Q.push(mkp(0, s)); dist[s] = 0;
12     while(sz(Q)){
13         ii p = Q.top(); Q.pop();
14         if(p.snd == t) break;
15         forall(it, G[p.snd])
16             if(dist[p.snd]+it->first < dist[it->snd]){
17                 dist[it->snd] = dist[p.snd] + it->fst;
18                 dad[it->snd] = p.snd;
19                 Q.push(mkp(dist[it->snd], it->snd));
20             }
21     }
22     return dist[t];
23     if(dist[t]<INF)//path generator
24         for(int i=t; i!=-1; i=dad[i])
25             printf("%d%c", i, (i==s?'\\n':' '));
26 }

```

## 6.2. Bellman-Ford

```

1 vector<ii> G[MAX_N]; //ady. list with pairs (weight, dst)
2 int dist[MAX_N];
3 void bford(int src){//O(VE)
4     dist[src]=0;
5     for(i, N-1) for(j, N) if(dist[j]!=INF) forall(it, G[j])
6         dist[it->snd]=min(dist[it->snd], dist[j]+it->fst);
7 }
8
9 bool hasNegCycle(){
10     for(j, N) if(dist[j]!=INF) forall(it, G[j])
11         if(dist[it->snd]>dist[j]+it->fst) return true;
12     //inside if: all points reachable from it->snd will have -INF distance
13     // (do bfs)
14     return false;
15 }

```

## 6.3. Floyd-Warshall

```

1 //G[i][j] contains weight of edge (i, j) or INF
2 //G[i][i]=0
3 int G[MAX_N][MAX_N];
4 void floyd(){//O(N^3)
5     for(k, N) for(i, N) if(G[i][k]!=INF) for(j, N) if(G[k][j]!=INF)
6         G[i][j]=min(G[i][j], G[i][k]+G[k][j]);
7 }
8 bool inNegCycle(int v){
9     return G[v][v]<0;}
10 //checks if there's a neg. cycle in path from a to b
11 bool hasNegCycle(int a, int b){
12     for(i, N) if(G[a][i]!=INF && G[i][i]<0 && G[i][b]!=INF)
13         return true;
14     return false;
15 }

```

## 6.4. 2-SAT + Tarjan SCC

```

1 //We have a vertex representing a var and other for his negation.
2 //Every edge stored in G represents an implication. To add an equation
3 //of the form a||b, use addor(a, b)
4 //MAX=max cant var, n=cant var
5 #define addor(a, b) (G[neg(a)].pb(b), G[neg(b)].pb(a))
6 vector<int> G[MAX*2];
7 //idx[i]=index assigned in the dfs
8 //lw[i]=lowest index(closer from the root) reachable from i
9 int lw[MAX*2], idx[MAX*2], qidx;
10 stack<int> q;
11 int qcmp, cmp[MAX*2];
12 //verdad[cmp[i]]=valor de la variable i
13 bool verdad[MAX*2+1];
14
15 int neg(int x) { return x>=n? x-n : x+n;}
16 void tjn(int v){
17     lw[v]=idx[v]==qidx;
18     q.push(v), cmp[v]=-2;
19     forall(it, G[v]){
20         if(!idx[*it] || cmp[*it]==-2){
21             if(!idx[*it]) tjn(*it);
22             lw[v]=min(lw[v], lw[*it]);
23         }
24     }
25 }

```

```

23 }
24 if(lw[v]==idx[v]){
25     qcmp++;
26     int x;
27     do{x=q.top(); q.pop(); cmp[x]=qcmp;}while(x!=v);
28     verdad[qcmp]=(cmp[neg(v)]<0);
29 }
30 }
31 //remember to CLEAR G!!!
32 bool satisf(){//0(n)
33     memset(idx, 0, sizeof(idx)), qidx=0;
34     memset(cmp, -1, sizeof(cmp)), qcmp=0;
35     forn(i, n){
36         if(!idx[i]) tjn(i);
37         if(!idx[neg(i)]) tjn(neg(i));
38     }
39     forn(i, n) if(cmp[i]==cmp[neg(i)]) return false;
40     return true;
41 }

```

## 6.5. Articulation Points

```

1 int N;
2 vector<int> G[1000000];
3 //V[i]=node number(if visited), L[i]= lowest V[i] reachable from i
4 int qV, V[1000000], L[1000000], P[1000000];
5 void dfs(int v, int f){
6     L[v]=V[v]=++qV;
7     forall(it, G[v])
8         if(!V[*it]){
9             dfs(*it, v);
10            L[v] = min(L[v], L[*it]);
11            P[v] += L[*it]>=V[v];
12        }
13        else if(*it!=f)
14            L[v]=min(L[v], V[*it]);
15 }
16 int cantart(){ //0(n)
17     qV=0;
18     zero(V), zero(P);
19     dfs(1, 0); P[1]--;
20     int q=0;
21     forn(i, N) if(P[i]) q++;

```

```

22 return q;
23 }

```

## 6.6. LCA + Climb

```

1 //f[v][k] holds the 2^k father of v
2 //L[v] holds the level of v
3 int N, f[100001][20], L[100001];
4 void build(){//f[i][0] must be filled previously, 0(nlgn)
5     forn(k, 20-1) forn(i, N) f[i][k+1]=f[f[i][k]][k];}
6
7 #define lg(x) (31-__builtin_clz(x))//=floor(log2(x))
8
9 int climb(int a, int d){//0(lgn)
10     if(!d) return a;
11     dforn(i, lg(L[a])+1)
12         if(1<<i<=d)
13             a=f[a][i], d-=1<<i;
14     return a;
15 }
16 int lca(int a, int b){//0(lgn)
17     if(L[a]<L[b]) swap(a, b);
18     a=climb(a, L[a]-L[b]);
19     if(a==b) return a;
20     dforn(i, lg(L[a])+1)
21         if(f[a][i]!=f[b][i])
22             a=f[a][i], b=f[b][i];
23     return f[a][0];
24 }

```

## 7. Network Flow

### 7.1. Dinic

```

1 int nodes, src, dest;
2 int dist[MAX], q[MAX], work[MAX];
3
4 struct Edge {
5     int to, rev;
6     ll f, cap;
7     Edge(int to, int rev, ll f, ll cap) : to(to), rev(rev), f(f), cap(cap)
8     {}
9 };

```

```

9
10 vector<Edge> G[MAX];
11
12 // Adds bidirectional edge
13 void addEdge(int s, int t, ll cap){
14     G[s].push_back(Edge(t, G[t].size(), 0, cap));
15     G[t].push_back(Edge(s, G[s].size()-1, 0, 0));
16 }
17
18 bool dinic_bfs() {
19     fill(dist, dist + nodes, -1);
20     dist[src] = 0;
21     int qt = 0;
22     q[qt++] = src;
23     for (int qh = 0; qh < qt; qh++) {
24         int u = q[qh];
25         forall(e, G[u]){
26             int v = e->to;
27             if(dist[v]<0 && e->f < e->cap){
28                 dist[v]=dist[u]+1;
29                 q[qt++]=v;
30             }
31         }
32     }
33     return dist[dest] >= 0;
34 }
35
36 ll dinic_dfs(int u, ll f) {
37     if (u == dest) return f;
38     for (int &i = work[u]; i < (int) G[u].size(); i++) {
39         Edge &e = G[u][i];
40         if (e.cap <= e.f) continue;
41         int v = e.to;
42         if (dist[v] == dist[u] + 1) {
43             ll df = dinic_dfs(v, min(f, e.cap - e.f));
44             if (df > 0) {
45                 e.f += df;
46                 G[v][e.rev].f -= df;
47                 return df;
48             }
49         }
50     }
51     return 0;

```

```

52 }
53
54 ll maxFlow(int _src, int _dest) { //O(V^2 E)<
55     src = _src;
56     dest = _dest;
57     ll result = 0;
58     while (dinic_bfs()) {
59         fill(work, work + nodes, 0);
60         while(ll delta = dinic_dfs(src, INF))
61             result += delta;
62     }
63     return result;
64 }

```

## 7.2. Edmonds Karp's

```

1 #define MAX_V 1000
2 #define INF 1e9
3 //special nodes
4 #define SRC 0
5 #define SNK 1
6 map<int, int> G[MAX_V]; //limpiar esto
7 //To add an edge use
8 #define add(a, b, w) G[a][b]=w
9 int f, p[MAX_V];
10 void augment(int v, int minE){
11     if(v==SRC) f=minE;
12     else if(p[v]!==-1){
13         augment(p[v], min(minE, G[p[v]][v]));
14         G[p[v]][v]-=f, G[v][p[v]]+=f;
15     }
16 }
17 ll maxflow(){ //O(VE^2)
18     ll Mf=0;
19     do{
20         f=0;
21         char used[MAX_V]; queue<int> q; q.push(SRC);
22         zero(used), memset(p, -1, sizeof(p));
23         while(sz(q)){
24             int u=q.front(); q.pop();
25             if(u==SNK) break;
26             forall(it, G[u])
27                 if(it->snd>0 && !used[it->fst])

```



```

28     used[it->fst]=true, q.push(it->fst), p[it->fst]=u;
29 }
30 augment(SNK, INF);
31 Mf+=f;
32 }while(f);
33 return Mf;
34 }

```

### 7.3. Push-Relabel

```

1  #define MAX_V 1000
2  int N;//valid nodes are [0...N-1]
3  #define INF 1e9
4  //special nodes
5  #define SRC 0
6  #define SNK 1
7  map<int, int> G[MAX_V];
8  //To add an edge use
9  #define add(a, b, w) G[a][b]=w
10 ll excess[MAX_V];
11 int height[MAX_V], active[MAX_V], count[2*MAX_V+1];
12 queue<int> Q;
13 void enqueue(int v) {
14     if (!active[v] && excess[v] > 0) active[v]=true, Q.push(v); }
15 void push(int a, int b) {
16     int amt = min(excess[a], ll(G[a][b]));
17     if(height[a] <= height[b] || amt == 0) return;
18     G[a][b]-=amt, G[b][a]+=amt;
19     excess[b] += amt, excess[a] -= amt;
20     enqueue(b);
21 }
22 void gap(int k) {
23     forn(v, N){
24         if (height[v] < k) continue;
25         count[height[v]]--;
26         height[v] = max(height[v], N+1);
27         count[height[v]]++;
28         enqueue(v);
29     }
30 }
31 void relabel(int v) {
32     count[height[v]]--;
33     height[v] = 2*N;

```

```

34     forall(it, G[v])
35         if(it->snd)
36             height[v] = min(height[v], height[it->fst] + 1);
37     count[height[v]]++;
38     enqueue(v);
39 }
40 ll maxflow() { //O(V^3)
41     zero(height), zero(active), zero(count), zero(excess);
42     count[0] = N-1;
43     count[N] = 1;
44     height[SRC] = N;
45     active[SRC] = active[SNK] = true;
46     forall(it, G[SRC]){
47         excess[SRC] += it->snd;
48         push(SRC, it->fst);
49     }
50     while(sz(Q)) {
51         int v = Q.front(); Q.pop();
52         active[v]=false;
53         forall(it, G[v]) push(v, it->fst);
54         if(excess[v] > 0)
55             count[height[v]] == 1? gap(height[v]):relabel(v);
56     }
57     ll mf=0;
58     forall(it, G[SNK]) mf+=G[it->fst][SNK];
59     return mf;
60 }

```

## 8. Ayudamemoria

### Límites

```

1  #include <climits> //INT_MIN, LONG_MAX, ULLONG_MAX, etc.

```

### Cant. decimales

```

1  #include <iomanip>
2  cout << setprecision(2) << fixed;

```

### Rellenar con espacios(para justificar)

```

1  #include <iomanip>
2  cout << setfill('␣') << setw(3) << 2 << endl;

```

### Leer hasta fin de línea

```
1 | #include <sstream>
2 | //hacer cin.ignore() antes de getline()
3 | while(getline(cin, line)){
4 |     istringstream is(line);
5 |     while(is >> X)
6 |         cout << X << "□";
7 |     cout << endl;
8 | }
```

### Aleatorios

```
1 | #define RAND(a, b) (rand()%(b-a+1)+a)
2 | srand(time(NULL));
```

### Doubles Comp.

```
1 | const double EPS = 1e-9;
2 | x == y <=> fabs(x-y) < EPS
3 | x > y <=> x > y + EPS
4 | x >= y <=> x > y - EPS
```

### Límites

```
1 | #include <limits>
2 | numeric_limits<T>
3 |     ::max()
4 |     ::min()
5 |     ::epsilon()
```

### Muahaha

```
1 | #include <signal.h>
2 | void divzero(int p){
3 |     while(true);}
4 | void segm(int p){
5 |     exit(0);}
6 | //in main
7 | signal(SIGFPE, divzero);
8 | signal(SIGSEGV, segm);
```

### Mejorar velocidad

```
1 | ios::sync_with_stdio(false);
```

### Leer del teclado

```
1 | freopen("/dev/tty", "a", stdin);
```

### File setup

```
1 | //tambien se pueden usar comas: {a, x, m, l}
2 | for i in {a..k}; do cp template.cpp $i.cpp; touch $i.in; done
```