

Quiz 18-25: Time Complexity, Set, and Dictionary

1) Choose the best container (synergy)

1. `set` — check membership (`"Ben" in guests`) — $O(1)$
 2. `dict` — look up value (`phones["Amy"]`) — $O(1)$
 3. `list` — keep order + print all (`for score in scores:`) — $O(n)$
-

2) Fill in the blanks (set vs list membership)

- `x in my_list` is usually $O(n)$.
 - `x in my_set` is usually $O(1)$ (average).
 - `x in my_dict` checks only the dictionary's **keys**.
-

3) What can be a set element / dict key?

Item	Can be in a <code>set</code> ?	Can be a <code>dict</code> key?
<code>7</code>	YES	YES
<code>"cat"</code>	YES	YES
<code>(1, 2)</code>	YES	YES
<code>[1, 2]</code>	NO	NO

Rule: A set element / dict key must be **hashable** (usually **immutable**).

4) Common keys between dictionaries

```
a = {"Amy": 3, "Ben": 5, "Chloe": 1}
b = {"Ben": 2, "Drew": 9}

s1 = set(a.keys())
s2 = set(b.keys())
s = s1 & s2
print(s)
```

(That makes `common == {"Ben"} .`)

5) Fast “seen before?” logic

Option B (a `set`) is better because `word in words_set` is **$O(1)$** on average, while `word in words_list` is **$O(n)$** .

6) Time complexity of a “build then look up” plan

- Step 1 (build dict from `n` pairs): **$O(n)$**
 - Step 2 (look up one key): **$O(1)$** (average)
-

7) Unique vs counts (set + dict together)

One correct output is:

```
{ 'A', 'B', 'C' }
2
3
```

(The set order may vary.)

8) Common players (dict keys → set intersection)

```
{ 'Ben' }
1
```

(Set order may vary, but there is only one item.)

9) Updating scores (dict overwrite)

Final dictionary (order may vary):

```
{ 'Amy': 2, 'Ben': 7, 'Chloe': 1 }  
7
```

10) “Any overlap?” two ways

Answer: $O(n^2)$

Explanation:

- The loop runs up to `n` times.
- `x in b` is a list membership check. Its time complexity is $O(n)$.
- Thus the overall time complexity is $O(n^2)$.

11) “Any overlap?” using a set (faster idea)

Answer: $O(n)$

Reason:

- Building `b_set` has $O(n)$ time complexity.
- Then we do `n` membership checks in a set. Each costs $O(1)$ time complexity.
- Totally $O(n)$ time complexity.

12) One bug: set method name

Corrected lines:

```
colors.add("red")  
colors.add("blue")
```

13) Build a frequency dictionary (fill in blanks)

```
counts[x] = counts.get(x, 0) + 1
```

14) Find duplicates (dict + set together)

One correct solution:

```
for f in fruits:
    counts[f] = counts.get(f, 0) + 1
    if counts[f] >= 2:
        dupes.add(f)
```

Expected results:

- `counts` is `{'apple': 3, 'banana': 2, 'orange': 1}` (order may vary)
- `dupes` is `{'apple', 'banana'}` (order may vary)

15) Set operations from lists (union + intersection)

One correct solution:

```
math_set = set(math)
music_set = set(music)

print(math_set | music_set)    # union
print(math_set & music_set)    # intersection
```

16) First repeated word (fast check with a set)

One correct solution:

```
seen = set()

for w in words:
    if w in seen:
        print(w)
        break
    seen.add(w)
```

It prints `cat` .

17) Mini inverted index (dict of sets) — fill in blanks

Blanks:

- `set()`
- `add`

So the completed part is:

```
if w not in index:
    index[w] = set()
index[w].add(i)
```

18) Pick the faster plan (big-O + explanation)

1) Plan A: $O(n^2)$

2) Plan B: $O(n)$

3) Because Plan A does up to `n` list membership checks and each check can take up to `n` steps, while Plan B scans the list once to build a set.