

SOLUTION ASSIGNMENT-05 5C & 5D

PART-01

R3, R13

A centralized routing algorithm computes the least-cost path between a source and destination by using complete, global knowledge about the network. The algorithm needs to have the complete knowledge of the connectivity between all nodes and all links' costs. The actual calculation can be run at one site or could be replicated in the routing component of each and every router. A distributed routing algorithm calculates the least-cost path in an iterative, distributed manner by the routers. With a decentralized algorithm, no node has the complete information about the costs of all network links. Each node begins with only the knowledge of the costs of its own directly attached links, and then through an iterative process of calculation and information exchange with its neighboring nodes, a node gradually calculates the least-cost path to a destination or a set of destinations.

OSPF protocol is an example of centralized routing algorithm, and BGP is an example of a distributed routing algorithm.

False.

A BGP router can choose not to add its own identity to the received path and then send that new path on to all of its neighbors, as BGP is a policy-based routing protocol. This can happen in the following scenario. The destination of the received path is some other AS, instead of the BGP router's AS, and the BGP router does not want to work as a transit router.

PROBLEMS

Problem 3

Step	N'	$D(t),p(t)$	$D(u),p(u)$	$D(v),p(v)$	$D(w),p(w)$	$D(y),p(y)$	$D(z),p(z)$
0	x	∞	∞	3,x	6,x	6,x	8,x
1	xv	7,v	6,v	3,x	6,x	6,x	8,x
2	xvu	7,v	6,v	3,x	6,x	6,x	8,x
3	xvuw	7,v	6,v	3,x	6,x	6,x	8,x
4	xvuwy	7,v	6,v	3,x	6,x	6,x	8,x
5	xvuwyt	7,v	6,v	3,x	6,x	6,x	8,x
6	xvuwytz	7,v	6,v	3,x	6,x	6,x	8,x

Problem 16

One way for C to force B to hand over all of B's traffic to D on the east coast is for C to only advertise its route to D via its east coast peering point with C.

Problem 20

Since Z wants to transit Y's traffic, Z will send route advertisements to Y. In this manner, when Y has a datagram that is destined to an IP that can be reached through Z, Y will have the option of sending the datagram through Z. However, if Z advertizes routes to Y, Y can re-advertize those routes to X. Therefore, in this case, there is nothing Z can do from preventing traffic from X to transit through Z.