

Database Systems (CS2005)

Sessional-2 Exam

Date: Thu, 10 Apr 2025

Course Instructor(s)

IR, ZA, MN, AA, HI, MM, SA

Total Time (Hrs.): 1

Total Marks: 20

Total Questions: 4

Roll No

Section

Student Signature

Instructions: Please ensure that you answer all questions in the given order.

SOLUTION

CLO # 3: Develop a normalized relational design to remove anomalies in a set of relations.

Q. No 1: Consider a relation R (A, B, C, D, E, F), with the set of FDs $\{AB \rightarrow C, BC \rightarrow E, AF \rightarrow D, D \rightarrow B, AC \rightarrow F\}$. Find all possible keys (i.e. candidate keys) of this relation? Prove it. [5]

Ans: Keys are AB, AC, AD, and AF.

CLO # 3: Develop a normalized relational design to remove anomalies in a set of relations.

Q. No 2: Consider the relation schema R (A, B, C, D), with FDs $F = \{AB \rightarrow C, AB \rightarrow D, A \rightarrow B, B \rightarrow D, A \rightarrow C, BD \rightarrow A\}$. Find a minimal cover of F (i.e. F_c). [5]

Ans: $\{A \rightarrow BC, B \rightarrow AD\}$ OR $\{A \rightarrow B, B \rightarrow ACD\}$

CLO # 3: Develop a normalized relational design to remove anomalies in a set of relations.

Q. No 3: Consider the relation R (A, B, C, D), with FDs $\{AB \rightarrow C, BC \rightarrow D, CD \rightarrow A\}$. State which of the following decompositions of R relation are lossless decomposition. Prove it. [5]

a. R1(B, C, D) and R2(A, B, C)

b. R1(B, C, D) and R2 (A, C, D)

Ans: a) lossless as $R1 \cap R2 \rightarrow R1 - R2$ i.e. $BC \rightarrow D$

b) lossless as $R1 \cap R2 \rightarrow R2 - R1$ i.e. $CD \rightarrow A$

CLO # 3: Develop a normalized relational design to remove anomalies in a set of relations.

Q. No 4: Consider the relation schema R (A, B, C, D, E), with FDs $F = \{AB \rightarrow C, D \rightarrow E, B \rightarrow D\}$. Key of this relation is AB. Identify the best normal form that R satisfies (1NF, 2NF, 3NF, or BCNF). Justify your answer. If R is not in BCNF, decompose it into a set of BCNF relations and show your steps. [5]

Ans: HNF is 1NF as FD3: $B \rightarrow D$ is PFD that violate 2NF.

BCNF Schema: R1(A, B, C), R2(B, D), R3(D, E)