

Math Methods and Characters

Common Mathematical Functions

- Java provides many **useful methods** in the **Math class** for performing common **mathematical functions**.
- In addition to methods, the **Math class** provides two useful double constants, **PI** and **E** (the base of natural logarithms).
- You can use these constants as **Math.PI** and **Math.E** in any program.

Trigonometric Methods

TABLE 4.1 Trigonometric Methods in the Math Class

<i>Method</i>	<i>Description</i>
<code>sin(radians)</code>	Returns the trigonometric sine of an angle in radians.
<code>cos(radians)</code>	Returns the trigonometric cosine of an angle in radians.
<code>tan(radians)</code>	Returns the trigonometric tangent of an angle in radians.
<code>toRadians(degree)</code>	Returns the angle in radians for the angle in degree.
<code>toDegree(radians)</code>	Returns the angle in degrees for the angle in radians.
<code>asin(a)</code>	Returns the angle in radians for the inverse of sine.
<code>acos(a)</code>	Returns the angle in radians for the inverse of cosine.
<code>atan(a)</code>	Returns the angle in radians for the inverse of tangent.

Trigonometric Methods

`Math.toDegrees(Math.PI / 2)` returns **90.0**
`Math.toRadians(30)` returns **0.5236** (same as $\pi/6$)
`Math.sin(0)` returns **0.0**
`Math.sin(Math.toRadians(270))` returns **-1.0**
`Math.sin(Math.PI / 6)` returns **0.5**
`Math.sin(Math.PI / 2)` returns **1.0**
`Math.cos(0)` returns **1.0**
`Math.cos(Math.PI / 6)` returns **0.866**
`Math.cos(Math.PI / 2)` returns **0**
`Math.asin(0.5)` returns **0.523598333** (same as $\pi/6$)
`Math.acos(0.5)` returns **1.0472** (same as $\pi/3$)
`Math.atan(1.0)` returns **0.785398** (same as $\pi/4$)

Exponent Methods

- There are five methods related to **exponents** in the Math class.

TABLE 4.2 Exponent Methods in the Math Class

<i>Method</i>	<i>Description</i>
<code>exp(x)</code>	Returns e raised to power of x (e^x).
<code>log(x)</code>	Returns the natural logarithm of x ($\ln(x) = \log_e(x)$).
<code>log10(x)</code>	Returns the base 10 logarithm of x ($\log_{10}(x)$).
<code>pow(a, b)</code>	Returns a raised to the power of b (a^b).
<code>sqrt(x)</code>	Returns the square root of x (\sqrt{x}) for $x \geq 0$.

Exponent Methods

`Math.exp(1)` returns `2.71828`

`Math.log(Math.E)` returns `1.0`

`Math.log10(10)` returns `1.0`

`Math.pow(2, 3)` returns `8.0`

`Math.pow(3, 2)` returns `9.0`

`Math.pow(4.5, 2.5)` returns `22.91765`

`Math.sqrt(4)` returns `2.0`

`Math.sqrt(10.5)` returns `4.24`

Rounding Methods

- The Math class contains five **rounding methods**.

TABLE 4.3 Rounding Methods in the Math Class

<i>Method</i>	<i>Description</i>
<code>ceil(x)</code>	x is rounded up to its nearest integer.
<code>floor(x)</code>	x is rounded down to its nearest integer.
<code>rint(x)</code>	x is rounded to its integer.
<code>round(x)</code>	Returns <code>Math.floor(x + 0.5)</code> .

Rounding Methods

```
Math.ceil(2.1) returns 3.0
Math.ceil(2.0) returns 2.0
Math.ceil(-2.0) returns -2.0
Math.ceil(-2.1) returns -2.0
Math.floor(2.1) returns 2.0
Math.floor(2.0) returns 2.0
Math.floor(-2.0) returns -2.0
Math.floor(-2.1) returns -3.0
Math.round(2.6f) returns 3 // Returns int
Math.round(2.0) returns 2 // Returns long
Math.round(-2.0f) returns -2 // Returns int
Math.round(-2.6) returns -3 // Returns long
Math.round(-2.4) returns -2 // Returns long
```


The min, max, and abs Methods

`Math.max(2, 3)` returns 3

`Math.max(2.5, 3)` returns 3

`Math.min(2.5, 4.6)` returns 2.5

`Math.abs(-2)` returns 2

`Math.abs(-2.1)` returns 2.1

The random Method

- This method generates a **random double value** greater than or equal to 0.0 and less than 1.0 ($0 \leq \text{Math.random()} < 1.0$).
- **Example:** The next code:
 - `System.out.println(Math.random());`
 - `System.out.println(Math.random());`
 - `System.out.println(Math.random());`
- **Generates:**
 - 0.034346306576394814
 - 0.8164034994234213
 - 0.49682156102145947

The random Method

- You can use it to write a simple expression to generate random numbers in any range.

<code>(int)(Math.random() * 10)</code>	→	Returns a random integer between 0 and 9.
<code>50 + (int)(Math.random() * 50)</code>	→	Returns a random integer between 50 and 99.

- In general:

<code>a + Math.random() * b</code>	→	Returns a random number between a and a + b, excluding a + b.
------------------------------------	---	---

Character Data Type and Operations

- The **character data type**, char, is used to represent a **single character**.
- A character **literal** is enclosed in **single quotation marks**.

```
char letter = 'A';
```

```
char numChar = '4';
```

Escape Sequences for Special Characters

- The **backslash** \ is called an escape character.
- It is a special character.
- It is used to display **escape sequences** (\n, \t, ...) and **special characters** (\\, \", ...)

Escape Sequences for Special Characters

TABLE 4.5 Escape Sequences

<i>Escape Sequence</i>	<i>Name</i>	<i>Unicode Code</i>	<i>Decimal Value</i>
<code>\b</code>	Backspace	<code>\u0008</code>	8
<code>\t</code>	Tab	<code>\u0009</code>	9
<code>\n</code>	Linefeed	<code>\u000A</code>	10
<code>\f</code>	Formfeed	<code>\u000C</code>	12
<code>\r</code>	Carriage Return	<code>\u000D</code>	13
<code>\\</code>	Backslash	<code>\u005C</code>	92
<code>\"</code>	Double Quote	<code>\u0022</code>	34

Escape Sequences for Special Characters

- `System.out.println("He said \nJava is fun");`
displays:

He said // new line

Java is fun

- `System.out.println("He said \"Java is fun\")`; displays:

He said "Java is fun " // quotation marks

Casting between char and Numeric Types

- A **char** can be **cast** into any **numeric type**, and vice versa.

```
char ch = (char)65.25;
```

```
// Decimal 65 is assigned to ch
```

```
System.out.println(ch); // ch is character A
```

```
System.out.println(++ch); // ch is character B
```


Casting between char and Numeric Types

- When a **char** is cast into a **numeric type**, the character's **Unicode** is cast into the specified numeric type.

```
int i = (int)'A';
```

```
// The Unicode of character A is assigned to i
```

```
System.out.println(i); // i is 65
```

Comparing and Testing Characters

- Two **characters** can be **compared** using the **relational operators** just like comparing two numbers.
 - **'a' < 'b'** is true because the Unicode for **'a' (97)** is less than the Unicode for **'b' (98)**.
 - **'a' < 'A'** is false because the Unicode for **'a' (97)** is greater than the Unicode for **'A' (65)**.
 - **'1' < '8'** is true because the Unicode for **'1' (49)** is less than the Unicode for **'8' (56)**.

Comparing and Testing Characters

- Java provides the following methods in the **Character class** for testing characters.

TABLE 4.6 Methods in the Character Class

<i>Method</i>	<i>Description</i>
<code>isDigit(ch)</code>	Returns true if the specified character is a digit.
<code>isLetter(ch)</code>	Returns true if the specified character is a letter.
<code>isLetterOfDigit(ch)</code>	Returns true if the specified character is a letter or digit.
<code>isLowerCase(ch)</code>	Returns true if the specified character is a lowercase letter.
<code>isUpperCase(ch)</code>	Returns true if the specified character is an uppercase letter.
<code>toLowerCase(ch)</code>	Returns the lowercase of the specified character.
<code>toUpperCase(ch)</code>	Returns the uppercase of the specified character.

Example

```
System.out.println("isDigit('a') is " + Character.isDigit('a'));
System.out.println("isLetter('a') is " + Character.isLetter('a'));
System.out.println("isLowerCase('a') is "
    + Character.isLowerCase('a'));
System.out.println("isUpperCase('a') is "
    + Character.isUpperCase('a'));
System.out.println("toLowerCase('T') is "
    + Character.toLowerCase('T'));
System.out.println("toUpperCase('q') is "
    + Character.toUpperCase('q'));
```

- Output

```
isDigit('a') is false
isLetter('a') is true
isLowerCase('a') is true
isUpperCase('a') is false
toLowerCase('T') is t
toUpperCase('q') is Q
```