السؤال الأول : جميل أنور

Q1: Write java program to create array (10 M)

X =	200	100	300	150	99	170	120	33	40	1	55

Then enter three cases **using switch** (**1:** sum items of array from 170 to end of array.
2: Input any key from keyboard then check it found or not found in array.
3: Sort items from 200 to 170).

```java
import java.util.Scanner;
class HelloWorld {
    public static void main(String[] args) {
        Scanner in = new Scanner(System.in);
        int x[] = {200,100,300,150,99,170,120,33,40,1,55};
        System.out.println("1 or 2 or 3 : ");
        int choice = in.nextInt();
        switch(choice){
            case 1:
                int sum = 0;
                for (int i=5 ; i < x.length ; i++)
                    sum+= x[i];
                System.out.println(sum);
                break;
            case 2:
                int fromkeyboard = in.nextInt();
                int flag = 0;
                for (int i=0 ; i< x.length ; i++){
                    if (x[i] == fromkeyboard)
                        flag = 1;
                }
                if (flag == 1)
                    System.out.println("found");
                else
                    System.out.println("not found");
                break;
            case 3:
                int temp ;
                for (int i=0 ; i <6 ; i++)
                    for (int j=i+1 ; j < 6 ; j++){
                        if (x[j] < x[i]){
                            temp = x[i];
                            x[i] = x[j];
                            x[j] = temp;
                        }
                    }
                break;
        } //switch


    } //main
} //public class
```

السؤال الثاني :

استخدام دالة

Q2: Write **java program** to get the following **output**. Using **(Prime Method)** **(10 M)**

```
true,  true,  true,  true,  false, true,
true,  true,  true,  true,  false, true,
true,  true,  true,  true,  false, true,
true,  true,  true,  true,  false, true,
false, false, false, false, false, false,
true,  true,  true,  true,  false, true,
```

```java
import java.util.Scanner;
class HelloWorld {
    static boolean isPrime(int number){
        int flag = 0 ;
        for (int i = number-1 ; i>1 ; i--){
            if (number%i == 0){
                flag = 1;
                break;
            }
        }
        if (flag == 1)
            return false;
        else
            return true;
    }
    public static void main(String[] args) {
        int[][] numbers = {{1,2,3,4,5,6},{7,8,9,10,11,12},{13,14,15,16,17,18},
            {19,20,21,22,23,24},{25,26,27,28,29,30},{31,32,33,34,35,36}};
        for (int i =0 ; i < 6 ; i++){
            for (int j =0 ; j<6 ; j++){
                System.out.print(isPrime(numbers[i][j])+",  ");
            }
            System.out.println("");
        }
    } //main
} //public class
```

السؤال الثالث :

Q3: Write java program to create method **MerregArray**(int **A1**[],int **A2**[]) and create **Sortarray**(int merrgedarray[]) , **let A1[4] , A2[4]** **(10 M)**

1- Return result as one **array** to main method.
2- Sort result using **Sortarray**(int **MerrgedArray**[ ]) .

```java
class HelloWorld {
    static int[] MerregArray(int A[] , int B[]){
        int NewArray[] = new int[8];
        for(int i =0 ; i<4 ; i++){
            NewArray[i] = A[i];
            NewArray[i+4] = B[i];}
        return NewArray;
    }
    static void Sortarray(int MerrgedArray[]){
        int temp;
        for (int i=0 ; i<MerrgedArray.length ; i++)
            for (int j=i+1 ; j<MerrgedArray.length ; j++){
                if (MerrgedArray[j] < MerrgedArray[i]){
                    temp = MerrgedArray[i];
                    MerrgedArray[i] = MerrgedArray[j];
                    MerrgedArray[j] = temp;
                }
            }
    }
    public static void main(String[] args) {
        int A[] = {1,2,3,4};
        int B[] = {5,6,7,8};
        int[] after = MerregArray(A,B);
        Sortarray(after);
    }
}
```

السؤال الرابع :

اختار الاجابة

Q4: Select the right answer **(10 M)**

1- Declaration of array XX has elements of type char

(a- int XX[ ] b- [ ]int XX c- char XX[ ] d- [ ]char XX)

2- All elements of array must be **of the**

(a- same data types b- different data types c- All data types d- integer data types)

3- We can specify the number of elements of the array XX by

(a- XX.size( ) b- XX.size c-XX.lenght( ) d- XX.lenght

4- Let X={ 3,5,6,8,2,8,9,7,11} to find middle of array using

(a-(Length-1)/2 b- length/2 c- length( )/2 d- (Length( )-1)/2)

5- Call method with pass parameter and return value like

(a-M=XX(10,1) b- M=XX( ) c-XX(10,1) d-XX( ))

1- c (char XX[])

2- a (same data types)

3- d (XX.length)

4- b (length/2)

5- a (M=XX(10,1))

السؤال الخامس أ :

Q5: Correct the following code

```
A) Public int [] secondarydia (int x [][]){
for (int i=0; i<=3; i++)
    {
        for(int j=0;j<4;++j)
        {  if(i=j)
           System.out.println(x[i][j]);
           if((j-i)==2-1)
        System.out.println(x[i][j] +",,");  }   }}
Public static void main(String args[] ){
int x[]= new {1,2,3,4},{5,6,7,8},{9,10,11,12};
secondarydia( );
```

```java
static void seconderydia (int x [][]){
        for (int i=0; i<=2; i++)
        {
            for(int j=0;j<3;++j)
            {  if(i==j)
                System.out.println(x[i][j]);
               if((j+i) == 2)
                System.out.println(x[i][j] + ",,");  }  }}

    public static void main(String args[]) {
        int x[][] = {{1,2,3},{4,5,6},{7,8,9}};
        seconderydia(x);


    }
```

السؤال الخامس ب :

(10 M)

B) class Main {
public static void square(int num) {
return num * num; }
public static void main(String[] args) {
int result;
square( );
System.out.println("Squared value of
10 is: " + result); } }

```
public class Main {

    public static int square(int num){
        return num*num;}

    public static void main(String[] args) {
        int result = square(10);
        System.out.println("Squared value of 10 is: "+result);} }
```