المصفوفة الأحادية
من الصفر حتى الأحترافية

إعداد الطالبة :- بتول هاتف جادر

JavaApplication16 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Search (Ctrl+I)

<default config>

Files Ser...

Application1
Application10
Application11
Application12
Application13
Application14
Application15
Application16
Source Packages
javaapplication16
JavaApplication16.java
Libraries
Application2
Application3
Application4
Application5
Application6
Application7
Application8
Application9

Start Page | JavaApplication16.java

Source History

```
1  package javaapplication16;
2  public class JavaApplication16 {
3  public static void main(String[] args) {
4          int x[]={1,3,4,5,6};
5          for(int i=0;i<5;i++)
6          System.out.print(x[i]+" ");
7  }}
8
```

Output - JavaApplication16 (run)

```
run:
1 3 4 5 6 BUILD SUCCESSFUL (total ti
```

طباعة العناصر

6:6 INS

111°F Sunny ENG 3:36 PM

JavaApplication16 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java

Source History

```
1  package javaapplication16;
2  public class JavaApplication16 {
3  public static void main(String[] args) {
4          int x[]={1,3,4,5,6};
5          for(int i=0;i<5;i++)
6          System.out.println("index:"+ i+" = " +x[i]+" ");
7  }}
8
```

Output - JavaApplication16 (run)

```
run:
index:0 = 1
index:1 = 3
index:2 = 4
index:3 = 5
index:4 = 6
BUILD SUCCESSFUL (tota
```

طباعة كل عنصر مع الموشر الخاص به

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source History

```
1   package javaapplication17;
2   public class JavaApplication17 {
3   public static void main(String[] args) {
4           int x[]={1,2,3,6,8};
5           int sum=0;
6           for(int i=0;i<5;i++){
7               sum=sum+x[i];
8           System.out.println(x[i]+" ");
9   }
10          System.out.println("sum :"+sum);
11  }
12  }
13
```

Output - JavaApplication17 (run)

```
run:
1
2
3
6
8
sum :20
BUILD SUCCESSFUL (total time: 0 sec
```

طباعة العناصر مع مجموع كل العناصر

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source History

```java
3   public static void main(String[] args) {
4       int x[]={1,2,3,6,8};
5       int sum=0;
6       for(int i=0;i<5;i++){
7       sum=sum+x[i];
8       System.out.println(x[i]+" ");
9   }
10      System.out.println("sum :"+sum);
11      System.out.println("sum sqrat root:"+Math.sqrt(sum));
12  }}
```

Output - JavaApplication17 (run)

```
run:
1
2
3
6
8
sum :20
sum sqrat root:4.47213595499958
```

طباعة العناصر مع مجموع كل العناصر مع الجذر التربيعي للمجموع

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

```java
package javaapplication17;
public class JavaApplication17 {
public static void main(String[] args) {
    int x[]={1,2,3,6,8};
    int sum=0;
    for(int i=0;i<5;i++){
    sum=sum+x[i];
    System.out.println(x[i]+" ");
}
    System.out.println("avarage :"+sum/5);
}}
```

Output - JavaApplication17 (run)

```
run:
1
2
3
6
8
avarage :4
BUILD SUCCESSFUL (total time: 0 second
```

طباعة العناصر مع طباعة المعدل لمجموع العناصر

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source History

```java
package javaapplication17;
public class JavaApplication17 {
public static void main(String[] args) {
    int x[]={1,2,3,6,-8};
    for(int i=0;i<5;i++){
            if(x[i]>0)
   System.out.println(x[i]+": positive");
}
}}
```

Output - JavaApplication17 (run)

```
run:
1: positive
2: positive
3: positive
6: positive
BUILD SUCCESSFUL (total time: 0 second
```

طباعة العناصر مع طباعة الـأعداد الموجبة فقط

10:1 INS

111°F Sunny ENG 3:57 PM

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source History

```java
package javaapplication17;
public class JavaApplication17 {
public static void main(String[] args) {
    int x[]={1,2,-3,6,-8};
    for(int i=0;i<5;i++){
            if(x[i]<0)
   System.out.println(x[i]+": nagaitive");
}
}}
```

Output - JavaApplication17 (run)

```
run:
-3: nagaitive
-8: nagaitive
BUILD SUCCESSFUL (total time: 0 second
```

طباعة العناصر مع طباعة الـأعداد السالبة فقط

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source History

```java
package javaapplication17;
public class JavaApplication17 {
public static void main(String[] args) {
    int x[]={1,2,3,6,8};
    for(int i=0;i<5;i++){
            if(x[i]%2==0)
   System.out.println(x[i]+": even");
}
}}
```

Output - JavaApplication17 (run)

```
run:
2: even
6: even
8: even
BUILD SUCCESSFUL (total time: 0 second
```

طباعة العناصر مع طباعة الـأعداد الزوجية فقط

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source History

```java
package javaapplication17;
public class JavaApplication17 {
public static void main(String[] args) {
    int x[]={1,2,3,6,8};
    for(int i=0;i<5;i++){
            if(x[i]%2!=0)
   System.out.println(x[i]+": odd");
}
}}
```

Output - JavaApplication17 (run)

```
run:
1: odd
3: odd
BUILD SUCCESSFUL (total time: 0 second
```

طباعة العناصر مع طباعة الـأعداد الفردية فقط

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source History

```java
package javaapplication17;
public class JavaApplication17 {
public static void main(String[] args) {
    int x[]={1,2,3,6,8};
    int s=2,c=0;
    for(int i=0;i<5;i++)
        if(s==x[i])
        {
        c=1;
        break;
        }
         if(c==1)
        System.out.println(s+ " :found ");
         else
        System.out.println("not found");
}}
```

Output - JavaApplication17 (run)

```
run:
2 :found
BUILD SUCCESSFUL (total time: 0 second
```

طباعة العناصر مع البحث عن عنصر

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source History

```
1   package javaapplication17;
2   public class JavaApplication17 {
3   public static void main(String[] args) {
4       int x[]={1,4,3,6,8};
5       int s;
6       for(int i=0;i<5;i++){
7       for(int j=i+1;j<5;j++){
8           if(x[i]>x[j]){
9               s=x[i];
10              x[i]=x[j];
11              x[j]=s;
12      }}}
13      System.out.println( " ترتيب تصاعدي");
14       for(int c=0;c<5;c++){
15       System.out.print(x[c]+ " ");
16       }}}
17
```

Output - JavaApplication17 (run)

```
run:
ترتيب تصاعدي
1 3 4 6 8 BUILD SUCCESSFUL (total time
```

طباعة العناصر مع طباعتهن ترتيب تصاعدي

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source History

```java
package javaapplication17;
public class JavaApplication17 {
public static void main(String[] args) {
    int x[]={1,2,3,7,6};
    int max =x[0];
    for(int i=0;i<5;i++){
        if(max < x[i])
         max=x[i];
}
    System.out.println("max number :"+ max);
}}
```

Output - JavaApplication17 (run)

```
run:
max number :7
BUILD SUCCESSFUL (total time: 0 seconds)
```

طباعة العناصر مع طباعة الرقم الأكبر

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source History

```java
package javaapplication17;
public class JavaApplication17 {
public static void main(String[] args) {
    int x[]={1,2,3,7,6};
    int min =x[0];
    for(int i=0;i<5;i++){
        if(min > x[i])
         min=x[i];
}
    System.out.println("min number :"+ min);
}}
```

Output - JavaApplication17 (run)

```
run:
min number :1
BUILD SUCCESSFUL (total time: 0 seconds)
```

طباعة العناصر مع طباعة الرقم الأصغر

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source | History

```java
package javaapplication17;
public class JavaApplication17 {
public static void main(String[] args) {
    int x[]={1,2,3,7,6};
    int min =x[0],max=x[0];
    for(int i=0;i<5;i++){
        if(min > x[i])
         min=x[i];
         if(max < x[i])
         max=x[i];
}
    System.out.println("min number :"+ min);
    System.out.println("max number :"+ max);
}}
```

Output - JavaApplication17 (run)

```
run:
min number :1
max number :7
BUILD SUCCESSFUL (total time: 0 seconds)
```

طباعة العناصر مع طباعة الرقم الأصغر والرقم الأكبر

15:1 INS

110°F Sunny ENG 5:16 PM

- حل جميع واجبات مصفوفة احادية

JavaApplication14 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java | JavaApplication14.java

Source | History

```java
package javaapplication14;
import java.util.Scanner;
public class JavaApplication14 {
public static void main(String[] args) {
        int n, x, count = 0, i = 0;
        Scanner s = new Scanner(System.in);
        System.out.print("Enter size in array:");
        n = s.nextInt();
        int a[] = new int[n];
        System.out.println("Enter all the elements:");
        for(i = 0; i < n; i++)
        {
            a[i] = s.nextInt();
        }
        System.out.print("Enter the element number of occurrences:");
        x = s.nextInt();
        for(i = 0; i < n; i++)
        {
            if(a[i] == x)
            {
                count++;
            }
        }
        System.out.println("Number of Occurrence of the Element:"+count);
    }
}
```

Output - JavaApplication14 (run)

```
run:
Enter size in array:5
Enter all the elements:
1
2
3
3
4
Enter the element number of occurrences:3
Number of Occurrence of the Element:2
BUILD SUCCESSFUL (total time: 11 seconds)
```

ادخال العناصر وحساب تكرار العنصر

JavaApplication14 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java | JavaApplication14.java

Source | History

```java
package javaapplication14;
public class JavaApplication14 {
public static void main(String[] args) {
 int c=0,f=0;
    int x[] = {10, 11, 13, 15, 17, 19, 23, 25, 30};
    for (c = 0; c < 9; c++) {
      f = 0;
      for (int i = 2; i < x[c] / 2; i++) {
        if (x[c] %i==0) {
          f = 1;
          break;
        }
      }
      System.out.printf("%3d - %s\n", x[c], (f == 0 ? "Prime" : "Not Prime"));
    }
    System.out.println();
}
}
```

Output - JavaApplication14 (run)

```
run:
 10 - Not Prime
 11 - Prime
 13 - Prime
 15 - Not Prime
 17 - Prime
 19 - Prime
 23 - Prime
 25 - Not Prime
 30 - Not Prime

BUILD SUCCESSFUL (total time: 0 seconds)
```

طباعة العدد الأولي

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source History

```
package javaapplication17;
public class JavaApplication17 {
public static void main(String[] args) {
    int x[]={1,4,3,6,8};
    int s;
    for(int i=0;i<5;i++){
    for(int j=i+1;j<5;j++){
        if(x[i]<x[j]){
            s=x[i];
            x[i]=x[j];
            x[j]=s;
    }}}
    System.out.println( " ترتيب تنازلي");
     for(int c=0;c<5;c++){
     System.out.print(x[c]+ " ");
     }}}
```

Output - JavaApplication17 (run)

```
run:
ترتيب تنازلي
8 6 4 3 1 BUILD SUCCESSFUL (total time
```

طباعة العناصر مع طباعتهن ترتيب تنازلي

JavaApplication17 - NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Start Page | JavaApplication16.java | JavaApplication17.java

Source History

```java
package javaapplication17;
import java.util.Arrays;

public class JavaApplication17 {
public static void main(String[] args) {
 String x[]={"ali","ahmed","noor","banen"};
 for(int i=0;i<4;i++){
 }
 Arrays.sort(x);
 System.out.println(Arrays.toString(x));
 }}
```

Output - JavaApplication17 (run)

```
run:
[ahmed, ali, banen, noor]
BUILD SUCCESSFUL (total time: 0 second
```

طباعة الأسماء ترتيب إبجدي