


How to monitor Java memory usage?

[Ask Question](#)

We have a j2ee application running on Jboss and we want to monitor its memory usage. Currently we use the following code

```
System.gc();
Runtime rt = Runtime.getRuntime();
long usedMB = (rt.totalMemory() - rt.freeMemory()) / 1024 / 1024;
logger.information(this, "memory usage" + usedMB);
```

This code works fine. That means it shows memory curve which corresponds to reality. When we create a big xml file from a DB a curve goes up, after the extraction is finished it goes down.



A consultant told us that calling gc() explicitly is wrong, "let jvm decide when to run gc". Basically his arguments were the same as [discussed here](#). But I still don't understand:

- how can I have my memory usage curve?
- what is wrong with the explicit gc()? I don't care about small performance issues which can happen with explicit gc() and which I would estimate in 1-3%. What I need is memory and thread monitor which helps me in analysis of our system on customer site.

java garbage-collection monitoring memory-management

edited May 23 '17 at 12:26



Community ♦
1 1

asked Jun 29 '09 at 15:41



Oleg Pavliv
11.7k 4 38 54

1 monitor with jvisualvm - gives better statistics. – [Thorbjørn Ravn Andersen](#) Aug 15 '12 at 19:20

14 Answers

If you want to really look at what is going on in the VM memory you should use a good tool like [VisualVM](#). This software is free and it's a great way to see what is going on.

Nothing is really "wrong" with explicit gc() calls. However, remember that when you call gc() you are "suggesting" that the garbage collector run. There is no guarantee that it will run at the exact time you run that command.

edited Jan 20 at 3:29



Tom Aranda
2,457 10 14 32

answered Jun 29 '09 at 15:46



amischief
2,788 2 20 20

1 Just been looking at VisualVM - it's sweet. – [Nick Holt](#) Jun 30 '09 at 14:55

-
- 4 System.gc() can harm performance because it does interfere with the GC's algorithms. This can degrade all the subsequent GCs. – [Mr. Shiny and New 安宇](#) Jul 2 '09 at 14:33
-
- 2 [citation needed] Care to demonstrate your claim? Please explain how making a call to gc() "interfere's" with the garbage collectors algorithms and how a call to a method 'degrades' subsequent calls? – [amischief](#) Jul 2 '09 at 17:25
-
- 1 I have used visual VM and it works awesome. It shows so much inside details inside server . – [vsingh](#) Oct 6 '10 at 21:14
-
- 11 There's a reason why the VM has a -XX:+DisableExplicitGC option! The problem isn't that it is necessarily bad to call GC. But it can be bad if you call GC *too often*. It can cause a full GC, when most of the algorithms don't stop the whole VM to do a full GC. This can be especially problematic if you're running a HUGE, where the whole VM could pause for minutes. If that happens, you could cause other operations to time out (like database connections, rmi connections, etc) – [John Gardner](#) Oct 6 '10 at 21:36
-

|

There are tools that let you monitor the VM's memory usage. The [VM can expose memory statistics using JMX](#). You can also [print GC statistics](#) to see how the memory is performing over time.

Invoking System.gc() can harm the GC's performance because objects will be prematurely moved from the new to old generations, and weak references will be cleared prematurely. This can result in decreased memory efficiency, longer GC times, and decreased cache hits (for caches that use weak refs). I agree with your consultant: System.gc() is bad. I'd go as far as to [disable it](#) using the command line switch.

edited Feb 16 '16 at 16:27

vageli
106 11

answered Jun 29 '09 at 15:59

Mr. Shiny and New 安宇
12.4k 5 33 63

-
- 2 +1 for the excellent comment on premature promotion. – [Robert Munteanu](#) Jun 29 '09 at 16:02
-

I would say that the consultant is right in the theory, and you are right in practice. As the [saying goes](#):

In theory, theory and practice are the same. In practice, they are not.

The Java spec says that System.gc suggests to call garbage collection. In practice, it just spawns a thread and runs right away on the Sun JVM.

Although in theory you could be messing up some finely tuned JVM implementation of garbage collection, unless you are writing generic code intended to be deployed on any JVM out there, don't worry about it. If it works for you, do it.

answered Jun 29 '09 at 15:47

Yishai
68.1k 18 156 235


do you know if this behavior *just spawns a thread and runs right away* is also applicable to current (Sun/Oracle/Hotspot) JVM (8)? – [Ben](#) May 8 '15 at 19:25

- 1 Running System.gc often, just to get sensible statistics of memory usage, *will* hurt performance. So it's not a "just do it". System.gc() is sensible in cases like "OK, now a big work that needed big memory is done, and I have nothing much to do right now, so I collect garbage to improve performance of minor garbage collections later." – [Hans-Peter Stör](#) Sep 4 '15 at 12:17
-

You can take a look at [stagemonitor](#). It is a open source java (web) application performance monitor. It captures response time metrics, JVM metrics, request details (including a call stack captured by the request profiler) and more. The overhead is very low.

Optionally, you can use the great timeseries database graphite with it to store a long history of datapoints that you can look at with fancy dashboards.

Example:



Take a look at the [project website](#) to see screenshots, feature descriptions and documentation.

Note: I am the developer of stagemonitor

edited Jul 30 '14 at 15:01

answered Jul 3 '14 at 18:29

Felix

2,781 4 18 28

1 thanks, I'll take a look on it. — [Oleg Pavliv](#) Jul 4 '14 at 3:22

Have you tried JMX?

<http://java.sun.com/developer/technicalArticles/J2SE/jconsole.html>


alt text <http://java.sun.com/developer/technicalArticles/J2SE/jconsole/HeapMemory.jpg>


answered Jun 29 '09 at 15:48

Tom

27.7k 19 111 155

Peek into what is happening inside tomcat through Visual VM. <http://www.skill-guru.com/blog/2010/10/05/increasing-permgen-size-in-your-server/>





answered Oct 6 '10 at 21:27



vsingh

2,975 1 36 38

Take a look at the JVM args:

<http://java.sun.com/javase/technologies/hotspot/vmoptions.jsp#DebuggingOptions>

XX:-PrintGC Print messages at garbage collection. Manageable.

-XX:-PrintGCDetails Print more details at garbage collection. Manageable. (Introduced in 1.4.0.)

-XX:-PrintGCTimeStamps Print timestamps at garbage collection. Manageable (Introduced in 1.4.0.)

-XX:-PrintTenuringDistribution Print tenuring age information.

While you're not going to upset the JVM with explicit calls to `System.gc()` they may not have the effect you are expecting. To really understand what's going on with the memory in a JVM with read anything and everything the [Brian Goetz](#) writes.

edited Jun 29 '09 at 16:03

answered Jun 29 '09 at 15:55



Nick Holt

25.3k 3 31 48

Explicitly running `System.gc()` on a production system is a terrible idea. If the memory gets to any size at all, the entire system can freeze while a full GC is running. On a multi-gigabyte-sized server, this can easily be very noticeable, depending on how the jvm is configured, and how much headroom it has, etc etc - I've seen pauses of more than 30 seconds.

Another issue is that by explicitly calling GC you're not actually monitoring how the JVM is running the GC, you're actually altering it - depending on how you've configured the JVM, it's going to garbage collect when appropriate, and usually incrementally (It doesn't just run a full GC when it runs out of memory). What you'll be printing out will be nothing like what the JVM will do on it's own - for one thing you'll probably see fewer automatic / incremental GC's as you'll be clearing the memory manually.

As Nick Holt's post points out, options to print GC activity already exist as JVM flags.

You could have a thread that just prints out free and available at reasonable intervals, this will show you actual mem usage.

edited Jun 29 '09 at 16:10

answered Jun 29 '09 at 16:03



Steve B.

36.5k 10 74 120

How is this mitigated by not calling `System.gc()`? Eventually the JVM garbage collects when it runs low on memory, so won't the delay happen then? (That has been my experience at least). – Yishai Jun 29 '09 at 17:03

The JVM allows you to specify from multiple GC algorithms. They all do some sort of incremental GC, and may occasionally trigger a full GC (I'm not too up on the details, but basically only when they have to - sort of a "last resort" kind of thing, e.g. when there's not enough room to make a new copy of some section of mem during incremental gc). If you're regularly calling `System.gc` it's going to happen much more often. You're essentially creating your own GC strategy, which is "just periodically run a full GC". The JVM has better strategies than this. – Steve B. Jun 29 '09 at 18:10

If you like a nice way to do this from the command line use `jstat`:

<http://java.sun.com/j2se/1.5.0/docs/tooldocs/share/jstat.html>

It gives raw information at configurable intervals which is very useful for logging and graphing purposes.

answered Jun 29 '09 at 20:01



Pablojim

6,007 7 35 61

If you use java 1.5, you can look at `ManagementFactory.getMemoryMXBean()` which give you numbers on all kinds of memory. heap and non-heap, perm-gen.

A good example can be found there <http://www.freshblurbs.com/explaining-java-lang-outofmemoryerror-permgen-space>

answered Jun 29 '09 at 15:57



Zoukaye

21 1

If you use the JMX provided history of GC runs you can use the same before/after numbers, you just dont have to force a GC.

You just need to keep in mind that those GC runs (typically one for old and one for new generation) are not on regular intervalls, so you need to extract the starttime as well for plotting (or you plot against a sequence number, for most practical purposes that would be enough for plotting).

For example on Oracle HotSpot VM with ParNewGC, there is a JMX MBean called `java.lang:type=GarbageCollector,name=PS Scavenge`, it has a attribute `LastGCInfo`, it returns a `CompositeData` of the last YG scavenger run. It is recorded with `duration`, `absolute startTime` and `memoryUsageBefore` and `memoryUsageAfter`.

Just use a timer to read that attribute. Whenever a new `startTime` shows up you know that it describes a new GC event, you extract the memory information and keep polling for the next update. (Not sure if a `AttributeChangeNotification` somehow can be used.)

Tip: in your timer you might measure the distance to the last GC run, and if that is too long for the resolution of your plotting, you could invoke `System.gc()` conditionally. But I would not do that in a OLTP instance.

answered Aug 15 '12 at 19:14

community wiki
eckes

As has been suggested, try VisualVM to get a basic view.

You can also use Eclipse MAT, to do a more detailed memory analysis.

It's ok to do a `System.gc()` as long as you dont depend on it, for the correctness of your program.

answered Jun 29 '09 at 19:14



Aakash

204 1 4

Adding to the List of Answers, JConsole (included in `jdk/bin` directory) is a also good interface to try out.

[Reference](#)

answered Apr 11 '17 at 14:01

[Ankit](#)

376 10 33

The problem with `system.gc`, is that the JVM already automatically allocates time to the garbage collector based on memory usage.

However, if you are, for instance, working in a very memory limited condition, like a mobile device, `System.gc` allows you to manually allocate more time towards this garbage collection, but at the cost of cpu time (but, as you said, you aren't that concerned about performance issues of gc).

Best practice would *probably* be to only use it where you might be doing large amounts of deallocation (like flushing a large array).

All considered, since you are simply concerned about memory usage, feel free to call `gc`, or, better yet, see if it makes much of a memory difference in your case, and then decide.

answered Jun 29 '09 at 22:04

[bgw](#)

1,717 1 17 27