

Verifix Public API v1.0 – Summary of Explored Endpoints

This document summarizes the Verifix Public API v1.0 based on the Postman documentation.

For each endpoint we provide the HTTP method, endpoint path, required headers, body parameters, response fields and any relevant enumeration codes.

This summary only covers endpoints inspected during our research and may not include every endpoint in the full API.

Introduction & Authorization

Verifix uses OAuth 2.0 for authentication. Every request requires the following headers:

Header	Description
<code>project_code</code>	Identifies the project code assigned by Verifix. Must be included in all requests.
<code>filial_id</code>	ID of the branch/filial where the request applies. Must be included in all requests.

To obtain an `access_token`, send a `POST` request to `https://app.verifix.com/security/oauth/token` with `grant_type=client_credentials`, `client_id` and `client_secret`.

The response contains `access_token` (JWT), `token_type: Bearer` and `expires_in` seconds ¹.

Basic authentication (`username@companycode:password` encoded in Base64) is deprecated.

Core (Basic) Methods

These methods cover core entities such as positions, groups, divisions, locations, schedules, employees, FTEs and more.

Most list endpoints support pagination via optional headers `cursor` and `limit` and return `meta.count` (number of records returned) and `meta.next_cursor` (cursor for the next page).

Jobs (Positions)

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List positions	<code>POST /b/vhr/api/v1/core/job\$list</code>	Headers: <code>project_code</code> , <code>filial_id</code> , optional <code>cursor</code> , <code>limit</code> .		

Operation	Endpoint / Method	Request parameters	Response fields	Notes
Body: optional <code>job_ids</code> list to filter.	Returns a list of jobs with fields: <code>job_id</code> , <code>name</code> , <code>job_group_id</code> , <code>job_group_name</code> , <code>code</code> , <code>state</code> (A – active, P – passive), along with <code>meta</code> pagination fields ² .	Allows filtering by specific IDs and paginated retrieval.		
Create position	POST <code>/b/vhr/api/v1/core/job\$create</code>	Body: <code>name</code> (required), optional <code>job_group_id</code> , <code>code</code> , <code>order_no</code> .	Responds with <code>job_id</code> of the newly created position ³ .	Creates a new position.
Update position	POST <code>/b/vhr/api/v1/core/job\$update</code>	Body: <code>job_id</code> (required) and fields <code>name</code> , <code>job_group_id</code> , <code>code</code> , <code>order_no</code> . Missing fields are also updated (so they should be sent if their value should remain unchanged) ⁴ .	No body.	Updates all fields of the position.
Delete position	POST <code>/b/vhr/api/v1/core/job\$delete</code>	Body: <code>job_id</code> (required).	No body ⁵ .	Deletes a position.

Job Groups

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List job groups	POST <code>/b/vhr/api/v1/core/job_group\$list</code>	Body: optional <code>job_group_ids</code> list.	Returns <code>job_group_id</code> , <code>name</code> , <code>code</code> , <code>state</code> for each group and pagination info ⁶ .	
Create job group	POST <code>/b/vhr/api/v1/core/job_group\$create</code>	Body: <code>name</code> (required), optional <code>code</code> .	Returns <code>job_group_id</code> ⁷ .	

Operation	Endpoint / Method	Request parameters	Response fields	Notes
Update job group	POST /b/vhr/api/v1/core/job_group\$update	Body: <code>job_group_id</code> (required), <code>name</code> and optional <code>code</code> . All fields are updated even if omitted ⁸ .	No body.	
Delete job group	POST /b/vhr/api/v1/core/job_group\$delete	Body: <code>job_group_id</code> (required).	No body ⁹ .	

Divisions

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List divisions	POST /b/vhr/api/v1/core/division\$list	Body: optional <code>division_ids</code> list.	Returns <code>division_id</code> , <code>name</code> , <code>parent_id</code> , <code>opened_date</code> , <code>closed_date</code> , <code>code</code> , <code>state</code> , and <code>meta</code> pagination fields ¹⁰ .	
Create division	POST /b/vhr/api/v1/core/division\$create	Body: <code>name</code> and <code>opened_date</code> (required); optional <code>parent_id</code> , <code>closed_date</code> , <code>code</code> .	Returns <code>division_id</code> ¹¹ .	
Update division	POST /b/vhr/api/v1/core/division\$update	Body: <code>division_id</code> (required), <code>name</code> , optional <code>parent_id</code> , <code>opened_date</code> , <code>closed_date</code> , <code>code</code> . All fields update even if omitted ¹² .	No body.	
Delete division	POST /b/vhr/api/v1/core/division\$delete	Body: <code>division_id</code> (required).	No body ¹³ .	

Division Groups

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List division groups	POST /b/vhr/api/v1/core/division_group\$list	Body: optional division_group_ids list.	Returns division_group_id, name, code, state and pagination fields ¹⁴ .	
Create division group	POST /b/vhr/api/v1/core/division_group\$create	Body: name (required), optional code.	Returns division_group_id ¹⁵ .	
Update division group	POST /b/vhr/api/v1/core/division_group\$update	Body: division_group_id (required), name and optional code. All fields updated ⁸ .	No body.	
Delete division group	POST /b/vhr/api/v1/core/division_group\$delete	Body: division_group_id (required).	No body ¹⁶ .	

Locations

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List locations	POST /b/vhr/api/v1/core/location\$list	Body: optional location_ids array.	Returns location_id, name, address, latlng (latitude, longitude, optional altitude), accuracy, code, state, plus pagination meta ¹⁷ .	

Operation	Endpoint / Method	Request parameters	Response fields	Notes
Attach employees to location	POST /b/vhr/api/v1/core/location\$save_employees	Body: location_id and employee_ids array.	No response body ¹⁸ .	Links employees to a location; employees not specified are detached.

Work Schedules

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List schedules	POST /b/vhr/api/v1/core/schedule\$list	Body: optional schedule_ids and optional year.	Returns schedule details with schedule_id, name, kind, code, state and nested schedule_days objects; kind values include: F – fixed schedule, H – hour-based, S – shift-based, etc. ¹⁹ .	
Create schedule	POST /b/vhr/api/v1/core/schedule\$create	Body: name and kind (required), optional code.	Returns schedule_id ²⁰ .	
Update schedule	POST /b/vhr/api/v1/core/schedule\$update	Body: schedule_id, name, optional code. All fields updated ²¹ .	No body.	
Delete schedule	POST /b/vhr/api/v1/core/schedule\$delete	Body: schedule_id.	No body ²² .	

Employees

Employees are represented with rich data structures and support a variety of operations.

List Employees

Endpoint: POST /b/vhr/api/v1/core/employee\$list

Parameters: optional employee_ids, npins (PINFL), statuses (e.g., A – active, P – passive), plus

pagination headers.

Response: An array of employee objects containing:

- **Identification:** `employee_id`, `employee_code`, `first_name`, `last_name`, `middle_name`, `gender`, `birth_date`, `phone_number`, `email`, `tin`, `pinfl`.
- **Nested structures:**
 - `person_family_members`: family members with fields like `person_family_member_id`, `name`, `relation_degree_id`, `birthday`, `is_dependent` and `is_private` ²³.
 - `person_langs`: languages known by the employee with `lang_id` and `lang_level_id` ²⁴.
 - `person_experiences`: records of employment history (duration in years/months, employer name, etc.).
 - `person_work_places`: previous workplaces with positions and dates.
 - `person_edu_stages`: education history (institution, specialty, start/end dates).
 - `dynamic_fields`: custom fields configured in Verifix.
 - `IdentificationPhoto`: nested object containing `photo_sha` and `is_main`, representing stored facial photos for identification ²⁵.

Create Employee

Endpoint: `POST /b/vhr/api/v1/core/employee$create`

Body parameters: `first_name`, `phone_number`, `birthday`, `gender` (required); optional `last_name`, `middle_name`, `email`, `tin`, `pinfl`, `dynamic_fields`.

Response: `employee_id` of the new employee ²⁶.

Update Employee

Endpoint: `POST /b/vhr/api/v1/core/employee$update`

Parameters: `employee_id` (required) along with fields for personal details, contact information, and `dynamic_fields`. All fields are updated even if omitted ²⁷.

Response: None.

Delete Employee

Endpoint: `POST /b/vhr/api/v1/core/employee$delete`

Parameters: `employee_id`.

Response: None ²⁸.

Set Employee Photo

Endpoint: `POST /b/vhr/api/v1/core/employee$set_photo` (multipart)

Parameters: `employee_id`, `photo_as_face_rec` (Y/N), `is_main` (Y/N), `photo_sha` (SHA of uploaded file). The file must be attached under multipart name `files` ²⁹.

Response: None.

Set Identification Photo

Endpoint: POST /b/vhr/api/v1/core/employee\$set_identification_photo

Parameters: employee_id, photo_sha.

Response: None ³⁰.

Search Employees by PINFL

Endpoint: POST /b/vhr/api/v1/core/employee\$search_by_pinfl

Parameters: npins – list of PINFLs.

Response: List of objects with npin and matching employee_id ³¹.

Save Locations for Employee

Endpoint: POST /b/vhr/api/v1/core/employee\$save_locations

Parameters: employee_id, location_ids (list of location IDs). This sets the employee's accessible locations; locations not included are removed ³².

Response: None.

Set Identification Methods

Endpoint: POST /b/vhr/api/v1/core/employee\$set_identification

Parameters: employee_id, optional identification fields: pin (string), pin_code (int), rfid_code (string), qr code (string). Only provided fields are updated ³³ ³⁴.

Response: None.

Download File

Endpoint: GET /b/biruni/m:download_file_v2?sha={sha}

Parameters: sha – file hash.

Response: Binary file contents ³⁵.

Full-Time Equivalent (FTE) – Employment Types

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List FTEs	POST /b/vhr/api/v1/core/fte\$list	Body: optional fte_ids list.	Returns fte_id, name, value (fraction representing workload) with pagination metadata ³⁶ .	
Create FTE	POST /b/vhr/api/v1/core/fte\$create	Body: name and value (required).	Returns fte_id ³⁷ .	

Operation	Endpoint / Method	Request parameters	Response fields	Notes
Update FTE	POST /b/vhr/api/v1/core/fte\$update	Body: fte_id, name, value. All fields updated ³⁸ .	No body.	
Delete FTE	POST /b/vhr/api/v1/core/fte\$delete	Body: fte_id.	No body ³⁹ .	

Termination Reasons

Reason codes used when terminating employees.

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List termination reasons	POST /b/vhr/api/v1/core/dismissal_reason\$list	Body: optional dismissal_reason_ids.	Returns dismissal_reason_id, name, description, reason_type (enum: P or N), state (A – active, P – passive) ⁴⁰ .	
Create termination reason	POST /b/vhr/api/v1/core/dismissal_reason\$create	Body: name and reason_type (P or N); optional description, state.	Returns dismissal_reason_id ⁴¹ .	
Update termination reason	POST /b/vhr/api/v1/core/dismissal_reason\$update	Body: dismissal_reason_id, name, reason_type, description, state. All fields updated ⁴¹ .	No body.	
Delete termination reason	POST /b/vhr/api/v1/core/dismissal_reason\$delete	Body: dismissal_reason_id.	No body ⁴² .	

Marks (Attendance / Track records)

Used to record entry/exit marks or presence in the system.

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List marks	POST /b/vhr/api/v1/core/track\$list	Body: optional employee_ids, begin_datetime, end_datetime.	Returns marks with fields: track_id, schedule_id, employee_id, location_id, track_type (I - arrival, O - exit, C - presence, M - continues work day, etc.), mark_type (P - PIN, T - card, R - FaceID, Q - QR code, F - fingerprint, M - mobile, A - admin, O - auto, C - correction, S - schedule), track_datetime, created_by, modified_by 43 44.	
Get mark information	POST /b/vhr/api/v1/core/track\$info	Body: track_id.	Returns personal data: person_id, name, email, main_phone, device_id, device_name, location_id, location_name, track_type, mark_type, track_datetime 45.	
Get last mark of the day	POST /b/vhr/api/v1/core/track\$last	Body: employee_id, track_date (date).	Returns last mark record for the day including track_id, staff_id, employee_id, location_id, device_id, track_type, track_datetime, photo_sha 46.	

Time Kinds (Work Time Types)

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List time kinds	POST /b/vhr/api/v1/core/time_kind\$list	Body: optional time_kind_ids.	Returns time_kind_id, name, letter_code (letter representing time code), digital_code (numeric code) 47.	Used to categorise attendance marks (e.g., working hours, overtime).

Leave Requests

Absence requests submitted by staff.

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List requests	POST /b/vhr/ api/v1/core/ request\$list	Body filters: optional request_ids , request_begin_date , request_end_date (dates).	Returns requests with fields request_id , request_kind_id (absence type), staff_id , begin_time , end_time , request_type (P - partial day, F - full day, M - multiple days), manager_note , note , accrual_kind (C - carry-over days, P - planned days, U - unplanned days), status (N - new, A - approved, C - cancelled, D - declined), and optional barcode ⁴⁸ ⁴⁹ ⁵⁰ .	
Create request	POST /b/vhr/ api/v1/core/ request\$create	Body: request_kind_id , staff_id , begin_time , end_time , request_type (P/F/M), optional note and accrual_kind .	Returns request_id ⁵¹ .	
Update request	POST /b/vhr/ api/v1/core/ request\$update	Body: request_id and same fields as creation. All fields updated ⁵² .	No body.	
Delete request	POST /b/vhr/ api/v1/core/ request\$delete	Body: request_id .	No body ⁵³ .	

Schedule Change Requests

Requests to modify work schedules.

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List schedule change requests	POST /b/vhr/api/v1/core/plan_change\$list	Body: optional change_ids .	Returns change requests with fields: change_id , staff_id , change_kind (S - swap days, C - shift change), work_day_before , work_day_after , manager_note , note , status (N - new, A - approved, C - cancelled, D - declined) ⁵⁴ ⁵⁵ ⁵⁶ .	Additional endpoints for create/ update/ delete exist but were not inspected.

Specialties

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List specialties	POST /b/vhr/api/v1/core/specialty\$list	Body: optional specialty_ids list.	Returns specialty_id , name , code , group_id , kind (enum G - group of specialties, S - single specialty) ⁵⁷ .	
Create specialty	POST /b/vhr/api/v1/core/specialty\$create	Body: name , kind (required), optional code , group_id , state (A or P).	Returns specialty_id and name ⁵⁸ ⁵⁹ .	
Update specialty	POST /b/vhr/api/v1/core/specialty\$update	Body: specialty_id , name , kind , optional code , group_id , state . All fields updated ⁶⁰ .	No body.	
Delete specialty	POST /b/vhr/api/v1/core/specialty\$delete	Body: specialty_id .	No body ⁶¹ .	

Marital Statuses

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List marital statuses	POST /b/vhr/api/v1/core/ marital_status\$list	Body: optional marital_status_ids .	Returns marital_status_id , name , code , state (A/P) with pagination ⁶² .	
Create marital status	POST /b/vhr/api/v1/core/ marital_status\$create	Body: name , optional code , state .	Returns marital_status_id ⁶³ .	
Update marital status	POST /b/vhr/api/v1/core/ marital_status\$update	Body: marital_status_id , name , code , state . All fields updated ⁶⁴ .	No body.	
Delete marital status	POST /b/vhr/api/v1/core/ marital_status\$delete	Body: marital_status_id .	No body ⁶⁵ .	

Production Calendars

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List calendars	POST /b/vhr/api/v1/core/ calendar\$list	Body: optional calendar_ids , optional year .	Returns calendar_id , name , code , and calendar_days – a list of holiday/weekend days where each object contains calendar_date and calendar_date_name ⁶⁶ ⁶⁷ .	
Create calendar	POST /b/vhr/api/v1/core/ calendar\$create	Body: name , year , optional code , calendar_days (list of date & name).	Returns calendar_id ⁶⁸ .	
Update calendar	POST /b/vhr/api/v1/core/ calendar\$update	Body: calendar_id , name , year , optional code , calendar_days . All fields updated ⁶⁹ .	No body.	

Operation	Endpoint / Method	Request parameters	Response fields	Notes
Delete calendar	POST /b/vhr/api/v1/core/calendar\$delete	Body: calendar_id .	No body ⁷⁰ .	

Organization Information

Endpoint: POST /b/vhr/api/v1/core/filial\$info

Parameters: none.

Response: returns information about the branch/organization including filial_name , photo_sha (logo), email , main_phone , web , telegram , address , address_guide , note , region_name and other descriptive fields ⁷¹ .

Employee Documents

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List documents	POST /b/vhr/api/v1/core/person_document\$list	Body: optional document_ids , optional person_ids .	Returns document_id , person_id , doc_type_id , doc_type (enum: P - passport, M - other), doc_series , doc_number , issued_by , issued_date , expiry_date , note , file_sha , state ⁷² ⁷³ .	

Operation	Endpoint / Method	Request parameters	Response fields	Notes
Create document	POST /b/vhr/api/v1/core/person_document\$create	Body: person_id (required), doc_type_id or doc_type , optional doc_series , doc_number , issued_by , issued_date , expiry_date , note , file_sha , state .	Returns document_id 74 .	Update and delete endpoints were not visible.

Employee Relatives (Family Members)

Operation	Endpoint / Method	Request parameters	Response fields
List family members	POST /b/vhr/api/v1/core/person_family_member\$list	Body: optional person_family_member_ids , optional person_ids .	Returns person_family_member_id , person_id , name , relation_degree_id , relation_degree_name , birthday , workplace , phone_number , address , note , state 75 76 .
Create family member	POST /b/vhr/api/v1/core/person_family_member\$create	Body: person_id , name , relation_degree_id (required); optional birthday , workplace , is_dependent (Y / N), is_private (Y / N), phone_number , address , note , state .	Returns person_family_member_id 77 78 .
Update family member	POST /b/vhr/api/v1/core/person_family_member\$update	Body: person_family_member_id , person_id , name , relation_degree_id and optional fields; updates all fields 79 .	No body.

Operation	Endpoint / Method	Request parameters	Response fields
Delete family member	POST /b/vhr/api/v1/core/person_family_member\$delete	Body: person_family_member_id .	No body ⁸⁰ .

Employee Languages

Operation	Endpoint / Method	Request parameters	Response fields	Notes
List employee languages	POST /b/vhr/api/v1/core/person_langs\$list	Body: optional lang_ids , optional person_ids .	Returns entries with person_id , person_name , lang_id , lang_name , lang_level_id , lang_level_name ⁸¹ .	
Create employee language	POST /b/vhr/api/v1/core/person_langs\$create	Body: person_id , lang_id , lang_level_id (all required).	Returns person_id confirming creation ⁸² .	
Update / Delete	There are likely person_langs\$update and person_langs\$delete endpoints, but they were not inspected.			

Notes & Observations

- **Pagination:** Many list endpoints use `cursor` and `limit` headers to paginate results; responses return `meta.count` and `meta.next_cursor` to retrieve subsequent pages.
- **Enumerations:** Several entities include `state` values (`A` – active, `P` – passive), `reason_type`, `kind`, etc. Use the tables above for definitions.
- **Dynamic fields:** Employee and other objects can include `dynamic_fields` arrays for custom attributes defined within Verifix.
- **API versioning:** Endpoints under `/b/vhr/api/v1/` refer to the basic module; other modules such as **Start** and **Pro** modules (e.g., `/pro/employee$list`) are available but were not fully inspected.
- **Additional entities:** The documentation includes many more categories (e.g., time off types, nationalities, degrees of kinship, languages and levels, work experience types, education institutions, organizations, devices, shift management, etc.) that were not fully covered here.

This summary can serve as a starting point for developers integrating with the Verifix API. For complete usage details, error codes and further modules, refer to the official documentation.

1 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR>

2 3 4 5 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2366ef8fa3-f125-4174-80a7-64386fbe33d3>

6 7 9 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23ff553a91-b9f3-4557-b13a-c163a09430ac>

8 14 15 16 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%232ad061b8-fb69-4526-9eb4-3762c3b9a2cf>

10 11 12 13 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%239b8d1d6f-0fed-44c8-8159-fc02958b9996>

17 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23935c35f2-fa66-4332-bb8a-a3ebbf20047>

18 19 20 21 22 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2360be0543-67e2-42b7-8d0b-ac309f347e47>

23 24 25 26 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2318ef034b-e3a4-4e6f-b19a-2be61cd4bf61>

27 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%239eec21f7-6fa7-43db-91ae-ae69c7cfd58b>

28 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%235d15d4ac-dc0c-46a7-b4a9-f872101a7797>

29 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2374913736-7bb4-490b-97d8-ac1d5197a7a8>

30 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23982047b0-ea4c-4aa1-b49e-70f989bc6982>

31 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%232b5c79a2-6dee-4508-a751-ae311f089756>

32 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23b9adedd1-276d-4629-9278-305da6f5db7f>

33 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23edd89e54-387b-4724-adf2-84058248b51c>

34 35 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23c8bd6f80-5480-429c-a8d6-ec9de81e14db>

36 37 38 39 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2321978dfb-5f32-485d-b1e8-5363285a4a48>

40 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2369087aed-489c-41cb-83f9-60166061e0ed>

41 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%239bbfe6e7-f3a6-494d-a40a-75fa3b008e9b>

42 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23991268a5-c30a-4c88-aeb7-91a80f2101a4>

43 44 45 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%234206a1cf-b183-471a-ba7e-38cd9970bd1c>

46 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%236e33f9dc-6711-44bc-8b72-7c3e19454e65>

47 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2370486616-944a-494a-b1ac-3cd9da550fdd>

48 49 50 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%235be6ebd6-a62b-4df0-92d6-dae17381445a>

51 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23e2835266-45ce-44e6-b288-7b05013a68aa>

52 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23e136de82-e76f-40a1-aa56-43e0f16e08e2>

53 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2365b49f54-4038-43f7-996f-13ea91e8dcf2>

54 55 56 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23f3f99e0c-66b8-4e55-b22e-a7ca49cd68f5>

57 58 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23c3880613-38b8-46de-85af-b995c8b3cd4a>

59 60 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2373a32a03-8e37-4f6a-9218-e5e9361a37c2>

61 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2344e834ea-d72a-4512-af51-b5902a7994b7>

62 63 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23a1e0d828-1263-43e4-abf6-6bfaa8ffd7cd>

64 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%231a2fd704-37fd-4858-b1f5-36be776a69bf>

65 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23a8879bf0-093b-4305-8a4c-1c85d211e34a>

66 67 68 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23e44329f6-2a06-4774-8696-3bdd0c76d8f3>

69 **Verifix Public API v1.0**
<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2334bf3e8e-22f7-468f-aa71-ace772f7a61c>

70 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%231d60f7ce-70d9-418f-82ad-038144b55b0d>

71 72 73 74 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23d70b5ef8-a848-4f73-897b-311d9a6344e7>

75 76 77 78 79 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%23484a825e-93aa-4db6-be54-d8ca76b43124>

80 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2361214a92-2d30-4853-901d-a670fad66356>

81 82 **Verifix Public API v1.0**

<https://documenter.getpostman.com/view/23097602/2s83ziN3VR%2307922280-6640-494c-9301-159ef7612982>