

HEAP SORT-2



Instructor: Javeria Naz

Definitions of heap:

A heap is a data structure that stores a collection of objects (with keys), and has the following properties:

- Complete Binary tree
- Heap Order


The heap sort algorithm has two major steps :

- i. The first major step involves transforming the complete tree into a heap.
- ii. The second major step is to perform the actual sort by extracting the largest or lowest element from the root and transforming the remaining tree into a heap.

Types of heap

- ❖ Max Heap
- ❖ Min Heap


Max Heap Example



19	12	16	1	4	7
----	----	----	---	---	---

Array A

Min heap example



1	4	16	7	12	19
---	---	----	---	----	----

Array A

1-Max heap :

max-heap Definition:



is a complete binary tree in which the value in each internal node is greater than or equal to the values in the children of that node.

Max-heap property:

- The key of a node is \geq than the keys of its children.


Max heap Operation

- A heap can be stored as an array A .
 - Root of tree is $A[1]$
 - Left child of $A[i] = A[2i]$
 - Right child of $A[i] = A[2i + 1]$
 - Parent of $A[i] = A[\lfloor i/2 \rfloor]$




Example Explaining: A

4	1	3	2	16	9	10	14	8	7
---	---	---	---	----	---	----	----	---	---



Build Max-heap


Heapify() Example



A =

16	4	10	14	7	9	3	2	8	1
----	---	----	----	---	---	---	---	---	---



Heapify() Example




A =

16	4	10	14	7	9	3	2	8	1
----	---	----	----	---	---	---	---	---	---

Heapify() Example




Heapify() Example




A =

16	14	10	4	7	9	3	2	8	1
----	----	----	---	---	---	---	---	---	---

Heapify() Example




Heapify() Example



A =

16	14	10	8	7	9	3	2	4	1
----	----	----	---	---	---	---	---	---	---


Heapify() Example



A =

16	4	10	14	7	9	3	2	8	1
----	---	----	----	---	---	---	---	---	---

Heapify() Example



A =

16	14	10	8	7	9	3	2	4	1
----	----	----	---	---	---	---	---	---	---


Heap-Sort

sorting strategy:

1. Build Max Heap from unordered array;
2. Find maximum element $A[1]$;
3. Swap elements $A[n]$ and $A[1]$:
now max element is at the end of the array! .
4. Discard node n from heap
(by decrementing heap-size variable).
5. New root may violate max heap property, but its children are max heaps. Run `max_heapify` to fix this.
6. Go to Step 2 unless heap is **empty**.


HeapSort() Example

- $A = \{16, 14, 10, 8, 7, 9, 3, 2, 4, 1\}$




HeapSort() Example

- $A = \{14, 8, 10, 4, 7, 9, 3, 2, 1, 16\}$




HeapSort() Example

- $A = \{10, 8, 9, 4, 7, 1, 3, 2, 14, 16\}$




HeapSort() Example

- $A = \{9, 8, 3, 4, 7, 1, 2, 10, 14, 16\}$




HeapSort() Example

- $A = \{8, 7, 3, 4, 2, 1, 9, 10, 14, 16\}$




HeapSort() Example

- $A = \{7, 4, 3, 1, 2, 8, 9, 10, 14, 16\}$




HeapSort() Example

- $A = \{4, 2, 3, 1, 7, 8, 9, 10, 14, 16\}$




HeapSort() Example

- $A = \{3, 2, 1, 4, 7, 8, 9, 10, 14, 16\}$




HeapSort() Example

- $A = \{2, 1, 3, 4, 7, 8, 9, 10, 14, 16\}$



HeapSort() Example

- $A = \{1, 2, 3, 4, 7, 8, 9, 10, 14, 16\}$ >> ordered



1	2	3	4	7	8	9	10	14	16
---	---	---	---	---	---	---	----	----	----

2-Min heap :

min-heap Definition:

is a complete binary tree in which the value in each internal node is lower than or equal to the values in the children of that node.


Min-heap property:

- The key of a node is \leq than the keys of its children.

Min heap Operation


- A heap can be stored as an array A .
 - Root of tree is $A[0]$
 - Left child of $A[i] = A[2i+1]$
 - Right child of $A[i] = A[2i + 2]$
 - Parent of $A[i] = A[(i/2)-1]$

Min Heap




Array A


Min Heap phase 1




Min Heap phase 1




Min Heap phase 1




Min Heap phase 2




Min Heap phase 2




Min Heap phase 2




Min Heap phase 3




Min Heap phase 3



Min Heap phase 4




Min Heap phase 4




1,4,7,12

Min Heap phase 5



Min Heap phase 5




1,4,7,12,16

Min Heap phase 7

19

1,4,7,12,16,19

Min heap final tree



1

4

7

12

16

19

Insertion



- Algorithm

1. Add the new element to the next available position at the lowest level
2. Restore the max-heap property if violated
 - General strategy is percolate up (or bubble up): if the parent of the element is smaller than the element, then interchange the parent and child.


OR

Restore the min-heap property if violated

- General strategy is percolate up (or bubble up): if the parent of the element is larger than the element, then interchange the parent and child.



Insert 17



A vertical bar on the left side of the slide, divided into three colored segments: yellow at the top, green in the middle, and red at the bottom.

The End