



University: Sharif University of Technology

Department: Electrical Engineering

Course Name: Advanced Neuroscience

Homework 4 Report

Traveling Waves

Student Name: Ali Shahbazi

Student ID: 98101866

Instructor: Prof. Ali Ghazizadeh

Academic Semester: 2023 Spring

LFP Ananlysis

- a) Before starting any analysis, we do the pre-process. Using *bandstop()* function, we remove the line noise from the data and using constant regression, we fit a pink noise (line with slope -1) to each channel and denoise the data (Figure 1). We fitted the pink noise to each channel separately because the amplitude of noise can vary along electrodes.




Figure 1: Line Noise and Pink Noise Removal

As can be seen above, the most dominant frequency is about $10^{Hz} - 15^{Hz}$.

- b) After removing pink noise, we have averaged power spectral density of each channel. If we find the peak frequency in each channel, Figure 2 would be obtained.




Figure 2: Clustering Dominant Frequencies

Dominant frequency for all channels is ~ 12.6953 .

- c) **Figure 3** shows power spectrum before and after pink noise cancellation. Clearly, we can see that β band is more active.




Figure 3: Power Spectrum

- **STFT:** First we calculate STFT of original signal and then we remove pink noise from it. **Figure 4** shows STFT color maps.




Figure 4: STFT - Power Spectrum

- **WELCH:** First we buffer the signal into overlapping frames, the calculate *pwelch()* of each time frame.
- d) Results indicate that the interval $10^{Hz} - 15^{Hz}$ is the most strongest band specially around 0.6 sec after onset. Comparing to [1], **Figure 6** is obtained.




Figure 5: WELCH - Power Spectrum




Figure 6: Comparing to [1]

Phase Propagation (Traveling Waves)

- a) Using `butter()` function, we design a second-order Butter-worth filter described as in Figure 7. The important point is that it's phase is linear around dominant frequency and we would still be able to see wave.




Figure 7: Butter-worth Filter Specification

- b) Here, we take the angle of hilbert transform of LFP data using this simple line code, resulting $\phi(x, y, t)$:

```
1 phase_mat(i, j, :, :) = angle(hilbert(clear_chan(ch).filt_lfp));
```

- c) Part c and e are done together as `demo.mp4` and `demo_filt.mp4`.
- d) In each time step, we calculate the *gradient()* of phase in the electrodes and take the average vector as direction of propagation. PGD and SPEED are calculated as mentioned in [1]:

$$PGD(t) = \|\overline{\nabla \phi}\| / \|\nabla \phi\|$$

$$speed(t) = |\overline{\partial \phi / \partial t}| / \|\nabla \phi\|$$

- e) Part c and e are done together as `demo.mp4` and `demo_filt.mp4`.
- f) If we calculate all parameters in `demo.mp4` for all trials, we can plot some histograms to test our hypothesis.




Figure 8: Wave Direction Histogram




Figure 9: Gradient Direction Histogram




Figure 10: Speed Histogram

References

- [1] Doug Rubino, Kay A Robbins, and Nicholas G Hatsopoulos. “Propagating waves mediate information transfer in the motor cortex”. en. In: *Nat. Neurosci.* 9.12 (Dec. 2006), pp. 1549–1557.